

LOAN DOCUMENT

DTIC ACCESSION NUMBER		PHOTOGRAPH THIS SHEET	INVENTORY	H A N D L E W I T H C A R E																
	LEVEL		(5)																	
	<u>NRL-MR-3059</u> DOCUMENT IDENTIFICATION May 75																			
		DISTRIBUTION STATEMENT Approved for public release Distribution Unlimited																		
		DISTRIBUTION STATEMENT																		
ACCESSION FOR <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 50%;">NTIS</td> <td style="width: 50%;">GRAM</td> <td style="width: 50%; text-align: center;">☒</td> </tr> <tr> <td>DTIC</td> <td>TRAC</td> <td style="text-align: center;">☐</td> </tr> <tr> <td>UNANNOUNCED</td> <td></td> <td style="text-align: center;">☐</td> </tr> <tr> <td>JUSTIFICATION</td> <td></td> <td></td> </tr> </table> BY DISTRIBUTION/ AVAILABILITY CODES <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 50%;">DISTRIBUTION</td> <td style="width: 50%;">AVAILABILITY AND/OR SPECIAL</td> </tr> <tr> <td style="height: 40px; vertical-align: bottom;">A-1</td> <td></td> </tr> </table>		NTIS	GRAM	☒	DTIC	TRAC	☐	UNANNOUNCED		☐	JUSTIFICATION			DISTRIBUTION	AVAILABILITY AND/OR SPECIAL	A-1				
NTIS	GRAM	☒																		
DTIC	TRAC	☐																		
UNANNOUNCED		☐																		
JUSTIFICATION																				
DISTRIBUTION	AVAILABILITY AND/OR SPECIAL																			
A-1																				
DISTRIBUTION STAMP		DATE RECEIVED IN DTIC																		
		19960625 189																		
		REGISTERED OR CERTIFIED NUMBER																		

Interaction of Relativistic Electron Beams with Fusion Target Blow-off Plasmas

D. MOSHER

*Plasma Applications Branch
Plasma Physics Division*

May 1975

This research was sponsored by the Defense Nuclear Agency under
Subtask T99QAX LA014, work unit 05, work unit title Advanced Concepts.



NAVAL RESEARCH LABORATORY
Washington, D.C.

DTIC QUALITY INSPECTED 1

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER NRL Memorandum Report 3059	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) INTERACTION OF RELATIVISTIC ELECTRON BEAMS WITH FUSION TARGET BLOW-OFF PLASMAS		5. TYPE OF REPORT & PERIOD COVERED Interim report on a continuing NRL Problem
		6. PERFORMING ORG. REPORT NUMBER
7. AUTHOR(s) D. Mosher		8. CONTRACT OR GRANT NUMBER(s)
9. PERFORMING ORGANIZATION NAME AND ADDRESS Naval Research Laboratory Washington, D.C. 20375		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS NRL Problem H02-26A Project DNA T990AXLA014
11. CONTROLLING OFFICE NAME AND ADDRESS Defense Nuclear Agency Washington, D.C. 20305		12. REPORT DATE May 1975
		13. NUMBER OF PAGES 18
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)		15. SECURITY CLASS. (of this report) UNCLASSIFIED
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release, distribution unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES This research was sponsored by the Defense Nuclear Agency under Subtask T99QAX LA014, work unit 05, work unit title Advanced Concepts.		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Relativistic electron beams Pellet fusion Beam-target interactions		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) The relativistic Boltzmann equation with a Fokker-Planck collision term is solved with the assumption that elastic scattering characterizes the shortest time and length scales of the beam- plasma system. Explicit one-dimensional solutions containing the self-consistent return-current electric field show that although range-shortening occurs, the primary effect of the electric field is to prevent high-current-density beams from penetrating into the dense-plasma region.		


DD FORM 1 JAN 73 1473

EDITION OF 1 NOV 65 IS OBSOLETE
S/N 0102-014-6601

i

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)



INTERACTION OF RELATIVISTIC ELECTRON BEAMS WITH FUSION TARGET BLOW-OFF PLASMAS

The development of high-power pulse generators has created interest in the use of relativistic electron beams to compress and heat small masses of deuterium and tritium to fusion in a manner similar to that proposed using lasers.^{1,2} In order to optimize thermonuclear yield, fusion-pellet designs employ thin shells of high-atomic-number material in which the beam deposits energy.^{3,4} Hydrodynamic modeling of pellet implosion has neglected both the effects of the electromagnetic field and scattering collisions in the beam-heated plasma blown off of the shell.^{1,3} This work presents a formalism which allows one to determine the character of beam deposition in the high-atomic-number plasma and shell when these effects are included. The Boltzmann equation describing the beam with a relativistically-correct Fokker-Planck collision term is solved with the assumption that the elastic-scattering collision time is the shortest characteristic time of the system. (This approximation is valid for cases of interest: the interaction of a 1-3 MeV electron beam of about 10 nsec duration with initially-solid shells of heavy material.) One-dimensional solutions are then calculated in two limiting cases of interest. From these, the energy-deposition profile and efficiency of energy coupling from beam to plasma are determined. Finally, the constraints placed on beams for fusion in light of the present analysis are discussed.

The equation describing the momentum distribution function of relativistic electrons interacting with a cold, high-atomic-number plasma may be written⁵

$$\frac{\partial f}{\partial t} + \frac{\vec{p}}{m\gamma} \cdot \nabla f - e \left(\vec{E} + \frac{\vec{p} \times \vec{B}}{m\gamma} \right) \cdot \nabla_p f = \nabla_p \cdot [\nu_S(p) (p^2 \vec{I} - \vec{p}\vec{p}) \cdot \nabla_p f] + \nabla_p \cdot [\nu_E(p) \vec{p} f] \quad (1)$$

where $\gamma^2 = 1 + p^2/(mc)^2$. The quantities ν_S and ν_E are energy-dependent

Note: Manuscript submitted May 13, 1975.

scattering and energy-loss frequencies

$$\nu_S = \Omega_S \gamma / (\gamma^2 - 1)^{3/2}; \quad \nu_E = \epsilon \gamma \nu_S \quad (2)$$

where

$$\Omega_S = 2\pi n_i r_o^2 c (Z^2 + Z) \ln \Lambda; \quad \epsilon = \frac{2}{Z+1}.$$

In the above, n_i is the plasma ion density, r_o is the classical electron radius, c is the velocity of light, Z is the plasma atomic number, and $\ln \Lambda$ is in the range 10-20 for plasmas of interest.⁵ We limit consideration to plasmas for which $\epsilon \ll 1$.

Treating ϵ as second order in ν_S^{-1} , the terms of Eq. (1) are ordered according to

$$O(\nu_S^{-2}) : O(\nu_S^{-1}) : O(\nu_S^{-1}) = O(1) : O(\nu_S^{-2}).$$

When f is expanded in powers of ν_S^{-1}

$$f = f_0 + f_1 + \dots,$$

Eq. (1) can be iteratively solved starting with $O(1)$ terms. The solution correct to second order is given by

$$f_0 = f_0(p, \vec{x}, t) \quad (3)$$

that is, f_0 is isotropic in momentum space and

$$f_1 = \vec{A} \cdot \vec{p} \quad (4)$$

$$f_2 = \frac{1}{6\nu_S} \left(\frac{e\vec{E}}{p} \frac{\partial \vec{A}}{\partial p} - \frac{1}{m\gamma} \nabla \vec{A} \right) : \vec{p}\vec{p} + \frac{e}{2\nu_S m\gamma} (\vec{B} \times \vec{A}) \cdot \vec{p} \quad (5)$$

where

$$\vec{A} = \frac{1}{2v_S} \left(\frac{e\vec{E}}{p} \frac{\partial f_o}{\partial p} - \frac{1}{m\gamma} \nabla f_o \right). \quad (6)$$

The equation governing f_o is obtained by setting secular terms in the second-order equation equal to zero

$$\frac{\partial f_o}{\partial t} + \frac{p^2}{3m\gamma} \nabla \cdot \vec{A} = \frac{1}{p^2} \frac{\partial}{\partial p} \left[p^3 (v_E f_o + \frac{1}{3} e\vec{E} \cdot \vec{A}) \right]. \quad (7)$$

In this work, moments of f which yield the beam-electron and energy fluxes are of interest. To lowest significant order, these quantities are determined from

$$\vec{\Phi} = \int \frac{\vec{p}}{m\gamma} f_1 d^3p = \int \frac{\vec{p}\vec{p}}{m\gamma} \cdot \vec{A} d^3p \quad (8)$$

$$\vec{Q} = \int mc^2(\gamma-1) \frac{\vec{p}}{m\gamma} f_1 d^3p = mc^2 \int (\gamma-1) \frac{\vec{p}\vec{p}}{m\gamma} \cdot \vec{A} d^3p. \quad (9)$$

Taking the divergence of $\vec{\Phi}$, substituting from Eq. (7) for $\nabla \cdot \vec{A}$, and integrating by parts yields

$$\nabla \cdot \vec{\Phi} = -4\pi \left(p^3 v_E f_o \right)_p = 0 \quad (10)$$

Lack of particle conservation is due to beam electrons, slowed by dynamic friction to very low energies, merging with the thermal-electron background. These are not accounted for in f since Eq. (1) describes only the distribution of super-thermal electrons.

The rate at which energy is transferred from the beam to a unit volume of plasma is obtained by taking the divergence of Eq. (9). In the steady state,

$$Q = -\nabla \cdot \vec{q} = e\vec{E} \cdot \vec{\Phi} + 4\pi \int_0^\infty \frac{p^4 v_E}{m\gamma} f_0 dp. \quad (11)$$

Steady-state solutions of f in one dimension are now considered. The plane $x = 0$ is chosen to divide a semi-infinite, uniform plasma occupying the region $x > 0$ from a vacuum. A monoenergetic, well-collimated beam of relativistic electrons (particle flux Φ_i) propagating in the vacuum is normally incident on the plasma. The plasma is assumed to be sufficiently conductive to exclude the vacuum magnetic field associated with the incident beam for times of interest.¹ Thus, a plasma return current $j = e\Phi$ of thermal electrons must flow towards the vacuum-plasma interface. The electric field associated with this current is

$$E = \eta j = \eta e\Phi \quad (12)$$

where η is the plasma resistivity.⁶ Plasma electrons which reach the interface are assumed to flow as $\nabla p \times \vec{B}$ surface currents along the $x = 0$ plane. This planar model approximates a relativistic electron beam incident on a spherical shell of high-atomic-number material for a shell thickness small compared to the radius of the sphere.

The beam-electron distribution function in the plasma can now be written

$$f = f_0(p, x) + \mu p A - \frac{\mu^2}{2v_s} \left[eEA + \frac{1}{p^2} \frac{\partial}{\partial p} (p^3 v_E f_0) \right] \quad (13)$$

correct to second order. The second-order term has been simplified using the secular equation

$$\frac{\partial A}{\partial x} = \frac{m\gamma}{p^4} \frac{\partial}{\partial p} \left[p^3 (3v_E f_0 + eEA) \right] \quad (14)$$

where

$$A = \frac{1}{2v_S} \left(\frac{eE}{p} \frac{\partial}{\partial p} - \frac{1}{m\gamma} \frac{\partial}{\partial x} \right) f_0 \quad (15)$$

and μ is the cosine of the polar angle in a spherical momentum-space geometry with polar axis along x .

The beam-electron flux is given by

$$\Phi(x) = 2\pi \int_{-1}^{+1} d\mu \mu^2 \int_0^\infty dp \frac{p^4 A}{m\gamma} \quad (16)$$

When $v_E f_0$ and eEA are comparable in magnitude, Eqs. (12) - (16) must be solved simultaneously using numerical techniques. Two limiting cases of interest which are amenable to analytical solution are now discussed.

When the plasma density is high and the beam-current density is low, dynamic friction dominates over energy loss to the electric field. Neglecting electric-field terms in Eq. (14) leads to the solution^{7,8}

$$\gamma^2 f_0 = \frac{C x}{\tau^{3/2}} \exp\left(-\frac{x^2}{4a^2 \tau}\right) \quad (17)$$

for an incident monoenergetic beam with $\gamma = \gamma_0$. In Eq. (17),

$$\tau = \int_{\gamma}^{\gamma_0} \frac{(\gamma'^2 - 1)^3 d\gamma'}{\gamma'^4} = \Gamma(\gamma_0) - \Gamma(\gamma), \quad (18)$$

$$\Gamma(\gamma) = \frac{(\gamma^2 + 1)(\gamma^4 - 10\gamma^2 + 1)}{3\gamma^3}, \quad (19)$$

$a^2 = \frac{c^2}{6e\Omega^2 S}$, and C is constant. The corresponding electron flux is

$$\Phi(x) = \Phi_0 \exp\left(-\frac{x^2}{4a^2\tau_1}\right) \quad (20)$$

where $\tau_1 = \Gamma(\gamma_0) - \Gamma(1)$, and $\Phi_0 = \Phi(0)$. The volume heating rate when $E = 0$ may be written

$$Q_C(x) = \frac{mc^2\Phi_0\tau_1^{1/2}}{2a^2} \int_1^{\gamma_0} \exp\left(-\frac{x^2}{4a^2\tau}\right) \frac{d\gamma}{\tau^{3/2}} \quad (21)$$

The variation of Q_C with x is shown in Fig. 1.

The transmission coefficient of beam current at the interface can be estimated by equating Φ_i with the positive-going beam current there.⁷

$$\Phi_i = 2\pi \int_0^1 d\mu \int_0^\infty dp \, p^2 f \frac{p\mu}{m\gamma} = \pi \int_0^\infty \frac{p^3 f_0(p,0) dp}{m\gamma} + \frac{1}{2} \Phi_0 \quad (22)$$

correct to first order. With f_0 given by Eq. (17), the transmission coefficient is

$$T_C = \Phi_0/\Phi_i = \left[\frac{1}{2} + \left(\frac{3\pi}{8\epsilon} \right)^{\frac{1}{2}} \frac{\gamma_0^2 \tau_1^{1/2}}{(\gamma_0^2 - 1)^2} \right]^{-1} \quad (23)$$

For $\gamma_0 = 3$, T_C ranges from .75 for aluminum to .40 for gold.

When the beam current is high and the plasma density is sufficiently low, dynamic friction can be neglected in comparison to electric-field slowing down. In that case, Eq. (10) predicts that Φ , and therefore E are constant. The solution of Eq. (14) to first order with $v_E = 0$ for an incident monoenergetic beam is

$$f = f_0 + \mu p A = \left\{ \alpha - \beta \left[K(\gamma^*) - K(\gamma_0) - \frac{e\mu}{\gamma^{*2} - 1} \right] \right\} \delta(\gamma - \gamma^*) \quad (24)$$

where α and β are constant, $\mathcal{E} = eE/(mc\Omega_s)$,

$$K(\gamma) = \frac{\gamma(\gamma^2 + 1)}{4(\gamma^2 - 1)^2} + \frac{1}{8} \ln\left(\frac{\gamma-1}{\gamma+1}\right), \quad (25)$$

and $\gamma^*(x) = \gamma_0 - eEx/(mc^2)$. The quantity β is determined by substitution into Eq. (16).

$$\Phi_0 = \frac{4\pi}{3} m^3 c^4 \mathcal{E} \beta \quad (26)$$

The heating rate in the absence of dynamic friction is given by Eq. (11).

$$Q_E = eE\Phi_0 \quad ; \quad \gamma^* \geq 1. \quad (27)$$

Using Eq. (22), the transmission coefficient is

$$T_E = \frac{4\mathcal{E}\beta/3}{(\gamma_0^2 - 1)\alpha + 2\mathcal{E}\beta/3} \quad (28)$$

A reasonable boundary condition for large x is needed to determine α . Since v_E increases with x according to Eq. (2) and the definition of γ^* , dynamic friction must dominate over the electric field for sufficiently-large x . The values of γ^* and x at which dynamic friction becomes important can be estimated by equating the two terms on the right side of Eq. (14)

$$3v_E f_0 = eEA \quad @ \quad \gamma^* = \gamma_c = \gamma_0 - eEx_c/(mc^2)$$

or

$$\mathcal{E}^2 \beta = 3\epsilon \gamma_c^2 \left\{ \alpha - \beta [K(\gamma_c) - K(\gamma_0)] \right\} \quad (29)$$

The region $x > x_c$ represents a strong absorber of slowed-down electrons. It is then reasonable to set the negative-going current at $x = x_c$ equal to zero. To first order,

$$\Phi_R(x_c) = 2\pi \int_1^0 \mu d\mu \int_0^\infty \frac{p^3 f_o(p, x_c)}{m\gamma} dp + \frac{1}{2} \Phi_o = 0$$

or

$$\alpha = \beta \left[\frac{2}{3} \frac{\mathcal{E}}{\gamma_c^2 - 1} + K(\gamma_c) - K(\gamma_o) \right]. \quad (30)$$

Simultaneous solution of Eqs. (29) and (30) yield γ_c and α . The resulting variation of transmission with electric field is shown in Fig. 2 for $\gamma_o = 3$. The electric field is related to the penetrating beam current by Eq. (12).

$$e\Phi_o = 8.4 \times 10^{-17} (Z + 1) n_1 \theta^{3/2} \mathcal{E} \quad \frac{\text{A}}{\text{cm}^2} \quad (31)$$

Here, θ is the plasma electron temperature in eV.

The above calculations show that although the electric field reduces the beam transmission into the plasma, it does increase the volume heating rate above that due to dynamic friction alone. Its importance to heating can be estimated by comparing the heating rates Q_E and Q_C averaged over x . For $\gamma_o = 3$, $Q_E/\bar{Q}_C \approx \mathcal{E}/\epsilon^{\frac{1}{2}}$, so that electric-field heating dominates when $\mathcal{E} \gg \epsilon^{\frac{1}{2}}$. The region indicated by this inequality is shown in Fig. 2. It is seen that electric-field (or return-current) heating is important only when $\mathcal{E}$ is large enough to reflect all but a small portion of the incident beam. Thus, in order to maximize energy transfer from beam to plasma, the plasma should be prepared in a manner which keeps $\mathcal{E}$ small everywhere. In terms

of the incident current $J_i = e\Phi_o/T_E$, this condition takes the form

$$J_i \leq 10^{-15} n_i \theta^{3/2} \frac{\text{A}}{\text{cm}^2} \quad (32)$$

For incident currents of 10^9 A/cm^2 and 1 keV temperatures,¹ Eq. (32) suggests that poor penetration occurs into plasmas with ion densities less than 10^{19} cm^{-3} . If, during pellet irradiation, the blow-off has sufficient time to expand to a low density region of large extent, poor coupling of the beam to the dense-plasma or solid portion of the shell is predicted. However, if the beam is not strongly scattered in the low-density blow-off, high transmission to, and collisional heating in the dense plasma region can occur. For blow-off plasmas obeying fluid-equation similarity solutions,² the condition that the beam not be strongly scattered in the region $n_i \leq 10^{15} J_i \theta^{-3/2}$ is

$$J_i \tau < 10^2 \sqrt{v_o^2 \theta / Z^2} \quad \text{C/cm}^2 \quad (33)$$

where τ is the beam duration in sec. Relativistic electron beams for fusion should, and as proposed¹ do, satisfy this requirement.

It should be mentioned that the assumption of poor magnetic field penetration leading to the creation of large electric fields in the plasma is not usually valid in present-day, low-temperature blow-off experiments. Comparing the electromagnetic skin depth³ with the blow-off thickness² suggests that magnetic neutralization occurs when

$$\tau > 5 \times 10^{-5} Z \theta^{-5/2} \quad \text{sec.} \quad (34)$$

Thus, temperatures in excess of about 10 eV are required for substantial return currents.

In summary, it has been shown that the existence of large return-current-generated electric fields in pellet blow-off plasmas do not increase beam-energy deposition because they tend to inhibit beam penetration to high plasma densities.

ACKNOWLEDGEMENT

The author is indebted to Prof. Ira Bernstein for his numerous invaluable suggestions. This work was supported by the Defense Nuclear Agency.

REFERENCES

1. G. Yonas, J. W. Poukey, K. R. Prestwich, J. R. Freeman, A. J. Toepfer and M. J. Clauser, Nucl. Fusion 14, 731 (1974).
2. K. M. Brueckner, IEEE Trans. Plasma Sci. 1, 13 (1973).
3. L. I. Rudakov and A. A. Samarsky in Proc. 6th Europ. Conf. on Controlled Fusion and Plasma Physics (Moscow 1973), p. 487.
4. M. J. Clauser, Phys. Rev. Lett. 34, 570 (1975).
5. D. Mosher, Naval Research Lab. Memo Report 2959 (1974), accepted for publication.
6. L. Spitzer, "Physics of Fully Ionized Gases" (Interscience, New York, 1962), p. 138.
7. H. A. Bethe, M. E. Rose and L. P. Smith, Proc. Amer. Phil. Soc. 78, 573 (1938).
8. P. M. Morse and H. Feshbach, "Methods of Theoretical Physics" (McGraw-Hill, New York, 1953), Chap. 7.
9. J. D. Jackson, "Classical Electrodynamics" (John Wiley & Sons, New York, 1962), Chap. 7.




Fig. 1 - Normalized volume-heating rate vs depth into plasma
for three values of γ_0




Fig. 2 - Transmission coefficient vs normalized electric field strength in plasma for $\gamma_0 = 3$ and three atomic numbers. Return-current heating dominates to the right of the $\epsilon = \epsilon^{1/2}$ curve.

1. Director
Defense Advanced Research Projects Agency
Architect Building
1400 Wilson Boulevard
Arlington, VA 22209
Attn: Sto. Ltc. R. P. Sullivan
2. Director
Defense Nuclear Agency
Washington, D. C. 20309
Attn: DDST, Mr. Peter Haas
RATN
APTL, Technical Library (2 copies)
RAEV
STVL
APSI (Archives)
3. Director of Defense Research and Engineering
Washington, D.C. 20301
Attn: DAD (SK) Mr. G. R. Barse
4. Commander
Harry Diamond Laboratories
Washington, D.C. 20438
Attn: AMXDO-RBF, Mr. John Rosaco
AMXDO-RBH, Mr. S. Graybill
AMXDO-RC, Dr. Robert Oswald, Chief Lab 300
5. Air Force Weapons Laboratory, AFSC
Kirkland AFB, NM 87117
Attn: DY, Dr. Guenther
EL, Mr. John Darrah
DYS, Dr. Payton
SAA
SUL, Technical Library
ELP, TRE Section
6. Space and Missile Systems Organization
Post Office Box 92960
Worldway Postal Center
Los Angeles, CA 90009
Attn: SKT, Peter H. Stadler
RSP, System Defn. and Assessment, Ltc. Gilbert

Sandia Laboratories
P. O. Box 5800
Albuquerque, NM 87115
Attn: Document Control for Dr. J. V. Walker, 5220
Document Control for 5242, Dr. G. Yonas
Document Control for Technical Library

Aerospace Corporation
P. O. Box 92957
Los Angeles, CA 90009
Attn: J. Benveniste
Dr. Jerry Comisar

Austin Research Associates, Inc.
600 West 28th Street
Austin, Texas 78705
Attn: Dr. William E. Drummond

Battelle Memorial Institute
505 King Avenue
Columbus, Ohio 43201
Attn: P. Malozzi

Maxwell Laboratories, Inc.
9244 Balboa Avenue
San Diego, CA 92123
Attn: Dr. P. Korn

Mission Research Corporation
735 State Street
Santa Barbara, CA 93101
Attn: Dr. Conrad L. Longmire

Physics International Company
2700 Merced Street
San Leandro, CA 94577
Attn: Doc. Control for Dr. Sid Putnam
Doc. Control for Mr. Ian Smith

R & D Associates
P. O. Box 3580
Santa Monica, CA 90403
Attn: Dr. Bruce Hartenbaum

Science Applications, Inc.
P. O. Box 2351
La Jolla, CA 92037
Attn: Dr. J. Robert Beyster

16. Stanford Research Institute
333 Ravenswood Avenue
Menlo Park, CA 94025
Attn: Dr. Robert A. Armistead
17. Van Lint, Victor A. J. (Consultant)
7850 Convoy Court
San Diego, CA 92111
18. DDC, 12 cys
19. Code 2628, 20 cys
20. Code 7700, 25 cys.
21. Code 7770, 20 cys