



**US Army Corps
of Engineers**

Hydrologic Engineering Center

The HEC Hydrologic Modeling System

Technical Paper No. 150

November 1995

19960719107

Approved for Public Release. Distribution Unlimited.

DTIC QUALITY INSPECTED 4

Papers in this series have resulted from technical activities of the Hydrologic Engineering Center. Versions of some of these have been published in technical journals or in conference proceedings. The purpose of this series is to make the information available for use in the Center's training program and for distribution within the Corps of Engineers

The findings in this report are not to be construed as an official Department of the Army position unless so designated by other authorized documents.

The contents of this report are not to be used for advertising, publication, or promotional purposes. Citation of trade names does not constitute an official endorsement or approval of the use of such commercial products.

THE HEC HYDROLOGIC MODELING SYSTEM

John Peters¹

ABSTRACT: The Hydrologic Modeling System is the Hydrologic Engineering Center's "next generation" software for precipitation-runoff simulation. The software will provide a variety of options for specifying observed or hypothetical meteorological inputs and for simulating losses, runoff transformation, and routing. Capabilities include a quasi-distributed runoff transformation that can be applied with gridded (e.g., radar) rainfall data. Soil-moisture accounting options that support period-of-record simulation will be provided, as will capability to simulate snow accumulation and melt. The software employs a graphical user interface and is designed for use in both X-Window and Microsoft Windows environments.

KEY TERMS: surface water hydrology; simulation; modeling.

INTRODUCTION

The Hydrologic Engineering Center (HEC) is developing a new generation of software for use in hydrologic engineering, water resource planning and project operation (Davis, 1993). The software for precipitation-runoff modeling is the Hydrologic Modeling System (HEC-HMS), a successor to the existing HEC-1, Flood Hydrograph Package (HEC, 1990). Release of the initial version of HEC-HMS is scheduled for 1996.

TECHNICAL FEATURES

The basic framework for simulation of basin runoff with HEC-HMS is similar to that in HEC-1. Hydrologic elements are arranged in a dendritic network, and computations are performed in an upstream-to-downstream sequence. An exception is that all subbasins having gridded rainfall are processed through the entire period of simulation prior to computations for remaining elements.

Computations are performed with SI (Système International d'Unités) units. However the user can choose to enter input and view output with units in the U.S Customary system.

The execution of a simulation with HEC-HMS requires specification of three sets of data. The first, labeled Basin Model, contains parameter and connectivity data for hydrologic elements. Types of element are: subbasin, routing reach, junction, reservoir, source, sink and diversion. The second set, labeled Precipitation Model, consists of meteorological data and information required to process it. The data

¹Senior Hydraulic Engineer, U.S. Army Corps of Engineers, Hydrologic Engineering Center, 609 Second St., Davis, CA 95616-4687

may represent historical or hypothetical conditions. The third set, labeled Control Specifications, specifies a simulation time window, time interval, and initial values for state variables. A Project can consist of a number of data sets of each type. Figure 1 illustrates an opening screen in the HEC-HMS graphical user interface which lists Project components. A "run" is configured with one (each) Basin Model, Precipitation Model and Control Specification.




Figure 1. HEC-HMS Project Components

Basin Model

Subbasin runoff can be computed in either a lumped or quasi-distributed mode. In a lumped mode, precipitation and "losses" are spatially-averaged over a subbasin. In the quasi-distributed mode, rainfall is specified on a gridded basis, and loss and excess are tracked separately for each grid cell in a subbasin.

Losses

Options for calculating losses for event simulation include initial/constant, SCS Curve No., and Green and Ampt. For continuous simulation, a simple deficit/constant loss function can be used. The user specifies a soil moisture storage capacity which must be filled before excess can occur. The capacity is filled by rainfall, and depleted during rain-free periods at a depletion rate specified on a daily or monthly basis. When the capacity is filled, loss occurs at the specified constant rate. It is planned to incorporate detailed soil moisture accounting options in future versions of HEC-HMS.

Runoff Transformation

Transformation of precipitation excess to direct runoff can be achieved with unit hydrograph or kinematic wave methods. A unit hydrograph may be specified in tabular form, or in terms of parameters defined by Clark, Snyder or SCS methods. The kinematic wave method permits definition of two rectangular overland flow planes. Runoff from an overland flow plane may be routed through one or two collector/main channel(s) with kinematic wave or Muskingum Cunge methods.

ModClark Method

A quasi-distributed treatment of subbasin runoff can be achieved with the modClark method, which is based on the Clark conceptual runoff model (Clark, 1945). The Clark conceptual model employs two components (1) a translation hydrograph to reflect the travel (lag) time required for 1 unit of rainfall excess (occurring instantaneously) to reach the basin outlet from isochrone-delineated basin segments, and (2) a linear reservoir to represent natural storage effects. The translation hydrograph is routed through the linear reservoir; the resulting outflow is an instantaneous unit hydrograph. The two parameters of the Clark method are the time-of-concentration T_c (time base of the translation hydrograph), and the storage coefficient of the linear reservoir, R . Both parameters have units of time.

In the modClark method, grid cells are superposed on the basin (Figure 2), and rainfall and losses are tracked uniquely for each cell. Rainfall excess from each cell is lagged to the basin outlet and routed through a linear reservoir. The outflows from the linear reservoir are summed and baseflow is added to obtain a total-runoff hydrograph. Information required for each grid cell are its area within the subbasin and an index of travel time from the cell to the subbasin outlet. The travel time for a cell is obtained by multiplying the time of concentration for the subbasin by the ratio of the cell's time index to the time index for the most remote cell (i.e., the cell with the largest time index). A simple time index for a cell is the reciprocal of the travel length of the flow path to the subbasin outlet. Implicit in this measure is the assumption that the velocity of travel is constant in the subbasin.

An alternative time index is based on cell slope and area. The travel time through a cell is assumed to be related to the cell slope and to the accumulated area of all cells contributing runoff to the cell. That is, $v_{cell} \propto S^a * A^b$, where S is the cell slope, and A is the accumulated area of contributing cells. The accumulated area can be regarded as a surrogate for depth. A value of 0.5 has been found to be reasonable for both the a and b exponents (Maidment et al., 1995). The time index for a given cell is defined as the integral of ℓ_{cell}/v_{cell} along the flow path to the subbasin outlet, where ℓ_{cell} is the length of flow path through a cell.




Figure 2. Basin with Rainfall Grid Superposed

A procedure has been developed (HEC, 1995a) to use a geographic information system (GIS) to produce cell data (area and time indices as defined above) for use with the modClark method. The procedure is based on processing digital elevation model (DEM) data such as is available for the continental U.S. from the USGS EROS Data Center (USGS, 1990). Once application of the GIS procedure has been completed, the resulting cell-parameter file is used by HEC-HMS with the modClark method. Thus GIS is used to preprocess data and is not required for subsequent application of the modClark method.

Routing

Routing options include Muskingum, Modified Puls and Muskingum Cunge methods. The latter may be invoked with standard geometric shapes (e.g., circle, trapezoid) or with cross sections defined with eight sets of X-Y coordinates and three Manning n values. Capability is also provided for routing through an uncontrolled reservoir, for which a relation between outflow and storage is required. If more sophisticated routing methods are required because of complex boundary conditions, hydrographs may be exported by HEC-HMS for use with software such as UNET (HEC, 1995b) which provides a numerical solution to the one-dimensional St. Venant equations.

Diversion

A diversion can be specified in terms of a tabular relation between inflow and diverted flow. The diverted hydrograph can be retrieved at a downstream location in a system network.

Precipitation Model

The precipitation model is the set of information required to define historical or hypothetical precipitation to be used in conjunction with a basin model. Types of hypothetical storm include frequency-

based and the Corps of Engineers' Standard Project Storm (Corps of Engineers, 1965). The latter is applicable only for drainage areas up to 2600 km² east of the Rocky Mountains. Frequency-based storms require that the user provide rainfall depths for various durations, sources of which include Technical Paper 40 (National Weather Service, 1961) and NOAA Atlas 2 (National Oceanic and Atmospheric Administration, 1973).

Several options are available for specifying historical precipitation: (1) utilize cell-based precipitation as required for the modClark method; (2) obtain spatial average precipitation from cell-based precipitation; (3) import previously determined spatially averaged precipitation; (4) specify gages and associated weights (e.g., from Thiessen polygons);, or (5) specify gages and their locations, and weights and locations of index nodes, to be used in an automated inverse distance squared weighting. The latter method is useful in cases of missing data, as data from the next nearest gage is automatically used.

GRAPHICAL USER INTERFACE

The Graphical User Interface (GUI) provides a means for specification of information to be retrieved or stored (e.g., importation of data from a previously developed HEC-1 data file), specification of application-specific information (data and execution instructions), and viewing of results.

A significant component of the GUI is capability for schematic representation of a network of hydrologic elements (see Figure 3). The schematic can be used in the initial configuration of a basin model by generating, dragging into place and connecting (graphically) icons that represent components of a basin network. Once a schematic is developed, popup menus can be invoked by double-clicking an element (e.g., subbasin) icon to bring up an editor for that element. Data associated with the hydrologic element can be entered or edited in the editor. Another option in the popup menu enables display of results of a simulation for that element. Figure 4 shows graphical output for a junction.

The entering of data for a large number of hydrologic elements can be tedious if single-element editors are used. The GUI contains global editors for entering or reviewing data of a given type (e.g., values for Green & Ampt parameters) for all applicable elements. If the same data values are being displayed in more than one GUI screen, a change in one screen will automatically be reflected in the other(s).

Because HEC-HMS contains a number of options for various types of computation, the specific option for a particular application must be chosen. In many cases, the user will choose to use the same option throughout a basin model (e.g., the Green & Ampt method for all subbasins). The user can set default method selections so that repetitive option designation is not required.




Figure 3. Schematic Representation of Network of Hydrologic Elements




Figure 4. Junction Hydrographs

A GUI can provide a very useful means for user interaction with simulation software. However there are situations where it is desired to repeat a series of runs with minor variations in model parameter values, or to run the software under control of another modeling process. It is planned to develop a scripting capability such that HEC-HMS can be driven with macros that contain both control instructions and data values.

SOFTWARE ARCHITECTURE

HEC-HMS is designed to be operational in both native X-Window and Microsoft Windows environments. The HEC Data Storage System (HEC 1994a) is used for storage and retrieval of time series records in a manner largely transparent to the user. Existing computational algorithms from HEC-1 have been incorporated in a library for access by HEC-HMS (HEC 1994b). The computational "engine" is being developed with object-oriented programming with C++ (Charley et al., 1995). Integrated use of HEC-HMS with other HEC software such as the River Analysis System (HEC 1995c) and software for flood damage evaluation, reservoir system analysis, etc. is being accommodated.

FUTURE DEVELOPMENT

Capability for semi-automated estimation (optimization) of parameter values is being developed. The scheme for optimization will be flexible with regard to choice of parameters for optimization and basin location and type of objective function. Enhanced capabilities for distributed modeling will be developed. Provision will be made for automated adjustment of discharge-frequency curves for alternative watershed conditions (e.g., land use changes). These capabilities along with soil moisture accounting and simulation of snow accumulation/melt are the primary areas where future development will be focused.

REFERENCES

- Charley, W., Pabst, A., and Peters, J., 1995. The Hydrologic Modeling System (HEC-HMS): Design and Development Issues. Proc. Am. Soc. Civil Engrs. 2nd Congress on Computing in Civil Engineering. Atlanta, Georgia.
- Clark, C.O., 1945. Storage and the Unit Hydrograph. Trans. Am. Soc. Civil Engrs. 110:1419-1488.
- Corps of Engineers, 1965. Standard Project Flood Determination. EM 1110-2-1411. Washington D.C.
- Davis, D.W., 1993. The HEC NexGen Software Development Project. Technical Paper No. 138. Hydrologic Engineering Center, Davis, CA.
- HEC, 1990. HEC-1 Flood Hydrograph Package, User's Manual. Hydrologic Engineering Center, Davis, CA.
- HEC, 1994a. HEC-DSS User's Guide and Utility Manuals. Hydrologic Engineering Center, Davis, CA.
- HEC, 1994b. libHydro Users Manual. Hydrologic Engineering Center, Davis, CA.
- HEC, 1995a. GridParm-DEM2HRAP: A Procedure for Evaluating Runoff Parameters for HRAP Cells from USGS Digital Elevation Models (draft). Hydrologic Engineering Center, Davis, CA.
- HEC, 1995b. One-Dimensional Unsteady Flow Through a Full Network of Open Channels (UNET), Draft User's Manual. Hydrologic Engineering Center, Davis, CA.
- HEC, 1995c. HEC-RAS, River Analysis System, User's Manual - Draft. Hydrologic Engineering Center, Davis, CA.
- Maidment, D.R., Olivera, J.F., Calver, A., Eatherall, A., and Fraczek, W., 1995. A Unit Hydrograph Derived from a Spatially Distributed Velocity Field. accepted for publication in Hydrologic Processes.

National Oceanic and Atmospheric Administration, 1973. Precipitation Frequency Atlas of the Western United States, Atlas 2. vol. 1-13. Washington, D.C.

National Weather Service, 1961. Rainfall Frequency Atlas of the United States, 30-Minute to 24-Hour Durations, 1- to 100-Year Return Periods. Technical Paper No. 40. U.S. Department of Commerce.

USGS, 1990. Digital Elevation Models. USGS Data Users Guide 5. US Geological Survey, Reston, Virginia.

REPORT DOCUMENTATION PAGE

Form Approved

OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)

2. REPORT DATE
November 19953. REPORT TYPE AND DATES COVERED
Technical Paper

4. TITLE AND SUBTITLE

The HEC Hydrologic Modeling System

5. FUNDING NUMBERS

6. AUTHOR(S)

John Peters

7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)

Hydrologic Engineering Center
609 Second Street
Davis, California 95616-46878. PERFORMING ORGANIZATION
REPORT NUMBERTechnical Paper
No. 150

9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES)

10. SPONSORING / MONITORING
AGENCY REPORT NUMBER

11. SUPPLEMENTARY NOTES

Paper presented at the 31st Annual American Water Resources Association Conference and Symposium, Houston, Texas, November 5-8, 1995.

12a. DISTRIBUTION / AVAILABILITY STATEMENT

Unlimited

12b. DISTRIBUTION CODE

13. ABSTRACT (Maximum 200 words)

The Hydrologic Modeling System is the Hydrologic Engineering Center's "next generation" software for precipitation-runoff simulation. The software will provide a variety of options for specifying observed or hypothetical meteorological inputs and for simulating losses, runoff transformation, and routing. Capabilities include a quasi-distributed runoff transformation that can be applied with gridded (e.g., radar), rainfall data. Soil-moisture accounting options that support period-of-record simulation will be provided, as will capability to simulate snow accumulation and melt. The software employs a graphical user interface and is designed for use in both X-Window and Microsoft Windows environments.

14. SUBJECT TERMS

Surface Water Hydrology; Simulation; Modeling

15. NUMBER OF PAGES
8

16. PRICE CODE

17. SECURITY CLASSIFICATION
OF REPORT
Unclassified18. SECURITY CLASSIFICATION
OF THIS PAGE19. SECURITY CLASSIFICATION
OF ABSTRACT

20. LIMITATION OF ABSTRACT

TECHNICAL PAPER SERIES

- | | | | |
|-------|--|-------|---|
| TP-1 | Use of Interrelated Records to Simulate Streamflow | TP-38 | Water Quality Evaluation of Aquatic Systems |
| TP-2 | Optimization Techniques for Hydrologic Engineering | TP-39 | A Method for Analyzing Effects of Dam Failures in Design Studies |
| TP-3 | Methods of Determination of Safe Yield and Compensation Water from Storage Reservoirs | TP-40 | Storm Drainage and Urban Region Flood Control Planning |
| TP-4 | Functional Evaluation of a Water Resources System | TP-41 | HEC-5C, A Simulation Model for System Formulation and Evaluation |
| TP-5 | Streamflow Synthesis for Ungaged Rivers | TP-42 | Optimal Sizing of Urban Flood Control Systems |
| TP-6 | Simulation of Daily Streamflow | TP-43 | Hydrologic and Economic Simulation of Flood Control Aspects of Water Resources Systems |
| TP-7 | Pilot Study for Storage Requirements for Low Flow Augmentation | TP-44 | Sizing Flood Control Reservoir Systems by Systems Analysis |
| TP-8 | Worth of Streamflow Data for Project Design - A Pilot Study | TP-45 | Techniques for Real-Time Operation of Flood Control Reservoirs in the Merrimack River Basin |
| TP-9 | Economic Evaluation of Reservoir System Accomplishments | TP-46 | Spatial Data Analysis of Nonstructural Measures |
| TP-10 | Hydrologic Simulation in Water-Yield Analysis | TP-47 | Comprehensive Flood Plain Studies Using Spatial Data Management Techniques |
| TP-11 | Survey of Programs for Water Surface Profiles | TP-48 | Direct Runoff Hydrograph Parameters Versus Urbanization |
| TP-12 | Hypothetical Flood Computation for a Stream System | TP-49 | Experience of HEC in Disseminating Information on Hydrological Models |
| TP-13 | Maximum Utilization of Scarce Data in Hydrologic Design | TP-50 | Effects of Dam Removal: An Approach to Sedimentation |
| TP-14 | Techniques for Evaluating Long-Term Reservoir Yields | TP-51 | Design of Flood Control Improvements by Systems Analysis: A Case Study |
| TP-15 | Hydrostatistics - Principles of Application | TP-52 | Potential Use of Digital Computer Ground Water Models |
| TP-16 | A Hydrologic Water Resource System Modeling Techniques | TP-53 | Development of Generalized Free Surface Flow Models Using Finite Element Techniques |
| TP-17 | Hydrologic Engineering Techniques for Regional Water Resources Planning | TP-54 | Adjustment of Peak Discharge Rates for Urbanization |
| TP-18 | Estimating Monthly Streamflows Within a Region | TP-55 | The Development and Servicing of Spatial Data Management Techniques in the Corps of Engineers |
| TP-19 | Suspended Sediment Discharge in Streams | TP-56 | Experiences of the Hydrologic Engineering Center in Maintaining Widely Used Hydrologic and Water Resource Computer Models |
| TP-20 | Computer Determination of Flow Through Bridges | TP-57 | Flood Damage Assessments Using Spatial Data Management Techniques |
| TP-21 | An Approach to Reservoir Temperature Analysis | TP-58 | A Model for Evaluating Runoff-Quality in Metropolitan Master Planning |
| TP-22 | A Finite Difference Method for Analyzing Liquid Flow in Variably Saturated Porous Media | TP-59 | Testing of Several Runoff Models on an Urban Watershed |
| TP-23 | Uses of Simulation in River Basin Planning | TP-60 | Operational Simulation of a Reservoir System with Pumped Storage |
| TP-24 | Hydroelectric Power Analysis in Reservoir Systems | TP-61 | Technical Factors in Small Hydropower Planning |
| TP-25 | Status of Water Resource Systems Analysis | TP-62 | Flood Hydrograph and Peak Flow Frequency Analysis |
| TP-26 | System Relationships for Panama Canal Water Supply | TP-63 | HEC Contribution to Reservoir System Operation |
| TP-27 | System Analysis of the Panama Canal Water Supply | TP-64 | Determining Peak-Discharge Frequencies in an Urbanizing Watershed: A Case Study |
| TP-28 | Digital Simulation of an Existing Water Resources System | TP-65 | Feasibility Analysis in Small Hydropower Planning |
| TP-29 | Computer Applications in Continuing Education | TP-66 | Reservoir Storage Determination by Computer Simulation of Flood Control and Conservation Systems |
| TP-30 | Drought Severity and Water Supply Dependability | TP-67 | Hydrologic Land Use Classification Using LANDSAT |
| TP-31 | Development of System Operation Rules for an Existing System by Simulation | TP-68 | Interactive Nonstructural Flood-Control Planning |
| TP-32 | Alternative Approaches to Water Resource System Simulation | TP-69 | Critical Water Surface by Minimum Specific Energy Using the Parabolic Method |
| TP-33 | System Simulation for Integrated Use of Hydroelectric and Thermal Power Generation | TP-70 | Corps of Engineers Experience with Automatic Calibration of a Precipitation-Runoff Model |
| TP-34 | Optimizing Flood Control Allocation for a Multipurpose Reservoir | TP-71 | Determination of Land Use from Satellite Imagery for Input to Hydrologic Models |
| TP-35 | Computer Models for Rainfall-Runoff and River Hydraulic Analysis | TP-72 | Application of the Finite Element Method to Vertically Stratified Hydrodynamic Flow and Water Quality |
| TP-36 | Evaluation of Drought Effects at Lake Atitlan | | |
| TP-37 | Downstream Effects of the Levee Overtopping at Wilkes-Barre, PA, During Tropical Storm Agnes | | |

- TP-73 Flood Mitigation Planning Using HEC-SAM
- TP-74 Hydrographs by Single Linear Reservoir Model
- TP-75 HEC Activities in Reservoir Analysis
- TP-76 Institutional Support of Water Resource Models
- TP-77 Investigation of Soil Conservation Service Urban Hydrology Techniques
- TP-78 Potential for Increasing the Output of Existing Hydroelectric Plants
- TP-79 Potential Energy and Capacity Gains from Flood Control Storage Reallocation at Existing U. S. Hydropower Reservoirs
- TP-80 Use of Non-Sequential Techniques in the Analysis of Power Potential at Storage Projects
- TP-81 Data Management Systems for Water Resources Planning
- TP-82 The New HEC-1 Flood Hydrograph Package
- TP-83 River and Reservoir Systems Water Quality Modeling Capability
- TP-84 Generalized Real-Time Flood Control System Model
- TP-85 Operation Policy Analysis: Sam Rayburn Reservoir
- TP-86 Training the Practitioner: The Hydrologic Engineering Center Program
- TP-87 Documentation Needs for Water Resources Models
- TP-88 Reservoir System Regulation for Water Quality Control
- TP-89 A Software System to Aid in Making Real-Time Water Control Decisions
- TP-90 Calibration, Verification and Application of a Two-Dimensional Flow Model
- TP-91 HEC Software Development and Support
- TP-92 Hydrologic Engineering Center Planning Models
- TP-93 Flood Routing Through a Flat, Complex Flood Plain Using a One-Dimensional Unsteady Flow Computer Program
- TP-94 Dredged-Material Disposal Management Model
- TP-95 Infiltration and Soil Moisture Redistribution in HEC-1
- TP-96 The Hydrologic Engineering Center Experience in Nonstructural Planning
- TP-97 Prediction of the Effects of a Flood Control Project on a Meandering Stream
- TP-98 Evolution in Computer Programs Causes Evolution in Training Needs: The Hydrologic Engineering Center Experience
- TP-99 Reservoir System Analysis for Water Quality
- TP-100 Probable Maximum Flood Estimation - Eastern United States
- TP-101 Use of Computer Program HEC-5 for Water Supply Analysis
- TP-102 Role of Calibration in the Application of HEC-6
- TP-103 Engineering and Economic Considerations in Formulating
- TP-104 Modeling Water Resources Systems for Water Quality
- TP-105 Use of a Two-Dimensional Flow Model to Quantify Aquatic Habitat
- TP-106 Flood-Runoff Forecasting with HEC-1F
- TP-107 Dredged-Material Disposal System Capacity Expansion
- TP-108 Role of Small Computers in Two-Dimensional Flow Modeling
- TP-109 One-Dimensional Model For Mud Flows
- TP-110 Subdivision Froude Number
- TP-111 HEC-5Q: System Water Quality Modeling
- TP-112 New Developments in HEC Programs for Flood Control
- TP-113 Modeling and Managing Water Resource Systems for Water Quality
- TP-114 Accuracy of Computed Water Surface Profiles - Executive Summary
- TP-115 Application of Spatial-Data Management Techniques in Corps Planning
- TP-116 The HEC's Activities in Watershed Modeling
- TP-117 HEC-1 and HEC-2 Applications on the MicroComputer
- TP-118 Real-Time Snow Simulation Model for the Monongahela River Basin
- TP-119 Multi-Purpose, Multi-Reservoir Simulation on a PC
- TP-120 Technology Transfer of Corps' Hydrologic Models
- TP-121 Development, Calibration and Application of Runoff Forecasting Models for the Allegheny River Basin
- TP-122 The Estimation of Rainfall for Flood Forecasting Using Radar and Rain Gage Data
- TP-123 Developing and Managing a Comprehensive Reservoir Analysis Model
- TP-124 Review of the U.S. Army Corps of Engineering Involvement With Alluvial Fan Flooding Problems
- TP-125 An Integrated Software Package for Flood Damage Analysis
- TP-126 The Value and Depreciation of Existing Facilities: The Case of Reservoirs
- TP-127 Floodplain-Management Plan Enumeration
- TP-128 Two-Dimensional Floodplain Modeling
- TP-129 Status and New Capabilities of Computer Program HEC-6: "Scour and Deposition in Rivers and Reservoirs"
- TP-130 Estimating Sediment Delivery and Yield on Alluvial Fans
- TP-131 Hydrologic Aspects of Flood Warning - Preparedness Programs
- TP-132 Twenty-five Years of Developing, Distributing, and Supporting Hydrologic Engineering Computer Programs
- TP-133 Predicting Deposition Patterns in Small Basins
- TP-134 Annual Extreme Lake Elevations by Total Probability Theorem
- TP-135 A Muskingum-Cunge Channel Flow Routing Method for Drainage Networks
- TP-136 Prescriptive Reservoir System Analysis Model - Missouri River System Application
- TP-137 A Generalized Simulation Model for Reservoir System Analysis
- TP-138 The HEC NexGen Software Development Project
- TP-139 Issues for Applications Developers
- TP-140 HEC-2 Water Surface Profiles Program
- TP-141 HEC Models for Urban Hydrologic Analysis
- TP-142 Systems Analysis Applications at the Hydrologic Engineering Center
- TP-143 Runoff Prediction Uncertainty for Ungauged Agricultural Watersheds
- TP-144 Review of GIS Applications in Hydrologic Modeling
- TP-145 Application of Rainfall-Runoff Simulation for Flood Forecasting
- TP-146 Application of the HEC Prescriptive Reservoir Model in the Columbia River System
- TP-147 HEC River Analysis System (HEC-RAS)
- TP-148 HEC-6: Reservoir Sediment Control Applications
- TP-149 The Hydrologic Modeling System (HEC-HMS): Design and Development Issues
- TP-150 The HEC Hydrologic Modeling System