



CALS TEST NETWORK

# AFCTN Test Report 93-033

AFCTB-ID  
93-039



## Technical Raster Transfer

Using:



4950th Test Wing/AMIS' Data



MIL-R-28002A (Raster)



Quick Short Test Report

19 April 1993



**DISTRIBUTION STATEMENT A**  
Approved for public release;  
Distribution Unlimited

19960822 185



Prepared for

Electronic Systems Center

DTIC QUALITY INSPECTED 3

**AFCTN Test Report**  
93-033

**AFCTB-ID**  
93-039

---

**Technical Raster Transfer**  
**Using:**  
**4950th Test Wing/ AMIS Data**

**MIL-R-28002A (Raster)**

**Quick Short Test Report**

**19 April 1993**

---

**Prepared By**  
Air Force CALS Test Bed  
Wright-Patterson AFB, OH 45433

**AFCTB Contact**  
Gary Lammers  
(513) 427-2295

**AFCTN Contact**  
Mel Lammers  
(513) 427-2295

**DTC QUALITY INSPECTED 3**

## DISCLAIMER

This document was prepared as an account of work sponsored by the Air Force. Neither the United States Government or the Air Force nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial products, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or the Air Force. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or the Air Force, and shall not be used for advertising or product endorsement purposes.

Available to the public from the  
National Technical Information Service  
U.S. Department of Commerce  
5285 Port Royal Rd.  
Springfield, VA 22161

This report and those involved in its preparation do not endorse any product, process, or company stated herein. Use of these means by anyone does not imply certification by the Air Force CALS Test Network (AFCTN).

---

---

## Contents

1.	Introduction.....	1
1.1.	Background.....	1
1.2.	Purpose.....	2
2.	Test Parameters.....	3
3.	1840A Analysis.....	5
3.1.	External Packaging.....	5
3.2.	Transmission Envelope.....	5
3.2.1.	Tape Formats.....	5
3.2.2.	Declaration and Header Fields.....	6
4.	IGES Analysis.....	9
5.	SGML Analysis.....	9
6.	Raster Analysis.....	9
7.	CGM Analysis.....	10
8.	Conclusions and Recommendations.....	11
9.	Appendix A - Tape Tool Report Logs.....	12
9.1.	Tape Catalog.....	12
9.2.	Tape Evaluation Log.....	13
9.3.	Tape File Set Validation Log.....	18
10.	Appendix B - Detail Raster Analysis.....	21
10.1.	File D001R001.....	21
10.1.1.	Error Log validg4.....	21

---

## 1. Introduction

### 1.1 Background

The Department of Defense (DoD) Continuous Acquisition and Life-Cycle Support (CALs) Test Network (AFCTN) is conducting tests of the military standard for the Automated Interchange of Technical Information, MIL-STD-1840A, and its companion suite of military specifications. The AFCTN is a DoD sponsored confederation of voluntary participants from industry and government managed by the Electronic Systems Center (ESC).

The primary objective of the AFCTN is to evaluate the effectiveness of the CALS standards for technical data interchange and to demonstrate the technical capabilities and operational suitability of those standards. Two general categories of tests are performed to evaluate the standards; formal and informal.

Formal tests are large comprehensive tests that follow a written test plan, require specific authorization from the DoD, and may take months to prepare, execute, and report.

Informal tests are quick and short, used by the AFCTN technical staff, to broaden the testing base. They include representative samples of the many systems and applications used by AFCTN participants. They also allow the AFCTN staff to gain feedback from many industry and government interpretations of the standards, to increase the base of participation in the CALS initiative, and respond to the many requests for help that come from participants. Participants take part voluntarily, benefit by receiving an evaluation of their latest implementation (interpretation) of the standards, interact with the AFCTN technical staff, gain experience using the standards, and develop increased confidence in them. The results of informal tests are reported in Quick Short Test Reports (QSTRs) that briefly summarize the standard(s) tested, the hardware and software used, the nature of the test, and the results.

---

## 1.2 Purpose

The purpose of the informal test, reported in this QSTR, was to analyze the 4950th Test Wing/AMIS's interpretation and use of the CALS standards, in transferring technical Raster data. They used the CALS Technical Data Interchange System to produce data, in accordance with the standards, and delivered it to the AFCTN technical staff on a 9-track magnetic tape.

## 2. Test Parameters

**Test Plan:** AFCTB 93-039

**Date of Evaluation:** 19 April 1993

**Evaluator:** George Elwood  
Air Force CALS Test Bed  
ESC/ENCP  
4027 Colonel Glenn Hwy  
Suite 200  
Dayton OH 45431-1672

**Data Originator:** Diane Sondergelt  
4950th Test Wing/AMIS  
Wright-Patterson AFB OH 45433  
(513) 257-9745

**Data Description:** Technical Raster Test  
1 Document Declaration file  
5 Raster files

**Data Source System:**

1840	<b>HARDWARE</b>	Unknown
	<b>SOFTWARE</b>	Unknown
Raster	<b>HARDWARE</b>	Unknown
	<b>SOFTWARE</b>	Unknown

**Evaluation Tools Used:**

**MIL-STD-1840A (TAPE)**

SUN 3/280

AFCTN *Tapetool v1.2.8 UNIX*

AGFA Compugraphics *CAPS/CALS v40.4*

Texas Instrument (TI) *Tapetool v1.0.1*

**MIL-R-28002 (Raster)**

SUN SparcStation 2

ArborText *g42tiff*

AGFA Compugraphics *CAPS ccitt2caps v6.0x*

AFCTN *validg4*

AFCTN *calstb.475*

IGES Data Analysis (IDA) *IGESView 3.0*

Island Graphics *IslandPaint 3.0*

Cheetah

Inset Systems *HiJaak V2.1*

Inset Systems *HiJaak Window V1.0*

Software Publishing Corporation

(SPC) *Harvard Graphics V3.0*

Xerox Ventura Publisher

**Standards**

**Tested:**

MIL-STD-1840A

MIL-R-28002A

### 3. 1840A Analysis

#### 3.1 External Packaging

The tape was hand delivered to the Air Force CALS Test Bed (AFCTB). It was not enclosed in a box in accordance with ASTM D 3951.

The tape was not enclosed in a barrier bag nor barrier sheet material as required by MIL-STD-1840A, para. 5.3.1.2. Inspection of the tape reel showed a label indicating the recording density as required by MIL-STD-1840A, para. 5.3.1. A packing list, showing all files recorded on the tape, was not enclosed.

#### 3.2 Transmission Envelope

The 9-track tape received by the AFCTB contained MIL-STD-1840A files. The files were named per the standard conventions.

##### 3.2.1 Tape Formats

The tape was run through the AFCTN *Tapetool* v1.2.8 utility. 24 errors and 1 note were reported while evaluating the contents of the tape labels. Both the HDR1 and EOF1 records were reported as having errors in the Block Count. The tape did not have any value for this field. The HDR1 record should have a value of 0000 and the EOF1 should reflect the actual blocks used for the data.

Block Count:  
Implementation Identifier:

\*\*\* ERROR (ANSI X3.27; 8.5.1.13) - The characters in Block Count must be digits.

\*\*\* ERROR (ANSI X3.27; 8.5.1.13) - EOF1 Block Count does not equal to the actual block count. Expected = 0; Actual = 1

---

An additional error flagged by the TI version of *Tapetool* for both HDR1 and HDR2 was the use of null characters starting in position 54 in the header. ANSI 3.27, para. 6.2.1 requires the use of spaces or "characters" in these positions.

HDR1D001                   TAPE0100010001000100 93104 93104

- \*\*\* ERROR (ANSI X3.27; 6.2.1) - A label shall be a record that shall have a length of 80 bytes. Each label shall be recorded only within the first 80 byte positions of a block.
- \*\*\* ERROR (ANSI X3.27; 8.1) - Unless otherwise stated, the characters in the labels shall be coded in accordance with ANSI X3.4-1986. The 57 characters used in the labels shall be those positions of the standard code table in ANSI X3.4-1986 listed on page 13 of ANSI X3.27-1987 (errors are marked by ^ and are printed as spaces in the label if necessary).
- \*\*\* WARNING - This error will cause the software to misinterpret some of the label fields.

Part of the TI *Tapetool* log files are included in the Appendix of this report.

### 3.2.2 Declaration and Header Fields

72 errors and 73 notes were found in the Document Declaration File and data file headers. In Document Declaration File D001, an invalid change level was flagged. The error related to use of upper and lower case letters. MIL-STD-1840A , para. 5.1.1.2 shows the change level as "ORIGINAL". The field "chglvl" was shown as "chglvel". This error caused the AGFA CAPS *read1840A* utility to terminate processing the tape.

Several errors were reported also relating to the use of both upper and lower case letters. The value "None" was inserted for several header records when it should have been "NONE."

A date was also reported in error. The date value should be in the format YYYYMMDD.

srcdocid: None

---

\*\*\* ERROR (MIL-STD-1840A; 5.1.1.2) - Invalid value for 'srcdocid: '.  
\*\*\* NOTE (MIL-STD-1840A; 5.1.1.2) - When the value 'NONE'  
is used, it must be capitalized.  
\*\*\* NOTE - The 'srcdocid: ' Header Record will be given the value NONE.  
\*\*\* NOTE - Correction made in new Document Declaration Header Record.  
srcrelid: None  
\*\*\* ERROR (MIL-STD-1840A; 5.1.1.2) - Invalid value for 'srcrelid: '.  
\*\*\* NOTE (MIL-STD-1840A; 5.1.1.2) - When the value 'NONE'  
is used, it must be capitalized.  
\*\*\* NOTE - The 'srcrelid: ' Header Record will be given the value NONE.  
\*\*\* NOTE - Correction made in new Document Declaration Header Record.  
chglvel: Original  
\*\*\* ERROR (MIL-STD-1840A; 5.1.1.2) - Invalid Document Declaration header  
record identifier. Expected => chglvl:  
\*\*\* NOTE - The value in the header record may not be evaluated.  
\*\*\* NOTE - Correction made in new Document Declaration Header Record.  
dteis: 19930407  
dstsys: Unknown  
dstdocid: Unknown  
dstrelid: Unknown  
dtetrn: m15  
\*\*\* ERROR (MIL-STD-1840A; 5.1.1.2) - Invalid date format encountered.  
\*\*\* NOTE (MIL-STD-1840A; 5.1.1.2) - Date Format shall be a four digit year  
followed by a two digit month followed by a two digit day.

In the Raster files, the dstdocid field was flagged as being incorrect. No value was assigned to the field even though the Document Declaration file assigned "Unknown" as the value.

The use of both upper and lower case letter were identified as being incorrect.

If a tape contains only Raster or IGES files, it is considered to contain only product data information. If it is product data the figure identification (figid) record should contain the value "NONE."

dstdocid:  
\*\*\* ERROR (MIL-STD-1840A; 5.1.4) - Space missing after header record  
identifier delimiter ':'.  
\*\*\* ERROR (MIL-STD-1840A; 5.1.4) - Value missing after header field.  
\*\*\* NOTE - The 'dstdocid: ' Header Record will be given the value 'NONE'.  
\*\*\* NOTE - Correction made in new Raster Header File.  
txtfilid: NONE  
figid: None

---

\*\*\* ERROR (MIL-STD-1840A; 5.1.4) - Invalid value for 'figid: ' .  
\*\*\* NOTE (MIL-STD-1840A; 5.1.4) - When the value 'NONE'  
is used, it must be capitalized.  
\*\*\* NOTE - The 'figid: ' Header Record will be given the value NONE.  
\*\*\* NOTE - Correction made in new Raster Header Record.  
srcgph: 9248492\_sheet1  
\*\*\* ERROR (MIL-STD-1840A; 5.1.4.4) - Invalid value for 'srcgph: ' .  
Expected 'NONE' for Product Data.  
\*\*\* NOTE - The 'srcgph: ' Header Record will be given the value NONE.  
\*\*\* NOTE - Correction made in new Raster Header Record.

All Raster files must contain specific information on how they were created. The rtype field will route the file into the correct type, either "1" or "2". There was no value for this record.

The "orient" value is required to correctly orient the file when it is displayed. No value was given for this record.

The "rpelcnt" and "density" record provides a location for other important Raster data. Without this information most systems can not process the file.

rtype:

\*\*\* ERROR (MIL-STD-1840A; 5.1.4) - Space missing after header record identifier delimiter ':'.  
\*\*\* ERROR (MIL-STD-1840A; 5.1.4) - Value missing after header field.  
\*\*\* NOTE - The 'rtype: ' Header Record will be given the value 'NONE'.  
\*\*\* NOTE - Correction made in new Raster Header File.

orient:

\*\*\* ERROR (MIL-STD-1840A; 5.1.4) - Space missing after header record identifier delimiter ':'.  
\*\*\* ERROR (MIL-STD-1840A; 5.1.4) - Invalid Raster header record identifier. Expected => rorient:  
\*\*\* NOTE - The value in the header record may not be evaluated.  
\*\*\* ERROR (MIL-STD-1840A; 5.1.4) - Value missing after header field.  
\*\*\* NOTE - The 'rorient: ' Header Record will be given the value 'NONE'.  
\*\*\* NOTE - Correction made in new Raster Header File.

rpelcnt:

\*\*\* ERROR (MIL-STD-1840A; 5.1.4) - Space missing after header record identifier delimiter ':'.  
\*\*\* ERROR (MIL-STD-1840A; 5.1.4) - Value missing after header field.  
\*\*\* NOTE - The 'rpelcnt: ' Header Record will be given the value 'NONE'.  
\*\*\* NOTE - Correction made in new Raster Header File.

density:

\*\*\* ERROR (MIL-STD-1840A; 5.1.4) - Space missing after header record identifier delimiter ':'.  
\*\*\* ERROR (MIL-STD-1840A; 5.1.4) - Value missing after header field.

\*\*\* ERROR (MIL-STD-1840A; 5.1.4) - Invalid Raster header record identifier. Expected => rdensty:  
\*\*\* NOTE - The value in the header record may not be evaluated.  
\*\*\* ERROR (MIL-STD-1840A; 5.1.4) - Value missing after header field.  
\*\*\* NOTE - The 'rdensty: ' Header Record will be given the value 'NONE'.  
\*\*\* NOTE - Correction made in new Raster Header File.

The tape does not meet the CALS MIL-STD-1840A requirements.

#### 4. IGES Analysis

No Initial Graphics Exchange Specification (IGES) files were included on this tape.

#### 5. SGML Analysis

No Standard Generalized Markup Language (SGML) files were included on this tape.

#### 6. Raster Analysis

The tape contained five Raster files. All five files were evaluated using the AFCTN *validg4* utility. This program reported errors in all files. The reported errors were in the CALS headers. AFCTN *validg4* uses information in the CALS headers during the parsing procedure. This information was not included. See Appendix for a sample log file.

An attempt to display the Raster files using the AFCTN *calstb.475* resulted in a core dump.

It was also noted that the Raster data did not start at the correct location. Performing an octal dump of the Raster files showed that the data started at location 4600 instead of the required 4000 hex. This error was probably caused by the incorrect tape written procedure.

The AFCTB has several tools for viewing Raster files. These tools are not used to generate a pass/fail but to report how commercially available software can handle the files. Many of these products are used in the development of technical

publications and are good indicators of usability. The use of these products is not an endorsement nor an indication of CALS capability. All operations were performed using the default settings.

An attempt to read the files with Inset Systems' *HiJaak for Windows*, Arbortext's *g42tiff* and IDA's *IGESView* resulted in error messages being generated. Per Beverly Bernard of Inset Systems, the problems associated with *HiJaak for Windows v1.0* have been corrected in *HiJaak PRO v2.0*.

The Raster files do not meet the CALS MIL-R-28002A specification.

## 7. CGM Analysis

No Computer Graphic Metafile (CGM) files were included on this tape.

## 8. Conclusions and Recommendations

In summary, the tape from the 4950th Test Wing/AMIS was not correct. The tape contained both basic ANSI tape errors and CALS header errors.

The five Raster files could not be displayed by any of the AFCTB tools. The AFCTN *validg4* utility also reported the files were bad.

The tape does not meet the CALS MIL-STD-1840A requirements.

---

## 9. Appendix A - Tapetool Report Logs

### 9.1 Tape Catalog

Texas Instruments Catalog Evaluation - Version 1.0; Release Number 1

Standards referenced:

- MIL-STD-1840A (1987) - Automated Interchange of Technical Information
- MIL-R-28003 (1988) - Digital Representation For Communication Of  
Illustration Data; CGM Application Profile
- ANSI X3.27 (1987) - File Structure and Labeling of Magnetic Tapes  
for Information Interchange
- ANSI X3.4 (1986) - Coded Character Sets - 7 Bit ASCII

Mon Apr 19 11:04:02 1993

MIL-STD-1840A File Catalog

File Set Directory: /cals/tt13/Set012

Tape Volume ID: TAPE01

Page: 1

File Name	File Type	Record Format/ Block Length	Length/Total	Selected/ Partial/ Extracted
D001	Document Declaration	D/00260	02048/000001	Extracted
D001R001	Raster	F/00128	02048/000074	Extracted
D001R002	Raster	F/00128	02048/000077	Extracted
D001R003	Raster	F/00128	02048/000054	Extracted
D001R004	Raster	F/00128	02048/000129	Extracted
D001R005	Raster	F/00128	02048/000040	Extracted

Catalog Process terminated normally.

---

## 9.2 Tape Evaluation Log

Texas Instruments Tape Evaluation - Version 1.0; Release Number 1

Standards referenced:

ANSI X3.27 (1987) - File Structure and Labeling of Magnetic Tapes  
for Information Interchange

ANSI X3.4 (1986) - Coded Character Sets - 7 Bit ASCII

Mon Apr 19 11:03:17 1993

ANSI Tape Import Log

Allocating tape drive /dev/rmt0...

/dev/rmt0 allocated.

VOL1TAPE01

SONDERGD

3

Label Identifier: VOL1  
Volume Identifier: TAPE01  
Volume Accessibility:  
Implementation Identifier:  
Owner Identifier: SONDERGD  
Label Standard Version: 3

HDR1D001

TAPE0100010001000100 93104 93104

.....

- \*\*\* ERROR (ANSI X3.27; 6.2.1) - A label shall be a record that shall have a length of 80 bytes. Each label shall be recorded only within the first 80 byte positions of a block.
- \*\*\* ERROR (ANSI X3.27; 8.1) - Unless otherwise stated, the characters in the labels shall be coded in accordance with ANSI X3.4-1986. The 57 characters used in the labels shall be those positions of the standard code table in ANSI X3.4-1986 listed on page 13 of ANSI X3.27-1987 (errors are marked by ^ and are printed as spaces in the label if necessary).
- \*\*\* WARNING - This error will cause the software to misinterpret some of the label fields.

Label Identifier: HDR1  
File Identifier: D001  
File Set Identifier: TAPE01  
File Section Number: 0001  
File Sequence Number: 0001  
Generation Number: 0001  
Generation Version Number: 00  
Creation Date: 93104

Expiration Date: 93104  
File Accessibility:  
Block Count:  
Implementation Identifier:

\*\*\* ERROR (ANSI X3.27; 8.5.1.13) - The characters in Block Count must be digits.

\*\*\* ERROR (ANSI X3.27; 8.5.1.13) - HDR1 Block Count must always be '000000'.

HDR2D020480026000SONDERGD//USR/BIN B 00

Label Identifier: HDR2  
Recording Format: D  
Block Length: 02048  
Record Length: 00260  
Offset Length: 00

\*\*\*\*\* Tape Mark \*\*\*\*\*

\*\*\*\*\* Tape Mark \*\*\*\*\*

Minimum Block Size Found = 301 Bytes.  
Maximum Block Size Found = 301 Bytes.

\*\*\* NOTE - Last block was incomplete. Short blocks are prone to be interpreted as noise by some tape drives.  
Tape Label = 2048, Actual = 301, Block Number = 1

Number of data blocks read = 1.

EOF1D001 TAPE0100010001000100 93104 93104

\*\*\* ERROR (ANSI X3.27; 6.2.1) - A label shall be a record that shall have a length of 80 bytes. Each label shall be recorded only within the first 80 byte positions of a block.

\*\*\* ERROR (ANSI X3.27; 8.1) - Unless otherwise stated, the characters in the labels shall be coded in accordance with ANSI X3.4-1986. The 57 characters used in the labels shall be those positions of the standard code table in ANSI X3.4-1986 listed on page 13 of ANSI X3.27-1987 (errors are marked by ^ and are printed as spaces in the label if necessary).

\*\*\* WARNING - This error will cause the software to misinterpret some of the label fields.

Label Identifier: EOF1  
File Identifier: D001  
File Set Identifier: TAPE01

---

File Section Number: 0001  
File Sequence Number: 0001  
Generation Number: 0001  
Generation Version Number: 00  
Creation Date: 93104  
Expiration Date: 93104  
File Accessibility:  
Block Count:  
Implementation Identifier:

\*\*\* ERROR (ANSI X3.27; 8.5.1.13) - The characters in Block Count must be digits.

\*\*\* ERROR (ANSI X3.27; 8.5.1.13) - EOF1 Block Count does not equal to the actual block count. Expected = 0; Actual = 1

EOF2D020480026000SONDERGD//USR/BIN B 00

Label Identifier: EOF2  
Recording Format: D  
Block Length: 02048  
Record Length: 00260  
Offset Length: 00

\*\*\*\*\* Tape Mark \*\*\*\*\*

HDR1D001R001 TAPE0100010002000100 93104 70001

\*\*\* ERROR (ANSI X3.27; 6.2.1) - A label shall be a record that shall have a length of 80 bytes. Each label shall be recorded only within the first 80 byte positions of a block.

\*\*\* ERROR (ANSI X3.27; 8.1) - Unless otherwise stated, the characters in the labels shall be coded in accordance with ANSI X3.4-1986. The 57 characters used in the labels shall be those positions of the standard code table in ANSI X3.4-1986 listed on page 13 of ANSI X3.27-1987 (errors are marked by ^ and are printed as spaces in the label if necessary).

\*\*\* WARNING - This error will cause the software to misinterpret some of the label fields.

Label Identifier: HDR1  
File Identifier: D001R001  
File Set Identifier: TAPE01  
File Section Number: 0001  
File Sequence Number: 0002  
Generation Number: 0001  
Generation Version Number: 00  
Creation Date: 93104

---

Expiration Date: 70001  
File Accessibility:  
Block Count:  
Implementation Identifier:

\*\*\* ERROR (ANSI X3.27; 8.5.1.13) - The characters in Block Count must be digits.

\*\*\* ERROR (ANSI X3.27; 8.5.1.13) - HDR1 Block Count must always be '000000'.

HDR2F020480012800SONDERGD//USR/BIN M B 00

Label Identifier: HDR2  
Recording Format: F  
Block Length: 02048  
Record Length: 00128  
Offset Length: 00

\*\*\*\*\* Tape Mark \*\*\*\*\*

\*\*\*\*\* Tape Mark \*\*\*\*\*

Minimum Block Size Found = 2048 Bytes.  
Maximum Block Size Found = 2048 Bytes.

Number of data blocks read = 74.

EOF1D001R001 TAPE0100010002000100 93104 70001

\*\*\* ERROR (ANSI X3.27; 6.2.1) - A label shall be a record that shall have a length of 80 bytes. Each label shall be recorded only within the first 80 byte positions of a block.

\*\*\* ERROR (ANSI X3.27; 8.1) - Unless otherwise stated, the characters in the labels shall be coded in accordance with ANSI X3.4-1986. The 57 characters used in the labels shall be those positions of the standard code table in ANSI X3.4-1986 listed on page 13 of ANSI X3.27-1987 (errors are marked by ^ and are printed as spaces in the label if necessary).

\*\*\* WARNING - This error will cause the software to misinterpret some of the label fields.

Label Identifier: EOF1  
File Identifier: D001R001  
File Set Identifier: TAPE01  
File Section Number: 0001  
File Sequence Number: 0002  
Generation Number: 0001  
Generation Version Number: 00

---

Creation Date: 93104  
Expiration Date: 70001  
File Accessibility:  
Block Count:  
Implementation Identifier:

\*\*\* ERROR (ANSI X3.27; 8.5.1.13) - The characters in Block Count must be digits.

\*\*\* ERROR (ANSI X3.27; 8.5.1.13) - EOF1 Block Count does not equal to the actual block count. Expected = 0; Actual = 74

EOF2F020480012800SONDERGD//USR/BIN M B 00

Label Identifier: EOF2  
Recording Format: F  
Block Length: 02048  
Record Length: 00128  
Offset Length: 00

\*\*\*\*\* Tape Mark \*\*\*\*\*

<<<<< PART OF LOG FILE REMOVED HERE >>>>>

\*\*\*\*\* Tape Mark \*\*\*\*\*

\*\*\*\*\* Tape Mark \*\*\*\*\*

##### End of Volume TAPE01 #####

##### End Of Tape File Set #####

Rewinding tape to load point...

Deallocating /dev/rmt0...

Tape Import Process terminated with 49 error(s), 12 warning(s), and 1 note(s).

---

## 9.3 Tape File Set Validation Log

Texas Instruments File Set Evaluation - Version 1.0; Release Number 1

Standards referenced:

MIL-STD-1840A (1987) - Automated Interchange of Technical Information

MIL-STD-804C (1990) - Formats and Coding of Aperture, Camera, Copy,  
and Tabulating Cards

MIL-R-28002 (1989) - Raster Graphics Representation In Binary  
Format, Requirements For

Mon Apr 19 11:04:04 1993

MIL-STD-1840A File Set Evaluation Log

File Set: Set012

Found file: D001

Extracting Document Declaration Header Records...

Evaluating Document Declaration Header Records...

srcsys: Intergraph

srcdocid: None

\*\*\* ERROR (MIL-STD-1840A; 5.1.1.2) - Invalid value for 'srcdocid: '.

\*\*\* NOTE (MIL-STD-1840A; 5.1.1.2) - When the value 'NONE'  
is used, it must be capitalized.

\*\*\* NOTE - The 'srcdocid: ' Header Record will be given the value NONE.

\*\*\* NOTE - Correction made in new Document Declaration Header Record.

srcrelid: None

\*\*\* ERROR (MIL-STD-1840A; 5.1.1.2) - Invalid value for 'srcrelid: '.

\*\*\* NOTE (MIL-STD-1840A; 5.1.1.2) - When the value 'NONE'  
is used, it must be capitalized.

\*\*\* NOTE - The 'srcrelid: ' Header Record will be given the value NONE.

\*\*\* NOTE - Correction made in new Document Declaration Header Record.

chglvl: Original

\*\*\* ERROR (MIL-STD-1840A; 5.1.1.2) - Invalid Document Declaration header  
record identifier. Expected => chglvl:

\*\*\* NOTE - The value in the header record may not be evaluated.

\*\*\* NOTE - Correction made in new Document Declaration Header Record.

dteisu: 19930407

dstsys: Unknown

dstdocid: Unknown

dstrelid: Unknown

dtetrn: m15

\*\*\* ERROR (MIL-STD-1840A; 5.1.1.2) - Invalid date format encountered.

\*\*\* NOTE (MIL-STD-1840A; 5.1.1.2) - Date Format shall be a four digit year  
followed by a two digit month followed by a two digit day.

dlvacc: Unknown

---

filcnt: r5  
ttlcls: Unclassified  
doccls: Unclassified  
doctyp: Project Header  
docttl: Trainer

4 error(s), 0 warning(s), and 9 note(s) were encountered  
in Document Declaration File D001.

Searching for data files...

Found file: D001R001  
Extracting Raster Header Records...  
Evaluating Raster Header Records...

srcdocid: 9248492s1.cit  
dstdocid:

\*\*\* ERROR (MIL-STD-1840A; 5.1.4) - Space missing after header record  
identifier delimiter ':'.  
\*\*\* ERROR (MIL-STD-1840A; 5.1.4) - Value missing after header field.  
\*\*\* NOTE - The 'dstdocid: ' Header Record will be given the value 'NONE'.  
\*\*\* NOTE - Correction made in new Raster Header File.

txtfilid: NONE

figid: None

\*\*\* ERROR (MIL-STD-1840A; 5.1.4) - Invalid value for 'figid: '.  
\*\*\* NOTE (MIL-STD-1840A; 5.1.4) - When the value 'NONE'  
is used, it must be capitalized.  
\*\*\* NOTE - The 'figid: ' Header Record will be given the value NONE.  
\*\*\* NOTE - Correction made in new Raster Header Record.

srcgph: 9248492\_sheet1

\*\*\* ERROR (MIL-STD-1840A; 5.1.4.4) - Invalid value for 'srcgph: '.  
Expected 'NONE' for Product Data.  
\*\*\* NOTE - The 'srcgph: ' Header Record will be given the value NONE.  
\*\*\* NOTE - Correction made in new Raster Header Record.

doccls: Unclassified

rtype:

\*\*\* ERROR (MIL-STD-1840A; 5.1.4) - Space missing after header record  
identifier delimiter ':'.  
\*\*\* ERROR (MIL-STD-1840A; 5.1.4) - Value missing after header field.  
\*\*\* NOTE - The 'rtype: ' Header Record will be given the value 'NONE'.  
\*\*\* NOTE - Correction made in new Raster Header File.

orient:

\*\*\* ERROR (MIL-STD-1840A; 5.1.4) - Space missing after header record  
identifier delimiter ':'.  
\*\*\* ERROR (MIL-STD-1840A; 5.1.4) - Invalid Raster header  
record identifier. Expected => rorient:  
\*\*\* NOTE - The value in the header record may not be evaluated.  
\*\*\* ERROR (MIL-STD-1840A; 5.1.4) - Value missing after header field.

---

\*\*\* NOTE - The 'rorient: ' Header Record will be given the value 'NONE'.

\*\*\* NOTE - Correction made in new Raster Header File.

rpelcnt:

\*\*\* ERROR (MIL-STD-1840A; 5.1.4) - Space missing after header record identifier delimiter ':'.

\*\*\* ERROR (MIL-STD-1840A; 5.1.4) - Value missing after header field.

\*\*\* NOTE - The 'rpelcnt: ' Header Record will be given the value 'NONE'.

\*\*\* NOTE - Correction made in new Raster Header File.

density:

\*\*\* ERROR (MIL-STD-1840A; 5.1.4) - Space missing after header record identifier delimiter ':'.

\*\*\* ERROR (MIL-STD-1840A; 5.1.4) - Invalid Raster header record identifier. Expected => rdensty:

\*\*\* NOTE - The value in the header record may not be evaluated.

\*\*\* ERROR (MIL-STD-1840A; 5.1.4) - Value missing after header field.

\*\*\* NOTE - The 'rdensty: ' Header Record will be given the value 'NONE'.

\*\*\* NOTE - Correction made in new Raster Header File.

notes: None

\*\*\* ERROR (MIL-STD-1840A; 5.1.4) - Invalid value for 'notes: '.

\*\*\* NOTE (MIL-STD-1840A; 5.1.4) - When the value 'NONE' is used, it must be capitalized.

\*\*\* NOTE - The 'notes: ' Header Record will be given the value NONE.

\*\*\* NOTE - Correction made in new Raster Header Record.

15 error(s), 0 warning(s), and 20 note(s) were encountered in Raster File D001R001.

Saving Raster Header File: D001R001\_HDR

Saving Raster Data File: D001R001\_GR4

\*\*\* ERROR (MIL-STD-1840A; 5.2.1.6) - Stray characters were found in the padding area of the Raster Header Block.

\*\*\* NOTE - Padding area will be considered to be data.

<<<< PART OF LOG FILE REMOVED HERE >>>>

Evaluating Document D001 numbering scheme...

No errors were encountered during numbering scheme evaluation.

Numbering scheme evaluation complete.

Checking Document D001 file count...

No errors were encountered during file count verification.

File Count verification complete.

Saving Document Declaration Header File: D001\_HDR

Saving Document D001 Map File: MAP.LIS

A total of 79 error(s), 0 warning(s), and 109 note(s) were encountered in Document D001.

A grand total of 79 error(s), 0 warning(s), and 109 note(s) were encountered in File Set Set012.

## **10. Appendix B - Raster Detailed Analysis**

### **10.1 File D001R001**

#### **10.1.1 Error Log validg4**

CALS header 2 coded improperly (see MIL-STD-1840A; 5.1.4).

Unable to read group 4 file = r001.cal  
return status from routine vfrini = 4

Bad CALS header terminated validation