

ARMY RESEARCH LABORATORY





Temperature-Controlled Bending of a Gun Tube

Mark Bundy

ARL-MR-315

June 1996

OCT 1996



APPROVED FOR PUBLIC RELEASE; DISTRIBUTION IS UNLIMITED.

Page intentionally blank

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188	
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project(0704-0188), Washington, DC 20503.				
1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE June 1996	3. REPORT TYPE AND DATES COVERED Final, Dec 1994 - 1995	
4. TITLE AND SUBTITLE Temperature-Controlled Bending of a Gun Tube			5. FUNDING NUMBERS PR: 1L162618AH80	
6. AUTHOR(S) Mark Bundy				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army Research Laboratory ATTN: AMSRL-WT-PB Aberdeen Proving Ground, MD 21005-5066			8. PERFORMING ORGANIZATION REPORT NUMBER ARL-MR-315	
9. SPONSORING/MONITORING AGENCY NAMES(S) AND ADDRESS(ES)			10. SPONSORING/MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES				
12a. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution is unlimited.			12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) For some ammunition types, the projectile impact location appears to be gun tube dependent, even though the aim point, barrel mount, and ammunition lot may be the same. It is thought that such barrel dependency is due to manufactured differences in the straightness of each tube. To test this hypothesis, we have devised a means to reversibly control the centerline curvature of a gun tube. This preliminary report describes how a series of heating pads, adhered to the external surface of the barrel, can be used to change the bore centerline curvature. Several centerline alterations are demonstrated on a 120-mm M256 tank cannon. The theoretical prediction for each of several heat-pad-induced centerline changes compares favorably with borescope measurements of the muzzle angle change and dial-indicator measurements of the outer-wall barrel displacement. Future gun firings of this temperature-controlled barrel will be used to examine the correlation between shot impact location and centerline curvature.				
14. SUBJECT TERMS accuracy, modeling, gun barrel, controlled centerline bend, distortion			15. NUMBER OF PAGES 29	
			16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT UL	

INTENTIONALLY LEFT BLANK

TABLE OF CONTENTS

LIST OF FIGURES	v
1. INTRODUCTION	1
2. INSTRUMENTATION	3
3. TUBE SHAPES	3
3.1 Straight	4
3.2 Half Sine Wave	9
3.3 Full Sine Wave	11
4. CONCLUSIONS	13
4. REFERENCES	15
DISTRIBUTION LIST	17

INTENTIONALLY LEFT BLANK

LIST OF FIGURES

<u>Figure</u>	<u>Page</u>
1. Illustrating the effect of recoil on a curved bore centerline.	1
2. Change in shot impacts and muzzle point angle during four 25-round bursts, with 2 min between bursts.	2
3. Illustration of temperature-controlled M256 gun barrel.	3
4. Comparison of centerline straightness for a relatively straight M256, serial number 2971, vs. a more typical M256 barrel, serial number 4088.....	4
5. CBTD needed to further straighten M256 serial number 2971 in the vertical (top) and horizontal (bottom) planes.	6
6. Temperature-controlled straightening of M256 serial number 2971 in the vertical (top) and horizontal (bottom) planes.	7
7. Comparison of CBTD-based prediction vs. measurement of muzzle angle and muzzle displacement induced by heating pad pattern used to further straighten M256 serial number 2971.	8
8. Heat-pad-induced CBTD profile used to create a half sine wave bore centerline curvature.....	9
9. Change in bore straightness due to Figure 8 heating.	10
10. Comparison of prediction vs. measurement over time.	10
11. Centerline change due to left-sided heating of Figure 8, compared to the natural horizontal curvature of tube 2971.	11
12. CBTD pattern used to create a sine-wave-like thermal distortion of the barrel.	12
13. Predicted bore centerline change, relative to the straight-line muzzle-to-chamber chord, due to the CBTD pattern of Figure 12.	12
14. Comparison of CBTD-based prediction vs. measurement of lateral barrel displacement induced by heating profile of Figure 12.	13

INTENTIONALLY LEFT BLANK

1. INTRODUCTION

The difference between where a gun is aimed (correcting for gravity drop, wind, and drag) and where the projectile actually strikes the target is referred to as projectile jump. Factors that contribute to projectile jump include, but are not limited to (Bornstein et al. 1988): (1) the muzzle angle and (2) its transverse velocity at shot exit, as well as (3) asymmetric sabot discard (for kinetic-energy-type ammunition). The following intuitive arguments describe how these factors could depend, to some extent, on bore straightness.

The explosion of gun gases in the chamber moves the projectile forward and the barrel rearward (recoil). The transmission of recoil forces along a curved barrel creates longitudinal and transverse components of force, and hence acceleration, as depicted in Figure 1. Since transverse motion of the muzzle will be imparted to the projectile at shot exit, it can affect projectile jump. Indeed, such circumstances could help explain the results of a recent 25-mm M242 accuracy test (Garner et al. 1995). Cross-barrel temperature differences (CBTDs) indicated that during rapid fire, thermal distortion of the gun barrel increased the curvature of the bore centerline to the gunner's left, while at the same time, the round impacts moved (in general) to the gunner's right, Figure 2. It can be reasoned that the correlation between change in prefiring bore curvature and change in projectile impact location resulted from transverse motion of the muzzle that was imparted to the projectile at shot exit.




Figure 1. Illustrating the effect of recoil on a curved bore centerline.

In the case of sabot rounds, forcing the projectile to follow the lateral oscillations of a curved bore centerline is thought to produce an asymmetric distribution of compressional energy loads within the elastic sabot petals. This is believed to affect the symmetry of sabot petal separation from the central long rod penetrator, and hence affect the symmetry of aerodynamic side forces (created by shock waves from the discarding sabot petals [Plostins, Bornstein, and Celmins 1991]) on the penetrator before it enters free flight.




Figure 2. Change in shot impacts and muzzle point angle during four 25-round bursts, with 2 min between bursts (Garner et al. 1995).

To study the relationship between tube straightness (centerline curvature) and projectile jump, we have instrumented a 120-mm M256 gun barrel with temperature-controlled heating pads along its axis, in both the horizontal and vertical planes. The heating pads are used to create a CBTD pattern that changes the bore centerline. Three cases of thermal bend are examined in this report. In each case, a thermal distortion model (Bundy 1993) is used to predict centerline change based on the measured CBTDs. A muzzle borescope and displacement-measuring dial indicators are used to validate the predicted change. At some future date, the barrel will be fired to ascertain the effect of centerline change on projectile jump.

2. INSTRUMENTATION

Twenty 5-in by 14-in (127-mm by 356-mm), 600-W heating pads (made by Ocean State Thermotics, Inc.) were affixed to the external surface of an M256 cannon using thermally conductive silicone rubber (Sylgard 577 by Dow Corning), as illustrated in Figure 3. Each pad was fabricated with a 0.5-in (~13-mm) hole in its center, through which a k-type (Chromel-Alumel) thermocouple monitored the gun barrel temperature. Each thermocouple and heating pad combination was connected to a temperature controller (manufactured by Omega Engineering, Inc.) that turned the heating pad on or off so as to maintain (within a few degrees Celsius) a preset barrel temperature.




Figure 3. Illustration of temperature-controlled M256 gun barrel.

An unsymmetric heat (pad) input pattern was used to create thermal distortion of the barrel, which was measured in two ways. Dial indicators were used to gauge the off-axis (transverse, or lateral) displacement, while a muzzle borescope was used to determine the change in muzzle pointing angle.

3. TUBE SHAPES

Three different centerline profiles were examined. The first profile attempted to make the bore centerline as straight as possible; the second created a bow-like (half sine wave) curvature in the barrel; and the third shape resembled that of a full sine wave. Bear in mind, these changes are not perceptible to the unaided eye, creating maximum centerline deviations from an end-to-end chord of less than 1 mm (as shown later).

3.1 Straight

The particular barrel chosen for this study (M256 serial number 2971) was manufactured relatively straight. In fact, "2971" is straighter than all 20 of the M256 barrels studied by Wilkerson (1995) in his report on barrel straightness and accuracy. Figure 4 shows a comparison of 2971's centerline with that of a typical barrel in the Wilkerson study (e.g., serial number 4088). The displacement in both planes in Figure 4 is measured relative to a straight-line chord drawn from the muzzle end of the bore, to the chamber end (specifically, from ~230 mm to ~4630 mm from the muzzle, which delimits the range of the bore centerline measuring device). A positive value means the bore centerline is displaced above the chord in the vertical plane, and to the (gunner's) right of the chord in the horizontal plane.




Figure 4. Comparison of centerline straightness for a relatively straight M256, serial number 2971, vs. a more typical M256 barrel, serial number 4088.

In spite of its inherent straightness, the heating pads were used to make 2971 even straighter. This was accomplished with the measured CBTD distribution shown in Figure 5. Note, there is a difference between the preset value for the CBTD and the measured CBTD. This is due, in part, to the fact that each temperature controller will turn on and off within a 1-2° C temperature range about the preset value. But a larger share of the disparity, particularly in the vertical plane, where more heating pads were installed, is due to the fact that heat from each pad migrates axially and circumferentially to the location of nearby heating pads. Furthermore, gravity predisposes the top of the barrel to be hotter than the bottom. As a result, each heating pad must compensate for heat input from nearby heating pads and gravity effects in order to obtain the sought-after CBTD profile.

It should also be pointed out that there is only one measured CBTD for every pair of laterally opposed heating pads. Nevertheless, close inspection of Figure 5 reveals that three CBTDs have been apportioned to the region spanned by each pad. The assignment of three CBTDs from a singular measurement is based on the a priori assumption that the region of the barrel under the central third of the pad is at the measured CBTD, while the outer two thirds are assumed to have half of this value. As is shown later, this prescription for assigning CBTDs leads to reasonably good agreement between theory and experiment, particularly in the horizontal plane. We shall henceforth refer to the assigned CBTDs as simply the measured CBTDs.

Figure 6 displays the predicted effect on straightness of two measured CBTD profiles, one of which is shown in Figure 5. The square-shaped symbols mark the inherent (manufactured) centerline curvature for tube 2971. The diamond-shaped symbols outline the predicted centerline change brought about by measured CBTDs from two different trials; and the circle-shaped symbols are a summation of the manufactured curvature with the CBTD-induced curvature.

Even though there is variation in the level of straightness from one trial to the next in Figure 6 (due to the on-off tolerance level in each temperature-controlling device), there is at least a twofold increase in straightness of 2971 that is brought about by use of the heating pads.




Figure 5. Cross barrel temperature difference (CBTD) needed to further straighten M256 serial number 2971 in the vertical (top plot) and horizontal (bottom plot) planes.




Figure 6. Temperature-controlled straightening of M256 serial number 2971, in the vertical (top) and horizontal (bottom) planes.

We would expect the summed curves in Figure 6 to be close to that which could be measured during these heating pad trials, if it were not for the fact that critical optical components in the centerline measuring device will not function properly in the turbulent bore atmosphere created by heating the barrel. Since it is not possible to directly measure the bore straightness with the heating pads in operation, the model is validated by comparing predictions with measurements of the muzzle angle and off-axis displacement of the outer barrel wall (using standard machinist's dial indicators). Figure 7 shows such a comparison.




Figure 7. Comparison of CBTD-based prediction vs. measurement of muzzle angle and muzzle displacement induced by heating pad pattern used to further straighten M256 serial number 2971.

As can be seen, the angular difference between theory and experiment is at most 0.1 mil, while the displacement difference can vary by 0.2 mm (0.008 in). In general, the agreement is better in the horizontal plane than in the vertical plane. Additional comparisons will be shown for other tube shapes.

3.2 Half Sine Wave

Many bore centerlines have a simple bow, or half sine wave shape (Wilkerson 1995), perhaps 50%. The heating pattern shown in Figure 8 was used to create such a shape in 2971. It can be seen that CBTDs greater than 20° C can be obtained with the heating pads. (For comparison, a CBTD of 26° C was observed when rain-like precipitation impinged on a hot, post-fired barrel [Bundy 1987]). Figure 9 shows how this type of left-sided heating pattern deflected the barrel to the right, relative to the unheated state. As shown, the measured and predicted displacement differed by less than 0.1 mm at two arbitrarily chosen locations on the barrel.




Figure 8. Heat-pad-induced CBTD profile used to create a half sine wave bore centerline curvature.

Figure 9 references a particular time during heating; Figure 10 shows how theory and experiment compare over time during the heating process. In general, the muzzle angle comparison agrees within 0.1 mil, while the muzzle displacement agrees within 0.2 mm, as was the case in Figure 7.




Figure 9. Change in bore straightness due to Figure 8 heating.




Figure 10. Comparison of prediction vs. measurement over time.

The left-sided heating of Figure 8 creates a centerline change that is several times larger in magnitude than the natural bore curvature, Figure 11.




Figure 11. Centerline change due to left-sided heating of Figure 8, compared to the natural horizontal curvature of tube 2971.

3.3 Full Sine Wave

The CBTD pattern shown in Figure 12 was used to create the full sine wave distortion shown in Figure 13. Dial indicators placed at three locations along the barrel show, Figure 14, that the predicted curve underestimates the measured shape change by 10–20%. Moreover (not shown), the predicted muzzle angle was 0.18 mil compared with the measured muzzle angle of 0.32 mil. Even though the differences between theory and experiment are larger in Figure 14 (vertical plane) than they were in Figure 9 (horizontal plane), the differences are not large in comparison to the overall shape change. In perspective, the difference in fall of shot from the predicted vs. the measured shape change in Figure 14 is expected to be far less than that produced by its mirror image, due to reversing the CBTD heating profile.




Figure 12. CBTD pattern used to create a sine-wave-like thermal distortion of the barrel.




Figure 13. Predicted bore centerline change, relative to the straight-line muzzle-to-chamber chord, due to the CBTD pattern of Figure 12.




Figure 14. Comparison of CBTD-based prediction vs. measurement of lateral barrel displacement induced by heating profile of Figure 12.

4. CONCLUSIONS

Heating pads were used to thermally distort the barrel, as demonstrated by creating three different tube shapes, viz., a straight tube, a half, and a full sine wave shape.

A thermal distortion model, based on measurements of the cross-barrel temperature differences, CBTDs, was used to predict/estimate the overall centerline shape change. It was not possible to measure the CBTD-induced shape change with a conventional (optically based) centerline measuring instrument, due to hot-air turbulence in the bore. Instead, the thermal distortion model was validated by comparing the predicted vs. measured muzzle angle (using a muzzle borescope), as well as the predicted vs. measured off-axis barrel displacement (using dial indicators).

As a whole, the prediction and measurement agreed fairly well—the muzzle angle values were within 0.1 mil (for comparison, the error in the muzzle scope reading is considered to be 0.05 mils), and the displacement values were within 0.2 mm (0.008 in).

Elaborating, the agreement between theory and experiment appeared to be better in the horizontal plane than in the vertical plane. It could be the case that the postulated distribution of barrel temperature beneath the pad is not as universal as was assumed. That is, the barrel section under the middle third of the heating pad was assigned the pad-centered CBTD measurement; whereas the barrel sections beneath the outer two thirds of the pad were assigned half the measured value. This assumed distribution of barrel temperature across the pad, based on one central-pad measurement, seems to provide better results in the horizontal plane, where the spacing between pads is slightly greater, than in the vertical plane. Nevertheless, the magnitude of the discrepancy is not sufficient to warrant further refinement in the predictive procedure at this time. It is expected that a bow-, or s-shaped, curve to the right vs. left, up, or down, will have a far larger affect on shot impact than the 10-20% discrepancy between the predicted and measured/actual barrel curvature.

Future live-fire tests will examine the influence of centerline shape on projectile impact locations by firing, for example, a bow shape to the right vs. left, and noting the difference, if any, in the fall-of-shot pattern.

4. REFERENCES

- Bundy, M. L. "Improved Thermal Shroud Protection for Tank Cannon from Internal and External Heat Flux Asymmetries." BRL-TR-2777, U.S. Army Ballistic Research Laboratory, Aberdeen Proving Ground, MD, February 1987.
- Bundy, M. L. "Gun Barrel Cooling and Thermal Droop Modeling." ARL-TR-189, U.S. Army Research Laboratory, Aberdeen Proving Ground, MD, August 1993.
- Bornstein, J., I. Celmins, P. Plostins, and E. M. Schmidt. "Techniques for the Measurement of Tank Cannon Jump." BRL-MR-3715, U.S. Army Ballistic Research Laboratory, Aberdeen Proving Ground, MD, December 1988.
- Garner, J. M., M. L. Bundy, D. W. Webb, and B. J. Patton. "Variation in Muzzle Pointing Angle and Shot Impact of M2452 Chain Gun." ARL-TR-785, U.S. Army Research Laboratory, Aberdeen Proving Ground, MD, July 1995.
- Plostins, P., J. A. Bornstein, and I. Celmins. "The Effect of Sabot Wheelbase and Position on the Launch Dynamics of Fin-Stabilized Kinetic Energy Ammunition." BRL-TR-3225, U.S. Army Ballistic Research Laboratory, Aberdeen Proving Ground, MD, April 1991.
- Wilkerson, S. "Possible Effects of Gun Tube Straightness on Dispersion." ARL-TR-767, U.S. Army Research Laboratory, Aberdeen Proving Ground, MD, June 1995.

INTENTIONALLY LEFT BLANK

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
2	DEFENSE TECHNICAL INFO CTR ATTN DTIC DDA 8725 JOHN J KINGMAN RD STE 0944 FT BELVOIR VA 22060-6218

1	DIRECTOR US ARMY RESEARCH LAB ATTN AMSRL OP SD TA 2800 POWDER MILL RD ADELPHI MD 20783-1145
---	---

3	DIRECTOR US ARMY RESEARCH LAB ATTN AMSRL OP SD TL 2800 POWDER MILL RD ADELPHI MD 20783-1145
---	---

1	DIRECTOR US ARMY RESEARCH LAB ATTN AMSRL OP SD TP 2800 POWDER MILL RD ADELPHI MD 20783-1145
---	---

ABERDEEN PROVING GROUND

2	DIR USARL ATTN AMSRL OP AP L (305)
---	---------------------------------------

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
4	COMMANDER US ARMY ARMOR CENTER ATTN ATSB CD ATSB SBE ORSA FORT KNOX KY 40121
5	COMMANDER US ARMY TACOM ATTN AMSTA CA AMSTA CF AMSTA CU AMSTA UW AMSTA UE WARREN MI 48397-5000
2	PEO FOR ARMAMENTS ATTN SFAE AR SFAE AR D PICATINNY ARSENAL NJ 07806-5000
8	PEO FOR ARMORED SYS MOD ATTN SFAE ASM SFAE ASM AB SFAE ASM AB SW SFAE ASM AB S SFAE ASM AG SFAE ASM SS SFAE ASM BT SFAE ASM FV WARREN MI 48397-5000
1	HEADQUARTERS US ARMY MATERIEL CMD ATTN AMCICP AD M FISETTE 5001 EISENHOWER AVE ALEXANDRIA VA 22333-0001
1	US ARMY BMDS CMD ADVANCED TECHLGY CTR PO BOX 1500 HUNTSVILLE AL 35807-3801
1	OFC OF THE PRODUCT MGR 155MM HOWITZER M109A6 PALADIN ATTN SFAE AR HIP IP MR R DE KLEINE PICATINNY ARSENAL NJ 07806-5000

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
7	COMMANDER TANK MAIN ARMAMENT SYS ATTN SFAE AR TMA V ROSAMILIA R BILLINGTON W KATZ R JOINSON C ROLLER E KOPACZ K RUBEN PICATINNY ARSENAL NJ 07806-5000
5	COMMANDER US ARMY ARDEC ATTN AMSTA AR AE AMSTA AR FSF GD K PFLEGER AMSTA AR FSF BV V GALGANO C GONZALES C LANGEN PICATINNY ARSENAL NJ 07806-5000
4	COMMANDER US ARMY ARDEC ATTN AMSTA AR CCH V C MANDALA E FENNELL A GOWARTY J PETTY PICATINNY ARSENAL NJ 07806-5000
1	COMMANDER US ARMY ARDEC ATTN AMSTA AR AEE B S BERNSTEIN PICATINNY ARSENAL NJ 07806-5000
4	COMMANDER US ARMY ARDEC ATTN AMSTA AR QAT A L DULISSI C PATEL R ROESER G MAGISTRO PICATINNY ARSENAL NJ 07806-5000

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
1	COMMANDER US ARMY ARDEC ATTN AMSTA AR AEE J LANNON PICATINNY ARSENAL NJ 07806-5000
1	COMMANDER US ARMY ARDEC ATTN AMSTA AR ATE A STAN KAHN PICATINNY ARSENAL NJ 07806-5000
5	COMMANDER US ARMY ARDEC ATTN SFAE FAS AF COL D NAPOLIELLO L YUNG T KURIATA E DELCOCO H TRAN PICATINNY ARSENAL NJ 07806-5000
2	COMMANDER US ARMY ARDEC ATTN AMSTA AR FSF BD R MEENAN J DELABAR PICATINNY ARSENAL NJ 07806-5000
2	COMMANDER US ARMY ARDEC ATTN AMSTA AR FSS A L MUND L PINDER PICATINNY ARSENAL NJ 07806-5000
2	COMMANDER US ARMY ARDEC ATTN AMSTA AR FSS E J BROOKS M ENNIS PICATINNY ARSENAL NJ 07806-5000
1	COMMANDER US ARMY ARDEC ATTN AMSTA AR FSE T GORA PICATINNY ARSENAL NJ 07806-5000

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
3	COMMANDER US ARMY ARDEC ATTN AMSTA AR TD R PRICE V LINDNER C SPINELLI PICATINNY ARSENAL NJ 07806-5000
1	COMMANDER US ARMY ARDEC ATTN F MCLAUGHLIN PICATINNY ARSENAL NJ 07806-5000
4	COMMANDER US ARMY ARDEC ATTN AMSTA AR CCH T S MUSALLI P CHRISTIAN R CARR N KRASNOW PICATINNY ARSENAL NJ 07806-5000
1	COMMANDER US ARMY ARDEC ATTN AMSTA AR CCH J DELORENZO PICATINNY ARSENAL NJ 07806-5000
2	COMMANDER US ARMY ARDEC ATTN AMSTA AR CC J HEDDERICH COL SINCLAIR PICATINNY ARSENAL NJ 07806-5000
1	COMMANDER US ARMY ARDEC ATTN AMSTA AR CCH P J LUTZ PICATINNY ARSENAL NJ 07806-5000
2	COMMANDER US ARMY ARDEC ATTN AMSTA AR FSA M D DEMELLA F DIORIO PICATINNY ARSENAL NJ 07806-5000

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>	<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
2	COMMANDER US ARMY ARDEC ATTN AMSTA AR FSA A WARNASH B MACHAK PICATINNY ARSENAL NJ 07806-5000	1	PROGRAM MANAGER US ARMY TACOM ATTN AMCPM ABMS T DEAN WARREN MI 48092-2498
20	DIRECTOR US ARMY ARDEC ATTN AMSTA AR CCB C KITCHENS J KEANE J BATTAGLIA J VASILAKIS G PFLEGL G FRIAR V MONTVOIR P O'HURA D PORTER M WITHESELL R GAST C A ANDRADE J HAAS A GABRIEL P VOTIS J HIGGINS F HEISER J WRZUCHALSKI R HASENBEIN AMSTA AR CCB T S SOPOK BENET LABS WATERVLIET NY 12189	1	PROGRAM MANAGER US ARMY TACOM ATTN SFAE ASM BV FIGHTING VEHICLE SYSTEMS WARREN MI 48397-5000
		2	COMMANDER US ARMY TACOM ATTN SFAE ASM AB SW DR PATTISON MAJ M PADGETT WARREN MI 48397-5000
		1	PROGRAM MANAGER ABRAMS TANK SYSTEM ATTN SFAE ASM AB WARREN MI 48397-5000
		1	COMMANDANT US ARMY CMD & GEN STAFF COLLEGE FORT LEAVENWORTH KS 66027
		1	COMMANDANT US ARMY SPCL WARFARE SCHL ATTN REV AND TRNG LIT DIV FORT BRAGG NC 28307
1	COMMANDER US ARMY ARDEC ATTN AMSMC PBM K PROD BASE MODERN ACTY PICATINNY ARSENAL NJ 07806-5000	1	COMMANDER RADFORD ARMY AMMUNITION PLANT ATTN SMCAR QA HI LIB RADFORD VA 24141-0298
2	DIRECTOR BENET WEAPONS LABS ATTN AMSTA AR CCB DI C RINALDI AMSTA AR CCB RP G CAPSINALIS WATERVLIET NY 12189-4050	1	COMMANDER US ARMY NGIC ATTN AMXST MC 3 220 SEVENTH STREET NE CHARLOTTESVILLE VA 22901-5396
1	COMMANDER USA CECOM ATTN ASQNC ELC IS L R MYER CTR R&D TECH LIB FORT MONMOUTH NJ 07703-5301	1	COMMANDANT US ARMY FIELD ARTLRY CTR & SCHOOL ATTN ATSF CD COL T STRICKLIN FORT SILL OK 73503-5600

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
1	COMMANDANT US ARMY FIELD ARTLRY CTR & SCHOOL ATTN ATSF CN P GROSS FORT SILL OK 73503-5600
1	COMMANDANT US ARMY ARMOR SCHOOL ATTN ATZK CD MS M FALKOVITCH ARMOR AGENCY FORT KNOX KY 40121-5215
1	DIRECTOR US ARMY ARMOR SCHOOL ATTN ATSB WP ORSA A POMEY WEAPONS DEPT FORT KNOX KY 40121-5212
2	PM AFAS ATTN SFAE ASM AF LTC A ELLIS LTC B ELLIS PICATINNY ARSENAL NJ 07806-5000
3	OFFICE OF THE PM M109/AG PALADIN ATTN SFAE AR HIP J CARBONE K HURBAN S WALL PICATINNY ARSENAL NJ 07806-5000
1	COMMANDER USA ARMAMENT MUNTNS & CHEMCL CMD ATTN AMSMC DSD C J O'DONNELL ROCK ISLAND IL 61299-6000
3	COMMANDANT US ARMY FIELD ARTILLERY SCHOOL ATTN ATSF CC R LILLARD ATSF GD ATSF CT J GEIST FORT SILL OK 73503-5600
1	DIRECTOR US ARMY FIELD ARTILLERY BOARD ATTN ATZR BDW FORT SILL OK 73503

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
1	HQDA PENTAGON ATTN SARD TT DR F MILTON WASHINGTON DC 20310-0103
1	HQDA PENTAGON ATTN SARD TR DR R CHAIT WASHINGTON DC 20310-0103
1	HQDA PENTAGON ATTN SARD TR MS K KOMINOS WASHINGTON DC 30310-0103
1	DIRECTOR US ARMY RESEARCH LAB ATTN AMSRL CP CA D SNIDER 2800 POWDER MILL RD ADELPHI MD 20783
1	COMMANDER US ARMY TACOM ATTN AMSTA JSK S GOODMAN WARREN MI 48397-5000
1	COMMANDER ATTN SMCWV QAE Q C HOWD BLDG 44 WATERVLIET ARSNL WATERVLIET NY 12189-4050
1	COMMANDER ATTN SMCWV SPM T MCCLOSKEY BLDG 25 3 WTRVLT ARSNL WATERVLIET NY 12189-4050
1	COMMANDER WATERVLIET ARSENAL ATTN SMCWV QA QS K INSCO WATERVLIET NY 12189-4050
1	COMMANDER US ARMY BELVOIR RD&E CTR ATTN STRBE JBC FORT BELVOIR VA 22060-5606
1	US ARMY COLD REGIONS RSCH & ENGINEERING LABORATORY ATTN P DUTTA 72 LYME RD HANOVER NH 03755

NO. OF
COPIES ORGANIZATION

1 DIRECTOR
US ARMY RESEARCH LAB
ATTN AMSRL WT L
D WOODBURY
2800 POWDER MILL RD
ADELPHI MD 20783-1145

2 US ARMY RESEARCH OFFICE
ATTN A CROWSON
J CHANDRA
PO BOX 12211
RESEARCH TRIANGLE PARK NC
27709-2211

3 COMMANDER
US ARMY MISSILE COMMAND
ATTN AMSMI RD W MCCORKLE
AMSMI RD ST P DOYLE
AMSMI RD ST CN T VANDIVER
REDSTONE ARSENAL AL 35898

3 US ARMY RESEARCH OFFICE
ATTN R SINGLETON
G ANDERSON
K IYER
ENGINEERING SCIENCES DIV
PO BOX 12211
RESEARCH TRIANGLE PARK NC
27709-2211

2 PROJECT MANAGER
SADARM
PICATINNY ARSENAL NJ
07806-5000

2 PM TANK MAIN ARM SYS
ATTN SFAE AR TMA
COL BREGARD
K KIMKER
PICATINNY ARSENAL NJ
07806-5000

3 PM TANK MAIN ARM SYS
ATTN SFAE AR TMA MD
R KOWALSKI
B HELD
B DACEY
PICATINNY ARSENAL NJ
07806-5000

NO. OF
COPIES ORGANIZATION

2 PEO FIELD ART SYS
ATTN SFAE FAS PM
D ADAMS
T MCWILLIAMS
PICATINNY ARSENAL NJ
07806-5000

1 PEO FIELD ART SYS
ATTN SFAE FAS PM
H GOLDMAN
PICATINNY ARSENAL NJ
07806-5000

2 PM AFAS
ATTN G DELCOCO
J SHIELDS
PICATINNY ARSENAL NJ
07806-5000

2 PROGRAM MANAGER
GROUND WEAPONS MCRDAC
CBGT
QUANTICO VA 22134-5000

2 COMMANDER
NAVAL SEA SYSTEMS CMD
ATTN SEA 62R
SEA 64
WASHINGTON DC 20362-5101

1 COMMANDER
NAVAL AIR SYSTEMS CMD
ATTN AIR 954 TECH LIBRARY
WASHINGTON DC 20360

4 COMMANDER
NAVAL RSRCH LAB
ATTN TECHNICAL LIBRARY
CODE 4410
K KAILASANATE
J BORIS
E ORAN
WASHINGTON DC 20375-5000

1 OFFICE OF NAVAL RSRCH
ATTN CODE 473 R S MILLER
800 N QUINCY ST
ARLINGTON VA 22217-5000

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
1	OFFICE OF NAVAL TECHLGY ATTN ONT 213 D SIEGEL 800 N QUINCY ST ARLINGTON VA 22217-5000
1	COMMANDER NAVAL SURFACE WARFARE CTR ATTN CODE 730 SILVER SPRING MD 20903-5000
1	COMMANDER NAVAL SURFACE WARFARE CTR ATTN CODE R 13 R BERNECKER SILVER SPRING MD 20903-5000
7	COMMANDER NAVAL SURFACE WARFARE CTR ATTN T C SMITH K RICE S MITCHELL S PETERS J CONSAGA C GOTZMER TECH LIB INDIAN HEAD MD 20640-5000
1	COMMANDER NAVAL SURFACE WARFARE CTR ATTN CODE G30 GUNS & MUNITIONS DIV DAHLGREN VA 22448-5000
1	COMMANDER NAVAL SURFACE WARFARE CTR ATTN CODE G32 GUNS SYSTEMS DIV DAHLGREN VA 22448-5000
1	COMMANDER NAVAL SURFACE WARFARE CTR ATTN CODE G33 T DORAN DAHLGREN VA 22448-5000
1	COMMANDER NAVAL SURFACE WARFARE CTR ATTN CODE E23 TECH LIB DAHLGREN VA 22448-5000
2	COMMANDER NAVAL SURFACE WARFARE CTR ATTN CODE G33 DAHLGREN DIV DAHLGREN VA 22448

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
1	COMMANDER NAVAL SURFACE WARFARE CTR ATTN JOSEPH H FRANCIS CODE G30 DAHLGREN VA 22448
1	COMMANDER NAVAL SURFACE WARFARE CTR ATTN JOHN FRAYSSE CODE G33 DAHLGREN VA 22448
1	COMMANDER NAVAL SURFACE WARFARE CTR ATTN MARY E LACY CODE D4 17320 DAHLGREN RD DAHLGREN VA 22448
2	COMMANDER NAVAL AIR WARFARE CTR ATTN CODE 388 C F PRICE T BOGGS CHINA LAKE CA 93555-6001
2	COMMANDER NAVAL AIR WARFARE CTR ATTN CODE 3895 T PARR R DERR CHINA LAKE CA 93555-6001
1	COMMANDER NAVAL AIR WARFARE CTR INFORMATION SCIENCE DIV CHINA LAKE CA 93555-6001
1	OFFICE OF NAVAL RESEARCH ATTN YAPA RAJAPAKSE MECH DIV CODE 1132SM ARLINGTON VA 22217
1	NAVAL ORDNANCE STATION ATTN D HOLMES CODE 2011 ADVANCED SYS TECH BR LOUISVILLE KY 40214-5245
2	DAVID TAYLOR RESEARCH CTR ATTN R ROCKWELL W PHYLLAIER BETHESDA MD 20054-5000

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
1	EXPED WARF DIV N85 ATTN DR FRANK SHOUP 2000 NAVY PENTAGON WASHINGTON DC 20350-2000
1	OFFICE OF NAVAL RESEARCH ATTN MR DAVID SIEGEL 351 800 N QUINCY ST ARLINGTON VA 22217-5660
1	COMMANDER NAVAL SEA SYSTEMS CMD ATTN D LIESE 2531 JEFFERSON DAVIS HWY ARLINGTON VA 22242-5160
1	SDIO TNI PENTAGON ATTN L H CAVENY WASHINGTON DC 20301-7100
1	SDIO DA PENTAGON ATTN E GERRY WASHINGTON DC 21301-7100
2	HQ DNA ATTN D LEWIS A FAHEY 6801 TELEGRAPH RD ALEXANDRIA VA 22310-3398
2	CPIA JHU ATTN H J HOFFMAN T CHRISTIAN 10630 LITTLE PATUXENT PWY STE 202 COLUMBIA MD 21044-3200
2	NASA LANGLEY RESEARCH CTR ATTN AMSRL VS W ELBER F BARTLETT JR MS 266 HAMPTON VA 23681-0001
1	DEFENSE NUCLEAR AGENCY ATTN DR R ROHR INNOVATIVE CONCEPTS DIV 6801 TELEGRAPH RD ALEXANDRIA VA 22310-3398

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
1	DEFENSE NUCLEAR AGENCY ATTN LTC JYUJI D HEWITT INNOVATIVE CONCEPTS DIV 6801 TELEGRAPH RD ALEXANDRIA VA 22310-3398
1	DIRECTOR SANDIA NATL LABS ATTN M BAER DEPARTMENT 1512 PO BOX 5800 ALBUQUERQUE NM 87185
1	DIRECTOR SANDIA NATL LABS ATTN R CARLING COMBUSTION RSRCH FACILITY LIVERMORE CA 94551-0469
1	DIRECTOR SANDIA NATL LABS ATTN 8741 G A BENEDITTI PO BOX 969 LIVERMORE CA 94551-0969
2	DIRECTOR LAWRENCE LIVERMORE NATL LABS ATTN L 355 A BUCKINGHAM M FINGER PO BOX 808 LIVERMORE CA 94550-0622
1	DIRECTOR LOS ALAMOS NATL LAB ATTN T3 D BUTLER PO BOX 1663 LOS ALAMOS NM 87544
1	DIRECTOR LOS ALAMOS NATL LAB ATTN M DIVISION B CRAIG PO BOX 1663 LOS ALAMOS NM 87544
1	GENERAL APPLIED SCIENCES LAB ATTN J ERDOS 77 RAYNOR AVE RONKONKAMA NY 11779-6649

NO. OF
COPIES ORGANIZATION

1 DIRECTOR
LOS ALAMOS NATL LAB
ATTN D RABERN
MEE 13 MS J 576
PO BOX 1633
LOS ALAMOS NM 87545

1 THE UNIV OF AUSTIN TEXAS
ATTN T M KIEHNE
INSTITUTE FOR ADVANCED TECHLGY
4030 2 W BRAKER LAND
AUSTIN TX 78759-5329

4 PENNSYLVANIA STATE UNIV
ATTN V YANG
K KUO
C MERKLE
G SETTLES
DEPT OF MECHANICAL ENGRG
UNIVERSITY PARK PA 16802-7501

1 PRINCETON COMBUSTION RSRCH LABS INC
ATTN N A MESSINA
PRINCETON CORPORATE PLAZA
11 DEERPARK DR BLDG IV SUITE 119
MONMOUTH JUNCTION NJ 08852

1 RENSSELAER POLYTECH INST
ATTN R B PIPES
PRES OFC PITTSBURGH BLDG
TROY NY 12180-3590

2 BATTELLE
ATTN TWSTIAC
V LEVIN
505 KING AVE
COLUMBUS OH 43201-2693

1 BATTELLE PNL
ATTN MR MARK GARNICH
PO BOX 999
RICHLAND WA 99352

1 BATTELLE
ATTN C R HARGREAVES
505 KING AVE
COLUMBUS OH 43201-2681

1 BATTELLE PNL
ATTN M SMITH
PO BOX 999
RICHLAND WA 99352

NO. OF
COPIES ORGANIZATION

1 AFELM THE RAND CORP
ATTN LIBRARY D
1700 MAIN ST
SANTA MONICA CA 90401-3297

2 AAI CORPORATION
ATTN J FRANKLE
D CLEVELAND
PO BOX 126
HUNT VALLEY MD 21030-0126

8 ALLIANT TECHSYSTEMS INC
ATTN R E TOMPKINS
J KENNEDY
J BODE
C CANDLAND
L OSGOOD
R BURETTA
R BECKER
M SWENSON
600 SECOND ST NE
HOPKINS MN 55343

4 ALLIANT TECHSYSTEMS INC
ATTN H HULS
R JOHNSON
T ROCKNE
W DAVIS
7225 NORTHLAND DR
BROOKLYN PK MN 55428

1 GENERAL ELECTRIC COMPANY
ATTN J MANDZY
TACTICAL SYSTEM DEPT
100 PLASTICS AVE
PITTSFIELD MA 01201-3698

1 LOCKHEED MARTIN
ATTN JIM TALLEY
ROOM 1309
LAKESIDE AVE
BURLINGTON VT 05401

1 OLIN ORDNANCE
ATTN A SAITTA
10101 9TH ST NORTH
ST PETERSBURG FL 33716

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
3	OLIN ORDNANCE ATTN E J KIRSCHKE A F GONZALEZ D W WORTHINGTON PO BOX 222 ST MARKS FL 32355-0222
1	OLIN ORDNANCE ATTN H A MCELROY 10101 9TH ST NORTH ST PETERSBURG FL 33716
1	PHYSICS INTRNATL LIBRARY ATTN H WAYNE WAMPLER PO BOX 5010 SAN LEANDRO CA 94577-0599
3	ROCKWELL INTRNTL ATTN BA08 J FLANAGAN J GRAY R B EDELMAN ROCKETDYNE DIV 6633 CANOGA AVE CANOGA PARK CA 91303-2703
2	ROCKWELL INTRNTL SCIENCE CTR ATTN DR S CHAKRAVARTHY DR S PALANISWAMY 1049 CAMINO DOS RIOS PO BOX 1085 THOUSAND OAKS CA 91360
1	SAIC ATTN M PALMER 2109 AIR PARK RD ALBUQUERQUE NM 87106
1	SOUTHWEST RSRCH INSTITUTE ATTN J P RIEGEL 6220 CULEBRA RD PO DRAWER 28510 SAN ANTONIO TX 78228-0510
3	THIOKOL CORPORATION ATTN R WILLER R BIDDLE TECH LIB ELKTON DIVISION PO BOX 241 ELKTON MD 21921-0241

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
4	VERITAY TECHLGY INC ATTN E B FISHER A CRICKENBERGER J BARNES J Z TALLEY PO BOX 305 4845 MILLERSPORT HWY EAST AMHERST NY 14501-0305
1	UNIVERSAL PROPULSION COMPANY ATTN H J MCSPADDEN 25401 NORTH CENTRAL AVE PHOENIX AZ 85027-7837
1	SRI INTERNATIONAL ATTN TECH LIB PROPULSION SCIENCES DIV 333 RAVENWOOD AVE MENLO PARK CA 94025-3493
1	CHAMBERLAIN MANUF CORP ATTN M TOWNSEND RSCH & DEV DIV PO BOX 2545 550 ESTHER ST WATERLOO IA 50704
1	GENERAL DYNAMICS ATTN D BARTLE LAND SYSTEMS DIVISION PO BOX 1901 WARREN MI 48090
1	PM ADVANCED CONCEPTS ATTN R TAYLOR LORAL VOUGHT SYSTEMS PO BOX 650003 MS WT 21 DALLAS TX 76265-0003
2	LORAL VOUGHT SYSTEMS ATTN G JACKSON K COOK 1701 W MARSHALL DR GRAND PRAIRIE TX 75051
2	UNITED DEFENSE LP ATTN P PARA G THOMAS 1107 COLEMAN AVE BOX 367 SAN JOSE CA 95103

NO. OF
COPIES ORGANIZATION

ABERDEEN PROVING GROUND

- 3 DIR USAMSAA
ATTN AMXSY GA
W BROOKS
B SIEGEL
AMXSY RA
C HEATWOLD
- 2 CDR USA TECOM
ATTN AMSTE SI F
AMSTE TA R
- 4 DIR USA ATC
ATTN STECS CC PC P DURKIN
STECS LI S
STECS AS
STECS AS H
- 5 DIR USARL
ATTN AMSRL WT P
A HORST 390A
AMSRL WT PD
T ERLINE 390
D HOPKINS 390
S WILKERSON 390
AMSRL WT WB
F BRANDON 120

INTENTIONALLY LEFT BLANK.

USER EVALUATION SHEET/CHANGE OF ADDRESS

This Laboratory undertakes a continuing effort to improve the quality of the reports it publishes. Your comments/answers to the items/questions below will aid us in our efforts.

1. ARL Report Number/Author ARL-MR-315 (Bundy) Date of Report June 1996
2. Date Report Received _____
3. Does this report satisfy a need? (Comment on purpose, related project, or other area of interest for which the report will be used.) _____

4. Specifically, how is the report being used? (Information source, design data, procedure, source of ideas, etc.) _____

5. Has the information in this report led to any quantitative savings as far as man-hours or dollars saved, operating costs avoided, or efficiencies achieved, etc? If so, please elaborate. _____

6. General Comments. What do you think should be changed to improve future reports? (Indicate changes to organization, technical content, format, etc.) _____

CURRENT
ADDRESS

Organization

Name

Street or P.O. Box No.

City, State, Zip Code

7. If indicating a Change of Address or Address Correction, please provide the Current or Correct address above and the Old or Incorrect address below.

OLD
ADDRESS

Organization

Name

Street or P.O. Box No.

City, State, Zip Code

(Remove this sheet, fold as indicated, tape closed, and mail.)
(DO NOT STAPLE)


DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO 0001,APG,MD

POSTAGE WILL BE PAID BY ADDRESSEE

**DIRECTOR
U.S. ARMY RESEARCH LABORATORY
ATTN: AMSRL-WT-PB
ABERDEEN PROVING GROUND, MD 21005-5066**



**NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES**

