

ARMY RESEARCH LABORATORY



Staged Ram Accelerator Experiments With Unique Projectile Geometries

D. Kruczynski
F. Liberatore
J. Hewitt
J. Tuerk

ARL-TR-1219

October 1996

19961101 021

DTIC QUALITY INSPECTED 4

APPROVED FOR PUBLIC RELEASE; DISTRIBUTION IS UNLIMITED.

NOTICES

Destroy this report when it is no longer needed. DO NOT return it to the originator.

Additional copies of this report may be obtained from the National Technical Information Service, U.S. Department of Commerce, 5285 Port Royal Road, Springfield, VA 22161.

The findings of this report are not to be construed as an official Department of the Army position, unless so designated by other authorized documents.

The use of trade names or manufacturers' names in this report does not constitute indorsement of any commercial product.

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188	
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project(0704-0188), Washington, DC 20503.				
1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE October 1996		3. REPORT TYPE AND DATES COVERED Final, Mar 95 - Feb 96
4. TITLE AND SUBTITLE Staged Ram Accelerator Experiments With Unique Projectile Geometries			5. FUNDING NUMBERS PR: 1L162618AH80	
6. AUTHOR(S) D. Kruczynski, F. Liberatore, J. Hewitt, and J. Tuerk				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army Research Laboratory ATTN: AMSRL-WT-PA Aberdeen Proving Ground, MD 21005-5066			8. PERFORMING ORGANIZATION REPORT NUMBER ARL-TR-1219	
9. SPONSORING/MONITORING AGENCY NAMES(S) AND ADDRESS(ES)			10. SPONSORING/MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES				
12a. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution is unlimited.			12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) First experiments using multiple propellant stages and unique projectile geometries in the U.S. Army Research Laboratory (ARL) ram accelerator are reported. New criteria for comparative analysis of experiments based on both total heat release and heat release rate are introduced and evaluated relative to these experiments. Finally, experimental data indicating that projectile material can influence the desired experiments through burning and heat release are presented.				
14. SUBJECT TERMS ram accelerator, multistage, hypervelocity gun, subsonic combustion, supersonic combustion			15. NUMBER OF PAGES 17	
			16. PRICE CODE	
17. SECURITY CLASSIFICATION OF THIS REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT UL	

INTENTIONALLY LEFT BLANK.

ACKNOWLEDGMENTS

The authors wish to thank Mr. Michael Nusca for critical insights provided by his companion CFD research; Mr. Robert Hall for continued experimental support; and Mr. Albert Horst and Dr. Thomas Minor for continued technical and programmatic support.

INTENTIONALLY LEFT BLANK.

TABLE OF CONTENTS

	<u>Page</u>
ACKNOWLEDGMENTS	iii
LIST OF FIGURES	v
LIST OF TABLES	v
1. INTRODUCTION	1
2. FACILITY	1
2.1 Accelerator and Injection Gun	1
2.2 Gas Handling and Mixing	2
3. STAGING EXPERIMENTS - RATIONALE, RANKING CRITERIA, AND TEST MATRIX	3
4. EXPERIMENTAL RESULTS	5
5. ANALYSIS	6
6. CONCLUSIONS	6
7. REFERENCES	7
DISTRIBUTION LIST	9

INTENTIONALLY LEFT BLANK.

LIST OF FIGURES

<u>Figure</u>	<u>Page</u>
1. ARL ram accelerator with one accelerator tube	1
2. 120-mm standard ram projectile	4
3. Velocity vs. travel	5

LIST OF TABLES

<u>Table</u>	<u>Page</u>
1. Analysis of Propellant Mixtures Taken at Different Locations in the Accelerator Tubes	2
2. Measurement of Propellant Mixtures Over Time	3
3. Comparison of Propellant Properties	4

INTENTIONALLY LEFT BLANK.

1. INTRODUCTION

Ram acceleration is initiated by injection of a projectile, similar in shape to the center body of a ramjet engine, into a tube filled with a combustible gaseous fuel/oxidizer/diluent, or simply propellant. As the subcaliber projectile and obturator enter the propellant at supersonic speeds, shock and viscous heating occurs. This heating ignites and sustains combustion on the aft section and behind the projectile. This energy release occurs continuously as the projectile accelerates. It is often useful to adjust the propellant composition down the length of the accelerator tube to ensure high efficiency of combustion in accelerating the projectile. In practice, this is accomplished by segmenting the accelerator tube with thin plastic diaphragms to separate the propellants. The fuel's components may be changed such that its properties (i.e. sound speed and chemical energy) are adjusted to maximize projectile acceleration (Knowlen, Bruckner, and Hertzberg 1992). The use of multiple fuels by segmenting the accelerator is often referred to as "staging" the accelerator.

The U.S. Army Research Laboratory (ARL) has been exploring in-bore ram acceleration as a technique to obtain hypervelocities with useful (5-10 kg) projectile masses. The research has consisted of an integrated program of experiment and computational modeling. Past research has investigated scaling and pressure effects and flow visualization (Kruczynski 1992; Kruczynski 1993a; Kruczynski 1993b). Current research is ongoing in the areas of projectile geometry and staging effects.

2. FACILITY

2.1 Accelerator and Injection Gun. The ARL facility was created by removing the breeches of 120-mm M256 tank guns and mating the tubes. Each accelerator section (tube) is 4.7 m long. Currently, three accelerator tubes are available for a total combined accelerator length of 14.1 m. The accelerator tubes may be segmented with PVC diaphragms and filled with different propellant gases or used without diaphragms for longer runs with single propellant mixtures. The projectile is brought up to injection speed (typically 1,200 m/s) using a conventional 120-mm tank gun and a solid propellant. Projectile transition to the first accelerator tube is made through a vented tube section. This section serves to both decouple the conventional gun recoil (through a sliding interface) and vent solid propellant gases to minimize interference with the ram acceleration process. Figure 1 shows the layout of the facility.




Figure 1. ARL ram accelerator with one accelerator tube.

2.2 Gas Handling and Mixing. A bank of gas storage bottles supplies the required gases. It should be noted that ram acceleration propellant components are readily available at bottled gas dealers in standard highway transportable storage bottles. The ARL facility also includes a compressor capable of charging the accelerator to 340 atm. Recent additions to the facility include a premix station and online gas chromatography for analyzing the propellant mixtures used. The premix station was installed to avoid any ambiguity about the content and homogeneity of the propellant and is particularly useful for multistage firings since the gas mixtures may be mixed, tested, and adjusted in advance.

Prior to installation of the premix station, the accelerator tubes in the ARL facility were directly filled with the desired propellant by partial pressure methods. Samples taken from the accelerator before firing (but analyzed days later) indicated that, in general, the actual propellant mixtures were in reasonable agreement with intended mixtures. However, it was suspected that the propellant mixture was not homogeneously mixed prior to firing (it was thought that mixing was being completed in the small sample bottles). When the portable gas chromatography (GC) system was installed, these suspicions were confirmed. Table 1 shows data from a two-accelerator tube shot in which the same mixture was simultaneously pumped into both tubes. Samples from both accelerator tubes were then taken and analyzed immediately after filling (about 10 min apart).

Table 1. Analysis of Propellant Mixtures Taken at Different Locations in the Accelerator Tubes

Shot/Stage and Fill Pressure	Mixture Component and Order of Fill	Desired Volume % (both stages)	GC* Analysis of Stage 1	GC Analysis of Stage 2
26/1 & 2 at 57 atm	CH ₄	20	15	22
	O ₂	13	15	14
	N ₂	67	70	64
* GC is gas chromatography.				

Table 1 shows a considerable discrepancy between the two samples.

The premix station consists of a bank of standard 44-liter gas bottles (initially mounted vertically), which are remotely filled from the individual source gases many hours (or days) before firing. Using the on-line GC, the banks of bottles may be sampled at any time and their contents adjusted if necessary. Analysis of the premixed gases over extended periods of time revealed that, in general, 48 hr or longer is required to ensure the gases have "completely" mixed by diffusion and residual turbulence from the filling process. This can be seen in the samples taken from the first stage mixture of shots 34 and 35 shown in Table 2. In the future, experiments with horizontally mounted bottles will be undertaken to reduce mixing times further.

When the propellant mixture appears to be within reasonable agreement with the desired mixture, it is ready to be pumped to the accelerator tube for firing. In addition, if desired, multiple shots may be made from the same premixed batch of propellant, ensuring repeatability. To date, no safety problems have been encountered handling these premixed, typically fuel rich, propellants.

Table 2. Measurement of Propellant Mixtures Over Time

Shot/Stage Number and Mixture Pressure	Mixture Component*	Desired Volume Percent in Mixture	**GC Result After 20 hr	GC Result After 48 hr	GC Result After 68 hr	GC Result After 140 hr	GC Result After 204 hr
34/1 at 81 atm	CH ₄	20	45	--	17	17	--
	O ₂	13	9	--	14	14	--
	N ₂	67	46	--	69	69	--
35/1 at 81 atm	CH ₄	20	--	17	--	--	17
	O ₂	13	--	14	--	--	14
	N ₂	67	--	69	--	--	69

* Mixtures were filled in nine steps using one-third of each gas in each step.
 **GC is gas chromatography.

3. STAGING EXPERIMENTS - RATIONALE, RANKING CRITERIA, AND TEST MATRIX

It has been well documented (Knowlen, Bruckner, Hertzberg 1992) that peak performance for a ram accelerator, operating below the Chapman-Jouget detonation speed, is obtained when the total heat release of the propellant (typically defined as $\frac{\Delta q}{C_p T}$) is kept as high as possible and the projectile's relative Mach number as low as possible. However care must be exercised so that the flow neither gas-dynamically chokes (becomes sonic) at the projectile's throat (area of minimum clearance between projectile body and the tube wall) nor discharges a normal shock through the throat from behind, during excessive heat addition (an unstart). Finding the optimum conditions may be dependent on the scale and design of the projectile. In addition, the conditions during initial projectile injection into the accelerator from the injector gun (obturator discard, etc.) may require that the initial propellant be characterized by lower heat release than propellant for "steady" operation (Kruczynski, Liberatore, Kiwan 1993).

ARL has only recently expanded its facility to the point where the "optimum" conditions for efficient operation (after the initial startup) are being explored. Due to the relatively high cost of experimental operation at 120-mm bore size, great care is taken in designing new experimental firing sequences in order to maximize the insights gained from each firing. In the case of the firings reported in this report, a qualitative ranking system was used to screen experiments. The ranking system is based on three simple comparative factors for analyzing the experimental potential of a shot. The first two factors, available heat release $\frac{\Delta q}{C_p T}$ and projectile Mach number (relative to the propellant), were briefly discussed previously and are further detailed in Knowlen, Bruckner, and Hertzberg (1992).

The third factor is the rate at which heat is released, as calculated using a methane/air combustion mechanism developed by the Gas Research Institute consisting of 32 species and 176 reactions. This mechanism is used in conjunction with the SENKIN kinetics code run at constant pressure with an initial temperature derived from previous computational fluid dynamics (CFD) runs. Further details on the use of this method are available in Nusca (1995). Using large kinetics mechanisms in CFD calculations results in prohibitively long computer run times. Therefore, kinetics codes such as SENKIN should provide information for screening new fuel mixtures and making comparative analyses, reducing the need for additional CFD calculations.

The first shot in the staging experiments (shot 34) was designed to evaluate the potential for operating the 120-mm ram accelerator at elevated (relative to the starting stage) heat release values. The second and

third accelerator tubes were filled with the more energetic mixture. No attempt was made in this experiment to adjust sound speed of the mixture. Since this shot was successful, it became the baseline for comparison with subsequent shots. Note that in all the shots in this series, the initial stage of the ram accelerator contained nominally the same propellant which has shown excellent repeatability in previous ARL experiments (Kruczynski 1992; Kruczynski 1993a; Kruczynski 1993b). The second and third firings of the series were designed to maximize acceleration by raising the heat release and sound speed of the propellant. This would allow both "high" $\frac{\Delta q}{C_p T}$ and low Mach number operation. The final shot of the series was made with the same propellant as in shot 34; however, both the projectile design and materials were different. This projectile contained a short constant diameter section (92 mm long) between the nose and aft sections. This "isolator" design was evaluated for its potential in preventing unstarts and is fully reported in Kruczynski and Liberatore (1995). A drawing of the "standard" projectile is seen in Figure 2. Table 3 summarizes properties for these experiments. Note that the total heat release values ($Q/C_p T$) were equal to or less than that of shot 34, in subsequent shots, while the release times for the shots after shot 34 were approximately equal or longer than the baseline shot 34.




Figure 2. 120-mm standard ram projectile.

Table 3. Comparison of Propellant Properties

Shot No.	Stage 1 - Propellant Properties (1Tube)			Stage 2 - Propellant Properties (2 tubes)			Notes
	Q/c _p T	Release ² Time (ms)	Entrance Mach No.	Q/c _p T	Release Time (ms)	Entrance Mach No.	
34	3.7	0.54	3.3	5.23	0.34	3.7	Standard Projectile
Moles ¹	2.5 CH ₄ + 2.0 O ₂ + 9.9N ₂			2.4 CH ₄ + 2.0 O ₂ + 5.8 N ₂			
35	3.7	0.54	3.3	3.95	0.41	3.1	Very Slight Mod ³
Moles	2.5 CH ₄ + 2.0 O ₂ + 9.9 N ₂			2.9 CH ₄ + 2.0 O ₂ + 3.5 N ₂ + 4.1 He			
36	3.49	0.51	3.4	3.99	0.38	2.9	Standard Projectile
Moles	2.8 CH ₄ + 2.0 O ₂ + 9.6 N ₂			5.0 CH ₄ + 2.0 O ₂ + 4.0 He			
37	3.71	0.50	3.4	4.33	0.36	3.93	Proj. With Isolator ⁴
Moles	2.6 CH ₄ + 2.0 O ₂ + 9.0 N ₂			2.7 CH ₄ + 2.0 O ₂ + 6.3 N ₂			

¹Molar content gas chromatography analysis

²Approximate time to maximum energy release at given temperature (1,350 K) and constant pressure (further details on the use of this method are available in Nusca)

³Small backward facing steps behind throat between fins (see Kruczynski and Liberatore)

⁴See projectile description above

4. EXPERIMENTAL RESULTS

The first shot of the series (34) exhibited successful ram acceleration in all three accelerator tubes. Photos of the projectile in flight after exit showed no damage. This shot then became the "standard" against which the succeeding tests were compared.

Shot 35 successfully accelerated through the first tube but unstarted (combustion moved forward and past the projectile midbody) 2.355 m into the stage two propellant mixture. The projectile's image was captured in-flight at exit from the last accelerator tube. The projectile appeared to be completely intact; this ruled out any question of projectile mechanical failure causing the unstart. The very slight modifications to the projectile noted in Table 3 above did not appear to be involved in the unstart based on its performance in the successful run of the first accelerator stage. Note that the unstart occurred even though the propellant mixtures in accelerator tubes two and three had equal or lower $\frac{\Delta q}{C_p T}$ values and longer release times than the previous shot.

Shot 36 successfully accelerated through the first stage mixture but again unstarted about halfway into the stage two propellant mixture. Again, an image of the projectile after exit from the accelerators revealed no structural damage. Note that this projectile design was identical to that of shot 34 and the fuels in accelerator tubes two and three again had lower $\frac{\Delta q}{C_p T}$ and longer release times.

Shot 37 used a significantly different projectile geometry and was fired primarily to evaluate the performance of projectiles with constant diameter sections (isolators) in ram accelerators. To make direct comparisons with previous "standard" projectiles, the mid and aft sections were made from a high-strength magnesium alloy (ZK-60) to reduce total projectile mass to that of the "standard" projectile design. The nose section was aluminum with a stainless steel tip like the other shots (see Figure 2). Again the projectile had successful ram acceleration in the first stage. Like the previous two shots, it unstarted (violently) in the middle of the second accelerator. This occurred even though the fuel mixture was the same as that of shot 34 which operated successfully throughout. There was very strong photographic and material evidence that the projectile was burning in the second stage of the accelerator. A photo of the projectile after exit was not obtained because extreme light emission overexposed the film. Residue from burning magnesium was scattered throughout the accelerator. The reason this test is included in this report, which is concerned primarily with kinetics and staging effects, is because projectile material burning obviously contributed to the heat addition of the ram cycle and sparked a separate study (Liberatore 1995) looking into the effects on propellant kinetics of the projectile's material. This is discussed further in the next section.

A plot of velocity vs. travel for the four cases previously mentioned may be seen in Figure 3.




Figure 3. Velocity vs. travel.

5. ANALYSIS

Gas dynamic unstarts occurred in both attempts to raise the propellant's sound speed (by adding He), even though other calculated properties, such as total heat release and release times, were lower (or equal) and longer respectively for these experiments. Since the heat content value $\frac{\Delta q}{C_p T}$ has been used and validated extensively as an experimental parameter, it was decided to re-examine the assumption used in calculating the "heat release time." The first and perhaps most important consideration for these calculations is the temperature selected to begin the combustion calculation. For the cases reported to date, an "average" temperature in the boundary layer behind the initial bow and reflected shocks, over an average range of expected projectile Mach numbers, was used. The calculations used in setting these conditions were from previous shots in the ARL first stage "standard" fuel. The initial temperature was set at 1,350 K.

Following the unstarts of shots 35 and 36, it was decided to examine the CFD calculations of the flow of shot 36 to assess an "average temperature" using a similar method to that described previously. It was found that despite the projectile's lower Mach number in the helium mixtures, the average temperature in the flow was about 50 K higher. It is believed that the lower heat capacity of atomic species, in this case helium (with three energy degrees of freedom) as compared to that of diatomic nitrogen (five energy degrees of freedom) may account for this difference. When the "heat release rate" calculations were redone starting at 1,400 K, the release time was found to be shorter than that for the nitrogen diluted mixtures. The new release times for shots 35 and 36 were calculated to average 0.24 ms. When compared to the previously calculated average of 0.40 ms at 1,350 K it appears that relatively minor temperature changes can make a considerable difference in the kinetic calculations. Therefore, the initial conditions for such calculations must be considered carefully.

As noted earlier, the magnesium projectile (shot 37) did burn and may have contributed significantly to the projectile unstart through this unplanned and excessive heat release. Indeed there is some evidence from the photographs of the aluminum projectiles, which survived unstarts (shots 35 and 36), that there may also be some burning around the projectile's base, although this is not conclusive at this time. It is known that aluminum projectiles are failing and perhaps burning at higher Mach numbers (Patz et al. 1995). If the projectiles do burn, they will have a significant effect on the amount of energy being released around the projectile. This could be responsible for some unexplained unstarts. A study of this potential was done at ARL and is reported separately (Liberatore 1995).

6. CONCLUSIONS

A comparative method of screening new ram accelerator propellant mixtures, incorporating both total heat release and heat release times, has been suggested. Experiments and subsequent analysis revealed that care must be taken in determining the initial conditions for these calculations.

A projectile design, which incorporates a constant diameter mid-section, has been successfully fired through the rigorous starting phase of a ram accelerator.

Finally, experiments reveal that burning projectile material may produce unstarts through unplanned energy release.

8. REFERENCES

Knowlen, C., A. P. Bruckner, and A. Hertzberg. "Internal Ballistics of the Ram Accelerator" Proceedings of the 13th International Symposium on Ballistics, Stockholm, Sweden, 1-3 June 1992.

Kruczynski, D. "Experimental Demonstration of a 120-mm Ram Accelerator" 29th JANNAF Combustion Meeting, CPIA 593, vol. 1, Oct. 1992, pp. 235-244.

Kruczynski, D. "New Experiments in a 120-mm Ram Accelerator at High Pressures" AIAA Paper 91-2589, AIAA/SAE/ASME/ASEE 29th Joint Propulsion Conference, Monterey, CA, 28-30 June 1993a.

Kruczynski, D., and F. Liberatore. "Ram Acceleration Experiments with Unique Projectile Geometries" AIAA Paper 95-2490, AIAA/SAE/ASME/ASEE 31st Joint Propulsion Conference, San Diego, CA, 10-12 July 1995.

Kruczynski, D., F. Liberatore, and M. Kiwan. "Flow Visualization of Steady and Transient Combustion in a 120-mm Ram Accelerator" AIAA Paper 94-3344, AIAA/SAE/ASME/ASEE 30th Joint Propulsion Conference, Indianapolis, IN, 27-29 June 1993b.

Liberatore, F. "The Effects of Real Material Behavior on Ram Accelerator Performance" Second International Workshop on Ram Accelerators, Seattle, Washington, 17-20 July 1995.

Nusca, M. "Reacting Flow Simulation of Transient Multi-Stage Ram Accelerator Operation and Design Studies" Second International Workshop on Ram Accelerators, Seattle, Washington, 17-20 July 1995.

Patz, G., F. Seiler, G. Smeets, and J. Srulijes. "Status of ISL's RAMAC 30 with Fin Guided Projectiles Accelerated in a Smooth Bore" Second International Workshop on Ram Accelerators, Seattle Washington, 17-20 July 1995.

INTENTIONALLY LEFT BLANK.

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
2	DEFENSE TECHNICAL INFO CTR ATTN DTIC DDA 8725 JOHN J KINGMAN RD STE 0944 FT BELVOIR VA 22060-6218

1	DIRECTOR US ARMY RESEARCH LAB ATTN AMSRL OP SD TA 2800 POWDER MILL RD ADELPHI MD 20783-1145
---	---

3	DIRECTOR US ARMY RESEARCH LAB ATTN AMSRL OP SD TL 2800 POWDER MILL RD ADELPHI MD 20783-1145
---	---

1	DIRECTOR US ARMY RESEARCH LAB ATTN AMSRL OP SD TP 2800 POWDER MILL RD ADELPHI MD 20783-1145
---	---

ABERDEEN PROVING GROUND

5	DIR USARL ATTN AMSRL OP AP L (305)
---	---------------------------------------

NO. OF
COPIES ORGANIZATION

1 HEADQUARTERS
USA MATERIEL CMD
ATTN AMCICP AD
M FISETTE
5001 EISENHOWER AVE
ALEXANDRIA VA 22333-0001

1 USA BALLISTIC MIS DEFNS SYS CMD
ADV TECH CTR
PO BOX 1500
HUNTSVILLE AL 35807-3801

2 COMMANDER
USA RSRCH OFC
ATTN TECH LIB
D MANN
PO BOX 12211
RESEARCH TRIANGLE PARK NC
227709-2211

1 COMMANDER
USA CECOM
ATTN ASQNC ELC IS L R
MYER CTR R&D TECH LIB
FORT MONMOUTH NJ
07703-5301

1 USA RSRCH OFC (UK)
PSC 802 BOX 15
DR ROY E REICHENBACH
APO AE 09499-1500

2 COMMANDER
NAVAL SEA SYS CMD
ATTN SEA 62R
SEA 64
WASHINGTON DC 20362-5101

1 COMMANDER
NAVAL AIR SYS CMD
ATTN AIR 954
TECH LIB
WASHINGTON DC 20360

1 COMMANDER
NAVAL RSRCH LAB
ATTN TECH LIB
WASHINGTON DC 20375-5000

NO. OF
COPIES ORGANIZATION

4 COMMANDER
NAVAL RSRCH LAB
ATTN CODE 6410
K KAILASANATH
C LI
J BORIS
E ORAN
WASHINGTON DC 20375-5000

1 OFFICE OF NAVAL RSRCH
ATTN CODE 473
R MILLER
800 N QUINCY ST
ARLINGTON VA 22217-9999

1 OFFICE OF NAVAL TECHNOLOGY
ATTN ONT 213
D SIEGEL
800 N QUINCY ST
ARLINGTON VA 22217-5000

7 COMMANDER
NSWC
ATTN T SMITH
K RICE
S MITCHELL
S PETERS
J CONSAGA
C GOTZMER
TECH LIB
INDIAN HEAD MD 20640-5000

1 COMMANDER
NSWC
ATTN CODE G30
GUNS & MUNITIONS DIV
DAHLGREN VA 22448-5000

1 COMMANDER
NSWC
ATTN CODE G32
GUNS SYSTEMS DIV
DAHLGREN VA 22448-5000

1 COMMANDER
NSWC
ATTN CODE G33
T DORAN
DAHLGREN VA 22448-5000

NO. OF
COPIES ORGANIZATION

1 COMMANDER
NSWC
ATTN CODE E23
TECH LIB
DAHLGREN VA 22448-5000

1 COMMANDER
NSWC
ATTN CODE C23
G GRAFF
DAHLGREN VA 22448-5000

2 COMMANDER
NAWC
ATTN CODE 388
C PRICE
T BOGGS
CHINA LAKE CA 93555-6001

2 COMMANDER
NAWC
ATTN CODE 3895
T PARR
R DERR
CHINA LAKE CA 93555-6001

1 COMMANDER
NAWC
ATTN INFO SCI DIV
CHINA LAKE CA 93555-6001

1 COMMANDING OFFICER
ATTN CODE 5B331
TECH LIB
NAVAL UNDERWATER SYS CTR
NEWPORT RI 02840

1 AFOSR NA
ATTN J TISHKOFF
BOLLING AFB DC 20332-6448

1 WL MNSH
ATTN G ABATE
EGLIN AFB FL 32542-5434

1 WL POPS
ATTN B SEKAR
BLDG 18
1950 FIFTH ST
WRIGHT PATTERSON AFB OH
45433

NO. OF
COPIES ORGANIZATION

2 NASA LANGLEY RSRCH CTR
ATTN MS 408
W SCALLION
D WITCOFSKI
HAMPTON VA 23605

1 ELORET
ATTN D BOGDANOFF
MS 230 2
NASA AMES RSRCH CTR
MOFFETT FIELD CA
94035-1000

1 SDIO TNI
ATTN L CAVENY
PENTAGON
WASHINGTON DC 20301-7100

1 SDIO DA
ATTN E GERRY
PENTAGON
WASHINGTON DC 21301-7100

1 DIRECTOR
SANDIA NATL LABS
ATTN M BAER
ENERGETIC MATL & FLUID MECH
DEPT 1512
PO BOX 5800
ALBUQUERQUE NM 87185

1 DIRECTOR
SANDIA NATL LABS
ATTN R CARLING
COMBUSTION RSRCH FACILITY
LIVERMORE CA 94551-0469

1 DIRECTOR
SANDIA NATL LABS
ATTN 8741 G BENEDETTI
PO BOX 969
LIVERMORE CA 94551-0969

2 DIRECTOR
LLNL
ATTN L355
A BUCKINGHAM
M FINGER
PO BOX 808
LIVERMORE CA 94550-0622

NO. OF
COPIES ORGANIZATION

1 DIRECTOR
LOS ALAMOS SCIENTIFIC LAB
ATTN T3
D BUTLER
PO BOX 1663
LOS ALAMOS NM 87544

1 DIRECTOR
LOS ALAMOS SCIENTIFIC LAB
ATTN M DIVISION
B CRAIG
PO BOX 1663
LOS ALAMOS NM 87544

1 UNIV OF TEXAS AT AUSTIN
INST FOR ADV TECH
ATTN T KIEHNE
4030 2 W BRAKER LN
AUSTIN TX 78759-5329

1 CA INST OF TECH
ATTN L STRAND MS 125 224
JET PROPULSION LAB
4800 OAK GROVE DR
PASADENA CA 91109

2 GA INST OF TECH
SCHOOL OF AEROSPACE ENGRG
ATTN B ZIM
E PRICE
ATLANTA GA 30332

1 PENNSYLVANIA STATE UNIV
DEPT OF MECHANICAL ENGRG
ATTN K KUO
UNIVERSITY PARK PA
16802-7501

1 RENSSELAER POLYTECHNIC INST
DEPT OF MATHEMATICS
TROY NY 12181

1 STANFORD UNIVERSITY
MECHANICAL ENGRNG DEPT
ATTN R HANSON
STANFORD CA 94305-3032

NO. OF
COPIES ORGANIZATION

1 PURDUE UNIVERSITY
SCHOOL OF AERO & ASTRO
ATTN N MESSERSMITH
1282 GRISSOM HALL
WEST LAFAYETTE IN
47907-1282

1 GENERAL APPLIED SCIENCES LAB
ATTN J ERDOS
77 RAYNOR AVE
RONKONKAMA NY 11779-6649

1 FMC CORPORATION
NAVAL SYSTEMS DIVISION
ATTN A GIOVANETTI
4800 E RIVER RD
MINNEAPOLIS MN 55421

1 SAIC
ATTN M PALMER
2109 AIR PARK RD
ALBUQUERQUE NM 87106

2 VERITAY TECHNOLOGY INC
ATTN E FISHER
R TALLEY
4845 MILLERSPORT HWY
EAST AMHERST NY
14501-0305

1 ADROIT SYSTEMS INC
ATTN J HINKEY
411 108TH AVE NE
STE 1080
BELLEVUE WA 98004

1 NASA
ATTN CODE 5 11
B MCBRIDE
CLEVELAND OH 44135-3191

2 UNIVERSITY OF WASHINGTON
AERO & ENGERTICS RSRCH PRGM
ATTN A BRUCKNER
BOX 352250
SEATTLE WA 98195-2250

1 THE JOHNS HOPKINS UNIV
APPLIED PHYSICS LABORATORY
ATTN D VAN WIE
LAUREL MD 20723

NO. OF
COPIES ORGANIZATION

ABERDEEN PROVING GROUND

1 COMMANDER
 USA ATC
 ATTN: STECS-LI
 R. HENDRICKSEN

NO. OF
COPIES ORGANIZATION

- | | |
|---|--|
| 1 | ERNST-MACH-INSTITUT
ATTN: DR. R HEISER
HAUPSTRASSE 18
WEIL AM RHEIM
GERMANY |
| 1 | DEFENCE RESEARCH AGENCY,
MILITARY DIVISION
ATTN: C. WOODLEY
RARDE FORT HALSTEAD
SEVENOAKS KENT, TN14 7BP
ENGLAND |
| 1 | DEFENCE RESEARCH AGENCY
FLIGHT DYNAMIC SECTION
ATTN: CASEY PHAN
WX7e BLDG S 16
FORT HALSTEAD
SEVENOAKS KENT TN 7BP
ENGLAND |
| 1 | SCHOOL OF MECHANICAL, MATERIALS,
AND CIVIL ENGINEERING
ATTN: DR. BRYAN LAWTON
ROYAL MILITARY COLLEGE OF SCIENCE
SCHRIVANHAM, SWINDON,
WILTSHIRE SN6 8LA
ENGLAND |
| 2 | INSTITUT SAINT LOUIS
ATTN: DR. MARC GIRAUD
DR. GUNTHER SMEETS
POSTFACH 1260
7858 WEAIL AM RHEIN 1
GERMANY |
| 1 | EXPLOSIVE ORDNANCE DIVISION
ATTN: A. WILDEGGER-GAISSMAIER
DEFENCE SCIENCE AND
TECHNOLOGY ORGANIZATION
P. O. BOX 1750
SALISBURY, SOUTH AUSTRALIA, 5108 |
| 1 | ARMAMENTS DIVISION
ATTN: DR. J. LAVIGNE
DEFENCE RESEARCH
ESTABLISHMENT VALCARTIER
2459, PIE XI BVLD., NORTH
P. O. BOX 8800
COURCELETTE, QUEBEC G0A 1R0
CANADA |

NO. OF
COPIES ORGANIZATION

- | | |
|---|--|
| 1 | BALLISTIC TECHNOLOGIES
ATTN: PAVEL KRYUKOV
MOSCOW REGION B. O. 92
KALININGRAD, MOSCOW 141070
RUSSIA |
| 1 | TOHOKU UNIVERSITY
INSTITUTE FOR FLUID SCIENCE
ATTN: AKIHIRO SASOH
2-1-1 KATAHIRA, AOBA
SENDAI, 980-77
JAPAN |
| 1 | HIROSHIMA UNIVERSITY
DEPT OF MECHANICAL ENGINEERING
ATTN: XINYU CHANG
1-4-1 KAGAMIYAMA
HIGASHI-HIROSHIMA, 739
JAPAN |

USER EVALUATION SHEET/CHANGE OF ADDRESS

This Laboratory undertakes a continuing effort to improve the quality of the reports it publishes. Your comments/answers to the items/questions below will aid us in our efforts.

1. ARL Report Number/Author ARL-TR-1219 (Kruczynski) Date of Report October 1996
2. Date Report Received _____
3. Does this report satisfy a need? (Comment on purpose, related project, or other area of interest for which the report will be used.) _____

4. Specifically, how is the report being used? (Information source, design data, procedure, source of ideas, etc.) _____

5. Has the information in this report led to any quantitative savings as far as man-hours or dollars saved, operating costs avoided, or efficiencies achieved, etc? If so, please elaborate. _____

6. General Comments. What do you think should be changed to improve future reports? (Indicate changes to organization, technical content, format, etc.) _____

CURRENT
ADDRESS

Organization

Name

Street or P.O. Box No.

City, State, Zip Code

7. If indicating a Change of Address or Address Correction, please provide the Current or Correct address above and the Old or Incorrect address below.

OLD
ADDRESS

Organization

Name

Street or P.O. Box No.

City, State, Zip Code

(Remove this sheet, fold as indicated, tape closed, and mail.)
(DO NOT STAPLE)