

ARMY RESEARCH LABORATORY



Laser Ignition of Liquid Propellant XM46: Ignition of Larger Volumes

by Richard A. Beyer
and G. Phillip Reeves

ARL-TR-1292

January 1997

DEFENSE INFORMATION

Approved for public release; distribution is unlimited.

19970324 037

The findings in this report are not to be construed as an official Department of the Army position unless so designated by other authorized documents.

Citation of manufacturer's or trade names does not constitute an official endorsement or approval of the use thereof.

Destroy this report when it is no longer need. Do not return it to the originator.

Army Research Laboratory

Aberdeen Proving Ground, MD 21005-5066

ARL-TR-1292

January 1997

Laser Ignition of Liquid Propellant XM46: Ignition of Larger Volumes

Richard A. Beyer, G. Phillip Reeves
Weapons and Materials Research Directorate, ARL

Abstract

Studies of the laser ignition of the liquid gun propellant XM46 have been extended to volumes up to 30 cm³ of propellant. In the first part of this work, a multistage initiator was designed and tested, patterned after earlier electrical ignition designs. The study then proceeded to attempt direct ignition of 5 cm³ and 30 cm³ of the liquid. Although marginally successful, these studies demonstrate the difficulty of igniting these amounts starting from atmospheric pressure in open vessels.

ACKNOWLEDGMENTS

This study could not have been done without extensive discussions and encouragement from James DeSpirito and John D. Knapton, Weapons Technology Directorate, U.S. Army Research Laboratory (ARL). Funding was provided by the Office of the Project Manager, Crusader.

INTENTIONALLY LEFT BLANK.

TABLE OF CONTENTS

	<u>Page</u>
ACKNOWLEDGMENTS	iii
LIST OF FIGURES	vii
1. INTRODUCTION	1
2. APPARATUS	1
3. OBSERVATIONS	3
3.1 Three-Stage Initiator	3
3.2 5-cm ³ Chamber	5
3.3 30-cm ³ Chamber	7
4. DISCUSSION	9
5. FUTURE STUDIES	10
6. REFERENCES	11
APPENDIX: THE EFFECT OF LIQUID COMPRESSIBILITY ON PRESSURE RISE	13
DISTRIBUTION LIST	17
REPORT DOCUMENTATION PAGE	25

INTENTIONALLY LEFT BLANK.

LIST OF FIGURES

<u>Figure</u>		<u>Page</u>
1.	Schematic of first chamber of multistage initiator	2
2.	5-cm ³ test vessel	3
3.	30-cm ³ test vessel	4
4.	Pressure-time records in first stage of initiator from four consecutive shots	5
5.	Pressure-time records from initiator when two stages are ignited	5
6.	Water shot in 5-cm ³ chamber	6
7.	Water doped with graphite in 5-cm ³ chamber	6
8.	XM46 laser ignition in 5-cm ³ vessel showing depressurization resulting in (A) extinction and (B) continued burning	8
9.	XM46 ignition in 5-cm ³ vessel showing laser pulse, prompt ignition, and delayed ignition	8
10.	Pressure response during ignition of 30-cm ³ of XM46	9
A-1.	The effect of a decrease in volume of 0.3 μ l with a chamber filled with XM46	16

INTENTIONALLY LEFT BLANK.

1. INTRODUCTION

Previous reports of the laser ignition of XM46 propellant in our laboratory have documented our characterization of the basic parameters of the process (Beyer 1996) and the first attempts to extend this technique to gun igniters (Beyer, DeSpirito, and Reeves 1996). Those studies were limited to devices with volumes of 0.1 and 1.0 cm³. In the present study, the effort toward a practical device was continued with a 17-cm³ multistage "initiator" filled with a total of 5 cm³ of propellant. This device uses ignition of a small chamber and transfer to larger volumes. Difficulties with the operation of this design and its inherent complexity led to the subsequent studies of direct ignition of 5- and 30-cm³ volumes of propellant.

2. APPARATUS

Two similar neodymium:glass lasers operating at 1.054 nm with nominal output energies up to 50 J were used. Most of the studies were done with a pulse length of 0.9 ms (10% points); the tests shown for the 30-cm³ chamber were performed using the 0.5-ms pulse length laser. We have not observed a major difference in the ignition behavior with these two lasers. However, with these energies and pulse lengths, operation is close to the damage threshold for the sapphire windows, so the longer pulse is generally preferred.

For the initiator studies, which were an extension of the work reported earlier (Beyer, DeSpirito, and Reeves 1996), the laser energy input was through an optical fiber. The fibers used were either of 1.0-mm or 1.5-mm core diameter. As was mentioned in that earlier report, an effort remains necessary to make fibers useful for this application. Connector lifetimes and survival of the fiber optic in the chamber during the transient ignition event are the main limitations. No connectors were used for these tests, and the fibers into the chambers were replaced after five tests or more frequently. For these reasons, the follow-on studies were done mostly with sapphire windows. However, sapphire is subject to absorption from nonlinear optical processes (not purity related) and is easily damaged by the lasers in use here. Window damage was usually avoided if the spot size entering the window was at least 3 mm in diameter and the window was kept meticulously clean. The latter requirement is not always easily achieved in a range area. In most cases, the laser energy was focused to a spot inside the propellant. While XM46 has no measurable absorption at the laser wavelength (Marrs 1993), we have demonstrated that there is a nonlinear absorption with the present lasers when focused. In a limited number of cases, with either a

solid graphite target or a suspension of powdered graphite in the propellant, a quasi-parallel beam of approximately 3-mm diameter was used. While no dramatic differences were seen, the dependence on energy density was not explored in these experiments.

The multistage initiator device was modeled after the comparable two-stage component of the electrical ignition fixture designed by Martin Marietta Defense Systems (Hanson 1993). It has three chambers of increasing volume, 0.1 cm^3 , 1.54 cm^3 , and 16.1 cm^3 , respectively. Each chamber vents tangentially into the next larger chamber. The smallest chamber is a 0.63-cm-diameter (0.25 in) cylinder of the same length. It is shown schematically in Figure 1. The light from the fiber optic enters the curved wall opposite the graphite target. One end of this chamber has a confinement/vent orifice diameter of 0.9 mm, about 1.5 mm long. Made of tantalum, it showed no evidence of wear after more than 30 shots. The face of a Kistler 607C pressure gauge formed the opposite end wall of this chamber.




Figure 1. Schematic of first chamber of multistage initiator.

The second chamber was a cylinder 1.27 cm in diameter (0.5 in) and 0.79 cm (0.313 in) long with a 1.27-cm-diameter (0.5 in) hemisphere at the output end. The vent of this chamber was 3.2 mm in diameter (0.125 in) and 1.9 cm (0.75 in) long. As designed, the first two chambers were to be completely filled by injection of the propellant into the smaller chamber. The large chamber, which was never tested, was to have a lower loading density, with a fill of less than 5 cm^3 of propellant anticipated.

The first of the vessels designed to explore the direct ignition of larger volumes is shown schematically in Figure 2. It is a simple extension of the design used extensively in our multitude of small




Figure 2. 5-cm³ test vessel.

chambers in the earlier studies (Beyer 1996; Beyer, DeSpirito, and Reeves 1996). The interior diameter is 0.95 cm (0.375 in) and approximately 6.3 cm (2.5 in) long. It was fabricated from Ph 13-8 Mo steel, but was not heat treated. It has a window and Mylar burst diaphragm that are sealed with o-rings and clamps. The pressure gauge (Kistler 211 B) serves as the primary diagnostic tool. The 7-cm-long, 1-mm-i.d. vent tube shown was not present for all tests. Its main purpose was to ensure that a test started at atmospheric pressure, since this device readily pressurizes the propellant upon assembly. This vessel was essentially duplicated in acrylic without the pressure gauge for the photographic observations.

The larger (30 cm³) vessel (stainless steel Ph 13-8 Mo, heat treated to about R45) is shown in Figure 3. Its interior chamber is 2.54 cm (1.0 in) in diameter and 6 cm (2.38 in) long. The vent is 0.79 cm (0.313 in) in diameter and 3.8 cm (1.5 in) long. Pressure is sealed with an o-ring at low pressure and a tapered metal seal for higher pressures. The window and pressure ports are both designed to accommodate Kistler 607C pressure gauges. Not shown is the simple clamp used to hold a Mylar diaphragm or breakaway window over the top of the vent in some tests.

3. OBSERVATIONS

3.1 Three-Stage Initiator. In spite of difficulties with the fiber optic input system, good results were obtained for ignition of the 0.1-cm³ first stage. The key successes were the achievement of reliable ignition and a reduction of the extreme peak pressures commonly seen with the present electrical ignition




Figure 3. 30-cm³ test vessel.

fixture. Reproducibility was quite good, as shown in Figure 4, where four consecutive shots are shown. For this series, nothing was done to the chamber except to open the fill valve and inject the propellant. As can be seen, besides some minor oscillations, the pressure repeatability is good. Also, the peak pressures ca. 170 MPa (25 ksi) are in a range to remove many concerns of material problems in critical regions of the design such as check valves on the fill system.

Following our successes with the first stage, several attempts were made to characterize the transfer of ignition to the second (1.5 cm³) chamber. At the same time, an effort was made to build and operate a remote fill system, which it was hoped would speed progress. Our expectations that this system would be simple to get operational were not met. Relatively few successful shots were fired. A typical "success" is shown in Figure 5. In this figure, the initial peak pressure of the first chamber is somewhat higher than in Figure 4, the result of deliberately depositing more laser energy to ensure ignition. Two characteristics stand out in these traces. Most significant is the magnitude and the oscillations of the pressure in chamber two. Also of note is that the highest pressure seen by the primary chamber is due to back pressure from the secondary chamber when it ignites. Thus, there may be limited value to keeping the first pressure rise low. The secondary chamber pressure trace shows indications of undesirable ignition, especially the pressure spikes for almost 0.5 ms before the major pressure rise.

These characteristics led to the conclusion that a major effort in understanding ignition transfer might be necessary to make this device work well. The additional difficulties with the fiber optic input designed into this fixture were mentioned earlier. Thus, this effort was delayed pending the delivery of fiber optic solutions being pursued under contract (General Fiber Optics, Inc. 1993).




Figure 4. Pressure-time records in first stage of initiator from four consecutive shots.




Figure 5. Pressure-time records from initiator when two stages are ignited.

3.2 5-cm³ Chamber. One of the major unknowns in going to a larger chamber is the influence of pressure waves resulting from the initial laser energy deposition. This phenomenon was explored with a large number of shots with both water and propellant in the chamber. As with the smaller chambers, it is usually the case that when there is robust ignition, there are minimal pressure waves during the pressure rise. However, cause and effect are not clear here. Two examples of less-than-ideal behavior are shown here for water shots. Figure 6 was done with no vent tube and starting from 1 atmosphere pressure. The laser beam was focused to a spot about 1 cm inside the window. As can be seen, the pressure rises during most of the laser pulse and then decays slowly. The magnitude of the pressure waves, especially during the pressure rise, is certainly enough to affect the ignition event. Although efforts were made to completely fill the chamber, the presence of small air bubbles cannot be ruled out and may be a contributing factor to the lower frequencies. A large gas bubble was observed after the event, but was expected from vaporization of water by the laser.

When the water was doped with graphite powder (ca. 2 mg/cm³), even more dramatic behavior was observed some of the time. A typical pressure trace is shown in Figure 7, which was done with the vent




Figure 6. Water shot in 5-cm³ chamber.




Figure 7. Water doped with graphite in 5-cm³ chamber.

tube mounted on the vessel. Most dramatic is that there is no pressure rise during most of the laser pulse. It appears that the graphite may be reflecting a large portion of the laser energy after an initial absorption, as indicated by the pressure rise. The dominant (slow) frequency is possibly related to the motion of the liquid in the vent tube. Traces quite similar to this have also been recorded with propellant heavily doped with graphite. The addition of the graphite, when used, was kept to small amounts following these observations.

Many successful ignition events were observed with this vessel. One of the characteristics of focusing the laser into the clear liquid is the randomness of response. While this may be due to impurities, it may also be caused by other variables such as changes in the laser mode structure and subsequent differences in nonlinear absorption. A limited number of high-speed film records were made with the acrylic chamber in an attempt to determine how extensive the ignition point is in these events. The film records are limited but show no dramatic difference in light intensity or distribution between using a solid target a few millimeters inside the window or light doping with graphite. In both cases, ignition appears to take place in a small region. With no target, ignition was observed to occur within a centimeter of the window.

One very clear observation, as with our earlier, smaller scale studies, is the dominance of prepressurization in the ignition of XM46. In this vessel, it is easy to prepressurize up to several hundred pounds/inch² (a few Megapascals) just by filling and tightening the screws for sealing the o-rings. The

lack of ignition reproducibility has so far prevented quantification of the pressure effect. An additional observation is that, because ignition takes place near the window, and the vent (burst disk) is at the opposite end, flow through the vessel from ignition point to vent provided sufficient confinement so that the propellant was often not extinguished upon burst of the diaphragm. The continued burning most frequently happened following an ignition delay, as discussed in the next sections.

Two related observations are shown in Figure 8. Although part of the trace is missing, the pressure is clearly rising in (B). The acoustic report in the laboratory was dramatic from this event. Two characteristics are seen in this and other events that continued to burn: a longer time delay and a higher peak pressure before diaphragm burst. Both events were done with a 0.5-ms laser pulse of approximately 30 J of energy (estimated energy reaching the propellant). Both started at pressures of about 200 psi (1.4 MPa). As can be seen, in event (A) the laser energy couples in better, the pressure rise is higher during the laser pulse, and the ignition delay is shorter. In the initially less robust shot (B), apparently a larger flame kernel or volume of reaction develops before the diaphragm bursts so that sufficient gas generation is present to continue the combustion with the chamber vented.

Similar behavior is shown in Figure 9. Again, in (A) the prompt ignition is detrimental to continued combustion. Though it takes most of a millisecond to complete, the chemistry is turned off by the depressurization. Prepressurization on both shots was measured at less than 100 psi (0.7 MPa). Clearly, full combustion is present in (B). Although no measurements of pressure rise were made in the dump vessel, the amount of unburned propellant recovered after (B) was much less than 5 cm³.

3.3 30-cm³ Chamber. The results with the 5-cm³ chamber suggested that with moderate prepressurization, a burst disk to allow reaction propagation to a critical extent, and modest confinement in venting the combustion products, a significant amount of propellant could be burned from direct ignition. The result was the design and construction of the 30-cm³ chamber.

The initial experiments were done with no prepressure. The laser light was introduced through a window mounted in the side port, according to the chamber design. Although full ignition was not expected without some temporary confinement (diaphragm equivalent), the vent was left open to the air to determine the level of response in this configuration. Typical pressure traces showed maximum levels of up to 200–300 psi (1–2 MPa). Attempts to deposit more laser energy and to tighten the focus spot in the propellant resulted only in many burned windows. Even with a Mylar diaphragm glued over the vent,




Figure 8. XM46 laser ignition in 5-cm³ vessel showing depressurization resulting in (A) extinction and (B) continued burning.




Figure 9. XM46 ignition in 5-cm³ vessel showing laser pulse, prompt ignition, and delayed ignition.

pressure rises did not vary much. Thus it was made clear that a major difficulty was to ensure that the chamber was completely filled with liquid. Inspection of partial fills showed that the liquid was not wetting the walls well and that many air bubbles remained.

Since prepressurization is the key to easy ignition of XM46, two such shots were tried with this chamber. In both shots, the side port was used for adding nitrogen gas pressure at 600 psi (4 MPa). Since the Mylar we use is only partially transmitting at the laser wavelength, it tends to burn above about 10 J of energy and is therefore not useful as a window here. Disposable windows were cut from fused silica substrate and clamped over the top of the vent hole. Clearly, igniting the propellant near the top of the vent will not result in a condition where there is sufficient confinement to maintain the pressure required for combustion. However, this arrangement allowed us to demonstrate ignition of the volume without waiting for modifications to the chamber.

The pressure result of the second of these shots is shown in Figure 10. As expected, there was no continuing pressure after the window released the initial pressure. Of note is the slow rate of pressure buildup after the laser pulse, following the 4-ms "induction period." Following this event, the chamber was completely empty except for ca. 1 cm³. Some ejected liquid showed evidence of partial reaction, but no analysis was made. It also appears that the pressurization rate (from 6 ms to 10 ms) is about one-fifth the comparable rate with the smaller chamber. This effect could perhaps be due to either gas bubbles in the volume or the compressibility of the liquid (Liquid Propellant XM46 Handbook 1994). Based on the 5-cm³ vessel results, there is not much doubt that a significant amount of the propellant would have burned in the chamber if ignition had taken place below the vent tube, as originally designed.




Figure 10. Pressure response during ignition of 30-cm³ of XM46.

4. DISCUSSION

The studies with the multistage initiator show the wisdom of using this method of igniting liquid propellant. The advantage has been demonstrated earlier of igniting a sufficiently small initial volume so that a complete fill can be used to get rapid pressurization; by limiting the volume to ca. 0.1 cm³, burnout occurs before extremely high pressures are reached. In past designs, the difficulties we have observed here in ignition transfer to larger volumes have been avoided by making the ratio of volumes small. The conclusion from the present study is that, while we might be able to engineer around these difficulties, some better systematic understanding of the control of the process would be valuable. It appears that this approach will work and was set aside primarily to wait for the fiber optic solutions.

The larger volume chambers demonstrate that, with a proper pressure release valve and modest prepressurization, a volume of 30 cm³ can be readily ignited directly with the deposition of ca. 30 J of laser energy. Since it appears that less-than-prompt ignition is advantageous, smaller amounts of energy (laser or electrical) may work reliably in a well-designed device. The design of an appropriate valve has not been attempted.

5. FUTURE STUDIES

Clearly, this present study is incomplete in many respects. Pending the availability of funding, attempts will be made to more clearly characterize the initiator behavior with three chambers loaded. The value of the direct ignition studies would be increased by experiments that couple them to a sealed dump chamber to measure the fraction of liquid propellant burned. It would also be valuable to characterize this approach more carefully for the effect of prepressurization and the amount and rate of deposition of energy.

6. REFERENCES

- Beyer, R. A. "Laser Ignition of Liquid Gun Propellant." ARL-TR-1058, U.S. Army Research Laboratory, Aberdeen Proving Ground, MD, April 1996.
- Beyer, R. A., J. DeSpirito, and G. P. Reeves. "Laser Ignition of Liquid Gun Propellant XM46: Transition From Small-Scale Laboratory Fixtures to Gun Igniters." ARL-TR-1056, U.S. Army Research Laboratory, Aberdeen Proving Ground, MD, April 1996.
- General Fiber Optics, Inc. Contract DAAA15-93-C-0068. Gregory C. Burke, Principal Investigator, 1993.
- Hanson, J. Private communication. Martin Marietta Defense Systems, Pittsfield MA, 1993.
- Liquid Propellant XM46 Handbook. JPL 8978, Jet Propulsion Laboratory, California Institute of Technology, Pasadena, CA, 29 July 1994.
- Marrs, C. D. Private communication. Naval Air Warfare Center, Weapons Division, China Lake, CA, 1993.

INTENTIONALLY LEFT BLANK.

APPENDIX:
THE EFFECT OF LIQUID COMPRESSIBILITY ON PRESSURE RISE

INTENTIONALLY LEFT BLANK.

If the liquid propellant (XM46) were an incompressible liquid, then the ignition would be much more independent of the initial volume of propellant. Although efforts were made in this study to distribute the laser energy over a larger volume, the energy deposition remains a local event. The result of this event is the creation of a thermally hot region (probably a plasma when a liquid-solid interface is involved), with some gas-phase products produced during the laser pulse. These gas-phase products are the source of the pressure rise that is important in the ignition process. Since the ignition reactions appear to have a strong pressure dependence (not necessarily the same dependence as the burning rate exponent), a good initial pressure rise yields a short ignition delay and usually more reproducible ignition. Conversely, if the pressure does not rise sufficiently, a long delay or no ignition will result. The principal effect of a larger volume of propellant is to reduce the pressure rise in the chamber through compression of the liquid.

From the Liquid Propellant XM46 Handbook (1994), for increases in pressure of this magnitude, the density changes are described by:

$$\rho = \rho_0 \exp \{-2.02 \times 10^{-5} * \text{pressure}\}$$

with the pressure in bar. For these calculations, $\rho_0 = 1.46 \text{ g/cm}^3$ was used.

From our observations, the maximum pressure rise for a 0.1-ml chamber is about 17 MPa (2,500 psi). From the compressibility data for M46, if we assume that a simple gas bubble has formed, the bubble volume would be about 0.3 μl . Using this same equation, the graph in Figure A-1 is generated. The largest volume plotted is 30 ml, with a corresponding pressure rise of 7 psi (50 kPa). Although the observed pressure jumps in the 30-ml chamber were somewhat larger, up to 1.3 MPa (200 psi), the difficulty of direct ignition where pressure must be generated during the laser pulse is clearly a formidable task. In addition, the importance of a completely filled volume (free of pressure-absorbing air bubbles) remains the same as the volume becomes larger.




Figure A-1. The effect of a decrease in volume of 0.3 μ l with a chamber filled with XM46.

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
2	DEFENSE TECHNICAL INFO CTR ATTN DTIC DDA 8725 JOHN J KINGMAN RD STE 0944 FT BELVOIR VA 22060-6218
1	HQDA DAMO FDQ ATTN DENNIS SCHMIDT 400 ARMY PENTAGON WASHINGTON DC 20310-0460
1	US MILITARY ACADEMY MATH SCI CTR OF EXCELLENCE DEPT OF MATHEMATICAL SCI ATTN MDN A MAJ DON ENGEN THAYER HALL WEST POINT NY 10996-1786
1	DIRECTOR US ARMY RESEARCH LAB ATTN AMSRL CS AL TP 2800 POWDER MILL RD ADELPHI MD 20783-1145
1	DIRECTOR US ARMY RESEARCH LAB ATTN AMSRL CS AL TA 2800 POWDER MILL RD ADELPHI MD 20783-1145
3	DIRECTOR US ARMY RESEARCH LAB ATTN AMSRL CILL 2800 POWDER MILL RD ADELPHI MD 20783-1145
 <u>ABERDEEN PROVING GROUND</u> 	
2	DIR USARL ATTN AMSRL CILP (305)

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
1	HQDA ATTN SARD TT DR F MILTON PENTAGON WASHINGTON DC 20310-0103
1	HQDA ATTN SARD TT MR J APPEL PENTAGON WASHINGTON DC 20310-0103
1	HQDA OASA RDA ATTN DR C H CHURCH PENTAGON ROOM 3E486 WASHINGTON DC 20310-0103
4	COMMANDER US ARMY RESEARCH OFFICE ATTN R GHIRARDELLI D MANN R SINGLETON R SHAW P O BOX 12211 RSCH TRNGLE PK NC 27709-2211
1	DIRECTOR ARMY RESEARCH OFFICE ATTN AMXRO RT IP LIB SERVICES P O BOX 12211 RSCH TRNGLE PK NC 27709-2211
2	COMMANDER US ARMY ARDEC ATTN SMCAR AEE B D S DOWNS PCTNY ARSNL NJ 07806-5000
2	COMMANDER US ARMY ARDEC ATTN SMCAR AEE J A LANNON PCTNY ARSNL NJ 07806-5000
1	COMMANDER US ARMY ARDEC ATTN SMCAR AEE BR L HARRIS PCTNY ARSNL NJ 07806-5000
2	COMMANDER US ARMY MISSILE COMMAND ATTN AMSMI RD PR E A R MAYKUT AMSMI RD PR P R BETTS REDSTONE ARSENAL AL 35809

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
1	OFFICE OF NAVAL RESEARCH DEPARTMENT OF THE NAVY ATTN R S MILLER CODE 432 800 N QUINCY STREET ARLINGTON VA 22217
1	COMMANDER NAVAL AIR SYSTEMS COMMAND ATTN J RAMNARACE AIR 54111C WASHINGTON DC 20360
2	COMMANDER NAVAL SURFACE WARFARE CENTER ATTN R BERNECKER R 13 G B WILMOT R 16 SILVER SPRING MD 20903-5000
5	COMMANDER NAVAL RESEARCH LABORATORY ATTN M C LIN J MCDONALD E ORAN J SHNUR R J DOYLE CODE 6110 WASHINGTON DC 20375
2	COMMANDER NAVAL WEAPONS CENTER ATTN T BOGGS CODE 388 T PARR CODE 3895 CHINA LAKE CA 93555-6001
1	SUPERINTENDENT NAVAL POSTGRADUATE SCHOOL DEPT OF AERONAUTICS ATTN D W NETZER MONTEREY CA 93940
3	AL LSCF ATTN R CORLEY R GEISLER J LEVINE EDWARDS AFB CA 93523-5000
1	AFOSR ATTN J M TISHKOFF BOLLING AIR FORCE BASE WASHINGTON DC 20332

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>	<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
1	OSD SDIO IST ATTN L CAVENY PENTAGON WASHINGTON DC 20301-7100	1	BRIGHAM YOUNG UNIVERSITY DEPT OF CHEMICAL ENGINEERING ATTN M W BECKSTEAD PROVO UT 84058
1	COMMANDANT USAFAS ATTN ATSF TSM CN FORT SILL OK 73503-5600	1	CALIFORNIA INSTITUTE OF TECH JET PROPULSION LABORATORY ATTN L STRAND MS 125 224 4800 OAK GROVE DRIVE PASADENA CA 91109
1	UNIV OF DAYTON RSCH INSTITUTE ATTN D CAMPBELL AL PAP EDWARDS AFB CA 93523	1	CALIFORNIA INSTITUTE OF TECHNOLOGY ATTN F E C CULICK MC 301 46 204 KARMAN LAB PASADENA CA 91125
1	NASA LANGLEY RESEARCH CENTER ATTN G B NORTHAM MS 168 LANGLEY STATION HAMPTON VA 23365	1	UNIVERSITY OF CALIFORNIA LOS ALAMOS SCIENTIFIC LAB P O BOX 1663 MAIL STOP B216 LOS ALAMOS NM 87545
4	NATIONAL BUREAU OF STANDARDS US DEPARTMENT OF COMMERCE ATTN J HASTIE M JACOX T KASHIWAGI H SEMERJIAN WASHINGTON DC 20234	1	UNIVERSITY OF CALIFORNIA BERKELEY CHEMISTRY DEPARMENT ATTN C BRADLEY MOORE 211 LEWIS HALL BERKELEY CA 94720
2	DIRECTOR LAWRENCE LIVERMORE NATIONAL LAB ATTN C WESTBROOK W TAO MS L 282 P O BOX 808 LIVERMORE CA 94550	1	UNIVERSITY OF CALIFORNIA SAN DIEGO ATTN F A WILLIAMS AMES B010 LA JOLLA CA 92093
1	DIRECTOR LOS ALAMOS NATIONAL LAB ATTN B NICHOLS T7 MS B284 P O BOX 1663 LOS ALAMOS NM 87545	2	UNIV OF CALIFORNIA SANTA BARBARA QUANTUM INSTITUTE ATTN K SCHOFIELD M STEINBERG SANTA BARBARA CA 93106
2	PRINCETON COMBUSTION RESEARCH LABORATORIES INC ATTN N A MESSINA M SUMMERFIELD PRINCETON CORPORATE PLAZA BLDG IV SUITE 119 11 DEERPARK DRIVE MONMOUTH JUNCTION NJ 08852	1	UNIV OF COLORADO AT BOULDER ENGINEERING CENTER ATTN J DAILY CAMPUS BOX 427 BOULDER CO 80309-0427
		3	UNIV OF SOUTHERN CALIFORNIA DEPT OF CHEMISTRY ATTN R BEAUDET S BENSON C WITTIG LOS ANGELES CA 90007

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>	<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
1	CORNELL UNIVERSITY DEPARTMENT OF CHEMISTRY ATTN T A COOL BAKER LABORATORY ITHACA NY 14853	4	PENNSYLVANIA STATE UNIVERSITY DEPT OF MECHANICAL ENGINEERING ATTN K KUO M MICCI S THYNELL V YANG UNIVERSITY PARK PA 16802
1	UNIVERSITY OF DELAWARE CHEMISTRY DEPARTMENT ATTN T BRILL NEWARK DE 19711	2	PRINCETON UNIVERSITY FORRESTAL CAMPUS LIBRARY ATTN K BREZINSKY I GLASSMAN P O BOX 710 PRINCETON NJ 08540
1	UNIVERSITY OF FLORIDA DEPT OF CHEMISTRY ATTN J WINEFORDNER GAINESVILLE FL 32611	1	PURDUE UNIVERSITY SCHL OF AERONAUTICS & ASTRONAUTICS ATTN J R OSBORN GRISSOM HALL WEST LAFAYETTE IN 47906
3	GEORGIA INSTITUTE OF TECHNOLOGY SCHOOL OF AEROSPACE ENGINEERING ATTN E PRICE W C STRAHLE B T ZINN ATLANTA GA 30332	1	PURDUE UNIVERSITY DEPARTMENT OF CHEMISTRY ATTN E GRANT WEST LAFAYETTE IN 47906
1	UNIVERSITY OF ILLINOIS DEPT OF MECH ENG ATTN H KRIER 144MEB 1206 W GREEN ST URBANA IL 61801	2	PURDUE UNIVERSITY SCHL OF MECHANICAL ENGNRNG ATTN N M LAURENDEAU S N B MURTHY TSPC CHAFFEE HALL WEST LAFAYETTE IN 47906
1	THE JOHNS HOPKINS UNIV CPIA ATTN T W CHRISTIAN 10630 LITTLE PATUXENT PKWY SUITE 202 COLUMBIA MD 21044-3200	1	RENSSELAER POLYTECHNIC INST DEPT OF CHEMICAL ENGINEERING ATTN A FONTIJN TROY NY 12181
1	UNIVERSITY OF MICHIGAN GAS DYNAMICS LAB ATTN G M FAETH AEROSPACE ENGINEERING BLDG ANN ARBOR MI 48109-2140	1	STANFORD UNIVERSITY DEPT OF MECHANICAL ENGINEERING ATTN R HANSON STANFORD CA 94305
1	UNIVERSITY OF MINNESOTA DEPT OF MECHANICAL ENGINEERING ATTN E FLETCHER MINNEAPOLIS MN 55455	1	UNIVERSITY OF TEXAS DEPT OF CHEMISTRY ATTN W GARDINER AUSTIN TX 78712
		1	VA POLYTECH INST AND STATE UNIV ATTN J A SCHETZ BLACKSBURG VA 24061

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
1	APPLIED COMBUSTION TECHNOLOGY INC ATTN A M VARNEY P O BOX 607885 ORLANDO FL 32860
2	APPLIED MECHANICS REVIEWS ASME ATTN R E WHITE & A B WENZEL 345 E 47TH STREET NEW YORK NY 10017
1	TEXTRON DEFENSE SYSTEMS ATTN A PATRICK 2385 REVERE BEACH PARKWAY EVERETT MA 02149-5900
1	BATTELLE TWSTIAC 505 KING AVENUE COLUMBUS OH 43201-2693
1	COHEN PROFESSIONAL SERVICES ATTN N S COHEN 141 CHANNING STREET REDLANDS CA 92373
1	EXXON RESEARCH & ENG CO ATTN A DEAN ROUTE 22E ANNANDALE NJ 08801
1	GENERAL APPLIED SCIENCE LABS INC 77 RAYNOR AVENUE RONKONKAMA NY 11779-6649
1	GENERAL ELECTRIC ORDNANCE SYSTEMS ATTN J MANDZY 100 PLASTICS AVENUE PITTSFIELD MA 01203
1	GENERAL MOTORS RSCH LABS PHYSICAL CHEMISTRY DEPARTMENT ATTN T SLOANE WARREN MI 48090-9055
2	HERCULES INC ATTN W B WALKUP E A YOUNT P O BOX 210 ROCKET CENTER WV 26726

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
1	HERCULES INC ATTN R V CARTWRIGHT 100 HOWARD BLVD KENVIL NJ 07847
1	ALLIANT TECHSYSTEMS INC MARINE SYSTEMS GROUP ATTN D E BRODEN MS MN50 2000 600 2ND STREET NE HOPKINS MN 55343
1	ALLIANT TECHSYSTEMS INC ATTN R E TOMPKINS MN 11 2720 600 SECOND ST NORTH HOPKINS MN 55343
1	IBM CORPORATION RESEARCH DIVISION ATTN A C TAM 5600 COTTLE ROAD SAN JOSE CA 95193
1	IIT RESEARCH INSTITUTE ATTN R F REMALY 10 WEST 35TH STREET CHICAGO IL 60616
1	LOCKHEED MISSILES & SPACE CO ATTN GEORGE LO 3251 HANOVER STREET DEPT 52 35 B204 2 PALO ALTO CA 94304
1	OLIN ORDNANCE ATTN V MCDONALD LIBRARY P O BOX 222 ST MARKS FL 32355-0222
1	PAUL GOUGH ASSOCIATES INC ATTN P S GOUGH 1048 SOUTH STREET PORTSMOUTH NH 03801-5423
1	HUGHES AIRCRAFT COMPANY ATTN T E WARD PO BOX 11337 TUCSON AZ 85734-1337

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
1	SCIENCE APPLICATIONS INC ATTN R B EDELMAN 23146 CUMORAH CREST WOODLAND HILLS CA 91364
3	SRI INTERNATIONAL ATTN G SMITH D CROSLY D GOLDEN 333 RAVENSWOOD AVENUE MENLO PARK CA 94025
1	STEVENS INSTITUTE OF TECH DAVIDSON LABORATORY ATTN R MCALEVY III HOBOKEN NJ 07030
1	SVERDRUP TECHNOLOGY INC LERC GROUP ATTN R J LOCKE MS SVR 2 2001 AEROSPACE PARKWAY BROOK PARK OH 44142
1	SVERDRUP TECHNOLOGY INC ATTN J DEUR 2001 AEROSPACE PARKWAY BROOK PARK OH 44142
3	THIOKOL CORPORATION ELKTON DIVISION ATTN R BIDDLE R WILLER TECH LIB P O BOX 241 ELKTON MD 21921
3	THIOKOL CORPORATION WASATCH DIVISION ATTN S J BENNETT P O BOX 524 BRIGHAM CITY UT 84302
1	UNITED TECHNOLOGIES RSCH CENTER ATTN A C ECKBRETH EAST HARTFORD CT 06108
1	UNITED TECHNOLOGIES CORP CHEMICAL SYSTEMS DIVISION ATTN R R MILLER P O BOX 49028 SAN JOSE CA 95161-9028

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
1	UNIVERSAL PROPULSION COMPANY ATTN H J MCSPADEN 25401 NORTH CENTRAL AVENUE PHOENIX AZ 85027-7837
1	VERITAY TECHNOLOGY INC ATTN E B FISHER 4845 MILLERSPORT HIGHWAY EAST AMHERST NY 14051-0305
1	FREEDMAN ASSOCIATES ATTN E FREEDMAN 2411 DIANA ROAD BALTIMORE MD 21209-1525
3	ALLIANT TECHSYSTEMS ATTN C CANDLAND L OSGOOD R BECKER 600 SECOND ST NE HOPKINS MN 55343
1	DIRECTOR US ARMY BENET LABS ATTN AMSTA AR CCB T SAM SOPOK WATERVLIET NY 12189

NO. OF
COPIES ORGANIZATION

ABERDEEN PROVING GROUND

36 DIR USARL
ATTN: AMSRL-WM-P, A HORST
AMSRL-WM-PC,
R A FIFER
G F ADAMS
W R ANDERSON
R A BEYER
S W BUNTE
C F CHABALOWSKI
K P MCNEILL-BOONSTOPPEL
A COHEN
R CUMPTON
R DANIEL
D DEVYNCK
N F FELL
B E FORCH
J GROSH
J M HEIMERL
A J KOTLAR
M R MANAA
W F MCBRATNEY
K L MCNESBY
S V MEDLIN
M S MILLER
A W MIZIOLEK
S H MODIANO
J B MORRIS
J E NEWBERRY
S A NEWTON
R A PESCE-RODRIGUEZ
B M RICE
R C SAUSA
M A SCHROEDER
J A VANDERHOFF
M WENSING
A WHREN
J M WIDDER
C WILLIAMSON

INTENTIONALLY LEFT BLANK.

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project(0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE January 1997	3. REPORT TYPE AND DATES COVERED Final, Oct 93 - Oct 94	
4. TITLE AND SUBTITLE Laser Ignition of Liquid Propellant XM46: Ignition of Larger Volumes			5. FUNDING NUMBERS PR: 1L161102AH43	
6. AUTHOR(S) Richard A. Beyer and G. Phillip Reeves				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army Research Laboratory ATTN: AMSRL-WM-PC Aberdeen Proving Ground, MD 21005-5066			8. PERFORMING ORGANIZATION REPORT NUMBER ARL-TR-1292	
9. SPONSORING/MONITORING AGENCY NAMES(S) AND ADDRESS(ES)			10. SPONSORING/MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES				
12a. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution is unlimited.			12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) Studies of the laser ignition of the liquid gun propellant XM46 have been extended to volumes up to 30 cm ³ of propellant. In the first part of this work, a multistage initiator was designed and tested, patterned after earlier electrical ignition designs. The study then proceeded to attempt direct ignition of 5 cm ³ and 30 cm ³ of the liquid. Although marginally successful, these studies demonstrate the difficulty of igniting these amounts starting from atmospheric pressure in open vessels.				
14. SUBJECT TERMS laser ignition, XM46, liquid propellant, ignition			15. NUMBER OF PAGES 28	
			16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT UL	

INTENTIONALLY LEFT BLANK.

USER EVALUATION SHEET/CHANGE OF ADDRESS

This Laboratory undertakes a continuing effort to improve the quality of the reports it publishes. Your comments/answers to the items/questions below will aid us in our efforts.

1. ARL Report Number/Author ARL-TR-1292 (Beyer) Date of Report January 1997

2. Date Report Received _____

3. Does this report satisfy a need? (Comment on purpose, related project, or other area of interest for which the report will be used.) _____

4. Specifically, how is the report being used? (Information source, design data, procedure, source of ideas, etc.) _____

5. Has the information in this report led to any quantitative savings as far as man-hours or dollars saved, operating costs avoided, or efficiencies achieved, etc? If so, please elaborate. _____

6. General Comments. What do you think should be changed to improve future reports? (Indicate changes to organization, technical content, format, etc.) _____

CURRENT
ADDRESS

Organization

Name

E-mail Name

Street or P.O. Box No.

City, State, Zip Code

7. If indicating a Change of Address or Address Correction, please provide the Current or Correct address above and the Old or Incorrect address below.

OLD
ADDRESS

Organization

Name

Street or P.O. Box No.

City, State, Zip Code

(Remove this sheet, fold as indicated, tape closed, and mail.)

(DO NOT STAPLE)

DEPARTMENT OF THE ARMY


OFFICIAL BUSINESS

BUSINESS REPLY MAIL

FIRST CLASS PERMIT NO 0001,APG,MD

POSTAGE WILL BE PAID BY ADDRESSEE

DIRECTOR
US ARMY RESEARCH LABORATORY
ATTN AMSRL WM PC
ABERDEEN PROVING GROUND MD 21005-5066



NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

