

AD


TECHNICAL REPORT ARCCB-TR-97010

**SCALING ANALYSIS OF THERMOGRAPHIC
IMAGES USING NEURAL NETWORKS**

**MARK A. JOHNSON
LAWRENCE V. MEISEL**

19970522 033

APRIL 1997

	<p>US ARMY ARMAMENT RESEARCH, DEVELOPMENT AND ENGINEERING CENTER CLOSE COMBAT ARMAMENTS CENTER BENÉT LABORATORIES WATERVLIET, N.Y. 12189-4050</p>	
---	--	---

APPROVED FOR PUBLIC RELEASE; DISTRIBUTION UNLIMITED

DTIC QUALITY INSPECTED 3

DISCLAIMER

The findings in this report are not to be construed as an official Department of the Army position unless so designated by other authorized documents.

The use of trade name(s) and/or manufacturer(s) does not constitute an official indorsement or approval.

DESTRUCTION NOTICE

For classified documents, follow the procedures in DoD 5200.22-M, Industrial Security Manual, Section II-19 or DoD 5200.1-R, Information Security Program Regulation, Chapter IX.

For unclassified, limited documents, destroy by any method that will prevent disclosure of contents or reconstruction of the document.

For unclassified, unlimited documents, destroy when the report is no longer needed. Do not return it to the originator.

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503

1. AGENCY USE ONLY (Leave blank)	2. REPORT DATE April 1997	3. REPORT TYPE AND DATES COVERED Final	
4. TITLE AND SUBTITLE SCALING ANALYSIS OF THERMOGRAPHIC IMAGES USING NEURAL NETWORKS		5. FUNDING NUMBERS AMCMS No. 6111.02.H671.1	
6. AUTHOR(S) Mark A. Johnson and Lawrence V. Meisel			
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army ARDEC Benet Laboratories, AMSTA-AR-CCB-O Watervliet, NY 12189-4050		8. PERFORMING ORGANIZATION REPORT NUMBER ARCCB-TR-97010	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) U.S. Army ARDEC Close Combat Armaments Center Picatinny Arsenal, NJ 07806-5000		10. SPONSORING/MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES Presented at the Acrosense Conference, Orlando, FL, 20-25 April 1997. Published in proceedings of the conference.			
12a. DISTRIBUTION AVAILABILITY STATEMENT Approved for public release; distribution unlimited.		12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) Sequences of thermographic images of burning residue produced by M198 155 (unicharge) test rounds fired at Yuma Proving Ground (YPG) were collected for analysis to elucidate the evolution of conditions in the breech after firing and to provide guidance in determining safe loading protocols for future autoloading. In order to better understand the thermal environment in the breech, we are developing advanced analytical tools that can be used to quantitatively characterize sequences of thermographic images. However, for this study the calibration data required to extract the temperature profiles the YPG thermographic images for these analyses was unavailable. No analytic solution could be determined to perform the highly nonlinear reverse transformation from RGB space to intensities; therefore, a neural network was employed. Furthermore, the experimental data provided by YPG were only measurable over a restricted range of temperatures extending from approximately 80°C up to 110°C. Since the highest temperatures measured in the thermographic data did not correspond to a hazardous condition, more complex measures than simple statistical averages of the temperature had to be used. A new numerical technique represented by sparse data sets was introduced for measuring the scaling properties of single-valued surfaces in 3-space.			
14. SUBJECT TERMS Neural Networks, Scaling Analysis, Parallel Processing, Image Processing, Fractal Analysis		15. NUMBER OF PAGES 8	
		16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT UL

TABLE OF CONTENTS

	<u>Page</u>
INTRODUCTION.....	1
BACKGROUND	1
NEURAL NETWORK TRANSFORMATION	2
FRACTAL CHARACTERIZATION	3
The Fractal Hypersurface.....	3
The Fractal Analysis Technique: Triangulation.....	3
LAM IMPLEMENTATION	4
SUMMARY	5
REFERENCES.....	6

LIST OF ILLUSTRATIONS

1. Thermographic Image.....	7
2. Neural Net Transform.....	7
3. <i>D</i> Contours	7

INTRODUCTION

As the Army moves toward higher energy ammunition and faster rates of fire, there is a greater risk of premature ignition when reloading rounds. A burning residue signature study performed by the Olin Defense Systems Group (ref 1) has indicated that the burn duration of gun bore debris almost always far exceeds the interval between rounds envisioned for future tank autoloaders. Therefore, if the residue is neither completely burned during firing, nor evacuated before the breech is opened, then there exists a potential for a hazardous condition.

Sequences of thermographic images of burning residue produced by M198 155 (unicharge) test rounds fired at Yuma Proving Ground (YPG) have been collected for analysis to elucidate the evolution of conditions in the breech after firing and to provide guidance in determining safe loading protocols for future autoloaders. In order to achieve these objectives, we are defining quantitative measures of the state of the system based on the YPG experimental thermographic image sequences, and we are developing techniques to predict the time to reach a safe-to-load state given a sequence of prior quantitative results. Procedures are being developed along the following lines to better understand the thermal environment in the breech after firing:

1. Conventional analysis with system characterization provided in terms of:
 - Statistical distributions of thermal gradients and other quantitative measures of the temperature distribution in the breech
 - Statistical particulate-hot gas distributions
2. Fractal approaches with system characterization provided in terms of :
 - Fractal measures deduced from hot gas and particulate perimeter-area analysis with coastlines defined by constant temperature contours
 - Fractal measures deduced from the analysis of the local scaling of hypersurfaces formed in temperature-position space

The present report describes results obtained by the application of the latter fractal approach, which required the development of specialized local fractal analysis techniques and had potential for providing insight into the state of general complex heterogeneous systems. We anticipated that optimal characterization of the YPG thermographic image sequences would employ a combination of the approaches outlined above and possibly some others as well.

BACKGROUND

The temperature distributions characteristic of the burning residue in the breech after firing are heterogeneous with the hot regions in the images comprising a relatively small fraction of the imaged area as shown in Figure 1. Additionally, the hot particulate/gaseous regions are mobile and the spaces

between the hot particle/gas regions are contaminated by noise. In our study the experimental data were further limited by recorded temperatures extending only from approximately 80°C to 110°C. Since the highest temperatures measured in the thermographic data did not correspond to a hazardous condition, more complex measures than simple statistical averages of the temperature had to be employed. For example, we have analyzed the evolution of particle sizes and temperature gradients in regions having temperatures greater than a threshold value for a number of firing sequences. However, no trends have yet been identified.

A complementary approach focuses attention on the complexity of the temperature distribution as reflected in its local fractal scaling properties. In particular, the temperature distribution has to be characterized in terms of the local fractal dimension D . The techniques developed for the determination of the local fractal scaling and typical results obtained by application to YPG thermographic image sequences are described in this report.

NEURAL NETWORK TRANSFORMATION

In order to perform scaling analysis of the thermographic images, the intensity profiles of the thermographic images had to be extracted from the red-green-blue (RGB) representation. This is because the calibration data normally recorded with the thermographic images were unavailable. The calibration scale on the bottom of Figure 1 shows the gray scale intensities corresponding to temperature values within a specified range. It also shows the upper and lower saturation regions beyond which temperature data were not recorded. In the figure, temperatures below 80°C were not recorded as gray scale intensities, but instead as a combination of unequal RGB values. A different set of RGB values was used for temperatures exceeding 110°C. Since the data were extracted from a low-resolution video source, the actual RGB values are unknown. The video source also introduced two transition zones between the gray scale extremes and the saturation regions. The RGB values within these zones vary significantly. No analytic solution could be determined to extract the temperature profiles from the RGB data; therefore, a feedforward neural network was employed to perform the highly nonlinear reverse transformation. Excellent results were obtained using the three RGB values as a feature vector, thirty neurons in a single hidden layer, and a single output neuron corresponding to intensity. The network was trained on a single frame using a random selection of pixels (RGB values) in each of the saturation regions, the transition zones, and the gray scale calibration region. The network converged to a solution and successfully transformed each pixel in the frame from which the training data were extracted, as well as (typically 1000) subsequent frames in the firing sequence. Figure 2 shows the results of the neural network transformation of Figure 1. The transition zones and background noise have been removed. The same network was also successfully used in obtaining the temperature profiles for the remaining ten (independently-measured) firing sequences.

FRACTAL CHARACTERIZATION

The Fractal Hypersurface

A hypersurface is defined for the temperature distribution in a thermographic image by combining the $\{i,j\}$ integer spatial coordinates with the integer gray level coordinates (which correspond to temperature values) to form a set of points belonging to a hypersurface $g(i,j)$. In order to define such a surface, the number of gray levels must be selected to correspond to one $\{i,j\}$ pixel spacing. This metric should be selected to maximize the variations in the local D -values for the transition region between safe and unsafe to load. In practice, values near one gray level per pixel spacing yielded "satisfactory" variations in local D for the YPG data and no attempt has been made thus far to optimize the metric. The thermographic image hypersurfaces are extremely heterogeneous: regions corresponding to hot particles and/or hot gasses have relatively high local fractal dimensions, but correspond to a relatively small fraction of the volume. Regions between the hot particles and hot gasses, which comprise the major part of the volume, have local D -values near 2.0.

The Fractal Analysis Technique: Triangulation

In order to measure the local fractal dimensions in the heterogeneous YPG thermographic image sequences, a fractal analysis technique is required to measure local D values based upon limited sets of data. Such an analysis would be impossible employing standard techniques of fractal analysis. For example, correlation-integral or box-counting fractal analysis of fractal sets having D near 2.0 requires more than 10^5 points for convergence within 15 percent (refs 2,3). Note, $10^5 \gg 17^2 = 289$. Therefore, a specialized technique of fractal analysis has been developed for the analysis of single-valued continuous surfaces of the sort described by $g(i,j)$.

The principle underlying the triangulation algorithm is that if the (i,j) -lattice is considered as the base plane of a set of hypercubes, then for a continuous single-valued surface, the sets of points

$$S(i,j) = \{(i,j,g(i,j)), (i+1,j,g(i+1,j)), (i,j+1,g(i,j+1)), (i+1,j+1,g(i+1,j+1))\} \quad (1)$$

determine that *all* the boxes located between the member of $S(i,j)$ having the largest value of g and the member of $S(i,j)$ having the smallest value of g contain pieces of the hypersurface. Furthermore, each point $(i,j,g(i,j))$ serves to (partially) define four $S(i,j)$, and therefore four sets of occupied boxes. The actual implementation of the triangulation principle focuses on the scaling of a hierarchy of approximate tessellation of the fractal surface based on the measured points $(i,j,g(i,j))$. The triangulation algorithm determines the fractal dimension of single-valued surfaces in 3-space. A detailed description of the triangulation algorithm, including a discussion concerning its sensitivity to uniformly and normally distributed random noise, is presented in Reference 4.

Consider L by L images, where L is taken as

$$L = 2^n + 1 \text{ for integer } n \quad (2)$$

to facilitate triangular approximations. For such choices of L , sets of triangles may be defined that tessellate the surface with no gaps or overlaps, whose vertices coincide with subsets of points on the lattice, and whose projections in the (i,j) -plane are right triangles of side lengths $Y(m)$, which are given by

$$Y(m) = 2^m \text{ for } m = \{0,1,\dots,n\} \quad (3)$$

The small $Y(m)$ approximations to the fractal surfaces scale according to

$$\frac{d \ln(A(m))}{d \ln(Y(m))} \xrightarrow{m \rightarrow \infty} 2 - D \quad (4)$$

where $A(m)$ is an approximate surface area that can be expressed in terms of individual triangle areas

$$A(m) \equiv \sum A_i(m) \quad (5)$$

for the triangulation based on $Y(m)$ by $Y(m)$ cells. Equation (3) defines the fractal dimension D . A slightly more general form of the triangulation algorithm, which allows for

$$Y(a,b,c,\dots) = 2^a 3^b 5^c \dots \text{ for } a = \{0,1,\dots,n_1\}, b = \{0,1,\dots,n_2\}, c = \{0,1,\dots,n_3\}, \dots \quad (6)$$

is presented in Reference 4.

Figure 3 shows useful values of D that were based upon 17x17 patches of elevation data of the thermographic image of Figure 2. The values of the D contours in Figure 3 range from 2.0 to 2.5.

LAM IMPLEMENTATION

The triangulation algorithm is capable of reliably determining *fractal* scaling parameters of relatively sparse, heterogeneous data sets. However, the generation of local D -maps for each frame of a set of firing sequences is impractical without exploiting the inherent parallelism of the problem. A suite of homogenous parallel procedures has been developed to map the triangulation algorithm to a multicomputer platform using a subset of Trollius (Ohio State University and Cornell Research Foundation) called *LAM* (ref 5) for interprocess communication. *LAM* supports only general purpose UNIX machines connected via a local area network or the Internet. *LAM* is a node-oriented computing environment that uses an identifier assigned to each node (nodeid) as the primary synchronization for communication. The nodes are usually fully connected (maximum 1-hop distance) since the network is

generally a shared resource. In our parallel implementation of the triangulation algorithm, a master process assigns equal-sized regions of each thermographic image to slave processing nodes for computation of local D -map subsets. The processing nodes return the results to the master process, where the D -map is assembled and the slave processors are assigned new regions to analyze. Although this approach does not fully exploit the communication advantages of a fully connected network, the load balancing has resulted in a performance improvement directly proportional to the number of workstations. This is likely due to the high computation/communication ratio and the relatively small number of workstations comprising our multicomputer.

The results shown in Figure 3 are limited because of the restricted distribution of recorded temperature values. Meaningful values of D can only be obtained where the complexity of the temperature distributions is faithfully represented in at least a 9×9 region. These regions are usually limited to small areas bounding the perimeter of larger particles. The D -maps were computed for each of the neural network transformed images in all of the firing sequences. The results are being included with conventional statistical measures (thermal gradients, temperature distributions, etc.) to help develop a database for a safe-to-load sensor design.

SUMMARY

A better understanding of the thermal environment in the breech after firing will enable engineers to provide guidance in determining safe loading protocols for future autoloaders. Quantitative characterization of complexity in the temperature distribution of thermographic data complements conventional statistical analysis techniques and provides additional insight into the nature of the problem. The use of standard analysis techniques to extract the scaling parameters of the thermographic data would yield inaccurate results because of the limited size of the data sets. Therefore, the triangulation fractal analysis technique was developed to provide a means of measuring local scaling properties of sparse data.

The recorded RGB values comprise a highly nonlinear representation of the actual temperatures. No analytic inverse transformation could be determined; therefore, a neural network was employed for extracting temperature intensity profiles. The computation of local D -maps for sequences of thermographic images using triangulation is numerically expensive, so the algorithm has been mapped to a powerful message-passing multicomputer using the *LAM* programming environment for interprocess communication. Several thermographic image sequences collected at YPG have been analyzed using triangulation and conventional analytic approaches in order to characterize the state of the system. The results are being used by our development engineers to help establish a database for a safe-to-load sensor design.

REFERENCES

1. Brown, C.W., and Cutchall, T.S., "Burning Residue Signature Study," Olin Defense Systems Group, St. Petersburg, Fl, 26-28 January 1990.
2. Meisel, L.V., Johnson, M.A., and Cote, P.J., "Box-Counting Multifractal Analysis," *Phys. Rev.*, Vol. 45, 1992, p. 6989.
3. Meisel, L.V., and Johnson, M.A., "Convergence of Numerical Box-Counting and Correlation Integral Multifractal Analysis," *Pattern Recognition 1997*, to be published.
4. Meisel, L.V., and Johnson, M.A., "Fractal Scaling in Cellular Automata Simulations of Dissipative Dynamical Systems," *Proceedings of the 1996 Simulation Multiconference*, New Orleans, LA, April 1996.
5. "LAM for C Programmers," Ohio Supercomputer Center, 1224 Kinnear Road, Columbus, OH 43212.

Fig. 1: Thermographic Image



Fig. 2: Neural Net Transform





Fig. 3: D Contours



TECHNICAL REPORT INTERNAL DISTRIBUTION LIST

	<u>NO. OF COPIES</u>
CHIEF, DEVELOPMENT ENGINEERING DIVISION	
ATTN: AMSTA-AR-CCB-DA	1
-DB	1
-DC	1
-DD	1
-DE	1
CHIEF, ENGINEERING DIVISION	
ATTN: AMSTA-AR-CCB-E	1
-EA	1
-EB	1
-EC	1
CHIEF, TECHNOLOGY DIVISION	
ATTN: AMSTA-AR-CCB-T	2
-TA	1
-TB	1
-TC	1
TECHNICAL LIBRARY	
ATTN: AMSTA-AR-CCB-O	5
TECHNICAL PUBLICATIONS & EDITING SECTION	
ATTN: AMSTA-AR-CCB-O	3
OPERATIONS DIRECTORATE	
ATTN: SIOVV-ODP-P	1
DIRECTOR, PROCUREMENT & CONTRACTING DIRECTORATE	
ATTN: SIOVV-PP	1
DIRECTOR, PRODUCT ASSURANCE & TEST DIRECTORATE	
ATTN: SIOVV-QA	1

NOTE: PLEASE NOTIFY DIRECTOR, BENÉT LABORATORIES, ATTN: AMSTA-AR-CCB-O OF ADDRESS CHANGES.

TECHNICAL REPORT EXTERNAL DISTRIBUTION LIST

	<u>NO. OF COPIES</u>		<u>NO. OF COPIES</u>
ASST SEC OF THE ARMY RESEARCH AND DEVELOPMENT ATTN: DEPT FOR SCI AND TECH THE PENTAGON WASHINGTON, D.C. 20310-0103	1	COMMANDER ROCK ISLAND ARSENAL ATTN: SMCRI-SEM ROCK ISLAND, IL 61299-5001	1
DEFENSE TECHNICAL INFO CENTER ATTN: DTIC-OCF (ACQUISITIONS) 8725 JOHN J. KINGMAN ROAD STE 0944 FT. BELVOIR, VA 22060-6218	2	COMMANDER U.S. ARMY TANK-AUTMV R&D COMMAND ATTN: AMSTA-DDL (TECH LIBRARY) WARREN, MI 48397-5000	1
COMMANDER U.S. ARMY ARDEC ATTN: AMSTA-AR-AEE, BLDG. 3022 AMSTA-AR-AES, BLDG. 321 AMSTA-AR-AET-O, BLDG. 183 AMSTA-AR-FSA, BLDG. 354 AMSTA-AR-FSM-E AMSTA-AR-FSS-D, BLDG. 94 AMSTA-AR-IMC, BLDG. 59 PICATINNY ARSENAL, NJ 07806-5000	1 1 1 1 1 1 2	COMMANDER U.S. MILITARY ACADEMY ATTN: DEPARTMENT OF MECHANICS WEST POINT, NY 10966-1792 U.S. ARMY MISSILE COMMAND REDSTONE SCIENTIFIC INFO CENTER ATTN: AMSMI-RD-CS-R/DOCUMENTS BLDG. 4484 REDSTONE ARSENAL, AL 35898-5241	1 2
DIRECTOR U.S. ARMY RESEARCH LABORATORY ATTN: AMSRL-DD-T, BLDG. 305 ABERDEEN PROVING GROUND, MD 21005-5066	1	COMMANDER U.S. ARMY FOREIGN SCI & TECH CENTER ATTN: DRXST-SD 220 7TH STREET, N.E. CHARLOTTESVILLE, VA 22901	1
DIRECTOR U.S. ARMY RESEARCH LABORATORY ATTN: AMSRL-WT-PD (DR. B. BURNS) ABERDEEN PROVING GROUND, MD 21005-5066	1	COMMANDER U.S. ARMY LABCOM, ISA ATTN: SLCIS-IM-TL 2800 POWER MILL ROAD ADELPHI, MD 20783-1145	1

NOTE: PLEASE NOTIFY COMMANDER, ARMAMENT RESEARCH, DEVELOPMENT, AND ENGINEERING CENTER,
BENÉT LABORATORIES, CCAC, U.S. ARMY TANK-AUTOMOTIVE AND ARMAMENTS COMMAND,
AMSTA-AR-CCB-O, WATERVLIET, NY 12189-4050 OF ADDRESS CHANGES.

TECHNICAL REPORT EXTERNAL DISTRIBUTION LIST (CONT'D)

	<u>NO. OF COPIES</u>		<u>NO. OF COPIES</u>
COMMANDER U.S. ARMY RESEARCH OFFICE ATTN: CHIEF, IPO P.O. BOX 12211 RESEARCH TRIANGLE PARK, NC 27709-2211	1	WRIGHT LABORATORY ARMAMENT DIRECTORATE ATTN: WL/MNM EGLIN AFB, FL 32542-6810	1
DIRECTOR U.S. NAVAL RESEARCH LABORATORY ATTN: MATERIALS SCI & TECH DIV WASHINGTON, D.C. 20375	1	WRIGHT LABORATORY ARMAMENT DIRECTORATE ATTN: WL/MNMF EGLIN AFB, FL 32542-6810	1

NOTE: PLEASE NOTIFY COMMANDER, ARMAMENT RESEARCH, DEVELOPMENT, AND ENGINEERING CENTER,
BENÉT LABORATORIES, CCAC, U.S. ARMY TANK-AUTOMOTIVE AND ARMAMENTS COMMAND,
AMSTA-AR-CCB-O, WATERVLIET, NY 12189-4050 OF ADDRESS CHANGES.

DEPARTMENT OF THE ARMY
ARMAMENT RESEARCH, DEVELOPMENT AND ENGINEERING CENTER
BENÉT LABORATORIES, CCAC
US ARMY TANK-AUTOMOTIVE AND ARMAMENTS COMMAND
WATERVLIET, N.Y. 12189-4050

OFFICIAL BUSINESS
AMSTA-AR-CCB-O
TECHNICAL LIBRARY

DEPARTMENT OF THE ARMY
OFFICIAL BUSINESS

Defense Technical Information Center
Attn: DTIC-OCP (Acquisitions)
8725 John J. Kingman Road
Ste 0944
Ft. Belvoir, VA 22060-6218

DA Label 18-1, Sep 83
Edition of Oct 74 will be used until exhausted.