

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank) 2. REPORT DATE
June 13, 1997 3. REPORT TYPE AND DATES COVERED
Annual, June 1, 1996 to May 31, 1997

4. TITLE AND SUBTITLE
Nonlinear Control of Mechanical Systems in the Presence
of Magnitude & Rate Saturation

5. FUNDING NUMBERS
GN00014-96-1-0804

6. AUTHOR(S)
Richard M. Murray

7. PERFORMING ORGANIZATION NAMES(S) AND ADDRESS(ES)
California Institute of Technology
1200 E. California Blvd.
Pasadena, CA 91125

8. PERFORMING ORGANIZATION
REPORT NUMBER
RMM970ONR-1

9. SPONSORING / MONITORING AGENCY NAMES(S) AND ADDRESS(ES)
Office of Naval Research

10. SPONSORING / MONITORING
AGENCY REPORT NUMBER

11. SUPPLEMENTARY NOTES

a. DISTRIBUTION / AVAILABILITY STATEMENT
Approved for Public Release

12. DISTRIBUTION CODE

13. ABSTRACT (Maximum 200 words)
Annual technical report for grant, covering period June 1, 1996 to May 31, 1997.
This report describes recent analytical and experimental results on nonlinear control of systems with simultaneous magnitude and rate saturations.

DTIC QUALITY INSPECTED 2

19970620 005

14. SUBJECT TERMS
Nonlinear Control Theory
Magnitude and Rate Saturation

15. NUMBER OF PAGES
3

16. PRICE CODE

17. SECURITY CLASSIFICATION
OF REPORT
Unclassified

18. SECURITY CLASSIFICATION
OF THIS PAGE
Unclassified

19. SECURITY CLASSIFICATION
OF ABSTRACT
Unclassified

20. LIMITATION OF ABSTRACT
UL

Nonlinear Control of Mechanical Systems in the Presence of Magnitude and Rate Saturations

Richard M. Murray
Mechanical Engineering
California Institute of Technology

Annual Report, Grant N00014-96-1-0804
1 June 1996 to 31 May 1997

This project is aimed at developing systematic techniques for control of mechanical systems in the presence of magnitude and rate saturations, with particular emphasis on problems arising in the context of high performance aircraft. Magnitude and rate saturations are a major source of nonlinearity in all flight control systems and are a fundamental mechanism of instability in both automated and piloted flight. Recent theoretical developments in nonlinear control theory as well as increasing computational power in offline and online computation are enabling the use of more powerful techniques for control of these systems. This project builds on an established base of work in nonlinear control of mechanical systems and stabilization of strongly nonlinear systems to explore new approaches to this problem. In addition to developing theoretical tools for analysis of flight control systems with saturations, experimental validation of the techniques is being performed using a flight control experiment at Caltech that exhibits many of the essential features of aircraft systems while remaining simple enough to allow meaningful testing of fundamental feedback mechanisms.

Our results to date have focused on two different approaches to modifying high performance control laws to maintain stability and performance in the presence of rate saturations. The first approach is the use of a nonlinear gain scheduling technique that degrades the performance of the system when actuators are saturated in such a way as to insure stability. Experimental results on the Caltech ducted fan show this approach to be very promising and these results will be presented at the AIAA Guidance, Navigation, and Control conference in August, 1997 [1]. Analytical results have been derived giving proof of convergence of the algorithm and indicating how and why the controller works [2].

The second approach that we have been pursuing is the use of homogeneous control techniques to convert a linear controller into a nonlinear controller that obeys magnitude and rate limits. This follows an idea based on the work of Praly (in France) and also builds on previous work at Caltech in the construction of homogeneous feedback laws. To date, we have made some progress on applying these ideas to linear systems that are marginally stable (no unstable eigenvalues) and are continuing to develop these techniques and understand how to apply them. The goal of this approach is to design controllers that can "wrap around" existing controllers to allow operation in the presence of magnitude and rate limits and we expect further progress in the coming year.

In addition, we have collaborated with Professor Andrew Teel at the University of Minnesota to test some of his controllers on our flight control experiment. Teel has developed techniques for combining local, high performance controllers with global, stabilizing controllers. These stabilizing controllers have poor performance, but can stabilize the system in the presence of actuator limits.




Figure 1: Experimental results on the Caltech ducted fan experiment. Left: linear controller with 20 deg/sec rate limit. Right: nonlinear scheduling control law (Lauvdal, 1996).

As a consequence, it should be possible to achieve very good local performance using aggressive control designs while maintaining stability of the system at the operating envelope. Experimental testing of these controllers has demonstrated the efficacy of the approach as was recently presented at the 1997 American Control Conference [3].

Finally, we are beginning to pursue the development of real-time trajectory generation techniques in the presence of magnitude and rate saturations. At the present we are limiting ourselves to so-called differentially flat systems, which are nonlinear systems for which trajectory generation is conceptually simple and computationally tractable. This work is just beginning and we have not achieved any significant new results to date, but we are expecting this to be a very fruitful avenue of research with many applications to aerospace systems.

References

- [1] T. Lauvdal and R. M. Murray. Stabilization of a pitch axis flight control experiment with input rate saturation. In *AIAA Conference on Guidance, Navigation, and Control*, 1997. To appear.
- [2] T. Lauvdal, R. M. Murray, and T. I. Fossen. Stabilization of integrator chains in the presence of magnitude and rate saturations: A gain scheduling approach. In *Proc. IEEE Control and Decision Conference*, 1997. Submitted.
- [3] A. R. Teel, O. Kaiser, and R. M. Murray. Uniting local and global controllers for the caltech ducted fan. In *Proc. American Control Conference*, 1997. To appear.