



RIA-81-U973
Supplement

**TECHNICAL
LIBRARY**

CONTRACTOR REPORT ARLCD-CR-81017

Supplement

HIGH FRAGMENTATION STEEL PRODUCTION PROCESS

Colin C. MacCrindle
Metallurgical Engineer
Chamberlain Manufacturing Corporation
Scranton Army Ammunition Plant
Scranton, PA 18505

William Sharpe
Project Engineer
ARRADCOM, Dover, NJ 07801

September 1982

19970908 132

Approved for public release; distribution unlimited.

DTIC QUALITY INSPECTED



Table of Contents

	<u>Page</u>
Introduction	1
Conclusion	26
Appendix A:	27
Appendix B: Hardness Pattern	30
Appendix C: ASTM Grain Size	33
Distribution List	36



List of Tables

<u>Table</u>	<u>Page</u>
1. Ladle Analysis Crucible Steel	2
2. Chemistry - Mid Radius vs Edge	4
3. Segregation	5
4. Hardness Pattern	5
5. Inclusion Rating	6
6. Mechanical Properties	25
7. ASTM Grain Size	26



List of Figures

<u>Figure</u>	<u>Page</u>
1. SEM Photomicrograph of Typical Inclusion (Crucible Steel)	7
2. EDAX-SEM Evaluation of Inclusion (Crucible Steel)	8
3. SEM Photomicrograph of Inclusion (Bethlehem Steel)	9
4. EDAX-SEM Evaluation of Inclusion (Bethlehem Steel)	10
5. EDAX-SEM Evaluation of Inclusion (Bethlehem Steel)	11
6. EDAX Evaluation of Complex Inclusion (Bethlehem Steel)	12
7. EDAX-SEM Evaluation of Matrix of Steel Common to Both Crucible and Bethlehem Steel	13
8. Photomicrograph of Flame Cut Surface	14
9. Photomicrograph of Longitudinal Section of Flame Cut Area	15
10. Photomicrograph of Untempered Platelets with Microcracks	18
11. Photomicrograph of Untempered Platelets with Microcracks	19
12. Mechanical Properties vs Tempering Temperatures - Crucible Steel - Longitudinal Coupons	20
13. Mechanical Properties vs Tempering Temperatures - Crucible Steel - Traverse Coupons	21
14. Mechanical Properties vs Tempering Temperatures - Bethlehem Steel - Longitudinal Coupon	22
15. Mechanical Properties vs Tempering Temperatures - Bethlehem Steel - Traverse Coupon	23



List of Figures

<u>Figure</u>		<u>Page</u>
16.	Composite Curves of Mechanical Properties vs Tempering Temperatures - Longitudinal Coupon	24
17.	Macro Etched Section - Crucible Steel . . .	28
18.	Macro Etched Section - Bethlehem Steel . . .	29
19.	Hardness Pattern - Bethlehem Steel	31
20.	Hardness Pattern - Crucible Steel	32
21.	ASTM Grain Size - Bethlehem Steel	34
22.	ASTM Grain Size - Crucible Steel	35



INTRODUCTION

In order to gain more data on HF-1 steel, two (2) samples were studied at the request of ARRADCOM. One (1) sample was produced by Bethlehem Steel Corporation at their California mill and the other was produced by Crucible Steel.

Both samples were evaluated according to the format in the contractor report ARLCD-CR-81017, MM&T Project 5794189 dated August, 1981.

ACQUISITION OF STEEL

Crucible Steel:

Crucible Steel billets were remnants of steel that was forged at Scranton Army Ammunition Plant for XM795 project and ordered as 5-1/4 inch RCS.

Bethlehem Steel:

Bethlehem Steel samples were pieces shipped to the contractor by Norris Industries, California. The size received was 4 inch RCS.

CHARACTERIZATION

Surface Quality:

Both samples had good surface quality with neither having excessive conditioning (grinding) by their respective mills.

METALLURGICAL EVALUATION

Heat Chemistry:

Samples of both materials were submitted to U. S. Testing for chemical analysis. The ladle chemistry from Bethlehem Steel was not available. The ladle chemistry of Crucible Steel is shown in Table 1.

TABLE 1
LADLE ANALYSIS FROM CRUCIBLE STEEL

<u>C</u>	<u>Mn</u>	<u>P</u>	<u>S</u>	<u>Si</u>	<u>Ni</u>	<u>Cr</u>	<u>Mo</u>	<u>Cu</u>	<u>Al</u>
1.08	1.82	0.023	0.022	0.86	0.13	0.09	0.004	0.03	0.009





U. S. Testing Company was sent samples from both suppliers so that the edge chemistry 0.25 inch beneath the surface could be compared with the chemistry at Mid Radius.

The results of the analysis are shown in Table 2.



TABLE 2 - CHEMISTRY OF MID RADIUS VS EDGE

	<u>% Carbon</u>	<u>% Manganese</u>	<u>% Silicon</u>
Crucible - Mid Radius	1.20	1.60	0.42
Crucible - Surface	1.04	1.70	0.44
Bethlehem XX2L30D Mid Radius	1.10	1.40	0.39
Bethlehem XX2L30D Surface	1.01	1.45	0.42

	<u>% Chromium</u>	<u>% Nickel</u>	<u>% Copper</u>	<u>% Molybdenum</u>
Crucible - Mid Radius	0.12	0.11	0.10	0.10
Crucible - Surface	0.13	0.10	0.10	0.10
Bethlehem XX2L30D Mid Radius	0.13	0.11	0.10	0.10
Bethlehem XX2L30D	0.13	0.11	0.11	0.10

	<u>% Aluminum</u>	<u>% Sulfur</u>	<u>% Phosphorus</u>
Crucible Mid Radius	0.01	0.030	0.012
Crucible Surface	0.01	0.013	0.014
Bethlehem XX2L30D Mid Radius	0.01	0.037	0.010
Bethlehem XX2L30D Surface	0.01	0.018	0.012



Both samples meet the chemical specification of HF-1 steel. Both steel samples show slight carbon and sulfur segregation.

Segregation:

In order to determine the segregation of both samples, billet sections from both heats were compared to macrographs in MIL-STD-1459A. Both samples were classified as acceptably sound steel. The macrographs are contained in Appendix A for comparison.

The segregation ratings for the subject steel are shown in Table 3. The ratings system consists of an alpha character and a numeral. A - designates center defects; B - subsurface; C - Ring; D - miscellaneous defects. The number designates the severity of the defect, progressing from one to seven, seven being the most severe. Any defect in the D series, except D-2, can be cause for rejection of the steel.

Both samples were etched in a solution of 50% hydrochloric acid and 50% water at 170°F after both samples were ground. Upon comparison with the MIL standard, both were rated as clean and sound.

TABLE 3 - SEGREGATION EVALUATION

Bethlehem Steel	B2	C1	A2
Crucible Steel	B2	C2	A3

Hardenability:

No hardenability data was available for either sample.

BILLET CROSS SECTION HARDNESS PATTERN

A 10 x 10 grid of 1/2 inch squares was inscribed on the Crucible Steel section and a 9 x 9 grid was inscribed on the Bethlehem Steel section. Hardness readings were taken in the Rockwell C range and are reported in Table 4. Actual hardness patterns are included in Appendix B.

TABLE 4 - HARDNESS PATTERN

	<u>RC Mean</u>	<u>BHN</u>
Bethelehm Steel	29.4	280
Cricible Steel	30.2	287



INCLUSIONS (Microcleanliness)

Both samples were evaluated with a Scanning Electron Microscope and EDAX analysis.

TABLE 5 - INCLUSION RATING

	<u>Manganese Sulfide</u>	<u>Calcium Silicate</u>
Bethlehem Steel	2 - Heavy	2 - Heavy
Crucible Steel	1/2 - Thin	1 - Thin

Crucible:

Figure 1 is an SEM photomicrograph of the inclusion from Crucible Steel and Figure 2 in its EDAX evaluation.

CRUCIBLE STEEL

SEM

Inclusion Analysis




Figure 1 - SEM photomicrograph of typical inclusion.
300X

CRUCIBLE STEEL

SEM

EDAX Evaluation of Inclusions




Figure 2 - EDAX Evaluation



Bethlehem Steel:

Figure 3 is an SEM photomicrograph of one type of inclusion found in the sample. It is typical Manganese Sulfide and its EDAX evaluation is depicted in Figure 4.

Figure 5 is an SEM photomicrograph of a round type inclusion. Its EDAX evaluation is illustrated in Figure 6. Its complexity is interesting. It is significantly higher in calcium. This information may be of value when evaluating cause of defects found in the processing stages.

It is thought that the heavier inclusion rating of Bethlehem Steel is due to the difference in melting practice of Bethlehem Steel (BOF) versus Crucible Steel (electric). The difference is not detrimental to obtaining the desired mechanical properties.

MATRIX OF BOTH SAMPLES

Figure 7 is the EDAX evaluation common to both vendors.

FLAME CUT ENDS

Bethlehem Steel flame cut several billets in order to provide sample bars for the contractor to evaluate. One of these flame cut ends was metallographically evaluated and revealed some interesting phenomena. Figure 8 shows the end surface of the billet on the flame cut surface. Figure 9 is the longitudinal section of the cut out in Figure 8. The top area is a layer of white (dendritic) cast iron formed by the absorption of carbon from the torch. The next layer is a section of untempered martensite. In this layer are white areas of retained austenite which are mainly perpendicular to the surface. Special attention should be given to the retained austenite streak in the center of the photomicrograph as it has intergranular cracking propagating from the surface along the austenitic grain boundaries. This crack will never self-weld on forging but will decarburize along its surface and subsequently produce a crack in a forging. Evidence of this was published by the author in a report dated 11 February 1981, entitled "M106, Evaluation of Base Defect".

Figure 10 and 11 are magnified centerline views of the untempered martensite platelets showing unique micro cracking in the platelets.

HEAT TREATMENT

Coupons of both vendors austenitized at 1500°F quenched in oil and tempered at various temperatures. Figures 12 through 15 illustrate the mechanical properties attainable at various tempering temperatures.

BETHLEHEM STEEL
SEM
Inclusion Analysis



Figure 3 - SEM photomicrograph of one type of inclusion.
300X

BETHLEHEM STEEL
SEM
Inclusion Evaluation




Figure 4 - EDAX Evaluation of inclusion.

BETHLEHEM STEEL

SEM




Figure 5 - SEM photomicrograph of a round type of inclusion.
3000X



BETHLEHEM STEEL

SEM

EDAX Analysis of Inclusion




Al Si S Ca Ca Mn Fe Fe

Figure 6 - EDAX Evaluation of complex round inclusion.



BETHLEHEM STEEL
CRUCIBLE STEEL

EDAX Evaluation of Steel Matrix



Si

Mn Fe Fe

Figure 7 - EDAX Evaluation of Matrix common to both vendor material.

BETHLEHEM STEEL

Flame Cut End Evaluation



Figure 8 - Photomicrograph of flame cut surface. 1X

BETHLEHEM STEEL
Flame Cut Evaluation



Figure 9 - Photomicrograph of longitudinal section of flame cut area.
63X

BETHLEHEM STEEL
Flame Cut Evaluation




Figure 10 - Photomicrograph of untempered martensite platelet
with micro-cracks. 500X

BETHLEHEM STEEL

Flame Cut Evaluation



Figure 11 - Photomicrograph of untempered martensite platelets with micro-cracks. 500X



Figure 16 illustrates the compsite of the mechanical properties of the material from the four vendors.

This figure shows that the steel from all four vendors will meet the minimum properties required for his scope of work.

Table 6 is in the mechanical data for both Crucible Steel and Bethlehem Steel (California).

46 1320

KEUFFEL & ESSER CO. MADE IN U.S.A.

% Elong.





Fig. 12 Tempering Temperature (°F)



HF-1 BETHLEHEM - CALIF. MILL

Mechanical Properties

vs.

Temper Temperature

Austenitize - 1500°F

○ Tensile Strength

△ Yield Strength

Quench Temperature 145-150°F

3/4 dia. Test Bars

Longitudinal Coupon

Texquench 500 (A)




Fig. 14

Tempering Temperature (°F)

40-1320

REDFEL & LESSER CO. MADE IN U.S.A.

HF-1 BETHLEHEM - CALIF. MILL
Mechanical Properties
vs.
Temper Temperature
Austenitize - 1500°F
Tensile Strength
Yield Strength
Quench Temperature 145-150°F
3/4 dia. Test Bars
Transverse Coupon
Texquench 500 (A)




Fig. 15

Tempering Temperature (°F)

46 1320

K+S
10 X 10 TO 1/2 INCH 7 X 10 INCHES
KEUFFEL & ESSER CO. MADE IN U.S.A.




Fig. 16

Tempering Temperature (°F)



TABLE 6

HF-1
Crucible Steel

<u>Austenitizing</u> <u>°F</u>	<u>Austenitizing</u> <u>°C</u>	<u>Section</u>	<u>Yield Strength</u> <u>(psi)</u>	<u>Yield Strength</u> <u>(Mpa)</u>	<u>Tensile Strength</u> <u>(psi)</u>	<u>Tensile Strength</u> <u>(Mpa)</u>	<u>Elong.</u> <u>(%)</u>	<u>RA</u> <u>(%)</u>
1000	538	L	152941	1054	195187	1346	6.4	18.7
1125	607	L	126462	872	165461	1141	10.4	26.5
1200	649	L	102863	709	144221	994	12.5	36.0
1300	704	L	96912	668	130990	903	14.0	35.7
1400	760	L	100212	691	141569	976	13.9	37.3
1000	538	T	176653	1218	193905	1337	5.1	5.0
1125	607	T	121406	837	161342	1112	8.6	6.0
1200	649	T	116736	805	151653	1045	11.0	14.8
1300	704	T	98140	677	130269	898	9.5	32.8
1400	760	T	94008	648	129132	890	8.0	6.1

HF-1
Bethlehem Steel (California)

<u>Austenitizing</u> <u>°F</u>	<u>Austenitizing</u> <u>°C</u>	<u>Section</u>	<u>Yield Strength</u> <u>(psi)</u>	<u>Yield Strength</u> <u>(Mpa)</u>	<u>Tensile Strength</u> <u>(psi)</u>	<u>Tensile Strength</u> <u>(Mpa)</u>	<u>Elong.</u> <u>(%)</u>	<u>RA</u> <u>(%)</u>
1000	538	L	149861	1033	193872	1337	6.9	13.8
1125	607	L	120873	833	167320	1153	11.0	24.7
1200	649	L	114400	789	157655	1087	11.5	22.7
1300	704	L	106180	732	129213	891	15.0	36.3
1400	760	L	95696	660	146055	1007	12.8	30.8
1000	538	T	149793	1033	162500	1120	5.1	4.3
1125	607	T	120582	831	141580	976	5.9	4.8
1200	649	T	111570	769	151343	1043	7.7	6.5
1300	704	T	101064	697	125851	868	11.1	16.6
1400	760	T	94595	652	132640	914	8.8	7.8



AUSTENITIC GRAIN SIZE

TABLE 7 - ASTM AUSTENITIC GRAIN SIZE

Crucible Steel	-	No. 4
Bethlehem Steel	-	No. 4

Photomicrographs are included in Appendix C.

CONCLUSION:

The following conclusions are a composite of those from the initial report and this supplemental report:

1. There is no significant difference between box-cooled or furnace-cooled material.
2. Material from all four sources will meet the desired mechanical properties.
3. Flame cutting must be forbidden.
4. HF-1 must be tempered immediately after quenching.
5. Severe surface conditioning by grinding is unacceptable.
6. All four heats of steel met the current specification (MIL-S-50783).



APPENDIX A

Photographs of Macro Cleanliness



MACRO CLEANLINESS

CRUCIBLE STEEL




Figure 17 - Macro etched section of Crucible Steel billet.

1X



MACRO CLEANLINESS

BETHLEHEM STEEL




Figure 18 - Macro etched section of Bethlehem Steel billet.
IX



APPENDIX B

Billet Cross Section Hardness Pattern

REVISIONS				
SYM.	DESCRIPTION	BY	DATE	APPR.

27.7	29.3	29.3	30.1	29.6	30.3	29.4	31.5	30.7
28.8	28.3	30.7	29.9	30.0	31.6	29.5	29.0	30.5
28.0	29.2	28.6	30.0	30.4	30.2	30.3	28.5	30.8
27.6	28.6	29.2	29.5	29.3	29.1	30.8	28.4	29.9
28.1	27.9	28.7	29.4	28.5	30.5	28.4	29.2	30.0
29.0	28.0	28.6	28.6	29.2	29.1	26.7	29.4	29.1
29.0	28.1	30.0	29.7	29.0	30.1	28.2	29.6	29.0
29.9	29.8	30.6	29.6	29.8	28.7	29.2	29.1	29.3
29.2	29.8	29.6	29.4	29.4	28.7	29.9	29.7	30.1

Average (81 reads) — 29.35 R_c

Standard Deviation ± 0.8895

TEST BLOCK (35.0 ± 1.0) — 34.6 R_c

Bethlehem Steel-California


TOLERANCES UNLESS OTHERWISE SPECIFIED		 Chamberlain Chamberlain Manufacturing Corporation Scranton Army Ammunition Plant			
.000	± .005				
.00	± .010	TITLE			
.0	± .020	BILLET			
FRAC.	± 1/32	DRN.	S. C.	DATE 5-7-81	SCALE FULL
ANGLE	± 1°	CXD.			
		APPD.			

Figure 19. Bethlehem Steel Cross Section Hardness Patterns

REVIS.JNS

SYM.	DESCRIPTION	BY	DATE	APPR.

30.8	31.7	29.3	30.3	31.1	31.5	30.8	29.6	30.5	31.3
31.4	30.7	30.9	31.0	30.6	30.8	31.2	30.6	30.2	31.0
31.7	30.6	30.5	30.5	30.7	30.9	31.0	30.5	31.0	30.9
30.5	31.1	30.8	30.9	31.1	30.8	31.2	30.9	30.7	30.7
30.6	31.1	30.5	30.8	31.1	30.6	31.2	30.8	30.9	30.4
30.3	30.5	30.9	30.2	30.5	31.0	30.3	30.9	30.5	30.7
31.4	30.2	30.7	29.5	30.1	29.7	28.4	28.8	29.8	30.5
30.0	30.0	30.2	30.2	29.2	28.4	28.6	29.3	29.9	30.4
29.1	29.6	29.5	29.9	29.3	29.3	30.1	29.7	29.6	30.3
28.9	29.2	29.5	29.4	29.9	29.9	29.3	28.9	29.5	29.6
29.5	28.6	28.8	28.9	29.9	29.5	29.8	29.5	28.9	29.7

Rockwell Test Block
 @ 35.0 ± 1.0 Rc
 5-7-81 35.0 (5 Tests)

Mean 30.225 Rc
 σ 0.7849

Crucible Steel


TOLERANCES UNLESS OTHERWISE SPECIFIED	.000	± .005	 Chamberlain Chamberlain Manufacturing Corporation Scranton Army Ammunition Plant
	.00	± .010	
	.0	± .020	
	FRAC.	± 1/32	
	ANGLE	± 1°	
TITLE			BILLET
DRM.		L J F	DATE 5 22 81
CKD.			SCALE FULL
APPD.			

Figure 20. Crucible Steel Cross Section Hardness Patterns.



APPENDIX C
ASTM GRAIN SIZE

ASTM GRAIN SIZE

BETHLEHEM STEEL




Figure 21 - ASTM Grain size of Bethlehem Steel material.
125X

ASTM GRAIN SIZE

CRUCIBLE STEEL




Figure 22 - ASTM Grain Size of Crucible Steel material.
125X

DISTRIBUTION

Commander

U. S. Army Armament Research and Development Command
ATTN: DRDAR-TSS (5) (Building 59)
DRDAR-CGL (1) (Building 3)
DRDAR-LCU-M (20)
DRCPM-PBM-MA (2)
DRDAR-QAR-Q (1)
Dover, NJ 07801

Administrator

Defense Technical Information Center
ATTN: Accessions Division (2)
Cameron Station
Alexandria, VA 22314

Director

U. S. Army Materiel Systems Analysis Activity
ATTN: DRXSY-MP
Aberdeen Proving Ground, MD 21005

Commander/Director

Chemical Systems Laboratory
U. S. Army Armament Research and Development Command
ATTN: DRDAR-CLJ-L
DRDAR-CLB-PA
APG, Edgewood Area, MD 21010

Director

Ballistics Research Laboratory
U. S. Army Armament Research and Development Command
ATTN: DRDAR-TSB-S
Aberdeen Proving Ground, MD 21005

Chief

Benet Weapons Laboratory, LCWSL
U. S. Army Armament Research and Development Command
ATTN: DRDAR-LCB-TL
Watervliet, NY 12189

Commander

U. S. Army Armament Materiel Readiness Command
ATTN: DRSAR-LEP-L
Rock Island, IL 61299

Director

U. S. Army TRADOC Systems Analysis Activity
ATTN: ATAA-SL
White Sands Missile Range, NM 88002