


ARMY RESEARCH LABORATORY



# A Proposal for an Active/Passive Signature Enhancer for Identification Friend-or-Foe

by Marcos C. Sola, E. Glenn Dockery, Joseph A. Penn, Paul L. Zirkle  
Charles R. Kohler, Teresa A. Kipp, and Janice F. Colby

ARL-TR-1377

October 1997

19971202 021

DTIC QUALITY INSPECTED 8

Approved for public release; distribution unlimited.

Reproduced From  
Best Available Copy

---

The findings in this report are not to be construed as an official Department of the Army position unless so designated by other authorized documents.

Citation of manufacturer's or trade names does not constitute an official endorsement or approval of the use thereof.

Destroy this report when it is no longer needed. Do not return it to the originator.

---

# Army Research Laboratory

Adelphi, MD 20783-1197

---

ARL-TR-1377

October 1997

---

## A Proposal for an Active/Passive Signature Enhancer for Identification Friend-or-Foe

Marcos C. Sola, E. Glenn Dockery, Joseph A. Penn, Paul L. Zirkle, Charles R. Kohler, Teresa A. Kipp, and Janice F. Colby  
Sensors and Electron Devices Directorate

THIS QUANTITY INDICATED 3

---

Approved for public release; distribution unlimited.

---

---

---

## Abstract

---

A major factor in the U.S. casualties during Operation Desert Storm was friendly fire. To minimize fratricide, signature tags on Blue (friendly) Force weapon platforms were used to enhance the level of acquisition of night-vision devices. These signature enhancements, however, could also be an excellent cue to the enemy and could result in increased Blue Force casualties. This report discusses the use of optical augmentation (OA) in conjunction with an active/passive signature enhancer (APSE) for identification friend-or-foe (IFF).

For military use, the APSE, interrogated with OA sensors on a platform such as a reconnaissance helicopter, will allow positive IFF between opposing forces at tactical range. In addition, due to the directional nature of the APSE reflection, the Red (enemy) Force, would not be able to intercept the reflected laser energy from the APSE unless the enemy is directly close along the optical path of the laser beam.

The APSE used with night-vision sensors could also have nonmilitary applications such as helping law enforcement officials with nighttime raids and assisting search-and-rescue personnel in missions to help vessels in distress. Whether for a military or nonmilitary application, the use of the APSE in conjunction with the appropriate devices will enhance positive identification and will allow for shorter detection times, which translates into saving lives and property.

## Contents

1. Background .....	1
2. Sensors .....	1
3. Hunter-Liggett Demonstration .....	1
4. Demonstration for the U.S. Coast Guard .....	5
5. Military Use .....	7
6. Recommendations .....	9
Acknowledgments .....	9
References .....	9
Distribution .....	11
Report Documentation Page .....	15

## Figures

1. Foxfire 1 system: AN/TVS-6, Night Observation Device, Long-Range (NODLR) with CO <sub>2</sub> laser and Foxfire 2: AN/TVS-5, Crew Serve Weapon System (CSWS) with GaAlAs laser .....	2
2. Dismounted TOW missile system without tube launcher .....	3
3. Passive-mode Foxfire 2 system image of a hill at 4.3 km distance with targets .....	4
4. Retroreflection from target seen by Foxfire 2 sensor .....	4
5. View of image intensifier located by Foxfire 2 system .....	4
6. Views through infrared imaging system with and without the active source (CO <sub>2</sub> ) .....	6
7. Configuration of higher fidelity active/passive signature enhancer .....	6
8. Simulated display on board a Scout helicopter .....	8

## Table

1. Attributes of Foxfire 1 and Foxfire 2 .....	2
--	---

# 1. Background

Retroreflection, also referred to as optical augmentation (OA), is a technique used for detecting electro-optical (EO) sensors. In a military application, this is done by using an imaging system with a co-located, co-boresighted, in-band laser source. The signal reflected from the targeted sensor is the means for detection. An example of this type of detection is the reflection from an animal's eyes of an automobile's headlights at night. This detection technique has military and nonmilitary uses, such as for battlefield identification friend-or-foe (IFF) or for a search-and-rescue mission of vessels in distress in a littoral environment. This report discusses the results of two field demonstrations and a computer-simulated study and the use of this detection technique in conjunction with an active/passive signature enhancer (APSE) for dual-use technology.\*

# 2. Sensors

For OA to occur, the in-band laser is co-located and co-boresighted with an imaging sensor, and there must be at least a partial alignment between the search sensor and the targeted sensor. The size of the return signal due to OA is a function of the optical cross section of the targeted sensor, the alignment between the targeted and search sensor, the laser power, the range to target, and the intervening atmosphere (which may be natural, artificially generated, or both).

The two prototype sensor systems that we used were designed and put together by the Army's Night Vision and Electro-Optics Laboratory.<sup>†</sup> The systems are called Foxfire 1 and Foxfire 2. Foxfire 1 is a first-generation forward-looking infrared (FLIR) sensor coupled with a carbon dioxide (CO<sub>2</sub>) laser, and Foxfire 2 is an image intensifier coupled with a gallium aluminum arsenide (GaAlAs) laser. (See fig. 1 and table 1.) All the parts of the systems are commercially available to authorized purchasers.

# 3. Hunter-Liggett Demonstration

In the summer of 1985, the Survivability Management Office of the Laboratory Command (LABCOM), now the Army Research Laboratory, led a piggyback experiment with the support of the Night Vision and Electro-Optics Laboratory in a field test called Thermal Pin Point.<sup>‡</sup> Simultaneous imageries were recorded with both Foxfire systems. Several targets were

\*Presented by Marcos C. Sola, Army Research Laboratory, at the 1997 Joint Services Combat Identification Systems Conference, Coronado Naval Amphibious Base, San Diego, Ca (15-17 April 1997).

<sup>†</sup>Prototype sensors furnished by the Army's Night Vision and Electro-Optics Laboratory (W. Trussel and C. Fox) under the Optical Improvement Program, 1985).

<sup>‡</sup>Thermal Pin Point, Hunter-Liggett, CA, July 1985, piggyback experiment by Marcos C. Sola, Survivability Management Office, with assistance from David Curran, NVEOL.




Figure 1. (a) Foxfire 1 system: AN/TVS-6, Night Observation Device, Long-Range (NODLR) with CO<sub>2</sub> laser and (b) Foxfire 2: AN/TVS-5, Crew Serve Weapon System (CSWS) with GaAlAs laser.

Table 1. Attributes of Foxfire 1 and Foxfire 2.

Foxfire 1	
AN/TVS-6 (NODLR)	CO <sub>2</sub> laser
Spectral band = 8-12 μm	Wavelength = 10.6 μm
NFOV = 1.1° × 2.3°	Beam divergence = 20 mr
WFOV/NFOV = 3	Peak power = 20 W
Magnification = 9	(Average measured power = 1 W)
	Pulsed: No
	Duty cycle: n/a
	Pulse width: n/a
Foxfire 2	
AN/TVS-5 (CSWS)	GaAlAs laser
Spectral band = 0.4-0.9 μm	Wavelength = 0.83 μm
NFOV = 9°	Beam divergence = 20 mr (variable)
WFOV/NFOV = 1	Peak power = 100 mW
Magnification = 6	(Average measured power = 20 mW)
	Pulsed: 6 Hz
	Duty cycle: 30%
	Pulse width: 50 ms

NFOV = narrow field of view; WFOV = wide field of view.

placed 4.3 km from the search sensors. The targets were a 2-in. corner cube; a 4-in. corner cube; a Foxfire 2 system; and a dismounted tube-launched, optically tracked, wire-guided (TOW) missile system without the tube launcher (see fig. 2).

This demonstration was conducted at night with visibility greater than 6 km. This was a field demonstration of a concept and not a field

Figure 2. Dismounted TOW missile system without tube launcher.



experiment. Imposing the Signature Quality Metrics [1] requirement was not adhered to in order to save money and personnel resources. Figure 3 is an image of the hill where the targets were located as seen by the Foxfire 2 system in the passive mode.

The user of each sensor system was asked to search a field of regard (FOR) of approximately  $90^\circ$ . At this range, the targets that were used were well beyond the resolution capability of either system. When the systems' lasers were activated, however, they created a footprint of approximately 9 m in diameter, and the targets were located in a matter of seconds. Figure 4 shows retroreflection from all four targets. The second target from the left is a Foxfire 2 system that is active and has a partial co-alignment with the search sensor. A drawback of this technique is the detection of the laser beam by an enemy's passive in-band sensor; survivability of the passive sensor can be increased by the use of reflecting surfaces as decoys to increase false alarm rate. Therefore, the use of our detection technique would be better suited for an attacking force (e.g., a small flotilla raiding a coastal area, drug agents in a convoy attacking a drug laboratory, or a mechanized unit assaulting a hill) where the main concern of the attacking force is ambush because its location is already known by the enemy, either due to its size or to strategic placement of surveillance sensors. In this demonstration, there was sufficient return signal from both prototype sensors such that the source-to-target sensor separation distance could have been increased. However, the physical terrain did not permit us to extend our line of sight (LOS) requirement.

Figure 5 is a view seen by the passive targeted sensor when it is identified by the search sensor (Foxfire 2). Even with the low-level laser power associated with this system, the search sensor was able to dazzle the targeted sensor to where it could not produce any useful image for acquisition. (The grids are the fixed-pattern noise of the microchannel plate.)

Figure 3. Passive-mode Foxfire 2 system (image intensifier) image of a hill at 4.3 km distance with targets (Hunter-Liggett demonstration).




Figure 4. Retroreflection from target seen by Foxfire 2 sensor. Four targets are located on a hill at 4.3 km distance (Hunter-Liggett demonstration).





Figure 5. View of image intensifier located by Foxfire 2 system. Note that targeted sensor is "dazzled"; thus no useful target acquisition could be made (Hunter-Liggett demonstration).



## 4. Demonstration for the U.S. Coast Guard

As part of the dual-use-technology approach, we demonstrated that this detection technique could be used in conjunction with an APSE to perform a search-and-rescue (SAR) mission in a littoral environment. We thought that this combination of techniques would prove to be beneficial because it would provide positive identification, reduce the time needed to find a vessel in distress in a crowded or target-rich environment, and minimize the on-the-scene time that SAR personnel would need for their work at a possibly dangerous site. Achieving these results should not only save lives and property, but also save taxpayers' dollars. The nighttime demonstration was done on 11 July 1995, at Gunston Cove, FT Belvoir, VA.\* Figures 6 (a) and 6 (b) are views through the FLIR sensor and were taken from atop the Night Vision and Electronic Sensors Directorate building—the location of the search sensors. Figures 6 (a) and 6 (b) are views through an infrared imaging system with (6 (a)) and without (6 (b)) the active source ( $\text{CO}_2$ ) overlooking Gunston Cove, FT Belvoir, VA. This view shows part of the FOR in the search for two vessels that were supplied by Flotilla 29, Division II, 5th District, U.S. Coast Guard Auxiliary. Both vessels were certified as operational facilities by the U.S. Coast Guard. They were both 24-ft cabin cruisers with single inboard/outboard engines. The lead vessel—auxiliary vessel 24833—had an APSE mounted on its stern. The visibility for the APSE was  $\pm 135^\circ$  from dead stern. Following the lead vessel was auxiliary vessel 24498. It had reflector tape on the port and starboard sides of its cabin.

One vessel was used as a baseline and the other was “jury-rigged” with an APSE. Simultaneous recordings of the targets were done with Foxfire 1 and 2 systems mounted on a common tripod. This insured that whatever scenario one system was looking at, the other system would see almost the same view (allowing for differences in each system's field of view). For this demonstration, the range was limited, and the targets were never beyond the resolution and sensitivity range of the imaging sensors. Maximum range obtained for this demonstration was about 1 nautical mile, due again to the need for LOS and the constraint imposed by the treelines on the shore in some parts of the FOR search.

In order to ensure a positive, distinct signal return from the APSE, a higher-fidelity diagram is proposed as shown in figure 7 [2]. Two concentric spheres of radius  $R_1$  and  $R_2$  are shown with the corner cubes (C) of a given aperture  $A_c$  placed along the inner sphere, with the corner cube separation of  $S_c$ . For each corner cube, a baffle of length  $B_d$  is created. The baffle length equals the distance between  $R_2$  and  $R_1$ . This signal allows for a unique or coded return when placed along a chosen lateral plane of the sphere perpendicular to its rotation. The sphere in this figure is rotating with an angular velocity  $\omega$  coming normal from the paper. There is a

\*Demonstration by M. Sola and E. G. Dockery, ARL, and Flotilla 29, Division II, 5th District, U.S. Coast Guard Auxiliary for U.S. Coast Guard, Research and Development Center Chief Scientist (Q. Robt), FT Belvoir, VA (11 July 1995).

Figure 6. Views through infrared imaging system (a) with and (b) without the active source (CO<sub>2</sub>).





Figure 7. Configuration of higher fidelity active/passive signature enhancer.



protective cover  $P_c$  with a wide dynamic transparent range to the incident laser energy wavelength ( $\lambda_i$ ) that is coming from the source weapon platform. This cover protects the corner cubes from any debris that would damage their reflective property.

The number of positive, distinct codes that can be created for a fixed angular frequency is optimized by the selection of the size and number of the corner cubes, the corner cube separation distance along the lateral plane (normal to vertical rotation) of the inner sphere, and the baffle length.

Additional codes could be added to the above for integral number ( $n \times \omega$ ) of the angular frequency, where  $n = 1, 2, 3, \dots$ .

For nonmilitary applications such as SAR in a target-rich littoral environment, rotation of the sphere in the horizontal axis may provide an ac signal, provided there is enough contrast in the vertical (for example, sky versus water) in terms of light level or temperature difference, depending on the passive sensor (without the illuminator) that is in use. If the sphere is not rotating, the wave action could provide for a twinkling effect when viewed by sensors with illuminators, which is a good cue to the observer even if the ac signal-to-noise ratio is low against a predominantly dc background.

Removal of personnel from a vessel in distress in the dark and in heavy seas poses a danger for the SAR personnel. With the APSE, a Coast Guard helicopter pilot could receive coded signals. These signals could provide the pilot with a very good idea of the condition of the sea and its roughness.

The APSE mounted on Drug Enforcement Agency (DEA) vehicles could track the DEA vehicles and distinguish them from drug traffickers' vehicles in the case of multiple engagements. Mounted on small boats, the APSE would allow the law enforcement vessels that were performing interdiction of illegal aliens in the U.S. littoral environment to be tracked and vectored to proper targets.


## 5. Military Use

A major factor in the U.S. military casualties during Operation Desert Storm was friendly fire. To minimize fratricide, signature tags on Blue (friendly) weapon platforms were used to enhance the level of acquisition of night-vision devices (FLIRs or image intensifiers). These signature tags included rotating hot plates, thermal tapes, and/or luminescent strips for IFF that were placed on weapon platforms. These signature enhancements, however, could also be an excellent cue to the enemy if it had comparable night-vision devices. If the enemy also had the capability of attacking any target that it acquired, this could result in increased friendly force casualties. The use of the APSE and OA sensors would mitigate fratricide and inadvertent detection by the enemy.

To demonstrate the feasibility of this concept, we used a high-resolution synthetic scene generator model (SSGM) called CREATION [3], in lieu of the more expensive Advanced Concept Field Demonstration. Some of the attributes of CREATION for concept demonstration are portrayal of the type of sensor planned for use, multispectral target signature, terrain/background, and atmospheric environment, including smoke/obscurant. A generic approach to validation of any SSGM and in particular of the CREATION model is in progress [4]. Figure 8 (a) shows a simulated display onboard a Scout (reconnaissance) helicopter at stand-off range where it is safe from a tank gun or antitank missile. Although the targets are recognizable and within the tactical range of an attack helicopter's weapons, the problem is that the helicopter's pilot needs to distinguish friend from foe. As shown in figure 8 (b), the friendly forces are immediately identified when the laser is turned on. (The Scout helicopter can then pass this information to an Apache (attack) helicopter, which attacks the target.) Thus, the APSE allows for positive identification of friendly forces and platforms at distances that are greater than the detection range of a passive sensor.

The amount and type of smoke/obscurant that would defeat an onboard FLIR or image intensifier can be simulated by the CREATION model. Calculations were actually performed for various EO near- and far-infrared sensors and laser guidance systems as a function of weather, season, environment, geography, and types of smoke [5].

Figure 8. Simulated display on board a Scout helicopter:  
(a) ground targets are recognized as tanks, but are not identified as friend or foe and  
(b) Scout helicopter activates Foxfire 1 system and identifies two tanks (upper right-hand corner) as friendly forces.



## 6. Recommendations

One conclusion from the CISC-97 Conference is that there is no "silver bullet" that would completely solve the fratricide problem. The signature enhancer along with the OA sensors discussed in this report can be used in conjunction with other IFF devices to mitigate fratricide. The ARL high-resolution synthetic scene rendering model CREATION, can be used to simulate and analyze future IFF concepts before actual field demonstrations, thus saving dollars and resources.

## Acknowledgments

The work done in the U.S. Coast Guard demonstration would not have been possible without the assistance of the Army's Night Vision and Electronic Sensors Directorate personnel, in particular, Ken Miller and Jaime Gonzalez. They provided ARL with the free use of the Directorate's prototype sensors, laser tunnel facility, and the observation platform in its main building. Special thanks goes to Quochien Vuong, Martin Lahart, Khang Bui, and Matthew Thielke of ARL for providing the graphics and a technical review of this report. We would also like to thank Deborah Lehtinen, Maurice Sheppard, and Bill Woodbridge of ARL's Technical Publishing Branch for their help in editing and preparing this document.

## References

1. Andrew Zembower/IITRI and Marcos C. Sola/S3TO, *Signature Quality Metrics*, Eleventh Annual Ground Vehicle Symposium, Keweenaw Research Center, Michigan Technical University, Houghton, MI (22-24 August 1989).
2. Marcos C. Sola, *Active/Passive Signature Enhancer*, Patent Application, Army Research Laboratory Docket 96-34 (26 October 1996).
3. Joseph A. Penn, H. Nguyen, M. Sola, C. Kohler, J. Weber, and S. Hawley, *The CREATION Scene Modeling Package Applied to Theater Air Defense Fire Control Situations*, Proceedings of the 1995 National Fire Control Symposium, Monterey, CA (31 July-3 August 1995).
4. Marcos C. Sola, Mark W. Orletsky, Quochien B. Vuong, and Charles R. Kohler, Army Research Laboratory, *Proposal for Validation of a Multispectral Synthetic Scene Generator Model*, Proceedings of the 1996 Battlespace Atmospheric Conference, Naval Command, Control and Ocean Surveillance Center, San Diego, CA (3-5 December 1996).
5. Marcos C. Sola, Nicholas A. Diakides, and Francis M. Manion, Survivability Management Office, *Obscurant Susceptibility Analysis of EO Sensors*, LABCOM-SR-86-1 (June 1986).

## Distribution

Admnstr  
Defns Techl Info Ctr  
Attn DTIC-OCP  
8725 John J Kingman Rd Ste 0944  
FT Belvoir VA 22060-6218

Defns Intel Agency  
Attn CMO-2 J Glover-Jones  
Bolling AFB  
Washington DC 20340

Natl Ground Intel Ctr  
Attn IANG-RSG B Reinhold  
220 Seventh Stret  
Charlottesville VA 22902-5396

Ofc of the Dir Rsrch and Engrg  
Attn R Menz  
Pentagon Rm 3E1089  
Washington DC 20301-3080

Ofc of the Secy of Defns  
Attn DASD/C3I B Leong-Hong  
The Pentagon Rm 3D228  
Washington DC 20301-7100

Ofc of the Secy of Defns  
Attn ODDRE (R&AT) G Singley  
Attn ODDRE (R&AT) S Gontarek  
The Pentagon  
Washington DC 20301-3080

OSD  
Attn OUSD(A&T)/ODDDR&E(R) J Lupo  
Attn OUSD(A&T)/ODDDR&E(R) S Ahmadi  
Washington DC 20301-7100

CECOM  
Attn PM GPS COL S Young  
FT Monmouth NJ 07703

CECOM RDEC Elect System Div Dir  
Attn J Niernela  
FT Monmouth NJ 07703

CECOM  
Sp & Terrestrial Commctn Div  
Attn AMSEL-RD-ST-MC-M H Soicher  
FT Monmouth NJ 07703-5203

Dpty Assist Secy for Rsrch & Techl  
Attn SARD-TR R Chait Rm 3E476  
Attn SARD-TT D Chait  
Attn SARD-TT F Milton Rm 3E479  
Attn SARD-TT K Kominos  
Attn SARD-TT R Reisman  
Attn SARD-TT T Killion  
The Pentagon  
Washington DC 20301-0103

Hdqtrs Dept of the Army  
Attn DAMO-FDT D Schmidt  
400 Army Pentagon Rm 3C514  
Washington DC 20301-0460

Night Vision & Elec Sensors Dir  
Attn AMSEL-RD-NV-LWS D Jenkins  
Attn AMSEL-RD-NV-OD J Ratches  
Attn AMSEL-RD-NV-OV C Fox  
Attn AMSEL-RD-NV-OV J Pollard  
Attn AMSEL-RD-NV-RPFS-PE D Currance  
Attn AMSEL-RD-NV-RPFS-PE J Gonzalez  
Attn AMSEL-RD-NV-RPFS-PE J Miller  
Attn AMSEL-RD-NV-RPFS-PE W Stump  
Attn AMSEL-RD-NV-ST-LT W Trussell  
10221 Burbeck Rd Ste 430  
FT Belvoir VA 22060-5806

US Army Matl Cmnd  
Dpty CG for RDE Hdqtrs  
Attn AMCRD BG Beauchamp  
5001 Eisenhower Ave  
Alexandria VA 22333-0001

US Army Matl Cmnd  
Prin Dpty for Acquisition Hdqtrs  
Attn AMCD CG-A D Adams  
5001 Eisenhower Ave  
Alexandria VA 22333-0001

US Army Matl Cmnd  
Prin Dpty for Techlgy Hdqtrs  
Attn AMCD CG-T M Fisette  
5001 Eisenhower Ave  
Alexandria VA 22333-0001

US Army Spc and Strat Defns Cmnd  
Attn CSSD-SD-T B Rogers  
Huntsville AL 35807-3801

## Distribution

US Military Academy  
Dept of Mathematical Sci  
Attn MAJ D Engen  
West Point NY 10996

USA STRICOM PMITTS, TMO  
Attn AMCPM-ITSS-QG M Haack  
Redstone Arsenal AL 35898-7458

USAASA  
Attn MOAS-AI W Parron  
9325 Gunston Rd Ste N319  
FT Belvoir VA 22060-5582

Nav Surface Warfare Ctr  
Attn Code 723 P Ostroski  
Carderock Div  
Bethesda MD 20084-5000

Nav Surface Warfare Ctr  
Attn Code B07 J Pennella  
17320 Dahlgren Rd Bldg 1470 Rm 1101  
Dahlgren VA 22448-5100

NAWCPNS  
Attn Code 4KM400E P Yu  
521 9th Stret  
Point Mugu CA 93042-5001

Ofc of Nav Intel  
Attn ONI-235 J D Camp  
4251 Suitland Rd  
Washington DC 20395-5720

GPS Joint Prog Ofc Dir  
Attn COL J Clay  
2435 Vela Way Ste 1613  
Los Angeles AFB CA 90245-5500

Joint Munitions Test & Eval Program  
Attn 46 OG/OGML M Heard  
Eglin AFB FL 32542

Marine Corps Intelligence Activity  
Attn MCIA 104 B Wong  
3300 Russell Rd Ste 250  
Quantico VA 22314

Special Assist to the Wing Cmndr  
Attn 50SW/CCX Capt P H Bernstein  
300 O'Malley Ave Ste 20  
Falcon AFB CO 80912-3020

US Air Force  
Attn 46 TW/OL-AG LT COL L Palmer  
MZ2161 Box 731  
FT Worth TX 76101-0371

US Coast Guard Auxiliary  
Attn Flotilla 29, FSO-OP M Arnold  
9226 Riverside Dr  
FT Washington MD 20744

US Coast Guard Auxiliary  
Attn Flotilla 29, INST M Sola  
8012 Vernon Dr  
FT Washington MD 20744

US Coast Guard Auxiliary  
Attn Flotilla 29, FC G Yardborough  
7008 Leyte Dr  
Oxon Hill MD 20745

US Coast Guard Hdqtrs  
Attn C Hover  
Attn Q Robe  
10892 Shennecossett Rd  
Groton CT 06340-6096

US Coast Guard Hdqtrs  
Attn CHDIRAUX CAPT A D Summy  
Attn GP-OPR LT R Patton  
2100 Second Stret SW  
Washington DC 20593-0001

US Coast Guard R&D Ctr  
Attn 5th Coast Guard District  
431 Crawford Stret  
Portsmouth VA 23704-5004

DARPA  
Attn B Kaspar  
Attn L Stotts  
3701 N Fairfax Dr  
Arlington VA 22203-1714

NASA Goddard Spc Flight Ctr  
Attn Code 480 R Wallace  
Greenbelt MD 20771

ARL Electromag Group  
Attn Campus Mail Code F0250 A Tucker  
University of Texas  
Austin TX 78712

## Distribution

Computer Sci Corp System Sci Div  
Attn B Trudell  
10101 Senate Dr  
Lanham MD 20706

DOT&E-1700  
Attn A Manriquez  
Pentagon Rm 3E333  
Washington DC 20301-1700

US Army RsrchLab  
Attn BED IS&TD R Shirkey  
Attn SLAD C R Cundiff  
White Sands Missile Range NM 88002

US Army Rsrch Lab  
Attn AMSRL-CI-LI Techl Lib (3 copies)  
Attn AMSRL-CS-AL-TA Mail & Records  
Mgmt  
Attn AMSRL-CS-AL-TP Techl Pub (3 copies)  
Attn AMSRL-SE J M Miller  
Attn AMSRL-SE-E J Pellegrino  
Attn AMSRL-SE-SE M Sola (10 copies)  
Attn AMSRL-SE-RS A Sindoris  
Adelphi MD 20783-1197

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188	
<small>Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing the burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.</small>				
1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE October 1997	3. REPORT TYPE AND DATES COVERED Final, March 1996 to December 1996	
4. TITLE AND SUBTITLE A Proposal for an Active/Passive Signature Enhancer for Identification Friend-or-Foe			5. FUNDING NUMBERS PE: 61102A	
6. AUTHOR(S) Marcos C. Sola, E. Glenn Dockery, Joseph A. Penn, Paul L. Zirkle, Charles R. Kohler, Teresa A. Kipp, and Janice F. Colby				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army Research Laboratory Attn: AMSRL-SE-SI 2800 Powder Mill Road Adelphi, MD 20783-1197			8. PERFORMING ORGANIZATION REPORT NUMBER ARL-TR-1377	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) U.S. Army Research Laboratory 2800 Powder Mill Road Adelphi, MD 20783-1197			10. SPONSORING/MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES AMS code: 611102.305 ARL PR: 7NEON1				
12a. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution unlimited.			12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words)  A major factor in the U.S. casualties during Operation Desert Storm was friendly fire. To minimize fratricide, signature tags on Blue (friendly) Force weapon platforms were used to enhance the level of acquisition of night-vision devices. These signature enhancements, however, could also be an excellent cue to the enemy and could result in increased Blue Force casualties. This report discusses the use of optical augmentation (OA) in conjunction with an active/passive signature enhancer (APSE) for identification friend or foe (IFF).  For military use, the APSE, interrogated with OA sensors on a platform such as a reconnaissance helicopter, will allow positive IFF between opposing forces at tactical range. In addition, due to the directional nature of the APSE reflection, the Red (enemy) Force, would not be able to intercept the reflected laser energy from the APSE unless the enemy is directly close along the optical path of the laser beam.  <div style="text-align: right;">(cont'd on reverse)</div>				
14. SUBJECT TERMS IFF, OA, FLIR, CREATION, image intensifier, signature, fratricide			15. NUMBER OF PAGES 20	
			16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT Unclassified	18. SECURITY CLASSIFICATION OF THIS PAGE Unclassified	19. SECURITY CLASSIFICATION OF ABSTRACT Unclassified	20. LIMITATION OF ABSTRACT UL	

---

13. Abstract (cont'd)

The APSE used with night-vision sensors could also have nonmilitary applications such as helping law enforcement officials with nighttime raids and assisting search-and-rescue personnel in missions to help vessels in distress. Whether for a military or nonmilitary application, the use of the APSE in conjunction with the appropriate devices will enhance positive identification and will allow for shorter detection times, which translates into saving lives and property.

---

## **REPRODUCTION QUALITY NOTICE**

We use state-of-the-art high speed document scanning and reproduction equipment. In addition, we employ stringent quality control techniques at each stage of the scanning and reproduction process to ensure that our document reproduction is as true to the original as current scanning and reproduction technology allows. However, the following original document conditions may adversely affect Computer Output Microfiche (COM) and/or print reproduction:

- Pages smaller or larger than 8.5 inches x 11 inches.
- Pages with background color or light colored printing.
- Pages with smaller than 8 point type or poor printing.
- Pages with continuous tone material or color photographs.
- Very old material printed on poor quality or deteriorating paper.

If you are dissatisfied with the reproduction quality of any document that we provide, particularly those not exhibiting any of the above conditions, please feel free to contact our Directorate of User Services at (703) 767-9066/9068 or DSN 427-9066/9068 for refund or replacement.

**END SCANNED DOCUMENT**