



Data Transfer Report - 30-mm Enhanced Alternate High-Energy Propellant Program (EAHEP): Test Fixture and Propellant Evaluation

by Melvin B. Ridgley, Sr.,
and Joseph W. Colburn

ARL-SR-88

January 1999

1
9990224025

Approved for public release; distribution is unlimited.

DISC
UNCLASSIFIED 4

The findings in this report are not to be construed as an official Department of the Army position unless so designated by other authorized documents.

Citation of manufacturer's or trade names does not constitute an official endorsement or approval of the use thereof.

Destroy this report when it is no longer needed. Do not return it to the originator.

Army Research Laboratory

Aberdeen Proving Ground, MD 21005-5066

ARL-SR-88**January 1999**

Data Transfer Report - 30-mm Enhanced Alternate High-Energy Propellant Program (EAHEP): Test Fixture and Propellant Evaluation

Melvin B. Ridgley, Sr., Joseph W. Colburn
Weapons and Materials Research Directorate, ARL

Abstract

Measurements in support of the 30-mm Enhanced Alternate High Energy Propellant Program (EAHEP) were taken at the Building 390 recording facility. Propellants evaluated for this series of tests were M30, U.S. Army Armament Research, Development, and Engineering Center (ARDEC) 7994, BAMO-AMMO/CL20, BAMO-AMMO/CL20/NQ, and BAMO-AMMO-RDX. This facility, the central data acquisition network for the Propulsion and Flight Division (PFD) of the U.S. Army Research Laboratory (ARL), was operated by the Experimental Ballistics Team (EBT) of the Propulsion Branch (PB). The testing was conducted in support of an ongoing Army effort to further investigate high-energy gun propellants that promise enhanced performance from existing tank and artillery systems.

Table of Contents

	<u>Page</u>
1. Background	1
2. Test Objectives	1
3. Summary of Results	1
4. Discussion and Results	3
Appendix A: Experimental Ballistics Team Firing Request	5
Appendix B: Gauge Locations and Range Setup for the 30-mm Gun	9
Appendix C: Tabular Data and Example of Experimental Firing Data	13
Appendix D: Examples of Run Summary and Channel Description/ Calibration Coefficients On Line for the 30-mm Enhanced Alternate High-Energy Program (EAHEP)	23
Appendix E: Analog Tape and Digital Acquisition System Parameters	29
Distribution List	33
Report Documentation Page	35

1. Background

Measurements in support of the 30-mm Enhanced Alternate High-Energy Propellant Program (EAHEP) were taken at the Building 390 recording facility. Propellants evaluated for this series of tests were M30, U.S. Army Armament Research, Development, and Engineering Center (ARDEC) 7994, BAMO-AMMO/CL20, BAMO-AMMO/CL20/NQ, and BAMO-AMMO-RDX. This facility, the central data acquisition network for the Propulsion and Flight Division (PFD) of the U.S. Army Research Laboratory (ARL), was operated by the Experimental Ballistics Team (EBT) of the Propulsion Branch (PB). The testing was conducted in support of an ongoing Army effort to further investigate high-energy gun propellants that promise enhanced performance from existing tank and artillery systems.

2. Test Objectives

The test objectives were to promote the evaluation of novel, high-energy gun propellants that promise enhanced performance from existing tank and artillery systems and to provide a facility that can assess the interior ballistic performance characteristics of small quantities of these propellants. Pertinent test information is detailed on the in-house branch firing request form, Appendix A. Test sample quantities, configurations, and data acquisition inputs were as requested by the project engineer. Appendix B shows a generalized gun configuration and pressure port locations, both in the chamber as well as in the barrel. In addition, it shows the range setup for the test. This report formally documents the data acquired during these tests for further use by the project engineer. Any technical information concerning the test setup or data should be solicited from the project engineer.

3. Summary of Results

A robust and easy-to-use test gun was required for the evaluation of small quantities (up to 125 g) of high-energy solid propellant samples. Due to funding constraints, a test gun was

designed based on available residual 30-mm hardware from a GT Devices (GTD)/General Dynamics Land Systems (GDLS) gun supplemented by existing ARL medium-caliber gun system components and several new parts. Unique features of the design include a simple dependable igniter system, which delivers a smooth ignition pulse to the experimental propelling charge; a robust chamber-tube seal system; and a ring-assisted stub case seal. These features permit safe, easy, and fast turnaround operations with the test gun. This report summarizes the data obtained during proof testing of the gun fixture and the initial propellant evaluation test series.

Experimental firing data and ignition system parameters are tabulated in Appendix C. The instrumentation typically used to acquire data during testing is as follows:

- (1) In-bore doppler radar (35 GHz) to measure the interior ballistic trajectory.
- (2) Discriminator system to measure projectile velocity.
- (3) Kistler 607C3 piezoelectric pressure transducers in gauge positions as shown in Appendix B to measure chamber and barrel pressures.
- (4) Downrange break screens to measure velocity.

Appendix D provides an example of a standard firing program file (FPF) that includes a Run Summary for the 30-mm EAHEP fixture and channel description/calibration coefficients for on-line and analog tape (A) for the EAHEP test rounds. Due to the number of rounds fired in this series, FPFs were not included for each round; however, Appendix E provides a summary of analog tape and digital acquisition system parameters. Twelve channels of data can be acquired on line using BALDAS II. It is standard procedure to back up the data on an analog tape recorder for future use or in case of computer malfunction.

4. Discussion and Results

Table 1 lists the test sequences with comments appropriate to instrumentation problems encountered for each test.

Table 1. Test Sequences and Accompanying Instrumentation Remarks

Test	Date	Comments
19	07 March 1996	EAHEP Gun 1 - M30 Propellant - good data
20	08 March 1996	EAHEP Gun 1 - M30 Propellant - P2L bad microdot cable
21	15 March 1996	EAHEP Gun 1 - M30 Propellant - good data
22	15 March 1996	EAHEP Gun 1 - M30 Propellant - good data
23	18 March 1996	EAHEP Gun 1 - M30 Propellant - good data
24	20 March 1996	EAHEP Gun 1 - M30 Propellant - good data
25	21 March 1996	EAHEP Gun 1 - M30 Propellant - good data
26	22 March 1996	EAHEP Gun 1 - M30 Propellant - good data
27	29 March 1996	EAHEP Gun 1 - Igniter tube integrity test
28	29 March 1996	EAHEP Gun 1 - 7994 ARDEC Propellant - good data
29	02 April 1996	EAHEP Gun 1 - 7994 ARDEC Propellant - good data
30	29 April 1996	EAHEP Gun 1 - 7994 ARDEC Propellant - good data
31	01 May 1996	EAHEP Gun 1 - 7994 ARDEC Propellant - good data
32	01 May 1996	EAHEP Gun 1 - 7994 ARDEC Propellant - good data
33	01 May 1996	EAHEP Gun 1 - 7994 ARDEC Propellant - good data
34	01 May 1996	EAHEP Gun 1 - 7994 ARDEC Propellant - good data
35	22 January 1997	EAHEP Gun 1 - M30 Propellant - good data
36	01 February 1997	EAHEP Gun 1 - M30 Propellant - good data
39	13 February 1997	EAHEP Gun 1 - B-A/RDX Propellant - Bad microdot cable, Barrel 3

During testing, the Building 390 recording room staff made the following specific contributions beyond the recording of data:

- Assisted with building and testing a different method for checking out break screens.

- When the signal from the discriminator seemed to drop out during test rounds 20, 22, 23, 25, and 26, traced the problem to an intermittent component on the frequency board and repaired it.

- Gave all ballistic data in the form of floppy disks (ASCII format), data plots, and FPFs to the project engineer at the conclusion of each test.

Appendix A:

Experimental Ballistics Team Firing Request

EXPERIMENTAL BALLISTICS TEAM FIRING REQUEST

BRANCH REQUEST: Advanced Propulsion Physics Branch

CONTRACTOR REQUEST: N/A

PROJECT TITLE: EAHEP Test Fixture and Propellant Evaluation

PROJECT ENGINEERS: J. Colburn, A. A. Juhasz, and A. Johnson

PURPOSE OF TEST: To promote the evaluation of novel, high-energy gun propellants that promise enhanced performance from existing tank and artillery systems. To provide a facility that can assess the interior ballistic performance characteristics of small quantities of these propellants.

TIME FRAME REQUEST: LENGTH OF TEST - 7 March 1996 to 13 February 1997
(Days and number of rounds): 16 Days, 21 Rounds

RANGE REQUIREMENTS:

GUN TYPE: 30-mm GDLS ETC

PROJECTILE TYPE: Slug

CHARGE TYPE:

PRIMER TYPE: M52

GUN INSTRUMENTATION: Pressure gauges in chamber and barrel.

RANGE INSTRUMENTATION:

- Interferometer
- Discriminator/Velocity
- Video/Audio
- Break Screens

INTERIOR BALLISTICIAN:

REVIEW OF TEST PLAN: A. A. Juhasz

OTHER REQUIREMENTS: As outlined by project engineer.

Appendix B:


Gauge Locations and Range Setup for the 30-mm Gun

EAHEP 30-mm Gauge Locations and Range Setup

Sand pile




Break screen one



Break screen two



Break screen three



Appendix C:

Tabular Data and Example of Experimental Firing Data


Tabular Data

Test No.	Peak, Quasi-Static Pressure (MPa)							
	P1 Left	P1 Right	P2 Left	P2 Right	Barrel 1	Barrel 2	Barrel 3	35 GHz m/s
19	84.4	86	77.7	81.2	75.9	64.2	17.1	875
20	90.7	91.3		85	81	71.2	15	—
21	154	159	148	151	143	131	20	1047
22	209	215	192	203	177	158	29	—
23	209	247	227	234	207	180	23	—
24	326	330	310	315	273	224	24	1402
25	392	422	313	398	335	312	40	—
26	377	390	374	381	328	313	34	—
27	Igniter	Tube	Integrity	Test	—	—	—	—
28	99	103	97	98	93	88	16	970
29	94.4	103.8	98	99	94.5	87	18	971
30	166	169	164	168	157	156	27	910
31	388	411	379	407	376	316	31	—
32	390	411	387	396	374	318	29	1216
33	394	—	386	397	380	337	31	1185
34	396	411	403	394	376	331	32	1234
35	330	325	318	324	309	230	22	936
36	318	307	310	304	298	224	21	926
37	169	164	164	161	166	136	16	721
38	134	133	133	127	136	102	12	399
39	74	77	77	73	81	53	—	240

P1L
P1R

EAHEP Round 39


13 FEB 1997



13 FEB 1997

EAHEP Round 39

P2L
P2R




13 FEB 1997

EAHEP Round 39

B BARREL 1 & B BARREL 2 & B BARREL 3


B BARREL
B BARREL
B BARREL



B-S1-2-3

EAHEP Round 39


13 FEB 1997



DISCRIMINATOR

EAHEP Round 32


01 MAY 1996



INTERFEROM

EAHEP Round 39

13 FEB 1997



Appendix D:

Examples of Run Summary and Channel Description/Calibration Coefficients On Line for the 30-mm EAHEP

RUN SUMMARY FOR EAHEP - EAP ROUND 39

TEST DATA

DATE : 13 FEB 1997
 LOCATION : R 166
 CLEARANCE : X

ENGINEER : COLBURN
 OPERATOR : MBR
 GUNNERS : COLBURN

ANALOG TAPE PARAMETERS

REEL NUMBER : 487
 STATUS : ON
 START : 5885
 STOP :

IDENT NUMBER : 32
 SPEED CODE : 120

ENVIRONMENT

TEMPERATURE : 20 C
 BAROMETER : mm Hg
 HUMIDITY : %

DENSITY : g/ml
 WIND SPEED : m/s
 WIND DIRECTION : Deg

GUN DATA

TUBE : EAHEP-1
 NUMBER : SN 529
 TUBE ROUND NUMBER : 0
 TRAVEL : 2670 mm
 CHAMBER VOLUME : 121.66 cc
 REMARKS : 529 USED PREV BY TBD

CALIBERS/TURN : 999999
 GROOVE DIAMETER : 29.21 mm
 LAND DIAMETER : 29.21 mm
 GROOVE/LAND RATIO : 1

MOUNT

RECOIL TYPE : 37-MM
 RECOIL SERIAL NUMBER : UNKNOWN
 ELEVATION : 0 mils

MOUNT TYPE : UNKNOWN
 MOUNT SERIAL NUMBER : UNKNOWN
 AZIMUTH : 0 mils

REMARKS : BLUE MOUNT & RECOIL

PROJECTILE

TYPE : MILD STEEL SLUG
 LOT NUMBER : 2
 WEIGHT : .305kg
 FILL : SOLID
 PROJECTILE TEMP : AMBIENT C

BAND TYPE : POLYPROPULUX
 BAND DIAMETER : N/A mm
 BAND WIDTH : N/A mm
 FUZE : N/A

REMARKS : TYPE 2 SLUG AND OBTURATOR

PRIMER

PRIMER TYPE : M52 A3 B1
 LOT NUMBER : LC-20-625

WEIGHT : N/Ag
 TEMPERATURE : AMBIENT C

REMARKS : 200V FIRING VOLTAGE

IGNITER

IGNITER TYPE : BENITE
 LOT NUMBER :

WEIGHT : 1.5g
 TEMPERATURE : AMBIENT C

REMARKS : USING BAYONETTE IGNITER TUBE

ADC 1

CHANNEL SIZE: 20 KBytes
 TIME PER SAMPLE: .005 ms
 MUX POSITION: 2

CHANNELS: 12
 PRETRIGGER SIZE: 1/8
 TRIGGER LEVEL: 2 Volts

CHANNEL	GAGE DESCRIPTION	CALIBRATION COEFFICIENTS
1	P1L KISTLER 607C3/C55333 Top step: 8	Constant : 4.4036E-01 Linear : 58.310 Quadratic: -3.2210E-01
2	P1R KISTLER 607C3/C54587 Top step: 8	Constant : 7.7135E-01 Linear : 61.052 Quadratic: -4.0050E-01
3	P2L KISTLER 607C3/C47191 Top step: 8	Constant : 1.4745E-01 Linear : 58.751 Quadratic: -3.3017E-01
4	P2R KISTLER 607C3/C55334 Top step: 8	Constant : -6.7238E-02 Linear : 57.788 Quadratic: -3.2828E-01
5	BARREL 1 KISTLER 607C3/C55331 Top step: 8	Constant : -1.1027E-01 Linear : 58.986 Quadratic: -4.7070E-01
6	BARREL 2 KISTLER 607C3/C55332 Top step: 8	Constant : 1.4386E-01 Linear : 57.344 Quadratic: -3.4921E-01
7	BARREL 3 KISTLER 607C3/C57305 Top step: 1	Constant : 1.2304E+00 Linear : 54.446 Quadratic: -1.4959E-01
8	FR FIRING VOLTAGE	NOT CALIBRATED
9	B-S1-2-3 BS COMMON OUTPUT	NOT CALIBRATED
10	NOT USED NOT USED	NOT CALIBRATED
11	DISCRIMINATOR 35 GHz Top step: 5	Constant : 0 Linear : 259.92 Quadratic: 0
12	INTERFEROMETER 35 GHz	NOT CALIBRATED

CHARGE

CHARGE TYPE : M30
LOT NUMBER : N/A

ZONE : RAD-PE-771-2
TEMPERATURE : AMBIENT C

REMARKS : 7-PERF M30 .0125 WEB

CASE

CASE TYPE : LEXAN

LOT NUMBER : 1

REMARKS : .125" THICK

LOADING

SEATING DISTANCE : mm

CHARGE STANDOFF : mm

REMARKS :

EAP Rd 39

PROPELLANTS

NUMBER OF PROPELLANTS: 1

PROPELLANT 1

PROPELLANT TYPE :		PERF DIAMETER :	
LOT NUMBER :		TEMPERATURE :	C
WEIGHT :	kg	IMPETUS :	J/kg
INNER WEB :	mm	SPECIFIC HEAT RATIO :	
OUTER WEB :	mm	FLAME TEMPERATURE :	K
LENGTH :	mm	COVOLUME :	cc/g
DIAMETER :	mm	DENSITY :	g/cc

REMARKS :

EAP Rd 39

VELOCITY

VELOCITY DEVICE: HP COUNTER

DISTANCE 1: 1.0025 m

ETS CHANNEL: 1

VELOCITY 1-2 256.886611147 m/s

DISTANCE 2: 1.062 m

ETS CHANNEL: 2

VELOCITY 2-3 241.182749302 m/s

DISTANCE 3: 2.0645 m

ETS CHANNEL: 3

VELOCITY 1-3 248.582196482 m/s

EVENT TIMER

ETS CLOCK RATE CODE:

CHANNELS: 6

CHANNEL	DESCRIPTION
---------	-------------

TIME (s)

1	+3.9025E-03
---	-------------

2	+4.4033E-03
---	-------------

3	+8.3051E-03
---	-------------

4	
---	--

5	
---	--

6	
---	--

TEST REMARKS

ONLINE DATA

Appendix E:
Analog Tape and Digital Acquisition System Parameters

Analog Tape and Digital Acquisition System Parameters

Round	Analog Tape	Identification	Start Footage		Tape Speed	Digital Sampling Rate		Channels	Channel Size	
			A			On Line (ms)	Tape Digitization (μs)		On Line	Digitized
19	487	12	1635–1750		120	.005	2.5	12	20,000	16,000
20	487	13	3725–3840		120	.005	2.5	12	20,000	16,000
21	487	14	3840–3960		120	.005	2.5	12	20,000	16,000
22	487	15	3960–4070		120	.005	2.5	12	20,000	16,000
23	487	16	4115–4245		120	.005	2.5	12	20,000	16,000
24	487	17	4245–4353		120	.005	2.5	12	20,000	16,000
25	487	18	4353–4450		120	.005	2.5	12	20,000	16,000
26	487	19	4450–4545		120	.005	2.5	12	20,000	16,000
27	487	20	4700–4860		120	.005	2.5	12	20,000	16,000
28	487	21	4860–4975		120	.005	2.5	12	20,000	16,000
29	487	22	4975–5075		120	.005	2.5	12	20,000	16,000
30	487	23	5075–5180		120	.005	2.5	12	20,000	16,000
31	487	24	5180–5275		120	.005	2.5	12	20,000	16,000
32	487	25	5275–5390		120	.005	2.5	12	20,000	16,000
33	487	26	5390–5485		120	.005	2.5	12	20,000	16,000
34	487	27	5485–5575		120	.005	2.5	12	20,000	16,000
35	487	28	5575–5656		120	.005	2.5	12	20,000	16,000
36	487	29	5656–5735		120	.005	2.5	12	20,000	16,000
37	487	30	5735–5810		120	.005	2.5	12	20,000	16,000
38	487	31	5810–5858		120	.005	2.5	12	20,000	16,000
39	487	32	5885–5965		120	.005	2.5	12	20,000	16,000

NO. OF COPIES	ORGANIZATION
2	DEFENSE TECHNICAL INFORMATION CENTER DTIC DDA 8725 JOHN J KINGMAN RD STE 0944 FT BELVOIR VA 22060-6218
1	HQDA DAMO FDQ D SCHMIDT 400 ARMY PENTAGON WASHINGTON DC 20310-0460
1	OSD OUSD(A&T)/ODDDR&E(R) R J TREW THE PENTAGON WASHINGTON DC 20301-7100
1	DPTY CG FOR RDE HQ US ARMY MATERIEL CMD AMCRD MG CALDWELL 5001 EISENHOWER AVE ALEXANDRIA VA 22333-0001
1	INST FOR ADVNCD TCHNLGY THE UNIV OF TEXAS AT AUSTIN PO BOX 202797 AUSTIN TX 78720-2797
1	DARPA B KASPAR 3701 N FAIRFAX DR ARLINGTON VA 22203-1714
1	NAVAL SURFACE WARFARE CTR CODE B07 J PENNELLA 17320 DAHLGREN RD BLDG 1470 RM 1101 DAHLGREN VA 22448-5100
1	US MILITARY ACADEMY MATH SCI CTR OF EXCELLENCE DEPT OF MATHEMATICAL SCI MAJ M D PHILLIPS THAYER HALL WEST POINT NY 10996-1786

NO. OF COPIES	ORGANIZATION
1	DIRECTOR US ARMY RESEARCH LAB AMSRL D R W WHALIN 2800 POWDER MILL RD ADELPHI MD 20783-1145
1	DIRECTOR US ARMY RESEARCH LAB AMSRL DD J J ROCCHIO 2800 POWDER MILL RD ADELPHI MD 20783-1145
1	DIRECTOR US ARMY RESEARCH LAB AMSRL CS AS (RECORDS MGMT) 2800 POWDER MILL RD ADELPHI MD 20783-1145
3	DIRECTOR US ARMY RESEARCH LAB AMSRL CI LL 2800 POWDER MILL RD ADELPHI MD 20783-1145
	<u>ABERDEEN PROVING GROUND</u>
4	DIR USARL AMSRL CI LP (305)

NO. OF
COPIES ORGANIZATION

ABERDEEN PROVING GROUND

10 DIR USARL
AMSRL WM B
A HORST
AMSRL WM BC
A JOHNSON
M RIDGLEY (2 CPS)
C RUTH
AMSRL WM BD
J COLBURN (2 CPS)
A JUHASZ
AMSRL WM BE
T MINOR
G WREN

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188	
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.				
1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE January 1999		3. REPORT TYPE AND DATES COVERED Final, Mar 96 - Feb 97
4. TITLE AND SUBTITLE Data Transfer Report - 30-mm Enhanced Alternate High-Energy Propellant Program (EAHEP): Test Fixture and Propellant Evaluation			5. FUNDING NUMBERS 1L162618AH30	
6. AUTHOR(S) Melvin B. Ridgley, Sr., and Joseph W. Colburn				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army Research Laboratory ATTN: AMSRL-WM-BE Aberdeen Proving Ground, MD 21005-5066			8. PERFORMING ORGANIZATION REPORT NUMBER ARL-SR-88	
9. SPONSORING/MONITORING AGENCY NAMES(S) AND ADDRESS(ES)			10. SPONSORING/MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES				
12a. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution is unlimited.			12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) Measurements in support of the 30-mm Enhanced Alternate High-Energy Propellant Program (EAHEP) were taken at the Building 390 recording facility. Propellants evaluated for this series of tests were M30, U.S. Army Armament Research, Development, and Engineering Center (ARDEC) 7994, BAMO-AMMO/CL20, BAMO-AMMO/CL20/NQ, and BAMO-AMMO-RDX. This facility, the central data acquisition network for the Propulsion and Flight Division (PFD) of the U.S. Army Research Laboratory (ARL), was operated by the Experimental Ballistics Team (EBT) of the Propulsion Branch (PB). The testing was conducted in support of an ongoing Army effort to further investigate high-energy gun propellants that promise enhanced performance from existing tank and artillery systems.				
14. SUBJECT TERMS guns, interior ballistics, gun propellant			15. NUMBER OF PAGES 29	
			16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT UL	

USER EVALUATION SHEET/CHANGE OF ADDRESS

This Laboratory undertakes a continuing effort to improve the quality of the reports it publishes. Your comments/answers to the items/questions below will aid us in our efforts.

1. ARL Report Number/Author ARL-SR-88 (Ridgley) Date of Report January 1999

2. Date Report Received _____

3. Does this report satisfy a need? (Comment on purpose, related project, or other area of interest for which the report will be used.) _____

4. Specifically, how is the report being used? (Information source, design data, procedure, source of ideas, etc.) _____

5. Has the information in this report led to any quantitative savings as far as man-hours or dollars saved, operating costs avoided, or efficiencies achieved, etc? If so, please elaborate. _____

6. General Comments. What do you think should be changed to improve future reports? (Indicate changes to organization, technical content, format, etc.) _____

CURRENT
ADDRESS

Organization

Name

E-mail Name

Street or P.O. Box No.

City, State, Zip Code

7. If indicating a Change of Address or Address Correction, please provide the Current or Correct address above and the Old or Incorrect address below.

OLD
ADDRESS

Organization

Name

Street or P.O. Box No.

City, State, Zip Code

(Remove this sheet, fold as indicated, tape closed, and mail.)
(DO NOT STAPLE)