

MRC-R-535

Copy No. 6

REVIEW OF CURRENT PHYSICAL SECURITY  
MODEL CAPABILITIES

J. C. Sanderlin

Mission Research Corporation  
P.O. Drawer 719, 735 State Street  
Santa Barbara, CA 93102

9 November 1979

Task Report, Task-A1 (A004)

Contract No. N00123-79-C-1446

19991019 024

Prepared for:

Navy Personnel Research and Development Center  
San Diego, California

Attn: Code 311, William Stinson

**Reproduced From  
Best Available Copy**

# REPORT DOCUMENTATION PAGE

Form Approved  
OMB No. 0704-0188

Public reporting burden for this collection of information is limited to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding the burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE November 1979		3. REPORT TYPE AND DATE COVERED Task Report, 1979	
4. TITLE AND SUBTITLE Review of current physical security model capabilities.				5. FUNDING NUMBERS Contract N0123-79-C-1446:	
6. AUTHOR(S) J.C. Sanderlin					
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Mission Research Corporation P.W. Drawer 719, 735 State Street Santa Barbara, California 93101				8. PERFORMING ORGANIZATION AGENCY REPORT NUMBER MRC-R-535	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) Navy Personnel Research and Development Center 53335 Ryne Rd. San Diego, CA 92152-7250				10. SPONSORING/MONITORING	
11. SUPPLEMENTARY NOTES Functional Area: Manpower, Personnel, Training, Organizational Systems Product Line: Effort:					
12a. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution is unlimited.				12B. DISTRIBUTION CODE A	
13. ABSTRACT (Maximum 200 words)  This report reviews literature pertaining to physical security and related simulation models, to determine the human factors attributes and human performance capabilities that have been included. It concluded that few attempts have been made to include a significant level of human factors attributes or human performance models in existing security system evaluations.					
14. SUBJECT TERMS Physical Security, Simulation models, safeguards, engagement models				15. NUMBER OF PAGES 54	
				16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT UNLIMITED		

MRC-R-535

Copy No. 6

REVIEW OF CURRENT PHYSICAL SECURITY  
MODEL CAPABILITIES

J. C. Sanderlin

Mission Research Corporation  
P.O. Drawer 719, 735 State Street  
Santa Barbara, CA 93102

9 November 1979

Task Report, Task-A1 (A004)

Contract No. N00123-79-C-1446

Prepared for:

Navy Personnel Research and Development Center  
San Diego, California

Attn: Code 311, William Stinson

## CONTENTS

<u>Section</u>		<u>Page</u>
1	INTRODUCTION	3
2	CURRENT PHYSICAL SECURITY MODEL CAPABILITIES	4
	2.1 MODEL-INSIDER SAFEGUARDS EFFECTIVENESS MODEL (ISEM)	5
	2.2 MODEL-FORCIBLE ENTRY SAFEGUARDS EFFECTIVENESS MODEL (FESEM)	7
	2.3 MODEL-SAFEGUARDS NETWORK ANALYSIS PROCEDURE (SNAP)	9
	2.4 MODEL-MATRIX ANALYSIS OF THE INSIDER THREAT (MAIT)	10
	2.5 MODEL-TECHNICAL SUPPORT ORGANIZATION PHYSICAL PROTECTION SIMULATION (TSO)	11
	2.6 MODEL-TRW PHYSICAL SECURITY DESIGN AND EVALU- ATION METHODOLOGY	13
	2.7 MODEL-FIXED SITE NEUTRALIZATION MODEL (FSNM)	15
	2.8 MODEL-PHYSICAL SECURITY SYSTEM PERFORMANCE ANALYSIS METHODOLOGY (SSPAM)	16
	2.9 MODEL-EASI	18
	2.10 MODEL-VISA	19
	2.11 MODEL-ADVERSARY ACTION MODELING	20
	2.12 MODEL-SDC TRANSPORTATION MODEL	21
3	ARMED FORCES INTERACTION MODELS	22
	3.1 MODEL: ARMED ESCORT MODEL	23
	3.2 MODEL: AIRCAV	24
	3.3 MODEL: AMSWAG	25
	3.4 MODEL: CARMONETTE	26
	3.5 MODEL: DYNTACS	27
	3.6 MODEL: JOLIWACO	28
	3.7 MDOEL: SIAF	29
	3.8 MODEL: TAM	30
4	SMALL GROUP ENGAGEMENT MODELS	31

CONTENTS (Continued)

<u>Section</u>		<u>Page</u>
4.1	MODEL: SABRES	33
4.2	MODEL: SCHAFER'S AMBUSH MODEL	34
4.3	MODEL: SOURCE	35
4.4	MODEL: TSEM	36
4.5	MODEL: ANALYTIC ENGAGEMENT MODEL	37
4.6	MODEL: BONDER/IUA	38
4.7	MODEL: BREAKPOINTS IN LAND COMBAT	39
4.8	MODEL: COUNTERMEASURES ENGAGEMENT ANALYSIS	40
4.9	MODEL: DAYLIGHT ASSAULT MODEL	41
4.10	MODEL: FIREFIGHT	42
4.11	MODEL: GCC FIREFIGHT	43
4.12	MODEL: ICM	44
4.13	MODEL: INTERDICTION MODEL	45
4.14	MODEL: MARKOV ENGAGEMENT MODEL	46
4.15	MODEL: MATH MODEL OF INFANTRY COMBAT	47
4.16	MODEL: PRENTRATION ATTRITION MODEL	48
5	REFERENCES	49

## SECTION 1 INTRODUCTION

This report is submitted in satisfaction of technical requirement 5.1.1 of Contract N00123-79-C-1446. As described in Technical Requirement 5.1.1 of the subject contract the available documentation on the most applicable current physical security models has been reviewed. The results of this review are presented in Section 2.0 of this report. The absence of behavioral models in the current physical security models led us to expand the scope of the literature review to include selected small unit Armed Force interaction models, which are presented in Section 3.0 and small unit engagement models, which are presented in Section 4.0 of this report.

## SECTION 2

### CURRENT PHYSICAL SECURITY MODEL CAPABILITIES

This section presents the results of a review of twelve models developed specifically for evaluation of physical security systems. All of these models describe land based sites and most of them are designed to evaluate physical security safeguards for Special Nuclear Materials (SNM) at nuclear materials processing plants. Two exceptions to this rule are the TRW Physical Security Model, which has been used to evaluate building security and the Mission Research Corporation (MRC) Security System Performance Analysis Methodology (SSPAM), which is being developed to evaluate physical security of Service operated nuclear weapons storage sites.

These models, developed specifically to address physical security, were considered to be the models most applicable to the modeling of shipboard security. Because this research program addresses human behavior as it relates to shipboard security, these models were reviewed primarily from the standpoint of the human attributes and human performance functions that were included in the models. With two exceptions, it was found that very few human (behavioral) attributes and essentially no behavior-related models have been included in current physical security models. The exceptions are the Vector Research Incorporated Fixed Site Neutralization Model (FSNM) and the MRC SSPAM.

## 2.1 MODEL-INSIDER SAFEGUARDS EFFECTIVENESS MODEL (ISEM)<sup>1</sup>

DEVELOPER - Sandia Laboratories

LANGUAGE - GASP IV

PERSONS INCLUDED - Employees, guards

PERSONNEL ATTRIBUTES -

Employees: authorized access to areas  
explosives on person  
SNM on person

Guards: authorized access to areas  
authorized access to portals

PERSONNEL FUNCTIONS -

Employees: motion  
disable sensor  
disable sensor communications  
engagement

Guards: motion  
engagement

ENGAGEMENT - Discrete state, continuous time  
stochastic process

DISCUSSION - The facility is described in terms of areas, barriers and portals. Motion is modeled in terms of the time interval required to cross an area or pass through a portal. The time intervals are obtained by a draw from a triangular probability density function, where the mean and standard deviation crossing or passage time are specified for each area and portal, respectively. Insider tampering with a sensor or alarm communications is modeled as a user specified time delay and probability of success. Engagements occur at user specified locations following an alarm if a guard and insider arrive at the same area or portal at the same time.

The engagement model describes the engagement states in terms of adversary force size, guard force size and arriving guards. State transitions are obtained by sampling probability density functions dependent upon current force sizes, force weapons level (low, medium, high) and force competence level (low, medium, high). ISEM contains only the attribute of combat competence level and no human performance models.

## 2.2 MODEL - FORCIBLE ENTRY SAFEGUARDS EFFECTIVENESS MODEL (FESEM)<sup>2</sup>

DEVELOPER - Sandia Laboratories

LANGUAGE - GASP IV

PERSONS INCLUDED - Guards, adversaries

PERSONNEL ATTRIBUTES -

Adversaries: number  
                  weapon type  
                  barrier penetration resources  
                  mobility  
                  dedication/sophistication

Guards: number of on-site response forces  
          number of off-site response forces  
          communications probability  
          dedication/sophistication  
          response time

PERSONNEL FUNCTIONS -

Adversaries: motion  
                  barrier penetration  
                  tampering (sensor or sensor communications)  
                  engagement

Guards: motion  
          engagement

ENGAGEMENT - Tenth order nonlinear Lanchester equation with time  
                  varying coefficients

DISCUSSION - FESEM is a computer model for analyzing the effectiveness of fixed-site nuclear safeguards against a forcible attack by an adversary intent on sabotage or theft. The model applies Monte Carlo methods to problems of forcible entry for any assumed path by an adversary with specified characteristics and estimates the probable adversary success. The evaluation technique includes variables related to detection assessment, communication, delay and neutralization. The physical security system is

modeled as a system of concentric shells of barriers and alarms with response forces. All guard and adversary motion is along radial lines. Motion, barrier penetration and tampering are modeled as delay times drawn from triangular probability density functions. Tampering also includes a user specified probability of success.

The engagement model allows ambushes, which are transformed to engagements as the ambushes "take cover" and start to return fire. During the transition from ambush to engagement the ambush's firepower effectiveness is allowed to increase.

The only human factors attribute included in FESEM is the dedication/sophistication parameter. This attribute is specified as high, medium or low, and is used principally in the engagement model to affect engagement proficiency and surrender or quit criteria. No human performance models are included in FESEM.

## 2.3 MODEL - SAFEGUARDS NETWORK ANALYSIS PROCEDURE (SNAP)<sup>3</sup>

DEVELOPER - Pritsker and Associates (for Sandia Laboratories)

LANGUAGE - GASP IV

PERSONS INCLUDED - Adversaries, guards

PERSONNEL ATTRIBUTES -

- Adversaries: number
- weapons
- Guards: number
- weapons
- training level

PERSONNEL FUNCTIONS -

- Adversaries: motion
- disable a barrier or sensor
- engagement
- Guards: motion
- engagement

ENGAGEMENT - Uses the Sandia Laboratories BATL engagement model

DISCUSSION - The facility is described in terms of areas, barriers and portals that are adjacent to one another. The security system is described in terms of guards, sensors and alarms. Conditions for and probabilities of detection and alarm are user specified. Detection and engagement can occur under user specified conditions if a guard and an adversary arrive simultaneously at the same block. Motion is defined by the time required to cross a block and is obtained by a draw from a probability density function, with user specified mean and standard deviation for each block. Disabling a barrier or sensor is characterized by a required time drawn from a probability density function and a user specified probability of success.

Engagements are simulated by the BATL model which requires as inputs force sizes, weapon type and, for guards, training level.

## 2.4 MODEL - MATRIX ANALYSIS OF THE INSIDER THREAT (MAIT)<sup>4</sup>

- DEVELOPER - Science Applications Incorporated (for Nuclear  
Regulatory Commission)
- LANGUAGE - GASP IV
- PERSONS INCLUDED - Employees, guards
- PERSONNEL ATTRIBUTES - Identification  
Authorized access  
Authorized control
- PERSONNEL FUNCTIONS - Movement  
Access  
Control
- ENGAGEMENT - None
- DISCUSSION - The design of MAIT does not allow inclusion or consideration of human factors or performance. MAIT is concerned with all of the possible paths from one point to another, together with the safeguards along that path. The insider is assigned certain access and control privileges associated with his job, and it is assumed that whatever he can do he will do to achieve his goal.

2.5 MODEL - TECHNICAL SUPPORT ORGANIZATION PHYSICAL PROTECTION  
SIMULATION (TSO)<sup>5,6</sup>

DEVELOPER - Brookhaven National Laboratories

LANGUAGE - FORTRAN (?)

PERSONS INCLUDED - Defenders, attackers

PERSONNEL ATTRIBUTES -

Defenders: number  
location  
time to alert  
transport mode and rate of movement  
adversary detection range

Attackers: number  
location  
barrier penetration resources  
transport mode and rate of motion  
delay in assessing progress of attack

PERSONNEL FUNCTIONS -

Defenders: movement  
detection

Attackers: movement

ENGAGEMENT - Engagement is modeled as a delay only, with no attrition.

DISCUSSION - The facility is modeled as a series of concentric circles, with straight line motion along radial lines. Barrier penetrations are modeled as delays, alert and assessment delays are user specified. Detection is automatic when the defender-adversary range is less than the adversary detection range. An engagement is modeled as a delay of length proportional to the ratio of defenders to attackers. The model computes the outcome of an invariant input adversary action sequence. The result is deterministic, all variables and parameters are fixed for a given case,

and uncertainties are not included. Detection is assumed to occur at one of three user specified locations: at the perimeter, at an inner barrier, or at specified locations between the perimeter and inner barrier. All three cases may be evaluated. The evaluation model is divided into two phases: the access phase, which ends when the intruders gain access to the SNM, and the removal phase which involves travel of the intruders and guards to an interception point. The modeling of sensors and guards is unrealistic in many ways. For example, the treatment of sensors neglects their probabilistic behavior, and the treatment of guards neglects their human attributes. The modeling of guard positions and movements oversimplifies the geometric realitites involved.

## 2.6 MODEL - TRW PHYSICAL SECURITY DESIGN AND EVALUATION METHODOLOGY<sup>7,8</sup>

DEVELOPER - TRW Systems Group

LANGUAGE - Unknown (probably GASP IV)

PERSONS INCLUDED - Adversaries, guards, insiders

PERSONNEL ATTRIBUTES -

Adversary/insider: capability to defeat barriers, alarms, locks  
attack type (overt/covert)  
recognizability

Guards: force posture  
procedures per post

PERSONNEL FUNCTIONS - Movement  
performance of specified tasks

ENGAGEMENT - No engagement is modeled

DISCUSSION - All possible paths from an initial assault point to the intended target are identified and the model uses graph techniques to evaluate the progress of the attack from grid point to grid point. The attack may employ outsiders or insiders using either stealth or force. If stealth is used the measure of security system effectiveness is the cumulative probability of adversary detection. If force is used the measure of system success is the delay time imposed on the attackers by the system. Adversary and guard attributes are translated into delay times, probabilities of success in performing specified tasks and probabilities of detection. Visible and aural detection are modeled.

The facility is characterized in terms of walls, doors, locks, and other familiar items. Detection is provided by sensors and roving guard patrols. The sensors modeled include ultrasonic, closed circuit television, photoelectric break-beam, line and point types. Models dealing with guards include guard patrol, guard fixed post, visual and aural detection, and lighting. Penetration activities include barriers, locked doors, and

vaults. Detection provides the start signal for responding guard forces. The guard response and time of arrival depend on the force posture, procedures, and the characteristics of the facility. The model terminates the adversary action sequence with the arrival of either the attackers or the security force at the protected area. Engagement simulation is avoided by terminating the adversary action sequence prior to an engagement. Extensive geometric route analysis is implicit in route optimization.

## 2.7 MODEL - FIXED SITE NEUTRALIZATION MODEL (FSNM)<sup>9</sup>

DEVELOPER - Vector Research Incorporated (for Sandia Laboratories)

LANGUAGE - Unknown (probably FORTRAN)

PERSONS INCLUDED - Security force, adversaries

PERSONNEL ATTRIBUTES - Type, physical status, location, allegiance, credentials, situation suppression, posture, weapons, ammunition, equipment, leader, subordinates, communication nets, perceptions, current activity time requirement, activity plans, standard operating procedures, activities to which victim

PERSONNEL FUNCTIONS - Movement, firing, observation, communication, planning, perception, sensory detection

DISCUSSION - Very little information is available on FSNM, the description presented here is based on a set of briefing charts. FSNM is basically an engagement model with very careful characterization of the involved persons. However, it is implied in the briefing paper that FSNM is a gaming model. If this is the case, the amount of actual modeling of human reactions and interactions may be very limited (i.e., depending in large part upon input from the players). Certainly a large number of human factors attributes are included in the model and much human performance and interaction is implied. For these reasons, it is considered important to obtain more information on the FSNM, and this end detailed documentation will be requested from Sandia Laboratories.

2.8 MODEL - PHYSICAL SECURITY SYSTEM PERFORMANCE ANALYSIS METHODOLOGY (SSPAM)<sup>10</sup>

- DEVELOPER - Mission Research Corporation (for Defense Nuclear Agency)
- LANGUAGE - FORTRAN IV
- PERSONS INCLUDED - Adversaries, patrol guard, static point guard, entry controller, intrusion detection alarm monitor, communicator, Sgt. of guard, Site Commander, visitors, maintenance persons
- PERSONNEL ATTRIBUTES - Identity, location, velocity, probability of visually detecting target, perceived probability of visually being detected by target, probability of aural detection of target, posture, penetration aids, penetration skills, dedication, experience under stress, training/organization, overt/covert intent, credentials, sound levels (e.g., talking, moving), brightness contrast, reflectivity, auditory threshold, average ratio of hours duty to rest, ratio hours duty to rest last shift, shift, average ratio motivational enrichment to duty, motivation level, average ratio hours on-job-training to duty, time of arousal level, reference time for arousal decay, training duration, training quality, level of experience, proficiency, weight
- PERSONNEL FUNCTIONS -
- Adversaries: Motion, search, detect, identify, select response to specified situation, penetrate barrier, tamper with sensor or sensor communications, open a lock, hide, evade
- Security personnel: Motion, search, detect, identify, select response to specified situation, communicate, monitor display, control entry, verify credentials, challenge, physical search, detain, communicate

ENGAGEMENT - None

DISCUSSION - The SSPAM is still in development, thus the above information represents current status. As can be seen a number of human factors attributes have been included in SSPAM, together with a limited number of human performance models. The information upon which these models are based ranges from high quality experimental data (e.g., video display target detection and identification) to expert opinion estimates (e.g., personnel response to specified situations). SSPAM represents a first attempt to include a significant level of human factors attributes and human performance models in a physical security system evaluation model.

## 2.9 MODEL: EASI<sup>11</sup>

DEVELOPING AGENCY: Sandia Laboratories

DESCRIPTION: A simple, easy-to-use method, called Estimate of Adversary Sequence Interruption (EASI), has been developed to evaluate physical security system performance under specified conditions of threat and system operation. The method consists of a probabilistic analysis of the interactions of basic security functions, such as detection, communications, response, etc. The evaluation can be performed on a hand-held programmable calculator. The results of the analysis are expressed in terms of the probability that the physical protection system can respond in time to interrupt specific adversary action sequences. The utility of the method depends upon the user's ability to identify significant adversary action sequences and to obtain data that properly reflect conditions created by the adversary action sequence of interest.

2.10 MODEL: VISA<sup>12,13</sup>

DEVELOPING AGENCY: Science Applications, Inc.

DESCRIPTION: Vulnerability of Integrated Safeguards Analysis (VISA) is an evaluation concept that can be used to evaluate the effectiveness of fixed-site security systems against hostile encounters, both overt and covert. The concept is divided into three sections: preparation, analysis, and assessment. The preparation section is simply a formalization of the site data input preparation process, and the assessment section is essentially concerned with the storage of case analysis results, with procedures to assess these results at different levels of detail via an interactive display terminal. The analysis section, which includes the principal evaluation tools, consists of four analysis modules (Path, Detection, Containment, and Interruption) and requires two data bases (Detection Mechanism, and Delay Mechanism and Engagement). Included in the Containment Analysis Module is a detailed network simulation that includes aggregated delay time and engagement simulations to evaluate the probabilities of adversary success along adversary action sequence segments. VISA is a concept only, and no development has been undertaken.

2.11 MODEL: ADVERSARY ACTION MODELING<sup>14,15</sup>

DEVELOPING AGENCY: Lawrence Livermore Laboratory

DESCRIPTION: An assessment procedure has been developed to evaluate the effectiveness of a potential nuclear licensee's material control system. The first step in this procedure is to identify targets within the facility that contain theft-attractive special nuclear material. The second step is to determine the adversary action sequences that could allow successful diversion of special nuclear material. Simulation is used for adversary event sets where timeliness and ordering of events is important for successful diversion. The qualitative and quantitative analysis of the event sets and the simulation results allows the effectiveness of the material control system to be estimated.

2.12 MODEL: SDC TRANSPORTATION MODEL<sup>16,17</sup>

DEVELOPING AGENCY: Systems Development Corporation

DESCRIPTION: The SDC Transportation Model is a methodology for defining, classifying, and analyzing adversary action sequences; defining safeguards system components; assessing the vulnerability of various safeguards systems and their component parts to the potential adversary action sequences, and conceptualizing system design requirements. The method of analysis is based on a comparison of adversary actions with safeguards measures to estimate vulnerability. Because of the limited data available for assessing vulnerability, the Delphi approach is used to generate data; values are estimated in a structured exercise by a panel of experts in the safeguards and terrorist fields.

### SECTION 3

#### ARMED FORCES INTERACTION MODELS

Because of the paucity of human performance characterization that is evident in current physical security models, the literature to be reviewed was expanded to include selected Armed Forces interaction models. The models reviewed were generally restricted to those involving company sized units, although some models that evaluate interactions among mechanized units and aircraft have been included. Some of these Armed Forces interaction models are very large gaming models (i.e., interactive models employing human "players" to represent the participating forces) and the documentation of these models frequently consists of thousands of pages. It is expected that some of these models will provide information on the approaches taken by other agencies in modeling human performance for tasks related to those performed by security personnel. In particular, the TRW-System Group, Small Infantry Action Force model (SIAF) and the General Research Corporation CARMONETTE model are known to include quite a few human factors attributes and some human performance models. These, and appropriate submodels of other applicable Armed Forces interaction models, will be reviewed in detail during the Algorithm Development Task to help identify modeling techniques for possible inclusion in the shipboard security behavioral model.

### 3.1 MODEL: ARMED ESCORT MODEL<sup>18,19</sup>

DEVELOPING AGENCY: Electronic Associates, Inc.

DESCRIPTION: The Armed Escort Model is a set of computer programs to simulate an engagement between a single ground weapon and a formation of troop-carrying helicopters (UH-1) escorted by a single armed aircraft. The model evaluates the effectiveness of different escort aircraft performing various maneuvers, armed with different weapon systems, and provides data for use in a comparison study. A dual-purpose digital simulation program evaluates the outcome of a single engagement in terms of expected numbers of aircraft lost, probabilities of specific damage inflicted, and similar results. The first objective was to provide a model to be used in studying the outcome of an engagement between the single ground weapon and an unescorted formation of lift aircraft that first approach the weapon position, hover for several seconds to unload or take on troops, and then pull out along prescribed flight path. The second objective was to provide a computer model to evaluate the outcome of a similar engagement including an armed escort aircraft.

3.2 MODEL: AIRCAV<sup>20,21</sup>

DEVELOPING AGENCY: Vector Research, Inc.

DESCRIPTION: AIRCAV is a set of two differential model programs incorporating attack helicopters and air defense weapon activities, differing principally in the detailed assumptions and logic of their ground scenarios and the format of their data bases. Both models treat a battalion-level engagement between Red and Blue forces, with Blue forces including attack helicopters in direct support and Red forces including air defense weapons. These programs were constructed as modifications of existing differential model programs treating ground combat without attack helicopter support. The scenarios were therefore constructed as modifications of basic ground combat scenarios.

### 3.3 MODEL: AMSWAG<sup>22</sup>

DEVELOPING AGENCY: Army Material Systems Analysis Agency

DESCRIPTION: The AMSAA War Game (AMSWAG) model is a time sequenced, deterministic, battalion-level, force-on-force computer model that simulates a classical attack and defense. Up to 64 defenders are deployed in fixed positions in hull defilade. The attacking force has already deployed and moves along predetermined routes of advance toward the defender. The attacking force is allowed a maximum of 12 routes of approach. The routes are administratively broken into one to three groupings of up to four routes each. These groupings are called axes, and each axis nominally contains a company-sized force. Thus, each route nominally contains a platoon. This platoon can be further split into two homogeneous sections (of two to four vehicles each) that maneuver together down the route. Normal movement techniques for these sections are either alternate bounds or successive bounds. The model conducts the battle in uniform time steps of 10 seconds each.

### 3.4 MODEL: CARMONETTE<sup>23-31</sup>

DEVELOPING AGENCY: General Research Corporation

DESCRIPTION: CARMONETTE is a critical-event-sequenced infantry combat simulation including the activities of movement, target acquisition, communications, and weapon employment. When a unit comes within line of sight of an enemy unit, it has a probability of acquiring information about the enemy as a target. The information it may acquire ranges from none to full knowledge of the exact location and nature of the enemy unit. If the unit gets sufficient information and has an appropriate order, it will select weapons and ammunition and take the enemy under fire. A weapon is simulated in terms of its rate of fire and its maximum range. The effects of a projectile are simulated by tables giving the probabilities that it will hit what it was aimed at as a function of the range and the size of the target, and by further tables giving the probability that it will kill the target if it is hit. Explosive projectiles are characterized in terms described on the basis of their average rates of movement under various conditions and in terms of their vulnerability to different kinds of weapons. Aircraft are characterized by their vertical and horizontal components of velocity and their vulnerability. Firing may be terminated by lack of ammunition, loss of target information, death of firing unit, known death of the target unit, or expenditure of an ordered amount of ammunition or by passage of a specified time interval.

3.5 MODEL: DYNTACS<sup>32-38</sup>

DEVELOPING AGENCY: Ohio State University

DESCRIPTION: DYNTACS is a small-unit, high-resolution simulation that can represent combat engagements ranging in size from a single element to a reinforced armored battalion. Attack, defense, delay, and meeting engagements can be portrayed. Armor, artillery, air defense, attack helicopters, crew-served weapons, and mounted infantry in the attack are modeled. Dis-mounted infantry are not modeled; the smallest resolution is the individual vehicle. Combat is represented as an adaptive process where each unit is constantly evaluating the battle situation in order to choose the tactic most appropriate for the tactical doctrine expressed by the input data.

3.6 MODEL: JOLIWACO<sup>39,40</sup>

DEVELOPING AGENCY: Control Data Corporation

DESCRIPTION: Joint Limited War Counterinsurgency Operations (JOLIWACO) is a computer-assisted manual war game between an insurgent force and a counter-insurgent force. An indigenous population also is assumed with the ability to provide intelligence, manpower, and supplies to either side. Depending on the scenario, any level of operations (village to national) may be modeled. Human players determine mission and policy. Lanchester-type models are used to determine outcomes of intelligence missions, engagements, and so on. Game outputs include resources consumed, casualties suffered, and mission results for the two forces and the indigenous population.

3.7 MODEL: SIAF<sup>41-47</sup>

DEVELOPING AGENCY: TRW Systems Group

DESCRIPTION: The Small Independent Action Force (SIAF) computer model has been developed to analyze the effectiveness of small patrols. In the model, patrols of up to 20 men can cover an area of about 25 km<sup>2</sup>. The model simulates the detection and engagement of enemy units involving less than 20 men or positions and can accommodate a time period of up to 10 days. A combination of graph ("grid") and event-driven techniques is used for the simulation. Submodels include enemy situation, command and control, communications, human maintenance, supply maintenance, fire support, surveillance/detection, navigation, movement, terrain, and weather. Output consists of an event table providing what happened at what time. The SIAF engagement model avoids the use of Lanchester models by keeping track of the performance and vulnerability of each combatant.

3.8 MODEL: TAM<sup>48</sup>

DEVELOPING AGENCY: Army Concepts Analysis Agency

DESCRIPTION: The Target Acquisition Model (TAM) simulates the acquisition of targets in a target force by the sensors of an acquiring force. The model generates acquisition events that result in requests for fire missions to be delivered by an artillery firing force. The target force is represented by a static target array which is modeled at the small-unit level of resolution. The acquiring force is modeled at the individual-sensor level of resolution. The model addresses input target arrays for a six hour time period and produces a history of acquisition events.

SECTION 4  
SMALL GROUP ENGAGEMENT MODELS

In addition to the small group encounter models described in this section, it should also be noted that engagement models are included in many of the Armed Forces interaction models described in Section 3 and in some of the security system evaluation models described in Section 2. In reading the engagement model descriptions, it will be observed that many of the models reviewed are based on Lanchester Technology. Lanchester models are based on simultaneous differential equations of the form (guards ambush adversaries)

$$\frac{dN_A}{dt} = \gamma_1 N_A N_G / \beta \quad (\text{linear law})$$

$$\frac{dN_G}{dt} = \gamma_2 N_A \quad (\text{square law})$$

where

$dN_A/dt$  = attrition rate of adversaries

$dN_G/dt$  = attrition rate of guards

$\gamma_1$  = adversary attrition coefficient, dependent on guard rate of fire

$N_A/\beta$  = adversary exposure coefficient

$\gamma_2$  = guard attrition coefficient, dependent on adversary fire rate and accuracy

A larger number than two simultaneous equations may be used, and the equations may contain more coefficients than shown, with the intent of including more characteristics of the opposing forces. Additionally, the coefficients may be time dependent with the intent of reflecting changes in force posture during the engagement. The definition of the derivation  $dN/dt$  is given by

$$\frac{dN}{dt} = \lim_{t_1 \rightarrow t_2} \left[ \frac{N(t_2) - N(t_1)}{t_2 - t_1} \right] .$$

Thus, there is no theoretical inconsistency in using a differential equation or, more appropriately, a finite difference equation, approach to modeling small group engagements. The difficulties lie in its inflexibility and the availability of more appropriate techniques. The differential equation approach does not allow for situation assessment, maneuvering to gain positional advantage, changes in tactics, etc., that may be important factors in determining the outcome of a small group engagement. In the case of large group (i.e., battalion size) encounters, these factors may be of less significance and certainly change more slowly. Further, in large group encounters, it is not possible (and probably not desirable) to keep track of all the combatants and maintain a record of each participant's performance and vulnerability. However, this can be done in the case of small group engagements and is considered by many to be an appropriate way to model such engagements. This approach has the advantage of allowing frequent situation assessment, alteration of tactics as the situation changes, movement to improve positional advantage, the effects of new arrivals, partitioning of the involved forces, etc. For these reasons, it is considered that an appropriate approach for modeling small group engagements should be one that maintains a running account of the performance and vulnerability of the participants. Some examples of this type engagement model are the approaches taken by SABRES,<sup>49</sup> described in SPPAM<sup>10</sup> and employed by SIAF.<sup>42</sup>

#### 4.1 MODEL: SABRES

DEVELOPING AGENCY: Sandia Laboratories<sup>49,50,51</sup>

DESCRIPTION: SABRES is a time-stepped Monte Carlo simulation developed to evaluate the outcomes of engagements between attackers and defenders after a transport vehicle has been stopped. At every time step, detection, posture, firing allocation, casualty assessment, suppression, and disengagement are considered for each participant, and the results are catalogued before moving to the next time step. The battle terminates when one side disengages. The program outputs for a series of replications of an ambush are the expected survivors on each side, the fraction of time each side is totally successful, and the expected battle time.

#### 4.2 MODEL: SCHAFFER'S AMBUSH MODEL<sup>52</sup>

DEVELOPING AGENCY: Naval Postgraduate School

DESCRIPTION: The Schaffer Ambush model is a mixed Lanchester linear/square-law attrition model that is representative of the many Lanchester-type simulations that could be used to evaluate the outcomes of engagements involving ambushes. The model assumes an ambusher force in concealed positions and initiates a surprise attack when the ambushee force arrives in a specified "killing zone." The ambushers' initial fire is aimed (Lanchester square law) while the ambushees initially react with area fire (Lanchester linear law). As the ambushees locate cover and begin to detect ambusher fire locations, they gradually switch from area to aimed fire. The ambushers maintain aimed fire throughout the engagement but with decreasing effectiveness as the engagement progresses. Ambushee desertions and ambusher withdrawals are considered (dedication/training) in the simulation and supporting weapons for the ambusher can also be included. For the initial surprise attack, the use of claymore mines is also an option.

#### 4.3 MODEL: SOURCE<sup>51,52,53</sup>

DEVELOPING AGENCY: Sandia Laboratories

DESCRIPTION: The SOURCE model is used to study the impact of convoy configuration and tactics upon personnel survival and emergency signal generation during an initial armed attack. SOURCE is a flexible, time-stepped Monte Carlo model that provides for extensive variations in convoy configuration (number of vehicles, distributions, vulnerabilities, velocity, and communications) and in adversary characterization (number of units, deployment, and weapon capabilities). The convoy is described by the number of vehicles, vulnerable areas, observation conditions, and communications capabilities. Convoys consisting of a number of different types of vehicles can be studied. Emergency messages can be initiated, either by a vehicle under attack or by a vehicle that has observed an attack on another vehicle. The conditions under which an attack is observed can be varied, and the capability of sending a message depends on the condition of the convoy crew and their equipment. SOURCE calculates the damage to personnel and equipment and includes the cumulative effects of multiple hits on a vehicle.

#### 4.4 MODEL: TSEM<sup>54,55,56</sup>

DEVELOPING AGENCY: The BDM Corporation

DESCRIPTION: TSEM (Transportation Safeguards Effectiveness Model) is designed to simulate a two-sided engagement between a group of adversaries and a road convoy. TSEM is a discrete, stochastic, event-driven simulation that individually models persons (with their associated weapons) and vehicles. The players in TSEM (i.e., persons and vehicles) can be directed by a script that includes actions (movement, firing, and dismounting) and contingency situations (player or vehicle at a location, players dead, attack started). The battles take place on a two-dimensional surface with topography and vegetation superimposed. Line-of-sight interruptions due to vehicles and terrain and vegetation features are calculated and taken into account in firing allocation. The battle progresses until all people on one side are killed, a preset time limit is reached, or prime vehicle penetration is successfully completed. A movie can be produced that shows the course of the battle, including player movements and shots fired.

#### 4.5 MODEL: ANALYTIC ENGAGEMENT MODEL<sup>57</sup>

DEVELOPING AGENCY: Sandia Laboratories

DESCRIPTION: The Analytic Engagement Model is a discrete-state, continuous-time stochastic process. The state of the battle is described in terms of the number of guards and adversaries actively engaged in battle, together with the number of arrivals to each of the opposing forces. The solution procedure is analytical in nature and involves solving sets of linear equations. For small battles, consisting of one or two combatants on each side, symbolic solutions can be found. The procedure can be used to compute analytic numerical solutions for larger battles with a total of less than ten combatants on both sides.

#### 4.6 MODEL: BONDER/IUA<sup>58</sup>

DEVELOPING AGENCY: Army Material Systems Analysis Agency

DESCRIPTION: The Bonder/IUA model is an adaptation of the general Bonder methodology to the Individual Unit Action (IUA) model scenarios. The Bonder model is a generalized differential equation model of ground combat. It is an extension of the Lanchester analytic formulations. In contrast to the classical Lanchester approach, which bases attrition rates on historical data, this model estimates attrition rates based on measurable weapon system parameters. It also allows a force to use more than one weapon type. Weapons of a given type in the same general location are aggregated into a single group. Different types of weapons and weapons of the same type in different locations are treated as distinct groups.

#### 4.7 MODEL: BREAKPOINTS IN LAND COMBAT<sup>59</sup>

DEVELOPING AGENCY: Naval Postgraduate School

DESCRIPTION: This concept considers battle termination (a unit reaching its so-called "breakpoint") in ground combat as a rational decision process. A commander's decision to break contact with an enemy force and withdraw from the battlefield is analyzed for company-size infantry units. Two approaches for modeling a commander's decision process to terminate an engagement are presented. The first approach is based on extrapolation of observations on past battle history into the future with no assumption about combat dynamics. The second is based on the assumption of known Lanchester-type combat dynamics (possibly with unknown parameters to be estimated) and uses Kalman filtering.

#### 4.8 MODEL: COUNTERMEASURES ENGAGEMENT ANALYSIS<sup>60</sup>

DEVELOPING AGENCY: Air Force Institute of Technology

DESCRIPTION: This analysis involved the construction of a computer model to study a one-on-one engagement. It is built so that parameters in the radio frequency or optical regime can be used. The aircraft flies over the threat, is not allowed to maneuver, and the atmosphere has been ignored.

Fly-By-1 introduces the techniques employed by the GASP IV simulation language. The aircraft is detected when it comes within range. In Fly-By-2, a more probabilistic determination of detection is used, and the radar scans for the aircraft. Fly-By-3 makes 20 runs of the Fly-By-2 program and collects statistics on the range of detection. Fly-By-4 incorporates a track-and-fire role into the threat.

#### 4.9 MODEL: DAYLIGHT ASSAULT MODEL<sup>61</sup>

DEVELOPING AGENCY: Naval Postgraduate School

DESCRIPTION: With Lanchester's Square Law providing a point of departure, a model of small-unit combat was developed in which major parameters of an encounter known to be time- or range-dependent were so treated, thus incorporating realism of dynamic combat. The single uncontrolled variable of the model is force size. Force sizes are specified at the start of each computer program and every one-tenth of a minute of the battle. The remaining variables are controlled in that they were either assumed, calculated from other data, or directly input as values from other research. Success in battle is considered dependent upon infliction of casualties on the opposing force and on the range between the forces at the termination of the engagement.

4.10 MODEL: FIREFIGHT<sup>62</sup>

DEVELOPING AGENCY: SRI International

DESCRIPTION: FIREFIGHT is a computer model developed to evaluate the effectiveness of alternative small arms, using the criterion of tactical mission success probability. It can be used to evaluate rifles, machine-guns, grenade launchers, and grenades. Mortar, artillery, and other supporting fires are not modeled. This small-unit engagement model can also be used to study tactics or nonweapon equipment options.

4.11 MODEL: GCC FIREFIGHT<sup>63</sup>

DEVELOPING AGENCY: Naval Weapons Laboratory

DESCRIPTION: The Firefight Submodel of the Ground Combat Confrontation (GCC) is a military operations analysis tool designed to assess the results of close combat between opposing forces of mixed infantry and mechanized units. The forces are considered to be composed of "fire units" (such as a USMC fire team or a single tank) which are elements of the forces that have their target acquisition, fire, and movement internally coordinated. Detailed round-by-round assessments are given to the fire of individual crew-served tank and antitank weapons belonging to a fire unit. The lethal and suppressive effects of individual projectiles are considered in terms of the activity and presentation of the target fire unit.

4.12      MODEL: ICM<sup>64</sup>

DEVELOPING AGENCY: Army Concepts Analysis Agency

DESCRIPTION: The Infantry Combat Model (ICM) is a two-sided ground combat model that simulates small infantry unit engagements of close combat over successive finite time intervals. The units can contain varying numbers of personnel with a variety of direct-fire weapons. Each unit can be augmented by reserve forces and can be supported by indirect fire of varying types. Each engagement is evaluated on the basis of assessing personnel casualties and ammunition expenditures in successive time intervals. The results are accumulated until the exchange terminates based on predetermined conditions. Each engagement is replicated and the results are averaged. The model output consists of average personnel casualties for both sides, direct- and indirect-fire weapon ammunition expenditures, termination distances between opposing forces, direct-fire weapon attrition, and average engagement time.

#### 4.13 MODEL: INTERDICTION MODEL<sup>65</sup>

DEVELOPING AGENCY: Rand Corporation

DESCRIPTION: The Interdiction Model is an algorithm for determining where to place forces in order to maximize the probability of preventing an opposing force from proceeding from one particular node in a network to another.

The usual gaming assumptions are invoked in this model—namely, that the strategy for placing forces is known to the opponent and that he will choose a path through the network that, based on this knowledge, maximizes his probability of successful traverse. As given quantities, the model requires a list of the arcs and nodes of the network, the number of forces available to stop the opposing force, and the probabilities for stopping the opposition at the arcs and nodes as functions of the number of forces placed there. From these data, the model calculates the probabilities of success for placing the force at the arcs and nodes when one force is available and the expected numbers of forces to place at the arcs and nodes when multiple forces are available.

4.14 MODEL: MARKOV ENGAGEMENT MODEL<sup>66</sup>

DEVELOPING AGENCY: Vector Research, Inc.

DESCRIPTION: The Markov Engagement Model is a conceptual formulization of a Markov or Semi-Markov model to evaluate the outcome between a set of attackers and a guard force. The range between opposing participants is maintained constant. The model allows for the possibility of arriving forces joining one side or both. The model does not allow for range closure, changes in force posture, exhaustion of ammunition supplies, and so on. However, modifications of the process are suggested to overcome some of the restrictions.

4.15 MODEL: MATH MODEL OF INFANTRY COMBAT<sup>67</sup>

DEVELOPING AGENCY: Naval Postgraduate School

DESCRIPTION: This is a deterministic combat model that takes into account the phenomenon of fire suppression. This model, based on Lanchester's theories of combat, can be used to investigate the offensive tactics and defensive fire distribution of a small-scale infantry action. Specifically, the type of action covered is an attack against a defended position. The missions of the attacking and defending units are, respectively, to gain or maintain control of the defended position while holding their own casualties to a minimum. The offensive force has two tactics it can employ—advance its entire force against the enemy or advance only a portion of its force while using the remainder to lay down covering fire. The defense then has to decide how to divide its fire to engage the attacking elements.

#### 4.16 MODEL: PENETRATION ATTRITION MODEL<sup>68</sup>

DEVELOPING AGENCY: Institute for Defense Analyses

DESCRIPTION: The Penetration Attrition Model is a probabilistic model designed to evaluate combat attrition between attackers (infiltrators) and defenders attempting to defend a passive target. Infiltrators attempt to reach a target successively, one after another. An infiltrator is detected by each defender present with a constant probability independent of any other defender and of past history. When a detection occurs, exactly one defender is assigned to engage the infiltrator. One-on-one engagements are evaluated by assigning probabilities, independent of past history, to the possible outcomes. Probability distributions are computed for infiltrators destroyed, infiltrators reaching target, and defenders destroyed, all conditioned on a specified number of attempted penetrations.

SECTION 5  
REFERENCES

1. Boozer, Drayton D. and Dennis Engi, Insider Safeguards Effectiveness Model (ISEM) User's Guide, SAND 77-0043, Sandia Laboratories, November 1977.
2. Chapman, Leon D., et al., User's Guide for Evaluating Alternative Fixed-Site Physical Protection Systems Using FESEM, SAND 77-1367, Sandia Laboratories, November 1977.
3. Miner, Robin J. and Floyd H. Grant III, User's Guide for SNAP, Pritsker and Associates, November 1978.
4. Glancy, J., et al., Analysis of Nuclear Fuel Facility Safeguards Against Threats Involving Insider Collusion, Science, SAI-78-547-LJ, Science Applications Incorporated, April 3, 1978.
5. Lemly, J. R., J. P. Indusi, and J. J. Cadwell, Test of the TSO Physical Protection Simulation Model at a Nuclear Power Plant, Technical Support Organization, Brookhave National Laboratories, January 21, 1977.
6. Zimmerman, Richard E., The Utility of the TSO Physical Protection Model, July 1, 1976.
7. Physical Security Design and Evaluation Methodology, TRW Technical Brief, Undated.
8. Gref, L. G. and J. W. Rosengren, An Assessment of Some Safeguards Technology, RDA-tr-5000-002, R&D Associates, February 1977.
9. Fixed Site Neutralization Model, Vector Research Incorporated, SAND-1-WP77-4, Sandia Laboratories, November 14, 1977.
10. Sanderlin, J. C. and C. E. Rathmann, A Concept for Assessment of Physical Security Performance, MRC-7850-1-1278, Mission Research Corporation, December 1978.
11. Bennett, H. A., The "EASI" Approach to Physical Security Evaluation, SAND 76-0500, Sandia Laboratories, January 1977.

12. Donnelly, H., et al, A Method for Evaluating the Performance of Integrated Safeguards Systems at Nuclear Facilities, Volume I NUREG-0317, Final Report, Science Applications, Inc., August 1977.
13. Donnelly, H. et al., A Method for Evaluating the Performance of Integrated Safeguards Systems at Nuclear Facilities, Volume II, Appendices, NUREG-0317, Final Report, Science Applications, Inc., August 1977.
14. Lambert, H. E. and J. J. Lim, The Modeling of Adversary Action for Safeguards Effectiveness Assessment, UCRL-79217, Rev. 1, Lawrence Livermore Laboratory, June 1977.
15. Gilman, F. M., H. E. Lambert, and J. J. Lim, The Results of a Directed Graph and Fault Tree Assessment of a MC&A System, UCRL-80802, Lawrence Livermore Laboratory, June 1978.
16. Baldonado, O. C., et al., Safeguards Systems Concepts for Nuclear Material Transportation, NUREG-0335, Final Report, Systems Development Corp., September 1977.
17. Baldonado, O. C., et al., Executive Summary of Safeguards Systems Concepts for Nuclear Material Transportation, NUREG-0334, Final Report, Systems Development Corp., September 1977.
18. Baker, E. B., et al., Development of Hybrid Computer Programs for AAFSS/COBRA/COIN Weapons Effectiveness Studies, Volume I, Simulating Aircraft Maneuvers and Weapon Firing Runs, RF-ECOM-0241-F1, Final Report, Electronic Associates, Inc., September 1968.
19. Baker, E. B., et al., Development of Hybrid Computer Programs for AAFSS/COBRA/COIN Weapons Effectiveness Studies, Volume 4, Monte Carlo Simulation of a Tactical Engagement Between Air and Ground Forces, TR-ECOM-0241-F4, Final Report, Electronic Associates, inc., October 1968.
20. Analytic Models of Air Cavalry Combat Operations—Volume I, Final Report No. SAG-1-Vol-1, FR-73-1-Vol-1, Vector Research Inc., May 1973.
21. Analytic Models of Air Cavalry Combat Operations—Volume II, Final Report No. SAG-1-Vol-2, FR-73-1-Vol-2, Vector Research Inc., May 1973.
22. Hawkins, J. H. The AMSAA War Game (AMSWAG) Computer Combat Simulation, Technical Report No. AMSAA-TR-169, Army Materiel Systems Analysis Activity, Aberdeen Proving Ground, May 1976.

23. Eckhardt, W. and D. W. Mader, CARMONETTE III Documentation, Volume I—General Description, RAC-R-28, Research Analysis Corp., October 1967.
24. Bruce, C. A., Jr., et al., CARMONETTE III Documentation, Volume II—Data Preparation Guide, RAC-R-28, Research Analysis Corp., February 1968.
25. Parsons, N. W., et al., The Use of CARMONETTE IV in Assessing the Combat Effectiveness of Small Units Equipped with Night Vision Devices, Final Report No. RAC-009.302, Research Analysis Corp. November 1969.
26. Parsons, N. W., CARMONETTE IV AND CARMONETTE V, Report No. RAC-D12-CR, Research Analysis Corp., October 1972.
27. Colonna, G. S. and R. G. Williams, CARMONETTE: Volume I—General Description, Report No. OAD-CR-73-Vol-1, General Research Corp. and Operations Analysis Division, Army Concepts Analysis Agency, November 1974.
28. Colonna, G. S. and R. G. Williams, CARMONETTE: VOLUME II—Data Preparation and Output Guide, Report No. OAD-CR-73-Vol-2, General Research Corporation and Operations Analysis Division, Army Concepts Analysis Agency, November 1974.
29. Williams, R. G., CARMONETTE: VOLUME III—Technical Documentation Report No. OAD-CR-73-Vol-3, General Research Corp. and Operations Analysis Division, Army Concepts Analysis Agency, November 1974.
30. Thorp, K. et al., Comparison of the CARMONETTE Model with the TETAM Field Experiment, Report No. CAA-TP-75-6, Army Concepts Analysis Agency, September 1975.
31. Zirkind, R. and R. E. Forrester, Tactical Electrooptical Effectiveness Model, Phase II—Volume I, Report No. CR-191, General Research Corp. June 1977.
32. Bishop, A. B. and S. Stellmack, The Tank Weapon System: Vol. I—Design Models, Report No. RF-573 AR 68-1, Systems Research Group, Ohio State University, September 1968.
33. Bishop, A. B. and G. M. Clark, The Tank Weapon System: Vol. II—Design of Operations Models, Report No. AR 69-2A, Systems Research Group, Ohio State University, 1969.
34. Clark, G. M. and L. C. Moss, The Tank Weapon System: Vol. III—DYNTACS Computer Program, Report No. AR 69-3A, Systems Research Group, Ohio State University, June 1979.

35. Bishop, A. B. and G. M. Clark, The Tank Weapon System: Vol. IV—Summary, Report No. AR 69-4, Systems Research Group, Ohio State University, 1969.
36. Clark, G. M. and S. H. Parry, Small Unit Combat Simulation (DYNTACS X)—Counterbattery Fire Models, Report RF-2978-FR-70-1, Systems Research Group, Ohio State University, October 1970.
37. Clark, G. M. Extensions to the Land Combat Model (DYNCOM), Volume 1. Helicopter and Missile Models, Report No. RF-2995-FR-71-1, Systems Research Group, Ohio State University, December 31, 1971.
38. Hugus, D. K., A Review of the Compilation of the DYNTACS(X) Data Base for the HELLFIRE COEA, Report No. CACDA-TR-9-76, Army Combined Combat Development Activity, Fort Leavenworth, June 1976.
39. Joint Limited War Counterinsurgency Operations (JOLIWACO)—Users Manual, Report No. CDC-90009-14, Control Data Corp. May 21, 1971.
40. Joint Limited War Counterinsurgency Operations (JOLIWACO)—Analytical Manual, Report No. CDC-90009-15, Control Data Corp., May 21, 1971.
41. Modification to Math Model for Small Independent Action Forces (SIAF), Final Report, TRW Systems Group, December 15, 1973.
42. SIAF System Model User's Manual: Small Independent Action Forces. Volume II. Model Subroutines (Terrain, Weather, Targets), Report No. 16905-6009-RD00, TRW System Group, December 15, 1973.
43. SIAF System Model User's Manual: Small Independent Action Forces. Volume III. Model Subroutines (SIAF Functions and Ancillary Routines), Report No. 16905-6010-RD001, TRW Systems Group, December 15, 1973.
44. SIAF System Model User's Manual: Small Independent Action Forces. Volume IV. Model Program Listing, Report No. 20660-6005-RD00, TRW Systems Group, December 15, 1973.
45. SIAF System Model User's Manual: Small Independent Action Forces. Volume V. Combat Initialization Subroutines, Report No. 20660-6006-RD00, TRW Systems Group, December 15, 1973.
46. SIAF System Model User's Manual: Small Independent Action Forces. Volume VI. Combat Execution Subroutines, Report No. 20660-6007-RF00, TRW Systems Group, December 15, 1973.
47. Deutscher, W. E., Small Independent Action Force (SIAF), Vegetation Classification Study, Master's Thesis, Naval Postgraduate School, Monterey, September 1974.

48. Jones, E. M., Target Acquisition Model, Report No. CAA-D-74-4, Army Concepts Analysis Agency, December 1974.
49. Keeton, S. C. and P. Laquil, III, Conflict Simulation for Surface Transport Systems, Report No. CONF-770656-23, Sandia Laboratories, July 1977.
50. Gallagher, R. J., et al., The Evaluation of Road-Transit Physical Protection Systems, Report No. SAND 78-8650, Sandia Laboratories, July 1978.
51. Chapman, L. D., Physical Protection of Nuclear Material in Transit, Quarterly Progress Report, April-June 1978, SAND 78-2043, Sandia Laboratories, December 1978.
52. Salikupta, N. A Factorial Parameter Analysis of Schaffer's Ambush Combat Model, Master's Thesis, Naval Postgraduate School, Monterey, September 1974.
53. Wagner, R. J., et al., Configuration of Road Convoys: A Simulation Study, Report No. CONF-770656-22, Sandia Laboratories, July 1977.
54. Transportation Safeguards Systems Support—Task 4 Final Technical Report, EMD/A-77-057-TR, The BDM Corporation, March 1977.
55. TSEM Preliminary Design-Functional Specification, BMD/A-77-264-TR, The BDM Corporation, June 1977.
56. TSEM Phase II User's Manual, BMD/TAX-78-253-TR, The BDM Corporation, June 1978.
57. Engi, D., Small-Scale Engagement Model with Arrivals: Analytical Solutions, Report No. NUREG-0238, Sandia Laboratories, April 1977.
58. Honig, J., et al., Review of Selected Army Models, Review Report, Department of the Army, Washington, D.C., May 1971.
59. Adkins, R. C., Analysis of Unit Breakpoints in Land Combat, Master's Thesis, Naval Postgraduate School, Monterey, March 1975.
60. Penick, J. R., Optical Threat/Laser Countermeasures Engagement Analysis, Report No. AFIT/GEP/PH/77-10, Air Force Institute of Technology, Wright-Patterson Air Force Base, December 1977.
61. Christy, D. E., A Lanchester Based Model for Analyzing Infantry Fire and Maneuver Tactics, Master's Thesis, Naval Postgraduate School, Monterey, October 1969.

62. Laurence, A. E. and G. V. Lucha, FIREFIGHT 2—User's Manual, Final Report, SRI IR&D Program 30201, Task BMV, SRI International, Menlo Park, June 1973.
63. Loomis, H. W., The Fire-Fight Assessment in the Ground Combat Confrontation (Gdd) Model, Report No. NWL-TR-2157, Naval Weapons Laboratory, April 17, 1968.
64. Hampton, E. W., Infantry Combat Model, Report No. CAA-D-74-5, Army Concepts Analysis Agency, December 1974.
65. Wollmer, R. D., An Interdiction Model for Sparsely Traveled Networks, Report No. RM-5539-PR, Rand Corp., April 1968.
66. Markov and Semi-Markov Modelling of Small Engagements, Report No. SANDIA-L WP77-5, Vector Research Inc., December 20, 1977.
67. Peterson, F. K., A Mathematical Model of Infantry Combat, Master's Thesis, Naval Postgraduate School, Monterey, April 1970.
68. Anderson, L. B., et al., An Attrition Model for Penetration Processes, Report No. P-1148, Institute for Defense Analyses, Arlington, March 1976.