



DISTRIBUTION STATEMENT A
Approved for Public Release
Distribution Unlimited

**Feasibility of Third World
Advanced Ballistic & Cruise Missile Threat
Volume 1: Long Range Ballistic Missile Threat**

Presented to
67th MORS Symposium
Working Group 4: Air and Missile Defense, TMD Threat

June 24, 1999

Robert E. Woodside
robert.e.woodside@boeing.com

20000517 045

DTIC QUALITY INSPECTED 3

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing this collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. **PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.**

1. REPORT DATE (DD-MM-YYYY) 24-06-1999		2. REPORT TYPE Technical Study		3. DATES COVERED (From - To) 1998-1999	
4. TITLE AND SUBTITLE Feasibility of Third World Advanced Ballistic and Cruise Missile Threat: Volume 1: Long Range Ballistic Missile Threat				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S) Robert Woodside, John McIver, Daniel Gadler, James Beyar, James Howe, Milton Gussow, Thomas K. Jones, H. William Beuttel, Theodore Kramer, Steven Woodall				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) National Defense Industrial Association (NDIA) 2111 Wilson Blvd., Suite 400 Arlington, VA 22201				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) Naval Sea Systems Command 2531 Jefferson Davis Highway NC#2 Arlington, VA 22242				10. SPONSOR/MONITOR'S ACRONYM(S) OPNAV PEO (TSC)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S) N/A	
12. DISTRIBUTION / AVAILABILITY STATEMENT The NDIA Study "Long range Ballistic Missile Threat" has been reviewed and is approved for public release; distribution is unlimited.					
13. SUPPLEMENTARY NOTES Abbreviated study materials presented at 67 th Military Operations Research Society Symposium at US Military Academy 24 June 1999.					
14. ABSTRACT "Feasibility of Third World Long Range Ballistic Missile Threat" presents the results of a United States aerospace industry study which assesses the likelihood of a Third World country developing a long range (3,000-10,000 km) ballistic missile (LRBM) system and the estimated time to field it. A 10,000-km range ballistic missile launched from North Korea, for example, can reach the western and central regions of the United States. Likewise, a 5,000-km range missile launched from Iran could reach cities throughout Western Europe. The study contains four technical sections: historical developments and technology migration, trends in Third World ballistic missile weaponry, threat development on a compressed schedule, and candidate LRBM configurations. The report is unclassified because it drew exclusively upon unclassified sources of information. The study traces the history of the LRBM threat from Germany's V-2 rockets of World War II to the present. It shows how Third World countries could quickly field and launch LRBM's with technical assistance and components imported from developed nations. The study examines five different options by which a Third World country could achieve a long range ballistic missile capability: Buy a long range ballistic missile; Buy and convert an available space launch vehicle; Cluster or stack existing tactical missiles as boosters; Design and build a booster and use existing tactical missile for upper stage; or Design and build an entire missile. The flight stability and performance characteristics of feasible Third World missile configurations are based on industry experience in the design of missile systems and verified by the use of standard engineering analysis tools and missile flight simulations. The report contains the estimated time required for a Third World nation to develop each option as measured from program start to first launch. The study concludes that the time between detectable evidence of a country's missile development program until the missile is fielded may be less than the time needed to build defenses against it.					
15. SUBJECT TERMS Ballistic missiles, history, technologies, guidance, warheads, propulsion, employment, threats, advanced weapons, proliferation, performance simulation, design synthesis					
16. SECURITY CLASSIFICATION OF: UNCLASSIFIED			17. LIMITATION OF ABSTRACT Unlimited	18. NUMBER OF PAGES 48	19a. NAME OF RESPONSIBLE PERSON Robert E. Woodside
a. REPORT UNCLASSIFIED	b. ABSTRACT UNCLASSIFIED	c. THIS PAGE UNCLASSIFIED			19b. TELEPHONE NUMBER (include area code) (253) 773-4164



**Feasibility of Third World
Advanced Ballistic & Cruise Missile Threat
Volume 1: Long Range Ballistic Missile Threat**

**Prepared By
Systems Assessment Group
NDIA Strike, Land Attack and Air Defense Committee**

**Released
November 1998**

Study Approach

- **Review lessons learned from historical missile development programs**
 - **WW II Germany, North Korea, Iraq**
 - **Development time and motivation**
 - **Strategic objectives for LRBMs with WMD warheads**
- **Assess potential range growth of evolving family of Third World TBM threats to include LRBM capability (3,000km - 10,000 km range)**
- **Conduct Third World Threat Analysis & Development Timelines**
 - **Technology assessment**
 - **Development forecast**
- **Assess Candidate LRBM Configuration Alternatives**
 - **Space launch vehicle conversion**
 - **TBM stacking / clustering**

Outline


- **German WW II Missile Development and Technology Migration**
- **Trends in Third World Ballistic Missile Weaponry**
- **Threat Development on a Compressed Schedule**
- **Candidate LRBM Configurations**
- **Summary**

Key Ingredients of the German Program

- **Political/Cultural Climate**
 - Rocket development not constrained by Versailles treaty
 - Autocratic rule
 - Warring factions within the Nazi party for control of ballistic missile program
 - 1920's Weimar Republic had strong interest in rocketry and space flight
 - Use of slave labor
- **Technological and Strategic Surprise**
 - Early recognition of the value of ballistic missiles for maximizing surprise (1929)
 - Extreme secrecy of the program - first large "black" program
 - Suppression of German amateur rocket societies for security reasons (1933-34)
- **Speed of Development**
 - National priority / significant funding resources available
 - Excellent domestic industrial skill base to develop required technologies
 - Rapid prototyping using technology demonstrators (Test / Fail / Fix / Re-Test...)

Many of these key ingredients are found in Third World programs today

German Intercontinental Missile Design




Manned A9

A9/A10

Source: "Secret Wonder Weapons of the Third Reich", J. Miranda, P. Mercado, Schiffer Military/Aviation History, 1996


Alternative Concept for Attacking North America



Project Lifevest

Source: "Secret Wonder Weapons of the Third Reich", J. Miranda, P. Mercado, Schiffer Military/Aviation History, 1996

Design for Use of Chemical/Radiological Payloads



Payload Compartment

Source: "Vengeance. Hitler's Nuclear Weapon. Fact or Fiction?", Phillip Henshall, Alan Sutton Publishing Ltd., 1995

International Technology Transfer


Technology Suppliers

	Technology Recipients									
	Israel	India	Egypt	Iraq	Pakistan	Iran	Libya	Saudi Arabia	Syria	
Trained Personnel/Advisors	NL, US		AT, DE, ES, CH, SU, US	AR, AT, BE, CL, EG, FR, DE, LI, KP, CN, CH, US, SU	CN	KP	DE	DE, PK, CN, US		
Reentry Vehicles			DE, CH, US, SU	CL, EG, FR, DE, LY, US	CN		CL			
Ballistic missile Propulsion				AT, BE, FR, DE, IT, LI, CH, US		CN, KP			CS, IR, IT, LY, SU	
Guidance/Navigation	ZA, TW, US			BR, FR, DE, US		HK, JP		IL, CN		
Flight Controls				BR, DE		HK, JP				
Production Assistance	FR, DE, NL, US		AR, DE, KP, SA, CH, US	AR, AT, BE, BR, EG, FR, DE, IT, MC, KP, CN, CH, GB, US, SU	DE, CN	KP, CN	DE	DE	CS, DE, LY, KP, SA, SU	
Materials Manufacture			US	DE, LI, GB, US	CA, FR, CH, US					
Computers		US	SA, CH, US	DE	NO, GB			US		
Testing/Ranges	ZA			MR						

Notes: (1) This information was extracted from the International ballistic missile Proliferation Project database, compiled by the Monterey Institute of International Studies under the direction of Dr. William C. Potter and Dr. Edward J. Laurance. It is a compilation of open source material and covers only reports of actual deliveries and transfers since 1989. The table does not include information relating to proposals, offers, negotiations, or orders (unless clear transfers have resulted).

(2) The two-letter codes used in this table are the American National Standard Institute (ANSI) international country codes, defined as follows: AR - Argentina, AT - Austria, BE - Belgium, BR - Brazil, CA - Canada, CH - Switzerland, CL - Chile, CN - China, CS - Czechoslovakia, DE - Germany, EG - Egypt, ES - Spain, FR - France, GB - United Kingdom, HK - Hong Kong, IL - Israel, IR - Iran, IT - Italy, JP - Japan, KP - North Korea, LI - Liechtenstein, LY - Libya, MC - Monaco, MR - Mauritania, NL - Netherlands, NO - Norway, PK - Pakistan, SA - Saudi Arabia, SU - Soviet Union, TW - Taiwan, US - United States, ZA - South Africa.

Iraqi Ballistic Missile Programs



- 1970s -- Iraq receives first Scud-B ballistic missiles from USSR (813 imported by 1990)
- 1982 -- First Iraqi Scud-B attack on Iran
- 3 August 1987 -- Al Husayn tested (500 km range)
- February - April 1988 -- 189 Al Husayn missiles fired in "war of the cities"
- 25 April 1988 -- Al Abbas missile fired on Tehran (860 km)
- 1980-1988 -- Total of 361 Scud-B and Al Husayn missiles fired in Iran-Iraq war
- 5 December 1989 -- Successful launch of Al Abid SLV
- 7 December 1989 -- Tammuz 1 SLV announced (2,000 km range)
- 1991-- Desert Storm saw 88 Al Husayns fired
- 1997 -- Iraq announces Al Hamid ballistic missile (150 km range)

Historical Parallel -- 1930s vs. 1990s

- **Missile Technology Control Regime no more effective than Versailles Treaty at limiting technology spread**
- **MTCR does not “control” anything. Its signers agree to exercise “restraint” .**
- **Ineffective at stopping:**
 - **Transfer of missiles and components from non-signatory states (e.g., North Korea and China)**
 - **Emigration of scientists, engineers and technicians**
 - **Technical education in sciences and engineering which provides missile skills**

Outline


- **German WW II Missile Development and Technology Migration**
- **Trends in Third World Ballistic Missile Weaponry**
- **Threat Development on a Compressed Schedule**
- **Candidate LRBM Configurations**
- **Summary**

Third World View of Effective Responses to U.S. Technical Superiority

- Cannot Defeat U.S. / Allies on Battlefield: Land, Sea, Air
 - Persian Gulf War showed failure of direct confrontation
- Development of Hi-tech Conventional Forces Constrained
 - Affordability
 - Technological Availability
 - National Leadership and Power Structures
- Aggressor Nations Must Develop Asymmetric Strategies & Forces to Counter U.S./Allies

Mission	Objective
<ul style="list-style-type: none"> - Threaten/Attack Population Centers - Threaten/Attack U.S. Forward-Deployed Forces and Allied Bases - Threaten/Attack Air and Sea Ports of Entry - Threaten/Attack Naval and Amphibious Operations 	<ul style="list-style-type: none"> - Prevent Creation and Maintenance of Coalitions - Deny Facilities/LOC's to U.S./Allies - Prevent Entry of U.S./Allied Forces - Raise Risk to Unacceptable Levels

MISSILES -- Cost-Effective Force Decision




Source: US Army ADA School, Air and Missile Defense Master Plan (threat section), September 1996


MISSILES -- Third World Weapons of Choice

- **Robust Force Structure**
 - Cruise and Ballistic missiles
 - Integrated Air Defense Systems
 - Aircraft with long-range missiles
- **Missiles -- Most Cost Effective Investment**
 - High speed improves penetration of defenses
 - Onboard seekers & GPS guidance for accuracy
 - WMD delivery meets military/political goals
 - Existing technology conceals development
- **Improved Targeting**
 - Increased access to space surveillance
 - Modern mobile communications coordinate dispersed launches
 - Computer flight planning allows pre-programmed attack profiles
 - GPS navigation updates enables cheap precision


Su-34 & Missile Armaments



C-801, -802




SA-15 Launch



North Korean
Ballistic Missiles

Third World Countries with Ballistic Missiles *



Third World Indigenous Capabilities

	Israel	India	Egypt	Iraq	Pakistan	Iran	Libya	Saudi Arabia	Syria
Human Resources	●	●	●	●	●	●	○	○	○
Technical Resources	Ballistic missiles	●	●	●	●	●	○		
	Space	●	●	○	●				
	Artillery	●	●	●	●	○			
	Ordnance	●	●	●	●	●	●	○	●
	Aircraft	●	●	●	○	●	○		
Electronics	●	●	○	●					
Test Resources	●	●	○	○	●		○		

- Substantial capability:
 - Large numbers of experts and technicians
 - Indigenous manufacturing
 - Instrumented test ranges
- Modest capability:
 - Some experts and technicians
 - Spare parts manufacturing
 - Component test/ground test
- Rudimentary capability:
 - Few experts or technicians
 - Repair and refurbishment
 - Limited test facilities

Reference: "Rest of World (ROW) Response to GPALS: Technology and Industry Bases", Strategic Defense Initiative Organization, June 1992


Current Third World Ballistic Missile Capabilities

Country	Missile System	Status	Propulsion	Launch Weight (kg)	Payload Weight (kg)	Range (km)
China	CSS-1 (DF-2A)	1966 IOC	L	26,000	1500	1250
	CSS-2 (DF-3)	1971 IOC	L/L	64,000	2000	2650
	CSS-2 (DF-3A)	1986 IOC	L/L	64,000	2150	2800
	CSS-3 (DF-4)	1978 IOC	L/L	82,000	2200	4750
	CSS-4 (DF-5A)	1986 IOC	L/L	183,000	3200	13000
	CSS-5 (DF-21A)	1987 IOC	L/L	14,700	600	1800
	DF-25	Reported Stopped	S/S/S		2000	1700
	DF-31	1996 IOC	S/S/S		700	8000
	DF-41	Under Dev.	S/S/S		800	12000
India	Agni I	Flight Tested	S/L	16,000	1000	>2000
	Agni II	Dev. Initiated	S/S		1000	3000
Iran	Shihab 3	Flight Tested	L		750	1700
	Shihab 4	Early Stages of Dev.	S		1000	3000
	Shihab 5	Engaged Effort				3000+
	Labour 1 (No Dong 1 import)		L			
	Labour 2 (No Dong 2 joint effort)	In Dev.	L/L			


Current Third World Ballistic Missile Capabilities (Cont)

Country	Missile System	Status	Propulsion	Launch Weight (kg)	Payload Weight (kg)	Range (km)
Iran (cont.)	Tondar 68 (Iran 700)	Dev. Prototype	L or S		500	700-1000
	Zelzal -3 (modified M-11)		S			1000-1500
	M-18 (import from China)		S			700-1000
Iraq	AlAbid	Dev. Cancelled	L/L	48,000		2000
	Tammuz 1	Dev. Cancelled			750	2000
	Badr 2000	Dev. Cancelled (Joint Iraq, Egypt, Argentina effort)			450	900
Israel	Jericho 2B (YA-2B)		S/S			1300
	Jericho 3	1990 IOC	S/S	29,000	1000	4800
North Korea	NoDong 1 (aka Rodong-1)	Flight Tested	L	21,000	800	1300
	Taepo Dong 1 (aka No Dong 2, Rodong-2)	In Dev. / Poss. 1 Flt Test	L/L	21,000	1000	1500-2000
Pakistan	Taepo Dong 2	Engaged Effort	L/L		1000	3,500-6000
	Ghauri/Mk III	One flight test	L		500-750	1500
Saudi Arabia	CSS-2 (imported from China)	1988 IOC	L	65,200	1900	3100


Iran's Ballistic Missile Development Program



Potential Iranian LRBM Coverage




North Korean Ballistic Missile Programs



- 1975 ~ DF-61 Program with China Terminated
- 1981 ~ Egypt Supplies Scud-B Missiles for Evaluation
- 1984 ~ Scud-B Mod A Tested
- 1985 ~ Scud-B Mod B Tested
- 1987 ~ Scud-B Mod B Exported to Iran
- 1989 ~ Scud-B Mod C Deployed
- 1990 ~ Nodong-1 Program Underway
- 1993 ~ Nodong-1 Tested
- 1995 ~ Taepo Dong 1 and 2 Programs Underway
- 1996 ~ Nodong-1 Exported to Iran
- 1998 ~ Nodong Technology in Pakistani Ghauri
- 1998 ~ Potential Space Launch/LRBM Capability

Potential North Korean LRBM Coverage



Outline

- **German WW II Missile Development and Technology Migration**
- **Trends in Third World Ballistic Missile Weaponry**
- **Threat Development on a Compressed Schedule**
- **Candidate LRBM Configurations**
- **Summary**

Overcoming Challenges to Third World LRBM Development

Obvious limitations...

- Access to Critical Technologies -- MTCR and economic sanctions
- Engineering and manufacturing infrastructure -- old facilities
- Missile system integration skills -- limited technical manpower

... *mitigated by innovative shortcuts:*



Key Technical Challenges

↑ Propulsion Systems

- Liquids
 - Ground handling and loading of propellants -- toxicity & volatility
 - Valves and flow control for predictable burnout
- Solids
 - Propellant grain consistency (motor-to-motor)
 - Dangerous large grain mix, pour, and cure

• Structures

- Design, fabrication, and assembly of truss structures and interstages
- Cluster/stack integration
- Dynamic load margins throughout flight

• Control Electronics

- Accurate navigation, timing, sensing of booster variations
- Staging
- Power supplies and thermal control for LRBM duration flight



Key Technical Challenges (Cont)

- **Reentry Systems**
 - **↑ Payload packaging for high deceleration shock loads**
 - **Stable dynamic shape design and balancing techniques**
 - **Thermal protection against heating loads at LRBM reentry velocities**
- **↑ Fusing for payload detonation/dispersal at desired altitude**
- **System Test and Verification Technology**
 - **Onboard system performance instrumentation**
 - **Telemetry electronics and antennas (ballistic missile and range)**
 - **Flight data analysis tools**

13 Critical Technologies

- **High Energy Propellants**
- **Light Weight Subsystems**
- **Dynamic Structures Design and Analysis**
- **Aerodynamic Heat Protection Materials**
- **Advanced Flight Dynamics Control Systems**
- **Multi-Stage Separation and Ignition**
- **Payload Separation and Stabilization**
- **Payload Reentry Survival**
- **Warhead Fusing**
- **Guidance and Control Computers**
- **GPS/INS Platforms**
- **Flight Test Tracking and Telemetry**
- **High Fidelity Computer Simulation**


Required Engineering Infrastructure

- **Technical Expertise**
 - System design engineering
 - Fabrication methods
 - Materials & processes
 - Flight mechanics
 - Guidance & control
 - Modeling & simulation
- **Industry**
 - Propellant processing and handling
 - Propulsion subsystems
 - Electro/mechanical control systems
 - Structures manufacturing/assembly
 - Materials processing
 - Electronics production
 - Precision guidance fab. & assembly
 - Computer hardware and software
- **Flight Test**
 - Range size and access
 - Range instrumentation
 - Data analysis

**Home-Grown or "Contracted" Foreign Assistance Satisfies
Required Development Functions**

Third World Development Time Compression

Accelerating Missile Development




Desired Missile Capability ▲ can be attained by a combination of development "investments" that may be hard to identify

? Critical Unknowns:


- 1) Level of missile technology at "start point"
- 2) Foreign assistance to expedite system integration of acquired components

Iran's Missile Program Evolution


- Combines imported systems with indigenous development and testing
- Extensive use of foreign expertise
- Steady range growth beyond regional requirements



Development Time Estimate



Effective Time to Respond



Outline

- **German WW II Missile Development and Technology Migration**
- **Trends in Third World Ballistic Missile Weaponry**
- **Threat Development on a Compressed Schedule**
- **Candidate LRBM Configurations**
- **Summary**

Options for LRBM Development

- ➔ • Buy LRBM (MRBM, IRBM, ICBM)**
- Buy & Convert Space Launch Vehicle
- Cluster/Stack Existing Tactical Missiles
- Design/Build Booster - Stack Existing Missile for Upper Stage
- Design/Build Entire Missile


Available IRBMs

Missile	Payload(kg)	Range(Km)	Warhead	Country	IOC
• DF-3/DF-3A	2000/ 2150	2800	Conv./ NBC	China	1971/ 1986
• CSS-2	1900	3100	Conv.	Saudi Arabia	1988
• CSS-3	2200	4750	Conv./ NBC	China	1978
• DF-25	2000	1700	Conv./ NBC	China	Dev. Stop 1996
• Agni 1	1000	2000	Conv.	India	1998
• Agni 2	1000	3000	Conv./ NBC	India	2002?
• Shahab 4	1000	3000	Conv./ NBC	Iran	2002
• Shahab 5	?	?	Conv./ NBC	Iran	2005?
• Jericho 3	1000	4800	Conv./N?	Israel	2000?
• TD-1	1000	1500-2000	NBC	N.Korea	1998?
• TD-2	1000	2000-4000	NBC	N.Korea	1998?

Options for LRBM Development

- **Buy LRBM (MRBM, IRBM, ICBM)**
- **Buy & Convert Space Launch Vehicle**
- **Cluster/Stack Existing Tactical Missiles**
- **Design/Build Booster - Stack Existing Missile for Upper Stage**
- **Design/Build Entire Missile**

CIA Assessment of SLV-LRBM Conversion




- Only unique ballistic missile technology is the warhead
- RV, separation, guidance & control, and strap-on booster SLV technologies may be adequate
- Staging, propellants, airframe, engines, thrust control, and nozzles are the same as SLV

Figure from 5/14/98 CIA briefing; as depicted in *Aviation Week & Space Technology*, June 1, 1998.

Indian ASLV Conversion

ASLV

- **Propulsion Configuration**
 - 4-stage solid propellant booster (SLV-3)
 - 2 strap-on rocket motors
- **Space Launch Capability**
 - Launch weight 39,000 kg
 - Payload weight 150 kg
 - Orbit altitude 400 km
 - Inclination 46 degrees
- **Ballistic Missile Capability**
 - Launch weight 40,000 kg
 - Payload weight 1000 kg
 - Range (NRE) 4,000 km



From Jane's Information Group


Drawing from Federation of American Scientists:
<http://www.fas.org/spp/guide/india/launch/aslv.htm>

Israeli SHAVIT Conversion

- **Propulsion Configuration**
 - 3-stage solid propellant booster (based on Jericho 2)
 - NEXT, slightly larger follow-on
- **Space Launch Capability**
 - Launch weight 29,000 kg
 - Payload weight 800 kg
 - Orbit altitude 400 km
 - Inclination Polar
- **Ballistic Missile Capability**
 - Launch weight 29,000 (est.)
 - Payload weight 1,100 kg
 - Range (NRE) 5,000-7,000 km

From Jane's Information Group

SHAVIT SLV



14 m. X
1.56 m. dia.

- Demonstrated 160 kg payload to 207 x 1587 km elliptical orbit @ 143 degree retrograde inclination.

Jericho 2 From Federation of American Scientists web site:
<http://www.fas.org/spp/guide/Israel/launch/index.htm>

Japanese M-3 or M-5 Conversion

- The M-3 space launch vehicle "family" could be converted into an IRBM with a 500+ kg payload and a range of 4,000+ km. The Japanese Government has officially refuted this allegation. *

- The M-5 is a three- or four-stage, solid propellant launch vehicle designed to carry payloads of 2,000 kg to 200 km; 1,200 kg to 500 km and 800 kg to GTO. *


- Three-stage version shown:

- Length = 31.0 m
- Diameter = 2.5 m
- Launch weight = 130,000 kg

M-5 LRBM performance has not yet been assessed

From Jane's Information Group


M-5 SLV



9 m.	Insulated payload faring &
6.7 m	Third stage w/ ENEC & TVC
13.7 m	2nd stage w/ ENEC & TVC
	1st stage w/ movable nozzle

Source: Jane's Strategic Weapons

Options for LRBM Development

- Buy LRBM (MRBM, IRBM, ICBM)
- Buy & Convert Space Launch Vehicle
-  Cluster/Stack Existing Missiles
- Design/Build Booster - Stack Existing Missile for Upper Stage
- Design/Build Entire Missile

Two Feasible LRBM Designs

Liquid

- Clustered CSS-2 ballistic missiles
Stage 1 -- 3 CSS-2's } Separate
Stage 2 -- 1 CSS-2 } at burnout

Payload -- 1000 kg

Guidance -- 150 kg

Launch Weight -- 255,400 kg

Reentry Angle -- 30 degrees

Time of Flight -- 46.5 minutes

Range -- 10,000 km

Solid

- Clustered M-9 ballistic missiles
Stage 1 -- 7 M-9's } Separate
Stage 2 -- 3 M-9's } at burnout
Stage 3 -- 1 M-9 }

Payload -- 750 kg

Guidance -- 150 kg

Launch Weight -- 59,000 kg


Reentry Angle -- 30 degrees

Time of Flight -- 28.5 minutes


Range -- 6,500 km

Design Issues Considered in Assessment

- RV structure & materials for 30 degree reentry
- Payload separation at booster burnout; G&C stays with spent upper stage
- Interstages between booster stages sized for flight loads at increased diameter
- Revised raceways and electrical system wiring
- Guidance subsystem increased power and cooling
- Truss structure for clustered rocket motors
- Extendible nozzle exit cones (upper stages only)
- Booster separation mechanisms
- Booster thermal protection for aero loads and motor nozzle heat



Range Sensitivity to Payload Weight



Evaluation Methodology

- **AS-2530 Flight Simulation Code**
 - 3 - degrees of freedom
 - Non-rotating spherical earth
 - Standard atmospheric properties
- **Powered ascent flight profile**
 - Vertical launch
 - Instantaneous pitchover
 - Gravity turn
 - Payload separation at booster burnout
- **Payload flight profile**
 - Keplerian free flight
 - Keplerian reentry
 - No reentry angle of attack
- **Missile characteristics**
 - Nominal ballistics
 - Nominal weights
 - Estimated drag properties

Outline

- **German WW II Missile Development and Technology Migration**
- **Trends in Third World Ballistic Missile Weaponry**
- **Threat Development on a Compressed Schedule**
- **Candidate LRBM Configurations**
- **Summary**

Summary

- **Third World Countries are capable of achieving LRBM capability**
- **Innovative technical shortcuts may be used for different national goals**
 - **Political or coercive vs military capability**
- **Time to First Flight may be much earlier than currently anticipated**
- **Time from observed threat to first launch may be very short**
- **MTCR is not stopping missile technology proliferation**
- **Developed countries are currently marketing critical ballistic missile technologies, systems, and personnel**

The Time Between Inescapable Evidence of a Developing Threat to When That Threat is Fielded May be Less Than the Time in Which We Can Respond