

AD

SPECIAL PUBLICATION ARCCB-SP-99006

**INDEX TO BENET LABORATORIES  
TECHNICAL REPORTS - 1998**

**R. D. NEIFELD**

APRIL 1999

	<p><b>US ARMY ARMAMENT RESEARCH, DEVELOPMENT AND ENGINEERING CENTER CLOSE COMBAT ARMAMENTS CENTER BENÉT LABORATORIES WATERVLIET, N.Y. 12189-4050</b></p>	
---	--	---

APPROVED FOR PUBLIC RELEASE; DISTRIBUTION UNLIMITED

20000612 085

## **DISCLAIMER**

The findings in this report are not to be construed as an official Department of the Army position unless so designated by other authorized documents.

The use of trade name(s) and/or manufacturer(s) does not constitute an official endorsement or approval.

## **DESTRUCTION NOTICE**

For classified documents, follow the procedures in DoD 5200.22-M, Industrial Security Manual, Section II-19, or DoD 5200.1-R, Information Security Program Regulation, Chapter IX.

For unclassified, limited documents, destroy by any method that will prevent disclosure of contents or reconstruction of the document.

For unclassified, unlimited documents, destroy when the report is no longer needed. Do not return it to the originator.

# REPORT DOCUMENTATION PAGE

*Form Approved*  
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

<b>1. AGENCY USE ONLY (Leave blank)</b>	<b>2. REPORT DATE</b> April 1999	<b>3. REPORT TYPE AND DATES COVERED</b> Final	
<b>4. TITLE AND SUBTITLE</b> INDEX TO BENET LABORATORIES TECHNICAL REPORTS - 1998		<b>5. FUNDING NUMBERS</b> N/A	
<b>6. AUTHOR(S)</b> R.D. Neifeld			
<b>7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)</b> U.S. Army ARDEC Benet Laboratories, AMSTA-AR-CCB-O Watervliet, NY 12189-4050		<b>8. PERFORMING ORGANIZATION REPORT NUMBER</b>  ARCCB-SP-99006	
<b>9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)</b> U.S. Army ARDEC Close Combat Armaments Center Picatinny Arsenal, NJ 07806-5000		<b>10. SPONSORING/MONITORING AGENCY REPORT NUMBER</b>	
<b>11. SUPPLEMENTARY NOTES</b>			
<b>12a. DISTRIBUTION / AVAILABILITY STATEMENT</b> Approved for public release; distribution unlimited.		<b>12b. DISTRIBUTION CODE</b>	
<b>13. ABSTRACT (Maximum 200 words)</b>  This is a compilation of technical reports published by Benet Laboratories during 1998.			
<b>14. SUBJECT TERMS</b> Benet Laboratories, Technical Publications, Bibliographies, Abstracts, Document Control Data			<b>15. NUMBER OF PAGES</b> 31
			<b>16. PRICE CODE</b>
<b>17. SECURITY CLASSIFICATION OF REPORT</b> UNCLASSIFIED	<b>18. SECURITY CLASSIFICATION OF THIS PAGE</b> UNCLASSIFIED	<b>19. SECURITY CLASSIFICATION OF ABSTRACT</b> UNCLASSIFIED	<b>20. LIMITATION OF ABSTRACT</b>  UL

## TABLE OF CONTENTS

	<u>Page</u>
LIST OF REPORTS.....	1
AUTHOR INDEX.....	3
SUBJECT INDEX.....	5
AD NUMBERS.....	10
REPORT DOCUMENTATION PAGES.....	11

## TECHNICAL REPORTS 1998

REPORT NUMBER	TITLE	AUTHOR	DATE
ARCCB-TR-98001	Elastic Comparison of Four Thread Forms	G.P. O'Hara	Feb 1998
ARCCB-TR-98002	The Effect of a Curing Agent and an Accelerator on the Glass Transition of Brominated and Unbrominated Diglycidyl Ether of Bisphenol A	M.F. Fleszar	Mar 1998
ARCCB-TR-98003	Texture Analysis of CoGe <sub>2</sub> Alloy Films Grown Heteroepitaxially on GaAs(100) Using Partially Ionized Beam Deposition	K.E. Mello S.L. Lee S.P. Murarka T.-M. Lu	Apr 1998
ARCCB-TR-98004	Grain Orientations in Electrolytic High Contraction and Low Contraction Chromium Deposition	S.L. Lee D. Windover K.E. Mello	Apr 1998
ARCCB-SP-98005	Index to Benet Laboratories Technical Reports - 1997	R.D. Neifeld	Apr 1998
ARCCB-TR-98006	Compressive Thermal Yielding Leading to Hydrogen Cracking in a Fired Cannon	J.H. Underwood A.P. Parker P.J. Cote S. Sopok	Apr 1998
ARCCB-TR-98007	Residual Stress in a Swage Autofrettaged Steel Cylinder with Semi-Circular Mid-Wall Channels	S.L. Lee E. Hyland J. Neese D. Windover	May 1998
ARCCB-TR-98008	(1/F) <sup>n</sup> Electronic Flicker Pulsing	M.A. Johnson P.J. Cote	May 1998
ARCCB-CR-98009	Stability of Arrays of Multiple-Edge Cracks	A.P. Parker J.H. Underwood (Benet POC)	Jun 1998
ARCCB-TR-98010	The Bauschinger Effect in Autofrettaged Tubes - A Comparison of Models Including the ASME Code	A.P. Parker J.H. Underwood	Jun 1998
ARCCB-TR-98011	X-Ray Determination of Texture and Residual Stress in Low Contraction Electrolytic Chromium Deposition	S.L. Lee D. Windover	Jul 1998
ARCCB-TR-98012	Phase, Residual Stress, and Texture in Triode-Sputtered Tantalum Coatings on Steel	S.L. Lee D. Windover	Jul 1998
ARCCB-TR-98013	Dynamic Modeling for Design: Space-Time Finite Element Formulation of an Euler Beam	E.L. Kathe	Jul 1998
ARCCB-TR-98014	Failure Analysis of an 84-mm, M3, Carl Gustaf, Recoilless Rifle	K. Miner A. Kapusta K. Olsen	Jul 1998

### TECHNICAL REPORTS 1998

REPORT NUMBER	TITLE	AUTHOR	DATE
ARCCB-TR-98015	Use of the Instrumented Bolt and Constant Displacement Bolt-Loaded Specimen to Measure In Situ Hydrogen Crack Growth in High Strength Steels	G.N. Vigilante J.H. Underwood D. Crayon	Aug 1998
ARCCB-TR-98016	The Role of Vanadium Carbide Traps in Reducing the Hydrogen Embrittlement Susceptibility of High Strength Alloy Steels	G.L. Spencer D.J. Duquette	Aug 1998
ARCCB-TR-98017	The Cannon-Projectile Blow-By Flow Field	C.A. Andrade A. Cunningham H.T. Nagamatsu D.G. Messitt	Sep 1998
ARCCB-TR-98018	Comprehensive Erosion Model for the 120-mm M256/M829A2 Gun System	S. Sopok P. Vottis P. O'Hara G. Pflegl C. Rickard	Oct 1998
ARCCB-TR-98019	Shot-by-Shot Erosion Modeling of Retired 120-mm M256 Gun Tube #1988	S. Sopok P. Vottis P. O'Hara G. Pflegl C. Rickard	Oct 1998
ARCCB-TR-98020	Comprehensive Erosion Model for the 120-mm M256/M829 Gun System	S. Sopok P. Vottis P. O'Hara G. Pflegl C. Rickard	Dec 1998

## AUTHOR INDEX 1998

<b>AUTHOR</b>	<b>REPORT NUMBER</b>
Andrade, C.A.	ARCCB-TR-98017
Cote, P.J.	ARCCB-TR-98006 ARCCB-TR-98008
Crayon, D.	ARCCB-TR-98015
Cunningham, B.	ARCCB-TR-98017
Duquette, D.J.	ARCCB-TR-98016
Fleszar, M.F.	ARCCB-TR-98002
Hyland, E.	ARCCB-TR-98007
Johnson, M.A.	ARCCB-TR-98008
Kapusta, A.	ARCCB-TR-98014
Kathe, E.L.	ARCCB-TR-98013
Lee, S.L.	ARCCB-TR-98003 ARCCB-TR-98004 ARCCB-TR-98007 ARCCB-TR-98011 ARCCB-TR-98012
Lu, T.-M.	ARCCB-TR-98003
Mello, K.E.	ARCCB-TR-98003 ARCCB-TR-98004
Messitt, D.G.	ARCCB-TR-98017
Miner, K.	ARCCB-TR-98014
Murarka, S.P.	ARCCB-TR-98003
Nagamatsu, H.T.	ARCCB-TR-98017
Neese, J.	ARCCB-TR-98007
Neifeld, R.D.	ARCCB-SP-98005

## AUTHOR INDEX 1998

O'Hara, G.P.	ARCCB-TR-98001 ARCCB-TR-98018 ARCCB-TR-98019 ARCCB-TR-98020
Olsen, K.	ARCCB-TR-98014
Parker, A.P.	ARCCB-TR-98006 ARCCB-CR-98009 ARCCB-TR-98010
Pflegl, G.	ARCCB-TR-98018 ARCCB-TR-98019 ARCCB-TR-98020
Rickard, C.	ARCCB-TR-98018 ARCCB-TR-98019 ARCCB-TR-98020
Sopok, S.	ARCCB-TR-98006 ARCCB-TR-98018 ARCCB-TR-98019 ARCCB-TR-98020
Spencer, G.L.	ARCCB-TR-98016
Underwood, J.H.	ARCCB-TR-98006 ARCCB-CR-98009 ARCCB-TR-98010 ARCCB-TR-98015
Vigilante, G.N.	ARCCB-TR-98015
Vottis, P.	ARCCB-TR-98018 ARCCB-TR-98019 ARCCB-TR-98020
Windover, D.	ARCCB-TR-98004 ARCCB-TR-98007 ARCCB-TR-98011 ARCCB-TR-98012

## SUBJECT INDEX 1998

<b>SUBJECT</b>	<b>REPORT NUMBER</b>
A723 Steel	ARCCB-TR-98006 ARCCB-TR-98015 ARCCB-TR-98016
Abstracts	ARCCB-SP-98005
Accelerators	ARCCB-TR-98002
Ammunition	ARCCB-TR-98018 ARCCB-TR-98019 ARCCB-TR-98020
Autofrettage	ARCCB-TR-98007 ARCCB-TR-98010
Bauschinger Effect	ARCCB-TR-98007 ARCCB-TR-98010
Beams (Structural)	ARCCB-TR-98013
Bibliographies	ARCCB-SP-98005
Bolt-Loaded Specimen	ARCCB-TR-98015
Cannon Tubes	ARCCB-TR-98006
Cannons	ARCCB-TR-98017
Carl Gustaf	ARCCB-TR-98014
Chaos Theory	ARCCB-TR-98008
Chromium	ARCCB-TR-98004 ARCCB-TR-98011
Cobalt Alloys	ARCCB-TR-98003
Composites	ARCCB-TR-98014
Computational Fluid Dynamics	ARCCB-TR-98017
Crack Propagation	ARCCB-TR-98015

## SUBJECT INDEX 1998

Cracking (Fracturing)	ARCCB-TR-98006 ARCCB-TR-98007 ARCCB-CR-98009
Curing Agents	ARCCB-TR-98002
Deposition	ARCCB-TR-98004
Diglycidyl Ether of Bisphenol A	ARCCB-TR-98002
Edge Cracks	ARCCB-CR-98009
Elastic Properties	ARCCB-TR-98001
Electrolytes	ARCCB-TR-98004
Electromagnetic Interference	ARCCB-TR-98008
Electronics	ARCCB-TR-98008
Environmental Cracking	ARCCB-TR-98006 ARCCB-TR-98015
Epitaxial Growth	ARCCB-TR-98003
Epoxy	ARCCB-TR-98002
Erosion	ARCCB-TR-98017 ARCCB-TR-98018 ARCCB-TR-98019 ARCCB-TR-98020
Euler Equations	ARCCB-TR-98013
Failure (Mechanics)	ARCCB-TR-98014
Fatigue Life	ARCCB-TR-98010
Finite Element Analysis	ARCCB-TR-98007 ARCCB-TR-98013
Flow Fields	ARCCB-TR-98017
4340 Steel	ARCCB-TR-98016
Fracture (Mechanics)	ARCCB-CR-98009 ARCCB-TR-98015

## SUBJECT INDEX 1998

Germanides	ARCCB-TR-98003
Glass Transition	ARCCB-TR-98002
Grain Structures (Metallurgy)	ARCCB-TR-98004
Gun Barrels	ARCCB-TR-98014
Gun Tubes	ARCCB-TR-98006 ARCCB-CR-98009 ARCCB-TR-98010 ARCCB-TR-98015 ARCCB-TR-98017 ARCCB-TR-98018 ARCCB-TR-98019 ARCCB-TR-98020
Guns	ARCCB-SP-98005
Heat Transfer	ARCCB-TR-98017
High Contraction	ARCCB-TR-98004 ARCCB-TR-98011
High Strength Alloys	ARCCB-TR-98015 ARCCB-TR-98016
High Strength Steels	ARCCB-TR-98010
Hydrogen Embrittlement	ARCCB-TR-98006 ARCCB-TR-98015 ARCCB-TR-98016
Indexes	ARCCB-SP-98005
Instrumented Bolt	ARCCB-TR-98015
Interior Ballistics	ARCCB-TR-98018 ARCCB-TR-98019 ARCCB-TR-98020
Ionization	ARCCB-TR-98003
Load Distribution	ARCCB-TR-98001
Low Contraction	ARCCB-TR-98004 ARCCB-TR-98011

## SUBJECT INDEX 1998

M829 Rounds	ARCCB-TR-98019 ARCCB-TR-98020
M829A2 Rounds	ARCCB-TR-98018 ARCCB-TR-98019
Magnetic Particle Inspection	ARCCB-TR-98014
Niobium	ARCCB-TR-98012
Noise (Electrical and Electromagnetic)	ARCCB-TR-98008
Notch Tensile Testing	ARCCB-TR-98016
Obturation (Ballistics)	ARCCB-TR-98017
120-mm M256 Cannons	ARCCB-TR-98018 ARCCB-TR-98019 ARCCB-TR-98020
Optimization	ARCCB-TR-98013
Orientation (Direction)	ARCCB-TR-98004
Perforated Cylinders	ARCCB-TR-98007
Permafrost	ARCCB-CR-98009
Phase Studies	ARCCB-TR-98012
Pressure Vessels	ARCCB-TR-98010
Projectile Leakage Blow-by	ARCCB-TR-98017
Protective Coatings	ARCCB-TR-98011
Pulsing	ARCCB-TR-98008
Radial Stress	ARCCB-TR-98001
Recoilless Guns	ARCCB-TR-98014
Refractory Coatings	ARCCB-TR-98012
Reports	ARCCB-SP-98005

## SUBJECT INDEX 1998

Residual Stress	ARCCB-TR-98006 ARCCB-TR-98007 ARCCB-CR-98009 ARCCB-TR-98011 ARCCB-TR-98012
Resins	ARCCB-TR-98002
Rifles	ARCCB-TR-98014
Scanning Electron Microscopy	ARCCB-TR-98014
Screw Threads	ARCCB-TR-98001
Shedding Behavior	ARCCB-CR-98009
Sputtering	ARCCB-TR-98012
Steel	ARCCB-TR-98010 ARCCB-TR-98015
Stress Concentration	ARCCB-TR-98001
Stress Intensity Factor	ARCCB-TR-98006 ARCCB-CR-98009
Structural Analysis	ARCCB-TR-98013
Tantalum	ARCCB-TR-98012
Technical Publications	ARCCB-SP-98005
Texture	ARCCB-TR-98003 ARCCB-TR-98004 ARCCB-TR-98011 ARCCB-TR-98012
Thermal Yielding	ARCCB-TR-98006
Thread Forms	ARCCB-TR-98001
Ultrasonic Tests	ARCCB-TR-98014
Vanadium	ARCCB-TR-98016
X-Ray Diffraction	ARCCB-TR-98012

## AD NUMBERS 1998

REPORT NUMBER	AD NUMBER
ARCCB-TR-98001	A338 658
ARCCB-TR-98002	A338 695
ARCCB-TR-98003	A342 320
ARCCB-TR-98004	A342 324
ARCCB-SP-98005	A342 997
ARCCB-TR-98006	A344 812
ARCCB-TR-98007	A346 749
ARCCB-TR-98008	A348 335
ARCCB-CR-98009	A348 587
ARCCB-TR-98010	A349 152
ARCCB-TR-98011	A350 268
ARCCB-TR-98012	A350 108
ARCCB-TR-98013	A350 722
ARCCB-TR-98014	A352 481
ARCCB-TR-98015	A353 523
ARCCB-TR-98016	A354 284
ARCCB-TR-98017	A354 740
ARCCB-TR-98018	A356 146
ARCCB-TR-98019	A355 855
ARCCB-TR-98020	A358 731

# REPORT DOCUMENTATION PAGE

Form Approved  
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

<b>1. AGENCY USE ONLY (Leave blank)</b>		<b>2. REPORT DATE</b> February 1998	<b>3. REPORT TYPE AND DATES COVERED</b> Final	
<b>4. TITLE AND SUBTITLE</b> ELASTIC COMPARISON OF FOUR THREAD FORMS			<b>5. FUNDING NUMBERS</b> AMCMS No. 6226.24.H191.1	
<b>6. AUTHOR(S)</b> G. Peter O'Hara				
<b>7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)</b> U.S. Army ARDEC Benet Laboratories, AMSTA-AR-CCB-O Watervliet, NY 12189-4050			<b>8. PERFORMING ORGANIZATION REPORT NUMBER</b>  ARCCB-TR-98001	
<b>9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES)</b> U.S. Army ARDEC Close Combat Armaments Center Picatinny Arsenal, NJ 07806-5000			<b>10. SPONSORING / MONITORING AGENCY REPORT NUMBER</b>	
<b>11. SUPPLEMENTARY NOTES</b>  Presented at the 1997 ASME Pressure Vessels and Piping Conference, 27 July 1997, Orlando, FL. Published in proceedings of the conference.				
<b>12a. DISTRIBUTION / AVAILABILITY STATEMENT</b>  Approved for public release; distribution unlimited.			<b>12b. DISTRIBUTION CODE</b>	
<b>13. ABSTRACT (Maximum 200 words)</b>  Previously, this author introduced the concept that all screw thread forms have a structural "Characteristic Curve," which defines the basic stress concentration as a function of a radial stress in the joint. An additional set of characteristic curves is produced when the general stress field is considered. The standard analysis is for a single-thread tooth, isolated from a long chain of identical teeth, that is computationally efficient and facilitates the calculation of a family of characteristic curves. This work presents the characteristic plots for four different threads, the 7-degree British buttress, a 15-degree asymmetric "V," the 20-degree Benet buttress, and a special 30-degree "V." These four threads were selected because they are or may be useful in high pressure systems. Together they suggest the possibility of a standard thread family for high pressure applications.				
<b>14. SUBJECT TERMS</b> Screws, Screw Threads, Thread Forms, Threaded Connections, Stress, Stress Concentration			<b>15. NUMBER OF PAGES</b> 23	
			<b>16. PRICE CODE</b>	
<b>17. SECURITY CLASSIFICATION OF REPORT</b> UNCLASSIFIED	<b>18. SECURITY CLASSIFICATION OF THIS PAGE</b> UNCLASSIFIED	<b>19. SECURITY CLASSIFICATION OF ABSTRACT</b> UNCLASSIFIED	<b>20. LIMITATION OF ABSTRACT</b> UL	

# REPORT DOCUMENTATION PAGE

Form Approved  
GSA No. 7540-01-280-5500

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (9704-0188), Washington, DC 20503.

<b>1. AGENCY USE ONLY (Leave blank)</b>	<b>2. REPORT DATE</b> March 1998	<b>3. REPORT TYPE AND DATES COVERED</b> Final	
<b>4. TITLE AND SUBTITLE</b> THE EFFECT OF A CURING AGENT AND AN ACCELERATOR ON THE GLASS TRANSITION OF BROMINATED AND UNBROMINATED DIGLYCIDYL ETHER OF BISPHENOL A		<b>5. FUNDING NUMBERS</b> AMCMS No. 6226.24.H180.0 PRON No. 7AARD00010	
<b>6. AUTHOR(S)</b> Mark F. Fleszar		<b>8. PERFORMING ORGANIZATION REPORT NUMBER</b> ARCCB-TR-98002	
<b>7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)</b> U.S. Army ARDEC Benet Laboratories, AMSTA-AR-CCB-O Watervliet, NY 12189-4050			
<b>9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES)</b> U.S. Army ARDEC Close Combat Armaments Center Picatinny Arsenal, NJ 07806-5000		<b>10. SPONSORING / MONITORING AGENCY REPORT NUMBER</b>	
<b>11. SUPPLEMENTARY NOTES</b> Presented at the 1997 North American Thermal Analysis Society Conference, McLean, VA, 6-9 September 1997. Published in proceedings of the conference.			
<b>12a. DISTRIBUTION / AVAILABILITY STATEMENT</b> Approved for public release; distribution unlimited.		<b>12b. DISTRIBUTION CODE</b>	
<b>13. ABSTRACT (Maximum 200 words)</b> Dicyandiamide—a solid with a melting point of 209°C—is one of a unique group of curing agents that are insoluble in epoxy at room temperature. As a curing agent for epoxy resins, dicyandiamide can react through all four nitrogen groups—reacting with the resin at both epoxide and hydroxyl sites. When mixed with either diglycidyl ether of bisphenol A or diglycidyl ether of tetrabromobisphenol A, the formulation is stable enough to be stored for 6 to 12 months. Because dicyandiamide's solubility is low at room temperature, the curing reaction is limited until the temperature increases enough to dissolve the curing agent. To improve the ability to process the resin, an accelerator (such as diuron) can be added to reduce the curing temperature. The curing reaction then proceeds via a complex mechanism that is not dominated by a single reaction. Each compound's effect on the cured material was studied by measuring changes in the glass transition temperature.			
<b>14. SUBJECT TERMS</b> Curing Agents, Accelerator, Glass Transition, Epoxy, Resins, Diglycidyl Ether of Bisphenol A		<b>15. NUMBER OF PAGES</b> 7	
<b>17. SECURITY CLASSIFICATION OF REPORT</b> UNCLASSIFIED		<b>16. PRICE CODE</b>	
		<b>20. LIMITATION OF ABSTRACT</b> UL	
<b>18. SECURITY CLASSIFICATION OF THIS PAGE</b> UNCLASSIFIED	<b>19. SECURITY CLASSIFICATION OF ABSTRACT</b> UNCLASSIFIED		

# REPORT DOCUMENTATION PAGE

Form Approved  
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

<b>1. AGENCY USE ONLY (Leave blank)</b>		<b>2. REPORT DATE</b> April 1998	<b>3. REPORT TYPE AND DATES COVERED</b> Final	
<b>4. TITLE AND SUBTITLE</b> TEXTURE ANALYSIS OF CoGe <sub>2</sub> ALLOY FILMS GROWN HETEROEPITAXIALLY ON GaAs(100) USING PARTIALLY IONIZED BEAM DEPOSITION			<b>5. FUNDING NUMBERS</b> AMCMS No. 6226.24.H191.1	
<b>6. AUTHOR(S)</b> K.E. Mello (RPI, Troy, NY), S.L. Lee, S.P. Murarka (RPI), and T.-M. Lu (RPI)				
<b>7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)</b> U.S. Army ARDEC Benet Laboratories, AMSTA-AR-CCB-O Watervliet, NY 12189-4050			<b>8. PERFORMING ORGANIZATION REPORT NUMBER</b>  ARCCB-TR-98003	
<b>9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)</b> U.S. Army ARDEC Close Combat Armaments Center Picatinny Arsenal, NJ 07806-5000			<b>10. SPONSORING/MONITORING AGENCY REPORT NUMBER</b>	
<b>11. SUPPLEMENTARY NOTES</b> Submitted to <i>Journal of Applied Physics</i> .				
<b>12a. DISTRIBUTION / AVAILABILITY STATEMENT</b> Approved for public release; distribution unlimited.			<b>12b. DISTRIBUTION CODE</b>	
<b>13. ABSTRACT (Maximum 200 words)</b> Reflection X-Ray pole figure analysis techniques were used to study the heteroepitaxial relationships of the cobalt germanide CoGe <sub>2</sub> to GaAs(100). The alloy films were grown using the partially ionized beam deposition technique, in which low energy Ge <sup>+</sup> ions are used to alter the heteroepitaxial orientation of the CoGe <sub>2</sub> deposits. The CoGe <sub>2</sub> [001](100)∥GaAs[100](001) orientation, which has the smallest lattice mismatch, occurred for depositions performed at a substrate temperature around 280°C and with ~1200 eV Ge <sup>+</sup> ions. Lowering the substrate temperature or reducing the Ge <sup>+</sup> ion energy leads to CoGe <sub>2</sub> (100) orientation domination with CoGe <sub>2</sub> [100](010)∥GaAs[100](001) and CoGe <sub>2</sub> [100](001)∥GaAs[100](001). Substrate temperature alone produced only the CoGe <sub>2</sub> (100) orientation. For CoGe <sub>2</sub> (001) films, additional energy was required from Ge <sup>+</sup> ions in the evaporant stream.				
<b>14. SUBJECT TERMS</b> CoGe <sub>2</sub> , Epitaxy, Texture, Partially Ionized Beam Deposition			<b>15. NUMBER OF PAGES</b> 24	
			<b>16. PRICE CODE</b>	
<b>17. SECURITY CLASSIFICATION OF REPORT</b> UNCLASSIFIED	<b>18. SECURITY CLASSIFICATION OF THIS PAGE</b> UNCLASSIFIED	<b>19. SECURITY CLASSIFICATION OF ABSTRACT</b> UNCLASSIFIED	<b>20. LIMITATION OF ABSTRACT</b> UL	

# REPORT DOCUMENTATION PAGE

Form Approved  
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE April 1998	3. REPORT TYPE AND DATES COVERED Final	
4. TITLE AND SUBTITLE GRAIN ORIENTATIONS IN ELECTROLYTIC HIGH CONTRACTION AND LOW CONTRACTION CHROMIUM DEPOSITION			5. FUNDING NUMBERS AMCMS No. 6111.01.91A1.1	
6. AUTHOR(S) S.L. Lee, D. Windover, and K.E. Mello (RPI, Troy, NY)				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army ARDEC Benet Laboratories, AMSTA-AR-CCB-O Watervliet, NY 12189-4050			8. PERFORMING ORGANIZATION REPORT NUMBER ARCCB-TR-98004	
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) U.S. Army ARDEC Close Combat Armaments Center Picatinny Arsenal, NJ 07806-5000			10. SPONSORING / MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES Published in <i>Advances in X-Ray Analysis</i> , Volume 41.				
12a. DISTRIBUTION / AVAILABILITY STATEMENT Approved for public release; distribution unlimited.			12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) Several electrochemical deposition parameters affect grain orientations, which, in turn, affect coating quality and performance. An enhanced x-ray pole figure technique has been used to study grain distribution anisotropy in electrolytic high contraction (HC) and low contraction (LC) chromium. Temperature and current density are the most important factors controlling grain orientation. Production HC chromium deposited on steel at low temperature and low current density exhibited strong <111> fiber texture, while LC chromium deposited on steel at high temperature and high current density exhibited near random crystalline orientation. The drastic change in grain orientation on steel from strongly textured HC chromium to randomly oriented LC chromium is accompanied by marked differences in crack density, hardness, deposition rate, microstructure, thermal behavior upon heating and cooling, and improved wear and erosion performance. Laboratory LC chromium specimens that were deposited on copper plates with and without sample rotation and pulse current plating showed preferred (211) and (222) orientations. Although substrate material affects grain orientation, sample rotation and pulse current plating play a less important role.				
14. SUBJECT TERMS Chromium, Electrolytic, Contraction, Texture, Pole Figure, Orientation			15. NUMBER OF PAGES 13	
			16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT UL	

# REPORT DOCUMENTATION PAGE

Form Approved  
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

<b>1. AGENCY USE ONLY (Leave blank)</b>		<b>2. REPORT DATE</b> April 1998	<b>3. REPORT TYPE AND DATES COVERED</b> Final	
<b>4. TITLE AND SUBTITLE</b> INDEX TO BENET LABORATORIES TECHNICAL REPORTS - 1997			<b>5. FUNDING NUMBERS</b> N/A	
<b>6. AUTHOR(S)</b> R.D. Neifeld				
<b>7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)</b> U.S. Army ARDEC Benet Laboratories, AMSTA-AR-CCB-O Watervliet, NY 12189-4050			<b>8. PERFORMING ORGANIZATION REPORT NUMBER</b>  ARCCB-SP-98005	
<b>9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES)</b> U.S. Army ARDEC Close Combat Armaments Center Picatinny Arsenal, NJ 07806-5000			<b>10. SPONSORING / MONITORING AGENCY REPORT NUMBER</b>	
<b>11. SUPPLEMENTARY NOTES</b>				
<b>12a. DISTRIBUTION / AVAILABILITY STATEMENT</b> Approved for public release; distribution unlimited.			<b>12b. DISTRIBUTION CODE</b>	
<b>13. ABSTRACT (Maximum 200 words)</b> This is a compilation of technical reports published by Benet Laboratories during 1997.				
<b>14. SUBJECT TERMS</b> Benet Laboratories, Technical Publications, Bibliographies, Abstracts, Document Control Data			<b>15. NUMBER OF PAGES</b> 44	
			<b>15. PRICE CODE</b>	
<b>17. SECURITY CLASSIFICATION OF REPORT</b> UNCLASSIFIED	<b>18. SECURITY CLASSIFICATION OF THIS PAGE</b> UNCLASSIFIED	<b>19. SECURITY CLASSIFICATION OF ABSTRACT</b> UNCLASSIFIED	<b>20. LIMITATION OF ABSTRACT</b> UL	

# REPORT DOCUMENTATION PAGE

Form Approved  
GMB No. 0704-0138

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0138), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)	2. REPORT DATE April 1998	3. REPORT TYPE AND DATES COVERED Final	
4. TITLE AND SUBTITLE COMPRESSIVE THERMAL YIELDING LEADING TO HYDROGEN CRACKING IN A FIRED CANNON		5. FUNDING NUMBERS AMCMS No. 6226.24.H180.0 PRON No. TU6A6F361ABJ	
6. AUTHOR(S) John H. Underwood, Anthony P. Parker (Royal Military College of Science, Cranfield University, UK), Paul J. Cote, and Samuel Sopok			
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army ARDEC Benet Laboratories, AMSTA-AR-CCB-O Watervliet, NY 12189-4050		8. PERFORMING ORGANIZATION REPORT NUMBER  ARCCB-TR-98006	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) U.S. Army ARDEC Close Combat Armaments Center Picatinny Arsenal, NJ 07806-5000		10. SPONSORING/MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES To be presented at the ASME Pressure Vessels and Piping Conference, San Diego, CA, 26-30 July 1998. To be published in <i>ASME Journal of Pressure Vessel Technology</i> .			
12a. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution unlimited.		12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words)  Investigation of environmental cracking of a 1100 MPa yield strength A723 steel cannon tube subjected to prototype firings is described. Metallographic results show cracking of the steel beneath a 0.12 mm protective layer of chromium. Cracks undermine and remove sections of chromium and lead to localized erosion that ruins the cannon. Key features of the firing thermal damage and cracking are: [i] recrystallization of the chromium to a depth of up to 0.08 mm; [ii] steel transformation to 0.19 mm below the chrome surface; [iii] two different periodic arrays of cracks normal to the hoop and axial directions, with mean depths of 0.23 and 0.46 mm, respectively.  Time-temperature-depth profiles for the firing cycle were derived via bi-material finite difference analysis of a semi-infinite solid which incorporated cannon combustion gas temperatures and material properties that vary as a function of temperature. The temperature and depth associated with the steel transformation were used to solve iteratively for the convective heat transfer coefficient. This value was further confirmed by the depths of chromium recrystallization and of the crack arrays in the two orientations. A profile of maximum temperature versus depth is used to determine the near-bore applied and residual stress distributions within the tube. The measured volume change of steel transformation is used to determine an upper limit on applied and residual stresses. These stresses are used to determine crack-tip stress intensity factors for the observed crack arrays and hence provide some explanation for the differential depths of cracking.  The near-bore temperature and residual stress distributions are used to help determine the cause of hydrogen cracking and measures to prevent cracking. Compressive yielding due to thermal loading produces near-bore tensile residual stresses and thereby causes hydrogen cracking. Prevention of cracking is discussed in relationship to hydrogen crack growth rate tests of alternative alloys and coatings.			
14. SUBJECT TERMS Thermal Yielding, Environmental Cracking, Hydrogen Cracking, A723 Steel, Cannon Tubes, Residual Stress, Stress Intensity Factors			15. NUMBER OF PAGES 10
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED			18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED
19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED		20. LIMITATION OF ABSTRACT UL	

# REPORT DOCUMENTATION PAGE

Form Approved  
GMB No. 0704-0133

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0133), Washington, DC 20503.

<b>1. AGENCY USE ONLY (Leave blank)</b>		<b>2. REPORT DATE</b> May 1998	<b>3. REPORT TYPE AND DATES COVERED</b> Final	
<b>4. TITLE AND SUBTITLE</b> RESIDUAL STRESS IN A SWAGE AUTOFRETTAGED STEEL CYLINDER WITH SEMI-CIRCULAR MID-WALL CHANNELS			<b>5. FUNDING NUMBERS</b> AMCMS No. 6111.01.91A1.1	
<b>6. AUTHOR(S)</b> S.L. Lee, E. Hyland, J. Neese, and D. Windover				
<b>7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)</b> U.S. Army ARDEC Benet Laboratories, AMSTA-AR-CCB-O Watervliet, NY 12189-4050			<b>8. PERFORMING ORGANIZATION REPORT NUMBER</b> ARCCB-TR-98007	
<b>9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES)</b> U.S. Army ARDEC Close Combat Armaments Center Picatinny Arsenal, NJ 07806-5000			<b>10. SPONSORING / MONITORING AGENCY REPORT NUMBER</b>	
<b>11. SUPPLEMENTARY NOTES</b> Presented at the SEM Spring Conference on Experimental and Applied Mechanics, Bellevue, WA, 2-4 June 1997. Published in proceedings of the conference.				
<b>12a. DISTRIBUTION / AVAILABILITY STATEMENT</b> Approved for public release; distribution unlimited.			<b>12b. DISTRIBUTION CODE</b>	
<b>13. ABSTRACT (Maximum 200 words)</b> <p>X-ray diffraction residual stress distribution analysis was performed for a swage autofrettaged, thick-walled, A723 steel compound cylinder with axial semi-circular mid-wall channels. Because of the existence of high stress gradient components in the stress distribution, the effect of spatial resolution and the x-ray beam spread function were investigated. Experimental stress measurements were compared with results from Tresca's model of a partially autofrettaged solid cylinder. Measured residual stresses were interpreted using an ABAQUS finite element model. Our experimental results verified most features of the predicted hoop stress distribution, including the high stress gradients and compressive stresses near the channel root areas. However, significantly reduced compressive stress levels were observed both near the bore and near the channel roots. An overestimate of fatigue lifetime could result if the reduction of compressive stresses observed experimentally were not taken into account. In solid autofrettaged cylinders, reduction of compressive stresses near the bore has been attributed to the Bauschinger effect. However, there is no analytical model incorporating the Bauschinger effect in the current geometry. This work demonstrated that the introduction of the semi-circular channels in a solid cylinder significantly modified the magnitude and location of stress fields. Both the bore and the channel roots are critical sites for stress concentration. Our analysis further determined that the channel roots were the most critical sites where cracks and failure should occur. Fatigue test results verified that cracking and failure occurred at the channel roots.</p>				
<b>14. SUBJECT TERMS</b> Swage Autofrettage, Perforated Cylinders, Bauschinger Effect, Residual Stress, Finite Element Analysis			<b>15. NUMBER OF PAGES</b> 14	
			<b>16. PRICE CODE</b>	
<b>17. SECURITY CLASSIFICATION OF REPORT</b> UNCLASSIFIED	<b>18. SECURITY CLASSIFICATION OF THIS PAGE</b> UNCLASSIFIED	<b>19. SECURITY CLASSIFICATION OF ABSTRACT</b> UNCLASSIFIED	<b>20. LIMITATION OF ABSTRACT</b> UL	

# REPORT DOCUMENTATION PAGE

Form Approved  
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)	2. REPORT DATE May 1998	3. REPORT TYPE AND DATES COVERED Final	
4. TITLE AND SUBTITLE  (1/f) <sup>n</sup> ELECTRONIC FLICKER PULSING		5. FUNDING NUMBERS  AMCMS No. 6111.01.91A1.1	
6. AUTHOR(S) Mark A. Johnson and Paul J. Cote		8. PERFORMING ORGANIZATION REPORT NUMBER  ARCCB-TR-98008	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army ARDEC Benet Laboratories, AMSTA-AR-CCB-O Watervliet, NY 12189-4050			
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) U.S. Army ARDEC Close Combat Armaments Center Picatinny Arsenal, NJ 07806-5000		10. SPONSORING / MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES Submitted for publication in <i>Electronic Design</i> .			
12a. DISTRIBUTION / AVAILABILITY STATEMENT Approved for public release; distribution unlimited.		12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words)  Pulsing circuits generate electromagnetic interference (EMI) that can affect sensitive circuitry and adversely contribute to the spectral signature of equipment. "Flicker noise" concepts, derived from chaos theory, have been employed to efficiently pulse circuitry while generating a virtually undetectable spectral signature. Pure flicker pulsing requires that the components be driven with a set of uncorrelated pulses, with random heights, starting at random times. However, a significant reduction in conspicuous power spectral density (PSD) components can be achieved when imposing practical constraints. We have been able to significantly reduce the dominant components of the power spectrum using fixed pulse durations and magnitudes. We employed flicker pulsing, with a PSD approaching (1/f) <sup>2</sup> , to drive our components more efficiently, resulting in a 40% increase in battery life. The contribution of the pulses to the spectral signature of the equipment appears only in the background noise of EMI detectors.			
14. SUBJECT TERMS Electromagnetic Interference (EMI), Chaos Theory, Flicker Noise, Electronics		15. NUMBER OF PAGES 11	
		15. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT UL

# REPORT DOCUMENTATION PAGE

Form Approved  
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

<b>1. AGENCY USE ONLY (Leave blank)</b>	<b>2. REPORT DATE</b> June 1998	<b>3. REPORT TYPE AND DATES COVERED</b> Final	
<b>4. TITLE AND SUBTITLE</b> STABILITY OF ARRAYS OF MULTIPLE-EDGE CRACKS		<b>5. FUNDING NUMBERS</b> Contract No. 8471-AN-06 (70-1S)	
<b>6. AUTHOR(S)</b> Anthony P. Parker			
<b>7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)</b> Royal Military College of Science Cranfield University Swindon, SN6 8LA, UK		<b>8. PERFORMING ORGANIZATION REPORT NUMBER</b>  ARCCB-CR-98009	
<b>9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)</b> U.S. Army ARDEC Benet Laboratories, AMSTA-AR-CCB-O Watervliet, NY 12189-4050		<b>10. SPONSORING/MONITORING AGENCY REPORT NUMBER</b>	
<b>11. SUPPLEMENTARY NOTES</b> John H. Underwood - Benet Laboratories Project Engineer. Submitted for publication in <i>Engineering Fracture Mechanics</i> .			
<b>12a. DISTRIBUTION / AVAILABILITY STATEMENT</b> Approved for public release; distribution unlimited.		<b>12b. DISTRIBUTION CODE</b>	
<b>13. ABSTRACT (Maximum 200 words)</b>  The creation and subsequent shedding of arrays of edge cracks is a natural phenomenon which occurs in heat-checked gun tubes, rapidly cooled pressure vessels, and rock, dried-out mud flats, paint, and concrete and in ceramic coatings and permafrost. The phenomenon covers five orders of magnitude in crack spacing. A simple model is developed which indicates that the shedding behaviour is governed by energy release from individual cracks rather than global energy changes. The model predicts that all cracks will deepen until a crack-spacing/crack-depth ratio (2h/a) of 3.0 is achieved, at which stage crack-shedding will commence. Two out of every three cracks will be shed, leading to a new (higher) crack-spacing/crack-depth ratio at which stage growth of all currently active cracks will be dominant.  An approach based upon rapid, approximate methods for determining stress intensity provides good indications of behaviour provided near-surface stress gradients are not excessive. In cases where stress gradients are high, it is shown that it is necessary to employ numerical techniques in calculating stress intensity. Two specific examples are presented, the first at very small scale (heat-check cracking, typical crack spacing 1mm) and the second very large scale (permafrost cracking, typical crack spacing 20m). The predicted ratios for the proportion of cracks shed and for crack-spacing/crack-depth are in agreement with experimental evidence for gun tubes, concrete, and permafrost. The ratios also appear to match experimental observations of 'island delamination' in ceramic coatings and paint films.			
<b>14. SUBJECT TERMS</b> Crack Arrays, Edge Cracks, Crack Shedding, Crack Growth, Fracture, Fracture Mechanics, Residual Stress, Stress Intensity Factor, Permafrost, Mud Flats, Gun Tubes, Concrete		<b>15. NUMBER OF PAGES</b> 20	
		<b>16. PRICE CODE</b>	
<b>17. SECURITY CLASSIFICATION OF REPORT</b> UNCLASSIFIED	<b>18. SECURITY CLASSIFICATION OF THIS PAGE</b> UNCLASSIFIED	<b>19. SECURITY CLASSIFICATION OF ABSTRACT</b> UNCLASSIFIED	<b>20. LIMITATION OF ABSTRACT</b> UL

# REPORT DOCUMENTATION PAGE

Form Approved  
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

<b>1. AGENCY USE ONLY (Leave blank)</b>	<b>2. REPORT DATE</b> June 1998	<b>3. REPORT TYPE AND DATES COVERED</b> Final	
<b>4. TITLE AND SUBTITLE</b> THE BAUSCHINGER EFFECT IN AUTOFRETTAGED TUBES - A COMPARISON OF MODELS INCLUDING THE ASME CODE		<b>5. FUNDING NUMBERS</b> AMCMS No. 6226.24.H180.0 PRON No. TU6A6F361ABJ	
<b>6. AUTHOR(S)</b> Anthony P. Parker (Royal Military College of Science, Cranfield University, Swindon, UK) and John H. Underwood			
<b>7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)</b> U.S. Army ARDEC Benet Laboratories, AMSTA-AR-CCB-O Watervliet, NY 12189-4050		<b>8. PERFORMING ORGANIZATION REPORT NUMBER</b>  ARCCB-TR-98010	
<b>9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES)</b> U.S. Army ARDEC Close Combat Armaments Center Picatinny Arsenal, NJ 07806-5000		<b>10. SPONSORING / MONITORING AGENCY REPORT NUMBER</b>	
<b>11. SUPPLEMENTARY NOTES</b> To be presented at the ASME Pressure Vessels and Piping Conference, San Diego, CA, 26-30 July 1998. To be published in Proceedings of the Conference and <i>ASME Journal of Pressure Vessel Technology</i> .			
<b>12a. DISTRIBUTION / AVAILABILITY STATEMENT</b> Approved for public release; distribution unlimited.		<b>12b. DISTRIBUTION CODE</b>	
<b>13. ABSTRACT (Maximum 200 words)</b> Autofrettage is used to introduce advantageous residual stresses into pressure vessels and to enhance their fatigue lifetimes. For many years workers have acknowledged the probable influence of the Bauschinger effect which serves to reduce the yield strength in compression as a result of prior tensile plastic overload. This in turn can produce lower compressive residual hoop stresses near the bore than are predicted by 'ideal' solutions (elastic/perfectly plastic without Bauschinger effect).  There have been several models proposed in order to predict the reduced stresses within the autofrettaged tube. The purpose of this paper is simply to compare a limited set of models, including the ASME code, with available experimental evidence. Three models are compared: Model A, based upon a quasi strain-hardening model developed by Chen; Model B, based upon a Bauschinger effect which varies with plastic strain and hence with radius; Model C, which is based upon section KD-522.2 of the recently revised ASME pressure vessel code. The models are compared against experimental data under three headings:  <ul style="list-style-type: none"> <li>• Measurements of Hoop Residual Stress at the Bore</li> <li>• Measurements of Hoop Residual Stress Variation Radially Through the Tube Wall, In Particular the Near-Bore Region</li> <li>• Measurements of Opening Angle When Autofrettaged Tubes are Slit Radially, Hence Releasing the Pure Bending Moment 'Locked In' by the Hoop Stress</li> </ul>			
<b>14. SUBJECT TERMS</b> Pressure Vessels, Autofrettage, High Strength Steel, Fatigue Life, Bauschinger Effect		<b>15. NUMBER OF PAGES</b> 10	
		<b>15. PRICE CODE</b>	
<b>17. SECURITY CLASSIFICATION OF REPORT</b> UNCLASSIFIED	<b>18. SECURITY CLASSIFICATION OF THIS PAGE</b> UNCLASSIFIED	<b>19. SECURITY CLASSIFICATION OF ABSTRACT</b> UNCLASSIFIED	<b>20. LIMITATION OF ABSTRACT</b> UL

# REPORT DOCUMENTATION PAGE

Form Approved  
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

<b>1. AGENCY USE ONLY (Leave blank)</b>		<b>2. REPORT DATE</b> July 1998	<b>3. REPORT TYPE AND DATES COVERED</b> Final	
<b>4. TITLE AND SUBTITLE</b> X-RAY DETERMINATION OF TEXTURE AND RESIDUAL STRESS IN LOW CONTRACTION ELECTROLYTIC CHROMIUM DEPOSITION			<b>5. FUNDING NUMBERS</b> AMCMS No. 6111.01.91A1.1	
<b>6. AUTHOR(S)</b> S.L. Lee and D. Windover				
<b>7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)</b> U.S. Army ARDEC Benet Laboratories, AMSTA-AR-CCB-O Watervliet, NY 12189-4050			<b>8. PERFORMING ORGANIZATION REPORT NUMBER</b>  ARCCB-TR-98011	
<b>9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES)</b> U.S. Army ARDEC Close Combat Armaments Center Picatinny Arsenal, NJ 07806-5000			<b>10. SPONSORING / MONITORING AGENCY REPORT NUMBER</b>	
<b>11. SUPPLEMENTARY NOTES</b> Presented at the 1998 SEM Spring Conference on Experimental and Applied Mechanics, Houston, TX, 1-3 June 1998. Published in proceedings of the conference.				
<b>12a. DISTRIBUTION / AVAILABILITY STATEMENT</b> Approved for public release; distribution unlimited.			<b>12b. DISTRIBUTION CODE</b>	
<b>13. ABSTRACT (Maximum 200 words)</b> Residual stresses are believed to be responsible for the intrinsic cracks observed in electrolytic chromium coatings. The cracks directly affect the wear and erosion behavior of the coating and substrate. Crystalline orientation significantly influences the elastic-plastic properties of materials. It also affects the method by which residual stress can be determined using x-ray diffraction. For this study, we investigated texture and residual stress analysis for two low contraction (LC) chromium coating specimens and compared the results with a high contraction (HC) chromium specimen. High-resolution pole figure analysis and x-ray diffraction were used to characterize the texture in the coatings. Randomly oriented materials allow the application of the x-ray diffraction $\sin^2\Psi$ stress measurement method. For highly textured body-centered-cubic crystals, the $\sin^2\Psi$ method failed, so a Matlab matrix inversion method was used to determine residual stress. One of the LC chromium specimens exhibited near random orientation with very weak fiber texture, and the other specimen exhibited intermediate mixed $\langle 111 \rangle$ and $\langle 211 \rangle$ fiber texture. The HC chromium specimen exhibited strong predominately $\langle 111 \rangle$ fiber texture. A correlation between residual stress and texture was found. The HC chromium specimen with high fiber texture showed higher surface tensile stresses, while the LC chromium specimens with more randomly oriented crystallites showed lower residual stresses.				
<b>14. SUBJECT TERMS</b> Chromium, Low Contraction Chromium, High Contraction Chromium, Texture, Residual Stress			<b>15. NUMBER OF PAGES</b> 11	
			<b>16. PRICE CODE</b>	
<b>17. SECURITY CLASSIFICATION OF REPORT</b> UNCLASSIFIED	<b>18. SECURITY CLASSIFICATION OF THIS PAGE</b> UNCLASSIFIED	<b>19. SECURITY CLASSIFICATION OF ABSTRACT</b> UNCLASSIFIED	<b>20. LIMITATION OF ABSTRACT</b> UL	

# REPORT DOCUMENTATION PAGE

Form Approved  
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)	2. REPORT DATE July 1998	3. REPORT TYPE AND DATES COVERED Final	
4. TITLE AND SUBTITLE PHASE, RESIDUAL STRESS, AND TEXTURE IN TRIODE-SPUTTERED TANTALUM COATINGS ON STEEL		5. FUNDING NUMBERS AMCMS No. 6111.01.91A1.1	
6. AUTHOR(S) S.L. Lee and D. Windover		8. PERFORMING ORGANIZATION REPORT NUMBER  ARCCB-TR-98012	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army ARDEC Benet Laboratories, AMSTA-AR-CCB-O Watervliet, NY 12189-4050			
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) U.S. Army ARDEC Close Combat Armaments Center Picatinny Arsenal, NJ 07806-5000		10. SPONSORING / MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES Presented at the 25 <sup>th</sup> International Conference on Metallurgical Coatings and Thin Films, San Diego, CA, 27 April to 1 May 1998. Published in Proceedings of the Conference and <i>Surface and Coatings Technology</i> .			
12a. DISTRIBUTION / AVAILABILITY STATEMENT Approved for public release; distribution unlimited.		12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words)  This work analyzes the unoptimized, prototype triode-sputtered, 150 μm thick tantalum coatings deposited with a 2.5 μm niobium under-layer onto the bore of a large-diameter A723 steel cylinder. The coating was deposited for wear and erosion protection by Pacific Northwest National Laboratory. Our phase determination was based on x-ray diffraction analysis, wavelength dispersive x-ray fluorescence analysis, energy dispersive x-ray analysis, and hardness and electrical resistivity measurements. Both x-ray diffraction and radius-of-curvature methods were used to determine residual stresses. A locally developed high-resolution pole figure technique was used to perform texture analysis. The post-firing, debonded coating showed alpha-tantalum, preferred [110] orientation, high surface stresses, tantalum oxides, entrapped krypton sputtering gas, interstitial oxygen, and other impurities. The surface and subsurface pole figures revealed broadened poles and body-centered-cubic tantalum crystalline structure.			
14. SUBJECT TERMS Residual Stress, Texture, Tantalum, Sputtered, Phase, Niobium, X-Ray Fluorescence, X-Ray Diffraction		15. NUMBER OF PAGES 17	
		16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT UJ

# REPORT DOCUMENTATION PAGE

Form Approved  
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

<b>1. AGENCY USE ONLY (Leave blank)</b>	<b>2. REPORT DATE</b> July 1998	<b>3. REPORT TYPE AND DATES COVERED</b> Final	
<b>4. TITLE AND SUBTITLE</b> DYNAMIC MODELING FOR DESIGN: SPACE-TIME FINITE ELEMENT FORMULATION OF AN EULER BEAM		<b>5. FUNDING NUMBERS</b> AMCMS No. 6226.24.H180.0 PRON No. 4A7A7FYA1ABJ	
<b>6. AUTHOR(S)</b> Eric L. Kathe			
<b>7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)</b> U.S. Army ARDEC Benet Laboratories, AMSTA-AR-CCB-O Watervliet, NY 12189-4050		<b>8. PERFORMING ORGANIZATION REPORT NUMBER</b>  ARCCB-TR-98013	
<b>9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES)</b> U.S. Army ARDEC Close Combat Armaments Center Picatinny Arsenal, NJ 07806-5000		<b>10. SPONSORING / MONITORING AGENCY REPORT NUMBER</b>	
<b>11. SUPPLEMENTARY NOTES</b> Presented at the 68 <sup>th</sup> Shock and Vibration Symposium, Baltimore, MD, 3-7 November 1997. Published in Proceedings of the Symposium.			
<b>12a. DISTRIBUTION / AVAILABILITY STATEMENT</b> Approved for public release; distribution unlimited.		<b>12b. DISTRIBUTION CODE</b>	
<b>13. ABSTRACT (Maximum 200 words)</b> This paper demonstrates the application of finite element methods in both space and time to the partial differential equations that govern beam dynamics. The approach enables design problems for the structural response of beams subject to shock and vibration loading to be posed. Numerical validation of the results using a forward Euler ordinary differential equation solver is also shown.			
<b>14. SUBJECT TERMS</b> Structural Dynamics, Space-Time Finite Element Analysis, Optimal Design			<b>15. NUMBER OF PAGES</b> 20
			<b>16. PRICE CODE</b>
<b>17. SECURITY CLASSIFICATION OF REPORT</b> UNCLASSIFIED	<b>18. SECURITY CLASSIFICATION OF THIS PAGE</b> UNCLASSIFIED	<b>19. SECURITY CLASSIFICATION OF ABSTRACT</b> UNCLASSIFIED	<b>20. LIMITATION OF ABSTRACT</b> UL

# REPORT DOCUMENTATION PAGE

Form Approved  
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

<b>1. AGENCY USE ONLY (Leave blank)</b>		<b>2. REPORT DATE</b> July 1998	<b>3. REPORT TYPE AND DATES COVERED</b> Final
<b>4. TITLE AND SUBTITLE</b> FAILURE ANALYSIS OF AN 84-MM, M3, CARL GUSTAF, RECOILLESS RIFLE		<b>5. FUNDING NUMBERS</b> AMCMS No. 6226.24.H180.0 PRON No. AFEMIPR95100	
<b>6. AUTHOR(S)</b> Kevin Miner, Adolf Kapusta, and Kenneth Olsen			
<b>7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)</b> U.S. Army ARDEC Benet Laboratories, AMSTA-AR-CCB-O Watervliet, NY 12189-4050		<b>8. PERFORMING ORGANIZATION REPORT NUMBER</b>  ARCCB-TR-98014	
<b>9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)</b> U.S. Army ARDEC Close Combat Armaments Center Picatinny Arsenal, NJ 07806-5000		<b>10. SPONSORING/MONITORING AGENCY REPORT NUMBER</b>	
<b>11. SUPPLEMENTARY NOTES</b>			
<b>12a. DISTRIBUTION / AVAILABILITY STATEMENT</b> Approved for public release; distribution unlimited.		<b>12b. DISTRIBUTION CODE</b>	
<b>13. ABSTRACT (Maximum 200 words)</b> During a February 26, 1997 training exercise at Fort Benning, Georgia, an 84-mm, M3, Carl Gustaf, shoulder-fired, recoilless rifle—the TACOM-ARDEC Multi-Role, Anti-Armor, Anti-Personnel Weapon System (MAAWS)—failed while firing an FFV552 training round. The composite-wrapped, steel-lined barrel burst open beneath the trigger housing—destroying the weapon but leaving the Gunner and Assistant Gunner uninjured. The rifle (serial number 14051) was evaluated in the field and at Benet Laboratories. Inspections included a bore surface inspection, dimensional checks, a magnetic particle inspection, an ultrasonic inspection, a crack evaluation, and a bore debris analysis. Although there is no clear evidence regarding the cause of the failure, the evidence does indicate that the failure may have been caused by a soil obstruction in the barrel. This obstruction probably produced a large amount of highly localized stress on the carbon fiber, composite-overwrapped, steel barrel—thereby causing the jacket that contains the pressure to fail and allowing the pressurized propellant gases to deform and rupture the underlying steel liner.			
<b>14. SUBJECT TERMS</b> Gun Failure, Carl Gustaf, MAAWS, M3, Composites, Composite Gun Barrels, Ultrasonic Inspection, Magnetic Particle Inspection, Scanning Electron Microscopy		<b>15. NUMBER OF PAGES</b> 31	
		<b>16. PRICE CODE</b>	
<b>17. SECURITY CLASSIFICATION OF REPORT</b> UNCLASSIFIED	<b>18. SECURITY CLASSIFICATION OF THIS PAGE</b> UNCLASSIFIED	<b>19. SECURITY CLASSIFICATION OF ABSTRACT</b> UNCLASSIFIED	<b>20. LIMITATION OF ABSTRACT</b> UL

# REPORT DOCUMENTATION PAGE

Form Approved  
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

<b>1. AGENCY USE ONLY (Leave blank)</b>		<b>2. REPORT DATE</b> August 1998	<b>3. REPORT TYPE AND DATES COVERED</b> Final	
<b>4. TITLE AND SUBTITLE</b> USE OF THE INSTRUMENTED BOLT AND CONSTANT DISPLACEMENT BOLT-LOADED SPECIMEN TO MEASURE IN SITU HYDROGEN CRACK GROWTH IN HIGH STRENGTH STEELS			<b>5. FUNDING NUMBERS</b> AMCMS No. 6111.01.91A1.100	
<b>6. AUTHOR(S)</b> Gregory N. Vigilante, John H. Underwood, and Daniel Crayon				
<b>7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)</b> U.S. Army ARDEC Benet Laboratories, AMSTA-AR-CCB-O Watervliet, NY 12189-4050			<b>8. PERFORMING ORGANIZATION REPORT NUMBER</b>  ARCCB-TR-98015	
<b>9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES)</b> U.S. Army ARDEC Close Combat Armaments Center Picatinny Arsenal, NJ 07806-5000			<b>10. SPONSORING / MONITORING AGENCY REPORT NUMBER</b>	
<b>11. SUPPLEMENTARY NOTES</b> Presented at the ASTM 30 <sup>th</sup> National Symposium on Fatigue and Fracture Mechanics, St. Louis, MO, 25-27 June 1998. Published in <i>ASTM STP 1360</i> .				
<b>12a. DISTRIBUTION / AVAILABILITY STATEMENT</b> Approved for public release; distribution unlimited.			<b>12b. DISTRIBUTION CODE</b>	
<b>13. ABSTRACT (Maximum 200 words)</b> Aggressive environments experienced by large caliber gun tubes during processing and firing have lead to a great deal of investigation on the hydrogen-induced cracking susceptibility of high strength steels. The constant displacement bolt-loaded specimen has been used to determine the hydrogen crack growth rates and threshold stress intensity of AF1410—both conventionally and isothermally heat treated—and AerMet 100. Additionally, the severe susceptibility of high strength steels has necessitated the application and modification of a low cost, highly reliable, in situ crack measurement method, called the instrumented bolt. The instrumented bolt consists of a full bridge, strain-gaged stainless steel bolt coupled to an automatic data acquisition system. New expressions have been developed for use with the instrumented bolt and bolt-loaded specimen to relate load to crack growth. Our study determined that Stage II crack growth rates for the AF1410 were $1.1E^{-2}$ and $2.3E^{-2}$ mm/s for conventional and isothermal AF1410, respectively. Threshold stress intensity levels for AF1410 were 16.0 and 13.7 MPa m <sup>1/2</sup> , respectively. Stage II crack growth rates for AerMet 100 were $2.4E^{-2}$ mm/s, while the threshold stress intensity was 14.1 MPa m <sup>1/2</sup> .				
<b>14. SUBJECT TERMS</b> Hydrogen-Induced Cracking, Hydrogen Embrittlement, Environmental Cracking, Environmental Fracture, Instrumented Bolt, Bolt-Loaded Specimen, High Strength Steels, ASTM A723, AF1410, AerMet 100			<b>15. NUMBER OF PAGES</b> 23	
			<b>16. PRICE CODE</b>	
<b>17. SECURITY CLASSIFICATION OF REPORT</b> UNCLASSIFIED	<b>18. SECURITY CLASSIFICATION OF THIS PAGE</b> UNCLASSIFIED	<b>19. SECURITY CLASSIFICATION OF ABSTRACT</b> UNCLASSIFIED	<b>20. LIMITATION OF ABSTRACT</b> U1	

# REPORT DOCUMENTATION PAGE

Form Approved  
GMS No. 0704-0138

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0138), Washington, DC 20503.

<b>1. AGENCY USE ONLY (Leave blank)</b>		<b>2. REPORT DATE</b> August 1998	<b>3. REPORT TYPE AND DATES COVERED</b> Final	
<b>4. TITLE AND SUBTITLE</b> THE ROLE OF VANADIUM CARBIDE TRAPS IN REDUCING THE HYDROGEN EMBRITTLEMENT SUSCEPTIBILITY OF HIGH STRENGTH ALLOY STEELS			<b>5. FUNDING NUMBERS</b> AMCMS No. 6111.01.91A1.100	
<b>6. AUTHOR(S)</b> G.L. Spencer and D.J. Duquette (RPI, Troy, NY)				
<b>7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)</b> U.S. Army ARDEC Benet Laboratories, AMSTA-AR-CCB-O Watervliet, NY 12189-4050			<b>8. PERFORMING ORGANIZATION REPORT NUMBER</b>  ARCCB-TR-98016	
<b>9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)</b> U.S. Army ARDEC Close Combat Armaments Center Picatinny Arsenal, NJ 07806-5000			<b>10. SPONSORING/MONITORING AGENCY REPORT NUMBER</b>	
<b>11. SUPPLEMENTARY NOTES</b> Submitted for publication in <i>Metallurgical and Material Transactions</i> . This report is an extract from Dr. Spencer's Ph.D. thesis, in which Dr. Duquette was his thesis advisor.				
<b>12a. DISTRIBUTION/AVAILABILITY STATEMENT</b> Approved for public release; distribution unlimited.			<b>12b. DISTRIBUTION CODE</b>	
<b>13. ABSTRACT (Maximum 200 words)</b> High strength alloy steels typically used for gun steel were investigated to determine their susceptibility to hydrogen embrittlement. Although AISI grade 4340 was quite susceptible to hydrogen embrittlement, ASTM A723 steel, which has identical mechanical properties but slightly different chemistries, was not susceptible to hydrogen embrittlement when exposed to the same conditions. The degree of embrittlement was determined by conducting notched tensile testing on uncharged and cathodically charged specimens. Chemical composition was modified to isolate the effect of alloying elements on hydrogen embrittlement susceptibility. Two steels—Modified A723 (C increased from 0.32% to 0.40%) and Modified 4340 (V increased from 0 to 0.12%)—were tested. X-ray diffraction identified the presence of vanadium carbide, V <sub>4</sub> C <sub>3</sub> , in A723 steels, and subsequent hydrogen extraction studies evaluated the trapping effect of vanadium carbide. Based on these tests, it was determined that adding vanadium carbide to 4340 significantly decreased hydrogen embrittlement susceptibility because vanadium carbide traps ties up diffusible hydrogen. The effectiveness of these traps is examined and discussed in this paper.				
<b>14. SUBJECT TERMS</b> Hydrogen Trapping, Vanadium Carbide Traps, Hydrogen Embrittlement of Steel, 4340 and Its Susceptibility to Hydrogen Embrittlement, Notch Tensile Testing, Vanadium Additions to High Strength Steel Alloys			<b>15. NUMBER OF PAGES</b> 20	
			<b>16. PRICE CODE</b>	
<b>17. SECURITY CLASSIFICATION OF REPORT</b> UNCLASSIFIED	<b>18. SECURITY CLASSIFICATION OF THIS PAGE</b> UNCLASSIFIED	<b>19. SECURITY CLASSIFICATION OF ABSTRACT</b> UNCLASSIFIED	<b>20. LIMITATION OF ABSTRACT</b> III	

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188	
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.				
1. AGENCY USE ONLY (Leave blank)	2. REPORT DATE September 1998	3. REPORT TYPE AND DATES COVERED Final		
4. TITLE AND SUBTITLE THE CANNON-PROJECTILE BLOW-BY FLOW FIELD			5. FUNDING NUMBERS AMCMS No. 6226.24.H181.0	
6. AUTHOR(S) C.A. Andrade, B. Cunningham, H.T. Nagamatsu (RPI, Troy, NY), and D.G. Messitt (RPI)				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army ARDEC Benet Laboratories, AMSTA-AR-CCB-O Watervliet, NY 12189-4050			8. PERFORMING ORGANIZATION REPORT NUMBER ARCCB-TR-98017	
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) U.S. Army ARDEC Close Combat Armaments Center Picatinny Arsenal, NJ 07806-5000			10. SPONSORING / MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES Presented at the 1998 Joint Army-Navy-NASA-Air Force Propulsion Meeting, Cleveland, OH, 15-17 July 1998. Published in proceedings of the meeting.				
12a. DISTRIBUTION / AVAILABILITY STATEMENT Approved for public release; distribution unlimited.			12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) The objective of this work was to document the numerical simulation of the cannon-projectile blow-by flow for a Zone six firing of an M549A1 with XM230 charge. The steady, axisymmetric flow was determined by use of the NPARC Computational Fluid Dynamics Code, given inflow boundary values at points on the ballistics path. We computed pressure distributions on the projectile, assuming a smooth cannon surface. Integration of the distribution over the projected lateral surface of the projectile gives an estimated side force of 500,000 pounds on the projectile as it enters the brake section of the tube. In a yawed attitude, such forces can effect inertial instabilities on the projectile which, in turn, contribute to balloting and mechanical wear of the tube. The same numerical solution computes local heat transfer rates on the obturator and rotating band surfaces. The effect of blow-by flow heat transfer on tube erosion is a factor that is not well understood. An extension of the present work will provide a basis for further understanding the combined effects of abrasive and chemical erosion. The present computations assume that the wear gap between projectile and cannon wall is 0.020 inch and that the obturator protrudes 70% into the gap. Results are presented at two points on the ballistics trajectory, 2.212 and 5.256 meters from the rifle origin. Local heat transfer to the barrel wall was obtained for projectiles with and without obturator and band. At the 2.212 meter location, the latter yielded maximum local heat transfer rates on the barrel surface that exceeded 30 times the heat transfer computed at 1.7 inches upstream of the projectile's base (i.e., in the projectile's wake boundary layer). With the obturator and band, and at the same travel point, the heat transfer ratio peaked at 2040, with the wake heat transfer computed at 6.7 inches upstream of the projectile's base.				
14. SUBJECT TERMS Computational Fluid Dynamics (CFD), Cannons, Tubes, Wear and Erosion Modeling, Projectile Leakage Blow-by, Flow Fields, Zone 6, M549A1, NPARC			15. NUMBER OF PAGES 19	
			16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT UL	

# REPORT DOCUMENTATION PAGE

Form Approved  
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

<b>1. AGENCY USE ONLY (Leave blank)</b>	<b>2. REPORT DATE</b> October 1998	<b>3. REPORT TYPE AND DATES COVERED</b> Final
---	---------------------------------------	--

<b>4. TITLE AND SUBTITLE</b> COMPREHENSIVE EROSION MODEL FOR THE 120-MM M256/M829A2 GUN SYSTEM	<b>5. FUNDING NUMBERS</b> AMCMS No. 6226.24.H180.0 PRON No. 4A8A8FYK1ABJ
<b>6. AUTHOR(S)</b> S. Sopok, P. Vottis, P. O'Hara, G. Pflagl, and C. Rickard	

<b>7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)</b> U.S. Army ARDEC Benet Laboratories, AMSTA-AR-CCB-O Watervliet, NY 12189-4050	<b>8. PERFORMING ORGANIZATION REPORT NUMBER</b>  ARCCB-TR-98018
---	---

<b>9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES)</b> U.S. Army ARDEC Close Combat Armaments Center Picatinny Arsenal, NJ 07806-5000	<b>10. SPONSORING / MONITORING AGENCY REPORT NUMBER</b>
--	---

**11. SUPPLEMENTARY NOTES**  
Presented at the 1998 120-mm Joint Configuration Board Meeting, Hampton, VA, 11-13 May 1998.  
Published in proceedings of the meeting.

<b>12a. DISTRIBUTION / AVAILABILITY STATEMENT</b> Approved for public release; distribution unlimited.	<b>12b. DISTRIBUTION CODE</b>
---	-------------------------------

**13. ABSTRACT (Maximum 200 words)**

Distinct erosion patterns and mechanisms are emerging as our gun erosion database increases for in-service and out-of-service 120-mm M256 tubes with M829A2 rounds. Variability exists for M256 guns with M829A2 rounds depending on round count, round type, round-conditioning temperature, and their order. Our M256/M829A2 gun system erosion model—with its interior ballistics, thermochemistry, and boundary layer components—is constantly being guided and refined by the erosion and materials analysis data from fired gun tubes. A recent refinement includes improvement of the gun steel subsurface exposure model due to high quality, difficult to obtain data from in-service M256 tubes. Other recent refinements to the boundary layer heat transfer model are based on thermal data from M256 tubes. These refinements include the improvement/incorporation of case gas cooling effects, turbulent gas mixing/heating effects, and a very minor contribution from forcing cone-induced vena contracta cooling effects. These latter refinements are calibrated away from crack walls by positional thermal wall repacking depth, thermal wall transformation depth, and thermocouple data. A comprehensive gun erosion model and multiple single-shot erosion condemnation predictions are described for the 120-mm M256 gun with its M829A2 round for hot-conditioned rounds only, ambient-conditioned rounds only, cold-conditioned rounds only, and an equal distribution of hot/ambient/cold-conditioned rounds. The gun erosion mechanism consists of heat checking the inert chromium plate, subsequent interfacial degradation of the subsurface gun steel substrate at the chromium crack bases, then chromium platelet spalling, and subsequent bare gun steel gas wash. This gun erosion model correctly calculates and predicts that the worst eroded region is at 1.2 to 2.4 meters from the rear face of the tube. The excessive muzzle wear is by a different, purely mechanical gas wash-free mechanism. Most importantly, given herein are the relative erosion-related effective full-charge values of the fielded M256 gun kinetic energy rounds at various round-conditioning temperatures.

<b>14. SUBJECT TERMS</b> Gun Erosion Modeling, 120-mm M256 Cannon, M829A2 Rounds	<b>15. NUMBER OF PAGES</b> 25
	<b>16. PRICE CODE</b>

<b>17. SECURITY CLASSIFICATION OF REPORT</b> UNCLASSIFIED	<b>18. SECURITY CLASSIFICATION OF THIS PAGE</b> UNCLASSIFIED	<b>19. SECURITY CLASSIFICATION OF ABSTRACT</b> UNCLASSIFIED	<b>20. LIMITATION OF ABSTRACT</b> III
--	---	--	--

# REPORT DOCUMENTATION PAGE

*Form Approved*  
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

<b>1. AGENCY USE ONLY (Leave blank)</b>		<b>2. REPORT DATE</b> October 1998	<b>3. REPORT TYPE AND DATES COVERED</b> Final	
<b>4. TITLE AND SUBTITLE</b> SHOT-BY-SHOT EROSION MODELING OF RETIRED 120-MM M256 GUN TUBE #1988			<b>5. FUNDING NUMBERS</b> AMCMS No. 6226.24.H180.0 PRON No. 4A8A8FYK1ABJ	
<b>6. AUTHOR(S)</b> S. Sopok, P. Vottis, P. O'Hara, G. Pflagl, and C. Rickard				
<b>7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)</b> U.S. Army ARDEC Benet Laboratories, AMSTA-AR-CCB-O Watervliet, NY 12189-4050			<b>8. PERFORMING ORGANIZATION REPORT NUMBER</b>  ARCCB-TR-98019	
<b>9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES)</b> U.S. Army ARDEC Close Combat Armaments Center Picatinny Arsenal, NJ 07806-5000			<b>10. SPONSORING / MONITORING AGENCY REPORT NUMBER</b>	
<b>11. SUPPLEMENTARY NOTES</b> Presented at the 34 <sup>th</sup> AIAA Joint Propulsion Conference, Cleveland, OH, 13-15 July 1998. Published in proceedings of the conference.				
<b>12a. DISTRIBUTION / AVAILABILITY STATEMENT</b> Approved for public release; distribution unlimited.			<b>12b. DISTRIBUTION CODE</b>	
<b>13. ABSTRACT (Maximum 200 words)</b> As our gun erosion database increases for in-service and out-of-service 120-mm M256 tubes with M829Ax series rounds, distinct erosion patterns and mechanisms are emerging. Variability exists for M256 guns with M829Ax series rounds depending on round count, round type, round-conditioning temperature, and their order. Our M256/M829Ax gun system erosion model—with its interior ballistics, thermochemistry, and boundary layer components—is constantly being guided and refined by the erosion and materials analysis data from fired gun tubes. A recent refinement includes the improvement of the gun steel subsurface exposure model due to high quality, difficult to obtain data from in-service M256 tubes. Other recent refinements to the boundary layer heat transfer model are based on thermal data from M256 tubes. These refinements include the improvement/incorporation of case gas cooling effects, turbulent gas mixing/heating effects, and a very minor contribution from forcing cone-induced vena contracta cooling effects. These latter refinements are calibrated away from crack walls by positional thermal wall repacking depth, thermal wall transformation depth, and thermocouple data. A comprehensive gun erosion model is described for the 120-mm M256 gun with its M829Ax series rounds. In addition, a detailed shot-by-shot erosion modeling prediction is described for retired 120-mm M256 gun tube serial #1988. For this gun tube, the erosion prediction includes the two types of rounds fired, M829 and M829A2, and their three round-conditioning temperatures, hot, ambient, and cold. The gun erosion mechanism consists of heat checking the inert chromium plate, subsequent interfacial degradation of the subsurface gun steel substrate at the chromium crack bases, then chromium platelet spalling, and subsequent bare gun steel gas wash. This gun erosion model correctly calculates and predicts that the worst eroded region is at 1.2 to 2.4 meters from the rear face of the tube. The excessive muzzle wear is by a different, purely mechanical gas wash-free mechanism. Most importantly, given herein are the relative erosion-related effective full-charge values of the fielded M256 gun kinetic energy rounds at various round-conditioning temperatures.				
<b>14. SUBJECT TERMS</b> Shot-by-Shot Gun Erosion Modeling, 120-mm M256 Cannon, M829A2 Rounds, M829 Rounds			<b>15. NUMBER OF PAGES</b> 20	
			<b>16. PRICE CODE</b>	
<b>17. SECURITY CLASSIFICATION OF REPORT</b> UNCLASSIFIED	<b>18. SECURITY CLASSIFICATION OF THIS PAGE</b> UNCLASSIFIED	<b>19. SECURITY CLASSIFICATION OF ABSTRACT</b> UNCLASSIFIED	<b>20. LIMITATION OF ABSTRACT</b> III	

# REPORT DOCUMENTATION PAGE

Form Approved  
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)	2. REPORT DATE December 1998	3. REPORT TYPE AND DATES COVERED Final	
4. TITLE AND SUBTITLE COMPREHENSIVE EROSION MODEL FOR THE 120-MM M256/M829 GUN SYSTEM		5. FUNDING NUMBERS AMCMS No. 6226.24.H180.0 PRON No. 4A8A8FYK1ABJ	
6. AUTHOR(S) S. Sopok, P. Vottis, P. O'Hara, G. Pflugi, and C. Rickard			
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)  U.S. Army ARDEC Benet Laboratories, AMSTA-AR-CCB-O Watervliet, NY 12189-4050		8. PERFORMING ORGANIZATION REPORT NUMBER  ARCCB-TR-98020	
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES)  U.S. Army ARDEC Close Combat Armaments Center Picatinny Arsenal, NJ 07806-5000		10. SPONSORING / MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES Presented at the 1998 JANNAF Propulsion Meeting, Cleveland, OH, 15-18 July 1998. Published in proceedings of the meeting.			
12a. DISTRIBUTION / AVAILABILITY STATEMENT Approved for public release; distribution unlimited.		12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) Most 120-mm M256 guns firing the M829 round as their "hottest" kinetic energy round have been condemned because of fatigue. Despite this fact, it is still important to determine the erosion life of the M829 round, since M256 guns that have fired the most recent kinetic energy rounds (M829A1, M829A2) rely on the M829 round for baseline dispersion testing of that gun. Today this generally results in M256 guns that having an equal mix of M829 and M829A2 rounds, thus necessitating the consideration of M829 round effects for any erosion analysis. Variability exists for M256 guns with M829 rounds depending on round count, round type, round-conditioning temperature, and their order. Distinctive erosion patterns and mechanisms are emerging as our gun erosion database increases for in-service and out-of-service 120-mm M256 tubes with M829 rounds. Our M256/M829 gun system erosion model—with its interior ballistics, thermochemistry, and boundary layer components—is constantly being guided and refined by the erosion and materials analysis data from fired gun tubes. A recent refinement includes improvement of the gun steel subsurface exposure model due to high quality, difficult to obtain data from in-service M256 tubes. Other recent refinements to the boundary layer heat transfer model are based on thermal data from M256 tubes. These refinements include the improvement/incorporation of case gas cooling effects, turbulent gas mixing/heating effects, and a very minor contribution from forcing cone-induced vena contracta cooling effects. These latter refinements are calibrated away from crack walls by positional thermal wall repacking depth, thermal wall transformation depth, and thermocouple data. A comprehensive gun erosion model and multiple single-shot erosion condemnation predictions are described for the 120-mm M256 gun with its M829 round for hot-conditioned rounds only, ambient-conditioned rounds only, cold-conditioned rounds only, and an equal distribution of hot/ambient/cold-conditioned rounds. The gun erosion mechanism consists of heat checking of the inert chromium plate, subsequent interfacial degradation of the subsurface gun steel substrate at the chromium crack bases, then subsequent chromium platelet spalling, and subsequent bare gun steel gas wash. This gun erosion model correctly calculates and predicts that the worst eroded region is at 1.2 to 2.4 meters from the rear face of the tube. The excessive muzzle wear is by a different, purely mechanical gas wash-free mechanism. Most importantly, given herein are the relative erosion related effective full-charge values of the fielded M256 gun kinetic energy rounds at various round-conditioning temperatures.			
14. SUBJECT TERMS Gun Erosion Modeling, 120-mm M256 Cannon, M829 Rounds		15. NUMBER OF PAGES 22	
		16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT U1

---

TECHNICAL REPORT INTERNAL DISTRIBUTION LIST

	<u>NO. OF COPIES</u>
CHIEF, DEVELOPMENT ENGINEERING DIVISION	
ATTN: AMSTA-AR-CCB-DA	1
-DB	1
-DC	1
-DD	1
-DE	1
CHIEF, ENGINEERING DIVISION	
ATTN: AMSTA-AR-CCB-E	1
-EA	1
-EB	1
-EC	1
CHIEF, TECHNOLOGY DIVISION	
ATTN: AMSTA-AR-CCB-T	2
-TA	1
-TB	1
-TC	1
TECHNICAL LIBRARY	
ATTN: AMSTA-AR-CCB-O	5
TECHNICAL PUBLICATIONS & EDITING SECTION	
ATTN: AMSTA-AR-CCB-O	3
OPERATIONS DIRECTORATE	
ATTN: SIOWV-ODP-P	1
DIRECTOR, PROCUREMENT & CONTRACTING DIRECTORATE	
ATTN: SIOWV-PP	1
DIRECTOR, PRODUCT ASSURANCE & TEST DIRECTORATE	
ATTN: SIOWV-QA	1

NOTE: PLEASE NOTIFY DIRECTOR, BENÉT LABORATORIES, ATTN: AMSTA-AR-CCB-O OF ADDRESS CHANGES.

---

---

TECHNICAL REPORT EXTERNAL DISTRIBUTION LIST

	<u>NO. OF COPIES</u>		<u>NO. OF COPIES</u>
DEFENSE TECHNICAL INFO CENTER ATTN: DTIC-OCA (ACQUISITIONS) 8725 JOHN J. KINGMAN ROAD STE 0944 FT. BELVOIR, VA 22060-6218	2	COMMANDER ROCK ISLAND ARSENAL ATTN: SIORI-SEM-L ROCK ISLAND, IL 61299-5001	1
COMMANDER U.S. ARMY ARDEC ATTN: AMSTA-AR-WEE, BLDG. 3022 AMSTA-AR-AET-O, BLDG. 183 AMSTA-AR-FSA, BLDG. 61 AMSTA-AR-FSX AMSTA-AR-FSA-M, BLDG. 61 SO AMSTA-AR-WEL-TL, BLDG. 59 PICATINNY ARSENAL, NJ 07806-5000	1 1 1 1 1 2	COMMANDER U.S. ARMY TANK-AUTMV R&D COMMAND ATTN: AMSTA-DDL (TECH LIBRARY) WARREN, MI 48397-5000	1
DIRECTOR U.S. ARMY RESEARCH LABORATORY ATTN: AMSRL-DD-T, BLDG. 305 ABERDEEN PROVING GROUND, MD 21005-5066	1	COMMANDER U.S. MILITARY ACADEMY ATTN: DEPT OF CIVIL & MECH ENGR WEST POINT, NY 10966-1792	1
DIRECTOR U.S. ARMY RESEARCH LABORATORY ATTN: AMSRL-WM-MB (DR. B. BURNS) ABERDEEN PROVING GROUND, MD 21005-5066	1	U.S. ARMY AVIATION AND MISSILE COM REDSTONE SCIENTIFIC INFO CENTER ATTN: AMSAM-RD-OB-R (DOCUMENTS) REDSTONE ARSENAL, AL 35898-5000	2
COMMANDER U.S. ARMY RESEARCH OFFICE ATTN: TECHNICAL LIBRARIAN P.O. BOX 12211 4300 S. MIAMI BOULEVARD RESEARCH TRIANGLE PARK, NC 27709-2211	1	COMMANDER U.S. ARMY FOREIGN SCI & TECH CENTER ATTN: DRXST-SD 220 7TH STREET, N.E. CHARLOTTESVILLE, VA 22901	1

---

NOTE: PLEASE NOTIFY COMMANDER, ARMAMENT RESEARCH, DEVELOPMENT, AND ENGINEERING CENTER,  
BENÉT LABORATORIES, CCAC, U.S. ARMY TANK-AUTOMOTIVE AND ARMAMENTS COMMAND,  
AMSTA-AR-CCB-O, WATERVLIET, NY 12189-4050 OF ADDRESS CHANGES.

---