

NAVAL POSTGRADUATE SCHOOL

Monterey, California



THESIS

**A STUDY OF THE FEASIBILITY AND APPLICABILITY
OF SHAPE CONTROLLED SPACE BASED INFLATABLE
MEMBRANE STRUCTURES**

by

Craig M. Whittinghill

September 2000

Thesis Advisor:

Brij Agrawal

Co-Advisor:

Donald v.Z. Wadsworth

Approved for public release; distribution is unlimited

DTIC QUALITY INSPECTED 4

20001026 140

REPORT DOCUMENTATION PAGE			<i>Form Approved</i> <i>OMB No. 0704-0188</i>	
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instruction, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188) Washington DC 20503.				
1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE September 2000	3. REPORT TYPE AND DATES COVERED Master's Thesis	
4. TITLE A Study of the Feasibility and Applicability of Shape Controlled Space Based Inflatable Membrane Structures			5. FUNDING NUMBERS	
6. AUTHOR(S) Whittinghill, Craig M.				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Naval Postgraduate School Monterey, CA 93943-5000			8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) N/A			10. SPONSORING / MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES The views expressed in this thesis are those of the author and do not reflect the official policy or position of the Department of Defense or the U.S. Government.				
12a. DISTRIBUTION / AVAILABILITY STATEMENT Approved for public release; distribution is unlimited			12b. DISTRIBUTION CODE	
13. ABSTRACT Inflatable structures used for space applications offer mass, volume, and cost savings to spacecraft programs, allowing larger space structures to be built. For certain space applications, there are advantages to using large structures. For example, antennas achieve higher gains when they are increased in size. Higher gains equate to higher data throughputs. Therefore, inflatable structures offer improvements in performance to certain types of spacecraft components. Environmental factors induce surface errors on large inflatable structures, though. This degrades performance, especially for inflatable antennas. To reduce this degradation, active and passive control systems can be used to sense errors and control the shape of the antenna. One method of applying an active and passive control system is by using piezoelectric films that are either attached to or are part of the inflatable structure. The research performed for this thesis explored the theoretical performance of a large inflatable space-based antenna via spreadsheet analysis and the physical performance of a piezoelectric film via laboratory experimentation. For the laboratory experiment, the film was attached to a drum and varying internal pressures and voltages were applied. Also, in order to validate the experimental results, an analytical model was created using MSC/PATRAN and MSC/NASTRAN software.				
14. SUBJECT TERMS Piezoelectric Film, Inflatable Structure, Antennas			15. NUMBER OF PAGES 200	
			16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT Unclassified	18. SECURITY CLASSIFICATION OF THIS PAGE Unclassified	19. SECURITY CLASSIFICATION OF ABSTRACT Unclassified	20. LIMITATION OF ABSTRACT UL	

THIS PAGE INTENTIONALLY LEFT BLANK

Approved for public release; distribution is unlimited

**A STUDY OF THE FEASIBILITY AND APPLICABILITY OF SHAPE
CONTROLLED SPACE BASED INFLATABLE MEMBRANE STRUCTURES**

Craig M. Whittinghill
Lieutenant, United States Navy
B.S., United States Naval Academy, 1995


Submitted in partial fulfillment of the
requirements for the degrees of

**MASTER OF SCIENCE IN
SPACE SYSTEMS OPERATIONS
and
ASTRONAUTICAL ENGINEERING**


from the

**NAVAL POSTGRADUATE SCHOOL
September 2000**


Author:



Craig M. Whittinghill

Approved by:


Brij Agrawal, Thesis Advisor


Donald v.Z. Wadsworth, Co-Advisor


for Max F. Platzzer, Chairman
Aeronautics and Astronautics Department


Rudy Panholzer, Chairman
Space Systems Academic Group

THIS PAGE INTENTIONALLY LEFT BLANK

ABSTRACT

Inflatable structures used for space applications offer mass, volume, and cost savings to spacecraft programs, allowing larger space structures to be built. For certain space applications, there are advantages to using large structures. For example, antennas achieve higher gains when they are increased in size. Higher gains equate to higher data throughputs. Therefore, inflatable structures offer improvements in performance to certain types of spacecraft components.

Environmental factors induce surface errors on large inflatable structures. This degrades performance, especially for inflatable antennas. To reduce this degradation, active and passive control systems can be used to sense errors and control the shape of the antenna. One method of applying an active and passive control system is by using piezoelectric films that are either attached to or are part of the inflatable structure.

The research performed for this thesis explored the theoretical performance of a large inflatable space-based antenna via spreadsheet analysis and the physical performance of a piezoelectric film via laboratory experimentation. For the laboratory experiment, the film was attached to a drum and varying internal pressures and voltages were applied. Also, in order to validate the experimental results, an analytical model was created using MSC/PATRAN and MSC/NASTRAN software.

THIS PAGE INTENTIONALLY LEFT BLANK

TABLE OF CONTENTS

I.	INTRODUCTION.....	1
II.	APPLICATION OF INFLATABLE TECHNOLOGY	3
	A. USE OF INFLATABLE TECHNOLOGY FOR ANTENNA DEVELOPMENT.....	3
	B. APPLYING INFLATABLE TECHNOLOGY TO SPACE-BORNE COMMUNICATIONS SYSTEMS	9
	C. OPERATIONAL USE OF SPACE INFLATABLE STRUCTURE TECHNOLOGY	15
III.	EXPERIMENT	25
	A. INFLATABLE STRUCTURE EXPERIMENTAL SET-UP	25
	B. INFLATABLE STRUCTURE EXPERIMENTAL RESULTS.....	32
IV.	ANALYTICAL MODEL SET-UP AND RESULTS	43
V.	CONCLUSIONS.....	51
	APPENDIX A - EQUATIONS USED FOR ANTENNA OPERATIONAL ANALYSIS.....	55
	APPENDIX B - ANTENNA ANALYSIS SPREADSHEETS AND GRAPHS	57
	APPENDIX C - LABORATORY EXPERIMENTAL RESULTS AND GRAPHS OF THESE RESULTS.....	81
	APPENDIX D - ANALYTICAL MODEL INFORMATION	91
	LIST OF REFERENCES	181
	INITIAL DISTRIBUTION LIST	185

THIS PAGE INTENTIONALLY LEFT BLANK

ACKNOWLEDGEMENT

The author would like to thank Professor Guillermo Ramirez, Professor Ramesh Kolar, Professor Donald v.Z. Wadsworth, Jeff Knight, Christian Taranti, and Professor Brij Agrawal for their help and academic guidance with this endeavor and research.

THIS PAGE INTENTIONALLY LEFT BLANK

I. INTRODUCTION

Inflatable structures are becoming the structures of choice for use in large, space-based structures. Inflatables have a long history of development, but not until recently have they received much attention. They offer many advantages that traditional structural materials (metals, for example) do not. One of their major drawbacks, though, is the fact that they are not as rigid as traditional structural materials.

To help maintain an inflatable structures shape, a control system could be developed to sense and correct these shape errors. Piezoelectric films (thin, flexible materials that change shape when an electric field is applied or create an electric field when their shape changes) are potential control devices that can be used to sense and correct shape errors. If this can be accomplished then the uses of large, inflatable structures can be implemented.

One potential use for inflatable structures in space is as antennas. Large antennas could be included on communications satellites without increasing the cost or mass of the satellite if inflatables are used, and data throughput could be greatly increased. The Department of Defense, for one, should be interested in such a technology advance. Therefore, this thesis intends to demonstrate that this technology can be realistically applied and that it offers great advantages to those who use it.

A look into the use of inflatables as antennas will begin this thesis followed by an examination of the improvements this technology can provide a communications system. Then, a discussion of the history, advantages, funding, and current work being done on inflatables will be presented. After this, the experimental portion of this thesis will be

discussed. A description of a piezoelectric film experiment's set-up and results will be described and presented, and then the efforts made to establish an analytical model will be provided. Finally, conclusions will be drawn.

This thesis intends to show the advantages of using inflatable technology for Department of Defense uses and to demonstrate the potential for using piezoelectric films as part of a shape control system.

II. APPLICATION OF INFLATABLE TECHNOLOGY

A. USE OF INFLATABLE TECHNOLOGY FOR ANTENNA DEVELOPMENT

Antennas in space are a necessity for communications systems utilizing satellites. Today, there are a number of applications for large aperture space-based antennas. Some of these are Very Long Baseline Interferometry (VLBI), mobile communications, earth observation radiometry, active microwave sensing, and space-based radar (Freeland and Bilyeu, p. 1-2). However, placing large antennas in orbit is not easy or cheap. To make large space-borne antennas practical and affordable, inflatable, thin walled structures are being developed. Inflatable structures offer many advantages over traditional metallic, rigid structures. These will be covered later in this work, but now a look at what types of structures are being considered for manufacture and those that have been manufactured will introduce the reader to this new and growing field. To accomplish this, two programs, the Advanced Radio Interferometry between Space and Earth (ARISE) and the Inflatable Antenna Experiment (IAE) programs will be examined. However, these two programs use the same basic structure and antenna type. Before beginning an in-depth look at ARISE and IAE, a look at some other alternative antenna types is appropriate.

Research for this thesis has produced three different types of potential inflatable, space-based antennas. They are an inflatable phased array antenna, an inflatable parabolic reflector antenna with phased array feeds, and a similar parabolic reflector antenna. The latter two will be addressed together. The shapes needed to attain these

types of antennas are achieved using inflation pressure and manufactured gores that when attached together and inflated produce a desired shape. Inflatable phased array antennas (without a reflector) have been proposed as a viable solution for making large space-based antennas with apertures up to fifty-five meters in diameter. This inflatable antenna would offer all of the advantages of conventional phased arrays (multiple, steerable beams, for example), but it would not retain the desirable traits of a continually inflated space structure because it would have to be rigidized.

Once in space, the antenna would be inflated and rigidized. The rigidization would take place by constructing the antenna using materials that solidify over a matter of hours when exposed to either the ultra-violet light or some other material solidification method. This would prevent distortion of the antenna in space when the gas used for inflation dissipates (Kunath and Sharp, 1991, p. 2).

The problem with using rigidization for the whole structure is that the inflatables lose the traits of ruggedness and damped dynamics, which are inherent in inflatables that are not rigidized (Palisoc et al, 1998, p. 748). This type of rigidized inflatable antenna would also become very complex with increasing size (Kunath and Sharp, 1991, p. 1). Therefore, the parabolic-shaped inflatable antennas offer a more attainable configuration in the short term, and consequently, more work has gone into their development.

Parabolic inflatable antennas that are being produced today include a lenticular structure with a torus and struts for support. The torus and struts are rigidized after inflation in orbit, and the lenticular structure is kept inflated with gas for the life of the satellite. The lenticular structure consists of a reflective parabolic surface and a symmetrical, radio frequency transparent canopy. The two parabolic surfaces are joined

together at the torus, which encircles the lenticular structure at the joining of the parabolic surfaces and attaches itself to the lenticular structure by means of adjustable ties. The struts then connect the antenna to the rest of the spacecraft (Cassapakis and Thomas, p. 5). Microstrip array feeds can be placed in the antenna structure so that multiple beams are available for use (Hoferer, 1998, p. 1452-1453), or the antenna can be configured for just one beam. The basic antenna structure is the same for either configuration. Figure 1 shows an artist's conception of such an antenna. This picture was found on the L'Garde, inc. webpage (www.lgarde.com).




Figure 1. Artist's Conception of an Inflatable Parabolic Antenna.

There are two major hurdles for this type of antenna to overcome: meteoroids ripping holes in the surface of the structure and surface errors.

Assuming that the inflatable antenna can be deployed properly and attain its desired shape, which IAE showed was possible, the antenna must maintain its desired shape for the remainder of its design life. There are many reasons why inflatable

antennas would lose their desired shape, and this topic is addressed in a later chapter. However, one major possibility of shape loss would come from deflation. Meteoroids could tear holes in the antenna, and the gas used to inflate the antenna could escape. Replacement gas is therefore needed to maintain the shape of the antenna and to keep it inflated. Analysis of the meteoroid environment has led to the conclusion that inflated systems could remain operational for ten or more years. This is due to the low pressures needed to maintain the shape of the antenna and the low weight of the gas system (Palisoc et al, 1998, p. 748). The low pressures required stems from the fact that these antennas will be in a zero gravity environment in which a small internal pressure is sufficient to provide stiffness and shape (Criswell et al, p. 1046). In fact, it is estimated that a 10-meter inflated antenna system with a ten year design life would have a mass of only 145 lbm and a 30-meter inflated antenna system with a ten-year design life would have a mass of only 190 lbm (Thomas and Friese, p. 66). These values are lower by hundreds of pounds (mass) than deployable antennas made from metals of comparable size. So, having a realistic ability to maintain inflation over the design life, only surface errors remain to be resolved.

Surface errors in the antenna reflector surface can come from a number of sources, and there are a number of ways to correct these errors. All of this is covered in a later chapter, but the precision that a reflector surface needs to have to be an effective antenna should be addressed now. Good antenna performance requires that the rms (root mean square) surface accuracy of the antenna be between sixteen and twenty times better than the wavelength (λ) being used (Ulvestad, Linfield, and Smith, p. 5). For frequencies of 6.32 GHz ($\lambda = 47.5$ mm) and 8.4 GHz ($\lambda = 35.7$ mm), the rms surface errors would

have to be kept to 2.4 mm and 1.8 mm, respectively. As an example, a 10-meter diameter antenna with a 0.77 mm rms error would have a gain of 79% of its theoretical maximum at 15 GHz which corresponds to a 20 mm wavelength (Thomas and Friese, p. 1). In later analysis, a 1 mm surface rms error is assumed, and the gain of antennas using different frequencies is calculated taking this error into account using the Ruze equation (Cassapakis, Love, and Palisoc, 1998, p. 456).

Also of concern for these large structures is atmospheric drag. If, however, these structures are placed above 750 km, there is no significant atmospheric drag (Cassapakis, 1999, p. 5). Having discussed this type of antenna in general terms, it is now appropriate to examine one use of this structure and one planned use of this structure.

The IAE was a NASA project launched from the space shuttle Endeavour as part of mission STS-77 on May 20, 1996. It was deployed in a Low Earth Orbit via a Spartan 207 retrievable satellite and remained operational for ninety minutes until jettisoned (NASA, p. 2). The reflector itself was fourteen meters in diameter, had twenty-nine meter struts, and weighed less than 200 lbs (Acree, p. 4). The design goal of the IAE was to achieve a surface precision of 1 mm root mean square error while on orbit (Freeland, p. 4). This was almost achieved, but a root mean square error of a few millimeters resulted (Freeland et al, p. 6). Still, even though no actuation system was used, the IAE could be used with frequencies around 5 GHz. This reaches into the C-band of the RF spectrum, and it could be used for mobile communications. Also, the stowage size of this antenna was roughly the size of an office desk (Freeland et al, p. 6). This experiment, the first of its kind, showed that inflatable reflectors in space are achievable, and its performance is helping the development of inflatable structures for future use.

The ARISE program is under development, but it is planned to be a Very Long Baseline Interferometry mission that will consist of at least one 25-meter diameter radio telescope that will have basically the same structure as IAE and other lenticular inflatable antennas. It will be placed in a Highly Elliptical Orbit (HEO), and the spacecraft will have a mass of approximately 1700 kg. The expected launch date is in 2008 (Chmielewski and Ulvestad, p. 2). ARISE will observe frequencies up to 86 GHz, meaning that the root mean square surface error needs to be approximately 0.175 mm. In 1999, L'Garde built a 7-meter inflatable antenna that had a 1.7 mm rms error, but it predicts that it can reduce that to 1 mm for a 25-meter reflector with appropriate development effort (Chmielewski, p. 5). More work and development is needed to make ARISE a reality. A later chapter will address the current work and funding for this technology, and another chapter will address a potential actuation method for surface accuracy maintenance. IAE and ARISE are both helping the development of inflatable structures and especially inflatable antennas. Because of the continuing maturation of this technology, the Department of Defense can benefit greatly from inflatable structures in space.

The next chapter will explore how inflatable antennas can improve data rates for space-based communications systems. A mobile, disadvantaged user (low power, small antenna) can receive extremely high volumes of data quickly if large inflatable antennas are used in space. There is one major drawback to using them (reduced footprint size), but the enhanced communications capabilities to the military are immense. With continuing research, an extremely viable group of materials for communications systems antenna design will be available.

B. APPLYING INFLATABLE TECHNOLOGY TO SPACE-BORNE COMMUNICATIONS SYSTEMS

Inflatable antennas offer many advantages to a satellite system. They are lightweight structures, can be stowed compactly, and are relatively cheap. Conventional antenna structures cannot compete with inflatable structures in these categories. Inflatable structures now make it feasible to put larger antennas in space. Larger antennas offer many advantages to ground users, especially mobile, disadvantaged users. The link can be closed for many more users, and the data rate throughputs that they can receive is excellent. To confirm these conclusions, a few link budget models were created and evaluated.

Using Excel, six different models were created. Two were Intelsat VII link budgets, and four were the Defense Satellite Communications System (DSCS) III Service Life Enhancement Program (SLEP) link budgets. These two satellite systems were selected because the military uses them for communications. One is commercially owned (Intelsat VII) and the other is a Department of Defense asset (DSCS III). Since most of the specifications for these two satellite systems and their operations were available in open literature, the link budgets have some real use numbers in them. Values for certain operational parameters (e.g., bandwidth and power for specific operational scenarios) are not available, so these were handled parametrically or nominal values were employed. Meaningful comparisons and conclusions can still be reached by this analysis. The environment used for this analysis is benign. No jamming or multiple user

considerations were modeled. Other constraints had to be applied to make the link budget analysis possible.

For the Intelsat VII link budgets, Intelsat 702 was selected, and for the DSCS III link budgets, the SLEP program was selected. Using Communications Satellites 1958-1995 produced by The Aerospace Corporation and a series of briefs produced by the U.S. Naval Space Command, bandwidths, frequencies, and antennas, for example, were extracted and entered into the models. These models can be seen in Appendix B, and to keep this chapter succinct, they can be referenced for exact data used in this analysis. The gray box entries are values entered into the model, and the rest of the boxes are solved for using equations that can be found in Appendix A. Of note, the edge of the ground footprint of the satellite system, not the center, was used in the analysis. This shows the robustness of the analysis. The Intelsat 702 spot beam and the DSCS III SLEP Channel 3 were used in the model. Also, the ship and ground antennas used for this analysis are not easily extracted from the models. For the Intelsat 702 models, the Navy Commercial Wideband SATCOM Shipboard antenna (2.7 meters) and the AN/FSC-78(V) (18.29 meters – ground antenna) were used. For DSCS III SLEP, the AN/WSC-6(V)5 (2.36 meters) was used for the shipboard antenna, and the AN/FSC-78(V) was used again for the ground antenna. The AN/WSC-6(V)5 is listed as a seven-foot antenna, but, according to Ray Gajan of the U.S. Naval Space Command, the diameter of the antenna is actually seven and three quarters feet in diameter (2.36 meters). For the disadvantaged user models using the DSCS III SLEP satellite system, the ground antenna used was the AN/FSC-78(V), and the disadvantaged user antenna was selected to be 0.25

meters (9.85 inches). With these assumptions presented, it is now appropriate to elaborate on the inflatable antenna aspect of the models.

For the inflatable antenna, two model parameters were varied. The diameter of the antenna was increased in 5-meter increments from that of the existing Intelsat 702 and DSCS III SLEP antennas to a maximum of forty meters. The second parameter was the rms surface deviation from ideal. Assuming that an rms surface error of one millimeter can be achieved on an inflatable antenna in space by use of some sort of actuation system, a degraded antenna gain was calculated for each antenna diameter. Of note, the space antenna for Intelsat 702 (existing on satellite now) and the inflatable antennas that replaced it in the analysis were both the transmitting and receiving antenna. For DSCS III SLEP equipment (existing on satellite now), a separate receive multi-beam antenna was used in the analysis since it has receive and transmit multi-beam antennas for channel 3. The inflatable antennas used to replace the existing DSCS III SLEP antennas in the analysis were used for both transmitting and receiving. The main advantages of using a larger antenna are that a weaker signal can be sensed at the satellite and more signal power can be received at the ground antenna. This is due to the increased gain of the antenna, due to its size. The result is more data throughput, since most disadvantaged users (ship or mobile) are not throughput-limited by the amount of bandwidth they are using but by the amount of received power. A major drawback to using larger space-borne antennas to improve link performance is that the ground footprint is diminished, so that only users in a smaller geographical area on the earth can access the space-borne antenna. With this in mind, an evaluation of the performance of the inflated antennas is in order.

Three relations are used to calculate throughput (i.e., information bit rate) for a space-based antenna system. One uses the received signal power C and required E_b/N_0 in order to calculate throughput. Another relation uses channel bandwidth and received signal to noise power ratio (Shannon's limit) to calculate throughput. The third uses bandwidth, signal modulation, and a waveform shaping or roll-off factor to calculate throughput. All of these relationships can be referenced in Appendix A. These three throughput relationships help in analyzing the effectiveness of a larger antenna. As will be seen, a large increase in space-borne antenna size will not do much for current ship configurations. However, the future disadvantaged user will benefit immensely from a larger space-borne antenna as will future ship configurations.

Appendix B shows the graphs of the throughputs based on the three relations mentioned earlier and antenna size. When examining these graphs, it is important to note that the maximum data throughput that can be achieved for a given antenna size can be no greater than the lowest throughput indicated by the three curves on the graph. Beginning with the Intelsat 702 and DSCS III SLEP ship-to-ship and shore-to-ship graphs, an examination reveals that they all present a similar picture. If there were no bandwidth limitations, the throughput could be vastly improved by increasing the size of the satellite antenna. However, this is not currently practical. The throughput theoretically could be improved somewhat up to Shannon's channel capacity limit, but the practical achievable throughput is much lower than this limit. Increasing signal power only improves the bit error rate beyond this threshold (Wadsworth). Larger antennas for this application provide little improvement in capability. Only small changes in antenna size make any difference. In fact, the throughput is optimized with a

satellite antenna diameter somewhere between the Intelsat or DSCS III antenna and a five-meter antenna. Of note, the DSCS III SLEP graphs and disadvantaged user graphs all show an antenna diameter of 0.711 meters for the first antenna diameter. This is the transmitting antenna diameter, but both the transmitting and receiving antennas were used in the analysis. Therefore, the graphical representation of these scenarios is not completely accurate, but they give a good approximation of throughput capabilities for the actual DSCS III SLEP antenna used. So, a small change in size maximizes throughput, but inflatable antennas could still be used to reduce weight, save cost, and provide numerous pre-deployment stowage options. However, the disadvantaged user who has a quarter of a meter antenna benefits greatly from larger space antennas.

The disadvantaged user has many limitations. Disadvantaged users are mobile so it is difficult to carry heavy and bulky equipment, and they have little power to transmit signals. With this in mind, two models were set up using the DSCS III SLEP satellite. The two models developed are a disadvantaged user to a disadvantaged user model and a ground to a disadvantaged user model. The maximum transmit power of a disadvantaged user was set at five watts. A soldier on the ground could carry a communications unit that meets these criteria. Appendix B can also be referenced for the disadvantaged user graphs and spreadsheet models. From that data, a disadvantaged user could send data to a disadvantaged user via a forty-meter space borne antenna with a data rate of approximately thirteen Mbps. That value is about eight T-1 lines, and this is not even the practical limit. With a larger space antenna, even more throughput could be achieved. A shore link to a disadvantaged user would provide the full potential throughput with a space antenna somewhere greater than forty meters in diameter. For a forty meter

antenna, the data rate is roughly twenty-seven T-1 lines. So, the throughput capability of a disadvantaged user would be tremendous. However, there is a drawback to using this larger antenna.

The geographical area of a satellite footprint is diminished with increasing satellite antenna size. In fact, frequency and antenna size affect footprint size, but since the frequencies are fixed in these models, only antenna size affects the footprint size. Now, some clarification is in order. The access field of view of a satellite is unchanged regardless of antenna size or frequency. The coverage field of view is what changes. So, a ground site would be in the field of view of what the satellite can see regardless of antenna size or frequency, but it may not be in the field of view of the satellite beam that can send or receive data. This would become a large factor in the disadvantaged user scenario. For example, for both disadvantaged user scenarios, the up-link footprint goes from approximately 1,500,000 square kilometers to 1,000 square kilometers if a forty meter antenna is used. For the down-link, the footprint goes from approximately 20,000,000 square kilometers to 5,000 square kilometers if a forty meter antenna is used. These are large differences. An accurate pointing system would have to be used on the ground and on the satellite. However, this is a small price to pay for such a large improvement in throughput. In fact, 1,000 square kilometers may be a major theater of war, especially in this age of low intensity conflict. The communications link produced by the satellite would be limited to those users in a certain geographical location, but the signal power provided to those users would be substantial, allowing many users to share that signal power and still maintain high data rates. With these advantages, the application of inflatable technology is extremely attractive.

Even though disadvantaged users with small antenna benefit greatly from a larger satellite antenna, it cannot hurt other users from using them as well, as long as accurate pointing schemes and mechanisms were present. A current ship configuration will have its throughput maximized if, for example, a forty meter satellite antenna were used. It would just need to be in the satellite's footprint. With beam pointing from the satellite and accurate tracking and pointing of the ship antenna, this is possible. In fact, ships could use the smaller quarter of a meter antennas. The space on a ship is limited, so any savings in antenna size are attractive. Using inflatable structures makes this concept a possibility. Large antennas will be able to be used in space due to the advantages and savings inflatable structures provide. More research and work is needed, though, to further validate this technology.

C. OPERATIONAL USE OF SPACE INFLATABLE STRUCTURE TECHNOLOGY

Inflatable space structures are a promising technology that has received renewed interest in recent years. These structures are made of thin, flexible materials that can be inflated into a predetermined, manufactured shape. Research and development began on these structures in the 1950's. Goodyear developed technology demonstrations on structures such as an inflatable search radar antenna, a lenticular inflatable parabolic reflector, an inflatable pyramidal horn, and a radar calibration sphere. All of these demonstrations were developed in the late 1950's, but they were not the first flight-tested inflatable structures (Freeland and Helms, 1999, p. 4-7). The first flight-tested inflatable

structures were balloons that were part of NASA's Echo program. Echo was a passive communications relay program, and seven balloons were launched between 1958 and 1964. Over twenty years passed before another inflatable structure was successfully used in space, except for the inflatable re-entry vehicle decoys used beginning in the late 1960's (Katuin, 1999, p. 1). These decoys were used to simulate the radar and IR signatures of re-entry vehicles. Interestingly, though, they were the first flight-tested inflatable structures that were configured in a shape other than a sphere (Freeland and Helms, 1999, p. 9). It wasn't until the mid-1980's until new inflatable structures were flight-tested.

In 1984, NASA unsuccessfully deployed an inflatable calibration target for a Ku-band radar. Then, in 1985, the Soviet Union used two inflatable balloons in its Venus missions, Vega 1 and Vega 2 (Katuin, 1999, p. 1). Over ten years passed before inflatable structures were used again, but there were significant technology demonstrations in the 1980's. For example, the European Space Agency developed a 6-meter inflatable very long baseline interferometry antenna, an inflatable telescope sunshade support structure, and a 10 by 12 meter inflatable land mobile communications reflector antenna. L'Garde, Inc. and the United States Air Force developed an inflatable large offset reflector structure in the late 1980's (Freeland and Helms, 1999, p. 10-13). However, it wasn't until 1996 that another inflatable structure was launched into orbit. On May 20, 1996, NASA launched the Inflatable Antenna Experiment (IAE) from the Space Shuttle Endeavour. The IAE was a 14-meter diameter antenna that was used to test the potential of using inflatable structures as antennas (Katuin, 1999, p. 1). The mission was a success, and there are more inflatable missions on the horizon.

One newly developed inflatable structure is part of a United States Air Force project that will use lasers to track an inflated sphere target. The sphere has a 12-meter diameter with a skin thickness that is thinner than a human hair and is silver in color. L'Garde, Inc. constructed the sphere in four months, and its cost was \$500,000. (Robbins, 1999, p. 1). A near future use of this technology is an inflatable solar array that will be part of the DS4/Champollion mission in 2003. This mission will be the first to land on and study the center of a comet (Acree, p. 15). Inflatable technology has a long and mostly successful history, and there is current work being done with this technology as well. In fact, inflatable technology is rapidly developing, and its uses are almost endless.

There are many potential applications for inflatable structures in space. Among these are space suits, habitats, antennas, attenuation systems, reflectors, covers and sun shields, solar arrays, and radars (ILC Dover, 1999, p. 8). Other possible uses are for rovers with inflatable wheels, sail occulters, infrared telescopes, and radiometers (Chmielewski, 1999, p. 17, 21). Science instrument support structures, solar cell support structures, large lightweight trusses, and solar collectors and concentrators are also possible uses (Freeland and Helms, 1999, p. 18). The Department of Defense, NASA, and commercial industry are even working on developing phased array antennas (Katuin, 1999, p. 6). In fact, the Air Force Research Laboratory initiated analytical and experimental evaluation of membrane phased array antennas in fiscal year 1998 (Acree, p. 1). Other types of more conventional structures could be used to try to achieve most of these applications, but there is a reason why there is considerable interest in using

inflatable space structures. Inflatable space structures have distinct advantages over conventional space structures.

Inflatable structures have low system mass, low development and production cost, low packing volume, packing flexibility, reduced system complexity (high reliability), controlled deployment, components that can be rigidized, long life, and design flexibility (many different configurations and shapes are possible) (ILC Dover, 1999, p. 10). These are all advantageous attributes for a space structure to possess, but perhaps the most advantageous attribute, that has not been mentioned yet, is low cost.

Inflatable space structures offer cost savings to a space system. Lower mass and stowed launcher volume may allow a smaller launch vehicle to be used. This will save a space system a considerable amount of money since a large portion of a space system's cost comes from its launch platform. In fact, a stowed inflatable space structure is ten to one hundred times smaller than a stowed mechanically deployed structure, and its mass can be up to ten times smaller than a conventional structure (Acree, p. 6). For example, in 1992 fiscal dollars, if using an inflatable space structure allowed a satellite to be launched in an Atlas G or a Centaur instead of a Titan IV, eighty-two million dollars would be saved in launch costs (Larson and Wertz, 1992, p. 731). Inflatable space structures offer possibilities like this. They are also inherently cheaper than conventional space structures. For example, an operational version of the IAE could be developed for approximately ten million dollars (in 1996), but a conventional space structure with the same capabilities as the IAE may cost as much as two hundred million dollars (Gipson, 1996, p. 1). Overall, inflatable space structures are ten to one hundred times cheaper than conventional structures (Acree, p. 6). It is postulated that in 2003, a UHF to X-band

antenna with millimeter surface accuracy will have a recurring cost of seven million dollars for a 10-meter antenna and ten million dollars for a 25-meter antenna (Acree, p. 4). These cost reductions are attractive, but there are even more advantages and attractive qualities that inflatable space structures offer to space systems.

Inflatable space structures are not susceptible to acoustics and vibrations caused by launches, and they can be deployed without using extravehicular activity. They also have excellent dynamics while in orbit, and they tend to have relatively small surface errors in orbit since gas pressure tends to perfect bodies of revolution (Frieze and Thomas, p. 1). Also, inflatable structures "offer better thermal control opportunities than open structures. The radiative exchange between the sides of the inflatable can sharply reduce temperature non-uniformities" (Thomas and Frieze, p. 1). Another advantage is the availability of materials and their abilities to be rigidized (inflated and then hardened into a firm shape). Some materials used for producing inflatable structures are polyesters, fluoroplastics, and polyimides. An example of a polyester is polyethylene terephthalate. Examples of fluoroplastics are Teflon (PTFE and CTFE), fluorinated ethylene propylene (FEP), and polyvinylidene fluoride (PVDF). An example of a polyimide is Kapton. Also, all of these types of materials are either thermosets or thermoplastics. These traits allow some forms of rigidization to be possible.

A thermoset is a material that when heated maintains its shape, and the process is not repeatable. A thermoplastic is a material that will melt when heated and solidify when cooled. This process is repeatable (Bradford, 1999, p. 4). Some methods that use these traits and other means for rigidization are fabric impregnation of resin that is cured by ultraviolet light exposure, fabric impregnation of water soluble resin that causes

rigidization upon water evaporation, fabric impregnation with a resin that rigidizes when cooled below its glass transition temperature, application of heat to cure plastic resin, and application of strain to aluminum laminate beyond its yield point (Freeland, Bilyeu, and Mikulas, p. 5). Rigidization may be desirable because some space inflatable structures, if not rigidized, will require relatively high pressures to maintain their shape. If leaks develop from holes caused by meteoroids, for example, the amount of gas needed to keep the structure's shape may not be practical. Larger inflatable structures that will not require high pressures for inflation will not have the same problem. Their inflation pressure will be around 10^{-7} psi (ILC Dover, 1999, p. 11). In fact, "the operating pressure of large antennas is sufficiently low so that they can operate in the meteoroid environment for many years. The replacement-inflatant weight is not excessive" (Friese and Thomas, p. 2). So, rigidization is not necessary for these structures. However, if surface accuracy is important to a particular inflatable structure, then shape control may be necessary to maintain its shape.

There are many sources of surface error for an inflatable structure. Some of them are "material stiffness properties and areal variation, material thickness and areal variation, creep, moisture effects, material 'wrinkling' or creasing due to handling and packaging, fabrication, analytical shape prediction, edge support conditions, pressure level, thermal distortion, and gravitational effects in earth testing" (Bilyeu, Freeland, and Mikulas, p. 9). With so many sources of error, a capable actuation system may be needed for certain applications of inflatable space structures. Some possible actuation methods are adjusting edge radial displacements, controlling internal pressure, using thermal gradients across the structure surface, and incorporating piezoelectric materials into the

body of the structure (Freeland, Bilyeu, and Mikulas, p. 11). Piezoelectric materials, materials that change shape in the presence of an electric charge or produce an electric charge when their shape changes (Shields, p. 7), offer a particularly attractive actuation method because not only could they be used to change the shape of the structure, they could also be used to sense when surface errors arise. This could lead to an active control system.

There are a few ways this active control system could be activated to produce an active control system. Two of these methods involve using an electron gun to control a piezoelectric film and using discrete electrode coatings on a piezoelectric film (Bradford, p. 2). The electron gun would scan the film, inducing an electric charge where needed to maintain the structure's shape (Clayton, p. 2). This scheme doesn't account for feedback of the structure's shape. Leads or some other device would have to be connected to the structure. The discrete electrode coatings, or patches of coated piezoelectric material, could be connected to a control system via leads or some other device that could deliver electric charge and sense it also. This seems to be the most practical. Another method would entail piezo-induced strains on the tie rods, if they exist, of a structure. The implementation of this method would be similar to that of the discrete electrode coatings (Salama et al, p. 5). Also, these types of materials are widely available. Of the previously mentioned materials, PVDF, at least, can have the piezo effect induced into it by permanently polarizing its dipoles by applying a high voltage at high temperature. In general, polymers can undergo this treatment to make them piezoelectric (Salama et al, p. 2). Of note, research has been done to develop materials with a large piezoelectric response suitable for inflatable structure shape control. This research produced several

compositions of perovskite $\text{PbZr}_{1-x}\text{Ti}_x\text{O}_3$ (PZT) for NASA for use in shape control applications (Neurgaonkar and Nelson, p. 1, 4, and 31).

Inflatable space structures are a developing, attractive technology that will allow missions that were impractical or impossible with conventional technology to become possible. The only other technology that claims that it is an effective alternative to inflatable technology for developing structures in space is space robots used for the assembly of structures. This claim does not take weight or stowed volume into account (Kimura et al, p. 14). If robots did assemble structures, the structure's components would still have to be placed into orbit. If these components weigh the same as conventional components, then there would be no savings in launch cost. Inflatable space structures are an attractive technology that has many applications and much work is being done in this field today.

Current and past funding levels for inflatable research and development are telling signs that there is a considerable amount of interest and enthusiasm regarding this technology. In fiscal year 1997, ten million dollars was spent at the Jet Propulsion Laboratory, NASA centers, the Department of Defense, and industry on inflatable research and development (Chmielewski, 1999, p. 8). In fiscal year 1998, this number grew to twelve million dollars (Chmielewski, 1999, p. 9). In fiscal year 1999, the funding number grew to twenty and a half million dollars (Chmielewski, 1999, p. 10). It is projected that, beginning in fiscal year 2000, inflatable structure funding will double every year (Chmielewski, 1999, p. 22). So, with funding on the increase, many industry organizations are becoming involved in the research and development of inflatable structures.

NASA and the Department of Defense are two of the main players in this technology field, but the number of corporations involved is growing. In 1995, L'Garde, Inc., SRS, Aerospace Recovery Systems, ILC Dover, and Thiokol were the main private organizations that had demonstrated large inflatable structure technology capability (Satter and Freeland, 1995, p. 1). In 1999, Winzen Engineering Inc., Sigma Labs Inc., ITN Energy Systems Inc., Vertigo Inc., Millimeter Wave Technology Inc., United Applied Technologies Inc., Adherent Technologies Inc., Energen Inc., Triton Systems Inc., Aeroplas Corp., and Raven Technologies could be added to the list of organizations with promising inflatable structures technology (Freeland and Helms, 1999, p. 16). All of these corporations are contributing to the body of knowledge of inflatable structures. Their work is paving the way for future uses of inflatable technology.

The current work being conducted in this technology field is the validation of inflatable structures. For example, the Air Force Research Laboratory is conducting work on controlled deployment (of structures from 8 meters to 200 meters), the validation of analytical models and tests, controlled structure interactions (pointing, for example), creating precision surfaces, and enhancing application performance. Other areas that this lab plans to address are creating rigidizing structures for space, developing membranes with good lifetime performance, and enhancing lifetime system performance (Acree, p. 28). With efforts like these, missions proposed for the future will become realities.

NASA has even set some goals for its inflatable structures program. These goals for the mid-term (2000 – 2005) are to develop technology for solar sails, antennas, rovers and to transition sunshields, solar arrays, and radars to industry (Chmielewski, 1999, p. 3). Its far-term goals (2005 – 2020) are to transition solar sails and antennas to industry

and to develop the Gossamer spacecraft architecture (NASA program that uses inflatable technology) (Chmielewski, 1999, p. 3). In fact, NASA is proposing that inflatable structures will be able to assist in a list of varied missions. These are imaging remote galaxies, detecting life on extrasolar planets, monitoring the earth using high resolution, imaging extrasolar planets, imaging active galactic nuclei, sending video from deep space, monitoring earth's environment, investigating planet subsurfaces, communicating optically, providing solar power in deep space, taking short time travel trips, non-Keplerian viewing, transporting cargo to Mars, and developing infrared astronomy (Chmielewski, 1999, p. 2). With goals and aspirations like these, NASA is pushing the development of this technology, and hopefully its near future timetable of inflatable projects may occur according to plan.

As of 1999, NASA planned to have a number of inflatable structures in space through 2020. Some of these are a radar by 2003, the NGST sunshield by 2007, solar sails for a Mercury orbiter by 2007, the Arise satellite by 2008, an interstellar probe by 2010, deep space antennas by 2010, and large optics by 2020 (Chmielewski, 1999, p. 5). This list is ambitious, but with current trends, it may not be unrealistic. However, there is still much work to be done.

Some of the areas that the Air Force Research Lab plans to do work in are areas of general improvement that need to be done to help validate this technology. ILC Dover lists five areas of potential improvement. They are testing and developing rigidizable materials, controlled deployment mechanisms, structural designs, adaptive structure designs, and manufacturing methods (ILC Dover, 1999, p. 38). With continuing effort, these improvements will be made and this technology will become completely validated.

III. EXPERIMENT

A. INFLATABLE STRUCTURE EXPERIMENTAL SET-UP

To begin to explain the work done at the Naval Postgraduate School (NPS), this section will discuss the equipment and procedure used for this experiment. The facility used was the Spacecraft Research and Design Center (SRDC) in Halligan Hall at NPS. The procedure used for this experiment was adapted from the work of Dr. Moktar Salama and Dr. C. P. Kuo of the Jet Propulsion Laboratory (JPL). Parts of the procedure were developed exclusively for this experiment, though. To begin this chapter, however, an in depth look at the equipment used for this experiment will be presented.

The pieces of equipment used for this experiment were procured from various sources. They were made in-house, purchased from industry, borrowed from other departments at NPS, or taken from the existing inventory of the SRDC. The major pieces of equipment used were a polyvinylidene fluoride (PVDF or Kynar) membrane, a polyvinyl chloride (PVC) drum with clamp, a tank of pressurized nitrogen gas, a low pressure air regulator, a voltage source and computer interface used for taking measurements (d-Space), an amplifier, copper tape, a displacement measurement laser, a low current power source, an oscilloscope, and various wires and tubes to connect it all together. The PVDF was the principle piece of equipment used since its response to different voltages and pressures was being studied. Figure 2 shows the drum, PVDF, and laser set-up.




Figure 2. Experimental Set-Up.

Membranes were purchased from a company called Measurement Specialties, Inc. The PVDF membranes are 52 micrometers (0.0020488 in) thick cut in a circular pattern with a 26.65 cm (10.5 in) diameter. A lead for a voltage source attachment was extended from the circular pattern, making the membrane look somewhat like an apple with its stem. The membranes are piezoelectric, poled to create a mechanical response (contraction or expansion) in the “3” or thickness direction when an electric field is applied. On both sides of each membrane is a thin coating of NiCu alloy, used as a conductor to apply an electric field to the membrane. To conduct the experiment, one membrane was attached to a PVC drum. A schematic of the experiment and its components can be seen in Figure 3.




Figure 3. Schematic of Experiment.

The drum has two basic parts. These parts are the base and the lip. The base is a cylinder that is open on one end and closed on the other. The outer diameter of the cylinder is 22.84 cm (9 in) and the inner diameter is 20.30 cm (8 in). The depth of the cylinder is 12.70 cm (5 in). The lip is rigidly attached to the cylinder on its open end and has an outer diameter of 26.65 cm (10.5 in) and an inner diameter of 21.57 cm (8.5 in).

The lip's thickness is 0.63 cm (.25 in). The lip has twenty-four 0.32 cm (0.125 in) diameter holes spaced evenly around it so that a clamp can be fastened to the lip. Placing the membrane between the lip and clamp secures the membrane so that the area from 10.79 cm (4.25 in) from the center of the membrane to the outer edge of the membrane for all 360 degrees of the circle is rigidly fixed. Twenty-four screws and nuts were used to attach the clamp. This didn't make the drum and membrane airtight, but it was made tight enough to hold enough nitrogen so that an air regulator could maintain a constant pressure.

A tank of nitrogen gas was used to provide the gas needed to pressurize the drum and membrane. A low-pressure gas regulator was attached to the nitrogen tank to supply the needed pressure to the drum and membrane. The regulator used was a Matheson ® Gas Products regulator model number 8-2. It is rated to receive pressures up to 20.7 MPa (3000 psi) and deliver pressures up to 20.7 KPa (3 psi). The tank offered enough nitrogen for the experiment, and the regulator supplied the proper amount of pressure to the membrane. Varying pressures caused varying displacements in the shape of the membrane, but applying an electric field to the piezoelectric membrane would also cause membrane displacements.

To apply an electric field, a voltage source was used. This was accomplished using d-Space. A program written by Christian Taranti of NPS controlled the voltages delivered to the experiment (0 to 8.5 volts). Since the response of hundreds of volts applied to the membrane was desired, a high gain amplifier was used. The amplifier, a Trek HV power supply amplifier, model 50/750, with a gain of one hundred, was used to increase the voltage applied to the membrane. To connect these pieces of equipment to

the membrane, two strips of copper tape were applied, one on each side, to the "stem" of the membrane. Leads were soldered onto the copper tape, and wires were used to connect the voltage source to the amplifier to the soldered leads of the copper tape. With the copper tape adhesive attached to both sides of the membrane, a positive and negative lead could be attached to the membrane. In this experiment, either the positive or the negative lead was attached to the side of the membrane facing away from the inside of the drum, and then the other lead was attached to the side of the membrane facing toward the inside of the drum. This will be important later for the discussion about the reaction of the membrane to the applied electric field. So, when an electric field was applied to the membrane, further displacements occurred. To measure these displacements, a laser measurement system was used.

A laser made by Matsushita Electric Works, Ltd. was used in this experiment. This laser is class II (685 nm wavelength) with a beam projector and receiver in one unit. The model used was an ANR12151, which has a measurable range of ± 50 mm. The output of the laser measurement system ranges from -5 Volts to $+5$ Volts. So, a 1 mV reading would theoretically equate to a 10-micrometer displacement. To operate this laser, a Power Designs Inc. transistorized power supply, model number 2015R, was used. It provides a voltage range of 0-20 Volts DC at 0-1.5 Amps. For this laser, the power supply was set at 15 Volts DC at 0.3 Amps. For a stationary target, like this one, this laser will produce the best resolution (20-micrometers) when the lowest speed selector switch setting (10 Hz) is used. Therefore, the 10 Hz setting was used for this experiment. To measure the displacements, the drum and membrane were fastened to a table so that the membrane was perpendicular to the table. The laser was attached to a structure that

placed the projector of the laser facing at the center of the membrane. So, deflections of the center of the membrane could be observed. See Figure 2 for more detail.

To display the displacement information, a Hewlett Packard 500 MHz oscilloscope, model number 54610B, was connected to the laser measurement system. A voltage signal from the laser could be seen on the screen of the oscilloscope when the laser was measuring displacements. The average voltage of the laser signal (256 setting on the Average selector) was used as the reading for general observation purposes. The d-Space system was used to collect the data from the laser measurement device. The same program that set the application voltage was also used to collect the displacement data. Two minutes were allowed to pass to let the membrane settle, and then measurements were taken for intervals of one minute. Approximately 60,000 measurements were taken per minute. These 60,000 measurements were averaged to create a super-measurement. When three super-measurements had been taken that were within a defined (arbitrary) tolerance range ($\sqrt{((\Sigma v^2)/n) - ((\Sigma v)/n)^2}$ $n =$ number of measurements, $v =$ measured voltage from laser) they were averaged and reported. This tolerance range approximated a steady state value. If one of these super-measurements did not fall within this tolerance range, the oldest one was disregarded, and a new super-measurement was taken until three super-measurements fell within the tolerance range. The three super-measurements were then averaged for a final reading.

Better results may have been found by using more sophisticated equipment that could be set and read more accurately. A laser that has a more fine resolution could be used, or sensors better able to detect micrometer deflections, like eddy current sensors, could be used. A more accurate low-pressure gas regulator or an airtight drum and

membrane apparatus could also be used. Of note, some errors may have been introduced when a 2.54 cm (1 in) diameter circle of VHT brand high-temperature white auto paint (SP-101) was placed on the center of the membrane facing the laser measurement system. This was done because without it, the membrane face, silver in color and very reflective, would not scatter the laser beam enough so that the laser receiver could sense any return from the membrane surface. White reflects light well, and the paint helped scatter the light. This paint was applied at the point of laser beam contact with the membrane so that the laser receiver could sense a return. Therefore, the results of a similar experiment could be more accurate if less is done to the membrane physically and more sophisticated equipment is used.

When taking experimental data, the readings provided by the laser measurement system did not appear to be linear and were therefore not reliable. So, before any measurements were recorded, the laser was calibrated in the lab, and, using this calibration data, a MATLAB m-file, also written by Christian Taranti, was used to convert laser voltage readings into distances.

For each of ten pressure settings (0.1 psi, 0.2 psi, etc.) the laser measurement device was used to measure the deflection of the membrane under pressure loads alone. This was done so that the analytical model could be compared to the experimental results for pressure loading only. This is displayed in the next chapter. To begin the study of the membrane's piezoelectric response to an applied voltage, the pressure inside the drum and membrane apparatus was set using the low-pressure regulator and nitrogen gas tank. Starting at 690 Pa (0.1 psi) and increasing by increments of 1380 Pa (0.2 psi), the pressure was increased to 4830 Pa (0.7 psi). At each pressure, voltage was applied to the

membrane. The voltages ranged from 0-850 Volts, applied at increments of 50 Volts. The actual voltages delivered, however, were 0, 50, 99.5, 148.9, 198.4, 247.9, 297.2, 346.7, 396.1, 445.6, 495.1, 544.4, 594.0, 643.3, 692.9, 742.3, 791.6, 841.1 volts due to line losses. Further data manipulation was conducted in an Excel spreadsheet to calculate the distance the membrane moved from a reference of zero applied voltage at a given pressure with increasing applied voltages.

Several errors, besides that introduced by the white paint, was introduced into the measurements. The laser measurement device has a $\pm 0.8\%$ error, and lighting conditions, laser resolution, inaccurate pressure settings, temperature (gas expansion or contraction), line losses, or noise (vibration) could have contributed to differences in readings. The following section will examine the results of the experiment and analyze the data.

B. INFLATABLE STRUCTURE EXPERIMENTAL RESULTS

This section will discuss the results of the experiment mentioned in the previous section. As mentioned previously, the laser measurement system is not the most accurate sensor that could be used to measure the displacement of the PVDF membrane. However, for every pressure used in the experiment, a general displacement trend was observed for both polarity settings. The membrane's displacement increased or decreased (slightly) by increasing the applied voltage. In other words, the membrane's center got closer to or further away from the laser measurement system when voltage was

applied to it. The data recorded and the graphs constructed from this data can be viewed in Appendix C.

As mentioned earlier, the membrane is coated on both sides by a thin metal layer. The positive electrode is indicated by a plus sign written on it (provided by Measurement Specialties, Inc.). The negative voltage lead was applied to this positive electrode. Voltage was applied creating an electric field with a negative polarity in the direction of the positive electrode (side of membrane facing the laser measurement system) and a positive polarity in the direction of the negative electrode (side of membrane facing the inside of the drum). The displacement of the membrane due to this electric field was in the direction of the laser measurement system. The positive and negative voltage leads were also reversed in position, but the response of the membrane to this configuration resulted only in displacement at 0.1 psig. At this pressure, the force pushing on the membrane was not so great as to hinder the movement of the membrane due to the piezoelectric effect. All other pressures tested did not allow such movement, perhaps due to an increased tension in the membrane that could not be overcome by piezoelectric induced movements. The results will be shown later.

Not initially being given the poling direction (defined as the direction from negative voltage lead to the positive voltage lead in the poling process) of the membrane by Measurement Specialties, Inc., it was derived from the information obtained through experimentation and other information provided by Measurement Specialties, Inc. A voltage applied to a piezoelectric ceramic material that is opposite in polarity to the poling direction results in a compression of the membrane in its thickness ("3" direction) and expansion of the membrane in its length and width directions ("1" and "2"

directions). This movement appears to be what occurred in this experiment when the negative lead of the voltage source was attached to the positive electrode. The internal pressure of the drum pushed the membrane out further when higher and higher voltages were applied. This occurred because the membrane had increasing amounts of slack (less taught) in the length and width directions. So, the membrane was capable of being pushed out more by the internal pressure. If the poling direction were in the direction of the applied voltage polarity, the thickness of the membrane would increase, contracting the length and width of the membrane. This would make it more taught and less capable of being pushed out by the internal pressure of the drum. In fact, the membrane would not be pushed out toward the laser measurement system in this set-up but would in fact either remain in its position or retreat from the laser measurement system. This appears to be what occurred when the positive lead of the voltage source was attached to the positive electrode. However, after receiving poling information from Measurement Specialties, Inc., the poling direction of the membrane was derived.

The poling direction of the film, in the thickness “3” direction, is in the negative electrode direction (away from the laser measurement device). This was determined using the following information. For piezofilms, the d constant (“ratio of strain developed along a specific axis to the value of electric field applied parallel to a given axis” (Shields, p. 13 – 14)) is negative in the “3” direction. This is just the opposite of the d constant of a piezoceramic. A positive “applied voltage produces a negative strain (i.e., the film gets thinner)” (Measurement Specialties, Inc., p. 3). The positive lead was placed on the side of the membrane that the poling direction pointed toward (the side facing away from the laser measurement device), and the film got thinner. The positive

electrode plus sign seems to have no correlation to the poling direction, unless it indicates the opposite of the poling direction. Knowing why the membrane behaved the way that it did, it is now appropriate to examine the amplitudes of the displacements.

Table 1 shows the displacement of the membrane at each internal pressure due to the piezoelectric effect induced by an applied voltage of 850 volts.

Internal Pressure of Drum (psi)	Total Displacement (micrometers)
0.1	169.786
0.3	92.03
0.5	183.6914
0.7	151.3092

Table 1. Displacement of Membrane due to Piezoelectric Effect (850 volts) and Pressure

These values are based on data collected and recorded by d-Space for each of the four pressure settings. They represent the displacement due to the application of 850 volts.

The expected results are a larger displacement of the membrane for larger applied voltages. This was observed and can be seen in Figures 4, 5, 6, and 7.




Figure 4. Deflection of Membrane due to Piezoelectric effect (0.1 psi) – Negative
Lead Attached to Positive Sign Side




Figure 5. Deflection of Membrane due to Piezoelectric effect (0.3 psi) – Negative
Lead Attached to Positive Sign Side




Figure 6. Deflection of Membrane due to Piezoelectric effect (0.5 psi) – Negative Lead Attached to Positive Sign Side




Figure 7. Deflection of Membrane due to Piezoelectric effect (0.7 psi) – Negative Lead Attached to Positive Sign Side

The displacement of the membrane at each pressure setting shows a general increase in the laser measurement system direction for each pressure setting. All of the graphs show a displacement in the same direction. For the measurements collected with the positive voltage lead on the positive electrode (plus sign side), the results showed that the membrane did not move in either direction, except for 0.1 psig, for reasons mentioned earlier. Figures 8, 9, 10, and 11 show this.




Figure 8. Deflection of Membrane due to Piezoelectric effect (0.1 psi) – Positive Lead
Attached to Positive Sign Side

Deflection of Membrane due to Piezoelectric Effect (0.3 psi) - Positive Lead Attached to Positive Sign Side




Figure 9. Deflection of Membrane due to Piezoelectric effect (0.3 psi) – Positive Lead Attached to Positive Sign Side

Deflection of Membrane due to Piezoelectric Effect (0.5 psi) - Positive Lead Attached to Positive Sign Side




Figure 10. Deflection of Membrane due to Piezoelectric effect (0.5 psi) – Positive Lead Attached to Positive Sign Side




Figure 11. Deflection of Membrane due to Piezoelectric effect (0.7 psi) – Positive Lead
Attached to Positive Sign Side

The resolution of the laser measurement device is only 20 micrometers, so the measurements for Figures 9, 10, and 11 show that the displacement was inside or very near this resolution. With this in mind, the membrane did not move for these pressure settings when the positive voltage lead was placed on the positive electrode of the membrane. With better measurement devices, however, better displacement readings could be obtained and then displacements could accurately be predicted for given pressure settings. With this knowledge, an actuation system could be developed to take advantage of these displacements.

An alternate method obtain values of displacement under this set of applied loads is through modeling the piezoelectric film as a thin shell. By using MSC/PATRAN and MSC/NASTRAN, or similar analytical modeling programs, this membrane can be

modeled and evaluated. Once the model responds like the experimental set-up to pressure and voltage, evaluation of the piezoelectric film in space application situations can be performed. The next chapter describes the efforts in accurate modeling of the piezoelectric film as a thin shell undergoing large displacements and large rotations using the nonlinear incremental finite element options of MSC/NASTRAN software.

THIS PAGE INTENTIONALLY LEFT BLANK

IV. ANALYTICAL MODEL SET-UP AND RESULTS

The analytical model used in this research was created using MSC/PATRAN and MSC/NASTRAN software. The software was used to create the geometric model, and combinations of pressure and voltage that were observed in the experiment were applied to the model. This chapter describes the modeling aspects of the thin piezoelectric film.

MSC/PATRAN and MSC/NASTRAN are capable of modeling piezoelectric materials by using a thermal analogy. The piezo strain constants of the material are converted into coefficients of thermal expansion. This is done using the following equation: $\alpha_{eq} = d / t_{piezo}$ (d = piezo strain constant, t = thickness). The coefficient of thermal expansion (α_{eq}) can then be prescribed to the experimental model as a material property in the analysis. The values of the voltage applied corresponds to the temperature that is to be used in the MSC/NASTRAN model (in this model, degrees fahrenheit). The values of the thermal coefficients of expansion are presented in Appendix D. There is a value for the “1” direction and the “2” direction. However, in MSC/PATRAN, as a first approximation of the study, the average of the two coefficients of thermal expansion was used in an isotropic setting. This approximation, as seen later, introduces a small percentage of error in the response of the film to applied loads.

MSC/PATRAN is a graphical user interface package used to model structural and thermal problems. It generates an interface to run MSC/NASTRAN analysis. The structural and thermal aspects were modeled using MSC/PATRAN. The model from MSC/PATRAN was then used to create an input file, (.bdf or .dat) for MSC/NASTRAN. MSC/NASTRAN, a multi-disciplinary finite element analysis tool, is used in computing

the response in the form of displacements, rotations, stresses, etc., based on input geometry, boundary conditions, and loads.

The finite element method offers virtually unlimited problem generality by permitting the use of elements of various regular shapes. These elements can be combined to approximate any irregular boundary. In similar fashion, loads and constraints of any type can be applied (Miller, p. 3).

The piezoelectric fim (approximate thickness of 0.002 in) modeled as a thin-shell undergoes large displacements and large rotations (also note that E is of the order of 500,000 psi). For the given pressure loadings and the temperature loadings, the displacements of the film are several thousand times the thickness. This behavior requires the use of a nonlinear approach as displacements and rotations are large (linear strain-displacement approximations are violated) and as such MSC/NASTRAN has the capability to analyze such problems. The input deck generated by MSC/NASTRAN is changed (or edited) to incorporate the analysis parameters for computing the response of the thin shell to the applied loadings. Before any solutions could be obtained, though, inputs into the MSC/PATRAN model had to be made.

The MSC/PATRAN model was constructed using 216 finite elements. This was accomplished by placing 36 mesh seeds about the perimeter of of an 8.5 in membrane. This size was selected for the analytical model corresponding to the diameter of the membrane that is not rigidly clamped by the lip and drum of the experiment. Figure 12 shows the finite element model developed in MSC/NASTRAN.




Figure 12. Finite Element Model Produced in MSC/PATRAN

Another assumption made was the modulus of elasticity of the membrane.

Measurement Specialties, Inc. gives a range of the modulus of elasticity of PVDF at a 52 micrometer thickness from 2 – 4 Gpa (290,000 psi to 580,000 psi). A modulus of elasticity of 537,500 psi was used in the analytical model.

Once the .dat file was generated, it was manipulated to solve a non-linear problem for multiple pressure and temperature combinations. The code solved for displacements due to each pressure setting and one temperature. So, the .dat file was changed for each temperature and run in MSC/NASTRAN. The MSC/NASTRAN analysis provided .fo6 files that included the displacements of the first nine elements of the finite element model of the membrane. These displacement vectors were compiled and placed in a word processor file (these values are in inches). The displacement vectors and the .dat file can be seen in Appendix D.

Figure 13 presents the results of the maximum displacement of the center as the pressure is increased. As can be seen, the maximum displacement at 0.1 psig is about a thousand times the thickness of the membrane. As mentioned earlier, the observed values have 'rounding off' errors in getting the measured displacements. The MSC/NASTRAN results agree well with the finite element results published by JPL. They also agree well with measured deflections of the membrane under solely pressure loads. Of note, the reference starting point for all three curves in the graph in Figure 13 is the membrane displacement at 0.1 psig as calculated by the MSC/NASTRAN code developed here at NPS. This was done to show the relative displacements of the three measurement attempts from a common reference.




Figure 13. Displacements of Membrane with only Internal Pressure Applied

The results of the analytical model when temperatures were applied, matched nicely with the experimental results. When different temperatures were put into the code,

the resulting displacements followed the same trends observed in the experiment. Graphs of these results can be seen in Appendix D. Two examples, Figures 14 and 15 follow.




Figure 14. Analytical Model Results of Displacement of Membrane Exposed to .1 psig and Positive Temperatures.




Figure 15. Analytical Model Results of Displacement of Membrane Exposed to .1 psig and Negative Temperatures.

Decreasing a negative temperature caused a decrease in the displacement of the membrane. An increase in temperature resulted in increases in displacement. In the experiment, an increase in voltage with the negative lead of the voltage source attached to the positive electrode of the membrane increased the displacement of the membrane. An increase in voltage with the positive lead of the voltage source attached to the positive electrode of the membrane did not change the displacement of the membrane. The latter experimental configuration corresponds to the decreasing temperature configuration for the analytical model. The model shows a negative displacement due to decreasing temperature, but the experiment showed that the membrane was not capable of moving in that direction with internal pressures higher than 0.1 psig, most likely due to increased tension in the membrane due to the higher pressure loads. The analytical model does make intuitive sense, because if the temperature of the membrane were reduced, it would not expand, but it would contract. This would correspond to a piezoelectric material becoming thicker in the “3” direction and shorter in the “1” and “2” directions. The increasing temperature configuration in the analytical model corresponds to the experimental configuration of the negative lead of the voltage source attached to the positive electrode of the membrane. An increasing temperature would expand the membrane, and this corresponds to a membrane becoming thinner in the “3” direction and longer in the “1” and “2” directions. Of note, if a positive temperature is applied to the membrane before a pressure load is, the rigidly bounded membrane will buckle. NASTRAN is then incapable of proceeding further. A pressure load needs to be applied first, giving stiffness to the membrane, allowing the temperature loads to be applied without buckling the membrane.

In the experiment, as has been mentioned before, there are a few things that may have contributed to inaccuracies in the results of the experiment. Also, there may be inaccuracies in the results obtained by the model. Inaccuracies may have been introduced because the average of the coefficients of thermal expansion may not be an accurate way to implement the temperature analogy, or the modulus of elasticity may not be accurate for the membrane used in this experiment.

A milestone in this research was establishing a nonlinear MSC/NASTRAN model that uses pressure and temperature loadings to calculate the displacements of an extremely thin membrane. Future work could be done to introduce membranes of larger size into the space environment. Also, the model can be used to determine the response of larger inflated structures to analogous voltage inputs. Optimum placement of piezoelectric films on large inflatable structures for desired responses could also be accomplished. This work can be used as a starting place for such future work.

THIS PAGE INTENTIONALLY LEFT BLANK

V. CONCLUSIONS

Inflatable thin film space-borne structures are revolutionary in terms of mass, stowed volume, and capability. The Navy and the Department of Defense should investigate using these materials in future space-borne communications platforms. It has been shown that a lot of work has been done and is going to be done with this technology, and its attributes far outweigh any drawbacks (which are very few in number). The enhanced communications capabilities that large antennas made of these materials offer are phenomenal. However, this technology is not quite ready for use in this application.

Surface errors in the shape of large parabolic antennas caused by the space environment can degrade the performance of these antennas, therefore some form of shape control has to be implemented to maintain the ideal shape of these antennas. Using piezoelectric material is one solution to this problem. The research done for this thesis shows that piezoelectric thin films are plausible materials to be used to help maintain shape. Not only can they be used to change an inflatable structure's shape, they can also be used to sense when the ideal shape has been changed. Through experimentation, it has been shown that the shape change of a piezoelectric thin film under pressure is repeatable. By developing a nonlinear MSC/NASTRAN model of a thin film under pressure and thermal loads, it has been shown that computer models can be constructed that will help predict and optimize piezoelectric thin film usage.

This thesis continued with the work of Dr. Salama, Dr. Kuo, B. Wada, and M. Thomas. Their work was very similar, but the research reported here placed a membrane

of a different size under a higher pressure. Displacements were observed and calculated that, without the influence of voltage or temperature, were very similar in nature to those reported by Salama, Kuo, Wada, and Thomas. They also reported that the out-of-plane displacement of their membrane due to an applied voltage of 300 volts was about .0012 in. The experiment conducted for this research produced an out-of-plane displacement of about .006 in for an applied voltage of 300 volts. The analytical model produced an out-of-plane displacement of about .0020 in for an applied voltage of 300 volts. However, the out-of-plane displacements for this model were obtained with a different configuration than those obtained by the experiment. They are both approximately, however, in the same range as the results obtained by Salama, Kuo, Wada, and Thomas. They stated that this out-of-plane displacement should scale directly with the diameter of the membrane (their diameter was 10 in). The experimental results for this thesis do not support this statement $((8.5 \text{ in} / 10 \text{ in}) * .0012 \text{ in} = .0010 \text{ in}, \text{ not } .006 \text{ in})$. Again, the laser measurement device is not the best instrument that could be used in this experiment, but there could also be error in the results of Salama, Kuo, Wada, and Thomas.

Future work that can be done at NPS includes using better measurement devices to measure surface deflections of the membrane and developing analytical models of large inflatable structures and predicting their behavior and performance. Also, conducting temperature experiments on the membrane and drum to see if this has an effect on deflection and testing for the modes and natural frequencies of the membrane could be pursued. There is a lot of work left to be done on this technology, and the Navy and the Department of Defense should keep a watchful eye on the progress of the developments of this technology.

The Navy and the Department of Defense could benefit greatly from using inflatable antennas on communications satellites. They are light and compact when stowed, both of which help reduced the size of the launch vehicle and subsequently the cost of the program. The enhanced capabilities that larger antennas bring to warfighters, especially disadvantaged users with limited power and antenna size are incredible. With information superiority becoming more and more important, this capability is becoming more and more valuable. Planning ahead now and investing in this technology will ensure its growth and rapid maturity. Using this technology is just one piece of the puzzle that will bring true information superiority to all Department of Defense personnel. Inflatable space structures will be a part of the future, and hopefully, they will be a part of the Navy's and the Department of Defense's future as well.

THIS PAGE INTENTIONALLY LEFT BLANK

APPENDIX A. EQUATIONS USED FOR ANTENNA OPERATIONAL ANALYSIS

Equation	Source
Wavelength = $C / \text{frequency}$	Larson and Wertz, p. 242
antenna gain = $\pi^2 D_r^2 \eta / \lambda^2$	Larson and Wertz, p. 521
degraded antenna gain = $\eta(\pi D_r / \lambda)^2 e^{[-(4\pi\epsilon/\lambda)^2]}$	Cassapakis, Love, and Palisoc, p. 456
EIRP = $P_t + G_t - L_{\text{line}}$ (in dB)	Baldwin, p. 36
FSPL = $32.4 + 20\log(\text{Freq(MHz)}) + 20\log(D(\text{km}))$ (in dB)	Baldwin, p. 36
$N_o = 10\log(K) + 10\log(T_e)$ (in dB)	Tomasi, p. 748
$C = \text{EIRP} - \text{FSPL} + G_r - L_{\text{line}}$ (in dB)	Baldwin, p. 36
$C/N_o = C - N_o$ (in dB)	Tomasi, p. 749
$N = \text{bandwidth} + N_o$ (in dB)	Tomasi, p. 748
$C/N = C - N$ (in dB)	decibel mathematics
Beamwidth = $21 \cdot 10^9 / \text{frequency} \cdot D_r$ (degrees)	Douglas, p. 74
$D (\text{km}) = \sin(\lambda_{FO})(6378) / \sin(\text{nadir ang} + \text{beamwidth})$	derived
$L_F (\text{km}) = K_L(\lambda_{FO} - \lambda_{FI})$	Larson and Wertz, p. 163
$W_F(\text{km}) = R_E \sin^{-1}(D \sin(\text{beamwidth}) / R_E)$	Larson and Wertz, p. 164
$F_A (\text{km}) = (\pi / 4) L_F W_F$	Larson and Wertz, p. 165
$C/N_o (\text{overall}) = (C/N_o)_u (C/N_o)_d / [(C/N_o)_u + (C/N_o)_d]$	Tomasi, p. 758

Throughput (bps) = $\text{alog}[(C/N_o - E_b/N_o - \text{required margin})/10]$ Baldwin, p. 36

$C/N \text{ (overall)} = (C/N)_u(C/N)_d / [(C/N)_u + (C/N)_d]$ Tomasi, p. 758

Shannon's Capacity Limit = $\text{bandwidth} * \log_2(1 + C/N)$ Baldwin, p. 16

Practical throughput = $\text{bandwidth} * \log_2(M) / (1 + R)$ M-ary PSKs (no coding)

Key:

C = speed of light ($3 * 10^8$ m/s)

λ = wavelength

η = antenna efficiency

D_r = diameter of receiver

ε = root mean square surface error

EIRP = Effective Isotropic Radiated Power

P_t = transmitter power

G_t = transmitter gain

FSPL = Free Space Path Loss

D = slant range

G_r = receiver gain

L_{line} = line losses

k = Boltzmann's Constant ($1.38 * 10^{-23}$ J/deg Kelvin)

T_e = equivalent temperature

C = received power

N_o = noise density

$K_L = 111.319543$

L_F = footprint length

W_F = footprint width

F_A = footprint area

R = roll-off factor


M = number of modulation symbols (e.g., $M = 2$ for BPSK)

APPENDIX B. ANTENNA ANALYSIS SPREADSHEETS AND GRAPHS

The material contained in this appendix displays the analysis performed on the link budgets of different ground and space-borne antennas. Graphs display the throughputs possible for different scenarios using the different antennas available. Six different scenarios are displayed.

DSCS III SLEP parameter
= .7112 m

Disadvantaged User to Disadvantaged User Throughput Based on Antenna Gain and Bandwidth




- ◆ Throughput Based on C/No and Eb/No
- Shannon's Limit
- ▲ Throughput Constrained by Bandwidth, Modulation, and Roll-Off Factor

DSCS III antenna diameter
= .7112 m
DSCS III SLEP parameter
DSCS III S mm
0

DSCS III antenna diameter
= .7112 m
DSCS III SLEP parameter
DSCS III S mm
0


Shore to Disadvantaged User Throughputs Based on Antenna Gain and Bandwidth



- ◆ Throughput Based on C/No and Eb/No
- Shannon's Limit
- ▲ Throughput Constrained by Bandwidth, Modulation, and Roll-Off Factor


65

DSCS III SLEP Theoretical Throughputs based on a 85 MHz Bandwidth (Ship to Ship)



- ◆ Theoretical Throughput Based on C/N₀ and E_b/N₀
- Shannon's Limit
- ▲ Throughput Constrained by Bandwidth, Modulation, and Roll-Off Factor

Close-Up of DSCS III SLEP Theoretical Throughputs based on a 85 MHz Bandwidth (Ship to Ship)



- ◆ Theoretical Throughput Based on C/N₀ and Eb/No
- Shannon's Limit
- △ Throughput Constrained by Bandwidth, Modulation, and Roll-Off Factor


Thesis Antenna Spreadsheet
ship to ship link

[illegible]


Intelsat 702 antenna diameter
= .7112 m
Intelsat 702 parameter
73.26007 mm

[illegible][illegible]

Intelsat 702 Theoretical Throughputs based on a 36MHz Bandwidth (Ship to Ship)




Close-up of Intelsat 702 Theoretical Throughputs Based on a 36 MHz Bandwidth (Ship to Ship)



- ◆ Theoretical Throughput Based on C/No and Eb/No
- Shannon's Limit
- ▲ Throughput Constrained by Bandwidth, Modulation, and Roll-Off Factor


DSCS III S mm
0

DSCS III SLEP Theoretical Throughputs Based on a 85 MHz Bandwidth (Shore to Ship)



- ◆ Theoretical Throughput Based on C/No and Eb/No
- Shannon's Limit
- ▲ Throughput Constrained by Bandwidth, Modulation, and Roll-Off Factor


Close-Up of DSCS III SLEP Theoretical Throughputs based on a 85 MHz Bandwidth (Shore to Ship)




- ◆ Theoretical Throughput Based on C/No and Eb/No
- Shannon's Limit
- ▲ Throughput Constrained by Bandwidth, Modulation, and Roll-Off Factor

uplink																	Inlensat 702 antenna diameter = .7112 m	
altitude of satellite (km)	35786	35786	35786	35786	35786	35786	35786	35786	35786	35786	35786	35786	35786	35786	35786	35786	Inlensat 702 parameter	
diameter of ground antenna (m)	18.29	18.29	18.29	18.29	18.29	18.29	18.29	18.29	18.29	18.29	18.29	18.29	18.29	18.29	18.29	18.29		
transmitted power (dBW)	40	40	40	40	40	40	40	40	40	40	40	40	40	40	40	40		
frequency (Hz)	6.320E+09	6.320E+09	6.320E+09	6.320E+09	6.320E+09	6.320E+09	6.320E+09	6.320E+09	6.320E+09	6.320E+09	6.320E+09	6.320E+09	6.320E+09	6.320E+09	6.320E+09	6.320E+09	73.26007 mm	
wavelength (m)	4.75E-02	4.75E-02	4.75E-02	4.75E-02	4.75E-02	4.75E-02	4.75E-02	4.75E-02	4.75E-02	4.75E-02	4.75E-02	4.75E-02	4.75E-02	4.75E-02	4.75E-02	4.75E-02		
gain of ground antenna (dB)	59.062815	59.062815	59.062815	59.062815	59.062815	59.062815	59.062815	59.062815	59.062815	59.062815	59.062815	59.062815	59.062815	59.062815	59.062815	59.062815		
EIRP of ground antenna (dBW)	97.00	97.00	97.00	97.00	97.00	97.00	97.00	97.00	97.00	97.00	97.00	97.00	97.00	97.00	97.00	97.00		
diameter of satellite antenna (m)	0.711	0.711	5	10	15	20	25	30	35	40	40	40	40	40	40	40		
satellite antenna efficiency	0.55	0.55	0.55	0.55	0.55	0.55	0.55	0.55	0.55	0.55	0.55	0.55	0.55	0.55	0.55	0.55		
gain of spacecraft antenna (dB)	30.855933	47.797941	53.818541	57.340366	59.839141	61.777341	63.360966	64.699302	65.859741	66.999302	68.100E-03	69.100E-03	70.100E-03	71.100E-03	72.100E-03	73.100E-03		
rms surface error (m)	0.00E+00	1.00E-03	1.00E-03	1.00E-03	1.00E-03	1.00E-03	1.00E-03	1.00E-03	1.00E-03	1.00E-03	1.00E-03	1.00E-03	1.00E-03	1.00E-03	1.00E-03	1.00E-03		
bandwidth (actual) gain of spacecraft (dB)	30.855933	47.663342	53.683942	57.205769	59.704542	61.642742	63.226367	64.565305	65.725142	66.885305	68.045305	69.205305	70.365305	71.525305	72.685305	73.845305		
free space path loss (dB)	3.60E+07	3.60E+07	3.60E+07	3.60E+07	3.60E+07	3.60E+07	3.60E+07	3.60E+07	3.60E+07	3.60E+07	3.60E+07	3.60E+07	3.60E+07	3.60E+07	3.60E+07	3.60E+07		
atmospheric attenuation (dB)	1.99E+02	1.99E+02	1.99E+02	1.99E+02	1.99E+02	1.99E+02	1.99E+02	1.99E+02	1.99E+02	1.99E+02	1.99E+02	1.99E+02	1.99E+02	1.99E+02	1.99E+02	1.99E+02		
line losses of receiver (dB)	3	3	3	3	3	3	3	3	3	3	3	3	3	3	3	3		
equivalent temperature (K) on satellite	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2		
No (dB)	3653	3653	3653	3653	3653	3653	3653	3653	3653	3653	3653	3653	3653	3653	3653	3653		
received power (C) (dBW)	-192.74201	-192.74201	-192.74201	-192.74201	-192.74201	-192.74201	-192.74201	-192.74201	-192.74201	-192.74201	-192.74201	-192.74201	-192.74201	-192.74201	-192.74201	-192.74201		
required margin (dB)	-76.839902	-59.829130	-53.805628	-50.283266	-47.784304	-45.846016	-44.262344	-42.923380	-41.763523	-40.603666	-39.443808	-38.283950	-37.124092	-35.964234	-34.804376	-33.644518		
C/N0 (dB)	3	3	3	3	3	3	3	3	3	3	3	3	3	3	3	3		
N (dB)	1.159E+02	1.329E+02	1.389E+02	1.425E+02	1.450E+02	1.469E+02	1.485E+02	1.498E+02	1.510E+02	1.519E+02	1.527E+02	1.535E+02	1.543E+02	1.551E+02	1.559E+02	1.567E+02		
C/N (dB)	-1.172E+02	-1.172E+02	-1.172E+02	-1.172E+02	-1.172E+02	-1.172E+02	-1.172E+02	-1.172E+02	-1.172E+02	-1.172E+02	-1.172E+02	-1.172E+02	-1.172E+02	-1.172E+02	-1.172E+02	-1.172E+02		
C/N (dB)	4.034E+01	5.735E+01	6.337E+01	6.690E+01	6.939E+01	7.133E+01	7.292E+01	7.426E+01	7.542E+01	7.650E+01	7.750E+01	7.845E+01	7.930E+01	8.010E+01	8.085E+01	8.155E+01		
spacecraft-centered nadir angle (deg)	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		
beamwidth (deg)	4.673E+00	6.646E+01	3.323E+01	2.215E+01	1.661E+01	1.329E+01	1.108E+01	9.494E+02	8.307E+02	7.426E+02	6.750E+02	6.175E+02	5.700E+02	5.290E+02	4.930E+02	4.610E+02		
lambda (f0) (deg)	27.916613	3.73294692	1.86489081	1.24306561	0.93224606	0.74577951	0.62147436	0.53268787	0.4660938	0.4090938	0.3590938	0.3140938	0.2730938	0.2350938	0.2000938	0.1670938		
lambda (f0) (deg)	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		
slant range (km)	36650.0579	35801.9401	35789.98	35787.7685	35786.9947	35786.6366	35786.4421	35786.3247	35786.2487	35786.1822	35786.1222	35786.0672	35786.0162	35785.9682	35785.9242	35785.8832		
L1 (km)	3107.6646	415.549945	207.598792	138.377495	103.777428	83.0198347	69.1822416	59.2985714	51.9859698	45.9859698	40.9859698	36.4859698	32.3859698	28.6859698	25.2859698	22.1859698		
W (km)	3.108E+03	4.155E+02	2.076E+02	1.384E+02	1.038E+02	8.302E+01	6.918E+01	5.930E+01	5.188E+01	4.593E+01	4.043E+01	3.533E+01	3.053E+01	2.603E+01	2.183E+01	1.793E+01		
a (km^2)	7.585E+06	1.356E+05	3.385E+04	1.504E+04	8.458E+03	5.413E+03	3.759E+03	2.762E+03	2.114E+03	1.614E+03	1.164E+03	8.14E+02	5.64E+02	3.94E+02	2.74E+02	1.84E+02		

Intelsat 702 Theoretical Throughputs Based on a 36 MHz Bandwidth (Shore to Ship)



Close-Up of Intelsat 702 Theoretical Throughputs Based on a 36 MHz Bandwidth (Shore to Ship)



- ◆ Theoretical Throughput Based on C/No and Eb/No
- Shannon's Limit
- ▲ Throughput Constrained by Bandwidth, Modulation, and Roll-Off Factor

THIS PAGE INTENTIONALLY LEFT BLANK


APPENDIX C. LABORATORY EXPERIMENTAL RESULTS AND GRAPHS OF THESE RESULTS

This appendix contains all of the raw data collected during the experiment conducted on the PVDF membrane. Data processing results are also displayed to the right of the raw data. The graphs that follow are based on this processed data.


(positive values mean the membrane is bulging outward toward the laser)

0	micrometers	0	micrometers	0	micrometers	0	micrometers	0	micrometers
50	40.2301	26.2694	3.7946	8.4648	12.0161	6.373	16.1511	2.6757	-13.914
100	26.4153	46.6023	3.3081	8.9513	11.9188	15.9565	45.0944	12.0647	-21.0658
150	13.4269	46.6023	0.3405	15.9565	21.7454	43.1487	45.2809	29.6259	-11.822
200	-14.9357	45.1917	4.0865	132.88	11.5783	45.2809		40.3761	-24.131
250	-14.5465	49.2289	-0.5838	123.3488				29.6259	-27.8773
300	-36.6837	60.2216	6.2757	132.88				51.2232	-29.3855
350	-46.5122	69.9493	0.0486	132.1992				43.0514	-17.125
400	-60.2337	71.3598	0.2432	137.9858				64.7937	-0.973
450	-70.9876	88.8202	3.3568	169.786				71.3598	7.8811
500	-84.5156	97.5743	5.4					73.8889	8.4648
550	-87.6787	102.3889	8.4648					85.7075	-3.6974
600	-90.2579	121.8899	12.0161					99.4223	6.373
650	-90.1605	123.3488	8.9513					102.4862	16.1511
700	-78.5301	132.88	11.9188					127.8713	25.5884
750	-63.0073	132.1992	15.9565					137.6454	45.0944
800	-65.343	137.9858	21.7454					154.2002	43.1487
850	-53.5675	169.786	11.5783						45.2809
0	micrometers	0	micrometers	0	micrometers	0	micrometers	0	micrometers
50	11.5783	11.3837	-6.3731	8.4648	12.0161	6.373	16.1511	2.6757	-13.914
100	13.9133	18.0969	0.6324	8.9513	11.9188	15.9565	45.0944	12.0647	-21.0658
150	12.5026	81.7194	7.7351	15.9565	21.7454	43.1487	45.2809	29.6259	-11.822
200	8.4648	96.5043	10.508	132.88	11.5783	45.2809		40.3761	-24.131
250	11.0918	116.2003	18.9726	123.3488				29.6259	-27.8773
300	16.9781	146.7385	20.0428	132.88				51.2232	-29.3855
350	16.443	157.5817	20.8211	137.9858				43.0514	-17.125
400	25.1992	156.901	16.0538	169.786				64.7937	-0.973
450	26.9018	160.9367	25.3451					71.3598	7.8811
500	22.7183	165.1669	29.5286					73.8889	8.4648
550	26.3667	164.4862	23.0588					85.7075	-3.6974
600	600	170.3208	20.8211					99.4223	6.373
650	30.161	171.4877	12.989					102.4862	16.1511
700	30.842	172.4116	19.459					127.8713	25.5884
750	30.7933	170.8557	3.4541					137.6454	45.0944
800	30.9879	177.5167	6.9081					154.2002	43.1487
850	30.3069	183.6914	12.4539						45.2809


Deflection of Membrane due to Piezoelectric Effect (0.1 psi) - Positive Lead Attached to Positive Sign Side




Deflection of Membrane due to Piezoelectric Effect (0.3 psi) - Positive Lead Attached to Positive Sign Side




Deflection of Membrane due to Piezoelectric Effect (0.5 psi) - Positive Lead Attached to Positive Sign Side




Deflection of Membrane due to Piezoelectric Effect (0.7 psi) - Positive Lead Attached Positive Sign Side




Deflection of Membrane due to Piezoelectric Effect (0.1 psi) - Negative Lead Attached to Positive Sign Side




Deflection of Membrane due to Piezoelectric Effect (0.3 psi) - Negative Lead Attached to Positive Sign Side



Deflection of Membrane due to Piezoelectric Effect (0.5 psi) - Negative Lead Attached Positive Sign Side



Deflection of Membrane due to Piezoelectric Effect (0.7 psi) - Negative Lead Attached Positive Sign Side



APPENDIX D. ANALYTICAL MODEL INFORMATION


This appendix contains four main parts. They all pertain to the analytical model produced using NASTRAN and PATRAN. The four parts are:

1. inputs necessary for the thermal analogy to model the piezoelectric effect
2. graphical displays of computer model results
3. the NASTRAN input file used to model the membrane
4. compilation of the displacement vectors of the first nine elements
(starting at the center of the membrane and proceeding radially outward
for six elements, then starting over at the center at element eight)
for all combinations of pressures and temperatures


This data is completely computer generated.

Voltage	d 31 (in/in)/(V/in)	E 3 (V/in)	alpha 31 ((in/in)/(deg F)	T (deg F)	d 32 (in/in)/(V/in)	E 3 (V/in)	alpha 32 ((in/in)/(deg F)	T (deg F)
0.00E+00	9.06E-10	0	4.42E-07	0.00E+00	1.182E-10	0	5.76923E-08	0.00E+00
5.00E+01	9.06E-10	24404.53	4.42E-07	5.00E+01	1.182E-10	24404.53	5.76923E-08	5.00E+01
1.00E+02	9.06E-10	48809.06	4.42E-07	1.00E+02	1.182E-10	48809.06	5.76923E-08	1.00E+02
1.50E+02	9.06E-10	73213.59	4.42E-07	1.50E+02	1.182E-10	73213.59	5.76923E-08	1.50E+02
2.00E+02	9.06E-10	97618.12	4.42E-07	2.00E+02	1.182E-10	97618.12	5.76923E-08	2.00E+02
2.50E+02	9.06E-10	122022.6	4.42E-07	2.50E+02	1.182E-10	122022.6	5.76923E-08	2.50E+02
3.00E+02	9.06E-10	146427.2	4.42E-07	3.00E+02	1.182E-10	146427.2	5.76923E-08	3.00E+02
3.50E+02	9.06E-10	170831.7	4.42E-07	3.50E+02	1.182E-10	170831.7	5.76923E-08	3.50E+02
4.00E+02	9.06E-10	195236.2	4.42E-07	4.00E+02	1.182E-10	195236.2	5.76923E-08	4.00E+02
4.50E+02	9.06E-10	219640.8	4.42E-07	4.50E+02	1.182E-10	219640.8	5.76923E-08	4.50E+02
5.00E+02	9.06E-10	244045.3	4.42E-07	5.00E+02	1.182E-10	244045.3	5.76923E-08	5.00E+02
5.50E+02	9.06E-10	268449.8	4.42E-07	5.50E+02	1.182E-10	268449.8	5.76923E-08	5.50E+02
6.00E+02	9.06E-10	292854.4	4.42E-07	6.00E+02	1.182E-10	292854.4	5.76923E-08	6.00E+02
6.50E+02	9.06E-10	317258.9	4.42E-07	6.50E+02	1.182E-10	317258.9	5.76923E-08	6.50E+02
7.00E+02	9.06E-10	341663.4	4.42E-07	7.00E+02	1.182E-10	341663.4	5.76923E-08	7.00E+02
7.50E+02	9.06E-10	366067.9	4.42E-07	7.50E+02	1.182E-10	366067.9	5.76923E-08	7.50E+02
8.00E+02	9.06E-10	390472.5	4.42E-07	8.00E+02	1.182E-10	390472.5	5.76923E-08	8.00E+02
8.50E+02	9.06E-10	414877	4.42E-07	8.50E+02	1.182E-10	414877	5.76923E-08	8.50E+02


Displacement of Membrane at .1 psig NASTRAN




Displacement of Membrane at .2 psig NASTRAN




Displacement of Membrane at .3 psig NASTRAN




Displacement of Membrane at .4 psig NASTRAN




Displacement of Membrane at .5 psig NASTRAN




Displacement of Membrane at .6 psig NASTRAN




Displacement of Membrane at .7 psig NASTRAN




Displacement of Membranes at .8 psig NASTRAN




Displacement of Membrane at .9 psig NASTRAN




Displacement of Membrane at 1 psig NASTRAN




Displacement of Membrane at .1 psig NASTRAN




Displacement of Membrane at .2 psig NASTRAN




Displacement of Membrane at .3 psig NASTRAN




Displacement of Membrane at .4 psig NASTRAN




Displacement of Membrane at .5 psig NASTRAN




Displacement of Membrane at .6 psig NASTRAN




Displacement of Membrane at .7 psig NASTRAN




Displacement of Membrane at .8 psig NASTRAN



Displacement of Membrane at .8 psig NASTRAN



Displacement of Membrane at 1 psig NASTRAN



```

knoxville.dat
$ NASTRAN input file created by the MSC MSC/NASTRAN input file
$ translator ( MSC/PATRAN Version 8.5 ) on July 06, 2000 at
$ 12:55:22.
$ASSIGN OUTPUT2 = 'dinky.op2', UNIT = 12
$ Direct Text Input for File Management Section
$ Linear Static Analysis, Database
SOL 100
TIME 600
$ Direct Text Input for Executive Control
CENF
SEALL = ALL
SUPER = ALL
TITLE = LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE
ECHO = SORT
MAXLINES = 999999999
SET 45 = 1,2,3,4,5,6,7,8,9
DISP = 45
TEMP(INIT) = 1
$
$ Direct Text Input for Global Case Control Data
SPC = 2
SUBCASE 4
LOAD = 33
LABEL = Small Mechanical Load
NLPARM = 108
$$$$
$$$$Subcase 5
$$$$TEMP(LOAD) = 55
$$$$NLPARM=108
$$$$LABEL = THERMAL LOADS AT 200
$stress=all
SUBCASE 10
LOAD = 100
TEMP(LOAD) = 55
LABEL = ONE TENTH, -50 DEG
NLPARM = 108
SUBCASE 20
LOAD = 200
TEMP(LOAD) = 55
LABEL = TWO TENTHS, -50 DEG
NLPARM = 108
SUBCASE 30
LOAD = 300
TEMP(LOAD) = 55
LABEL = THREE TENTHS, -50 DEG
NLPARM = 108
SUBCASE 40
LOAD = 400
TEMP(LOAD) = 55
LABEL = FOUR TENTHS, -50 DEG
NLPARM = 108
SUBCASE 50
LOAD = 500
TEMP(LOAD) = 55
LABEL = FIVE TENTHS, -50 DEG
NLPARM = 108
SUBCASE 60
LOAD = 600
TEMP(LOAD) = 55
LABEL = SIX TENTHS, -50 DEG
NLPARM = 108
SUBCASE 70
LOAD = 700
TEMP(LOAD) = 55
LABEL = SEVEN TENTHS, -50 DEG
NLPARM = 108
SUBCASE 80
LOAD = 800
TEMP(LOAD) = 55
LABEL = EIGHT TENTHS, -50 DEG
NLPARM = 108
SUBCASE 90
LOAD = 900
TEMP(LOAD) = 55
LABEL = NINE TENTHS, -50 DEG
NLPARM = 108
SUBCASE 101
LOAD = 1000
TEMP(LOAD) = 55
LABEL = ONE, -50 DEG
NLPARM = 108
$ TEMPERATURE(BOTH) = 2
$ DISPLACEMENT(SORT1,REAL)=ALL
$ SPCFORCES(SORT1,REAL)=ALL
$ STRESS(SORT1,REAL,VONMISES,BILIN)=ALL
$ Direct Text Input for this Subcase
BEGIN BULK
PARAM POST -1
PARAM PATVER 3.
$PARAM AUTOSPC YES
$PARAM INREL 0
$PARAM ALTRED NO
PARAM COUPMASS -1
PARAM,K6ROT,1000.
PARAM WTMASS 1.
PARAM,NOCOMPS,-1
PARAM PRTHMAXIM YES
$ Direct Text Input for Bulk Data
$ Elements and Element Properties for region : membrane

```

\$12345678901234567890123456789012345678901234567890
 \$23456789012345678901234567890123456789012345678901234567890
 PSHELL 1 1 .002047 1 1.25

\$\$PSHELL,1,1,0.002047,1,1.0
 \$ Pset: "membrane" will be imported as: "pshell.1"

CTRIA3	1	1	1	2	8
CQUAD4	2	1	2	3	9
CQUAD4	3	1	3	4	10
CQUAD4	4	1	4	5	11
CQUAD4	5	1	5	6	12
CQUAD4	6	1	6	7	13
CTRIA3	7	1	1	8	14
CQUAD4	8	1	8	9	15
CQUAD4	9	1	9	10	16
CQUAD4	10	1	10	11	17
CQUAD4	11	1	11	12	18
CQUAD4	12	1	12	13	19
CTRIA3	13	1	1	14	20
CQUAD4	14	1	14	15	21
CQUAD4	15	1	15	16	22
CQUAD4	16	1	16	17	23
CQUAD4	17	1	17	18	24
CQUAD4	18	1	18	19	25
CTRIA3	19	1	1	20	26
CQUAD4	20	1	20	21	27
CQUAD4	21	1	21	22	28
CQUAD4	22	1	22	23	29
CQUAD4	23	1	23	24	30
CQUAD4	24	1	24	25	31
CTRIA3	25	1	1	26	32
CQUAD4	26	1	26	27	33
CQUAD4	27	1	27	28	34
CQUAD4	28	1	28	29	35
CQUAD4	29	1	29	30	36
CQUAD4	30	1	30	31	37
CTRIA3	31	1	1	32	38
CQUAD4	32	1	32	33	39
CQUAD4	33	1	33	34	40
CQUAD4	34	1	34	35	41
CQUAD4	35	1	35	36	42
CQUAD4	36	1	36	37	43
CTRIA3	37	1	1	38	44
CQUAD4	38	1	38	39	45
CQUAD4	39	1	39	40	46
CQUAD4	40	1	40	41	47
CQUAD4	41	1	41	42	48
CQUAD4	42	1	42	43	49
CTRIA3	43	1	1	44	50
CQUAD4	44	1	44	45	51
CQUAD4	45	1	45	46	52
CQUAD4	46	1	46	47	53
CQUAD4	47	1	47	48	54
CQUAD4	48	1	48	49	55
CTRIA3	49	1	1	50	56
CQUAD4	50	1	50	51	57
CQUAD4	51	1	51	52	58
CQUAD4	52	1	52	53	59
CQUAD4	53	1	53	54	60
CQUAD4	54	1	54	55	61
CTRIA3	55	1	1	56	62
CQUAD4	56	1	56	57	63
CQUAD4	57	1	57	58	64
CQUAD4	58	1	58	59	65
CQUAD4	59	1	59	60	66
CQUAD4	60	1	60	61	67
CTRIA3	61	1	1	62	68
CQUAD4	62	1	62	63	69
CQUAD4	63	1	63	64	70
CQUAD4	64	1	64	65	71
CQUAD4	65	1	65	66	72
CQUAD4	66	1	66	67	73
CTRIA3	67	1	1	68	74
CQUAD4	68	1	68	69	75
CQUAD4	69	1	69	70	76
CQUAD4	70	1	70	71	77
CQUAD4	71	1	71	72	78
CQUAD4	72	1	72	73	79
CTRIA3	73	1	1	74	80
CQUAD4	74	1	74	75	81
CQUAD4	75	1	75	76	82
CQUAD4	76	1	76	77	83
CQUAD4	77	1	77	78	84
CQUAD4	78	1	78	79	85
CTRIA3	79	1	1	80	86
CQUAD4	80	1	80	81	87
CQUAD4	81	1	81	82	88
CQUAD4	82	1	82	83	89
CQUAD4	83	1	83	84	90
CQUAD4	84	1	84	85	91
CTRIA3	85	1	1	86	92
CQUAD4	86	1	86	87	93
CQUAD4	87	1	87	88	94
CQUAD4	88	1	88	89	95
CQUAD4	89	1	89	90	96
CQUAD4	90	1	90	91	97
CTRIA3	91	1	1	92	98
CQUAD4	92	1	92	93	99
CQUAD4	93	1	93	94	100
CQUAD4	94	1	94	95	101

CQUAD4	95	1	95	96	102	101
CQUAD4	96	1	96	97	103	102
CTRIA3	97	1	1	98	104	
CQUAD4	98	1	98	99	105	104
CQUAD4	99	1	99	100	106	105
CQUAD4	100	1	100	101	107	106
CQUAD4	101	1	101	102	108	107
CQUAD4	102	1	102	103	109	108
CTRIA3	103	1	1	104	110	
CQUAD4	104	1	104	105	111	110
CQUAD4	105	1	105	106	112	111
CQUAD4	106	1	106	107	113	112
CQUAD4	107	1	107	108	114	113
CQUAD4	108	1	108	109	115	114
CTRIA3	109	1	1	110	116	
CQUAD4	110	1	110	111	117	116
CQUAD4	111	1	111	112	118	117
CQUAD4	112	1	112	113	119	118
CQUAD4	113	1	113	114	120	119
CQUAD4	114	1	114	115	121	120
CTRIA3	115	1	1	116	122	
CQUAD4	116	1	116	117	123	122
CQUAD4	117	1	117	118	124	123
CQUAD4	118	1	118	119	125	124
CQUAD4	119	1	119	120	126	125
CQUAD4	120	1	120	121	127	126
CTRIA3	121	1	1	122	128	
CQUAD4	122	1	122	123	129	128
CQUAD4	123	1	123	124	130	129
CQUAD4	124	1	124	125	131	130
CQUAD4	125	1	125	126	132	131
CQUAD4	126	1	126	127	133	132
CTRIA3	127	1	1	128	134	
CQUAD4	128	1	128	129	135	134
CQUAD4	129	1	129	130	136	135
CQUAD4	130	1	130	131	137	136
CQUAD4	131	1	131	132	138	137
CQUAD4	132	1	132	133	139	138
CTRIA3	133	1	1	134	140	
CQUAD4	134	1	134	135	141	140
CQUAD4	135	1	135	136	142	141
CQUAD4	136	1	136	137	143	142
CQUAD4	137	1	137	138	144	143
CQUAD4	138	1	138	139	145	144
CTRIA3	139	1	1	140	146	
CQUAD4	140	1	140	141	147	146
CQUAD4	141	1	141	142	148	147
CQUAD4	142	1	142	143	149	148
CQUAD4	143	1	143	144	150	149
CQUAD4	144	1	144	145	151	150
CTRIA3	145	1	1	146	152	
CQUAD4	146	1	146	147	153	152
CQUAD4	147	1	147	148	154	153
CQUAD4	148	1	148	149	155	154
CQUAD4	149	1	149	150	156	155
CQUAD4	150	1	150	151	157	156
CTRIA3	151	1	1	152	158	
CQUAD4	152	1	152	153	159	158
CQUAD4	153	1	153	154	160	159
CQUAD4	154	1	154	155	161	160
CQUAD4	155	1	155	156	162	161
CQUAD4	156	1	156	157	163	162
CTRIA3	157	1	1	158	164	
CQUAD4	158	1	158	159	165	164
CQUAD4	159	1	159	160	166	165
CQUAD4	160	1	160	161	167	166
CQUAD4	161	1	161	162	168	167
CQUAD4	162	1	162	163	169	168
CTRIA3	163	1	1	164	170	
CQUAD4	164	1	164	165	171	170
CQUAD4	165	1	165	166	172	171
CQUAD4	166	1	166	167	173	172
CQUAD4	167	1	167	168	174	173
CQUAD4	168	1	168	169	175	174
CTRIA3	169	1	1	170	176	
CQUAD4	170	1	170	171	177	176
CQUAD4	171	1	171	172	178	177
CQUAD4	172	1	172	173	179	178
CQUAD4	173	1	173	174	180	179
CQUAD4	174	1	174	175	181	180
CTRIA3	175	1	1	176	182	
CQUAD4	176	1	176	177	183	182
CQUAD4	177	1	177	178	184	183
CQUAD4	178	1	178	179	185	184
CQUAD4	179	1	179	180	186	185
CQUAD4	180	1	180	181	187	186
CTRIA3	181	1	1	182	188	
CQUAD4	182	1	182	183	189	188
CQUAD4	183	1	183	184	190	189
CQUAD4	184	1	184	185	191	190
CQUAD4	185	1	185	186	192	191
CQUAD4	186	1	186	187	193	192
CTRIA3	187	1	1	188	194	
CQUAD4	188	1	188	189	195	194
CQUAD4	189	1	189	190	196	195
CQUAD4	190	1	190	191	197	196
CQUAD4	191	1	191	192	198	197
CQUAD4	192	1	192	193	199	198
CTRIA3	193	1	1	194	200	

CQUAD4	194	1	194	195	201	200
CQUAD4	195	1	195	196	202	201
CQUAD4	196	1	196	197	203	202
CQUAD4	197	1	197	198	204	203
CQUAD4	198	1	198	199	205	204
CTRIA3	199	1	1	200	206	
CQUAD4	200	1	200	201	207	206
CQUAD4	201	1	201	202	208	207
CQUAD4	202	1	202	203	209	208
CQUAD4	203	1	203	204	210	209
CQUAD4	204	1	204	205	211	210
CTRIA3	205	1	1	206	212	
CQUAD4	206	1	206	207	213	212
CQUAD4	207	1	207	208	214	213
CQUAD4	208	1	208	209	215	214
CQUAD4	209	1	209	210	216	215
CQUAD4	210	1	210	211	217	216
CTRIA3	211	1	1	212	218	
CQUAD4	212	1	212	213	219	218
CQUAD4	213	1	213	214	220	219
CQUAD4	214	1	214	215	221	220
CQUAD4	215	1	215	216	222	221
CQUAD4	216	1	216	217	223	222

\$ Referenced Material Records

\$ Material Record : kynar

\$ Description of Material : Date: 01-Jun-00 Time: 15:44:27

SMAT1 1 580156. .387 .064307 2.498-7 0.

MAT1 1 537500. .387 .064307 2.498-7 0.

\$ Nodes of the Entire Model

GRID	1	0.	0.	0.
GRID	2	.708333	0.	0.
GRID	3	1.41666	0.	0.
GRID	4	2.125	0.	0.
GRID	5	2.83333	0.	0.
GRID	6	3.54166	0.	0.
GRID	7	4.25	0.	0.
GRID	8	.697572	.123001	0.
GRID	9	1.39514	.246002	0.
GRID	10	2.09271	.369003	0.
GRID	11	2.79028	.492005	0.
GRID	12	3.48786	.615007	0.
GRID	13	4.18543	.738009	0.
GRID	14	.665615	.242264	0.
GRID	15	1.33123	.484529	0.
GRID	16	1.99684	.726795	0.
GRID	17	2.66246	.969061	0.
GRID	18	3.32807	1.21132	0.
GRID	19	3.99369	1.45359	0.
GRID	20	.613434	.354167	0.
GRID	21	1.22686	.708335	0.
GRID	22	1.84030	1.06250	0.
GRID	23	2.45373	1.41667	0.
GRID	24	3.06716	1.77084	0.
GRID	25	3.68060	2.12501	0.
GRID	26	.542615	.455308	0.
GRID	27	1.08522	.910617	0.
GRID	28	1.62784	1.36592	0.
GRID	29	2.17045	1.82123	0.
GRID	30	2.71306	2.27654	0.
GRID	31	3.25567	2.73186	0.
GRID	32	.455307	.542615	0.
GRID	33	.910614	1.08523	0.
GRID	34	1.36592	1.62784	0.
GRID	35	1.82122	2.17046	0.
GRID	36	2.27652	2.71308	0.
GRID	37	2.73183	3.25570	0.
GRID	38	.354166	.613435	0.
GRID	39	.708331	1.22687	0.
GRID	40	1.06249	1.84030	0.
GRID	41	1.41665	2.45374	0.
GRID	42	1.77081	3.06718	0.
GRID	43	2.12497	3.68062	0.
GRID	44	.242263	.665616	0.
GRID	45	.484526	1.33123	0.
GRID	46	.726786	1.99684	0.
GRID	47	.969045	2.66246	0.
GRID	48	1.21130	3.32808	0.
GRID	49	1.45356	3.99370	0.
GRID	50	.123	.697572	0.
GRID	51	.245998	1.39514	0.
GRID	52	.368994	2.09271	0.
GRID	53	.491989	2.79029	0.
GRID	54	.614982	3.48786	0.
GRID	55	.737973	4.18543	0.
GRID	56	-1.092-6	.708333	0.
GRID	57	-4.041-6	1.41666	0.
GRID	58	-8.846-6	2.125	0.
GRID	59	-1.604-5	2.83333	0.
GRID	60	-2.469-5	3.54166	0.
GRID	61	-3.599-5	4.25	0.
GRID	62	-.123002	.697572	0.
GRID	63	-.246006	1.39514	0.
GRID	64	-.369012	2.09271	0.
GRID	65	-.492021	2.79028	0.
GRID	66	-.615032	3.48785	0.
GRID	67	-.738045	4.18542	0.
GRID	68	-.242265	.665615	0.
GRID	69	-.484533	1.33123	0.
GRID	70	-.726803	1.99684	0.

GRID	71	- .969076 2.66245 0.
GRID	72	-1.21135 3.32806 0.
GRID	73	-1.45362 3.99367 0.
GRID	74	- .354166 .613434 0.
GRID	75	- .708338 1.22686 0.
GRID	76	-1.06251 1.84029 0.
GRID	77	-1.41668 2.45372 0.
GRID	78	-1.77086 3.06715 0.
GRID	79	-2.12504 3.68058 0.
GRID	80	- .455309 .542614 0.
GRID	81	- .91062 1.08522 0.
GRID	82	-1.36593 1.62783 0.
GRID	83	-1.82124 2.17044 0.
GRID	84	-2.27656 2.71305 0.
GRID	85	-2.73188 3.25565 0.
GRID	86	- .542616 .455307 0.
GRID	87	-1.08523 .910611 0.
GRID	88	-1.62785 1.36591 0.
GRID	89	-2.17047 1.82121 0.
GRID	90	-2.71309 2.27651 0.
GRID	91	-3.25572 2.73180 0.
GRID	92	- .613435 .354165 0.
GRID	93	-1.22687 .708328 0.
GRID	94	-1.84031 1.06248 0.
GRID	95	-2.45375 1.41664 0.
GRID	96	-3.06719 1.77079 0.
GRID	97	-3.68063 2.12494 0.
GRID	98	- .665616 .242263 0.
GRID	99	-1.33123 .484522 0.
GRID	100	-1.99685 .726778 0.
GRID	101	-2.66247 .96903 0.
GRID	102	-3.32809 1.21128 0.
GRID	103	-3.99371 1.45352 0.
GRID	104	- .697572 .122999 0.
GRID	105	-1.39514 .245994 0.
GRID	106	-2.09271 .368986 0.
GRID	107	-2.79029 .491973 0.
GRID	108	-3.48786 .614958 0.
GRID	109	-4.18544 .737938 0.
GRID	110	- .708333-2.184-6 0.
GRID	111	-1.41666-8.082-6 0.
GRID	112	-2.125 -1.769-5 0.
GRID	113	-2.83333-3.208-5 0.
GRID	114	-3.54166-4.938-5 0.
GRID	115	-4.25 -7.199-5 0.
GRID	116	- .697572-.123003 0.
GRID	117	-1.39514-.24601 0.
GRID	118	-2.09271-.369022 0.
GRID	119	-2.79028-.492036 0.
GRID	120	-3.48785-.615055 0.
GRID	121	-4.18542-.738079 0.
GRID	122	- .665615-.242266 0.
GRID	123	-1.33122-.484537 0.
GRID	124	-1.99684-.726812 0.
GRID	125	-2.66245-.969091 0.
GRID	126	-3.32805-1.21137 0.
GRID	127	-3.99366-1.45366 0.
GRID	128	- .613433-.354169 0.
GRID	129	-1.22686-.708341 0.
GRID	130	-1.84029-1.06251 0.
GRID	131	-2.45372-1.41669 0.
GRID	132	-3.06714-1.77088 0.
GRID	133	-3.68056-2.12507 0.
GRID	134	- .542613-.45531 0.
GRID	135	-1.08522-.910623 0.
GRID	136	-1.62783-1.36594 0.
GRID	137	-2.17043-1.82126 0.
GRID	138	-2.71303-2.27658 0.
GRID	139	-3.25563-2.73191 0.
GRID	140	- .455306-.542617 0.
GRID	141	- .910608-1.08523 0.
GRID	142	-1.36590-1.62785 0.
GRID	143	-1.8212 -2.17048 0.
GRID	144	-2.27649-2.71311 0.
GRID	145	-2.73177-3.25574 0.
GRID	146	- .354164-.613436 0.
GRID	147	- .708324-1.22687 0.
GRID	148	-1.06247-1.84031 0.
GRID	149	-1.41662-2.45376 0.
GRID	150	-1.77077-3.06720 0.
GRID	151	-2.12491-3.68065 0.
GRID	152	- .242262-.665617 0.
GRID	153	- .484518-1.33123 0.
GRID	154	- .726769-1.99685 0.
GRID	155	- .969015-2.66247 0.
GRID	156	-1.21125-3.32810 0.
GRID	157	-1.45349-3.99372 0.
GRID	158	-1.22998-.697573 0.
GRID	159	- .24599 -1.39514 0.
GRID	160	- .368977-2.09272 0.
GRID	161	- .491958-2.79029 0.
GRID	162	- .614933-3.48787 0.
GRID	163	- .737903-4.18545 0.
GRID	164	3.010-6-.708333 0.
GRID	165	1.185-5-1.41666 0.
GRID	166	2.654-5-2.125 0.
GRID	167	4.706-5-2.83333 0.
GRID	168	7.341-5-3.54166 0.
GRID	169	1.056-4-4.25 0.

```

GRID 170 .123004-.697572 0.
GRID 171 .246014-1.39514 0.
GRID 172 .369029-2.09271 0.
GRID 173 .492052-2.79028 0.
GRID 174 .615079-3.48784 0.
GRID 175 .738114-4.18541 0.
GRID 176 .242267-.665614 0.
GRID 177 .484541-1.33122 0.
GRID 178 .72682 -1.99683 0.
GRID 179 .969105-2.66244 0.
GRID 180 1.21139-3.32805 0.
GRID 181 1.45369-3.99365 0.
GRID 182 .354169-.613433 0.
GRID 183 .708345-1.22686 0.
GRID 184 1.06252-1.84028 0.
GRID 185 1.41671-2.45371 0.
GRID 186 1.77090-3.06713 0.
GRID 187 2.12510-3.68054 0.
GRID 188 .455311-.542613 0.
GRID 189 .910626-1.08522 0.
GRID 190 1.36594-1.62782 0.
GRID 191 1.82127-2.17042 0.
GRID 192 2.27660-2.71302 0.
GRID 193 2.73194-3.25561 0.
GRID 194 .542617-.455305 0.
GRID 195 1.08523-.910605 0.
GRID 196 1.62786-1.3659 0.
GRID 197 2.17049-1.82118 0.
GRID 198 2.71313-2.27647 0.
GRID 199 3.25576-2.73175 0.
GRID 200 .613437-.354163 0.
GRID 201 1.22687-.708321 0.
GRID 202 1.84032-1.06247 0.
GRID 203 2.45376-1.41661 0.
GRID 204 3.06721-1.77075 0.
GRID 205 3.68067-2.12488 0.
GRID 206 .665617-.242261 0.
GRID 207 1.33123-.484515 0.
GRID 208 1.99685-.726761 0.
GRID 209 2.66248-.969002 0.
GRID 210 3.32810-1.21123 0.
GRID 211 3.99373-1.45346 0.
GRID 212 .697573-.122997 0.
GRID 213 1.39514-.245986 0.
GRID 214 2.09272-.368968 0.
GRID 215 2.79029-.491943 0.
GRID 216 3.48787-.61491 0.
GRID 217 4.18545-.73787 0.
GRID 218 .708333 1.238-7 0.
GRID 219 1.41666 2.476-7 0.
GRID 220 2.125 3.715-7 0.
GRID 221 2.83333 4.953-7 0.
GRID 222 3.54166 6.192-7 0.
GRID 223 4.25 7.430-7 0.

```

\$ Loads for Load Case : loadcase1

```

$SPCADD 2 1
$234567890123456789012345678901234567890

```

```

LOAD 100 1. 1. 10
LOAD 33 1. 1. 11
LOAD 200 1. 1. 20
LOAD 300 1. 1. 30
LOAD 400 1. 1. 40
LOAD 500 1. 1. 50
LOAD 600 1. 1. 60
LOAD 700 1. 1. 70
LOAD 800 1. 1. 80
LOAD 900 1. 1. 90
LOAD 1000 1. 1. 101
PLOAD4 11 1 .10 THRU 216
PLOAD4 10 1 .1 THRU 216
PLOAD4 20 1 .2 THRU 216
PLOAD4 30 1 .3 THRU 216
PLOAD4 40 1 .4 THRU 216
PLOAD4 50 1 .5 THRU 216
PLOAD4 60 1 .6 THRU 216
PLOAD4 70 1 .7 THRU 216
PLOAD4 80 1 .8 THRU 216
PLOAD4 90 1 .9 THRU 216
PLOAD4 101 1 1.0 THRU 216

```

\$ Static Plate Element Temperatures of Load Set : temperature

```

TEMPD 1 0
TEMPD,55,-50.0

```

```

$+ A 2 THRU 216

```

\$ Displacement Constraints of Load Set : constraint

```

SPC1 2 123456 7 13 19 25 31 37 + B
+ B 43 49 55 61 67 73 79 85 + C
+ C 91 97 103 109 115 121 127 133 + D
+ D 139 145 151 157 163 169 175 181 + E
+ E 187 193 199 205 211 217 223

```

\$ Pressure Loads of Load Set : pressure.1

```

PARAM,LGDISP,1

```

```

NLPARM,108,20

```

```

$NLPARM,107,8,,ITER

```

\$ Referenced Coordinate Frames

```

ENDDATA

```

ONE TENTH, ZERO DEG
LOAD STEP = 2.00000E+00

nastran_final_results_negative_temps.txt

SUBCASE 10

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	2.341992E-03	7.401508E-08	2.133318E-01	4.767032E-06	-3.194503E-03	-5.698712E-07
2	G	3.587988E-03	7.349566E-03	2.514677E-01	-1.103176E-01	-1.476892E-02	5.080811E-03
3	G	4.534828E-03	8.846126E-03	2.499020E-01	-8.563810E-02	1.971927E-02	6.239635E-04
4	G	5.228249E-03	8.234358E-03	2.196153E-01	-6.538023E-02	7.205004E-02	-2.608204E-03
5	G	4.716984E-03	6.243060E-03	1.661580E-01	-4.700415E-02	6.834459E-02	-2.289620E-03
6	G	2.905966E-03	3.391708E-03	9.238727E-02	-5.754874E-02	1.687762E-01	-6.500938E-03
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	3.094946E-03	6.582240E-03	2.393183E-01	-8.740198E-02	-2.736874E-02	6.174818E-03
9	G	3.969544E-03	7.959296E-03	2.311131E-01	-6.769782E-02	2.627526E-02	3.668207E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE
AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 256

TWO TENTHS, ZERO DEG
LOAD STEP = 3.00000E+00

SUBCASE 20

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	3.699800E-03	1.900756E-07	2.688976E-01	1.839473E-05	1.517781E-02	-1.255206E-06
2	G	5.657619E-03	1.171388E-02	3.170216E-01	-1.449520E-01	-1.793619E-02	7.857751E-03
3	G	7.199376E-03	1.407835E-02	3.150148E-01	-1.108159E-01	2.398902E-02	1.075015E-03
4	G	8.308156E-03	1.309270E-02	2.767770E-01	-8.485006E-02	9.233310E-02	-4.319508E-03
5	G	7.475621E-03	9.907982E-03	2.091379E-01	-5.601881E-02	8.507415E-02	-3.609077E-03
6	G	4.664267E-03	5.411784E-03	1.167564E-01	-7.577603E-02	2.122634E-01	-1.049676E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	4.905153E-03	1.043558E-02	3.012488E-01	-1.115717E-01	-3.500446E-02	9.848427E-03
9	G	6.283277E-03	1.261670E-02	2.908130E-01	-8.601391E-02	3.350478E-02	5.465528E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE
AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 257

THREE TENTHS, ZERO DEG
LOAD STEP = 4.00000E+00

SUBCASE 30

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	4.827071E-03	3.296506E-07	3.079243E-01	3.776644E-05	3.347854E-02	-1.804291E-06
2	G	7.381059E-03	1.537338E-02	3.629159E-01	-1.692394E-01	-2.032832E-02	1.019281E-02
3	G	9.427924E-03	1.846821E-02	3.606077E-01	-1.285687E-01	2.704221E-02	1.458444E-03
4	G	1.088789E-02	1.716879E-02	3.168018E-01	-9.846851E-02	1.064855E-01	-5.772921E-03
5	G	9.785834E-03	1.298225E-02	2.392366E-01	-6.223028E-02	9.684050E-02	-4.719901E-03
6	G	6.145012E-03	7.111489E-03	1.338336E-01	-8.868869E-02	2.424940E-01	-1.388027E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	6.415361E-03	1.365929E-02	3.446157E-01	-1.283657E-01	-4.029152E-02	1.293319E-02
9	G	8.215570E-03	1.651759E-02	3.326161E-01	-9.873720E-02	3.847246E-02	7.060374E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE
AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 258

FOUR TENTHS, ZERO DEG
LOAD STEP = 5.00000E+00

SUBCASE 40

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	5.824279E-03	4.875732E-07	3.390261E-01	6.160066E-05	5.096036E-02	-2.113337E-06
2	G	8.910754E-03	1.863601E-02	3.993870E-01	-1.884515E-01	-2.228624E-02	1.228464E-02
3	G	1.141145E-02	2.238498E-02	3.968402E-01	-1.426764E-01	2.949344E-02	1.803628E-03
4	G	1.318708E-02	2.080704E-02	3.486135E-01	-1.092386E-01	1.176858E-01	-7.074701E-03
5	G	1.184594E-02	1.572718E-02	2.631682E-01	-6.716432E-02	1.062277E-01	-5.714348E-03
6	G	7.469765E-03	8.631983E-03	1.474169E-01	-9.904365E-02	2.663847E-01	-1.692065E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	7.756472E-03	1.653108E-02	3.790943E-01	-1.416347E-01	-4.442729E-02	1.568392E-02
9	G	9.934303E-03	1.999619E-02	3.658510E-01	-1.087726E-01	4.236004E-02	8.567687E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE
AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 259

FIVE TENTHS, ZERO DEG
LOAD STEP = 6.00000E+00

SUBCASE 50

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	6.733309E-03	6.604511E-07	3.653156E-01	8.914154E-05	6.754070E-02	-2.123406E-06
2	G	1.030995E-02	2.163025E-02	4.301342E-01	-2.045407E-01	-2.394332E-02	1.421139E-02
3	G	1.322947E-02	2.598237E-02	4.273852E-01	-1.545321E-01	3.156491E-02	2.124286E-03
4	G	1.529706E-02	2.415056E-02	3.754366E-01	-1.182674E-01	1.270934E-01	-8.271642E-03
5	G	1.373792E-02	1.825094E-02	2.833554E-01	-7.133682E-02	1.141674E-01	-6.630572E-03
6	G	8.689254E-03	1.003195E-02	1.588780E-01	-1.078429E-01	2.864297E-01	-1.973036E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	8.983096E-03	1.916613E-02	4.081779E-01	-1.527627E-01	-4.784866E-02	1.820671E-02
9	G	1.150918E-02	2.319106E-02	3.938858E-01	-1.171724E-01	4.559385E-02	1.002825E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE
AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 260

SIX TENTHS, ZERO DEG
LOAD STEP = 7.00000E+00

SUBCASE 60

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	7.576771E-03	8.463200E-07	3.883161E-01	1.198958E-04	8.326672E-02	-1.794408E-06
2	G	1.161256E-02	2.442559E-02	4.569698E-01	-2.184867E-01	-2.537364E-02	1.601396E-02
3	G	1.492490E-02	2.934340E-02	4.540426E-01	-1.648382E-01	3.336866E-02	2.427868E-03
4	G	1.726710E-02	2.727639E-02	3.988505E-01	-1.261049E-01	1.352782E-01	-9.389993E-03
5	G	1.550585E-02	2.061162E-02	3.009839E-01	-7.499430E-02	1.211151E-01	-7.488977E-03
6	G	9.830929E-03	1.134300E-02	1.688890E-01	-1.155808E-01	3.038500E-01	-2.237032E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.012471E-02	2.162636E-02	4.335753E-01	-1.624303E-01	-5.077100E-02	2.055860E-02
9	G	1.297765E-02	2.617656E-02	4.183674E-01	-1.244550E-01	4.838090E-02	1.146241E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 261
SEVEN TENTHS, ZERO DEG
LOAD STEP = 8.00000E+00 SUBCASE 70

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	8.368637E-03	1.043875E-06	4.089008E-01	1.534985E-04	9.821242E-02	-1.097446E-06
2	G	1.283945E-02	2.706503E-02	4.809326E-01	-2.308585E-01	-2.662448E-02	1.771732E-02
3	G	1.652423E-02	3.251937E-02	4.778447E-01	-1.740040E-01	3.497084E-02	2.718891E-03
4	G	1.912758E-02	3.023202E-02	4.197606E-01	-1.330689E-01	1.425671E-01	-1.044636E-02
5	G	1.717687E-02	2.284497E-02	3.167335E-01	-7.827581E-02	1.273323E-01	-8.302107E-03
6	G	1.091176E-02	1.258460E-02	1.778352E-01	-1.225415E-01	3.193446E-01	-2.487816E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.119955E-02	2.394984E-02	4.562658E-01	-1.710281E-01	-5.331921E-02	2.277482E-02
9	G	1.436278E-02	2.899843E-02	4.402396E-01	-1.309180E-01	5.083937E-02	1.288188E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 262
EIGHT TENTHS, ZERO DEG
LOAD STEP = 9.00000E+00 SUBCASE 80

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.118314E-03	1.252067E-06	4.276222E-01	1.896795E-04	1.124524E-01	-1.115805E-08
2	G	1.400462E-02	2.957748E-02	5.026800E-01	-2.420164E-01	-2.772826E-02	1.933831E-02
3	G	1.804524E-02	3.554473E-02	4.994448E-01	-1.822887E-01	3.641428E-02	3.000361E-03
4	G	2.089888E-02	3.304930E-02	4.387399E-01	-1.393600E-01	1.491668E-01	-1.145202E-02
5	G	1.876916E-02	2.497493E-02	3.310342E-01	-8.126815E-02	1.329847E-01	-9.078379E-03
6	G	1.194312E-02	1.376981E-02	1.859604E-01	-1.289042E-01	3.333558E-01	-2.727912E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.221985E-02	2.616216E-02	4.768688E-01	-1.788021E-01	-5.557397E-02	2.487925E-02
9	G	1.568006E-02	3.168732E-02	4.600995E-01	-1.367493E-01	5.304433E-02	1.429357E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 263
NINE TENTHS, ZERO DEG
LOAD STEP = 1.00000E+01 SUBCASE 90

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.832514E-03	1.470081E-06	4.448548E-01	2.282205E-04	1.260549E-01	1.480952E-06
2	G	1.511807E-02	3.198354E-02	5.226576E-01	-2.522050E-01	-2.870859E-02	2.088898E-02
3	G	1.950064E-02	3.844401E-02	5.192854E-01	-1.898682E-01	3.772863E-02	3.274368E-03
4	G	2.259555E-02	3.575092E-02	4.561765E-01	-1.451146E-01	1.552172E-01	-1.241510E-02
5	G	2.029565E-02	2.701854E-02	3.441771E-01	-8.402963E-02	1.381845E-01	-9.823789E-03
6	G	1.293314E-02	1.490792E-02	1.934295E-01	-1.347904E-01	3.461829E-01	-2.959114E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.319438E-02	2.828150E-02	4.958042E-01	-1.859184E-01	-5.759095E-02	2.688901E-02
9	G	1.694051E-02	3.426507E-02	4.783516E-01	-1.420764E-01	5.504677E-02	1.570176E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 264
ONE, ZERO DEG
LOAD STEP = 1.10000E+01 SUBCASE 101

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	1.051625E-02	1.697254E-06	4.608655E-01	2.689482E-04	1.390801E-01	3.391936E-06
2	G	1.618723E-02	3.429857E-02	5.411828E-01	-2.615984E-01	-2.958344E-02	2.237843E-02
3	G	2.089988E-02	4.123551E-02	5.376822E-01	-1.968684E-01	3.893548E-02	3.542423E-03
4	G	2.422840E-02	3.835374E-02	4.723471E-01	-1.504295E-01	1.608177E-01	-1.334169E-02
5	G	2.176594E-02	2.898466E-02	3.563698E-01	-8.660164E-02	1.430123E-01	-1.054280E-02
6	G	1.388785E-02	1.600586E-02	2.003604E-01	-1.402865E-01	3.580391E-01	-3.182759E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.412965E-02	3.032140E-02	5.133712E-01	-1.924952E-01	-5.941056E-02	2.881701E-02
9	G	1.815236E-02	3.674791E-02	4.952843E-01	-1.469900E-01	5.688317E-02	1.710918E-03

ONE TENTH, -50 DEG
LOAD STEP = 2.00000E+00 SUBCASE 10

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	2.340110E-03	7.428115E-08	2.128451E-01	4.820706E-06	-3.093266E-03	-5.687948E-07
2	G	3.573806E-03	7.377742E-03	2.511588E-01	-1.115135E-01	-1.483492E-02	5.071481E-03
3	G	4.521884E-03	8.881387E-03	2.496999E-01	-8.697136E-02	1.952435E-02	6.339154E-04
4	G	5.216466E-03	8.264905E-03	2.194424E-01	-6.612002E-02	7.222390E-02	-2.638099E-03
5	G	4.708288E-03	6.271722E-03	1.660596E-01	-4.742451E-02	6.795779E-02	-2.273157E-03
6	G	2.902673E-03	3.413449E-03	9.238085E-02	-5.830716E-02	1.688848E-01	-6.558518E-03
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	3.085376E-03	6.596376E-03	2.388850E-01	-8.812183E-02	-2.740703E-02	6.182708E-03
9	G	3.952518E-03	7.971100E-03	2.306560E-01	-6.821154E-02	2.621001E-02	3.656474E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 256
TWO TENTHS, -50 DEG
LOAD STEP = 3.00000E+00 SUBCASE 20

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	3.695489E-03	1.901606E-07	2.684774E-01	1.843426E-05	1.522711E-02	-1.252465E-06
2	G	5.646479E-03	1.172431E-02	3.166179E-01	-1.450697E-01	-1.782726E-02	7.848052E-03
3	G	7.180028E-03	1.409234E-02	3.146470E-01	-1.108860E-01	2.377016E-02	1.094783E-03
4	G	8.284997E-03	1.310903E-02	2.764712E-01	-8.492364E-02	9.239355E-02	-4.330716E-03
5	G	7.455591E-03	9.927552E-03	2.089401E-01	-5.601626E-02	8.470047E-02	-3.592703E-03
6	G	4.654681E-03	5.430381E-03	1.166949E-01	-7.620370E-02	2.122201E-01	-1.053437E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	4.893503E-03	1.044339E-02	3.008387E-01	-1.116107E-01	-3.509798E-02	9.864526E-03
9	G	6.264481E-03	1.262562E-02	2.904265E-01	-8.607171E-02	3.352496E-02	5.432384E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 257
THREE TENTHS, -50 DEG
LOAD STEP = 4.00000E+00 SUBCASE 30

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	4.822721E-03	3.299782E-07	3.075567E-01	3.783335E-05	3.353043E-02	-1.799412E-06
2	G	7.369811E-03	1.538384E-02	3.625630E-01	-1.693538E-01	-2.022869E-02	1.018174E-02
3	G	9.408536E-03	1.848219E-02	3.602862E-01	-1.286347E-01	2.684639E-02	1.478984E-03
4	G	1.086471E-02	1.718508E-02	3.165345E-01	-9.854170E-02	1.065437E-01	-5.785028E-03
5	G	9.765700E-03	1.300166E-02	2.390625E-01	-6.221803E-02	9.651127E-02	-4.703567E-03
6	G	6.135495E-03	7.130122E-03	1.337804E-01	-8.906911E-02	2.424554E-01	-1.391827E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	6.403677E-03	1.366700E-02	3.442564E-01	-1.284023E-01	-4.037400E-02	1.294937E-02
9	G	8.196723E-03	1.652636E-02	3.322772E-01	-9.879033E-02	3.849163E-02	7.025059E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 258
FOUR TENTHS, -50 DEG
LOAD STEP = 5.00000E+00 SUBCASE 40

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	5.819908E-03	4.878975E-07	3.386915E-01	6.168208E-05	5.101324E-02	-2.106644E-06
2	G	8.899365E-03	1.864665E-02	3.990668E-01	-1.885721E-01	-2.219472E-02	1.227260E-02
3	G	1.139207E-02	2.239911E-02	3.965490E-01	-1.427500E-01	2.931394E-02	1.824474E-03
4	G	1.316395E-02	2.082337E-02	3.483711E-01	-1.093134E-01	1.177421E-01	-7.087563E-03
5	G	1.182582E-02	1.574654E-02	2.630098E-01	-6.714895E-02	1.059271E-01	-5.698006E-03
6	G	7.460356E-03	8.650656E-03	1.473690E-01	-9.939503E-02	2.663496E-01	-1.695908E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	7.744778E-03	1.653871E-02	3.787669E-01	-1.416744E-01	-4.450060E-02	1.569982E-02
9	G	9.915403E-03	2.000480E-02	3.655417E-01	-1.088242E-01	4.237664E-02	8.532427E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 259
FIVE TENTHS, -50 DEG
LOAD STEP = 6.00000E+00 SUBCASE 50

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	6.728907E-03	6.608419E-07	3.650045E-01	8.924057E-05	6.759333E-02	-2.114550E-06
2	G	1.029848E-02	2.164088E-02	4.298367E-01	-2.046583E-01	-2.385704E-02	1.419874E-02
3	G	1.321006E-02	2.599648E-02	4.271145E-01	-1.546037E-01	3.139688E-02	2.145426E-03
4	G	1.527392E-02	2.416683E-02	3.752113E-01	-1.183401E-01	1.271475E-01	-8.284899E-03
5	G	1.371773E-02	1.827020E-02	2.832076E-01	-7.131873E-02	1.138874E-01	-6.614246E-03
6	G	8.679868E-03	1.005063E-02	1.588336E-01	-1.081717E-01	2.863965E-01	-1.976893E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	8.971375E-03	1.917369E-02	4.078732E-01	-1.528009E-01	-4.791618E-02	1.822251E-02
9	G	1.149023E-02	2.319956E-02	3.935978E-01	-1.172212E-01	4.560918E-02	9.992832E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 260
SIX TENTHS, -50 DEG
LOAD STEP = 7.00000E+00 SUBCASE 60

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	7.572337E-03	8.467820E-07	3.880230E-01	1.200103E-04	8.331862E-02	-1.783222E-06
2	G	1.160104E-02	2.443619E-02	4.566893E-01	-2.186005E-01	-2.529143E-02	1.600087E-02
3	G	1.490546E-02	2.935746E-02	4.537874E-01	-1.649071E-01	3.320949E-02	2.449239E-03
4	G	1.724393E-02	2.729259E-02	3.986380E-01	-1.261755E-01	1.353302E-01	-9.403517E-03
5	G	1.548560E-02	2.063078E-02	3.008443E-01	-7.497447E-02	1.208511E-01	-7.472665E-03
6	G	9.821549E-03	1.136167E-02	1.688472E-01	-1.158920E-01	3.038180E-01	-2.240897E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.011296E-02	2.163383E-02	4.332880E-01	-1.624668E-01	-5.083411E-02	2.057432E-02
9	G	1.295867E-02	2.618497E-02	4.180957E-01	-1.245012E-01	4.839526E-02	1.142697E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 261
SEVEN TENTHS, -50 DEG
LOAD STEP = 8.00000E+00 SUBCASE 70

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	8.364175E-03	1.044396E-06	4.086220E-01	1.536290E-04	9.826335E-02	-1.083836E-06
2	G	1.282787E-02	2.707558E-02	4.806656E-01	-2.309684E-01	-2.654559E-02	1.770389E-02
3	G	1.650475E-02	3.253337E-02	4.776019E-01	-1.740701E-01	3.481886E-02	2.740447E-03
4	G	1.910436E-02	3.024815E-02	4.195584E-01	-1.331373E-01	1.426173E-01	-1.046007E-02
5	G	1.715656E-02	2.286404E-02	3.166003E-01	-7.825480E-02	1.270811E-01	-8.285803E-03
6	G	1.090237E-02	1.260325E-02	1.777954E-01	-1.228383E-01	3.193135E-01	-2.491684E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.118777E-02	2.395725E-02	4.559923E-01	-1.710629E-01	-5.337878E-02	2.279046E-02
9	G	1.434376E-02	2.900675E-02	4.399810E-01	-1.309619E-01	5.085292E-02	1.284652E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 262
EIGHT TENTHS, -50 DEG
LOAD STEP = 9.00000E+00 SUBCASE 80

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.113822E-03	1.252646E-06	4.273553E-01	1.898231E-04	1.125023E-01	4.977331E-09
2	G	1.399301E-02	2.958797E-02	5.024242E-01	-2.421227E-01	-2.765216E-02	1.932460E-02
3	G	1.802573E-02	3.555866E-02	4.992120E-01	-1.823522E-01	3.626829E-02	3.022067E-03
4	G	2.087563E-02	3.306536E-02	4.385461E-01	-1.394264E-01	1.492154E-01	-1.146588E-02
5	G	1.874879E-02	2.499392E-02	3.309062E-01	-8.124633E-02	1.327440E-01	-9.062080E-03
6	G	1.193373E-02	1.378845E-02	1.859221E-01	-1.291890E-01	3.333254E-01	-2.731781E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.220805E-02	2.616949E-02	4.766067E-01	-1.788354E-01	-5.563058E-02	2.489480E-02
9	G	1.566101E-02	3.169556E-02	4.598516E-01	-1.367913E-01	5.305718E-02	1.425836E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 263
 NINE TENTHS, -50 DEG
 LOAD STEP = 1.00000E+01 SUBCASE 90

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.827995E-03	1.470714E-06	4.445979E-01	2.283776E-04	1.261036E-01	1.499701E-06
2	G	1.510642E-02	3.199397E-02	5.224112E-01	-2.523078E-01	-2.863491E-02	2.087505E-02
3	G	1.948109E-02	3.845786E-02	5.190611E-01	-1.899295E-01	3.758777E-02	3.296199E-03
4	G	2.257226E-02	3.576690E-02	4.559897E-01	-1.451791E-01	1.552642E-01	-1.242907E-02
5	G	2.027521E-02	2.703745E-02	3.440535E-01	-8.400726E-02	1.379530E-01	-9.807492E-03
6	G	1.292373E-02	1.492654E-02	1.933926E-01	-1.350649E-01	3.461531E-01	-2.962984E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.318255E-02	2.828877E-02	4.955517E-01	-1.859503E-01	-5.764504E-02	2.690448E-02
9	G	1.692144E-02	3.427324E-02	4.781128E-01	-1.421166E-01	5.505901E-02	1.566675E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 264
 ONE, -50 DEG
 LOAD STEP = 1.10000E+01 SUBCASE 101

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	1.051170E-02	1.697941E-06	4.606173E-01	2.691182E-04	1.391278E-01	3.413375E-06
2	G	1.617554E-02	3.430895E-02	5.409444E-01	-2.616982E-01	-2.951188E-02	2.236431E-02
3	G	2.088029E-02	4.124929E-02	5.374652E-01	-1.969276E-01	3.879909E-02	3.564358E-03
4	G	2.420507E-02	3.836966E-02	4.721664E-01	-1.504922E-01	1.608635E-01	-1.335573E-02
5	G	2.174545E-02	2.900730E-02	3.562501E-01	-8.657888E-02	1.427885E-01	-1.052650E-02
6	G	1.387843E-02	1.602445E-02	2.003246E-01	-1.405521E-01	3.580098E-01	-3.186629E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.411779E-02	3.032861E-02	5.131269E-01	-1.925259E-01	-5.946245E-02	2.883240E-02
9	G	1.813325E-02	3.675601E-02	4.950534E-01	-1.470286E-01	5.689486E-02	1.707441E-03

LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 257
 ONE TENTH, -100 DEG
 LOAD STEP = 2.00000E+00 SUBCASE 10

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	2.337973E-03	7.494951E-08	2.123175E-01	4.909183E-06	-2.985408E-03	-5.697601E-07
2	G	3.558577E-03	7.407735E-03	2.508172E-01	-1.127651E-01	-1.490065E-02	5.061528E-03
3	G	4.507627E-03	8.919111E-03	2.494726E-01	-8.837102E-02	1.930935E-02	6.452446E-04
4	G	5.203352E-03	8.297700E-03	2.192494E-01	-6.690559E-02	7.240685E-02	-2.670262E-03
5	G	4.698484E-03	6.302553E-03	1.659484E-01	-4.786848E-02	6.754102E-02	-2.255370E-03
6	G	2.898776E-03	3.436888E-03	9.237087E-02	-5.911401E-02	1.689950E-01	-6.620207E-03
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	3.074961E-03	6.611493E-03	2.384136E-01	-8.887411E-02	-2.745105E-02	6.191441E-03
9	G	3.934066E-03	7.983810E-03	2.301606E-01	-6.875311E-02	2.614201E-02	3.643246E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 258
 TWO TENTHS, -100 DEG
 LOAD STEP = 3.00000E+00 SUBCASE 20

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	3.691157E-03	1.905202E-07	2.680572E-01	1.847643E-05	1.527627E-02	-1.248713E-06
2	G	5.635408E-03	1.173461E-02	3.162127E-01	-1.451740E-01	-1.771712E-02	7.838580E-03
3	G	7.160627E-03	1.410619E-02	3.142774E-01	-1.109430E-01	2.355055E-02	1.114703E-03
4	G	8.261741E-03	1.312533E-02	2.761639E-01	-8.499318E-02	9.245283E-02	-4.341727E-03
5	G	7.435414E-03	9.947084E-03	2.087409E-01	-5.601097E-02	8.432796E-02	-3.576442E-02
6	G	4.644937E-03	5.448967E-03	1.166323E-01	-7.662639E-02	2.121746E-01	-1.057166E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	4.881834E-03	1.045123E-02	3.004286E-01	-1.116431E-01	-3.519308E-02	9.880900E-03
9	G	6.245694E-03	1.263463E-02	2.900405E-01	-8.612657E-02	3.354646E-02	5.398593E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 259
 THREE TENTHS, -100 DEG
 LOAD STEP = 4.00000E+00 SUBCASE 30

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	4.818393E-03	3.303268E-07	3.071887E-01	3.789037E-05	3.358318E-02	-1.794215E-06
2	G	7.358482E-03	1.539462E-02	3.622115E-01	-1.694845E-01	-2.013173E-02	1.017058E-02
3	G	9.389227E-03	1.849651E-02	3.599688E-01	-1.287184E-01	2.665234E-02	1.499262E-03
4	G	1.084166E-02	1.720156E-02	3.162685E-01	-9.862070E-02	1.066026E-01	-5.797445E-03
5	G	9.745697E-03	1.302121E-02	2.388895E-01	-6.220870E-02	9.618243E-02	-4.687210E-03
6	G	6.126054E-03	7.148823E-03	1.337277E-01	-8.945189E-02	2.424180E-01	-1.395661E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	6.392026E-03	1.367477E-02	3.438969E-01	-1.284474E-01	-4.045379E-02	1.296521E-02
9	G	8.177868E-03	1.653513E-02	3.319375E-01	-9.884719E-02	3.850844E-02	6.991255E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 260
 FOUR TENTHS, -100 DEG
 LOAD STEP = 5.00000E+00 SUBCASE 40

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	5.815549E-03	4.882976E-07	3.383566E-01	6.176219E-05	5.106654E-02	-2.099691E-06
2	G	8.887932E-03	1.865747E-02	3.987474E-01	-1.887014E-01	-2.210472E-02	1.226054E-02
3	G	1.137274E-02	2.241346E-02	3.962588E-01	-1.428327E-01	2.913562E-02	1.845148E-03
4	G	1.314090E-02	2.083980E-02	3.481293E-01	-1.093907E-01	1.177987E-01	-7.100588E-03
5	G	1.180575E-02	1.576597E-02	2.628518E-01	-6.713477E-02	1.056267E-01	-5.681665E-03
6	G	7.450973E-03	8.669370E-03	1.473214E-01	-9.974714E-02	2.663150E-01	-1.699767E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	7.733103E-03	1.654639E-02	3.784393E-01	-1.417183E-01	-4.457231E-02	1.571552E-02
9	G	9.896498E-03	2.001343E-02	3.652318E-01	-1.088776E-01	4.239183E-02	8.498236E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE
AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 261
FIVE TENTHS, -100 DEG
LOAD STEP = 6.00000E+00 SUBCASE 50

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	6.724511E-03	6.612528E-07	3.646933E-01	8.933952E-05	6.764618E-02	-2.105637E-06
2	G	1.028700E-02	2.165163E-02	4.295394E-01	-2.047803E-01	-2.377161E-02	1.418610E-02
3	G	1.319068E-02	2.601072E-02	4.268444E-01	-1.546800E-01	3.122950E-02	2.166471E-03
4	G	1.525081E-02	2.418317E-02	3.749863E-01	-1.184143E-01	1.272016E-01	-8.298245E-03
5	G	1.369757E-02	1.828950E-02	2.830600E-01	-7.130133E-02	1.136077E-01	-6.597931E-03
6	G	8.670487E-03	1.006933E-02	1.587893E-01	-1.085007E-01	2.863633E-01	-1.980759E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	8.959666E-03	1.918127E-02	4.075684E-01	-1.528413E-01	-4.798283E-02	1.823821E-02
9	G	1.147129E-02	2.320808E-02	3.933094E-01	-1.172708E-01	4.562372E-02	9.958071E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE
AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 262
SIX TENTHS, -100 DEG
LOAD STEP = 7.00000E+00 SUBCASE 60

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	7.567908E-03	8.472538E-07	3.877298E-01	1.201250E-04	8.337066E-02	-1.772012E-06
2	G	1.158950E-02	2.444687E-02	4.564089E-01	-2.187168E-01	-2.520978E-02	1.598779E-02
3	G	1.488603E-02	2.937162E-02	4.535326E-01	-1.649788E-01	3.305077E-02	2.470545E-03
4	G	1.722077E-02	2.730885E-02	3.984258E-01	-1.262469E-01	1.353822E-01	-9.417096E-03
5	G	1.546536E-02	2.064998E-02	3.007046E-01	-7.495505E-02	1.205873E-01	-7.456366E-03
6	G	9.812166E-03	1.138036E-02	1.688054E-01	-1.162030E-01	3.037859E-01	-2.244765E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.010122E-02	2.164133E-02	4.330005E-01	-1.625046E-01	-5.089664E-02	2.058996E-02
9	G	1.293969E-02	2.619340E-02	4.178238E-01	-1.245479E-01	4.840908E-02	1.139202E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE
AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 263
SEVEN TENTHS, -100 DEG
LOAD STEP = 8.00000E+00 SUBCASE 70

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	8.359713E-03	1.044926E-06	4.083432E-01	1.537585E-04	9.831440E-02	-1.070209E-06
2	G	1.281629E-02	2.708620E-02	4.803988E-01	-2.310800E-01	-2.646712E-02	1.769048E-02
3	G	1.648528E-02	3.254744E-02	4.773592E-01	-1.741381E-01	3.466722E-02	2.761953E-03
4	G	1.908116E-02	3.026432E-02	4.193563E-01	-1.332062E-01	1.426674E-01	-1.047382E-02
5	G	1.713625E-02	2.288314E-02	3.164670E-01	-7.823407E-02	1.268301E-01	-8.269516E-03
6	G	1.089298E-02	1.262193E-02	1.777555E-01	-1.231348E-01	3.192823E-01	-2.495554E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.117600E-02	2.396467E-02	4.557187E-01	-1.710986E-01	-5.343791E-02	2.280604E-02
9	G	1.432475E-02	2.901509E-02	4.397222E-01	-1.310061E-01	5.086607E-02	1.281156E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE
AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 264
EIGHT TENTHS, -100 DEG
LOAD STEP = 9.00000E+00 SUBCASE 80

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.109332E-03	1.253231E-06	4.270884E-01	1.899668E-04	1.125522E-01	2.112483E-08
2	G	1.398139E-02	2.959852E-02	5.021684E-01	-2.422301E-01	-2.757640E-02	1.931092E-02
3	G	1.800622E-02	3.557264E-02	4.989793E-01	-1.824172E-01	3.612259E-02	3.043732E-03
4	G	2.085239E-02	3.308145E-02	4.383523E-01	-1.394931E-01	1.492638E-01	-1.147975E-02
5	G	1.872842E-02	2.501293E-02	3.307782E-01	-8.122472E-02	1.325037E-01	-9.045799E-03
6	G	1.192433E-02	1.380710E-02	1.858838E-01	-1.294734E-01	3.332949E-01	-2.735650E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.219625E-02	2.617685E-02	4.763445E-01	-1.788693E-01	-5.568686E-02	2.491031E-02
9	G	1.564196E-02	3.170382E-02	4.596036E-01	-1.368334E-01	5.306972E-02	1.422349E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE
AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 265
NINE TENTHS, -100 DEG
LOAD STEP = 1.00000E+01 SUBCASE 90

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.823477E-03	1.471353E-06	4.443410E-01	2.285347E-04	1.261525E-01	1.518459E-06
2	G	1.509476E-02	3.200445E-02	5.221648E-01	-2.524115E-01	-2.856151E-02	2.086115E-02
3	G	1.946155E-02	3.847177E-02	5.188370E-01	-1.899918E-01	3.744717E-02	3.317993E-03
4	G	2.254898E-02	3.578291E-02	4.558030E-01	-1.452438E-01	1.553112E-01	-1.244304E-02
5	G	2.025479E-02	2.705638E-02	3.439300E-01	-8.398504E-02	1.377216E-01	-9.791214E-03
6	G	1.291432E-02	1.494517E-02	1.933557E-01	-1.353390E-01	3.461232E-01	-2.966852E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.317072E-02	2.829606E-02	4.952992E-01	-1.859828E-01	-5.769885E-02	2.691992E-02
9	G	1.690236E-02	3.428142E-02	4.778739E-01	-1.421570E-01	5.507099E-02	1.563205E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE
AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 266
ONE, -100 DEG
LOAD STEP = 1.10000E+01 SUBCASE 101

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	1.050716E-02	1.698633E-06	4.603690E-01	2.692883E-04	1.391755E-01	3.434821E-06
2	G	1.616384E-02	3.431936E-02	5.407061E-01	-2.617986E-01	-2.944057E-02	2.235022E-02
3	G	2.086071E-02	4.126310E-02	5.372483E-01	-1.969875E-01	3.866293E-02	3.586259E-03
4	G	2.418175E-02	3.838560E-02	4.719857E-01	-1.505552E-01	1.609090E-01	-1.336978E-02
5	G	2.172497E-02	2.902616E-02	3.561304E-01	-8.655624E-02	1.425650E-01	-1.051022E-02
6	G	1.386900E-02	1.604306E-02	2.002888E-01	-1.408173E-01	3.579803E-01	-3.190494E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.410594E-02	3.033584E-02	5.128826E-01	-1.925571E-01	-5.951411E-02	2.884776E-02
9	G	1.811415E-02	3.676413E-02	4.948224E-01	-1.470674E-01	5.690632E-02	1.703992E-03

LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 255

ONE TENTH, -150 DEG
LOAD STEP = 2.00000E+00

SUBCASE 10

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	2.329357E-03	7.437726E-08	2.117432E-01	4.830657E-06	-3.062573E-03	-5.652146E-07
2	G	3.554602E-03	7.382452E-03	2.499540E-01	-1.108043E-01	-1.442291E-02	5.059672E-03
3	G	4.477409E-03	8.890040E-03	2.485298E-01	-8.601610E-02	1.895038E-02	6.768920E-04
4	G	5.159586E-03	8.284648E-03	2.184707E-01	-6.563790E-02	7.223493E-02	-2.638176E-03
5	G	4.658239E-03	6.303390E-03	1.654289E-01	-4.711042E-02	6.696173E-02	-2.240450E-03
6	G	2.877196E-03	3.447597E-03	9.215534E-02	-5.912841E-02	1.686269E-01	-6.614641E-03
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	3.060283E-03	6.605336E-03	2.377721E-01	-8.760615E-02	-2.769051E-02	6.220341E-03
9	G	3.913347E-03	7.986764E-03	2.296523E-01	-6.793053E-02	2.631566E-02	3.592006E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 256

TWO TENTHS, -150 DEG
LOAD STEP = 3.00000E+00

SUBCASE 20

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	3.686817E-03	1.903182E-07	2.676367E-01	1.849735E-05	1.532557E-02	-1.245954E-06
2	G	5.624424E-03	1.174474E-02	3.158057E-01	-1.452613E-01	-1.760436E-02	7.829248E-03
3	G	7.141180E-03	1.411988E-02	3.139054E-01	-1.109813E-01	2.332847E-02	1.134883E-03
4	G	8.238425E-03	1.314163E-02	2.758557E-01	-8.505850E-02	9.251013E-02	-4.352503E-03
5	G	7.415195E-03	9.966651E-03	2.085413E-01	-5.600548E-02	8.395544E-02	-3.560192E-03
6	G	4.635133E-03	5.467578E-03	1.165695E-01	-7.704809E-02	2.121285E-01	-1.060899E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	4.870153E-03	1.045910E-02	3.000183E-01	-1.116668E-01	-3.529124E-02	9.897561E-03
9	G	6.226935E-03	1.264375E-02	2.896551E-01	-8.617808E-02	3.356984E-02	5.363917E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 257

THREE TENTHS, -150 DEG
LOAD STEP = 4.00000E+00

SUBCASE 30

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	4.814030E-03	3.251841E-07	3.068205E-01	3.753560E-05	3.363425E-02	-1.796317E-06
2	G	7.347537E-03	1.540439E-02	3.618525E-01	-1.695409E-01	-2.002201E-02	1.015977E-02
3	G	9.369682E-03	1.850986E-02	3.596382E-01	-1.287229E-01	2.644521E-02	1.521028E-03
4	G	1.081836E-02	1.721783E-02	3.159991E-01	-9.868506E-02	1.066554E-01	-5.808874E-03
5	G	9.725576E-03	1.304074E-02	2.387155E-01	-6.219887E-02	9.585211E-02	-4.670788E-03
6	G	6.116510E-03	7.167524E-03	1.336745E-01	-8.983377E-02	2.423800E-01	-1.399505E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	6.380294E-03	1.368252E-02	3.435376E-01	-1.284556E-01	-4.054826E-02	1.298240E-02
9	G	8.159135E-03	1.654421E-02	3.316016E-01	-9.889132E-02	3.853524E-02	6.951347E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 258

FOUR TENTHS, -150 DEG
LOAD STEP = 5.00000E+00

SUBCASE 40

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	5.811173E-03	4.886369E-07	3.380218E-01	6.184368E-05	5.111982E-02	-2.092935E-06
2	G	8.876565E-03	1.866814E-02	3.984268E-01	-1.888199E-01	-2.201346E-02	1.224863E-02
3	G	1.135335E-02	2.242764E-02	3.959672E-01	-1.429043E-01	2.895646E-02	1.865994E-03
4	G	1.311776E-02	2.085618E-02	3.478866E-01	-1.094648E-01	1.178543E-01	-7.113407E-03
5	G	1.178558E-02	1.578537E-02	2.626931E-01	-6.711914E-02	1.053268E-01	-5.665388E-03
6	G	7.441477E-03	6.688073E-03	1.472733E-01	-1.000967E-01	2.662792E-01	-1.703605E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	7.721408E-03	1.655408E-02	3.781117E-01	-1.417571E-01	-4.464569E-02	1.573151E-02
9	G	9.877605E-03	2.002212E-02	3.649224E-01	-1.089289E-01	4.240833E-02	8.463067E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 259

FIVE TENTHS, -150 DEG
LOAD STEP = 6.00000E+00

SUBCASE 50

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	6.720106E-03	6.616519E-07	3.643821E-01	8.943871E-05	6.769919E-02	-2.096743E-06
2	G	1.027555E-02	2.166231E-02	4.292416E-01	-2.048970E-01	-2.368563E-02	1.417355E-02
3	G	1.317127E-02	2.602490E-02	4.265735E-01	-1.547509E-01	3.106178E-02	2.187601E-03
4	G	1.522766E-02	2.419949E-02	3.747607E-01	-1.184869E-01	1.272552E-01	-8.311487E-03
5	G	1.367735E-02	1.830881E-02	2.829121E-01	-7.128321E-02	1.133282E-01	-6.581658E-03
6	G	8.661034E-03	1.008803E-02	1.587447E-01	-1.088282E-01	2.863295E-01	-1.984614E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	8.947946E-03	1.918888E-02	4.072635E-01	-1.528792E-01	-4.805029E-02	1.825406E-02
9	G	1.145235E-02	2.321666E-02	3.930213E-01	-1.173195E-01	4.563889E-02	9.922792E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 260

SIX TENTHS, -150 DEG
LOAD STEP = 7.00000E+00

SUBCASE 60

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	7.563472E-03	8.477174E-07	3.874366E-01	1.202402E-04	8.342290E-02	-1.760800E-06
2	G	1.157799E-02	2.445752E-02	4.561283E-01	-2.188301E-01	-2.512785E-02	1.597478E-02
3	G	1.486659E-02	2.938574E-02	4.532773E-01	-1.650473E-01	3.289188E-02	2.491906E-03
4	G	1.719759E-02	2.732510E-02	3.982132E-01	-1.263174E-01	1.354339E-01	-9.430614E-03
5	G	1.544509E-02	2.066919E-02	3.005648E-01	-7.493524E-02	1.203236E-01	-7.440100E-03
6	G	9.802728E-03	1.139905E-02	1.687634E-01	-1.165131E-01	3.037534E-01	-2.248629E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.008948E-02	2.164886E-02	4.327130E-01	-1.625410E-01	-5.095967E-02	2.060572E-02
9	G	1.292071E-02	2.620186E-02	4.175520E-01	-1.245941E-01	4.842327E-02	1.135673E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 261
SEVEN TENTHS, -150 DEG
LOAD STEP = 8.00000E+00 SUBCASE 70

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	8.355249E-03	1.045449E-06	4.080644E-01	1.538888E-04	9.836563E-02	-1.056563E-06
2	G	1.280473E-02	2.709679E-02	4.801317E-01	-2.311895E-01	-2.638847E-02	1.767712E-02
3	G	1.646580E-02	3.256149E-02	4.771162E-01	-1.742041E-01	3.451546E-02	2.783500E-03
4	G	1.905794E-02	3.028050E-02	4.191539E-01	-1.332746E-01	1.427173E-01	-1.048753E-02
5	G	1.711592E-02	2.290226E-02	3.163337E-01	-7.821310E-02	1.265792E-01	-8.253254E-03
6	G	1.088355E-02	1.264060E-02	1.777156E-01	-1.234307E-01	3.192509E-01	-2.499422E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.116422E-02	2.397212E-02	4.554450E-01	-1.711334E-01	-5.349740E-02	2.282171E-02
9	G	1.430574E-02	2.902346E-02	4.394634E-01	-1.310501E-01	5.087947E-02	1.277633E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 262
EIGHT TENTHS, -150 DEG
LOAD STEP = 9.00000E+00 SUBCASE 80

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.104838E-03	1.253812E-06	4.268213E-01	1.901112E-04	1.126024E-01	3.730487E-08
2	G	1.396978E-02	2.960906E-02	5.019125E-01	-2.423361E-01	-2.750053E-02	1.929727E-02
3	G	1.798671E-02	3.558661E-02	4.987465E-01	-1.824807E-01	3.597681E-02	3.065430E-03
4	G	2.082913E-02	3.309755E-02	4.381584E-01	-1.395595E-01	1.493121E-01	-1.149361E-02
5	G	1.870802E-02	2.503196E-02	3.306501E-01	-8.120295E-02	1.322634E-01	-9.029538E-03
6	G	1.191489E-02	1.382576E-02	1.858455E-01	-1.297574E-01	3.332642E-01	-2.739521E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.218444E-02	2.618423E-02	4.760823E-01	-1.789027E-01	-5.574339E-02	2.492590E-02
9	G	1.562292E-02	3.171211E-02	4.593556E-01	-1.368754E-01	5.308243E-02	1.418841E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 263
NINE TENTHS, -150 DEG
LOAD STEP = 1.00000E+01 SUBCASE 90

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.818955E-03	1.471989E-06	4.440840E-01	2.286926E-04	1.262015E-01	1.537260E-06
2	G	1.508311E-02	3.201493E-02	5.219182E-01	-2.525143E-01	-2.848804E-02	2.084726E-02
3	G	1.944200E-02	3.848566E-02	5.186126E-01	-1.900531E-01	3.730650E-02	3.339815E-03
4	G	2.252568E-02	3.579894E-02	4.556162E-01	-1.453084E-01	1.553580E-01	-1.245701E-02
5	G	2.023434E-02	2.707533E-02	3.438064E-01	-8.396272E-02	1.374903E-01	-5.774952E-03
6	G	1.290488E-02	1.496381E-02	1.933187E-01	-1.356129E-01	3.460931E-01	-2.970723E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.315889E-02	2.830337E-02	4.950466E-01	-1.860148E-01	-5.775286E-02	2.693542E-02
9	G	1.688329E-02	3.428964E-02	4.776351E-01	-1.421972E-01	5.508309E-02	1.559716E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 264
ONE, -150 DEG
LOAD STEP = 1.10000E+01 SUBCASE 101

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	1.050261E-02	1.699322E-06	4.601206E-01	2.694591E-04	1.392234E-01	3.456320E-06
2	G	1.615215E-02	3.432978E-02	5.404676E-01	-2.618983E-01	-2.936919E-02	2.233615E-02
3	G	2.084113E-02	4.127693E-02	5.370312E-01	-1.970467E-01	3.852671E-02	3.608186E-03
4	G	2.415842E-02	3.840156E-02	4.718050E-01	-1.506180E-01	1.609545E-01	-1.338383E-02
5	G	2.170447E-02	2.904503E-02	3.560107E-01	-8.653355E-02	1.423415E-01	-1.049396E-02
6	G	1.385955E-02	1.606168E-02	2.002529E-01	-1.410823E-01	3.579507E-01	-3.194365E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.409408E-02	3.034309E-02	5.126384E-01	-1.925879E-01	-5.956592E-02	2.886317E-02
9	G	1.809505E-02	3.677227E-02	4.945914E-01	-1.471060E-01	5.691789E-02	1.700527E-03

LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 255
ONE TENTH, -200 DEG
LOAD STEP = 2.00000E+00 SUBCASE 10

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	2.325145E-03	7.450133E-08	2.112128E-01	4.852360E-06	-3.017707E-03	-5.637214E-07
2	G	3.543497E-03	7.393614E-03	2.494490E-01	-1.109679E-01	-1.430976E-02	5.052850E-03
3	G	4.458285E-03	8.904914E-03	2.480719E-01	-8.614436E-02	1.869600E-02	6.945065E-04
4	G	5.136708E-03	8.301627E-03	2.180888E-01	-6.572475E-02	7.229453E-02	-2.648136E-03
5	G	4.638614E-03	6.323676E-03	1.651854E-01	-4.714686E-02	6.650320E-02	-2.224147E-03
6	G	2.867461E-03	3.466329E-03	9.207732E-02	-5.965106E-02	1.685755E-01	-6.652638E-03
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	3.048743E-03	6.614806E-03	2.372560E-01	-8.767575E-02	-2.779697E-02	6.235649E-03
9	G	3.894632E-03	7.996119E-03	2.291646E-01	-6.800894E-02	2.632786E-02	3.567292E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 256
TWO TENTHS, -200 DEG
LOAD STEP = 3.00000E+00 SUBCASE 20

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	3.682544E-03	1.905734E-07	2.672155E-01	1.854526E-05	1.537727E-02	-1.242979E-06
2	G	5.613167E-03	1.175579E-02	3.154044E-01	-1.454095E-01	-1.750137E-02	7.819555E-03
3	G	7.121970E-03	1.413456E-02	3.135413E-01	-1.110846E-01	2.311382E-02	1.154171E-03
4	G	8.215481E-03	1.315839E-02	2.755522E-01	-8.514321E-02	9.257090E-02	-4.364204E-03
5	G	7.395362E-03	9.986543E-03	2.083453E-01	-5.600919E-02	8.358337E-02	-3.543831E-03
6	G	4.625593E-03	5.486342E-03	1.165089E-01	-7.747866E-02	2.120869E-01	-1.064724E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	4.585860E-03	1.046712E-02	2.996074E-01	-1.117226E-01	-3.537972E-02	9.913184E-03
9	G	6.208139E-03	1.265278E-02	2.892666E-01	-8.624350E-02	3.358529E-02	5.333286E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 257
THREE TENTHS, -200 DEG
LOAD STEP = 4.00000E+00 SUBCASE 30

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	4.809710E-03	3.259699E-07	3.064521E-01	3.763924E-05	3.368774E-02	-1.790909E-06
2	G	7.336203E-03	1.541532E-02	3.615010E-01	-1.696751E-01	-1.992615E-02	1.014869E-02
3	G	9.350399E-03	1.852436E-02	3.593191E-01	-1.288104E-01	2.625190E-02	1.541222E-03
4	G	1.079535E-02	1.723446E-02	3.157334E-01	-9.876554E-02	1.067136E-01	-5.821362E-03
5	G	9.705601E-03	1.306040E-02	2.385427E-01	-6.219085E-02	9.552394E-02	-4.654460E-03
6	G	6.107036E-03	7.186289E-03	1.336219E-01	-9.021625E-02	2.423425E-01	-1.403355E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	6.368657E-03	1.369038E-02	3.431777E-01	-1.285028E-01	-4.062732E-02	1.299818E-02
9	G	8.140288E-03	1.655307E-02	3.312614E-01	-9.894916E-02	3.855113E-02	6.918191E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 258
FOUR TENTHS, -200 DEG
LOAD STEP = 5.00000E+00 SUBCASE 40

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	5.806813E-03	4.889875E-07	3.376867E-01	6.192640E-05	5.117357E-02	-2.086160E-06
2	G	8.865143E-03	1.867904E-02	3.981071E-01	-1.889490E-01	-2.192397E-02	1.223667E-02
3	G	1.133402E-02	2.244207E-02	3.956768E-01	-1.429871E-01	2.877855E-02	1.886650E-03
4	G	1.309470E-02	2.087269E-02	3.476447E-01	-1.095423E-01	1.179103E-01	-7.126434E-03
5	G	1.176550E-02	1.580487E-02	2.625349E-01	-6.710525E-02	1.050271E-01	-5.649099E-03
6	G	7.432031E-03	8.706826E-03	1.472255E-01	-1.004475E-01	2.662439E-01	-1.707466E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	7.709738E-03	1.656182E-02	3.777839E-01	-1.418013E-01	-4.471721E-02	1.574725E-02
9	G	9.858708E-03	2.003082E-02	3.646124E-01	-1.089824E-01	4.242320E-02	8.429107E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 259
FIVE TENTHS, -200 DEG
LOAD STEP = 6.00000E+00 SUBCASE 50

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	6.715709E-03	6.620672E-07	3.640707E-01	8.953828E-05	6.775243E-02	-2.087806E-06
2	G	1.026407E-02	2.167313E-02	4.289442E-01	-2.050193E-01	-2.360067E-02	1.416099E-02
3	G	1.315189E-02	2.603922E-02	4.263033E-01	-1.548277E-01	3.089481E-02	2.208617E-03
4	G	1.520455E-02	2.421590E-02	3.745356E-01	-1.185612E-01	1.273089E-01	-8.324843E-03
5	G	1.365718E-02	1.832817E-02	2.827644E-01	-7.126600E-02	1.130491E-01	-6.565391E-03
6	G	8.651598E-03	1.010677E-02	1.587003E-01	-1.091561E-01	2.862959E-01	-1.988480E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	8.936241E-03	1.919652E-02	4.069586E-01	-1.529199E-01	-4.811667E-02	1.826977E-02
9	G	1.143342E-02	2.322524E-02	3.927328E-01	-1.173693E-01	4.565309E-02	9.888312E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 260
SIX TENTHS, -200 DEG
LOAD STEP = 7.00000E+00 SUBCASE 60

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	7.559042E-03	8.481928E-07	3.871433E-01	1.203556E-04	8.347527E-02	-1.749561E-06
2	G	1.156646E-02	2.446826E-02	4.558479E-01	-2.189467E-01	-2.504660E-02	1.596178E-02
3	G	1.484717E-02	2.939996E-02	4.530224E-01	-1.651195E-01	3.273351E-02	2.513185E-03
4	G	1.717443E-02	2.734142E-02	3.980008E-01	-1.263889E-01	1.354855E-01	-9.444203E-03
5	G	1.542484E-02	2.068844E-02	3.004251E-01	-7.491597E-02	1.200603E-01	-7.423847E-03
6	G	9.793295E-03	1.141777E-02	1.687214E-01	-1.168232E-01	3.037210E-01	-2.252498E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.007774E-02	2.165641E-02	4.324254E-01	-1.625791E-01	-5.102198E-02	2.062138E-02
9	G	1.290174E-02	2.621035E-02	4.172800E-01	-1.246409E-01	4.843680E-02	1.132203E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 261
SEVEN TENTHS, -200 DEG
LOAD STEP = 8.00000E+00 SUBCASE 70

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	8.350787E-03	1.045982E-06	4.077854E-01	1.540190E-04	9.841696E-02	-1.042901E-06
2	G	1.279316E-02	2.710746E-02	4.798647E-01	-2.313013E-01	-2.631034E-02	1.766377E-02
3	G	1.644634E-02	3.257562E-02	4.768734E-01	-1.742725E-01	3.436412E-02	2.804983E-03
4	G	1.903475E-02	3.029673E-02	4.189517E-01	-1.333436E-01	1.427671E-01	-1.050129E-02
5	G	1.709560E-02	2.292140E-02	3.162003E-01	-7.819250E-02	1.263286E-01	-8.237008E-03
6	G	1.087411E-02	1.265930E-02	1.776756E-01	-1.237264E-01	3.192193E-01	-2.503292E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.115245E-02	2.397959E-02	4.551713E-01	-1.711694E-01	-5.355635E-02	2.283731E-02
9	G	1.428673E-02	2.903185E-02	4.392045E-01	-1.310944E-01	5.089237E-02	1.274160E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 262
EIGHT TENTHS, -200 DEG
LOAD STEP = 9.00000E+00 SUBCASE 80

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.100347E-03	1.254400E-06	4.265543E-01	1.902556E-04	1.126526E-01	5.349411E-08
2	G	1.395816E-02	2.961965E-02	5.016567E-01	-2.424437E-01	-2.742507E-02	1.928365E-02
3	G	1.796721E-02	3.560065E-02	4.985138E-01	-1.825460E-01	3.583137E-02	3.087074E-03
4	G	2.080589E-02	3.311370E-02	4.379645E-01	-1.396264E-01	1.493602E-01	-1.150750E-02
5	G	1.868764E-02	2.505101E-02	3.305221E-01	-8.118144E-02	1.320233E-01	-9.013296E-03
6	G	1.190545E-02	1.384443E-02	1.858071E-01	-1.300412E-01	3.332334E-01	-2.743390E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.217264E-02	2.619163E-02	4.758200E-01	-1.789369E-01	-5.579950E-02	2.494142E-02
9	G	1.560388E-02	3.172042E-02	4.591075E-01	-1.369177E-01	5.309474E-02	1.415376E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 263
NINE TENTHS, -200 DEG
LOAD STEP = 1.00000E+01 SUBCASE 90

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.814437E-03	1.472632E-06	4.438269E-01	2.288505E-04	1.262505E-01	1.556066E-06
2	G	1.507146E-02	3.202546E-02	5.216718E-01	-2.526182E-01	-2.841490E-02	2.083342E-02
3	G	1.942246E-02	3.849962E-02	5.183883E-01	-1.901156E-01	3.716613E-02	3.361591E-03
4	G	2.250241E-02	3.581501E-02	4.554294E-01	-1.453732E-01	1.554047E-01	-1.247099E-02
5	G	2.021390E-02	2.709430E-02	3.436828E-01	-8.394060E-02	1.372593E-01	-9.758710E-03
6	G	1.289542E-02	1.498246E-02	1.932816E-01	-1.358864E-01	3.460628E-01	-2.974590E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.314706E-02	2.831070E-02	4.947939E-01	-1.860475E-01	-5.780651E-02	2.695087E-02
9	G	1.686422E-02	3.429786E-02	4.773961E-01	-1.422376E-01	5.509487E-02	1.556266E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 264
ONE, -200 DEG
LOAD STEP = 1.10000E+01 SUBCASE 101

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	1.049806E-02	1.700017E-06	4.598722E-01	2.696298E-04	1.392713E-01	3.477820E-06
2	G	1.614046E-02	3.434024E-02	5.402293E-01	-2.619988E-01	-2.929811E-02	2.232211E-02
3	G	2.082155E-02	4.129080E-02	5.368142E-01	-1.971070E-01	3.839075E-02	3.630070E-03
4	G	2.413510E-02	3.841754E-02	4.716242E-01	-1.506810E-01	1.609999E-01	-1.339789E-02
5	G	2.168398E-02	2.906392E-02	3.558909E-01	-8.651098E-02	1.421183E-01	-1.047772E-02
6	G	1.385009E-02	1.608031E-02	2.002170E-01	-1.413469E-01	3.579210E-01	-3.198231E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.408223E-02	3.035035E-02	5.123940E-01	-1.926192E-01	-5.961743E-02	2.887855E-02
9	G	1.807595E-02	3.678042E-02	4.943602E-01	-1.471448E-01	5.692917E-02	1.697097E-03

LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 255
ONE TENTH, -250 DEG
LOAD STEP = 2.00000E+00 SUBCASE 10

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	2.320932E-03	7.463038E-08	2.106818E-01	4.874085E-06	-2.970313E-03	-5.619806E-07
2	G	3.532331E-03	7.405038E-03	2.489449E-01	-1.111462E-01	-1.420031E-02	5.045667E-03
3	G	4.439197E-03	8.920093E-03	2.476158E-01	-8.629019E-02	1.844441E-02	7.121947E-04
4	G	5.113875E-03	8.318784E-03	2.177075E-01	-6.581748E-02	7.235470E-02	-2.658388E-03
5	G	4.618987E-03	6.344083E-03	1.649420E-01	-4.718475E-02	6.604616E-02	-2.207666E-03
6	G	2.857662E-03	3.485128E-03	9.199908E-02	-6.017214E-02	1.685231E-01	-6.688290E-03
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	3.037208E-03	6.623178E-03	2.367392E-01	-8.775382E-02	-2.790111E-02	6.250920E-03
9	G	3.875895E-03	8.005532E-03	2.286754E-01	-6.809194E-02	2.633825E-02	3.542903E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 256
TWO TENTHS, -250 DEG
LOAD STEP = 3.00000E+00 SUBCASE 20

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	3.678284E-03	1.885241E-07	2.667924E-01	1.843549E-05	1.542881E-02	-1.238610E-06
2	G	5.601716E-03	1.176736E-02	3.150064E-01	-1.456029E-01	-1.740650E-02	7.809766E-03
3	G	7.102863E-03	1.414977E-02	3.131819E-01	-1.112372E-01	2.290610E-02	1.172803E-03
4	G	8.192702E-03	1.317539E-02	2.752510E-01	-8.524233E-02	9.263380E-02	-4.376611E-03
5	G	7.375674E-03	1.006588E-02	2.081508E-01	-5.601952E-02	8.321179E-02	-3.527544E-03
6	G	4.616120E-03	5.505166E-03	1.164491E-01	-7.791381E-02	2.120471E-01	-1.068636E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	4.846986E-03	1.047521E-02	2.991948E-01	-1.118033E-01	-3.546118E-02	9.928572E-03
9	G	6.189289E-03	1.266173E-02	2.888743E-01	-8.632021E-02	3.359534E-02	5.303946E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 257
THREE TENTHS, -250 DEG
LOAD STEP = 4.00000E+00 SUBCASE 30

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	4.805389E-03	3.316792E-07	3.060798E-01	3.812827E-05	3.374373E-02	-1.779553E-06
2	G	7.324293E-03	1.542751E-02	3.611553E-01	-1.699081E-01	-1.984781E-02	1.013709E-02
3	G	9.331335E-03	1.854010E-02	3.590081E-01	-1.290037E-01	2.607567E-02	1.559522E-03
4	G	1.077260E-02	1.725134E-02	3.154693E-01	-9.886760E-02	1.067775E-01	-5.835169E-03
5	G	9.685749E-03	1.308012E-02	2.383694E-01	-6.218661E-02	9.519698E-02	-4.638191E-03
6	G	6.097623E-03	7.205063E-03	1.335689E-01	-9.060080E-02	2.423039E-01	-1.407233E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	6.357061E-03	1.369822E-02	3.428131E-01	-1.285995E-01	-4.068710E-02	1.301228E-02
9	G	8.121215E-03	1.656145E-02	3.309118E-01	-9.902477E-02	3.855321E-02	6.892584E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 258
FOUR TENTHS, -250 DEG
LOAD STEP = 5.00000E+00 SUBCASE 40

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	5.802449E-03	4.893259E-07	3.373516E-01	6.200936E-05	5.122748E-02	-2.079423E-06
2	G	8.853743E-03	1.868992E-02	3.977871E-01	-1.890754E-01	-2.183435E-02	1.222478E-02
3	G	1.131468E-02	2.245649E-02	3.953860E-01	-1.430673E-01	2.860061E-02	1.907338E-03
4	G	1.307162E-02	2.088923E-02	3.474025E-01	-1.096191E-01	1.179658E-01	-7.139410E-03
5	G	1.174538E-02	1.582438E-02	2.623765E-01	-6.709108E-02	1.047278E-01	-5.632846E-03
6	G	7.422531E-03	8.725591E-03	1.471774E-01	-1.007972E-01	2.662082E-01	-1.711322E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	7.698064E-03	1.656959E-02	3.774561E-01	-1.418442E-01	-4.478906E-02	1.576307E-02
9	G	9.839816E-03	2.003958E-02	3.643023E-01	-1.090354E-01	4.243826E-02	8.395010E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 259
FIVE TENTHS, -250 DEG
LOAD STEP = 6.00000E+00 SUBCASE 50

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	6.711310E-03	6.624807E-07	3.637592E-01	8.963820E-05	6.780585E-02	-2.078865E-06
2	G	1.025260E-02	2.168395E-02	4.286467E-01	-2.051404E-01	-2.351577E-02	1.414848E-02
3	G	1.313251E-02	2.605356E-02	4.260328E-01	-1.549034E-01	3.072793E-02	2.229641E-03
4	G	1.518144E-02	2.423234E-02	3.743103E-01	-1.186352E-01	1.273623E-01	-8.338177E-03
5	G	1.363699E-02	1.834755E-02	2.826166E-01	-7.124867E-02	1.127702E-01	-6.549153E-03
6	G	8.642124E-03	1.012552E-02	1.586557E-01	-1.094832E-01	2.862620E-01	-1.992345E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	8.924535E-03	1.920418E-02	4.066535E-01	-1.529602E-01	-4.818316E-02	1.828553E-02
9	G	1.141448E-02	2.323386E-02	3.924443E-01	-1.174189E-01	4.566730E-02	9.853814E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 260
SIX TENTHS, -250 DEG
LOAD STEP = 7.00000E+00 SUBCASE 60

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	7.554611E-03	8.486675E-07	3.868498E-01	1.204713E-04	8.352781E-02	-1.738311E-06
2	G	1.155494E-02	2.447901E-02	4.555673E-01	-2.190627E-01	-2.496544E-02	1.594882E-02
3	G	1.482774E-02	2.941421E-02	4.527673E-01	-1.651911E-01	3.257523E-02	2.534469E-03
4	G	1.715128E-02	2.735776E-02	3.977884E-01	-1.264603E-01	1.355369E-01	-9.457780E-03
5	G	1.540457E-02	2.070770E-02	3.002853E-01	-7.489666E-02	1.197972E-01	-7.407617E-03
6	G	9.783830E-03	1.143650E-02	1.686794E-01	-1.171328E-01	3.036883E-01	-2.256366E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.006600E-02	2.166398E-02	4.321377E-01	-1.626170E-01	-5.108432E-02	2.063707E-02
9	G	1.288276E-02	2.621886E-02	4.170079E-01	-1.246876E-01	4.845031E-02	1.128734E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 261
SEVEN TENTHS, -250 DEG
LOAD STEP = 8.00000E+00 SUBCASE 70

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	8.346325E-03	1.046515E-06	4.075064E-01	1.541497E-04	9.846845E-02	-1.029221E-06
2	G	1.278159E-02	2.711814E-02	4.795977E-01	-2.314127E-01	-2.623229E-02	1.765046E-02
3	G	1.642687E-02	3.258977E-02	4.766306E-01	-1.743406E-01	3.421286E-02	2.826468E-03
4	G	1.901155E-02	3.031298E-02	4.187495E-01	-1.334126E-01	1.428167E-01	-1.051505E-02
5	G	1.707527E-02	2.294057E-02	3.160670E-01	-7.817189E-02	1.260781E-01	-8.220783E-03
6	G	1.086465E-02	1.267801E-02	1.776355E-01	-1.240217E-01	3.191876E-01	-2.507161E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.114069E-02	2.398709E-02	4.548975E-01	-1.712053E-01	-5.361531E-02	2.285293E-02
9	G	1.426772E-02	2.904027E-02	4.389455E-01	-1.311388E-01	5.090524E-02	1.270689E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 262
EIGHT TENTHS, -250 DEG
LOAD STEP = 9.00000E+00 SUBCASE 80

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.095855E-03	1.254989E-06	4.262871E-01	1.904004E-04	1.127029E-01	6.970729E-08
2	G	1.394655E-02	2.963027E-02	5.014008E-01	-2.425510E-01	-2.734969E-02	1.927006E-02
3	G	1.794770E-02	3.561472E-02	4.982809E-01	-1.826111E-01	3.568601E-02	3.108719E-03
4	G	2.078265E-02	3.312986E-02	4.377706E-01	-1.396932E-01	1.494083E-01	-1.152138E-02
5	G	1.866725E-02	2.507009E-02	3.303940E-01	-8.115994E-02	1.317835E-01	-8.997073E-03
6	G	1.189598E-02	1.386312E-02	1.857687E-01	-1.303245E-01	3.332025E-01	-2.747259E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.216085E-02	2.619904E-02	4.755576E-01	-1.789710E-01	-5.585559E-02	2.495697E-02
9	G	1.558484E-02	3.172875E-02	4.588593E-01	-1.369599E-01	5.310702E-02	1.411913E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 263
NINE TENTHS, -250 DEG
LOAD STEP = 1.00000E+01 SUBCASE 90

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.809917E-03	1.473275E-06	4.435698E-01	2.290088E-04	1.262997E-01	1.574900E-06
2	G	1.505981E-02	3.203600E-02	5.214252E-01	-2.527219E-01	-2.834184E-02	2.081959E-02
3	G	1.940292E-02	3.851359E-02	5.181640E-01	-1.901781E-01	3.702582E-02	3.383366E-03
4	G	2.247912E-02	3.583109E-02	4.552425E-01	-1.454380E-01	1.554513E-01	-1.248497E-02
5	G	2.019345E-02	2.711329E-02	3.435592E-01	-8.391847E-02	1.370284E-01	-9.742486E-03
6	G	1.288595E-02	1.500113E-02	1.932445E-01	-1.361596E-01	3.460325E-01	-2.978459E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.313524E-02	2.831805E-02	4.945412E-01	-1.860801E-01	-5.786016E-02	2.696634E-02
9	G	1.684515E-02	3.430612E-02	4.771570E-01	-1.422780E-01	5.510661E-02	1.552819E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 264
ONE, -250 DEG
LOAD STEP = 1.10000E+01 SUBCASE 101

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	1.049352E-02	1.700713E-06	4.596237E-01	2.698010E-04	1.393193E-01	3.499352E-06
2	G	1.612878E-02	3.435071E-02	5.399908E-01	-2.620993E-01	-2.922709E-02	2.230809E-02
3	G	2.080198E-02	4.130469E-02	5.365972E-01	-1.971671E-01	3.825486E-02	3.651954E-03
4	G	2.411178E-02	3.843355E-02	4.714434E-01	-1.507441E-01	1.610451E-01	-1.341195E-02
5	G	2.166348E-02	2.908282E-02	3.557711E-01	-8.648844E-02	1.418951E-01	-1.046149E-02
6	G	1.384060E-02	1.609895E-02	2.001811E-01	-1.416113E-01	3.578911E-01	-3.202097E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.407038E-02	3.035763E-02	5.121496E-01	-1.926505E-01	-5.966892E-02	2.889393E-02
9	G	1.805685E-02	3.678860E-02	4.941291E-01	-1.471836E-01	5.694041E-02	1.693669E-03

LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 255

ONE TENTH, -300 DEG
LOAD STEP = 2.00000E+00

SUBCASE 10

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	2.316669E-03	7.475861E-08	2.101518E-01	4.899284E-06	-2.923653E-03	-5.608063E-07
2	G	3.521375E-03	7.415888E-03	2.484362E-01	-1.112821E-01	-1.408487E-02	5.039105E-03
3	G	4.420004E-03	8.934611E-03	2.471527E-01	-8.638688E-02	1.819098E-02	7.299841E-04
4	G	5.090829E-03	8.335573E-03	2.173218E-01	-6.589039E-02	7.240821E-02	-2.667701E-03
5	G	4.599148E-03	6.364242E-03	1.646957E-01	-4.721436E-02	6.559100E-02	-2.191554E-03
6	G	2.847666E-03	3.503786E-03	9.191887E-02	-6.068237E-02	1.684658E-01	-6.725298E-03
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	3.025678E-03	6.631402E-03	2.36224E-01	-8.780676E-02	-2.800854E-02	6.266480E-03
9	G	3.857235E-03	8.014949E-03	2.281882E-01	-6.815975E-02	2.635139E-02	3.518716E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 256

TWO TENTHS, -300 DEG
LOAD STEP = 3.00000E+00

SUBCASE 20

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	3.673996E-03	1.910591E-07	2.663724E-01	1.863860E-05	1.548181E-02	-1.236910E-06
2	G	5.590672E-03	1.177810E-02	3.146017E-01	-1.457074E-01	-1.729724E-02	7.800407E-03
3	G	7.083566E-03	1.416413E-02	3.128130E-01	-1.112938E-01	2.268621E-02	1.192656E-03
4	G	8.169603E-03	1.319213E-02	2.749451E-01	-8.531338E-02	9.269084E-02	-4.387623E-03
5	G	7.355652E-03	1.002649E-02	2.079530E-01	-5.601740E-02	8.284128E-02	-3.511222E-03
6	G	4.606365E-03	5.523964E-03	1.163871E-01	-7.833627E-02	2.120020E-01	-1.072378E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	4.835389E-03	1.048331E-02	2.987851E-01	-1.118357E-01	-3.555569E-02	9.944486E-03
9	G	6.170563E-03	1.267103E-02	2.884890E-01	-8.637503E-02	3.361492E-02	5.272790E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 257

THREE TENTHS, -300 DEG
LOAD STEP = 4.00000E+00

SUBCASE 30

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	4.801068E-03	3.252617E-07	3.057149E-01	3.766801E-05	3.379554E-02	-1.783049E-06
2	G	7.313522E-03	1.543739E-02	3.607984E-01	-1.699495E-01	-1.973660E-02	1.012669E-02
3	G	9.311859E-03	1.855360E-02	3.586811E-01	-1.289925E-01	2.586740E-02	1.581433E-03
4	G	1.074935E-02	1.726787E-02	3.152019E-01	-9.892787E-02	1.068294E-01	-5.846417E-03
5	G	9.665619E-03	1.309985E-02	2.381968E-01	-6.217523E-02	9.486917E-02	-4.621909E-03
6	G	6.087971E-03	7.223889E-03	1.335161E-01	-9.097851E-02	2.422662E-01	-1.411057E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	6.345398E-03	1.370622E-02	3.424575E-01	-1.286006E-01	-4.078369E-02	1.302968E-02
9	G	8.102600E-03	1.657090E-02	3.305802E-01	-9.906612E-02	3.858129E-02	6.852927E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 258

FOUR TENTHS, -300 DEG
LOAD STEP = 5.00000E+00

SUBCASE 40

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	5.798093E-03	4.897053E-07	3.370163E-01	6.209256E-05	5.128177E-02	-2.072546E-06
2	G	8.842313E-03	1.870095E-02	3.974676E-01	-1.892077E-01	-2.174588E-02	1.221289E-02
3	G	1.129538E-02	2.247107E-02	3.950959E-01	-1.431539E-01	2.842355E-02	1.927907E-03
4	G	1.304859E-02	2.090585E-02	3.471608E-01	-1.096977E-01	1.180214E-01	-7.152503E-03
5	G	1.172531E-02	1.584397E-02	2.622184E-01	-6.707784E-02	1.044289E-01	-5.616602E-03
6	G	7.413041E-03	8.744391E-03	1.471295E-01	-1.011473E-01	2.661727E-01	-1.715189E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	7.686405E-03	1.657741E-02	3.771280E-01	-1.418903E-01	-4.485977E-02	1.577875E-02
9	G	9.820923E-03	2.004834E-02	3.639919E-01	-1.090897E-01	4.245229E-02	8.361682E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 259

FIVE TENTHS, -300 DEG
LOAD STEP = 6.00000E+00

SUBCASE 50

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	6.706915E-03	6.629033E-07	3.634476E-01	8.973843E-05	6.785949E-02	-2.069897E-06
2	G	1.024112E-02	2.169487E-02	4.283493E-01	-2.052643E-01	-2.343149E-02	1.413599E-02
3	G	1.311315E-02	2.606799E-02	4.257627E-01	-1.549822E-01	3.056152E-02	2.250603E-03
4	G	1.515834E-02	2.424884E-02	3.740852E-01	-1.187102E-01	1.274156E-01	-8.351570E-03
5	G	1.361682E-02	1.836698E-02	2.824689E-01	-7.123186E-02	1.124916E-01	-6.532928E-03
6	G	8.632645E-03	1.014429E-02	1.586111E-01	-1.098103E-01	2.862281E-01	-1.996215E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	8.912839E-03	1.921188E-02	4.063483E-01	-1.530020E-01	-4.824905E-02	1.830122E-02
9	G	1.139555E-02	2.324251E-02	3.921556E-01	-1.174691E-01	4.568096E-02	9.819777E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 260

SIX TENTHS, -300 DEG
LOAD STEP = 7.00000E+00

SUBCASE 60

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	7.550181E-03	8.491492E-07	3.865563E-01	1.205873E-04	8.358051E-02	-1.727039E-06
2	G	1.154341E-02	2.448983E-02	4.552868E-01	-2.191803E-01	-2.488471E-02	1.593588E-02
3	G	1.480833E-02	2.942852E-02	4.525124E-01	-1.652647E-01	3.241730E-02	2.555707E-03
4	G	1.712813E-02	2.737415E-02	3.975760E-01	-1.265323E-01	1.355882E-01	-9.471395E-03
5	G	1.538432E-02	2.072701E-02	3.001456E-01	-7.487767E-02	1.195343E-01	-7.391405E-03
6	G	9.774355E-03	1.145525E-02	1.686373E-01	-1.174421E-01	3.036556E-01	-2.260237E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.005427E-02	2.167159E-02	4.318500E-01	-1.626558E-01	-5.114626E-02	2.065272E-02
9	G	1.286379E-02	2.622740E-02	4.167356E-01	-1.247348E-01	4.846342E-02	1.125302E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 261

SEVEN TENTHS, -300 DEG
LOAD STEP = 8.00000E+00

SUBCASE 70

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	8.341864E-03	1.047054E-06	4.072273E-01	1.542805E-04	9.852006E-02	-1.015523E-06
2	G	1.277001E-02	2.712888E-02	4.793307E-01	-2.315252E-01	-2.615458E-02	1.763718E-02
3	G	1.640742E-02	3.260398E-02	4.763878E-01	-1.744100E-01	3.406188E-02	2.847915E-03
4	G	1.898836E-02	3.032927E-02	4.185472E-01	-1.334820E-01	1.428662E-01	-1.052882E-02
5	G	1.705494E-02	2.295976E-02	3.159336E-01	-7.815149E-02	1.258280E-01	-8.204577E-03
6	G	1.085517E-02	1.269673E-02	1.775954E-01	-1.243166E-01	3.191558E-01	-2.511031E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.112892E-02	2.399461E-02	4.546236E-01	-1.712417E-01	-5.367396E-02	2.286852E-02
9	G	1.424872E-02	2.904871E-02	4.386864E-01	-1.311833E-01	5.091779E-02	1.267248E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 262

EIGHT TENTHS, -300 DEG
LOAD STEP = 9.00000E+00

SUBCASE 80

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.091364E-03	1.255583E-06	4.260199E-01	1.905454E-04	1.127534E-01	8.593555E-08
2	G	1.393494E-02	2.964092E-02	5.011449E-01	-2.426592E-01	-2.727458E-02	1.925650E-02
3	G	1.792821E-02	3.562883E-02	4.980482E-01	-1.826771E-01	3.554089E-02	3.130333E-03
4	G	2.075942E-02	3.314606E-02	4.375767E-01	-1.397603E-01	1.494561E-01	-1.153528E-02
5	G	1.864686E-02	2.508918E-02	3.302658E-01	-8.113860E-02	1.315438E-01	-1.980869E-03
6	G	1.188650E-02	1.388182E-02	1.857302E-01	-1.306075E-01	3.331713E-01	-2.751128E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.214906E-02	2.620648E-02	4.752952E-01	-1.790056E-01	-5.591145E-02	2.497249E-02
9	G	1.556581E-02	3.173710E-02	4.586110E-01	-1.370023E-01	5.311904E-02	1.408477E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 263

NINE TENTHS, -300 DEG
LOAD STEP = 1.00000E+01

SUBCASE 90

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.805398E-03	1.473923E-06	4.433127E-01	2.291672E-04	1.263490E-01	1.593748E-06
2	G	1.504816E-02	3.204658E-02	5.211788E-01	-2.528262E-01	-2.826901E-02	2.080580E-02
3	G	1.938339E-02	3.852761E-02	5.179397E-01	-1.902413E-01	3.688573E-02	3.405114E-03
4	G	2.245585E-02	3.584721E-02	4.550557E-01	-1.455031E-01	1.554977E-01	-1.249897E-02
5	G	2.017301E-02	2.713229E-02	3.434355E-01	-8.389647E-02	1.367977E-01	-9.726280E-03
6	G	1.287646E-02	1.501980E-02	1.932074E-01	-1.364324E-01	3.460020E-01	-2.982326E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.312342E-02	2.832541E-02	4.942884E-01	-1.861130E-01	-5.791359E-02	2.698179E-02
9	G	1.682608E-02	3.431439E-02	4.769179E-01	-1.423186E-01	5.511813E-02	1.549396E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 264

ONE, -300 DEG
LOAD STEP = 1.10000E+01

SUBCASE 101

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	1.048897E-02	1.701413E-06	4.593752E-01	2.699723E-04	1.393674E-01	3.520899E-06
2	G	1.611709E-02	3.436121E-02	5.397523E-01	-2.622001E-01	-2.915629E-02	2.229410E-02
3	G	2.078241E-02	4.131861E-02	5.363801E-01	-1.972278E-01	3.811916E-02	3.673812E-03
4	G	2.408846E-02	3.844958E-02	4.712626E-01	-1.508072E-01	1.610902E-01	-1.342602E-02
5	G	2.164298E-02	2.910175E-02	3.556515E-01	-8.646598E-02	1.416722E-01	-1.044528E-02
6	G	1.383111E-02	1.611760E-02	2.001451E-01	-1.418753E-01	3.578611E-01	-3.205962E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.405853E-02	3.036493E-02	5.119051E-01	-1.926821E-01	-5.972024E-02	2.890931E-02
9	G	1.803776E-02	3.679679E-02	4.938978E-01	-1.472225E-01	5.695147E-02	1.690265E-03

LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 255

ONE TENTH, -350 DEG
LOAD STEP = 2.00000E+00

SUBCASE 10

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	2.312457E-03	7.485583E-08	2.096203E-01	4.925781E-06	-2.872987E-03	-5.594613E-07
2	G	3.510286E-03	7.427397E-03	2.479310E-01	-1.114530E-01	-1.397600E-02	5.032715E-03
3	G	4.400928E-03	8.949907E-03	2.466954E-01	-8.652706E-02	1.793946E-02	7.473367E-04
4	G	5.068014E-03	8.352903E-03	2.169402E-01	-6.598334E-02	7.246548E-02	-2.677941E-03
5	G	4.579475E-03	6.384779E-03	1.644517E-01	-4.725303E-02	6.513751E-02	-2.175384E-03
6	G	2.837709E-03	3.522654E-03	9.183972E-02	-6.119790E-02	1.684113E-01	-6.763017E-03
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	3.014166E-03	6.639925E-03	2.357052E-01	-8.788177E-02	-2.811258E-02	6.281768E-03
9	G	3.838546E-03	8.024569E-03	2.276989E-01	-6.824119E-02	2.636091E-02	3.494884E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 256

TWO TENTHS, -350 DEG
LOAD STEP = 3.00000E+00

SUBCASE 20

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	3.669722E-03	1.913565E-07	2.659505E-01	1.868937E-05	1.553466E-02	-1.233905E-06
2	G	5.579437E-03	1.178934E-02	3.142000E-01	-1.458566E-01	-1.719600E-02	7.790956E-03
3	G	7.064371E-03	1.417904E-02	3.124486E-01	-1.113991E-01	2.247311E-02	1.211864E-03
4	G	8.146666E-03	1.320910E-02	2.746414E-01	-8.539881E-02	9.274997E-02	-4.399336E-03
5	G	7.335776E-03	1.004654E-02	2.077566E-01	-5.602194E-02	8.247127E-02	-3.494973E-03
6	G	4.596677E-03	5.542822E-03	1.163259E-01	-7.876331E-02	2.119589E-01	-1.076208E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	4.823809E-03	1.049149E-02	2.983736E-01	-1.118928E-01	-3.564332E-02	9.960175E-03
9	G	6.151784E-03	1.268025E-02	2.880998E-01	-8.644105E-02	3.362919E-02	5.242876E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 257
THREE TENTHS, -350 DEG
LOAD STEP = 4.00000E+00 SUBCASE 30

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	4.796747E-03	3.241819E-07	3.053461E-01	3.762563E-05	3.384986E-02	-1.780094E-06
2	G	7.302183E-03	1.544852E-02	3.604470E-01	-1.700882E-01	-1.964265E-02	1.011578E-02
3	G	9.292597E-03	1.856833E-02	3.583622E-01	-1.290856E-01	2.567590E-02	1.601484E-03
4	G	1.072635E-02	1.728465E-02	3.149361E-01	-9.900946E-02	1.068868E-01	-5.858966E-03
5	G	9.645611E-03	1.311964E-02	2.380237E-01	-6.216765E-02	9.454251E-02	-4.605682E-02
6	G	6.078380E-03	7.242724E-03	1.334631E-01	-9.135833E-02	2.422276E-01	-1.414908E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	6.333775E-03	1.371421E-02	3.420972E-01	-1.286506E-01	-4.086133E-02	1.304544E-02
9	G	8.083759E-03	1.657988E-02	3.302393E-01	-9.912498E-02	3.859578E-02	6.820686E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 258
FOUR TENTHS, -350 DEG
LOAD STEP = 5.00000E+00 SUBCASE 40

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	5.793731E-03	4.900643E-07	3.366809E-01	6.217619E-05	5.133621E-02	-2.065738E-06
2	G	8.830904E-03	1.871196E-02	3.971477E-01	-1.893373E-01	-2.165729E-02	1.220107E-02
3	G	1.127606E-02	2.248565E-02	3.948053E-01	-1.432378E-01	2.824644E-02	1.948511E-03
4	G	1.302554E-02	2.092249E-02	3.469187E-01	-1.097756E-01	1.180766E-01	-7.165544E-03
5	G	1.170520E-02	1.586356E-02	2.620601E-01	-6.706432E-02	1.041303E-01	-5.600395E-03
6	G	7.403498E-03	8.763202E-03	1.470814E-01	-1.014962E-01	2.661367E-01	-1.719052E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	7.674742E-03	1.658525E-02	3.767999E-01	-1.419351E-01	-4.493082E-02	1.579452E-02
9	G	9.802036E-03	2.005716E-02	3.636815E-01	-1.091435E-01	4.246651E-02	8.328207E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 259
FIVE TENTHS, -350 DEG
LOAD STEP = 6.00000E+00 SUBCASE 50

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	6.702518E-03	6.633241E-07	3.631360E-01	8.983901E-05	6.791331E-02	-2.060927E-06
2	G	1.022965E-02	2.170579E-02	4.280517E-01	-2.053870E-01	-2.334726E-02	1.412356E-02
3	G	1.309378E-02	2.608244E-02	4.254923E-01	-1.550600E-01	3.039519E-02	2.271574E-03
4	G	1.513524E-02	2.426536E-02	3.738600E-01	-1.187848E-01	1.274686E-01	-8.364941E-03
5	G	1.359662E-02	1.838643E-02	2.823210E-01	-7.121494E-02	1.122133E-01	-6.516734E-03
6	G	8.623126E-03	1.016308E-02	1.585664E-01	-1.101366E-01	2.861938E-01	-2.000082E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	8.901141E-03	1.921961E-02	4.060431E-01	-1.530433E-01	-4.831504E-02	1.831696E-02
9	G	1.137662E-02	2.325119E-02	3.918668E-01	-1.175192E-01	4.569464E-02	9.785724E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 260
SIX TENTHS, -350 DEG
LOAD STEP = 7.00000E+00 SUBCASE 60

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	7.545751E-03	8.496301E-07	3.862627E-01	1.207037E-04	8.363338E-02	-1.715757E-06
2	G	1.153189E-02	2.450067E-02	4.550062E-01	-2.192973E-01	-2.480407E-02	1.592299E-02
3	G	1.478892E-02	2.944286E-02	4.522573E-01	-1.653376E-01	3.225946E-02	2.576948E-03
4	G	1.710498E-02	2.739056E-02	3.973635E-01	-1.266041E-01	1.356393E-01	-9.484997E-03
5	G	1.536405E-02	2.074633E-02	3.000057E-01	-7.485864E-02	1.192717E-01	-7.375218E-03
6	G	9.764848E-03	1.147401E-02	1.685952E-01	-1.177508E-01	3.036226E-01	-2.264106E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.004254E-02	2.167922E-02	4.315621E-01	-1.626943E-01	-5.120823E-02	2.066841E-02
9	G	1.284483E-02	2.623597E-02	4.164633E-01	-1.247818E-01	4.847651E-02	1.121870E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 261
SEVEN TENTHS, -350 DEG
LOAD STEP = 8.00000E+00 SUBCASE 70

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	8.337401E-03	1.047593E-06	4.069482E-01	1.544118E-04	9.857182E-02	-1.001807E-06
2	G	1.275845E-02	2.713963E-02	4.790637E-01	-2.316373E-01	-2.607696E-02	1.762393E-02
3	G	1.638796E-02	3.261821E-02	4.761450E-01	-1.744791E-01	3.391099E-02	2.869364E-03
4	G	1.896516E-02	3.034558E-02	4.183449E-01	-1.335513E-01	1.429155E-01	-1.054259E-02
5	G	1.703461E-02	2.297897E-02	3.158001E-01	-7.813107E-02	1.255780E-01	-8.188393E-03
6	G	1.084567E-02	1.271547E-02	1.775553E-01	-1.246111E-01	3.191238E-01	-2.514901E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.111716E-02	2.400215E-02	4.543496E-01	-1.712781E-01	-5.373261E-02	2.288414E-02
9	G	1.422972E-02	2.905718E-02	4.384272E-01	-1.312279E-01	5.093031E-02	1.263810E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 262
EIGHT TENTHS, -350 DEG
LOAD STEP = 9.00000E+00 SUBCASE 80

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.086872E-03	1.256178E-06	4.257527E-01	1.906908E-04	1.128040E-01	1.021879E-07
2	G	1.392333E-02	2.965159E-02	5.008889E-01	-2.427670E-01	-2.719956E-02	1.924296E-02
3	G	1.790871E-02	3.564296E-02	4.978154E-01	-1.827429E-01	3.539584E-02	3.151947E-03
4	G	2.073618E-02	3.316228E-02	4.373828E-01	-1.398273E-01	1.495039E-01	-1.154918E-02
5	G	1.862647E-02	2.510830E-02	3.301377E-01	-8.111725E-02	1.313043E-01	-8.964685E-03
6	G	1.187700E-02	1.390053E-02	1.856917E-01	-1.308901E-01	3.331401E-01	-2.754997E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.213726E-02	2.621394E-02	4.750327E-01	-1.790401E-01	-5.596730E-02	2.498803E-02
9	G	1.554677E-02	3.174549E-02	4.583627E-01	-1.370447E-01	5.313103E-02	1.405044E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 263

NINE TENTHS, -350 DEG
LOAD STEP = 1.00000E+01

SUBCASE 90

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.800877E-03	1.474571E-06	4.430555E-01	2.293261E-04	1.263984E-01	1.612626E-06
2	G	1.503651E-02	3.205717E-02	5.209322E-01	-2.529303E-01	-2.819626E-02	2.079203E-02
3	G	1.936385E-02	3.854164E-02	5.177153E-01	-1.903044E-01	3.674570E-02	3.426862E-03
4	G	2.243257E-02	3.586334E-02	4.548688E-01	-1.455681E-01	1.555440E-01	-1.251296E-02
5	G	2.015255E-02	2.715132E-02	3.433118E-01	-8.387449E-02	1.365672E-01	-9.710093E-03
6	G	1.286696E-02	1.503849E-02	1.931702E-01	-1.367049E-01	3.459714E-01	-2.986194E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.311159E-02	2.833280E-02	4.940356E-01	-1.861460E-01	-5.796701E-02	2.699725E-02
9	G	1.680702E-02	3.432268E-02	4.766788E-01	-1.423591E-01	5.512961E-02	1.545975E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 264

ONE, -350 DEG
LOAD STEP = 1.10000E+01

SUBCASE 101

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	1.048443E-02	1.702114E-06	4.591266E-01	2.701441E-04	1.394157E-01	3.542479E-06
2	G	1.610541E-02	3.437173E-02	5.395138E-01	-2.623009E-01	-2.908555E-02	2.228014E-02
3	G	2.076284E-02	4.133256E-02	5.361630E-01	-1.972885E-01	3.798351E-02	3.695670E-03
4	G	2.406515E-02	3.846563E-02	4.710818E-01	-1.508704E-01	1.611353E-01	-1.344009E-02
5	G	2.162247E-02	2.912069E-02	3.555314E-01	-8.644354E-02	1.414494E-01	-1.042909E-02
6	G	1.382159E-02	1.613627E-02	2.001090E-01	-1.421390E-01	3.578310E-01	-3.209827E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.404668E-02	3.037225E-02	5.116606E-01	-1.927136E-01	-5.977153E-02	2.892469E-02
9	G	1.801866E-02	3.680501E-02	4.936665E-01	-1.472614E-01	5.696248E-02	1.686863E-03

LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 255

ONE TENTH, -400 DEG
LOAD STEP = 2.00000E+00

SUBCASE 10

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	2.308255E-03	7.494755E-08	2.090882E-01	4.952560E-06	-2.820690E-03	-5.579416E-07
2	G	3.499173E-03	7.439137E-03	2.474265E-01	-1.116330E-01	-1.386989E-02	5.026489E-03
3	G	4.381892E-03	8.965499E-03	2.462397E-01	-8.668194E-02	1.768865E-02	7.645553E-04
4	G	5.045276E-03	8.370449E-03	2.165598E-01	-6.608344E-02	7.252375E-02	-2.688557E-03
5	G	4.559818E-03	6.405460E-03	1.642081E-01	-4.729382E-02	6.468567E-02	-2.159282E-03
6	G	2.827697E-03	3.541601E-03	9.176043E-02	-6.171228E-02	1.683564E-01	-6.800756E-03
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	3.002666E-03	6.648575E-03	2.351877E-01	-8.796283E-02	-2.821519E-02	6.297006E-03
9	G	3.819854E-03	8.034292E-03	2.272086E-01	-6.832678E-02	2.636920E-02	3.471074E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 256

TWO TENTHS, -400 DEG
LOAD STEP = 3.00000E+00

SUBCASE 20

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	3.665449E-03	1.915687E-07	2.655284E-01	1.873404E-05	1.558788E-02	-1.230821E-06
2	G	5.568208E-03	1.180066E-02	3.137983E-01	-1.460064E-01	-1.709542E-02	7.781586E-03
3	G	7.045182E-03	1.419402E-02	3.120842E-01	-1.115054E-01	2.226060E-02	1.231041E-03
4	G	8.123734E-03	1.322614E-02	2.743376E-01	-8.548456E-02	9.280857E-02	-4.411058E-03
5	G	7.315885E-03	1.006665E-02	2.075602E-01	-5.602675E-02	8.210197E-02	-3.478763E-03
6	G	4.586940E-03	5.561711E-03	1.162645E-01	-7.918912E-02	2.119152E-01	-1.080039E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	4.812235E-03	1.049972E-02	2.979619E-01	-1.119504E-01	-3.573059E-02	9.975884E-03
9	G	6.133011E-03	1.268953E-02	2.877105E-01	-8.650734E-02	3.364302E-02	5.213219E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 257

THREE TENTHS, -400 DEG
LOAD STEP = 4.00000E+00

SUBCASE 30

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	4.792425E-03	3.214724E-07	3.049771E-01	3.745417E-05	3.390450E-02	-1.779322E-06
2	G	7.290816E-03	1.545979E-02	3.600962E-01	-1.702339E-01	-1.955030E-02	1.010491E-02
3	G	9.273359E-03	1.858319E-02	3.580440E-01	-1.291861E-01	2.548607E-02	1.621375E-03
4	G	1.070338E-02	1.730151E-02	3.146705E-01	-9.909234E-02	1.069444E-01	-5.871600E-03
5	G	9.625591E-03	1.313946E-02	2.378505E-01	-6.216011E-02	9.421655E-02	-4.589502E-03
6	G	6.068749E-03	7.261581E-03	1.334099E-01	-9.173707E-02	2.421885E-01	-1.418757E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	6.322161E-03	1.372223E-02	3.417366E-01	-1.287041E-01	-4.093736E-02	1.306110E-02
9	G	8.064911E-03	1.658888E-02	3.298979E-01	-9.918506E-02	3.860906E-02	6.789217E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 258

FOUR TENTHS, -400 DEG
LOAD STEP = 5.00000E+00

SUBCASE 40

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	5.789370E-03	4.904277E-07	3.363454E-01	6.226011E-05	5.139089E-02	-2.058912E-06
2	G	8.819500E-03	1.872302E-02	3.968277E-01	-1.894671E-01	-2.156900E-02	1.218930E-02
3	G	1.125674E-02	2.250027E-02	3.945147E-01	-1.433220E-01	2.806960E-02	1.969098E-03
4	G	1.300249E-02	2.093918E-02	3.466766E-01	-1.098535E-01	1.181314E-01	-7.178590E-03
5	G	1.168508E-02	1.588319E-02	2.619017E-01	-6.705094E-02	1.038320E-01	-5.584215E-03
6	G	7.393923E-03	8.782032E-03	1.470332E-01	-1.018444E-01	2.661004E-01	-1.722915E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	7.663083E-03	1.659312E-02	3.764717E-01	-1.419801E-01	-4.500171E-02	1.581031E-02
9	G	9.783152E-03	2.006602E-02	3.633710E-01	-1.091974E-01	4.248053E-02	8.294894E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 259

FIVE TENTHS, -400 DEG
LOAD STEP = 6.00000E+00

SUBCASE 50

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	6.698120E-03	6.637467E-07	3.628242E-01	8.993992E-05	6.796733E-02	-2.051945E-06
2	G	1.021819E-02	2.171674E-02	4.277541E-01	-2.055098E-01	-2.326327E-02	1.411116E-02
3	G	1.307441E-02	2.609693E-02	4.252218E-01	-1.551380E-01	3.022908E-02	2.292530E-03
4	G	1.511214E-02	2.428192E-02	3.736347E-01	-1.188595E-01	1.275214E-01	-8.378317E-03
5	G	1.357642E-02	1.840590E-02	2.821731E-01	-7.119813E-02	1.119353E-01	-6.500564E-03
6	G	8.613579E-03	1.018188E-02	1.585216E-01	-1.104623E-01	2.861593E-01	-2.003950E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	8.889445E-03	1.922737E-02	4.057377E-01	-1.530848E-01	-4.838090E-02	1.833270E-02
9	G	1.135769E-02	2.325991E-02	3.915779E-01	-1.175693E-01	4.570814E-02	9.751815E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 260

SIX TENTHS, -400 DEG
LOAD STEP = 7.00000E+00

SUBCASE 60

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	7.541319E-03	8.501127E-07	3.859691E-01	1.208205E-04	8.368642E-02	-1.704459E-06
2	G	1.152037E-02	2.451153E-02	4.547256E-01	-2.194144E-01	-2.472362E-02	1.591013E-02
3	G	1.476950E-02	2.945723E-02	4.520022E-01	-1.654108E-01	3.210180E-02	2.598176E-03
4	G	1.708183E-02	2.740701E-02	3.971510E-01	-1.266759E-01	1.356901E-01	-9.498605E-03
5	G	1.534377E-02	2.076568E-02	2.998658E-01	-7.483970E-02	1.190093E-01	-7.359053E-03
6	G	9.755315E-03	1.149278E-02	1.685529E-01	-1.180591E-01	3.035894E-01	-2.267976E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.003081E-02	2.168687E-02	4.312742E-01	-1.627330E-01	-5.127009E-02	2.068410E-02
9	G	1.282586E-02	2.624457E-02	4.161909E-01	-1.248289E-01	4.848946E-02	1.118452E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 261

SEVEN TENTHS, -400 DEG
LOAD STEP = 8.00000E+00

SUBCASE 70

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	8.332939E-03	1.048133E-06	4.066690E-01	1.545435E-04	9.862373E-02	-9.880730E-07
2	G	1.274688E-02	2.715041E-02	4.787965E-01	-2.317495E-01	-2.599951E-02	1.761071E-02
3	G	1.636851E-02	3.263247E-02	4.759021E-01	-1.745484E-01	3.376025E-02	2.890802E-03
4	G	1.894197E-02	3.036193E-02	4.181426E-01	-1.336206E-01	1.429647E-01	-1.055637E-02
5	G	1.701426E-02	2.299821E-02	3.156666E-01	-7.811073E-02	1.253282E-01	-8.172230E-03
6	G	1.083614E-02	1.273421E-02	1.775150E-01	-1.249052E-01	3.190916E-01	-2.518772E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.110540E-02	2.400971E-02	4.540756E-01	-1.713146E-01	-5.379117E-02	2.289976E-02
9	G	1.421072E-02	2.906568E-02	4.381680E-01	-1.312725E-01	5.094271E-02	1.260383E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 262

EIGHT TENTHS, -400 DEG
LOAD STEP = 9.00000E+00

SUBCASE 80

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.082381E-03	1.256774E-06	4.254853E-01	1.908366E-04	1.128547E-01	1.184614E-07
2	G	1.391173E-02	2.966229E-02	5.006329E-01	-2.428750E-01	-2.712469E-02	1.922946E-02
3	G	1.788922E-02	3.565712E-02	4.975825E-01	-1.828089E-01	3.525093E-02	3.173550E-03
4	G	2.071294E-02	3.317853E-02	4.371888E-01	-1.398944E-01	1.495515E-01	-1.156308E-02
5	G	1.860606E-02	2.512743E-02	3.300959E-01	-8.109596E-02	1.310650E-01	-8.948520E-03
6	G	1.186747E-02	1.391925E-02	1.856530E-01	-1.311724E-01	3.331087E-01	-2.758867E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.212547E-02	2.622142E-02	4.747701E-01	-1.790747E-01	-5.602306E-02	2.500358E-02
9	G	1.552774E-02	3.175389E-02	4.581144E-01	-1.370872E-01	5.314290E-02	1.401621E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 263

NINE TENTHS, -400 DEG
LOAD STEP = 1.00000E+01

SUBCASE 90

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.796358E-03	1.475222E-06	4.427982E-01	2.294853E-04	1.264479E-01	1.631528E-06
2	G	1.502486E-02	3.206779E-02	5.206856E-01	-2.530344E-01	-2.812365E-02	2.077829E-02
3	G	1.934432E-02	3.855571E-02	5.174910E-01	-1.903676E-01	3.660579E-02	3.448600E-03
4	G	2.240929E-02	3.587950E-02	4.546819E-01	-1.456332E-01	1.555902E-01	-1.252696E-02
5	G	2.013209E-02	2.717036E-02	3.431880E-01	-8.385254E-02	1.363368E-01	-9.693924E-03
6	G	1.285743E-02	1.505718E-02	1.931329E-01	-1.369771E-01	3.459406E-01	-2.990061E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.309977E-02	2.834020E-02	4.937827E-01	-1.861790E-01	-5.802036E-02	2.701272E-02
9	G	1.678795E-02	3.433100E-02	4.764395E-01	-1.423997E-01	5.514100E-02	1.542565E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 264

ONE, -400 DEG
LOAD STEP = 1.10000E+01

SUBCASE 101

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	1.047988E-02	1.702817E-06	4.588780E-01	2.703163E-04	1.394640E-01	3.564086E-06
2	G	1.609373E-02	3.438227E-02	5.392752E-01	-2.624017E-01	-2.901493E-02	2.226620E-02
3	G	2.074327E-02	4.134653E-02	5.359460E-01	-1.973493E-01	3.784797E-02	3.717520E-03
4	G	2.404183E-02	3.848171E-02	4.709010E-01	-1.509336E-01	1.611802E-01	-1.345416E-02
5	G	2.160195E-02	2.913965E-02	3.554115E-01	-8.642115E-02	1.412267E-01	-1.041291E-02
6	G	1.381206E-02	1.615494E-02	2.000729E-01	-1.424024E-01	3.578008E-01	-3.213693E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.403483E-02	3.037958E-02	5.114161E-01	-1.927453E-01	-5.982276E-02	2.894008E-02
9	G	1.799957E-02	3.681325E-02	4.934352E-01	-1.473004E-01	5.697341E-02	1.683470E-03

LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 255

ONE TENTH, -450 DEG
LOAD STEP = 2.00000E+00

SUBCASE 10

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	2.304088E-03	7.515781E-08	2.085542E-01	4.974300E-06	-2.776541E-03	-5.568507E-07
2	G	3.488095E-03	7.451091E-03	2.469207E-01	-1.118084E-01	-1.376341E-02	5.019781E-03
3	G	4.362812E-03	8.981237E-03	2.457813E-01	-8.681615E-02	1.744131E-02	7.825728E-04
4	G	5.022375E-03	8.388198E-03	2.161767E-01	-6.616744E-02	7.257900E-02	-2.698074E-03
5	G	4.540121E-03	6.426458E-03	1.639645E-01	-4.733540E-02	6.422859E-02	-2.142978E-03
6	G	2.817672E-03	3.560777E-03	9.168179E-02	-6.223441E-02	1.683041E-01	-6.839190E-03
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	2.991151E-03	6.657483E-03	2.346693E-01	-8.804253E-02	-2.832149E-02	6.312940E-03
9	G	3.801164E-03	8.044388E-03	2.267190E-01	-6.841060E-02	2.637788E-02	3.448799E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 256

TWO TENTHS, -450 DEG
LOAD STEP = 3.00000E+00

SUBCASE 20

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	3.661242E-03	1.918983E-07	2.651055E-01	1.879017E-05	1.564352E-02	-1.227963E-06
2	G	5.556697E-03	1.181292E-02	3.134026E-01	-1.462186E-01	-1.700501E-02	7.771819E-03
3	G	7.026229E-03	1.421000E-02	3.117279E-01	-1.116785E-01	2.205599E-02	1.249330E-03
4	G	8.101170E-03	1.324366E-02	2.740387E-01	-8.558998E-02	9.287065E-02	-4.423741E-03
5	G	7.296368E-03	1.008708E-02	2.073672E-01	-5.604057E-02	8.173344E-02	-3.462453E-03
6	G	4.577451E-03	5.580750E-03	1.162053E-01	-7.962316E-02	2.118756E-01	-1.083957E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	4.800749E-03	1.050809E-02	2.975496E-01	-1.120409E-01	-3.580775E-02	9.990525E-03
9	G	6.114198E-03	1.269871E-02	2.873178E-01	-8.658780E-02	3.364861E-02	5.187748E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 257

THREE TENTHS, -450 DEG
LOAD STEP = 4.00000E+00

SUBCASE 30

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	4.788151E-03	3.324142E-07	3.046080E-01	3.834717E-05	3.396193E-02	-1.760349E-06
2	G	7.279094E-03	1.547213E-02	3.597524E-01	-1.704506E-01	-1.947058E-02	1.009372E-02
3	G	9.254361E-03	1.859914E-02	3.577344E-01	-1.293625E-01	2.530883E-02	1.639888E-03
4	G	1.068067E-02	1.731869E-02	3.144083E-01	-9.919026E-02	1.070067E-01	-5.885233E-03
5	G	9.605717E-03	1.315943E-02	2.376786E-01	-6.215456E-02	9.389264E-02	-4.573410E-03
6	G	6.059187E-03	7.280503E-03	1.333572E-01	-9.211653E-02	2.421498E-01	-1.422616E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	6.310639E-03	1.373037E-02	3.413756E-01	-1.287934E-01	-4.099940E-02	1.307545E-02
9	G	8.045966E-03	1.659768E-02	3.295526E-01	-9.925777E-02	3.861241E-02	6.763845E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 258

FOUR TENTHS, -450 DEG
LOAD STEP = 5.00000E+00

SUBCASE 40

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	5.785025E-03	4.907810E-07	3.360096E-01	6.234580E-05	5.144604E-02	-2.052146E-06
2	G	8.808040E-03	1.873430E-02	3.965086E-01	-1.896074E-01	-2.148250E-02	1.217748E-02
3	G	1.123748E-02	2.251513E-02	3.942254E-01	-1.434174E-01	2.789405E-02	1.989497E-02
4	G	1.297953E-02	2.095599E-02	3.464352E-01	-1.099349E-01	1.181866E-01	-7.191845E-03
5	G	1.166504E-02	1.590292E-02	2.617438E-01	-6.703928E-02	1.035341E-01	-5.568025E-03
6	G	7.384393E-03	8.800912E-03	1.469853E-01	-1.021938E-01	2.660647E-01	-1.726799E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	7.651448E-03	1.660105E-02	3.761432E-01	-1.420305E-01	-4.507072E-02	1.582584E-02
9	G	9.764264E-03	2.007488E-02	3.630598E-01	-1.092535E-01	4.249289E-02	8.262810E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 259

FIVE TENTHS, -450 DEG
LOAD STEP = 6.00000E+00

SUBCASE 50

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	6.693732E-03	6.641853E-07	3.625123E-01	9.004123E-05	6.802158E-02	-2.042921E-06
2	G	1.020669E-02	2.172784E-02	4.274569E-01	-2.056382E-01	-2.318031E-02	1.409876E-02
3	G	1.305508E-02	2.611157E-02	4.249520E-01	-1.552219E-01	3.006373E-02	2.313373E-03
4	G	1.508909E-02	2.429856E-02	3.734098E-01	-1.189360E-01	1.275742E-01	-8.391808E-03
5	G	1.355626E-02	1.842544E-02	2.820254E-01	-7.118223E-02	1.116576E-01	-6.484400E-03
6	G	8.604050E-03	1.020072E-02	1.584769E-01	-1.107884E-01	2.861250E-01	-2.007828E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	8.877765E-03	1.923516E-02	4.054322E-01	-1.531291E-01	-4.844568E-02	1.834830E-02
9	G	1.133877E-02	2.326864E-02	3.912886E-01	-1.176206E-01	4.572067E-02	9.718709E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 260

SIX TENTHS, -450 DEG
LOAD STEP = 7.00000E+00

SUBCASE 60

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	7.536894E-03	8.506073E-07	3.856753E-01	1.209374E-04	8.373959E-02	-1.693135E-06
2	G	1.150884E-02	2.452249E-02	4.544452E-01	-2.195349E-01	-2.464387E-02	1.589728E-02
3	G	1.475011E-02	2.947171E-02	4.517474E-01	-1.654876E-01	3.194468E-02	2.619324E-03
4	G	1.705872E-02	2.742351E-02	3.969387E-01	-1.267488E-01	1.357410E-01	-9.512282E-03
5	G	1.532352E-02	2.078507E-02	2.997260E-01	-7.482130E-02	1.187472E-01	-7.342902E-03
6	G	9.745788E-03	1.151158E-02	1.685107E-01	-1.183673E-01	3.035562E-01	-2.271851E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.001909E-02	2.169455E-02	4.309862E-01	-1.627735E-01	-5.133123E-02	2.069969E-02
9	G	1.280690E-02	2.625319E-02	4.159183E-01	-1.248767E-01	4.850174E-02	1.115094E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 261
SEVEN TENTHS, -450 DEG
LOAD STEP = 8.00000E+00 SUBCASE 70

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	8.328480E-03	1.048683E-06	4.063897E-01	1.546751E-04	9.867573E-02	-9.743221E-07
2	G	1.273531E-02	2.716126E-02	4.785295E-01	-2.318640E-01	-2.592258E-02	1.759752E-02
3	G	1.634907E-02	3.264682E-02	4.756594E-01	-1.746201E-01	3.360994E-02	2.912176E-03
4	G	1.891880E-02	3.037832E-02	4.179404E-01	-1.336906E-01	1.430137E-01	-1.057019E-02
5	G	1.699393E-02	2.301748E-02	3.155332E-01	-7.809075E-02	1.250787E-01	-8.156084E-03
6	G	1.082661E-02	1.275298E-02	1.774748E-01	-1.251991E-01	3.190593E-01	-2.522643E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.109365E-02	2.401730E-02	4.538015E-01	-1.713522E-01	-5.384918E-02	2.291531E-02
9	G	1.419172E-02	2.907419E-02	4.379086E-01	-1.313175E-01	5.095461E-02	1.257007E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 262
EIGHT TENTHS, -450 DEG
LOAD STEP = 9.00000E+00 SUBCASE 80

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.077892E-03	1.257378E-06	4.252180E-01	1.909823E-04	1.129055E-01	1.347442E-07
2	G	1.390011E-02	2.967304E-02	5.003771E-01	-2.429844E-01	-2.705023E-02	1.921598E-02
3	G	1.786974E-02	3.567134E-02	4.973498E-01	-1.828767E-01	3.510636E-02	3.195100E-03
4	G	2.068972E-02	3.319482E-02	4.369949E-01	-1.399620E-01	1.495990E-01	-1.157701E-02
5	G	1.858567E-02	2.514660E-02	3.298813E-01	-8.107492E-02	1.308260E-01	-8.932373E-03
6	G	1.185794E-02	1.393799E-02	1.856144E-01	-1.314543E-01	3.330772E-01	-2.762735E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.211369E-02	2.622893E-02	4.745075E-01	-1.791101E-01	-5.607839E-02	2.501908E-02
9	G	1.550871E-02	3.176231E-02	4.578658E-01	-1.371299E-01	5.315438E-02	1.398242E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 263
NINE TENTHS, -450 DEG
LOAD STEP = 1.00000E+01 SUBCASE 90

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.791840E-03	1.475879E-06	4.425409E-01	2.296445E-04	1.264975E-01	1.650433E-06
2	G	1.501322E-02	3.207845E-02	5.204390E-01	-2.531397E-01	-2.805137E-02	2.076458E-02
3	G	1.932480E-02	3.856982E-02	5.172666E-01	-1.904321E-01	3.646619E-02	3.470291E-03
4	G	2.238603E-02	3.589570E-02	4.544950E-01	-1.456985E-01	1.556363E-01	-1.254098E-02
5	G	2.011164E-02	2.718943E-02	3.430643E-01	-8.383079E-02	1.361067E-01	-9.677775E-03
6	G	1.284789E-02	1.507589E-02	1.930956E-01	-1.372488E-01	3.459097E-01	-2.993926E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.308796E-02	2.834763E-02	4.935298E-01	-1.862126E-01	-5.807335E-02	2.702815E-02
9	G	1.676889E-02	3.433933E-02	4.762002E-01	-1.424405E-01	5.515205E-02	1.539193E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 264
ONE, -450 DEG
LOAD STEP = 1.10000E+01 SUBCASE 101

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	1.047533E-02	1.703526E-06	4.586293E-01	2.704884E-04	1.395124E-01	3.585693E-06
2	G	1.608205E-02	3.439285E-02	5.390367E-01	-2.625033E-01	-2.894461E-02	2.225229E-02
3	G	2.072371E-02	4.136055E-02	5.357289E-01	-1.974111E-01	3.771271E-02	3.739326E-03
4	G	2.401852E-02	3.849781E-02	4.707201E-01	-1.509971E-01	1.612249E-01	-1.346842E-02
5	G	2.158145E-02	2.915863E-02	3.552915E-01	-8.639888E-02	1.410043E-01	-1.039676E-02
6	G	1.380252E-02	1.617362E-02	2.000367E-01	-1.426653E-01	3.577704E-01	-3.217554E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.402299E-02	3.038693E-02	5.111715E-01	-1.927774E-01	-5.987368E-02	2.895543E-02
9	G	1.798048E-02	3.682150E-02	4.932038E-01	-1.473394E-01	5.698405E-02	1.680113E-03

LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 255
ONE TENTH, -500 DEG
LOAD STEP = 2.00000E+00 SUBCASE 10

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	2.299862E-03	7.515276E-08	2.080212E-01	4.978161E-06	-2.726826E-03	-5.510882E-07
2	G	3.477071E-03	7.462800E-03	2.464132E-01	-1.119725E-01	-1.365458E-02	5.014147E-03
3	G	4.343722E-03	8.996816E-03	2.453219E-01	-8.695167E-02	1.718899E-02	7.991262E-04
4	G	4.999582E-03	8.405868E-03	2.157945E-01	-6.626406E-02	7.263131E-02	-2.709181E-03
5	G	4.520403E-03	6.447258E-03	1.637199E-01	-4.737791E-02	6.378037E-02	-2.126602E-03
6	G	2.807487E-03	3.579784E-03	9.160139E-02	-6.274306E-02	1.682469E-01	-6.876492E-03
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	2.979649E-03	6.666231E-03	2.341504E-01	-8.811483E-02	-2.842436E-02	6.328108E-03
9	G	3.782498E-03	8.054296E-03	2.262283E-01	-6.849127E-02	2.638571E-02	3.423569E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 256
TWO TENTHS, -500 DEG
LOAD STEP = 3.00000E+00 SUBCASE 20

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	3.656902E-03	1.916278E-07	2.646835E-01	1.880115E-05	1.569548E-02	-1.224665E-06
2	G	5.545766E-03	1.182350E-02	3.129946E-01	-1.463089E-01	-1.689638E-02	7.763091E-03
3	G	7.006826E-03	1.422423E-02	3.113553E-01	-1.117221E-01	2.183751E-02	1.269281E-03
4	G	8.077881E-03	1.326044E-02	2.737299E-01	-8.565726E-02	9.292430E-02	-4.434540E-03
5	G	7.276057E-03	1.010703E-02	2.071668E-01	-5.603714E-02	8.136562E-02	-3.446469E-03
6	G	4.567314E-03	5.599580E-03	1.161411E-01	-8.003695E-02	2.118262E-01	-1.087704E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	4.789103E-03	1.051635E-02	2.971380E-01	-1.120679E-01	-3.590390E-02	1.000734E-02
9	G	6.095479E-03	1.270827E-02	2.869310E-01	-8.664090E-02	3.366925E-02	5.154744E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 257
THREE TENTHS, -500 DEG
LOAD STEP = 4.00000E+00 SUBCASE 30

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	4.783797E-03	3.338586E-07	3.042389E-01	3.851227E-05	3.401581E-02	-1.754121E-06
2	G	7.268087E-03	1.548252E-02	3.593948E-01	-1.705291E-01	-1.936719E-02	1.008331E-02
3	G	9.234907E-03	1.861315E-02	3.574077E-01	-1.293914E-01	2.510821E-02	1.661027E-03
4	G	1.065744E-02	1.733538E-02	3.141391E-01	-9.925894E-02	1.070584E-01	-5.896907E-03
5	G	9.585520E-03	1.317923E-02	2.375039E-01	-6.214558E-02	9.356624E-02	-4.557253E-03
6	G	6.049371E-03	7.299366E-03	1.333030E-01	-9.249187E-02	2.421091E-01	-1.426457E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	6.298953E-03	1.373843E-02	3.410153E-01	-1.288137E-01	-4.108819E-02	1.309239E-02
9	G	8.027227E-03	1.660702E-02	3.292146E-01	-9.930599E-02	3.863440E-02	6.727108E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 258
FOUR TENTHS, -500 DEG
LOAD STEP = 5.00000E+00 SUBCASE 40

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	5.780647E-03	4.911277E-07	3.356740E-01	6.242961E-05	5.150095E-02	-2.045358E-06
2	G	8.796705E-03	1.874525E-02	3.961876E-01	-1.897270E-01	-2.139332E-02	1.216592E-02
3	G	1.121811E-02	2.252965E-02	3.939334E-01	-1.434914E-01	2.771673E-02	2.010220E-03
4	G	1.295639E-02	2.097267E-02	3.461922E-01	-1.100098E-01	1.182403E-01	-7.204693E-03
5	G	1.164481E-02	1.592255E-02	2.615846E-01	-6.702455E-02	1.032366E-01	-5.551941E-03
6	G	7.374675E-03	8.819750E-03	1.469364E-01	-1.025388E-01	2.660270E-01	-1.730641E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	7.639773E-03	1.660898E-02	3.758149E-01	-1.420708E-01	-4.514302E-02	1.584191E-02
9	G	9.745395E-03	2.008384E-02	3.627496E-01	-1.093054E-01	4.250794E-02	8.228751E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 259
FIVE TENTHS, -500 DEG
LOAD STEP = 6.00000E+00 SUBCASE 50

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	6.689325E-03	6.645969E-07	3.622004E-01	9.014281E-05	6.807594E-02	-2.033949E-06
2	G	1.019527E-02	2.173876E-02	4.271586E-01	-2.057560E-01	-2.309602E-02	1.408651E-02
3	G	1.303568E-02	2.612603E-02	4.246809E-01	-1.552949E-01	2.989751E-02	2.334396E-03
4	G	1.506594E-02	2.431514E-02	3.731840E-01	-1.190093E-01	1.276263E-01	-8.405081E-03
5	G	1.353598E-02	1.844494E-02	2.818770E-01	-7.116479E-02	1.113801E-01	-6.468301E-03
6	G	8.594401E-03	1.021954E-02	1.584317E-01	-1.111122E-01	2.860897E-01	-2.011686E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	8.866061E-03	1.924297E-02	4.051268E-01	-1.531682E-01	-4.851222E-02	1.836422E-02
9	G	1.131985E-02	2.327744E-02	3.909999E-01	-1.176698E-01	4.573462E-02	9.684429E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 260
SIX TENTHS, -500 DEG
LOAD STEP = 7.00000E+00 SUBCASE 60

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	7.532456E-03	8.510837E-07	3.853815E-01	1.210550E-04	8.379299E-02	-1.681820E-06
2	G	1.149734E-02	2.453335E-02	4.541641E-01	-2.196490E-01	-2.456334E-02	1.588453E-02
3	G	1.473069E-02	2.948608E-02	4.514919E-01	-1.655578E-01	3.178703E-02	2.640592E-03
4	G	1.703554E-02	2.743999E-02	3.967259E-01	-1.268199E-01	1.357913E-01	-9.525833E-03
5	G	1.530319E-02	2.080444E-02	2.995858E-01	-7.480203E-02	1.184852E-01	-7.326793E-03
6	G	9.736177E-03	1.153038E-02	1.684682E-01	-1.186742E-01	3.035225E-01	-2.275716E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.000736E-02	2.170225E-02	4.306982E-01	-1.628109E-01	-5.139347E-02	2.071550E-02
9	G	1.278794E-02	2.626186E-02	4.156459E-01	-1.249233E-01	4.851491E-02	1.111654E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 261
SEVEN TENTHS, -500 DEG
LOAD STEP = 8.00000E+00 SUBCASE 70

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	8.324013E-03	1.049219E-06	4.061103E-01	1.548078E-04	9.872798E-02	-9.605506E-07
2	G	1.272377E-02	2.717204E-02	4.782622E-01	-2.319743E-01	-2.584512E-02	1.758438E-02
3	G	1.632960E-02	3.266110E-02	4.754162E-01	-1.746875E-01	3.345924E-02	2.933641E-03
4	G	1.889558E-02	3.039470E-02	4.177378E-01	-1.337595E-01	1.430625E-01	-1.058394E-02
5	G	1.697355E-02	2.303674E-02	3.153995E-01	-7.807024E-02	1.248292E-01	-8.139967E-03
6	G	1.081702E-02	1.277175E-02	1.774344E-01	-1.254922E-01	3.190267E-01	-2.526512E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.108189E-02	2.402490E-02	4.535274E-01	-1.713879E-01	-5.390799E-02	2.293103E-02
9	G	1.417273E-02	2.908275E-02	4.376493E-01	-1.313618E-01	5.096712E-02	1.253565E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 262
EIGHT TENTHS, -500 DEG
LOAD STEP = 9.00000E+00 SUBCASE 80

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.073395E-03	1.257971E-06	4.249506E-01	1.911292E-04	1.129565E-01	1.510723E-07
2	G	1.388852E-02	2.968375E-02	5.001209E-01	-2.430911E-01	-2.697539E-02	1.920254E-02
3	G	1.785023E-02	3.568552E-02	4.971167E-01	-1.829415E-01	3.496150E-02	3.216725E-03
4	G	2.066647E-02	3.321111E-02	4.368008E-01	-1.400288E-01	1.496463E-01	-1.159090E-02
5	G	1.856523E-02	2.516576E-02	3.297529E-01	-8.105355E-02	1.305869E-01	-8.916249E-03
6	G	1.184836E-02	1.395673E-02	1.855757E-01	-1.317359E-01	3.330455E-01	-2.766605E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.210190E-02	2.623645E-02	4.742449E-01	-1.791443E-01	-5.613431E-02	2.503470E-02
9	G	1.548968E-02	3.177077E-02	4.576174E-01	-1.371722E-01	5.316631E-02	1.394809E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 263

NINE TENTHS, -500 DEG
LOAD STEP = 1.00000E+01

SUBCASE 90

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.787316E-03	1.476527E-06	4.422835E-01	2.298049E-04	1.265473E-01	1.669404E-06
2	G	1.500158E-02	3.208909E-02	5.201922E-01	-2.532430E-01	-2.797880E-02	2.075089E-02
3	G	1.930526E-02	3.858392E-02	5.170421E-01	-1.904945E-01	3.632632E-02	3.492048E-03
4	G	2.236274E-02	3.591189E-02	4.543079E-01	-1.457635E-01	1.556823E-01	-1.255497E-02
5	G	2.009115E-02	2.720850E-02	3.429404E-01	-8.380880E-02	1.358765E-01	-9.661641E-03
6	G	1.283831E-02	1.509461E-02	1.930583E-01	-1.375205E-01	3.458787E-01	-2.997796E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.307614E-02	2.835507E-02	4.932768E-01	-1.862454E-01	-5.812681E-02	2.704368E-02
9	G	1.674983E-02	3.434770E-02	4.759610E-01	-1.424810E-01	5.516347E-02	1.535775E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 264

ONE, -500 DEG

LOAD STEP = 1.10000E+01

SUBCASE 101

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	1.047078E-02	1.704229E-06	4.583807E-01	2.706617E-04	1.395610E-01	3.607381E-06
2	G	1.607038E-02	3.440342E-02	5.387980E-01	-2.626035E-01	-2.887404E-02	2.223839E-02
3	G	2.070414E-02	4.137455E-02	5.355116E-01	-1.974713E-01	3.757720E-02	3.761193E-03
4	G	2.399519E-02	3.851392E-02	4.705392E-01	-1.510603E-01	1.612697E-01	-1.348232E-02
5	G	2.156091E-02	2.917762E-02	3.551716E-01	-8.637647E-02	1.407818E-01	-1.038061E-02
6	G	1.379294E-02	1.619231E-02	2.000006E-01	-1.429284E-01	3.577400E-01	-3.221423E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.401114E-02	3.039430E-02	5.109268E-01	-1.928089E-01	-5.992500E-02	2.897088E-02
9	G	1.796139E-02	3.682978E-02	4.929724E-01	-1.473784E-01	5.699499E-02	1.676714E-03

LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 255

ONE TENTH, -550 DEG

LOAD STEP = 2.00000E+00

SUBCASE 10

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	2.295661E-03	7.537840E-08	2.074880E-01	5.020152E-06	-2.679436E-03	-5.545637E-07
2	G	3.466067E-03	7.474671E-03	2.459067E-01	-1.121414E-01	-1.354922E-02	5.008161E-03
3	G	4.324663E-03	9.012480E-03	2.448625E-01	-8.708533E-02	1.694321E-02	8.167097E-04
4	G	4.976693E-03	8.423569E-03	2.154108E-01	-6.634987E-02	7.268287E-02	-2.718549E-03
5	G	4.500583E-03	6.468148E-03	1.634745E-01	-4.741664E-02	6.333075E-02	-2.110782E-03
6	G	2.797216E-03	3.598866E-03	9.152062E-02	-6.325019E-02	1.681881E-01	-6.915083E-03
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	2.968170E-03	6.675127E-03	2.336319E-01	-8.819053E-02	-2.852671E-02	6.343790E-03
9	G	3.763860E-03	8.064387E-03	2.257381E-01	-6.857148E-02	2.639212E-02	3.402916E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 256

TWO TENTHS, -550 DEG

LOAD STEP = 3.00000E+00

SUBCASE 20

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	3.652629E-03	1.922329E-07	2.642608E-01	1.887295E-05	1.574992E-02	-1.221769E-06
2	G	5.534565E-03	1.183500E-02	3.125924E-01	-1.464588E-01	-1.679735E-02	7.753968E-03
3	G	6.987651E-03	1.423942E-02	3.109905E-01	-1.118290E-01	2.162649E-02	1.288380E-03
4	G	8.054951E-03	1.327768E-02	2.734257E-01	-8.574314E-02	9.298106E-02	-4.446246E-03
5	G	7.256120E-03	1.012729E-02	2.069699E-01	-5.604271E-02	8.099839E-02	-3.430375E-03
6	G	4.557427E-03	5.618561E-03	1.160791E-01	-8.045912E-02	2.117809E-01	-1.091540E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	4.777544E-03	1.052474E-02	2.967257E-01	-1.121263E-01	-3.599044E-02	1.002311E-02
9	G	6.076724E-03	1.271774E-02	2.865410E-01	-8.670744E-02	3.368194E-02	5.125852E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 257

THREE TENTHS, -550 DEG

LOAD STEP = 4.00000E+00

SUBCASE 30

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	4.779464E-03	3.237590E-07	3.038694E-01	3.776144E-05	3.407036E-02	-1.763257E-06
2	G	7.256863E-03	1.549358E-02	3.590412E-01	-1.706499E-01	-1.927164E-02	1.007274E-02
3	G	9.215605E-03	1.862786E-02	3.570863E-01	-1.294669E-01	2.491444E-02	1.681377E-03
4	G	1.063440E-02	1.735232E-02	3.138724E-01	-9.933815E-02	1.071130E-01	-5.909255E-03
5	G	9.565464E-03	1.319918E-02	2.373305E-01	-6.213906E-02	9.324086E-02	-4.541111E-03
6	G	6.039631E-03	7.318296E-03	1.332494E-01	-9.286890E-02	2.420693E-01	-1.430320E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	6.287323E-03	1.374655E-02	3.406545E-01	-1.288555E-01	-4.116887E-02	1.310853E-02
9	G	8.008433E-03	1.661626E-02	3.288741E-01	-9.936245E-02	3.865039E-02	6.694036E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 258

FOUR TENTHS, -550 DEG

LOAD STEP = 5.00000E+00

SUBCASE 40

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	5.776286E-03	4.915153E-07	3.353381E-01	6.251411E-05	5.155633E-02	-2.038441E-06
2	G	8.785312E-03	1.875643E-02	3.958674E-01	-1.898576E-01	-2.130599E-02	1.215431E-02
3	G	1.119881E-02	2.254442E-02	3.936427E-01	-1.435770E-01	2.754075E-02	2.030746E-03
4	G	1.293335E-02	2.098948E-02	3.459499E-01	-1.100882E-01	1.182943E-01	-7.217756E-03
5	G	1.162466E-02	1.594228E-02	2.614259E-01	-6.701155E-02	1.029395E-01	-5.535847E-03
6	G	7.365003E-03	8.838637E-03	1.468878E-01	-1.028850E-01	2.659898E-01	-1.734505E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	7.628122E-03	1.661695E-02	3.754864E-01	-1.421166E-01	-4.521336E-02	1.585772E-02
9	G	9.726521E-03	2.009282E-02	3.624387E-01	-1.093597E-01	4.252127E-02	8.195970E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 259
FIVE TENTHS, -550 DEG
LOAD STEP = 6.00000E+00 SUBCASE 50

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	6.684926E-03	6.650252E-07	3.618884E-01	9.024473E-05	6.813055E-02	-2.024933E-06
2	G	1.018381E-02	2.174982E-02	4.268608E-01	-2.058793E-01	-2.301277E-02	1.407424E-02
3	G	1.301633E-02	2.614064E-02	4.244103E-01	-1.553737E-01	2.973206E-02	2.355306E-03
4	G	1.504285E-02	2.433180E-02	3.729585E-01	-1.190843E-01	1.276784E-01	-8.418471E-03
5	G	1.351575E-02	1.846450E-02	2.817290E-01	-7.114827E-02	1.111030E-01	-6.452207E-03
6	G	8.584770E-03	1.023839E-02	1.583866E-01	-1.114363E-01	2.860545E-01	-2.015554E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	8.854373E-03	1.925081E-02	4.048212E-01	-1.532103E-01	-4.857767E-02	1.838000E-02
9	G	1.130093E-02	2.328626E-02	3.907107E-01	-1.177201E-01	4.574760E-02	9.650955E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 260
SIX TENTHS, -550 DEG
LOAD STEP = 7.00000E+00 SUBCASE 60

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	7.528024E-03	8.515719E-07	3.850877E-01	1.211727E-04	8.384653E-02	-1.670478E-06
2	G	1.148584E-02	2.454430E-02	4.538833E-01	-2.197665E-01	-2.448350E-02	1.587179E-02
3	G	1.471128E-02	2.950056E-02	4.512367E-01	-1.656318E-01	3.162991E-02	2.661780E-03
4	G	1.701239E-02	2.745653E-02	3.965132E-01	-1.268920E-01	1.358417E-01	-9.539453E-03
5	G	1.528289E-02	2.082386E-02	2.994458E-01	-7.478333E-02	1.182235E-01	-7.310698E-03
6	G	9.726569E-03	1.154919E-02	1.684257E-01	-1.189811E-01	3.034887E-01	-2.279586E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	9.995637E-03	2.170998E-02	4.304101E-01	-1.628501E-01	-5.145498E-02	2.073121E-02
9	G	1.276898E-02	2.627054E-02	4.153733E-01	-1.249706E-01	4.852742E-02	1.108274E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 261
SEVEN TENTHS, -550 DEG
LOAD STEP = 8.00000E+00 SUBCASE 70

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	8.319549E-03	1.049765E-06	4.058309E-01	1.549405E-04	9.878033E-02	-9.467619E-07
2	G	1.271221E-02	2.718290E-02	4.779949E-01	-2.320868E-01	-2.576819E-02	1.757127E-02
3	G	1.631015E-02	3.267545E-02	4.751732E-01	-1.747574E-01	3.330896E-02	2.955043E-03
4	G	1.887239E-02	3.041113E-02	4.175354E-01	-1.338291E-01	1.431112E-01	-1.059773E-02
5	G	1.695319E-02	2.305604E-02	3.152659E-01	-7.805009E-02	1.245800E-01	-8.123867E-03
6	G	1.080743E-02	1.279054E-02	1.773939E-01	-1.257851E-01	3.189940E-01	-2.530381E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.107013E-02	2.403253E-02	4.532532E-01	-1.714248E-01	-5.396625E-02	2.294667E-02
9	G	1.415373E-02	2.909133E-02	4.373899E-01	-1.314065E-01	5.097914E-02	1.250174E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 262
EIGHT TENTHS, -550 DEG
LOAD STEP = 9.00000E+00 SUBCASE 80

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.068903E-03	1.258573E-06	4.246831E-01	1.912760E-04	1.130076E-01	1.674099E-07
2	G	1.387692E-02	2.969452E-02	4.998647E-01	-2.431993E-01	-2.690096E-02	1.918913E-02
3	G	1.783074E-02	3.569977E-02	4.968838E-01	-1.830081E-01	3.481698E-02	3.238297E-03
4	G	2.064324E-02	3.322744E-02	4.366067E-01	-1.400961E-01	1.496935E-01	-1.160482E-02
5	G	1.854481E-02	2.518495E-02	3.296246E-01	-8.103243E-02	1.303482E-01	-8.900143E-03
6	G	1.183877E-02	1.397549E-02	1.855369E-01	-1.320171E-01	3.330137E-01	-2.770474E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.209011E-02	2.624399E-02	4.739822E-01	-1.791792E-01	-5.618981E-02	2.505026E-02
9	G	1.547065E-02	3.177924E-02	4.573689E-01	-1.372148E-01	5.317785E-02	1.391419E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 263
NINE TENTHS, -550 DEG
LOAD STEP = 1.00000E+01 SUBCASE 90

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.782795E-03	1.477183E-06	4.420261E-01	2.299652E-04	1.265972E-01	1.688378E-06
2	G	1.498995E-02	3.209977E-02	5.199455E-01	-2.533474E-01	-2.790657E-02	2.073723E-02
3	G	1.928573E-02	3.859806E-02	5.168176E-01	-1.905582E-01	3.618676E-02	3.513757E-03
4	G	2.233946E-02	3.592813E-02	4.541209E-01	-1.458287E-01	1.557281E-01	-1.256898E-02
5	G	2.007067E-02	2.722760E-02	3.428166E-01	-8.378701E-02	1.356465E-01	-9.645528E-03
6	G	1.282873E-02	1.511334E-02	1.930209E-01	-1.377917E-01	3.458476E-01	-3.001663E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.306433E-02	2.836253E-02	4.930238E-01	-1.862787E-01	-5.817992E-02	2.705917E-02
9	G	1.673078E-02	3.435608E-02	4.757216E-01	-1.425217E-01	5.517455E-02	1.532395E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 264
ONE, -550 DEG
LOAD STEP = 1.10000E+01 SUBCASE 101

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	1.046624E-02	1.704937E-06	4.581319E-01	2.708349E-04	1.396096E-01	3.629069E-06
2	G	1.605870E-02	3.441402E-02	5.385594E-01	-2.627046E-01	-2.880377E-02	2.222452E-02
3	G	2.068458E-02	4.138859E-02	5.352945E-01	-1.975326E-01	3.744198E-02	3.783017E-03
4	G	2.397188E-02	3.853007E-02	4.703582E-01	-1.511237E-01	1.613143E-01	-1.349640E-02
5	G	2.154038E-02	2.919662E-02	3.550515E-01	-8.635420E-02	1.405596E-01	-1.036449E-02
6	G	1.378335E-02	1.621101E-02	1.999643E-01	-1.431909E-01	3.577095E-01	-3.225288E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.399930E-02	3.040168E-02	5.106822E-01	-1.928408E-01	-5.997601E-02	2.898628E-02
9	G	1.794230E-02	3.683808E-02	4.927409E-01	-1.474174E-01	5.700565E-02	1.673350E-03

LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 255

ONE TENTH, -600 DEG
LOAD STEP = 2.00000E+00

SUBCASE 10

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	2.291474E-03	7.550521E-08	2.069545E-01	5.050520E-06	-2.628602E-03	-5.546576E-07
2	G	3.455011E-03	7.486895E-03	2.454016E-01	-1.123253E-01	-1.344750E-02	5.002198E-03
3	G	4.305667E-03	9.028614E-03	2.444059E-01	-8.723929E-02	1.669829E-02	8.340076E-04
4	G	4.953946E-03	8.441598E-03	2.150294E-01	-6.644751E-02	7.273548E-02	-2.728714E-03
5	G	4.480851E-03	6.489241E-03	1.632303E-01	-4.746044E-02	6.288357E-02	-2.094904E-03
6	G	2.786925E-03	3.618041E-03	9.144012E-02	-6.375752E-02	1.681302E-01	-6.952989E-03
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	2.956713E-03	6.684167E-03	2.331132E-01	-8.827510E-02	-2.862779E-02	6.359392E-03
9	G	3.745222E-03	8.074575E-03	2.252470E-01	-6.865823E-02	2.639732E-02	3.381439E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 256

TWO TENTHS, -600 DEG
LOAD STEP = 3.00000E+00

SUBCASE 20

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	3.648356E-03	1.924721E-07	2.638379E-01	1.892123E-05	1.580471E-02	-1.218782E-06
2	G	5.523366E-03	1.184657E-02	3.121902E-01	-1.466102E-01	-1.669918E-02	7.744930E-03
3	G	6.968485E-03	1.425471E-02	3.106257E-01	-1.119381E-01	2.141618E-02	1.307438E-03
4	G	8.032030E-03	1.329500E-02	2.731215E-01	-8.582987E-02	9.303743E-02	-4.457983E-03
5	G	7.236168E-03	1.014762E-02	2.067729E-01	-5.604860E-02	8.063199E-02	-3.414326E-03
6	G	4.547490E-03	5.637572E-03	1.160168E-01	-8.087997E-02	2.117351E-01	-1.095376E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	4.765990E-03	1.053319E-02	2.963133E-01	-1.121857E-01	-3.607646E-02	1.003890E-02
9	G	6.057975E-03	1.272727E-02	2.861508E-01	-8.677454E-02	3.369413E-02	5.097218E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 257

THREE TENTHS, -600 DEG
LOAD STEP = 4.00000E+00

SUBCASE 30

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	4.775143E-03	3.243314E-07	3.034998E-01	3.784936E-05	3.412623E-02	-1.758146E-06
2	G	7.245555E-03	1.550495E-02	3.586893E-01	-1.707896E-01	-1.917966E-02	1.006215E-02
3	G	9.196364E-03	1.864287E-02	3.567670E-01	-1.295619E-01	2.472473E-02	1.701323E-03
4	G	1.061142E-02	1.736937E-02	3.136062E-01	-9.942049E-02	1.071686E-01	-5.921821E-03
5	G	9.545399E-03	1.321917E-02	2.371569E-01	-6.213238E-02	9.291663E-02	-4.525048E-03
6	G	6.029847E-03	7.337247E-03	1.331956E-01	-9.324441E-02	2.420288E-01	-1.434175E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	6.275718E-03	1.375474E-02	3.402935E-01	-1.289068E-01	-4.124551E-02	1.312436E-02
9	G	7.989615E-03	1.662548E-02	3.285325E-01	-9.942192E-02	3.866353E-02	6.662751E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 258

FOUR TENTHS, -600 DEG
LOAD STEP = 5.00000E+00

SUBCASE 40

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	5.771924E-03	4.918817E-07	3.350022E-01	6.259945E-05	5.161196E-02	-2.031602E-06
2	G	8.773925E-03	1.876765E-02	3.955472E-01	-1.899881E-01	-2.121893E-02	1.214275E-02
3	G	1.117950E-02	2.255923E-02	3.933519E-01	-1.436627E-01	2.736503E-02	2.051259E-03
4	G	1.291031E-02	2.100634E-02	3.457075E-01	-1.101667E-01	1.183481E-01	-7.230821E-03
5	G	1.160450E-02	1.596204E-02	2.612672E-01	-6.699868E-02	1.026427E-01	-5.519781E-03
6	G	7.355298E-03	8.857543E-03	1.468391E-01	-1.032306E-01	2.659524E-01	-1.738369E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	7.616474E-03	1.662496E-02	3.751577E-01	-1.421626E-01	-4.528358E-02	1.587354E-02
9	G	9.707651E-03	2.010183E-02	3.621277E-01	-1.094140E-01	4.253441E-02	8.163330E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 259

FIVE TENTHS, -600 DEG
LOAD STEP = 6.00000E+00

SUBCASE 50

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	6.680528E-03	6.654550E-07	3.615763E-01	9.034701E-05	6.818534E-02	-2.015906E-06
2	G	1.017236E-02	2.176091E-02	4.265630E-01	-2.060027E-01	-2.292976E-02	1.406202E-02
3	G	1.299697E-02	2.615529E-02	4.241397E-01	-1.554529E-01	2.956682E-02	2.376201E-03
4	G	1.501975E-02	2.434851E-02	3.727331E-01	-1.191594E-01	1.277303E-01	-8.431864E-03
5	G	1.349552E-02	1.848408E-02	2.815808E-01	-7.113186E-02	1.108261E-01	-6.436139E-03
6	G	8.575111E-03	1.025726E-02	1.583415E-01	-1.117598E-01	2.860191E-01	-2.019423E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	8.842688E-03	1.925868E-02	4.045155E-01	-1.532524E-01	-4.864299E-02	1.839578E-02
9	G	1.128202E-02	2.329511E-02	3.904215E-01	-1.177706E-01	4.576040E-02	9.617627E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 260

SIX TENTHS, -600 DEG
LOAD STEP = 7.00000E+00

SUBCASE 60

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	7.523592E-03	8.520619E-07	3.847937E-01	1.212909E-04	8.390024E-02	-1.659121E-06
2	G	1.147433E-02	2.455529E-02	4.536025E-01	-2.198841E-01	-2.440386E-02	1.585908E-02
3	G	1.469188E-02	2.951507E-02	4.509814E-01	-1.657059E-01	3.147298E-02	2.682955E-03
4	G	1.698925E-02	2.747311E-02	3.963006E-01	-1.269642E-01	1.358918E-01	-9.553078E-03
5	G	1.526258E-02	2.084331E-02	2.993057E-01	-7.476470E-02	1.179621E-01	-7.294626E-03
6	G	9.716937E-03	1.156803E-02	1.683832E-01	-1.192875E-01	3.034548E-01	-2.283456E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	9.983917E-03	2.171774E-02	4.301219E-01	-1.628894E-01	-5.151638E-02	2.074694E-02
9	G	1.275003E-02	2.627926E-02	4.151006E-01	-1.250179E-01	4.853978E-02	1.104907E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 261

SEVEN TENTHS, -600 DEG
LOAD STEP = 8.00000E+00

SUBCASE 70

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	8.315085E-03	1.050313E-06	4.055514E-01	1.550735E-04	9.883282E-02	-9.329551E-07
2	G	1.270066E-02	2.719379E-02	4.777276E-01	-2.321994E-01	-2.569142E-02	1.755818E-02
3	G	1.629071E-02	3.268984E-02	4.749302E-01	-1.748275E-01	3.315884E-02	2.976433E-03
4	G	1.884920E-02	3.042758E-02	4.173329E-01	-1.338987E-01	1.431598E-01	-1.061152E-02
5	G	1.693282E-02	2.307537E-02	3.151322E-01	-7.803001E-02	1.243311E-01	-8.107790E-03
6	G	1.079781E-02	1.280934E-02	1.773534E-01	-1.260776E-01	3.189612E-01	-2.534251E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.105838E-02	2.404019E-02	4.529790E-01	-1.714618E-01	-5.402440E-02	2.296232E-02
9	G	1.413474E-02	2.909993E-02	4.371304E-01	-1.314514E-01	5.099103E-02	1.246795E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 262

EIGHT TENTHS, -600 DEG
LOAD STEP = 9.00000E+00

SUBCASE 80

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.064409E-03	1.259177E-06	4.244155E-01	1.914232E-04	1.130589E-01	1.837689E-07
2	G	1.386533E-02	2.970531E-02	4.996086E-01	-2.433076E-01	-2.682668E-02	1.917574E-02
3	G	1.781126E-02	3.571405E-02	4.966508E-01	-1.830748E-01	3.467260E-02	3.259858E-03
4	G	2.062000E-02	3.324379E-02	4.364126E-01	-1.401634E-01	1.497406E-01	-1.161874E-02
5	G	1.852438E-02	2.520417E-02	3.294962E-01	-8.101136E-02	1.301096E-01	-8.884057E-03
6	G	1.182916E-02	1.399426E-02	1.854980E-01	-1.322979E-01	3.329816E-01	-2.774342E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.207833E-02	2.625155E-02	4.737194E-01	-1.792143E-01	-5.624522E-02	2.506584E-02
9	G	1.545163E-02	3.178774E-02	4.571202E-01	-1.372574E-01	5.318928E-02	1.388040E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 263

NINE TENTHS, -600 DEG
LOAD STEP = 1.00000E+01

SUBCASE 90

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.778273E-03	1.477841E-06	4.417686E-01	2.301259E-04	1.266471E-01	1.707377E-06
2	G	1.497831E-02	3.211048E-02	5.196987E-01	-2.534519E-01	-2.783448E-02	2.072360E-02
3	G	1.926621E-02	3.861223E-02	5.165932E-01	-1.906221E-01	3.604732E-02	3.535457E-03
4	G	2.231619E-02	3.594438E-02	4.539339E-01	-1.458940E-01	1.557738E-01	-1.258300E-02
5	G	2.005019E-02	2.724671E-02	3.426926E-01	-8.376526E-02	1.354168E-01	-9.629433E-03
6	G	1.281912E-02	1.513208E-02	1.929834E-01	-1.380626E-01	3.458163E-01	-3.005530E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.305251E-02	2.837001E-02	4.927707E-01	-1.863121E-01	-5.823294E-02	2.707466E-02
9	G	1.671172E-02	3.436449E-02	4.754822E-01	-1.425625E-01	5.518553E-02	1.529026E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 264

ONE, -600 DEG
LOAD STEP = 1.10000E+01

SUBCASE 101

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	1.046169E-02	1.705648E-06	4.578831E-01	2.710085E-04	1.396583E-01	3.650784E-06
2	G	1.604703E-02	3.442465E-02	5.383207E-01	-2.628056E-01	-2.873362E-02	2.221068E-02
3	G	2.066501E-02	4.140267E-02	5.350772E-01	-1.975939E-01	3.730685E-02	3.804832E-03
4	G	2.394856E-02	3.854623E-02	4.701772E-01	-1.511871E-01	1.613588E-01	-1.351049E-02
5	G	2.151985E-02	2.921565E-02	3.549315E-01	-8.633197E-02	1.403375E-01	-1.034839E-02
6	G	1.377375E-02	1.622972E-02	1.999280E-01	-1.434532E-01	3.576788E-01	-3.229153E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.398746E-02	3.040909E-02	5.104374E-01	-1.928728E-01	-6.002694E-02	2.900169E-02
9	G	1.792322E-02	3.684640E-02	4.925094E-01	-1.474565E-01	5.701622E-02	1.669995E-03

LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 255

ONE TENTH, -650 DEG
LOAD STEP = 2.00000E+00

SUBCASE 10

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	2.287252E-03	7.910892E-08	2.064204E-01	5.399912E-06	-2.577379E-03	-5.724411E-07
2	G	3.444084E-03	7.498775E-03	2.448924E-01	-1.124810E-01	-1.334117E-02	4.996710E-03
3	G	4.286566E-03	9.044335E-03	2.439437E-01	-8.736223E-02	1.645091E-02	8.511074E-04
4	G	4.931010E-03	8.459427E-03	2.146441E-01	-6.653176E-02	7.278421E-02	-2.738726E-03
5	G	4.460924E-03	6.510229E-03	1.629835E-01	-4.749802E-02	6.243654E-02	-2.078902E-03
6	G	2.776465E-03	3.637183E-03	9.135806E-02	-6.425864E-02	1.680687E-01	-6.990748E-03
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	2.945235E-03	6.693173E-03	2.325933E-01	-8.834393E-02	-2.873055E-02	6.374983E-03
9	G	3.726599E-03	8.084839E-03	2.247560E-01	-6.873520E-02	2.640378E-02	3.359273E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 256

TWO TENTHS, -650 DEG
LOAD STEP = 3.00000E+00

SUBCASE 20

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	3.644084E-03	1.932423E-07	2.634148E-01	1.902012E-05	1.585981E-02	-1.217111E-06
2	G	5.512174E-03	1.185822E-02	3.117880E-01	-1.467629E-01	-1.660183E-02	7.735979E-03
3	G	6.949327E-03	1.427009E-02	3.102610E-01	-1.120493E-01	2.120656E-02	1.326465E-03
4	G	8.009116E-03	1.331239E-02	2.728174E-01	-8.591735E-02	9.309340E-02	-4.469746E-03
5	G	7.216203E-03	1.016800E-02	2.065758E-01	-5.605482E-02	8.026640E-02	-3.398323E-03
6	G	4.537503E-03	5.656614E-03	1.159544E-01	-8.129951E-02	2.116888E-01	-1.099211E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	4.754442E-03	1.054170E-02	2.959007E-01	-1.122462E-01	-3.616206E-02	1.005472E-02
9	G	6.039232E-03	1.273687E-02	2.857604E-01	-8.684220E-02	3.370585E-02	5.068778E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE
THREE TENTHS, -650 DEG
LOAD STEP = 4.00000E+00
AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 257
SUBCASE 30

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	4.770831E-03	3.334980E-07	3.031302E-01	3.861471E-05	3.418307E-02	-1.741293E-06
2	G	7.234218E-03	1.551648E-02	3.583382E-01	-1.709367E-01	-1.908915E-02	1.005155E-02
3	G	9.177148E-03	1.865803E-02	3.564485E-01	-1.296642E-01	2.453684E-02	1.721101E-03
4	G	1.058845E-02	1.738648E-02	3.133402E-01	-9.950395E-02	1.072241E-01	-5.934459E-03
5	G	9.525322E-03	1.323919E-02	2.369833E-01	-6.212578E-02	9.259318E-02	-4.509039E-03
6	G	6.020021E-03	7.356221E-03	1.331417E-01	-9.361879E-02	2.419879E-01	-1.438027E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	6.264127E-03	1.376298E-02	3.399324E-01	-1.289619E-01	-4.132046E-02	1.314008E-02
9	G	7.970792E-03	1.663472E-02	3.281905E-01	-9.948253E-02	3.867539E-02	6.632310E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE
FOUR TENTHS, -650 DEG
LOAD STEP = 5.00000E+00
AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 258
SUBCASE 40

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	5.767562E-03	4.922269E-07	3.346661E-01	6.268568E-05	5.166781E-02	-2.024840E-06
2	G	8.762541E-03	1.877891E-02	3.952269E-01	-1.901189E-01	-2.113221E-02	1.213124E-02
3	G	1.116021E-02	2.257409E-02	3.930610E-01	-1.437489E-01	2.718959E-02	2.071751E-03
4	G	1.288726E-02	2.102323E-02	3.454651E-01	-1.102453E-01	1.184015E-01	-7.243892E-03
5	G	1.158433E-02	1.598183E-02	2.611085E-01	-6.698594E-02	1.023463E-01	-5.503745E-03
6	G	7.345560E-03	8.876468E-03	1.467903E-01	-1.035754E-01	2.659147E-01	-1.742234E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	7.604830E-03	1.663301E-02	3.748290E-01	-1.422088E-01	-4.535360E-02	1.588938E-02
9	G	9.688784E-03	2.011088E-02	3.618166E-01	-1.094684E-01	4.254732E-02	8.130876E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE
FIVE TENTHS, -650 DEG
LOAD STEP = 6.00000E+00
AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 259
SUBCASE 50

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	6.676129E-03	6.658864E-07	3.612641E-01	9.044966E-05	6.824034E-02	-2.006868E-06
2	G	1.016091E-02	2.177204E-02	4.262651E-01	-2.061263E-01	-2.284700E-02	1.404985E-02
3	G	1.297762E-02	2.616999E-02	4.238690E-01	-1.555324E-01	2.940181E-02	2.397079E-03
4	G	1.499665E-02	2.436525E-02	3.725075E-01	-1.192346E-01	1.277819E-01	-8.445262E-03
5	G	1.347527E-02	1.850370E-02	2.814326E-01	-7.111554E-02	1.105496E-01	-6.420097E-03
6	G	8.565423E-03	1.027614E-02	1.582962E-01	-1.120828E-01	2.859834E-01	-2.023291E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	8.831005E-03	1.926658E-02	4.042097E-01	-1.532948E-01	-4.870817E-02	1.841157E-02
9	G	1.126311E-02	2.330399E-02	3.901321E-01	-1.178211E-01	4.577303E-02	9.584447E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE
SIX TENTHS, -650 DEG
LOAD STEP = 7.00000E+00
AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 260
SUBCASE 60

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	7.519160E-03	9.525539E-07	3.844997E-01	1.214093E-04	8.395411E-02	-1.647749E-06
2	G	1.146283E-02	2.456630E-02	4.533216E-01	-2.200018E-01	-2.432443E-02	1.584641E-02
3	G	1.467247E-02	2.952963E-02	4.507262E-01	-1.657803E-01	3.131622E-02	2.704116E-03
4	G	1.696610E-02	2.748971E-02	3.960879E-01	-1.270365E-01	1.359418E-01	-9.566707E-03
5	G	1.524227E-02	2.086277E-02	2.991655E-01	-7.474615E-02	1.177009E-01	-7.278577E-03
6	G	9.707280E-03	1.158687E-02	1.683406E-01	-1.195934E-01	3.034206E-01	-2.287326E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	9.972199E-03	2.172552E-02	4.298336E-01	-1.629288E-01	-5.157767E-02	2.076266E-02
9	G	1.273108E-02	2.628801E-02	4.148279E-01	-1.250653E-01	4.855198E-02	1.101554E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE
SEVEN TENTHS, -650 DEG
LOAD STEP = 8.00000E+00
AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 261
SUBCASE 70

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	8.310623E-03	1.050863E-06	4.052719E-01	1.552069E-04	9.888546E-02	-9.191298E-07
2	G	1.268911E-02	2.720470E-02	4.774602E-01	-2.323121E-01	-2.561483E-02	1.754514E-02
3	G	1.627126E-02	3.270427E-02	4.746871E-01	-1.748978E-01	3.300887E-02	2.997811E-03
4	G	1.882601E-02	3.044407E-02	4.171304E-01	-1.339684E-01	1.432081E-01	-1.062532E-02
5	G	1.691244E-02	2.309471E-02	3.149984E-01	-7.801001E-02	1.240823E-01	-8.091733E-03
6	G	1.078817E-02	1.282815E-02	1.773129E-01	-1.263696E-01	3.189282E-01	-2.538121E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.104663E-02	2.404786E-02	4.527047E-01	-1.714989E-01	-5.408246E-02	2.297798E-02
9	G	1.411575E-02	2.910855E-02	4.368709E-01	-1.314962E-01	5.100279E-02	1.243428E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE
EIGHT TENTHS, -650 DEG
LOAD STEP = 9.00000E+00
AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 262
SUBCASE 80

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.059916E-03	1.259782E-06	4.241479E-01	1.915708E-04	1.131102E-01	2.001494E-02
2	G	1.385374E-02	2.971613E-02	4.993524E-01	-2.434160E-01	-2.675255E-02	1.916239E-02
3	G	1.779177E-02	3.572836E-02	4.964178E-01	-1.831417E-01	3.452836E-02	3.281408E-03
4	G	2.059677E-02	3.326017E-02	4.362185E-01	-1.402308E-01	1.497875E-01	-1.163266E-02
5	G	1.850394E-02	2.522340E-02	3.293678E-01	-8.099036E-02	1.298712E-01	-8.867992E-03
6	G	1.181953E-02	1.401304E-02	1.854592E-01	-1.325784E-01	3.329495E-01	-2.778211E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.206654E-02	2.625914E-02	4.734566E-01	-1.792495E-01	-5.630053E-02	2.508141E-02
9	G	1.543261E-02	3.179626E-02	4.568716E-01	-1.373001E-01	5.320060E-02	1.384673E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 263
NINE TENTHS, -650 DEG
LOAD STEP = 1.00000E+01 SUBCASE 90

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.773752E-03	1.478501E-06	4.415111E-01	2.302869E-04	1.266972E-01	1.726401E-06
2	G	1.496668E-02	3.212121E-02	5.194520E-01	-2.535565E-01	-2.776252E-02	2.070999E-02
3	G	1.924668E-02	3.862643E-02	5.163686E-01	-1.906861E-01	3.590800E-02	3.557147E-03
4	G	2.229291E-02	3.596066E-02	4.537469E-01	-1.459594E-01	1.558194E-01	-1.259702E-02
5	G	2.002970E-02	2.726585E-02	3.425687E-01	-8.374356E-02	1.351872E-01	-9.613357E-03
6	G	1.280950E-02	1.515083E-02	1.929459E-01	-1.383332E-01	3.457849E-01	-3.009397E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.304070E-02	2.837751E-02	4.925176E-01	-1.863456E-01	-5.828589E-02	2.709015E-02
9	G	1.669267E-02	3.437291E-02	4.752427E-01	-1.426033E-01	5.519642E-02	1.525667E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 264
ONE, -650 DEG
LOAD STEP = 1.10000E+01 SUBCASE 101

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	1.045714E-02	1.706360E-06	4.576343E-01	2.711824E-04	1.397072E-01	3.672527E-06
2	G	1.603536E-02	3.443529E-02	5.380820E-01	-2.629068E-01	-2.866358E-02	2.219687E-02
3	G	2.064545E-02	4.141676E-02	5.348600E-01	-1.976555E-01	3.717184E-02	3.826638E-03
4	G	2.392525E-02	3.856242E-02	4.699962E-01	-1.512506E-01	1.614031E-01	-1.352458E-02
5	G	2.149932E-02	2.923469E-02	3.548114E-01	-8.630978E-02	1.401155E-01	-1.033230E-02
6	G	1.376412E-02	1.624844E-02	1.998917E-01	-1.437151E-01	3.576480E-01	-3.233017E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.397562E-02	3.041651E-02	5.101926E-01	-1.929048E-01	-6.007781E-02	2.901710E-02
9	G	1.790413E-02	3.665474E-02	4.922778E-01	-1.474956E-01	5.702669E-02	1.666651E-03

LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 255
ONE TENTH, -700 DEG
LOAD STEP = 2.00000E+00 SUBCASE 10

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	2.283061E-03	7.271444E-08	2.058859E-01	4.817924E-06	-2.525184E-03	-5.530223E-07
2	G	3.432868E-03	7.511606E-03	2.443911E-01	-1.127083E-01	-1.325129E-02	4.991211E-03
3	G	4.267682E-03	9.061085E-03	2.434921E-01	-8.757121E-02	1.621780E-02	8.673381E-04
4	G	4.908330E-03	8.477666E-03	2.142631E-01	-6.663544E-02	7.283894E-02	-2.749537E-03
5	G	4.441098E-03	6.531435E-03	1.627382E-01	-4.754052E-02	6.199282E-02	-2.063137E-03
6	G	2.765978E-03	3.656422E-03	9.127624E-02	-6.475849E-02	1.680076E-01	-7.028689E-03
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	2.933813E-03	6.702396E-03	2.320735E-01	-8.845323E-02	-2.881933E-02	6.389588E-03
9	G	3.707904E-03	8.095055E-03	2.242609E-01	-6.882986E-02	2.640041E-02	3.341507E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 256
TWO TENTHS, -700 DEG
LOAD STEP = 3.00000E+00 SUBCASE 20

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	3.639812E-03	1.928396E-07	2.629915E-01	1.900381E-05	1.591541E-02	-1.212241E-06
2	G	5.500991E-03	1.186993E-02	3.113855E-01	-1.469153E-01	-1.650495E-02	7.727112E-03
3	G	6.930173E-03	1.428554E-02	3.098961E-01	-1.121602E-01	2.099739E-02	1.345463E-03
4	G	7.986202E-03	1.332985E-02	2.725131E-01	-8.600470E-02	9.314869E-02	-4.481496E-03
5	G	4.196222E-03	1.018843E-02	2.063785E-01	-5.606125E-02	7.990152E-02	-3.382360E-03
6	G	7.527465E-03	5.675685E-03	1.158917E-01	-8.171778E-02	2.116419E-01	-1.103048E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	4.742900E-03	1.055026E-02	2.954879E-01	-1.123066E-01	-3.624742E-02	1.007055E-02
9	G	6.020494E-03	1.274652E-02	2.853698E-01	-8.690979E-02	3.371719E-02	5.040659E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 257
THREE TENTHS, -700 DEG
LOAD STEP = 4.00000E+00 SUBCASE 30

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	4.766509E-03	3.340114E-07	3.027604E-01	3.870000E-05	3.423945E-02	-1.736160E-06
2	G	7.222942E-03	1.552789E-02	3.579858E-01	-1.710727E-01	-1.899725E-02	1.004110E-02
3	G	9.157904E-03	1.867311E-02	3.561286E-01	-1.297559E-01	2.434702E-02	1.741089E-03
4	G	1.056546E-02	1.740362E-02	3.130738E-01	-9.958604E-02	1.072785E-01	-5.946987E-03
5	G	9.505234E-03	1.325926E-02	2.368096E-01	-6.211956E-02	9.226983E-02	-4.493036E-03
6	G	6.010159E-03	7.375218E-03	1.330876E-01	-9.399265E-02	2.419468E-01	-1.441884E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	6.252526E-03	1.377125E-02	3.395711E-01	-1.290117E-01	-4.139753E-02	1.315601E-02
9	G	7.951991E-03	1.664405E-02	3.278488E-01	-9.954164E-02	3.868855E-02	6.601054E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 258
FOUR TENTHS, -700 DEG
LOAD STEP = 5.00000E+00 SUBCASE 40

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	5.763200E-03	4.925960E-07	3.343300E-01	6.277172E-05	5.172390E-02	-2.017988E-06
2	G	8.751163E-03	1.879021E-02	3.949065E-01	-1.902498E-01	-2.104577E-02	1.211978E-02
3	G	1.114091E-02	2.258900E-02	3.927701E-01	-1.438354E-01	2.701442E-02	2.092228E-03
4	G	1.286422E-02	2.104018E-02	3.452227E-01	-1.103240E-01	1.184547E-01	-7.256964E-03
5	G	1.156416E-02	1.600166E-02	2.609496E-01	-6.697334E-02	1.020503E-01	-5.487738E-03
6	G	7.335790E-03	8.895412E-03	1.467414E-01	-1.039196E-01	2.658767E-01	-1.746098E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	7.593188E-03	1.664109E-02	3.745001E-01	-1.422552E-01	-4.542349E-02	1.590522E-02
9	G	9.669922E-03	2.011996E-02	3.615054E-01	-1.095229E-01	4.256003E-02	8.098573E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 259
FIVE TENTHS, -700 DEG
LOAD STEP = 6.00000E+00 SUBCASE 50

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	6.671730E-03	6.663198E-07	3.609518E-01	9.055264E-05	6.829553E-02	-1.997819E-06
2	G	1.014947E-02	2.178320E-02	4.259671E-01	-2.062500E-01	-2.276448E-02	1.403771E-02
3	G	1.295826E-02	2.618473E-02	4.235984E-01	-1.556122E-01	2.923702E-02	2.417943E-03
4	G	1.497356E-02	2.438202E-02	3.722820E-01	-1.193100E-01	1.278334E-01	-8.458664E-03
5	G	1.345502E-02	1.852334E-02	2.812843E-01	-7.109933E-02	1.102733E-01	-6.404080E-03
6	G	8.555708E-03	1.029504E-02	1.582509E-01	-1.124052E-01	2.859476E-01	-2.027159E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	8.819325E-03	1.927451E-02	4.039039E-01	-1.533374E-01	-4.877321E-02	1.842737E-02
9	G	1.124420E-02	2.331291E-02	3.898427E-01	-1.178717E-01	4.578548E-02	9.551414E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 260
SIX TENTHS, -700 DEG
LOAD STEP = 7.00000E+00 SUBCASE 60

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	7.514727E-03	8.530476E-07	3.842055E-01	1.215281E-04	8.400816E-02	-1.636362E-06
2	G	1.145133E-02	2.457735E-02	4.530406E-01	-2.201196E-01	-2.424521E-02	1.583379E-02
3	G	1.465308E-02	2.954421E-02	4.504708E-01	-1.658550E-01	3.115966E-02	2.725264E-03
4	G	1.694296E-02	2.750635E-02	3.958751E-01	-1.271089E-01	1.359915E-01	-9.580340E-03
5	G	1.522195E-02	2.088227E-02	2.990253E-01	-7.472769E-02	1.174400E-01	-7.262552E-03
6	G	9.697597E-03	1.160574E-02	1.682979E-01	-1.198988E-01	3.033863E-01	-2.291195E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	9.960483E-03	2.173333E-02	4.295453E-01	-1.629684E-01	-5.163884E-02	2.077840E-02
9	G	1.271213E-02	2.629678E-02	4.145550E-01	-1.251128E-01	4.856405E-02	1.098214E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 261
SEVEN TENTHS, -700 DEG
LOAD STEP = 8.00000E+00 SUBCASE 70

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	8.306158E-03	1.051414E-06	4.049923E-01	1.553407E-04	9.893824E-02	-9.052860E-07
2	G	1.267756E-02	2.721564E-02	4.771928E-01	-2.324249E-01	-2.553841E-02	1.753212E-02
3	G	1.625182E-02	3.271873E-02	4.744440E-01	-1.749684E-01	3.285906E-02	3.019178E-03
4	G	1.880282E-02	3.046059E-02	4.169278E-01	-1.340382E-01	1.432563E-01	-1.063912E-02
5	G	1.689206E-02	2.311408E-02	3.148647E-01	-7.799006E-02	1.238338E-01	-8.075697E-03
6	G	1.077851E-02	1.284698E-02	1.772722E-01	-1.266613E-01	3.188950E-01	-2.541991E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.103488E-02	2.405556E-02	4.524303E-01	-1.715361E-01	-5.414042E-02	2.299364E-02
9	G	1.409677E-02	2.911721E-02	4.366112E-01	-1.315411E-01	5.101442E-02	1.240072E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 262
EIGHT TENTHS, -700 DEG
LOAD STEP = 9.00000E+00 SUBCASE 80

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.055423E-03	1.260390E-06	4.238803E-01	1.917187E-04	1.131617E-01	2.165516E-07
2	G	1.384214E-02	2.972698E-02	4.990962E-01	-2.435244E-01	-2.667857E-02	1.914907E-02
3	G	1.777229E-02	3.574270E-02	4.961848E-01	-1.832088E-01	3.438424E-02	3.302948E-03
4	G	2.057354E-02	3.327657E-02	4.360243E-01	-1.402983E-01	1.498343E-01	-1.164659E-02
5	G	1.848350E-02	2.524265E-02	3.292393E-01	-8.096941E-02	1.296329E-01	-8.851946E-03
6	G	1.180988E-02	1.403183E-02	1.854202E-01	-1.328585E-01	3.329172E-01	-2.782079E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.205476E-02	2.626674E-02	4.731937E-01	-1.792848E-01	-5.635576E-02	2.509700E-02
9	G	1.541359E-02	3.180480E-02	4.566228E-01	-1.373428E-01	5.321180E-02	1.381316E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 263
NINE TENTHS, -700 DEG
LOAD STEP = 1.00000E+01 SUBCASE 90

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.769230E-03	1.479162E-06	4.412536E-01	2.304483E-04	1.267474E-01	1.745449E-06
2	G	1.495505E-02	3.213197E-02	5.192052E-01	-2.536611E-01	-2.769068E-02	2.069642E-02
3	G	1.922716E-02	3.864066E-02	5.161440E-01	-1.907503E-01	3.576880E-02	3.578828E-03
4	G	2.226964E-02	3.597696E-02	4.535598E-01	-1.460248E-01	1.558649E-01	-1.261104E-02
5	G	2.000920E-02	2.728500E-02	3.424447E-01	-8.372191E-02	1.349578E-01	-9.597300E-03
6	G	1.279986E-02	1.516959E-02	1.929084E-01	-1.386034E-01	3.457533E-01	-3.013263E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.302889E-02	2.838503E-02	4.922644E-01	-1.863793E-01	-5.833876E-02	2.710565E-02
9	G	1.667362E-02	3.438136E-02	4.750031E-01	-1.426441E-01	5.520720E-02	1.522318E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 264
ONE, -700 DEG
LOAD STEP = 1.10000E+01 SUBCASE 101

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	1.045259E-02	1.707074E-06	4.573854E-01	2.713567E-04	1.397562E-01	3.694297E-06
2	G	1.602369E-02	3.444596E-02	5.378432E-01	-2.630080E-01	-2.859366E-02	2.218308E-02
3	G	2.062589E-02	4.143089E-02	5.346427E-01	-1.977171E-01	3.703693E-02	3.848434E-03
4	G	2.390194E-02	3.857863E-02	4.698152E-01	-1.513141E-01	1.614474E-01	-1.353868E-02
5	G	2.147876E-02	2.925375E-02	3.546913E-01	-8.628764E-02	1.398937E-01	-1.031623E-02
6	G	1.375448E-02	1.626717E-02	1.998553E-01	-1.439768E-01	3.576170E-01	-3.236881E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.396378E-02	3.042395E-02	5.099478E-01	-1.929370E-01	-6.012860E-02	2.903252E-02
9	G	1.788505E-02	3.686310E-02	4.920462E-01	-1.475348E-01	5.703707E-02	1.663315E-03

LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 255

ONE TENTH, -750 DEG
LOAD STEP = 2.00000E+00

SUBCASE 10

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	2.278889E-03	7.514779E-08	2.053510E-01	5.022590E-06	-2.471722E-03	-5.254731E-07
2	G	3.421840E-03	7.524222E-03	2.438858E-01	-1.128969E-01	-1.315226E-02	4.985532E-03
3	G	4.248729E-03	9.077728E-03	2.430362E-01	-8.773575E-02	1.597273E-02	8.847227E-04
4	G	4.885691E-03	8.496183E-03	2.138831E-01	-6.674550E-02	7.289003E-02	-2.760152E-03
5	G	4.421356E-03	6.552867E-03	1.624941E-01	-4.758956E-02	6.155096E-02	-2.047227E-03
6	G	2.755477E-03	3.675777E-03	9.119479E-02	-6.526110E-02	1.679476E-01	-7.066955E-03
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	2.922378E-03	6.711755E-03	2.315539E-01	-8.854304E-02	-2.891976E-02	6.405245E-03
9	G	3.689295E-03	8.105586E-03	2.237683E-01	-6.892199E-02	2.640406E-02	3.320307E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST

8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 256

TWO TENTHS, -750 DEG
LOAD STEP = 3.00000E+00

SUBCASE 20

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	3.635541E-03	1.928652E-07	2.625679E-01	1.904706E-05	1.597142E-02	-1.209851E-06
2	G	5.489817E-03	1.188171E-02	3.109829E-01	-1.470677E-01	-1.640856E-02	7.718326E-03
3	G	6.911026E-03	1.430107E-02	3.095311E-01	-1.122712E-01	2.078874E-02	1.364427E-03
4	G	7.963289E-03	1.334737E-02	2.722086E-01	-8.609203E-02	9.320334E-02	-4.493240E-03
5	G	7.176223E-03	1.020891E-02	2.061811E-01	-5.606790E-02	7.953735E-02	-3.366439E-03
6	G	4.517375E-03	5.694787E-03	1.158289E-01	-8.213477E-02	2.115945E-01	-1.106885E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	4.731364E-03	1.055888E-02	2.950749E-01	-1.123673E-01	-3.633249E-02	1.008638E-02
9	G	6.001764E-03	1.275625E-02	2.849790E-01	-8.697741E-02	3.372810E-02	5.012862E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST

8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 257

THREE TENTHS, -750 DEG
LOAD STEP = 4.00000E+00

SUBCASE 30

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	4.762192E-03	3.336256E-07	3.023905E-01	3.871292E-05	3.429648E-02	-1.732318E-06
2	G	7.211570E-03	1.553963E-02	3.576353E-01	-1.712287E-01	-1.890940E-02	1.003063E-02
3	G	9.138719E-03	1.868851E-02	3.558110E-01	-1.298693E-01	2.416150E-02	1.760658E-03
4	G	1.054251E-02	1.742086E-02	3.128080E-01	-9.967161E-02	1.073342E-01	-5.959769E-03
5	G	9.485135E-03	1.327937E-02	2.366358E-01	-6.211311E-02	9.194758E-02	-4.477109E-03
6	G	6.000254E-03	7.394236E-03	1.330333E-01	-9.436497E-02	2.419050E-01	-1.445733E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	6.240948E-03	1.377958E-02	3.392097E-01	-1.290717E-01	-4.147027E-02	1.317162E-02
9	G	7.933160E-03	1.665336E-02	3.275059E-01	-9.960410E-02	3.869867E-02	6.571675E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST

8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 258

FOUR TENTHS, -750 DEG
LOAD STEP = 5.00000E+00

SUBCASE 40

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	5.758838E-03	4.929673E-07	3.339937E-01	6.285802E-05	5.178022E-02	-2.011127E-06
2	G	8.739793E-03	1.880155E-02	3.945860E-01	-1.903806E-01	-2.095959E-02	1.210837E-02
3	G	1.112161E-02	2.260396E-02	3.924792E-01	-1.439218E-01	2.683947E-02	2.112693E-03
4	G	1.284118E-02	2.105716E-02	3.449802E-01	-1.104028E-01	1.185075E-01	-7.270036E-03
5	G	1.154397E-02	1.602151E-02	2.607907E-01	-6.696087E-02	1.017546E-01	-5.471759E-03
6	G	7.325988E-03	8.914375E-03	1.466974E-01	-1.042631E-01	2.658385E-01	-1.749962E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	7.581549E-03	1.664920E-02	3.741712E-01	-1.423017E-01	-4.549327E-02	1.592109E-02
9	G	9.651064E-03	2.012909E-02	3.611942E-01	-1.095774E-01	4.257258E-02	8.066396E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST

8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 259

FIVE TENTHS, -750 DEG
LOAD STEP = 6.00000E+00

SUBCASE 50

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	6.667332E-03	6.667552E-07	3.606394E-01	9.065596E-05	6.835092E-02	-1.988757E-06
2	G	1.013803E-02	2.179440E-02	4.256690E-01	-2.063739E-01	-2.268221E-02	1.402562E-02
3	G	1.293892E-02	2.619950E-02	4.233277E-01	-1.556922E-01	2.907246E-02	2.438790E-03
4	G	1.495047E-02	2.439884E-02	3.720563E-01	-1.193854E-01	1.278846E-01	-8.472070E-03
5	G	1.343475E-02	1.854301E-02	2.811359E-01	-7.108321E-02	1.099974E-01	-6.388091E-03
6	G	8.545963E-03	1.031396E-02	1.582054E-01	-1.127271E-01	2.859115E-01	-2.031028E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	8.807647E-03	1.928247E-02	4.035980E-01	-1.533801E-01	-4.883812E-02	1.844318E-02
9	G	1.122529E-02	2.332186E-02	3.895532E-01	-1.179223E-01	4.579775E-02	9.518529E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST

8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 260

SIX TENTHS, -750 DEG
LOAD STEP = 7.00000E+00

SUBCASE 60

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	7.510295E-03	8.535432E-07	3.839114E-01	1.216473E-04	8.406237E-02	-1.624960E-06
2	G	1.143984E-02	2.458843E-02	4.527597E-01	-2.202375E-01	-2.416618E-02	1.582119E-02
3	G	1.463368E-02	2.955884E-02	4.502155E-01	-1.659299E-01	3.100327E-02	2.746398E-03
4	G	1.691982E-02	2.752302E-02	3.956623E-01	-1.271814E-01	1.360411E-01	-9.593978E-03
5	G	1.520162E-02	2.090179E-02	2.988850E-01	-7.470931E-02	1.171793E-01	-7.246550E-03
6	G	9.687889E-03	1.162461E-02	1.682551E-01	-1.202038E-01	3.033518E-01	-2.295065E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	9.948769E-03	2.174116E-02	4.292569E-01	-1.630082E-01	-5.169989E-02	2.079414E-02
9	G	1.269318E-02	2.630559E-02	4.142821E-01	-1.251604E-01	4.857596E-02	1.094887E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 261

SEVEN TENTHS, -750 DEG
LOAD STEP = 8.00000E+00

SUBCASE 70

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	8.301694E-03	1.051968E-06	4.047126E-01	1.554748E-04	9.899118E-02	-8.914236E-07
2	G	1.266602E-02	2.722661E-02	4.769254E-01	-2.325378E-01	-2.546217E-02	1.751914E-02
3	G	1.623238E-02	3.273322E-02	4.742009E-01	-1.750391E-01	3.270940E-02	3.040532E-03
4	G	1.877963E-02	3.047713E-02	4.167252E-01	-1.341081E-01	1.433044E-01	-1.065293E-02
5	G	1.687166E-02	2.313346E-02	3.147309E-01	-7.797018E-02	1.235855E-01	-8.059684E-03
6	G	1.076883E-02	1.286582E-02	1.772316E-01	-1.269525E-01	3.188616E-01	-2.545860E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.102313E-02	2.406329E-02	4.521559E-01	-1.715735E-01	-5.419827E-02	2.300931E-02
9	G	1.407779E-02	2.912589E-02	4.363515E-01	-1.315861E-01	5.102593E-02	1.236729E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 262

EIGHT TENTHS, -750 DEG
LOAD STEP = 9.00000E+00

SUBCASE 80

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.050928E-03	1.260999E-06	4.236126E-01	1.918669E-04	1.132133E-01	2.329755E-07
2	G	1.383056E-02	2.973785E-02	4.988399E-01	-2.436330E-01	-2.660474E-02	1.913578E-02
3	G	1.775281E-02	3.575706E-02	4.959517E-01	-1.832761E-01	3.424027E-02	3.324477E-03
4	G	2.055031E-02	3.329301E-02	4.358301E-01	-1.403659E-01	1.498809E-01	-1.166052E-02
5	G	1.846305E-02	2.526193E-02	3.291108E-01	-8.094852E-02	1.293949E-01	-8.835920E-03
6	G	1.180021E-02	1.405063E-02	1.853812E-01	-1.331382E-01	3.328848E-01	-2.785947E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.204299E-02	2.627437E-02	4.729307E-01	-1.793202E-01	-5.641090E-02	2.511258E-02
9	G	1.539457E-02	3.181338E-02	4.563740E-01	-1.373856E-01	5.322288E-02	1.377970E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 263

NINE TENTHS, -750 DEG
LOAD STEP = 1.00000E+01

SUBCASE 90

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.764709E-03	1.479826E-06	4.409959E-01	2.306101E-04	1.267978E-01	1.764522E-06
2	G	1.494342E-02	3.214274E-02	5.189583E-01	-2.537659E-01	-2.761899E-02	2.068287E-02
3	G	1.920764E-02	3.865492E-02	5.159195E-01	-1.908147E-01	3.562971E-02	3.600499E-03
4	G	2.224636E-02	3.599329E-02	4.533726E-01	-1.460902E-01	1.559102E-01	-1.262507E-02
5	G	1.998870E-02	2.730417E-02	3.423207E-01	-8.370031E-02	1.347285E-01	-9.581261E-03
6	G	1.279019E-02	1.518836E-02	1.928708E-01	-1.388733E-01	3.457217E-01	-3.017129E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.301708E-02	2.839257E-02	4.920112E-01	-1.864130E-01	-5.839154E-02	2.712116E-02
9	G	1.665457E-02	3.438983E-02	4.747635E-01	-1.426850E-01	5.521788E-02	1.518979E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 264

ONE, -750 DEG
LOAD STEP = 1.10000E+01

SUBCASE 101

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	1.044804E-02	1.707791E-06	4.571365E-01	2.715314E-04	1.398052E-01	3.716095E-06
2	G	1.601203E-02	3.445666E-02	5.376045E-01	-2.631093E-01	-2.852386E-02	2.216931E-02
3	G	2.060634E-02	4.144504E-02	5.344254E-01	-1.977790E-01	3.690212E-02	3.870222E-03
4	G	2.387862E-02	3.859486E-02	4.696342E-01	-1.513777E-01	1.614915E-01	-1.355278E-02
5	G	2.145821E-02	2.927283E-02	3.545712E-01	-8.626554E-02	1.396720E-01	-1.030018E-02
6	G	1.374482E-02	1.628591E-02	1.998189E-01	-1.442381E-01	3.575860E-01	-3.240745E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.395194E-02	3.043141E-02	5.097030E-01	-1.929693E-01	-6.017932E-02	2.904794E-02
9	G	1.786597E-02	3.687148E-02	4.918145E-01	-1.475740E-01	5.704737E-02	1.659990E-03

LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 255

ONE TENTH, -800 DEG
LOAD STEP = 2.00000E+00

SUBCASE 10

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	2.274634E-03	7.612573E-08	2.048162E-01	5.148670E-06	-2.418904E-03	-5.467502E-07
2	G	3.411162E-03	7.535812E-03	2.433703E-01	-1.130074E-01	-1.304096E-02	4.980474E-03
3	G	4.229523E-03	9.093167E-03	2.425659E-01	-8.780509E-02	1.572328E-02	9.021625E-04
4	G	4.862542E-03	8.514048E-03	2.134928E-01	-6.681153E-02	7.292970E-02	-2.769299E-03
5	G	4.401190E-03	6.573945E-03	1.622443E-01	-4.762139E-02	6.110731E-02	-2.031520E-03
6	G	2.744701E-03	3.694980E-03	9.111045E-02	-6.575089E-02	1.678804E-01	-7.104478E-03
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	2.910909E-03	6.720882E-03	2.310326E-01	-8.858611E-02	-2.902829E-02	6.421582E-03
9	G	3.670756E-03	8.116199E-03	2.232785E-01	-6.898540E-02	2.641367E-02	3.297512E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE
AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 256
TWO TENTHS, -800 DEG
LOAD STEP = 3.00000E+00 SUBCASE 20

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	3.631270E-03	1.934207E-07	2.621442E-01	1.912171E-05	1.602782E-02	-1.207310E-06
2	G	5.478656E-03	1.189354E-02	3.105802E-01	-1.472196E-01	-1.631265E-02	7.709634E-03
3	G	6.891882E-03	1.431666E-02	3.091659E-01	-1.123821E-01	2.058046E-02	1.383380E-03
4	G	7.940378E-03	1.336497E-02	2.719041E-01	-8.617951E-02	9.325738E-02	-4.504980E-03
5	G	7.156210E-03	1.022945E-02	2.059836E-01	-5.607485E-02	7.917393E-02	-3.350560E-03
6	G	4.507235E-03	5.713919E-03	1.157658E-01	-8.255049E-02	2.115466E-01	-1.110723E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	4.719832E-03	1.056755E-02	2.946618E-01	-1.124280E-01	-3.641743E-02	1.010225E-02
9	G	5.983042E-03	1.276604E-02	2.845880E-01	-8.704510E-02	3.373874E-02	4.985234E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE
AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 257
THREE TENTHS, -800 DEG
LOAD STEP = 4.00000E+00 SUBCASE 30

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	4.757872E-03	3.324121E-07	3.020204E-01	3.865983E-05	3.435354E-02	-1.729629E-06
2	G	7.200258E-03	1.555127E-02	3.572836E-01	-1.713745E-01	-1.882023E-02	1.002029E-02
3	G	9.119511E-03	1.870384E-02	3.554921E-01	-1.299724E-01	2.397433E-02	1.780409E-03
4	G	1.051955E-02	1.743813E-02	3.125418E-01	-9.975559E-02	1.073887E-01	-5.972430E-03
5	G	9.465025E-03	1.329952E-02	2.364619E-01	-6.210705E-02	9.162544E-02	-4.461190E-03
6	G	5.990313E-03	7.413279E-03	1.329790E-01	-9.473679E-02	2.418630E-01	-1.449586E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	6.229363E-03	1.378794E-02	3.388481E-01	-1.291268E-01	-4.154494E-02	1.318742E-02
9	G	7.914351E-03	1.666275E-02	3.271635E-01	-9.966506E-02	3.870997E-02	6.541596E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE
AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 258
FOUR TENTHS, -800 DEG
LOAD STEP = 5.00000E+00 SUBCASE 40

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	5.754476E-03	4.933397E-07	3.336573E-01	6.294475E-05	5.183679E-02	-2.004261E-06
2	G	8.728424E-03	1.881293E-02	3.942655E-01	-1.905118E-01	-2.087378E-02	1.209702E-02
3	G	1.110232E-02	2.261896E-02	3.921882E-01	-1.440090E-01	2.666487E-02	2.133132E-03
4	G	1.281814E-02	2.107418E-02	3.447376E-01	-1.104818E-01	1.185601E-01	-7.283117E-03
5	G	1.52377E-02	1.604141E-02	2.606317E-01	-6.694853E-02	1.014593E-01	-5.455812E-03
6	G	7.316152E-03	8.933356E-03	1.466433E-01	-1.046058E-01	2.657999E-01	-1.753827E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	7.569914E-03	1.665734E-02	3.738421E-01	-1.423485E-01	-4.556281E-02	1.593696E-02
9	G	9.632209E-03	2.013826E-02	3.608828E-01	-1.096321E-01	4.258485E-02	8.034436E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE
AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 259
FIVE TENTHS, -800 DEG
LOAD STEP = 6.00000E+00 SUBCASE 50

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	6.662933E-03	6.671924E-07	3.603269E-01	9.075963E-05	6.840651E-02	-1.979684E-06
2	G	1.012660E-02	2.180564E-02	4.253710E-01	-2.064979E-01	-2.260019E-02	1.401358E-02
3	G	1.291957E-02	2.621432E-02	4.230569E-01	-1.557726E-01	2.890811E-02	2.459622E-03
4	G	1.492737E-02	2.441568E-02	3.718307E-01	-1.194609E-01	1.279355E-01	-8.485480E-03
5	G	1.341448E-02	1.856271E-02	2.809876E-01	-7.106721E-02	1.097217E-01	-6.372127E-03
6	G	8.536191E-03	1.033289E-02	1.581599E-01	-1.130483E-01	2.858752E-01	-2.034896E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	8.795971E-03	1.929045E-02	4.032920E-01	-1.534230E-01	-4.890289E-02	1.845899E-02
9	G	1.120639E-02	2.333084E-02	3.892636E-01	-1.179731E-01	4.580985E-02	9.485795E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE
AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 260
SIX TENTHS, -800 DEG
LOAD STEP = 7.00000E+00 SUBCASE 60

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	7.505862E-03	8.540407E-07	3.836171E-01	1.217668E-04	8.411674E-02	-1.613542E-06
2	G	1.142835E-02	2.459954E-02	4.524786E-01	-2.203556E-01	-2.408736E-02	1.580864E-02
3	G	1.461429E-02	2.957350E-02	4.499601E-01	-1.660050E-01	3.084708E-02	2.767518E-03
4	G	1.689668E-02	2.753972E-02	3.954495E-01	-1.272539E-01	1.360905E-01	-9.607619E-03
5	G	1.518128E-02	2.092133E-02	2.987447E-01	-7.469101E-02	1.169189E-01	-7.230572E-03
6	G	9.678156E-03	1.164350E-02	1.682123E-01	-1.205083E-01	3.033170E-01	-2.298934E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	9.937057E-03	2.174902E-02	4.289684E-01	-1.630481E-01	-5.176082E-02	2.080989E-02
9	G	1.267424E-02	2.631442E-02	4.140091E-01	-1.252080E-01	4.858772E-02	1.091574E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE
AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 261
SEVEN TENTHS, -800 DEG
LOAD STEP = 8.00000E+00 SUBCASE 70

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	8.297229E-03	1.052523E-06	4.044329E-01	1.556092E-04	9.904426E-02	-8.775427E-07
2	G	1.265448E-02	2.723761E-02	4.766580E-01	-2.326508E-01	-2.538610E-02	1.750619E-02
3	G	1.621294E-02	3.274774E-02	4.739577E-01	-1.751101E-01	3.255991E-02	3.061874E-03
4	G	1.875645E-02	3.049370E-02	4.165226E-01	-1.341780E-01	1.433523E-01	-1.066674E-02
5	G	1.685126E-02	2.315287E-02	3.145970E-01	-7.795038E-02	1.233374E-01	-8.043693E-03
6	G	1.075912E-02	1.288467E-02	1.771908E-01	-1.272433E-01	3.188281E-01	-2.549729E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.101138E-02	2.407103E-02	4.518813E-01	-1.716110E-01	-5.425603E-02	2.302498E-02
9	G	1.405881E-02	2.913459E-02	4.360918E-01	-1.316311E-01	5.103730E-02	1.233398E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 262
EIGHT TENTHS, -800 DEG
LOAD STEP = 9.00000E+00 SUBCASE 80

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.046434E-03	1.261610E-06	4.233448E-01	1.920155E-04	1.132651E-01	2.494212E-07
2	G	1.381897E-02	2.974874E-02	4.985836E-01	-2.437416E-01	-2.653106E-02	1.912251E-02
3	G	1.773333E-02	3.577146E-02	4.957186E-01	-1.833436E-01	3.409643E-02	3.345995E-03
4	G	2.052707E-02	3.330946E-02	4.356359E-01	-1.404334E-01	1.499274E-01	-1.167446E-02
5	G	1.844260E-02	2.528122E-02	3.289823E-01	-8.092768E-02	1.291571E-01	-8.819915E-03
6	G	1.179052E-02	1.406945E-02	1.853421E-01	-1.334176E-01	3.328522E-01	-2.789815E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.203121E-02	2.628202E-02	4.726678E-01	-1.793557E-01	-5.646595E-02	2.512818E-02
9	G	1.537556E-02	3.182197E-02	4.561252E-01	-1.374284E-01	5.323386E-02	1.374636E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 263
NINE TENTHS, -800 DEG
LOAD STEP = 1.00000E+01 SUBCASE 90

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.760186E-03	1.480491E-06	4.407383E-01	2.307722E-04	1.268482E-01	1.783620E-06
2	G	1.493179E-02	3.215354E-02	5.187113E-01	-2.538706E-01	-2.754742E-02	2.066934E-02
3	G	1.918812E-02	3.866920E-02	5.156949E-01	-1.908792E-01	3.549075E-02	3.622160E-03
4	G	2.222309E-02	3.600964E-02	4.531855E-01	-1.461558E-01	1.559554E-01	-1.263910E-02
5	G	1.996819E-02	2.732336E-02	3.421967E-01	-8.367875E-02	1.344994E-01	-9.565242E-03
6	G	1.278051E-02	1.520714E-02	1.928331E-01	-1.391428E-01	3.456899E-01	-3.020995E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.300527E-02	2.840013E-02	4.917579E-01	-1.864468E-01	-5.844425E-02	2.713667E-02
9	G	1.663552E-02	3.439832E-02	4.745239E-01	-1.427259E-01	5.522846E-02	1.515650E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 264
ONE, -800 DEG
LOAD STEP = 1.10000E+01 SUBCASE 101

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	1.044349E-02	1.708509E-06	4.568875E-01	2.717064E-04	1.398544E-01	3.737921E-06
2	G	1.600036E-02	3.446737E-02	5.373657E-01	-2.632107E-01	-2.845417E-02	2.215558E-02
3	G	2.058678E-02	4.145921E-02	5.342081E-01	-1.978409E-01	3.676742E-02	3.892002E-03
4	G	2.385531E-02	3.861111E-02	4.694531E-01	-1.514413E-01	1.615356E-01	-1.356688E-02
5	G	2.143765E-02	2.929192E-02	3.544510E-01	-8.624348E-02	1.394505E-01	-1.028414E-02
6	G	1.373514E-02	1.630466E-02	1.997824E-01	-1.444991E-01	3.575548E-01	-3.244608E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.394010E-02	3.043889E-02	5.094581E-01	-1.930016E-01	-6.022996E-02	2.906337E-02
9	G	1.784690E-02	3.687988E-02	4.915828E-01	-1.476133E-01	5.705757E-02	1.656674E-03

ONE TENTH, -850 DEG
LOAD STEP = 2.00000E+00 SUBCASE 10

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	2.270442E-03	7.627559E-08	2.042809E-01	5.174657E-06	-2.365638E-03	-5.453617E-07
2	G	3.400191E-03	7.548475E-03	2.428637E-01	-1.131925E-01	-1.294472E-02	4.975366E-03
3	G	4.210559E-03	9.109799E-03	2.421077E-01	-8.796486E-02	1.548423E-02	9.189713E-04
4	G	4.839766E-03	8.532519E-03	2.131094E-01	-6.690789E-02	7.297698E-02	-2.779592E-03
5	G	4.381250E-03	6.595381E-03	1.619977E-01	-4.766401E-02	6.066730E-02	-2.015819E-03
6	G	2.733972E-03	3.714354E-03	9.102726E-02	-6.624407E-02	1.678160E-01	-7.142470E-03
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	2.899497E-03	6.730330E-03	2.305119E-01	-8.867331E-02	-2.912490E-02	6.437106E-03
9	G	3.652162E-03	8.126861E-03	2.227851E-01	-6.907176E-02	2.641450E-02	3.278067E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 256
TWO TENTHS, -850 DEG
LOAD STEP = 3.00000E+00 SUBCASE 20

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	3.627000E-03	1.940123E-07	2.617203E-01	1.917093E-05	1.608459E-02	-1.202626E-06
2	G	5.467513E-03	1.190541E-02	3.101772E-01	-1.473705E-01	-1.621710E-02	7.701037E-03
3	G	6.872741E-03	1.433231E-02	3.088004E-01	-1.124922E-01	2.037250E-02	1.402337E-03
4	G	7.917467E-03	1.338263E-02	2.715994E-01	-8.626711E-02	9.331074E-02	-4.516703E-03
5	G	7.136182E-03	1.025004E-02	2.057859E-01	-5.608220E-02	7.881123E-02	-3.334720E-03
6	G	4.497047E-03	5.733081E-03	1.157025E-01	-8.296502E-02	2.114981E-01	-1.114562E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	4.708305E-03	1.057628E-02	2.942485E-01	-1.124885E-01	-3.650242E-02	1.011820E-02
9	G	5.964329E-03	1.277590E-02	2.841969E-01	-8.711286E-02	3.374923E-02	4.957663E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 257
THREE TENTHS, -850 DEG
LOAD STEP = 4.00000E+00 SUBCASE 30

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	4.753550E-03	3.374733E-07	3.016502E-01	3.910557E-05	3.441067E-02	-1.717992E-06
2	G	7.189105E-03	1.556255E-02	3.569290E-01	-1.714908E-01	-1.872591E-02	1.001012E-02
3	G	9.100223E-03	1.871882E-02	3.551697E-01	-1.300438E-01	2.378175E-02	1.800718E-03
4	G	1.049651E-02	1.745538E-02	3.122745E-01	-9.983449E-02	1.074404E-01	-5.984700E-03
5	G	9.444899E-03	1.331971E-02	2.362879E-01	-6.210179E-02	9.130295E-02	-4.445244E-03
6	G	5.980339E-03	7.432348E-03	1.329245E-01	-9.510867E-02	2.418211E-01	-1.453455E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	6.217757E-03	1.379632E-02	3.384867E-01	-1.291674E-01	-4.162553E-02	1.320374E-02
9	G	7.895600E-03	1.667230E-02	3.268225E-01	-9.972121E-02	3.872508E-02	6.509271E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE nastran_final_results_negative temps.txt
AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 258
FOUR TENTHS, -850 DEG
LOAD STEP = 5.00000E+00

SUBCASE 40

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	5.750115E-03	4.937203E-07	3.333208E-01	6.303169E-05	5.189360E-02	-1.997364E-06
2	G	8.717060E-03	1.882435E-02	3.939449E-01	-1.906433E-01	-2.078827E-02	1.208571E-02
3	G	1.108304E-02	2.263402E-02	3.918971E-01	-1.440965E-01	2.649054E-02	2.153553E-03
4	G	1.279510E-02	2.109125E-02	3.444951E-01	-1.105609E-01	1.186124E-01	-7.296201E-03
5	G	1.150357E-02	1.606133E-02	2.604726E-01	-6.693634E-02	1.011644E-01	-5.439894E-03
6	G	7.306284E-03	8.952356E-03	1.465940E-01	-1.049479E-01	2.657611E-01	-1.757691E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	7.558282E-03	1.666553E-02	3.735130E-01	-1.423956E-01	-4.563219E-02	1.595284E-02
9	G	9.613358E-03	2.014747E-02	3.605712E-01	-1.096869E-01	4.259691E-02	8.002642E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 259
FIVE TENTHS, -850 DEG
LOAD STEP = 6.00000E+00

SUBCASE 50

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	6.658534E-03	6.676315E-07	3.600144E-01	9.086364E-05	6.846229E-02	-1.970599E-06
2	G	1.011517E-02	2.181691E-02	4.250728E-01	-2.066221E-01	-2.251842E-02	1.400158E-02
3	G	1.290023E-02	2.622919E-02	4.227861E-01	-1.558532E-01	2.874400E-02	2.480438E-03
4	G	1.490428E-02	2.443257E-02	3.716050E-01	-1.195365E-01	1.279863E-01	-8.498894E-03
5	G	1.339420E-02	1.858244E-02	2.808391E-01	-7.105130E-02	1.094464E-01	-6.356189E-03
6	G	8.526389E-03	1.035184E-02	1.581143E-01	-1.133691E-01	2.858386E-01	-2.038764E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	8.784299E-03	1.929847E-02	4.029859E-01	-1.534661E-01	-4.896751E-02	1.847482E-02
9	G	1.118749E-02	2.333986E-02	3.889739E-01	-1.180239E-01	4.582176E-02	9.453209E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 260
SIX TENTHS, -850 DEG
LOAD STEP = 7.00000E+00

SUBCASE 60

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	7.501429E-03	8.545401E-07	3.833228E-01	1.218867E-04	8.417130E-02	-1.602109E-06
2	G	1.141686E-02	2.461068E-02	4.521975E-01	-2.204738E-01	-2.400875E-02	1.579612E-02
3	G	1.459490E-02	2.958820E-02	4.497046E-01	-1.660804E-01	3.069106E-02	2.788624E-03
4	G	1.687354E-02	2.755645E-02	3.952366E-01	-1.273265E-01	1.361397E-01	-9.621264E-03
5	G	1.516093E-02	2.094090E-02	2.986044E-01	-7.467280E-02	1.166587E-01	-7.214619E-03
6	G	9.668398E-03	1.166240E-02	1.681693E-01	-1.208123E-01	3.032821E-01	-2.302803E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	9.925348E-03	2.175690E-02	4.286798E-01	-1.630881E-01	-5.182164E-02	2.082565E-02
9	G	1.265530E-02	2.632328E-02	4.137360E-01	-1.252557E-01	4.859934E-02	1.088273E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 261
SEVEN TENTHS, -850 DEG
LOAD STEP = 8.00000E+00

SUBCASE 70

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	8.292765E-03	1.053080E-06	4.041531E-01	1.557440E-04	9.909748E-02	-8.636430E-07
2	G	1.264294E-02	2.724863E-02	4.763904E-01	-2.327639E-01	-2.531020E-02	1.749328E-02
3	G	1.619351E-02	3.276230E-02	4.737146E-01	-1.751812E-01	3.241057E-02	3.083204E-03
4	G	1.873326E-02	3.051031E-02	4.163200E-01	-1.342480E-01	1.434000E-01	-1.068055E-02
5	G	1.683086E-02	2.317230E-02	3.144631E-01	-7.793064E-02	1.230895E-01	-8.027723E-03
6	G	1.074939E-02	1.290353E-02	1.771500E-01	-1.275337E-01	3.187944E-01	-2.553598E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.099964E-02	2.407880E-02	4.516068E-01	-1.716487E-01	-5.431368E-02	2.304066E-02
9	G	1.403983E-02	2.914333E-02	4.358320E-01	-1.316762E-01	5.104855E-02	1.230079E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 262
EIGHT TENTHS, -850 DEG
LOAD STEP = 9.00000E+00

SUBCASE 80

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.041940E-03	1.262223E-06	4.230770E-01	1.921645E-04	1.133170E-01	2.658888E-07
2	G	1.380739E-02	2.975966E-02	4.983272E-01	-2.438504E-01	-2.645754E-02	1.910928E-02
3	G	1.771385E-02	3.578589E-02	4.954855E-01	-1.834113E-01	3.395272E-02	3.367502E-03
4	G	2.050385E-02	3.332594E-02	4.354417E-01	-1.405011E-01	1.499738E-01	-1.168840E-02
5	G	1.842214E-02	2.530053E-02	3.288537E-01	-8.090691E-02	1.289194E-01	-8.803930E-03
6	G	1.178081E-02	1.408828E-02	1.853030E-01	-1.336966E-01	3.328195E-01	-2.793683E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.201943E-02	2.628968E-02	4.724047E-01	-1.793913E-01	-5.652091E-02	2.514378E-02
9	G	1.535654E-02	3.183059E-02	4.558763E-01	-1.374713E-01	5.324472E-02	1.371312E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 263
NINE TENTHS, -850 DEG
LOAD STEP = 1.00000E+01

SUBCASE 90

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.755664E-03	1.481158E-06	4.404806E-01	2.309346E-04	1.268988E-01	1.802742E-06
2	G	1.492017E-02	3.216437E-02	5.184644E-01	-2.539755E-01	-2.747598E-02	2.065585E-02
3	G	1.916861E-02	3.868351E-02	5.154703E-01	-1.909439E-01	3.535190E-02	3.643811E-03
4	G	2.219982E-02	3.602602E-02	4.529983E-01	-1.462213E-01	1.560005E-01	-1.265313E-02
5	G	1.994768E-02	2.734256E-02	3.420726E-01	-8.365725E-02	1.342705E-01	-9.549242E-03
6	G	1.277081E-02	1.522594E-02	1.927954E-01	-1.394121E-01	3.456579E-01	-3.024861E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.299347E-02	2.840770E-02	4.915046E-01	-1.864807E-01	-5.849687E-02	2.715218E-02
9	G	1.661647E-02	3.440684E-02	4.742842E-01	-1.427669E-01	5.523895E-02	1.512332E-03

nastran_final_results_negative_temps.txt
 1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 264
 ONE, -850 DEG
 LOAD STEP = 1.10000E+01 SUBCASE 101

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	1.043894E-02	1.709229E-06	4.566384E-01	2.718818E-04	1.399036E-01	3.759774E-06
2	G	1.598870E-02	3.447810E-02	5.371268E-01	-2.633121E-01	-2.838461E-02	2.214186E-02
3	G	2.056723E-02	4.147341E-02	5.339908E-01	-1.979031E-01	3.663283E-02	3.913772E-03
4	G	2.383200E-02	3.862739E-02	4.692720E-01	-1.515050E-01	1.615795E-01	-1.358099E-02
5	G	2.141709E-02	2.931103E-02	3.543308E-01	-8.622146E-02	1.392292E-01	-1.026813E-02
6	G	1.372545E-02	1.632342E-02	1.997459E-01	-1.447599E-01	3.575235E-01	-3.248471E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.392827E-02	3.044638E-02	5.092131E-01	-1.930341E-01	-6.028054E-02	2.907880E-02
9	G	1.782782E-02	3.688830E-02	4.913510E-01	-1.476525E-01	5.706769E-02	1.653368E-03

ONE TENTH, ZERO DEG
LOAD STEP = 2.00000E+00

nastran_final_results_positive_temp.txt

SUBCASE 10

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	2.341992E-03	7.401508E-08	2.133318E-01	4.767032E-06	-3.194503E-03	-5.698712E-07
2	G	3.587988E-03	7.349566E-03	2.514677E-01	-1.103176E-01	-1.476892E-02	5.080811E-03
3	G	4.534828E-03	8.846126E-03	2.499020E-01	-8.563810E-02	1.971927E-02	6.239635E-04
4	G	5.228249E-03	8.234358E-03	2.196153E-01	-6.538023E-02	7.205004E-02	-2.608204E-03
5	G	4.716984E-03	6.243060E-03	1.661580E-01	-4.700415E-02	6.834459E-02	-2.289620E-03
6	G	2.905966E-03	3.391708E-03	9.238727E-02	-5.754874E-02	1.687762E-01	-6.500938E-03
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	3.094946E-03	6.582240E-03	2.393183E-01	-8.740198E-02	-2.736874E-02	6.174818E-03
9	G	3.969544E-03	7.959296E-03	2.311131E-01	-6.769782E-02	2.627526E-02	3.668207E-04
1	LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE	AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99					

TWO TENTHS, ZERO DEG
LOAD STEP = 3.00000E+00

SUBCASE 20

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	3.699800E-03	1.900756E-07	2.688976E-01	1.839473E-05	1.517781E-02	-1.255206E-06
2	G	5.657619E-03	1.171388E-02	3.170216E-01	-1.449520E-01	-1.793619E-02	7.857751E-03
3	G	7.199376E-03	1.407835E-02	3.150148E-01	-1.108159E-01	2.398902E-02	1.075015E-03
4	G	8.308156E-03	1.309270E-02	2.767770E-01	-8.485006E-02	9.233310E-02	-4.319508E-03
5	G	7.475621E-03	9.907982E-03	2.091379E-01	-5.601881E-02	8.507415E-02	-3.609077E-03
6	G	4.664267E-03	5.411784E-03	1.167564E-01	-7.577603E-02	2.122634E-01	-1.049676E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	4.905153E-03	1.043558E-02	3.012488E-01	-1.115717E-01	-3.500446E-02	9.848427E-03
9	G	6.283277E-03	1.261670E-02	2.908130E-01	-8.601391E-02	3.350478E-02	5.465528E-04
1	LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE	AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99					

THREE TENTHS, ZERO DEG
LOAD STEP = 4.00000E+00

SUBCASE 30

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	4.827071E-03	3.296506E-07	3.079243E-01	3.776644E-05	3.347854E-02	-1.804291E-06
2	G	7.381059E-03	1.537338E-02	3.629159E-01	-1.692394E-01	-2.032832E-02	1.019281E-02
3	G	9.427924E-03	1.846821E-02	3.606077E-01	-1.285687E-01	2.704221E-02	1.458444E-03
4	G	1.088789E-02	1.716879E-02	3.168018E-01	-9.846851E-02	1.064855E-01	-5.772921E-03
5	G	9.785834E-03	1.298225E-02	2.392366E-01	-6.223028E-02	9.684050E-02	-4.719901E-03
6	G	6.145012E-03	7.111489E-03	1.338336E-01	-8.868869E-02	2.424940E-01	-1.388027E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	6.415361E-03	1.365929E-02	3.446157E-01	-1.283657E-01	-4.029152E-02	1.293319E-02
9	G	8.215570E-03	1.651759E-02	3.326161E-01	-9.873720E-02	3.847246E-02	7.060374E-04
1	LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE	AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99					

FOUR TENTHS, ZERO DEG
LOAD STEP = 5.00000E+00

SUBCASE 40

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	5.824279E-03	4.875732E-07	3.390261E-01	6.160066E-05	5.096036E-02	-2.113337E-06
2	G	8.910754E-03	1.863601E-02	3.993870E-01	-1.884515E-01	-2.228624E-02	1.228464E-02
3	G	1.141145E-02	2.238498E-02	3.968402E-01	-1.426764E-01	2.949344E-02	1.803628E-03
4	G	1.318708E-02	2.080704E-02	3.486135E-01	-1.092386E-01	1.176858E-01	-7.074701E-03
5	G	1.184594E-02	1.572718E-02	2.631682E-01	-6.716432E-02	1.062277E-01	-5.714348E-03
6	G	7.469765E-03	8.631983E-03	1.474169E-01	-9.904365E-02	2.663847E-01	-1.692065E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	7.756472E-03	1.653108E-02	3.790943E-01	-1.416347E-01	-4.442729E-02	1.568392E-02
9	G	9.934303E-03	1.999619E-02	3.658510E-01	-1.087726E-01	4.236004E-02	8.567687E-04
1	LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE	AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99					

FIVE TENTHS, ZERO DEG
LOAD STEP = 6.00000E+00

SUBCASE 50

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	6.733309E-03	6.604511E-07	3.653156E-01	8.914154E-05	6.754070E-02	-2.123406E-06
2	G	1.030995E-02	2.163025E-02	4.301342E-01	-2.045407E-01	-2.394332E-02	1.421139E-02
3	G	1.322947E-02	2.598237E-02	4.273852E-01	-1.545321E-01	3.156491E-02	2.124286E-03
4	G	1.529706E-02	2.415056E-02	3.754366E-01	-1.182674E-01	1.270934E-01	-8.271642E-03
5	G	1.373792E-02	1.825094E-02	2.833554E-01	-7.133682E-02	1.141674E-01	-6.630572E-03
6	G	8.689254E-03	1.003195E-02	1.588780E-01	-1.078429E-01	2.864297E-01	-1.973036E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	8.983096E-03	1.916613E-02	4.081779E-01	-1.527627E-01	-4.784866E-02	1.820671E-02
9	G	1.150918E-02	2.319106E-02	3.938858E-01	-1.171724E-01	4.559385E-02	1.002825E-03
1	LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE	AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99					

SIX TENTHS, ZERO DEG
LOAD STEP = 7.00000E+00

SUBCASE 60

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	7.576771E-03	8.463200E-07	3.883161E-01	1.198958E-04	8.326672E-02	-1.794408E-06
2	G	1.161256E-02	2.442559E-02	4.569698E-01	-2.184867E-01	-2.537364E-02	1.601396E-02
3	G	1.492490E-02	2.934340E-02	4.540426E-01	-1.648382E-01	3.336866E-02	2.427868E-03
4	G	1.726710E-02	2.727639E-02	3.988505E-01	-1.261049E-01	1.352782E-01	-9.389993E-03
5	G	1.550585E-02	2.061162E-02	3.009839E-01	-7.499430E-02	1.211151E-01	-7.488977E-03
6	G	9.830929E-03	1.134300E-02	1.688890E-01	-1.155808E-01	3.038500E-01	-2.237032E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.012471E-02	2.162636E-02	4.335753E-01	-1.624303E-01	-5.077100E-02	2.055860E-02
9	G	1.297765E-02	2.617656E-02	4.183674E-01	-1.244550E-01	4.838090E-02	1.146241E-03
1	LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE	AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99					

SEVEN TENTHS, ZERO DEG
LOAD STEP = 8.00000E+00

nastran_final_results_positve_temp.txt

SUBCASE 70

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	8.368637E-03	1.043875E-06	4.089008E-01	1.534995E-04	9.821242E-02	-1.097446E-06
2	G	1.283945E-02	2.706503E-02	4.809326E-01	-2.308585E-01	-2.662448E-02	1.771732E-02
3	G	1.652423E-02	3.251937E-02	4.778447E-01	-1.740040E-01	3.497084E-02	2.718891E-03
4	G	1.912758E-02	3.023202E-02	4.197606E-01	-1.330689E-01	1.425671E-01	-1.044636E-02
5	G	1.717687E-02	2.284497E-02	3.167335E-01	-7.827581E-02	1.273323E-01	-8.302107E-03
6	G	1.091176E-02	1.258460E-02	1.778352E-01	-1.225415E-01	3.193446E-01	-2.487816E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.119955E-02	2.394984E-02	4.562658E-01	-1.710281E-01	-5.331921E-02	2.277482E-02
9	G	1.436278E-02	2.899843E-02	4.402396E-01	-1.309180E-01	5.083937E-02	1.288188E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 262

EIGHT TENTHS, ZERO DEG
LOAD STEP = 9.00000E+00

SUBCASE 80

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.118314E-03	1.252067E-06	4.276222E-01	1.896795E-04	1.124524E-01	-1.115805E-08
2	G	1.400462E-02	2.957748E-02	5.026800E-01	-2.420164E-01	-2.772826E-02	1.933831E-02
3	G	1.804524E-02	3.554473E-02	4.994448E-01	-1.822887E-01	3.641428E-02	3.000361E-03
4	G	2.089888E-02	3.304930E-02	4.387399E-01	-1.393600E-01	1.491668E-01	-1.145202E-02
5	G	1.876916E-02	2.497493E-02	3.310342E-01	-8.126815E-02	1.329847E-01	-9.078379E-03
6	G	1.194312E-02	1.376981E-02	1.859604E-01	-1.289042E-01	3.333558E-01	-2.727912E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.221985E-02	2.616216E-02	4.768688E-01	-1.788021E-01	-5.557397E-02	2.487925E-02
9	G	1.568006E-02	3.168732E-02	4.600995E-01	-1.367493E-01	5.304433E-02	1.429357E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 263

NINE TENTHS, ZERO DEG
LOAD STEP = 1.00000E+01

SUBCASE 90

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.832514E-03	1.470081E-06	4.448548E-01	2.282205E-04	1.260549E-01	1.480952E-06
2	G	1.511807E-02	3.198354E-02	5.226576E-01	-2.522050E-01	-2.870859E-02	2.088898E-02
3	G	1.950064E-02	3.844401E-02	5.192854E-01	-1.898682E-01	3.772863E-02	3.274368E-03
4	G	2.259555E-02	3.575092E-02	4.561765E-01	-1.451146E-01	1.552172E-01	-1.241510E-02
5	G	2.029565E-02	2.701854E-02	3.441771E-01	-8.402963E-02	1.381845E-01	-9.823789E-03
6	G	1.293314E-02	1.490792E-02	1.934295E-01	-1.347904E-01	3.461829E-01	-2.959114E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.319438E-02	2.828150E-02	4.958042E-01	-1.859184E-01	-5.759095E-02	2.688901E-02
9	G	1.694051E-02	3.426507E-02	4.783516E-01	-1.420764E-01	5.504677E-02	1.570176E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 264

ONE, ZERO DEG
LOAD STEP = 1.10000E+01

SUBCASE 101

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	1.051625E-02	1.697254E-06	4.608655E-01	2.689482E-04	1.390801E-01	3.391936E-06
2	G	1.618723E-02	3.429857E-02	5.411828E-01	-2.615984E-01	-2.958344E-02	2.237843E-02
3	G	2.089988E-02	4.123551E-02	5.376822E-01	-1.968684E-01	3.893548E-02	3.542423E-03
4	G	2.422840E-02	3.835374E-02	4.723471E-01	-1.504295E-01	1.608177E-01	-1.334169E-02
5	G	2.176594E-02	2.898846E-02	3.563698E-01	-8.660164E-02	1.430123E-01	-1.054280E-02
6	G	1.388785E-02	1.600586E-02	2.003604E-01	-1.402865E-01	3.580391E-01	-3.182759E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.412965E-02	3.032140E-02	5.133712E-01	-1.924952E-01	-5.941056E-02	2.881701E-02
9	G	1.815236E-02	3.674791E-02	4.952843E-01	-1.469900E-01	5.688317E-02	1.710918E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 256

ONE TENTH, 50 DEG
LOAD STEP = 2.00000E+00

SUBCASE 10

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	2.344982E-03	7.372912E-08	2.138460E-01	4.721140E-06	-3.269909E-03	-5.707928E-07
2	G	3.600940E-03	7.329270E-03	2.518731E-01	-1.095916E-01	-1.478822E-02	5.089241E-03
3	G	4.550870E-03	8.820355E-03	2.502274E-01	-8.485451E-02	1.994637E-02	6.103521E-04
4	G	5.245470E-03	8.210093E-03	2.198898E-01	-6.494360E-02	7.192380E-02	-2.587451E-03
5	G	4.730938E-03	6.218150E-03	1.663262E-01	-4.676238E-02	6.877638E-02	-2.306383E-03
6	G	2.912157E-03	3.371158E-03	9.242661E-02	-5.688357E-02	1.687386E-01	-6.452031E-03
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	3.105605E-03	6.570819E-03	2.397963E-01	-8.697853E-02	-2.729649E-02	6.163362E-03
9	G	3.987649E-03	7.948643E-03	2.315908E-01	-6.738293E-02	2.630314E-02	3.687229E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 257

TWO TENTHS, 50 DEG
LOAD STEP = 3.00000E+00

SUBCASE 20

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	3.703974E-03	1.895745E-07	2.693188E-01	1.833968E-05	1.512457E-02	-1.259003E-06
2	G	5.669242E-03	1.170201E-02	3.174151E-01	-1.447326E-01	-1.803124E-02	7.868384E-03
3	G	7.218304E-03	1.406285E-02	3.153686E-01	-1.106389E-01	2.419892E-02	1.056592E-03
4	G	8.330598E-03	1.307564E-02	2.770733E-01	-8.474120E-02	9.226575E-02	-4.306667E-03
5	G	7.494790E-03	9.887892E-03	2.093277E-01	-5.600226E-02	8.545002E-02	-3.625840E-03
6	G	4.673128E-03	5.392959E-03	1.168124E-01	-7.532460E-02	2.122953E-01	-1.045714E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	4.916652E-03	1.042766E-02	3.016593E-01	-1.114795E-01	-3.492519E-02	9.834217E-03
9	G	6.302128E-03	1.260809E-02	2.912040E-01	-8.593208E-02	3.349661E-02	5.492606E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 258

THREE TENTHS, 50 DEG
LOAD STEP = 4.00000E+00

SUBCASE 30

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	4.831350E-03	3.293509E-07	3.082924E-01	3.769924E-05	3.342521E-02	-1.809064E-06
2	G	7.392572E-03	1.536215E-02	3.632641E-01	-1.690759E-01	-2.042136E-02	1.020441E-02
3	G	9.447088E-03	1.845342E-02	3.609227E-01	-1.284512E-01	2.723373E-02	1.438638E-03
4	G	1.091069E-02	1.715213E-02	3.170648E-01	-9.837919E-02	1.064240E-01	-5.759921E-03
5	G	9.805522E-03	1.296258E-02	2.394071E-01	-6.223445E-02	9.717071E-02	-4.736444E-03
6	G	6.154139E-03	7.092744E-03	1.338844E-01	-8.829744E-02	2.425276E-01	-1.384126E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	6.426958E-03	1.365156E-02	3.449753E-01	-1.283043E-01	-4.021651E-02	1.291812E-02
9	G	8.234454E-03	1.650901E-02	3.329572E-01	-9.867344E-02	3.845945E-02	7.091786E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST

4, 2000 MSC/NASTRAN 2/ 9/99

PAGE 259

FOUR TENTHS, 50 DEG
LOAD STEP = 5.00000E+00

SUBCASE 40

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	5.828626E-03	4.872697E-07	3.393608E-01	6.151665E-05	5.090738E-02	-2.119924E-06
2	G	8.922231E-03	1.862514E-02	3.997057E-01	-1.883159E-01	-2.237591E-02	1.229687E-02
3	G	1.143075E-02	2.237059E-02	3.971294E-01	-1.425875E-01	2.967170E-02	1.783026E-03
4	G	1.321007E-02	2.079063E-02	3.488545E-01	-1.091593E-01	1.176283E-01	-7.061554E-03
5	G	1.186591E-02	1.570777E-02	2.633256E-01	-6.717757E-02	1.065288E-01	-5.730771E-03
6	G	7.479027E-03	8.613285E-03	1.474639E-01	-9.868883E-02	2.664182E-01	-1.688193E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	7.768138E-03	1.652346E-02	3.794217E-01	-1.415879E-01	-4.435632E-02	1.566841E-02
9	G	9.953219E-03	1.998766E-02	3.661610E-01	-1.087179E-01	4.234533E-02	8.601545E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST

4, 2000 MSC/NASTRAN 2/ 9/99

PAGE 260

FIVE TENTHS, 50 DEG
LOAD STEP = 6.00000E+00

SUBCASE 50

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	6.737697E-03	6.600227E-07	3.656266E-01	8.904380E-05	6.748820E-02	-2.132352E-06
2	G	1.032147E-02	2.161949E-02	4.304310E-01	-2.044148E-01	-2.402863E-02	1.422415E-02
3	G	1.324883E-02	2.596812E-02	4.276547E-01	-1.544521E-01	3.173229E-02	2.103293E-03
4	G	1.532014E-02	2.413426E-02	3.756612E-01	-1.181922E-01	1.270386E-01	-8.258222E-03
5	G	1.375802E-02	1.823166E-02	2.835026E-01	-7.135382E-02	1.144477E-01	-6.646950E-03
6	G	8.698544E-03	1.001327E-02	1.589219E-01	-1.075122E-01	2.864622E-01	-1.969164E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	8.994799E-03	1.915860E-02	4.084826E-01	-1.527206E-01	-4.778250E-02	1.819116E-02
9	G	1.152813E-02	2.318262E-02	3.941741E-01	-1.171221E-01	4.557959E-02	1.006277E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST

4, 2000 MSC/NASTRAN 2/ 9/99

PAGE 261

SIX TENTHS, 50 DEG
LOAD STEP = 7.00000E+00

SUBCASE 60

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	7.581194E-03	8.458436E-07	3.886092E-01	1.197820E-04	8.321504E-02	-1.805600E-06
2	G	1.162412E-02	2.441492E-02	4.572498E-01	-2.183680E-01	-2.545530E-02	1.602713E-02
3	G	1.494432E-02	2.932926E-02	4.542971E-01	-1.647644E-01	3.352745E-02	2.406591E-03
4	G	1.729024E-02	2.726018E-02	3.990625E-01	-1.260330E-01	1.352257E-01	-9.376374E-03
5	G	1.552605E-02	2.059246E-02	3.011233E-01	-7.501353E-02	1.213794E-01	-7.505327E-03
6	G	9.840242E-03	1.132434E-02	1.689306E-01	-1.152686E-01	3.038815E-01	-2.233161E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.013645E-02	2.161890E-02	4.338627E-01	-1.623916E-01	-5.070873E-02	2.054305E-02
9	G	1.299663E-02	2.616820E-02	4.186393E-01	-1.244080E-01	4.836719E-02	1.149724E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST

4, 2000 MSC/NASTRAN 2/ 9/99

PAGE 262

SEVEN TENTHS, 50 DEG
LOAD STEP = 8.00000E+00

SUBCASE 70

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	8.373094E-03	1.043343E-06	4.091794E-01	1.533709E-04	9.816170E-02	-1.111037E-06
2	G	1.285104E-02	2.705444E-02	4.811992E-01	-2.307455E-01	-2.670303E-02	1.773081E-02
3	G	1.654369E-02	3.250533E-02	4.780871E-01	-1.739347E-01	3.512258E-02	2.697402E-03
4	G	1.915076E-02	3.021589E-02	4.199625E-01	-1.329996E-01	1.425166E-01	-1.043259E-02
5	G	1.719715E-02	2.282590E-02	3.168666E-01	-7.829646E-02	1.275837E-01	-8.318437E-03
6	G	1.092109E-02	1.256595E-02	1.778749E-01	-1.222441E-01	3.193755E-01	-2.483946E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.121132E-02	2.394246E-02	4.565393E-01	-1.709919E-01	-5.326021E-02	2.275931E-02
9	G	1.438179E-02	2.899014E-02	4.404984E-01	-1.308735E-01	5.082625E-02	1.291679E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST

4, 2000 MSC/NASTRAN 2/ 9/99

PAGE 263

EIGHT TENTHS, 50 DEG
LOAD STEP = 9.00000E+00

SUBCASE 80

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.122801E-03	1.251481E-06	4.278890E-01	1.895368E-04	1.124028E-01	-2.725551E-08
2	G	1.401626E-02	2.956696E-02	5.029356E-01	-2.419081E-01	-2.780411E-02	1.935205E-02
3	G	1.806474E-02	3.553078E-02	4.996772E-01	-1.822229E-01	3.656007E-02	2.978708E-03
4	G	2.092211E-02	3.303325E-02	4.389335E-01	-1.392932E-01	1.491181E-01	-1.143814E-02
5	G	1.878951E-02	2.495595E-02	3.311620E-01	-8.128972E-02	1.332253E-01	-9.094697E-03
6	G	1.195247E-02	1.375118E-02	1.859985E-01	-1.286191E-01	3.333861E-01	-2.724044E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.223165E-02	2.615484E-02	4.771309E-01	-1.787678E-01	-5.551777E-02	2.486379E-02
9	G	1.569910E-02	3.167911E-02	4.603474E-01	-1.367071E-01	5.303178E-02	1.432841E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST

4, 2000 MSC/NASTRAN 2/ 9/99

PAGE 264

NINE TENTHS, 50 DEG
LOAD STEP = 1.00000E+01

SUBCASE 90

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.837030E-03	1.469442E-06	4.451116E-01	2.280643E-04	1.260063E-01	1.462256E-06
2	G	1.512974E-02	3.197308E-02	5.229038E-01	-2.521006E-01	-2.878208E-02	2.090293E-02
3	G	1.952018E-02	3.843015E-02	5.195095E-01	-1.898055E-01	3.786932E-02	3.252583E-03
4	G	2.261883E-02	3.573494E-02	4.563631E-01	-1.450498E-01	1.551700E-01	-1.240113E-02
5	G	2.031605E-02	2.699964E-02	3.443005E-01	-8.405184E-02	1.384161E-01	-9.840101E-03
6	G	1.294250E-02	1.488931E-02	1.934664E-01	-1.345158E-01	3.462127E-01	-2.955249E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.320621E-02	2.827425E-02	4.960567E-01	-1.858857E-01	-5.753719E-02	2.687362E-02
9	G	1.695959E-02	3.425693E-02	4.785904E-01	-1.420361E-01	5.503477E-02	1.573644E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST

4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 265

ONE, 50 DEG
LOAD STEP = 1.10000E+01

SUBCASE 101

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	1.052079E-02	1.696563E-06	4.611138E-01	2.687792E-04	1.390327E-01	3.370562E-06
2	G	1.619893E-02	3.428819E-02	5.414210E-01	-2.614976E-01	-2.965485E-02	2.239256E-02
3	G	2.091945E-02	4.122172E-02	5.378991E-01	-1.968081E-01	3.907171E-02	3.520532E-03
4	G	2.425172E-02	3.833784E-02	4.725277E-01	-1.503665E-01	1.607720E-01	-1.332765E-02
5	G	2.178640E-02	2.896964E-02	3.564894E-01	-8.662429E-02	1.432360E-01	-1.055911E-02
6	G	1.389723E-02	1.598726E-02	2.003961E-01	-1.400209E-01	3.580684E-01	-3.178896E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.414151E-02	3.031421E-02	5.136153E-01	-1.924639E-01	-5.935894E-02	2.880169E-02
9	G	1.817147E-02	3.673984E-02	4.955153E-01	-1.469513E-01	5.687167E-02	1.714366E-03

ONE TENTH, 100 DEG
LOAD STEP = 2.00000E+00

SUBCASE 10

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	2.346308E-03	7.315836E-08	2.143476E-01	4.636918E-06	-3.391188E-03	-5.705064E-07
2	G	3.616564E-03	7.295535E-03	2.521480E-01	-1.080737E-01	-1.467426E-02	5.099681E-03
3	G	4.562809E-03	8.778515E-03	2.503752E-01	-8.314878E-02	2.013658E-02	6.022101E-04
4	G	5.255025E-03	8.174803E-03	2.200199E-01	-6.401072E-02	7.170751E-02	-2.551846E-03
5	G	4.737286E-03	6.186046E-03	1.663934E-01	-4.622937E-02	6.917207E-02	-2.323524E-03
6	G	2.913811E-03	3.347543E-03	9.241429E-02	-5.601825E-02	1.685808E-01	-6.386887E-03
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	3.115156E-03	6.554442E-03	2.402304E-01	-8.605577E-02	-2.727074E-02	6.156646E-03
9	G	4.005122E-03	7.935530E-03	2.320633E-01	-6.773310E-02	2.638878E-02	3.697436E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST

4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 260

TWO TENTHS, 100 DEG
LOAD STEP = 3.00000E+00

SUBCASE 20

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	3.708173E-03	1.840091E-07	2.697348E-01	1.788180E-05	1.507292E-02	-1.255223E-06
2	G	5.680357E-03	1.169128E-02	3.178137E-01	-1.446105E-01	-1.814258E-02	7.878458E-03
3	G	7.237460E-03	1.404849E-02	3.157307E-01	-1.105667E-01	2.442227E-02	1.036704E-03
4	G	8.353421E-03	1.305899E-02	2.773728E-01	-8.466130E-02	9.220309E-02	-4.295149E-03
5	G	7.514353E-03	9.868060E-03	2.095197E-01	-5.599876E-02	8.582520E-02	-3.642480E-03
6	G	4.682269E-03	5.374234E-03	1.168698E-01	-7.488492E-02	2.123306E-01	-1.041886E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	4.928184E-03	1.041977E-02	3.020646E-01	-1.114390E-01	-3.482983E-02	9.818718E-03
9	G	6.320811E-03	1.259911E-02	2.915854E-01	-8.587228E-02	3.347580E-02	5.524671E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST

4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 261

THREE TENTHS, 100 DEG
LOAD STEP = 4.00000E+00

SUBCASE 30

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	4.835729E-03	3.483844E-07	3.086623E-01	3.497380E-05	3.337522E-02	-2.329401E-06
2	G	7.404882E-03	1.534977E-02	3.636039E-01	-1.688070E-01	-2.045884E-02	1.021138E-02
3	G	9.466154E-03	1.843808E-02	3.612303E-01	-1.282386E-01	2.735849E-02	1.426965E-03
4	G	1.093451E-02	1.713703E-02	3.173424E-01	-9.838071E-02	1.063695E-01	-5.751423E-03
5	G	9.826409E-03	1.294387E-02	2.395884E-01	-6.226590E-02	9.750358E-02	-4.752915E-03
6	G	6.164168E-03	7.074482E-03	1.339424E-01	-8.794532E-02	2.425731E-01	-1.380619E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	6.438554E-03	1.364417E-02	3.453385E-01	-1.281950E-01	-4.017808E-02	1.290656E-02
9	G	8.253767E-03	1.650107E-02	3.333047E-01	-9.860296E-02	3.848257E-02	7.094024E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST

4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 262

FOUR TENTHS, 100 DEG
LOAD STEP = 5.00000E+00

SUBCASE 40

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	5.832965E-03	4.869472E-07	3.396954E-01	6.143744E-05	5.085446E-02	-2.126539E-06
2	G	8.933751E-03	1.861420E-02	4.000237E-01	-1.881740E-01	-2.246493E-02	1.230921E-02
3	G	1.145002E-02	2.235614E-02	3.974178E-01	-1.424921E-01	2.984951E-02	1.762529E-03
4	G	1.323303E-02	2.077421E-02	3.490951E-01	-1.090783E-01	1.175702E-01	-7.048291E-03
5	G	1.188583E-02	1.568835E-02	2.634825E-01	-6.719013E-02	1.068303E-01	-5.747240E-03
6	G	7.488214E-03	8.594590E-03	1.475106E-01	-9.833232E-02	2.664510E-01	-1.684310E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	7.779792E-03	1.651586E-02	3.797491E-01	-1.415380E-01	-4.428633E-02	1.565308E-02
9	G	9.972143E-03	1.997920E-02	3.664712E-01	-1.086622E-01	4.233133E-02	8.634869E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST

4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 263

FIVE TENTHS, 100 DEG
LOAD STEP = 6.00000E+00

nastran_final_results_positive_temp.txt

SUBCASE 50

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	6.742080E-03	6.595982E-07	3.659376E-01	8.894584E-05	6.743587E-02	-2.141277E-06
2	G	1.033300E-02	2.160871E-02	4.307275E-01	-2.042864E-01	-2.411381E-02	1.423699E-02
3	G	1.326819E-02	2.595385E-02	4.279239E-01	-1.543696E-01	3.189964E-02	2.082332E-03
4	G	1.534319E-02	2.411796E-02	3.758855E-01	-1.181162E-01	1.269835E-01	-8.244753E-03
5	G	1.377808E-02	1.821239E-02	2.836495E-01	-7.137049E-02	1.147282E-01	-6.663362E-03
6	G	8.707782E-03	9.994596E-03	1.589656E-01	-1.071804E-01	2.864941E-01	-1.965287E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	9.006498E-03	1.915109E-02	4.087872E-01	-1.526774E-01	-4.771665E-02	1.817569E-02
9	G	1.154708E-02	2.317423E-02	3.944625E-01	-1.170714E-01	4.556552E-02	1.009712E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 264

SIX TENTHS, 100 DEG
LOAD STEP = 7.00000E+00

SUBCASE 60

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	7.585615E-03	8.453646E-07	3.889022E-01	1.196685E-04	8.316352E-02	-1.816783E-06
2	G	1.163568E-02	2.440424E-02	4.575296E-01	-2.182479E-01	-2.553693E-02	1.604035E-02
3	G	1.496373E-02	2.931513E-02	4.545513E-01	-1.646891E-01	3.368625E-02	2.385333E-03
4	G	1.731335E-02	2.724398E-02	3.992743E-01	-1.259606E-01	1.351730E-01	-9.362727E-03
5	G	1.554621E-02	2.057330E-02	3.012625E-01	-7.503260E-02	1.216438E-01	-7.521703E-03
6	G	9.849513E-03	1.130568E-02	1.689720E-01	-1.149557E-01	3.039127E-01	-2.229287E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.014819E-02	2.161147E-02	4.341500E-01	-1.623522E-01	-5.064663E-02	2.052756E-02
9	G	1.301562E-02	2.615988E-02	4.189112E-01	-1.243607E-01	4.835358E-02	1.153197E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 265

SEVEN TENTHS, 100 DEG
LOAD STEP = 8.00000E+00

SUBCASE 70

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	8.377548E-03	1.042809E-06	4.094581E-01	1.532427E-04	9.811117E-02	-1.124610E-06
2	G	1.286265E-02	2.704385E-02	4.814656E-01	-2.306315E-01	-2.678158E-02	1.774433E-02
3	G	1.656314E-02	3.249130E-02	4.783294E-01	-1.738645E-01	3.527433E-02	2.675928E-03
4	G	1.917393E-02	3.019978E-02	4.201643E-01	-1.329302E-01	1.424660E-01	-1.041880E-02
5	G	1.721740E-02	2.280684E-02	3.169996E-01	-7.831702E-02	1.278352E-01	-8.334791E-03
6	G	1.093038E-02	1.254731E-02	1.779145E-01	-1.219462E-01	3.194060E-01	-2.480075E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.122308E-02	2.393509E-02	4.568128E-01	-1.709552E-01	-5.320133E-02	2.274385E-02
9	G	1.440081E-02	2.898189E-02	4.407571E-01	-1.308290E-01	5.081318E-02	1.295162E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 266

EIGHT TENTHS, 100 DEG
LOAD STEP = 9.00000E+00

SUBCASE 80

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.127286E-03	1.250894E-06	4.281558E-01	1.893946E-04	1.123533E-01	-4.332662E-08
2	G	1.402789E-02	2.955644E-02	5.031911E-01	-2.417991E-01	-2.787998E-02	1.936582E-02
3	G	1.808424E-02	3.551684E-02	4.999096E-01	-1.821566E-01	3.670589E-02	2.957067E-03
4	G	2.094533E-02	3.301722E-02	4.391271E-01	-1.392261E-01	1.490692E-01	-1.142424E-02
5	G	1.880983E-02	2.493698E-02	3.312898E-01	-8.131126E-02	1.334661E-01	-9.111037E-03
6	G	1.196179E-02	1.373256E-02	1.860366E-01	-1.283336E-01	3.334161E-01	-2.720176E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.224345E-02	2.614754E-02	4.773930E-01	-1.787333E-01	-5.546166E-02	2.484837E-02
9	G	1.571815E-02	3.167093E-02	4.605953E-01	-1.366648E-01	5.301927E-02	1.436319E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 267

NINE TENTHS, 100 DEG
LOAD STEP = 1.00000E+01

SUBCASE 90

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.841545E-03	1.468802E-06	4.453684E-01	2.279087E-04	1.259579E-01	1.443594E-06
2	G	1.514141E-02	3.196264E-02	5.231500E-01	-2.519959E-01	-2.885560E-02	2.091691E-02
3	G	1.953972E-02	3.841630E-02	5.197335E-01	-1.897423E-01	3.801002E-02	3.230809E-03
4	G	2.264209E-02	3.571898E-02	4.565497E-01	-1.449849E-01	1.551228E-01	-1.238715E-02
5	G	2.033645E-02	2.698075E-02	3.444239E-01	-8.407404E-02	1.386478E-01	-9.856430E-03
6	G	1.295184E-02	1.487071E-02	1.935032E-01	-1.342409E-01	3.462422E-01	-2.951384E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.321803E-02	2.826701E-02	4.963092E-01	-1.858529E-01	-5.748349E-02	2.685826E-02
9	G	1.697867E-02	3.424882E-02	4.788292E-01	-1.419957E-01	5.502278E-02	1.577108E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 268

ONE, 100 DEG
LOAD STEP = 1.10000E+01

SUBCASE 101

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	1.052533E-02	1.695872E-06	4.613619E-01	2.686107E-04	1.389854E-01	3.349228E-06
2	G	1.621063E-02	3.427781E-02	5.416592E-01	-2.613965E-01	-2.972628E-02	2.240671E-02
3	G	2.093902E-02	4.120795E-02	5.381159E-01	-1.967476E-01	3.920795E-02	3.498649E-03
4	G	2.427502E-02	3.832196E-02	4.727083E-01	-1.503035E-01	1.607262E-01	-1.331361E-02
5	G	2.180685E-02	2.895083E-02	3.566090E-01	-8.664693E-02	1.434598E-01	-1.057543E-02
6	G	1.390659E-02	1.596868E-02	2.004318E-01	-1.397551E-01	3.580976E-01	-3.175035E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.415336E-02	3.030703E-02	5.138595E-01	-1.924326E-01	-5.930737E-02	2.878639E-02
9	G	1.819057E-02	3.673179E-02	4.957463E-01	-1.469126E-01	5.686019E-02	1.717809E-03

ONE TENTH, 150 DEG
LOAD STEP = 2.00000E+00

nastran_final_results_positive_temp.txt

SUBCASE 10

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	2.354563E-03	7.366276E-08	2.149118E-01	4.696348E-06	-3.328901E-03	-5.742499E-07
2	G	3.621486E-03	7.317279E-03	2.529716E-01	-1.098151E-01	-1.511953E-02	5.103266E-03
3	G	4.592068E-03	8.802887E-03	2.512641E-01	-8.524304E-02	2.049389E-02	5.709227E-04
4	G	5.296557E-03	8.184847E-03	2.207512E-01	-6.510935E-02	7.185407E-02	-2.577779E-03
5	G	4.775199E-03	6.183512E-03	1.668808E-01	-4.689491E-02	6.973214E-02	-2.339091E-03
6	G	2.933926E-03	3.336375E-03	9.261449E-02	-5.595305E-02	1.689154E-01	-6.389252E-03
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	3.129553E-03	6.558679E-03	2.408560E-01	-8.719178E-02	-2.704529E-02	6.129972E-03
9	G	4.025673E-03	7.932787E-03	2.325669E-01	-6.745957E-02	2.623035E-02	3.747195E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 256

TWO TENTHS, 150 DEG
LOAD STEP = 3.00000E+00

SUBCASE 20

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	3.712575E-03	1.694269E-07	2.701582E-01	1.826190E-05	1.502717E-02	-1.264309E-06
2	G	5.691628E-03	1.168124E-02	3.182202E-01	-1.444839E-01	-1.824957E-02	7.888268E-03
3	G	7.256961E-03	1.403500E-02	3.161014E-01	-1.104852E-01	2.463765E-02	1.017125E-03
4	G	8.376823E-03	1.304318E-02	2.776830E-01	-8.458919E-02	9.214108E-02	-4.284007E-03
5	G	7.534677E-03	9.848950E-03	2.097218E-01	-5.600616E-02	8.620033E-02	-3.658775E-03
6	G	4.691985E-03	5.355895E-03	1.169338E-01	-7.446147E-02	2.123782E-01	-1.038185E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	4.939951E-03	1.041229E-02	3.024785E-01	-1.113954E-01	-3.473910E-02	9.802400E-03
9	G	6.339755E-03	1.259060E-02	2.919766E-01	-8.581370E-02	3.345615E-02	5.559138E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 257

THREE TENTHS, 150 DEG
LOAD STEP = 4.00000E+00

SUBCASE 30

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	4.839993E-03	3.288491E-07	3.090273E-01	3.757990E-05	3.332148E-02	-1.818605E-06
2	G	7.415303E-03	1.534081E-02	3.639657E-01	-1.688086E-01	-2.061691E-02	1.022721E-02
3	G	9.485699E-03	1.842505E-02	3.615601E-01	-1.282794E-01	2.762326E-02	1.398076E-03
4	G	1.095675E-02	1.711948E-02	3.175957E-01	-9.822046E-02	1.063034E-01	-5.735007E-03
5	G	9.845399E-03	1.292373E-02	2.397522E-01	-6.225341E-02	9.783161E-02	-4.769385E-03
6	G	6.172716E-03	7.055494E-03	1.339885E-01	-8.752506E-02	2.425996E-01	-1.376457E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	6.450269E-03	1.363628E-02	3.456935E-01	-1.282124E-01	-4.005688E-02	1.288674E-02
9	G	8.272197E-03	1.649183E-02	3.336361E-01	-9.855925E-02	3.842499E-02	7.159968E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 258

FOUR TENTHS, 150 DEG
LOAD STEP = 5.00000E+00

SUBCASE 40

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	5.837342E-03	4.865723E-07	3.400296E-01	6.135544E-05	5.080239E-02	-2.133453E-06
2	G	8.945124E-03	1.860377E-02	4.003441E-01	-1.880589E-01	-2.255802E-02	1.232134E-02
3	G	1.146943E-02	2.234224E-02	3.977095E-01	-1.424248E-01	3.003020E-02	1.741557E-03
4	G	1.325620E-02	2.075806E-02	3.493377E-01	-1.090056E-01	1.175133E-01	-7.035545E-03
5	G	1.190598E-02	1.566913E-02	2.636411E-01	-6.720678E-02	1.071319E-01	-5.763636E-03
6	G	7.497573E-03	8.575993E-03	1.475584E-01	-9.798019E-02	2.664857E-01	-1.680482E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	7.791505E-03	1.650834E-02	3.800761E-01	-1.415015E-01	-4.421180E-02	1.563709E-02
9	G	9.991050E-03	1.997068E-02	3.667799E-01	-1.086119E-01	4.231346E-02	8.671052E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 259

FIVE TENTHS, 150 DEG
LOAD STEP = 6.00000E+00

SUBCASE 50

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	6.746485E-03	6.592109E-07	3.662484E-01	8.884835E-05	6.738384E-02	-2.150111E-06
2	G	1.034446E-02	2.159823E-02	4.310251E-01	-2.041718E-01	-2.420116E-02	1.424973E-02
3	G	1.328762E-02	2.593991E-02	4.281947E-01	-1.543016E-01	3.206852E-02	2.061103E-03
4	G	1.536636E-02	2.410183E-02	3.761109E-01	-1.180446E-01	1.269289E-01	-8.231565E-03
5	G	1.379827E-02	1.819324E-02	2.837973E-01	-7.138930E-02	1.150090E-01	-6.679747E-03
6	G	8.717111E-03	9.975981E-03	1.590099E-01	-1.068506E-01	2.865269E-01	-1.961438E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	9.018232E-03	1.914363E-02	4.090916E-01	-1.526410E-01	-4.764832E-02	1.815984E-02
9	G	1.156603E-02	2.316581E-02	3.947501E-01	-1.170234E-01	4.554931E-02	1.013325E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 260

SIX TENTHS, 150 DEG
LOAD STEP = 7.00000E+00

SUBCASE 60

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	7.590050E-03	8.449124E-07	3.891950E-01	1.195550E-04	8.311211E-02	-1.827921E-06
2	G	1.164721E-02	2.439377E-02	4.578101E-01	-2.181361E-01	-2.561997E-02	1.605353E-02
3	G	1.498318E-02	2.930121E-02	4.548065E-01	-1.646226E-01	3.384609E-02	2.363893E-03
4	G	1.733655E-02	2.722789E-02	3.994867E-01	-1.258908E-01	1.351205E-01	-9.349250E-03
5	G	1.556466E-02	2.055423E-02	3.014021E-01	-7.505291E-02	1.219086E-01	-7.538075E-03
6	G	9.858836E-03	1.128706E-02	1.690136E-01	-1.146434E-01	3.039443E-01	-2.225427E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.015995E-02	2.160407E-02	4.344371E-01	-1.623169E-01	-5.058291E-02	2.051182E-02
9	G	1.303461E-02	2.615155E-02	4.191825E-01	-1.243150E-01	4.833854E-02	1.156801E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 261

SEVEN TENTHS, 150 DEG
LOAD STEP = 8.00000E+00

nastran_final_results_positive_temp.txt

SUBCASE 70

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	8.382013E-03	1.042297E-06	4.097366E-01	1.531141E-04	9.806063E-02	-1.138168E-06
2	G	1.287422E-02	2.703340E-02	4.817325E-01	-2.305230E-01	-2.686114E-02	1.775786E-02
3	G	1.658263E-02	3.247742E-02	4.785722E-01	-1.738001E-01	3.542689E-02	2.654313E-03
4	G	1.919716E-02	3.018375E-02	4.203665E-01	-1.328623E-01	1.424153E-01	-1.040512E-02
5	G	1.723771E-02	2.278785E-02	3.171327E-01	-7.833837E-02	1.280871E-01	-8.351152E-03
6	G	1.093971E-02	1.252870E-02	1.779542E-01	-1.216483E-01	3.194367E-01	-2.476209E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.123487E-02	2.392776E-02	4.570861E-01	-1.709213E-01	-5.314126E-02	2.272819E-02
9	G	1.441984E-02	2.897364E-02	4.410155E-01	-1.307854E-01	5.079908E-02	1.298751E-03
1	LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE				AUGUST	4, 2000 MSC/NASTRAN 2/ 9/99	PAGE 262

EIGHT TENTHS, 150 DEG
LOAD STEP = 9.00000E+00

SUBCASE 80

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.131779E-03	1.250324E-06	4.284225E-01	1.892518E-04	1.123038E-01	-5.940598E-08
2	G	1.403951E-02	2.954604E-02	5.034468E-01	-2.416939E-01	-2.795664E-02	1.937961E-02
3	G	1.810377E-02	3.550302E-02	5.001423E-01	-1.820944E-01	3.685236E-02	2.935308E-03
4	G	2.096860E-02	3.300125E-02	4.393209E-01	-1.391602E-01	1.490203E-01	-1.141041E-02
5	G	1.883020E-02	2.491806E-02	3.314177E-01	-8.133333E-02	1.337073E-01	-9.127391E-03
6	G	1.197113E-02	1.371396E-02	1.860746E-01	-1.280479E-01	3.334461E-01	-2.716306E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.225526E-02	2.614027E-02	4.776550E-01	-1.787006E-01	-5.540462E-02	2.483280E-02
9	G	1.573721E-02	3.166275E-02	4.608430E-01	-1.366231E-01	5.300594E-02	1.439887E-03
1	LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE				AUGUST	4, 2000 MSC/NASTRAN 2/ 9/99	PAGE 263

NINE TENTHS, 150 DEG
LOAD STEP = 1.00000E+01

SUBCASE 90

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.846064E-03	1.468177E-06	4.456252E-01	2.277524E-04	1.259095E-01	1.424906E-06
2	G	1.515307E-02	3.195228E-02	5.233963E-01	-2.518938E-01	-2.892977E-02	2.093092E-02
3	G	1.955928E-02	3.840254E-02	5.199577E-01	-1.896821E-01	3.815131E-02	3.208932E-03
4	G	2.266539E-02	3.570307E-02	4.567364E-01	-1.449207E-01	1.550754E-01	-1.237321E-02
5	G	2.035687E-02	2.696190E-02	3.445473E-01	-8.409661E-02	1.388799E-01	-9.872780E-03
6	G	1.296120E-02	1.485213E-02	1.935399E-01	-1.339653E-01	3.462717E-01	-2.947513E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.322987E-02	2.825980E-02	4.965615E-01	-1.858215E-01	-5.742903E-02	2.684277E-02
9	G	1.699775E-02	3.424071E-02	4.790678E-01	-1.419557E-01	5.501014E-02	1.580653E-03
1	LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE				AUGUST	4, 2000 MSC/NASTRAN 2/ 9/99	PAGE 264

ONE, 150 DEG
LOAD STEP = 1.10000E+01

SUBCASE 101

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	1.052988E-02	1.695193E-06	4.616101E-01	2.684416E-04	1.389380E-01	3.327855E-06
2	G	1.622233E-02	3.426750E-02	5.418974E-01	-2.612973E-01	-2.979827E-02	2.242091E-02
3	G	2.095861E-02	4.119426E-02	5.383328E-01	-1.966893E-01	3.934472E-02	3.476672E-03
4	G	2.429836E-02	3.830611E-02	4.728889E-01	-1.502410E-01	1.606801E-01	-1.329958E-02
5	G	2.182733E-02	2.893204E-02	3.567286E-01	-8.666985E-02	1.436840E-01	-1.059178E-02
6	G	1.391596E-02	1.595011E-02	2.004674E-01	-1.394885E-01	3.581266E-01	-3.171164E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.416523E-02	3.029988E-02	5.141035E-01	-1.924023E-01	-5.925516E-02	2.877099E-02
9	G	1.820968E-02	3.672376E-02	4.959770E-01	-1.468741E-01	5.684813E-02	1.721327E-03

ONE TENTH, 200 DEG
LOAD STEP = 2.00000E+00

SUBCASE 10

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	2.358828E-03	7.355487E-08	2.154434E-01	4.684988E-06	-3.362801E-03	-5.761007E-07
2	G	3.632650E-03	7.307108E-03	2.534819E-01	-1.096795E-01	-1.524501E-02	5.110674E-03
3	G	4.611491E-03	8.789221E-03	2.517288E-01	-8.515172E-02	2.075714E-02	5.528591E-04
4	G	5.319860E-03	8.168803E-03	2.211388E-01	-6.504311E-02	7.178964E-02	-2.568360E-03
5	G	4.795018E-03	6.163848E-03	1.671271E-01	-4.686970E-02	7.020464E-02	-2.355721E-03
6	G	2.943332E-03	3.317913E-03	9.269178E-02	-5.541647E-02	1.689633E-01	-6.350109E-03
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	3.141251E-03	6.551024E-03	2.413739E-01	-8.714139E-02	-2.693313E-02	6.114659E-03
9	G	4.044584E-03	7.924038E-03	2.330549E-01	-6.739330E-02	2.621151E-02	3.774358E-04
1	LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE				AUGUST	4, 2000 MSC/NASTRAN 2/ 9/99	PAGE 256

TWO TENTHS, 200 DEG
LOAD STEP = 3.00000E+00

SUBCASE 20

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	3.716719E-03	1.888906E-07	2.705789E-01	1.821163E-05	1.497423E-02	-1.268621E-06
2	G	5.703422E-03	1.166910E-02	3.186098E-01	-1.442316E-01	-1.834102E-02	7.899298E-03
3	G	7.275778E-03	1.401925E-02	3.164505E-01	-1.102743E-01	2.484437E-02	9.992043E-04
4	G	8.399097E-03	1.302614E-02	2.779767E-01	-8.447200E-02	9.206965E-02	-4.270735E-03
5	G	7.553637E-03	9.828915E-03	2.099097E-01	-5.598703E-02	8.657819E-02	-3.675682E-03
6	G	4.700567E-03	5.337120E-03	1.169882E-01	-7.400262E-02	2.124067E-01	-1.034199E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	4.951420E-03	1.040448E-02	3.028885E-01	-1.112869E-01	-3.466473E-02	9.788832E-03
9	G	6.358653E-03	1.258226E-02	2.923686E-01	-8.572534E-02	3.345108E-02	5.584656E-04
1	LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE				AUGUST	4, 2000 MSC/NASTRAN 2/ 9/99	PAGE 257

THREE TENTHS, 200 DEG
LOAD STEP = 4.00000E+00

nastran_final_results_positive_temp.txt

SUBCASE 30

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	4.844261E-03	3.265192E-07	3.093947E-01	3.734945E-05	3.326790E-02	-1.825553E-06
2	G	7.427104E-03	1.532900E-02	3.643081E-01	-1.685910E-01	-2.070095E-02	1.023906E-02
3	G	9.504713E-03	1.840973E-02	3.618683E-01	-1.281048E-01	2.780457E-02	1.379467E-03
4	G	1.097943E-02	1.710287E-02	3.178566E-01	-9.812324E-02	1.062364E-01	-5.721403E-03
5	G	9.865088E-03	1.290421E-02	2.399226E-01	-6.226011E-02	9.816133E-02	-4.785878E-03
6	G	6.181776E-03	7.036840E-03	1.340392E-01	-8.713431E-02	2.426335E-01	-1.372599E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	6.461823E-03	1.362863E-02	3.460529E-01	-1.281249E-01	-3.999297E-02	1.287267E-02
9	G	8.291194E-03	1.648359E-02	3.339798E-01	-9.848730E-02	3.841891E-02	7.187132E-04
1	LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE				AUGUST	4, 2000 MSC/NASTRAN 2/ 9/99	PAGE 258

FOUR TENTHS, 200 DEG
LOAD STEP = 5.00000E+00

SUBCASE 40

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	5.841684E-03	4.862183E-07	3.403639E-01	6.127398E-05	5.075003E-02	-2.140217E-06
2	G	8.956624E-03	1.859299E-02	4.006624E-01	-1.879218E-01	-2.264834E-02	1.233374E-02
3	G	1.148873E-02	2.232796E-02	3.979982E-01	-1.423348E-01	3.020914E-02	1.720930E-03
4	G	1.327918E-02	2.074175E-02	3.495784E-01	-1.089258E-01	1.174549E-01	-7.022371E-03
5	G	1.192590E-02	1.564980E-02	2.637981E-01	-6.721988E-02	1.074341E-01	-5.780150E-03
6	G	7.506717E-03	8.557346E-03	1.476050E-01	-9.762285E-02	2.665181E-01	-1.676605E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	7.803173E-03	1.650081E-02	3.804033E-01	-1.414543E-01	-4.414062E-02	1.562166E-02
9	G	1.000997E-02	1.996228E-02	3.670896E-01	-1.085571E-01	4.229835E-02	8.705228E-04
1	LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE				AUGUST	4, 2000 MSC/NASTRAN 2/ 9/99	PAGE 259

FIVE TENTHS, 200 DEG
LOAD STEP = 6.00000E+00

SUBCASE 50

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	6.750870E-03	6.587941E-07	3.665591E-01	8.875101E-05	6.733190E-02	-2.159005E-06
2	G	1.035600E-02	2.158754E-02	4.313215E-01	-2.040451E-01	-2.428700E-02	1.426264E-02
3	G	1.330698E-02	2.592576E-02	4.284639E-01	-1.542211E-01	3.223641E-02	2.040091E-03
4	G	1.538942E-02	2.408561E-02	3.763352E-01	-1.179692E-01	1.268734E-01	-8.218135E-03
5	G	1.381833E-02	1.817404E-02	2.839442E-01	-7.140635E-02	1.152901E-01	-6.696200E-03
6	G	8.726306E-03	9.957343E-03	1.590535E-01	-1.065180E-01	2.865586E-01	-1.957565E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	9.029939E-03	1.913618E-02	4.093960E-01	-1.525989E-01	-4.758198E-02	1.814435E-02
9	G	1.158499E-02	2.315747E-02	3.950382E-01	-1.169731E-01	4.553472E-02	1.016604E-02
1	LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE				AUGUST	4, 2000 MSC/NASTRAN 2/ 9/99	PAGE 260

SIX TENTHS, 200 DEG
LOAD STEP = 7.00000E+00

SUBCASE 60

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	7.594471E-03	8.444396E-07	3.894878E-01	1.194421E-04	8.306091E-02	-1.839073E-06
2	G	1.165878E-02	2.438316E-02	4.580899E-01	-2.180170E-01	-2.570211E-02	1.606681E-02
3	G	1.500260E-02	2.928716E-02	4.550608E-01	-1.645487E-01	3.400532E-02	2.342595E-03
4	G	1.735968E-02	2.721176E-02	3.996986E-01	-1.258189E-01	1.350674E-01	-9.335631E-03
5	G	1.558663E-02	2.053513E-02	3.015413E-01	-7.507224E-02	1.221735E-01	-7.554492E-03
6	G	9.868067E-03	1.126844E-02	1.690550E-01	-1.143297E-01	3.039752E-01	-2.221555E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.017169E-02	2.159669E-02	4.347242E-01	-1.622783E-01	-5.052045E-02	2.049632E-02
9	G	1.305360E-02	2.614329E-02	4.194542E-01	-1.242680E-01	4.832452E-02	1.160310E-03
1	LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE				AUGUST	4, 2000 MSC/NASTRAN 2/ 9/99	PAGE 261

SEVEN TENTHS, 200 DEG
LOAD STEP = 8.00000E+00

SUBCASE 70

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	8.386467E-03	1.041769E-06	4.100151E-01	1.529866E-04	9.801036E-02	-1.151706E-06
2	G	1.288582E-02	2.702288E-02	4.819990E-01	-2.304098E-01	-2.694011E-02	1.777144E-02
3	G	1.660210E-02	3.246347E-02	4.788145E-01	-1.737308E-01	3.557900E-02	2.632805E-03
4	G	1.922034E-02	3.016770E-02	4.205683E-01	-1.327931E-01	1.423644E-01	-1.039136E-02
5	G	1.725796E-02	2.276884E-02	3.172656E-01	-7.835913E-02	1.283390E-01	-8.367544E-03
6	G	1.094897E-02	1.251009E-02	1.779936E-01	-1.213497E-01	3.194670E-01	-2.472340E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.124664E-02	2.392044E-02	4.573594E-01	-1.708851E-01	-5.308209E-02	2.271272E-02
9	G	1.443886E-02	2.896544E-02	4.412740E-01	-1.307411E-01	5.078568E-02	1.302265E-03
1	LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE				AUGUST	4, 2000 MSC/NASTRAN 2/ 9/99	PAGE 262

EIGHT TENTHS, 200 DEG
LOAD STEP = 9.00000E+00

SUBCASE 80

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.136263E-03	1.249742E-06	4.286892E-01	1.891103E-04	1.122545E-01	-7.543910E-08
2	G	1.405115E-02	2.953558E-02	5.037022E-01	-2.415854E-01	-2.803286E-02	1.939344E-02
3	G	1.812327E-02	3.548915E-02	5.003747E-01	-1.820288E-01	3.699848E-02	2.913637E-03
4	G	2.099183E-02	3.298527E-02	4.395144E-01	-1.390933E-01	1.489712E-01	-1.139654E-02
5	G	1.885052E-02	2.489913E-02	3.315454E-01	-8.135502E-02	1.339484E-01	-9.143766E-03
6	G	1.198041E-02	1.369537E-02	1.861126E-01	-1.277617E-01	3.334759E-01	-2.712439E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.226706E-02	2.613301E-02	4.779169E-01	-1.786665E-01	-5.534826E-02	2.481738E-02
9	G	1.575626E-02	3.165462E-02	4.610908E-01	-1.365809E-01	5.299314E-02	1.443394E-03
1	LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE				AUGUST	4, 2000 MSC/NASTRAN 2/ 9/99	PAGE 263

NINE TENTHS, 200 DEG
LOAD STEP = 1.00000E+01

nastran_final_results_positive_temp.txt

SUBCASE 90

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.850577E-03	1.467542E-06	4.458818E-01	2.275975E-04	1.258613E-01	1.406285E-06
2	G	1.516475E-02	3.194189E-02	5.236424E-01	-2.517894E-01	-2.900360E-02	2.094495E-02
3	G	1.957882E-02	3.838874E-02	5.201817E-01	-1.896195E-01	3.829228E-02	3.187131E-03
4	G	2.268866E-02	3.568717E-02	4.569229E-01	-1.448560E-01	1.550279E-01	-1.235925E-02
5	G	2.037725E-02	2.694305E-02	3.446706E-01	-8.411893E-02	1.391118E-01	-9.889145E-03
6	G	1.297050E-02	1.483355E-02	1.935766E-01	-1.336898E-01	3.463010E-01	-2.943649E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.324170E-02	2.825260E-02	4.968138E-01	-1.857890E-01	-5.737512E-02	2.682741E-02
9	G	1.701683E-02	3.423264E-02	4.793065E-01	-1.419154E-01	5.499790E-02	1.584143E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 264

ONE, 200 DEG
LOAD STEP = 1.10000E+01

SUBCASE 101

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	1.053442E-02	1.694507E-06	4.618582E-01	2.682737E-04	1.388909E-01	3.306567E-06
2	G	1.623403E-02	3.425718E-02	5.421355E-01	-2.611965E-01	-2.986997E-02	2.243511E-02
3	G	2.097819E-02	4.118055E-02	5.385495E-01	-1.966292E-01	3.948121E-02	3.454765E-03
4	G	2.432167E-02	3.829027E-02	4.730695E-01	-1.501782E-01	1.606341E-01	-1.328555E-02
5	G	2.184778E-02	2.891327E-02	3.568482E-01	-8.669259E-02	1.439081E-01	-1.060814E-02
6	G	1.392529E-02	1.593155E-02	2.005030E-01	-1.392221E-01	3.581556E-01	-3.167303E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.417708E-02	3.029274E-02	5.143476E-01	-1.923712E-01	-5.920339E-02	2.875570E-02
9	G	1.822879E-02	3.671575E-02	4.962078E-01	-1.468355E-01	5.683643E-02	1.724796E-03

ONE TENTH, 250 DEG
LOAD STEP = 2.00000E+00

SUBCASE 10

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	2.363033E-03	7.343962E-08	2.159703E-01	4.665842E-06	-3.403791E-03	-5.777393E-07
2	G	3.643904E-03	7.296593E-03	2.539834E-01	-1.095093E-01	-1.536469E-02	5.118910E-03
3	G	4.630649E-03	8.775120E-03	2.521832E-01	-8.501925E-02	2.101760E-02	5.348585E-04
4	G	5.342728E-03	8.152617E-03	2.215182E-01	-6.495472E-02	7.172048E-02	-2.558138E-03
5	G	4.814449E-03	6.144236E-03	1.673685E-01	-4.683664E-02	7.067232E-02	-2.372622E-03
6	G	2.952478E-03	3.299581E-03	9.276688E-02	-5.487816E-02	1.690079E-01	-6.314811E-03
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	3.152844E-03	6.543413E-03	2.418869E-01	-8.707152E-02	-2.682437E-02	6.099723E-03
9	G	4.063388E-03	7.915500E-03	2.335400E-01	-6.731428E-02	2.619459E-02	3.801831E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 256

TWO TENTHS, 250 DEG
LOAD STEP = 3.00000E+00

SUBCASE 20

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	3.721013E-03	1.876693E-07	2.709981E-01	1.806309E-05	1.492617E-02	-1.268161E-06
2	G	5.714573E-03	1.165900E-02	3.190134E-01	-1.441215E-01	-1.845442E-02	7.909453E-03
3	G	7.295143E-03	1.400564E-02	3.168182E-01	-1.102137E-01	2.506831E-02	9.791233E-04
4	G	8.422216E-03	1.301008E-02	2.782815E-01	-8.439799E-02	9.200720E-02	-4.259521E-03
5	G	7.573499E-03	9.809544E-03	2.101060E-01	-5.598822E-02	8.695560E-02	-3.692281E-03
6	G	4.709831E-03	5.318651E-03	1.170481E-01	-7.356627E-02	2.124461E-01	-1.030420E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	4.963083E-03	1.039693E-02	3.032975E-01	-1.112528E-01	-3.456799E-02	9.772852E-03
9	G	6.377453E-03	1.257362E-02	2.927535E-01	-8.566884E-02	3.342805E-02	5.619347E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 257

THREE TENTHS, 250 DEG
LOAD STEP = 4.00000E+00

SUBCASE 30

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	4.848585E-03	3.294755E-07	3.097619E-01	3.753616E-05	3.321725E-02	-1.826345E-06
2	G	7.438387E-03	1.531869E-02	3.646605E-01	-1.684768E-01	-2.080315E-02	1.025057E-02
3	G	9.524080E-03	1.839592E-02	3.621891E-01	-1.280400E-01	2.800407E-02	1.358714E-03
4	G	1.100250E-02	1.708670E-02	3.181224E-01	-9.804715E-02	1.061767E-01	-5.709176E-03
5	G	9.884978E-03	1.288487E-02	2.400948E-01	-6.226915E-02	9.849365E-02	-4.802479E-03
6	G	6.190944E-03	7.018265E-03	1.340908E-01	-8.674479E-02	2.426680E-01	-1.368752E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	6.473503E-03	1.362111E-02	3.464116E-01	-1.280889E-01	-3.990861E-02	1.285669E-02
9	G	8.310039E-03	1.647504E-02	3.343178E-01	-9.843343E-02	3.839834E-02	7.223327E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 258

FOUR TENTHS, 250 DEG
LOAD STEP = 5.00000E+00

SUBCASE 40

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	5.846040E-03	4.858726E-07	3.406981E-01	6.119399E-05	5.069811E-02	-2.146970E-06
2	G	8.968079E-03	1.858240E-02	4.009814E-01	-1.877940E-01	-2.274017E-02	1.234609E-02
3	G	1.150808E-02	2.231390E-02	3.982881E-01	-1.422546E-01	3.038908E-02	1.700149E-03
4	G	1.330224E-02	2.072557E-02	3.498198E-01	-1.088492E-01	1.173968E-01	-7.009384E-03
5	G	1.194591E-02	1.563056E-02	2.639557E-01	-6.723475E-02	1.077364E-01	-5.796646E-03
6	G	7.515911E-03	8.538748E-03	1.476520E-01	-9.726696E-02	2.665512E-01	-1.672753E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	7.814863E-03	1.649334E-02	3.807302E-01	-1.414118E-01	-4.406792E-02	1.560602E-02
9	G	1.002890E-02	1.995388E-02	3.673987E-01	-1.085044E-01	4.228185E-02	8.74045E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 259

FIVE TENTHS, 250 DEG
LOAD STEP = 6.00000E+00

nastran_final_results_positive_temp.txt

SUBCASE 50

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	6.755263E-03	6.583928E-07	3.668698E-01	8.865409E-05	6.728020E-02	-2.167857E-06
2	G	1.036750E-02	2.157700E-02	4.316184E-01	-2.039240E-01	-2.437386E-02	1.427552E-02
3	G	1.332638E-02	2.591176E-02	4.287338E-01	-1.541465E-01	3.240503E-02	2.018962E-03
4	G	1.541253E-02	2.406949E-02	3.765600E-01	-1.178957E-01	1.268180E-01	-8.204821E-03
5	G	1.383844E-02	1.815490E-02	2.840914E-01	-7.142432E-02	1.155715E-01	-6.712656E-03
6	G	8.735521E-03	9.938740E-03	1.590973E-01	-1.061860E-01	2.865905E-01	-1.953703E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	9.041660E-03	1.912876E-02	4.097003E-01	-1.525595E-01	-4.751458E-02	1.812871E-02
9	G	1.160395E-02	2.314915E-02	3.953259E-01	-1.169239E-01	4.551916E-02	1.020362E-03
1	LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE	AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99					

SIX TENTHS, 250 DEG
LOAD STEP = 7.00000E+00

SUBCASE 60

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	7.598898E-03	8.439784E-07	3.897805E-01	1.193295E-04	8.300985E-02	-1.850199E-06
2	G	1.167033E-02	2.437266E-02	4.583699E-01	-2.179014E-01	-2.578493E-02	1.608010E-02
3	G	1.502204E-02	2.927322E-02	4.553154E-01	-1.644784E-01	3.416507E-02	2.321215E-03
4	G	1.738283E-02	2.719570E-02	3.999106E-01	-1.257480E-01	1.350144E-01	-9.322083E-03
5	G	1.560682E-02	2.051608E-02	3.016806E-01	-7.509211E-02	1.224387E-01	-7.570918E-03
6	G	9.877303E-03	1.124984E-02	1.690963E-01	-1.140160E-01	3.040062E-01	-2.217690E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.018344E-02	2.158933E-02	4.350112E-01	-1.622413E-01	-5.045727E-02	2.048072E-02
9	G	1.307259E-02	2.613503E-02	4.197256E-01	-1.242217E-01	4.830984E-02	1.163878E-03
1	LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE	AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99					

SEVEN TENTHS, 250 DEG
LOAD STEP = 8.00000E+00

SUBCASE 70

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	8.390925E-03	1.041250E-06	4.102935E-01	1.528591E-04	9.796018E-02	-1.165229E-06
2	G	1.289742E-02	2.701242E-02	4.822655E-01	-2.302988E-01	-2.701958E-02	1.778504E-02
3	G	1.662157E-02	3.244960E-02	4.790569E-01	-1.736640E-01	3.573152E-02	2.611233E-03
4	G	1.924354E-02	3.015169E-02	4.207702E-01	-1.327246E-01	1.423133E-01	-1.037764E-02
5	G	1.727822E-02	2.274987E-02	3.173986E-01	-7.838023E-02	1.285912E-01	-8.383950E-03
6	G	1.095823E-02	1.249150E-02	1.780331E-01	-1.210509E-01	3.194973E-01	-2.468472E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.125842E-02	2.391315E-02	4.576326E-01	-1.708502E-01	-5.302238E-02	2.269718E-02
9	G	1.445788E-02	2.895726E-02	4.415324E-01	-1.306971E-01	5.077178E-02	1.305829E-03
1	LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE	AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99					

EIGHT TENTHS, 250 DEG
LOAD STEP = 9.00000E+00

SUBCASE 80

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.140751E-03	1.249168E-06	4.289558E-01	1.889687E-04	1.122053E-01	-9.146328E-08
2	G	1.406279E-02	2.952518E-02	5.039577E-01	-2.414786E-01	-2.810949E-02	1.940729E-02
3	G	1.814279E-02	3.547534E-02	5.006071E-01	-1.819649E-01	3.714494E-02	2.891913E-03
4	G	2.101507E-02	3.296933E-02	4.397080E-01	-1.390270E-01	1.489219E-01	-1.138269E-02
5	G	1.887085E-02	2.488024E-02	3.316731E-01	-8.137695E-02	1.341898E-01	-9.160158E-03
6	G	1.198969E-02	1.367679E-02	1.861505E-01	-1.274752E-01	3.335055E-01	-2.708571E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.227887E-02	2.612578E-02	4.781788E-01	-1.786332E-01	-5.529148E-02	2.480190E-02
9	G	1.577532E-02	3.164650E-02	4.613384E-01	-1.365391E-01	5.297995E-02	1.446943E-03
1	LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE	AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99					

NINE TENTHS, 250 DEG
LOAD STEP = 1.00000E+01

SUBCASE 90

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.855093E-03	1.466914E-06	4.461384E-01	2.274424E-04	1.258131E-01	1.387669E-06
2	G	1.517642E-02	3.193155E-02	5.238886E-01	-2.516862E-01	-2.907776E-02	2.095901E-02
3	G	1.959837E-02	3.837501E-02	5.204057E-01	-1.895582E-01	3.843356E-02	3.165283E-03
4	G	2.271195E-02	3.567130E-02	4.571095E-01	-1.447916E-01	1.549802E-01	-1.234530E-02
5	G	2.039765E-02	2.692423E-02	3.447939E-01	-8.414143E-02	1.393441E-01	-9.905529E-03
6	G	1.297980E-02	1.481498E-02	1.936132E-01	-1.334138E-01	3.463302E-01	-2.939781E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.325354E-02	2.824542E-02	4.970661E-01	-1.857572E-01	-5.732085E-02	2.681200E-02
9	G	1.703592E-02	3.422458E-02	4.795450E-01	-1.418754E-01	5.498534E-02	1.587671E-03
1	LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE	AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99					

ONE, 250 DEG
LOAD STEP = 1.10000E+01

SUBCASE 101

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	1.053896E-02	1.693926E-06	4.621062E-01	2.681058E-04	1.388438E-01	3.285279E-06
2	G	1.624574E-02	3.424689E-02	5.423737E-01	-2.610965E-01	-2.994197E-02	2.244934E-02
3	G	2.099777E-02	4.116688E-02	5.387663E-01	-1.965701E-01	3.961797E-02	3.432815E-03
4	G	2.434500E-02	3.827447E-02	4.732500E-01	-1.501155E-01	1.605879E-01	-1.327153E-02
5	G	2.186823E-02	2.889451E-02	3.569677E-01	-8.671547E-02	1.441324E-01	-1.062452E-02
6	G	1.393461E-02	1.591300E-02	2.005386E-01	-1.389552E-01	3.581844E-01	-3.163436E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.418895E-02	3.026561E-02	5.145916E-01	-1.923406E-01	-5.915133E-02	2.874036E-02
9	G	1.824790E-02	3.670775E-02	4.964386E-01	-1.467970E-01	5.682444E-02	1.728299E-03

ONE TENTH, 300 DEG
LOAD STEP = 2.00000E+00

nastran_final_results_positive_temp.txt

SUBCASE 10

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	2.367231E-03	7.332545E-08	2.164965E-01	4.645270E-06	-3.444421E-03	-5.792397E-07
2	G	3.655146E-03	7.286183E-03	2.544847E-01	-1.093424E-01	-1.548555E-02	5.126880E-03
3	G	4.649807E-03	8.761142E-03	2.526376E-01	-8.489065E-02	2.127886E-02	5.170402E-04
4	G	5.365598E-03	8.136533E-03	2.218976E-01	-6.486823E-02	7.165094E-02	-2.548040E-03
5	G	4.833857E-03	6.124710E-03	1.676096E-01	-4.680381E-02	7.114077E-02	-2.389323E-03
6	G	2.961559E-03	3.281304E-03	9.284169E-02	-5.433842E-02	1.690515E-01	-6.277717E-03
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	3.164432E-03	6.535877E-03	2.423992E-01	-8.700369E-02	-2.671536E-02	6.084937E-03
9	G	4.082184E-03	7.907037E-03	2.340243E-01	-6.723669E-02	2.617735E-02	3.829050E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE
AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 256

TWO TENTHS, 300 DEG
LOAD STEP = 3.00000E+00

SUBCASE 20

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	3.725439E-03	1.889507E-07	2.714158E-01	1.813912E-05	1.488237E-02	-1.273246E-06
2	G	5.725359E-03	1.165020E-02	3.194245E-01	-1.440907E-01	-1.857800E-02	7.918866E-03
3	G	7.314885E-03	1.399343E-02	3.171967E-01	-1.102358E-01	2.529720E-02	9.580322E-04
4	G	8.446011E-03	1.299481E-02	2.785947E-01	-8.435494E-02	9.194899E-02	-4.249698E-03
5	G	7.594205E-03	9.790799E-03	2.103101E-01	-5.600928E-02	8.733071E-02	-3.708508E-03
6	G	4.719755E-03	5.300478E-03	1.171133E-01	-7.315342E-02	2.124966E-01	-1.026866E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	4.974892E-03	1.038957E-02	3.037057E-01	-1.112604E-01	-3.446111E-02	9.755251E-03
9	G	6.396240E-03	1.256487E-02	2.931347E-01	-8.563216E-02	3.339537E-02	5.659220E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE
AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 257

THREE TENTHS, 300 DEG
LOAD STEP = 4.00000E+00

SUBCASE 30

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	4.852986E-03	3.283553E-07	3.101283E-01	3.739091E-05	3.316884E-02	-1.831720E-06
2	G	7.449308E-03	1.530956E-02	3.650196E-01	-1.684336E-01	-2.091648E-02	1.026163E-02
3	G	9.543752E-03	1.838334E-02	3.625188E-01	-1.280505E-01	2.821230E-02	1.336702E-03
4	G	1.102603E-02	1.707107E-02	3.183935E-01	-9.799135E-02	1.061213E-01	-5.698113E-03
5	G	9.905346E-03	1.286589E-02	2.402707E-01	-6.228699E-02	9.882587E-02	-4.818925E-03
6	G	6.200474E-03	6.999864E-03	1.341448E-01	-8.636558E-02	2.427074E-01	-1.365015E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	6.485301E-03	1.361371E-02	3.467694E-01	-1.280889E-01	-3.981226E-02	1.283924E-02
9	G	8.328821E-03	1.646632E-02	3.346521E-01	-9.839413E-02	3.836816E-02	7.265609E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE
AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 258

FOUR TENTHS, 300 DEG
LOAD STEP = 5.00000E+00

SUBCASE 40

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	5.850434E-03	4.857433E-07	3.410318E-01	6.111067E-05	5.064701E-02	-2.152988E-06
2	G	8.979396E-03	1.857231E-02	4.013026E-01	-1.876912E-01	-2.283575E-02	1.235824E-02
3	G	1.152756E-02	2.230036E-02	3.985811E-01	-1.422006E-01	3.057159E-02	1.678923E-03
4	G	1.332551E-02	2.070965E-02	3.500633E-01	-1.087805E-01	1.173398E-01	-6.996883E-03
5	G	1.196615E-02	1.561151E-02	2.641148E-01	-6.725361E-02	1.080389E-01	-5.813071E-03
6	G	7.525272E-03	8.520246E-03	1.477000E-01	-9.691537E-02	2.665863E-01	-1.668954E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	7.826608E-03	1.648592E-02	3.810567E-01	-1.413818E-01	-4.399104E-02	1.558977E-02
9	G	1.004780E-02	1.994544E-02	3.677065E-01	-1.084568E-01	4.226176E-02	8.778234E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE
AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 259

FIVE TENTHS, 300 DEG
LOAD STEP = 6.00000E+00

SUBCASE 50

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	6.759678E-03	6.579987E-07	3.671802E-01	8.855948E-05	6.722878E-02	-2.176700E-06
2	G	1.037893E-02	2.156675E-02	4.319165E-01	-2.038171E-01	-2.446296E-02	1.428832E-02
3	G	1.334585E-02	2.589808E-02	4.290054E-01	-1.540870E-01	3.257529E-02	1.997545E-03
4	G	1.543577E-02	2.405353E-02	3.767858E-01	-1.178264E-01	1.267631E-01	-8.191791E-03
5	G	1.385868E-02	1.813587E-02	2.842394E-01	-7.144435E-02	1.158531E-01	-6.729087E-03
6	G	8.744824E-03	9.920197E-03	1.591415E-01	-1.058557E-01	2.866232E-01	-1.949869E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	9.053417E-03	1.912139E-02	4.100043E-01	-1.525272E-01	-4.744458E-02	1.811268E-02
9	G	1.162290E-02	2.314080E-02	3.956128E-01	-1.168775E-01	4.550137E-02	1.024107E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE
AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 260

SIX TENTHS, 300 DEG
LOAD STEP = 7.00000E+00

SUBCASE 60

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	7.603341E-03	8.435464E-07	3.900730E-01	1.192166E-04	8.295889E-02	-1.861275E-06
2	G	1.168183E-02	2.436238E-02	4.586506E-01	-2.177948E-01	-2.586929E-02	1.609335E-02
3	G	1.504153E-02	2.925951E-02	4.555710E-01	-1.644178E-01	3.432596E-02	2.299629E-03
4	G	1.740608E-02	2.717976E-02	4.001232E-01	-1.256798E-01	1.349615E-01	-9.308717E-03
5	G	1.562710E-02	2.049710E-02	3.018203E-01	-7.511331E-02	1.227042E-01	-7.587337E-03
6	G	9.886597E-03	1.123128E-02	1.691380E-01	-1.137031E-01	3.040375E-01	-2.213838E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.019522E-02	2.158201E-02	4.352980E-01	-1.622089E-01	-5.039230E-02	2.046484E-02
9	G	1.309158E-02	2.612677E-02	4.199965E-01	-1.241771E-01	4.829361E-02	1.167591E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE
AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 261

SEVEN TENTHS, 300 DEG
LOAD STEP = 8.00000E+00

nastran_final_results_positive_temp.txt

SUBCASE 70

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	8.395394E-03	1.040754E-06	4.105718E-01	1.527310E-04	9.791000E-02	-1.178735E-06
2	G	1.290898E-02	2.700212E-02	4.825325E-01	-2.301937E-01	-2.710015E-02	1.779864E-02
3	G	1.664109E-02	3.243589E-02	4.793001E-01	-1.736036E-01	3.588490E-02	2.589505E-03
4	G	1.926681E-02	3.013578E-02	4.209725E-01	-1.326578E-01	1.422623E-01	-1.036403E-02
5	G	1.729855E-02	2.273095E-02	3.175318E-01	-7.840219E-02	1.288438E-01	-8.400363E-03
6	G	1.096752E-02	1.247294E-02	1.780727E-01	-1.207521E-01	3.195276E-01	-2.464609E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.127022E-02	2.390589E-02	4.579057E-01	-1.708181E-01	-5.296138E-02	2.268143E-02
9	G	1.447691E-02	2.894907E-02	4.417904E-01	-1.306543E-01	5.075677E-02	1.309507E-03
1	LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE				AUGUST	4, 2000 MSC/NASTRAN 2/ 9/99	PAGE 262

EIGHT TENTHS, 300 DEG
LOAD STEP = 9.00000E+00

SUBCASE 80

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.145248E-03	1.248612E-06	4.292223E-01	1.888263E-04	1.121561E-01	-1.074963E-07
2	G	1.407440E-02	2.951490E-02	5.042135E-01	-2.413757E-01	-2.818697E-02	1.942116E-02
3	G	1.816233E-02	3.546166E-02	5.008400E-01	-1.819055E-01	3.729211E-02	2.870061E-03
4	G	2.103836E-02	3.295346E-02	4.399018E-01	-1.389618E-01	1.488726E-01	-1.136891E-02
5	G	1.889123E-02	2.486138E-02	3.318010E-01	-8.139946E-02	1.344316E-01	-9.176566E-03
6	G	1.199899E-02	1.365823E-02	1.861885E-01	-1.271884E-01	3.335351E-01	-2.704701E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.229070E-02	2.611857E-02	4.784405E-01	-1.786019E-01	-5.523369E-02	2.478626E-02
9	G	1.579438E-02	3.163838E-02	4.615857E-01	-1.364979E-01	5.296589E-02	1.450590E-03
1	LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE				AUGUST	4, 2000 MSC/NASTRAN 2/ 9/99	PAGE 263

NINE TENTHS, 300 DEG
LOAD STEP = 1.00000E+01

SUBCASE 90

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.859617E-03	1.466301E-06	4.463950E-01	2.272865E-04	1.257649E-01	1.369025E-06
2	G	1.518807E-02	3.192129E-02	5.241349E-01	-2.515858E-01	-2.915262E-02	2.097310E-02
3	G	1.961795E-02	3.836136E-02	5.206300E-01	-1.895001E-01	3.857545E-02	3.143323E-03
4	G	2.273527E-02	3.565548E-02	4.572962E-01	-1.447279E-01	1.549324E-01	-1.233139E-02
5	G	2.041808E-02	2.690544E-02	3.449173E-01	-8.416432E-02	1.395768E-01	-9.921934E-03
6	G	1.298912E-02	1.479644E-02	1.936498E-01	-1.331372E-01	3.463593E-01	-2.935907E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.326539E-02	2.823826E-02	4.973182E-01	-1.857268E-01	-5.726577E-02	2.679646E-02
9	G	1.705501E-02	3.421653E-02	4.797833E-01	-1.418357E-01	5.497207E-02	1.591287E-03
1	LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE				AUGUST	4, 2000 MSC/NASTRAN 2/ 9/99	PAGE 264

ONE, 300 DEG
LOAD STEP = 1.10000E+01

SUBCASE 101

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	1.054351E-02	1.693159E-06	4.623542E-01	2.679370E-04	1.387966E-01	3.263949E-06
2	G	1.625744E-02	3.423667E-02	5.426119E-01	-2.609986E-01	-3.001457E-02	2.246363E-02
3	G	2.101739E-02	4.115329E-02	5.389833E-01	-1.965135E-01	3.975530E-02	3.410762E-03
4	G	2.436835E-02	3.825870E-02	4.734306E-01	-1.500534E-01	1.605414E-01	-1.325752E-02
5	G	2.188871E-02	2.887578E-02	3.570872E-01	-8.673865E-02	1.443572E-01	-1.064092E-02
6	G	1.394394E-02	1.589447E-02	2.005741E-01	-1.386875E-01	3.582129E-01	-3.159559E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.420082E-02	3.027851E-02	5.148355E-01	-1.923111E-01	-5.909856E-02	2.872492E-02
9	G	1.826702E-02	3.669976E-02	4.966691E-01	-1.467588E-01	5.681183E-02	1.731883E-03

LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 255

ONE TENTH, 350 DEG
LOAD STEP = 2.00000E+00

SUBCASE 10

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	2.371495E-03	7.320489E-08	2.170217E-01	4.630460E-06	-3.476444E-03	-5.806948E-07
2	G	3.666557E-03	7.275717E-03	2.549841E-01	-1.091455E-01	-1.559989E-02	5.135071E-03
3	G	4.668949E-03	8.747096E-03	2.530893E-01	-8.472092E-02	2.153227E-02	4.999061E-04
4	G	5.388543E-03	8.120810E-03	2.222783E-01	-6.478049E-02	7.157630E-02	-2.537698E-03
5	G	4.853522E-03	6.105624E-03	1.678543E-01	-4.678436E-02	7.160768E-02	-2.406012E-03
6	G	2.970786E-03	3.263273E-03	9.291686E-02	-5.381036E-02	1.691005E-01	-6.241180E-03
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	3.176010E-03	6.528637E-03	2.429127E-01	-8.692455E-02	-2.661762E-02	6.071128E-03
9	G	4.101096E-03	7.899066E-03	2.345122E-01	-6.715883E-02	2.616498E-02	3.852794E-04
1	LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE				AUGUST	4, 2000 MSC/NASTRAN 2/ 9/99	PAGE 256

TWO TENTHS, 350 DEG
LOAD STEP = 3.00000E+00

SUBCASE 20

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	3.729725E-03	1.887200E-07	2.718346E-01	1.808593E-05	1.482835E-02	-1.275194E-06
2	G	5.736610E-03	1.164003E-02	3.198259E-01	-1.439630E-01	-1.868842E-02	7.928989E-03
3	G	7.334214E-03	1.397976E-02	3.175620E-01	-1.101564E-01	2.551834E-02	9.383397E-04
4	G	8.469090E-03	1.297885E-02	2.788986E-01	-8.427811E-02	9.188408E-02	-4.238381E-03
5	G	7.614023E-03	9.771534E-03	2.105061E-01	-5.601090E-02	8.770895E-02	-3.725113E-03
6	G	4.728916E-03	5.282075E-03	1.171728E-01	-7.271501E-02	2.125353E-01	-1.023089E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	4.986551E-03	1.038213E-02	3.041144E-01	-1.112177E-01	-3.436704E-02	9.739504E-03
9	G	6.415078E-03	1.255643E-02	2.935203E-01	-8.557276E-02	3.337402E-02	5.693221E-04
1	LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE				AUGUST	4, 2000 MSC/NASTRAN 2/ 9/99	PAGE 257

THREE TENTHS, 350 DEG
LOAD STEP = 4.00000E+00

SUBCASE 30

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	4.857322E-03	3.278347E-07	3.104949E-01	3.733337E-05	3.311871E-02	-1.837423E-06
2	G	7.460625E-03	1.529932E-02	3.653711E-01	-1.683142E-01	-2.101783E-02	1.027318E-02
3	G	9.563133E-03	1.836963E-02	3.628388E-01	-1.279804E-01	2.840982E-02	1.316117E-03
4	G	1.104917E-02	1.705508E-02	3.186597E-01	-9.791681E-02	1.060603E-01	-5.685914E-03
5	G	9.925346E-03	1.284671E-02	2.404437E-01	-6.229918E-02	9.915807E-02	-4.835480E-03
6	G	6.209685E-03	6.981382E-03	1.341969E-01	-8.597846E-02	2.427431E-01	-1.361213E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	6.496992E-03	1.360627E-02	3.471277E-01	-1.280508E-01	-3.972953E-02	1.282332E-02
9	G	8.347698E-03	1.645789E-02	3.349902E-01	-9.834041E-02	3.834802E-02	7.301614E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST

4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 258

FOUR TENTHS, 350 DEG
LOAD STEP = 5.00000E+00

SUBCASE 40

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	5.854804E-03	4.852837E-07	3.413655E-01	6.103665E-05	5.059585E-02	-2.160220E-06
2	G	8.990797E-03	1.856199E-02	4.016224E-01	-1.875743E-01	-2.292969E-02	1.237059E-02
3	G	1.154697E-02	2.228660E-02	3.988722E-01	-1.421323E-01	3.075313E-02	1.657910E-03
4	G	1.334866E-02	2.069364E-02	3.503054E-01	-1.087073E-01	1.172818E-01	-6.984108E-03
5	G	1.198623E-02	1.559240E-02	2.642729E-01	-6.727016E-02	1.083418E-01	-5.829583E-03
6	G	7.534479E-03	8.501718E-03	1.477472E-01	-9.656009E-02	2.666197E-01	-1.665123E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	7.838324E-03	1.647852E-02	3.813833E-01	-1.413450E-01	-4.391624E-02	1.557388E-02
9	G	1.006672E-02	1.993708E-02	3.680149E-01	-1.084064E-01	4.224337E-02	8.814840E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST

4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 259

FIVE TENTHS, 350 DEG
LOAD STEP = 6.00000E+00

SUBCASE 50

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	6.764079E-03	6.576447E-07	3.674905E-01	8.846173E-05	6.717764E-02	-2.185476E-06
2	G	1.039041E-02	2.155637E-02	4.322136E-01	-2.037011E-01	-2.455098E-02	1.430125E-02
3	G	1.336528E-02	2.588426E-02	4.292757E-01	-1.540181E-01	3.274478E-02	1.976296E-03
4	G	1.545893E-02	2.403752E-02	3.770108E-01	-1.177546E-01	1.267076E-01	-8.178585E-03
5	G	1.387882E-02	1.811682E-02	2.843868E-01	-7.146326E-02	1.161350E-01	-6.745568E-03
6	G	8.754029E-03	9.901644E-03	1.591853E-01	-1.055235E-01	2.866550E-01	-1.946019E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	9.065155E-03	1.911404E-02	4.103083E-01	-1.524906E-01	-4.737612E-02	1.809693E-02
9	G	1.164186E-02	2.313253E-02	3.959001E-01	-1.168294E-01	4.548479E-02	1.027749E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST

4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 260

SIX TENTHS, 350 DEG
LOAD STEP = 7.00000E+00

SUBCASE 60

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	7.607771E-03	8.430965E-07	3.903655E-01	1.191050E-04	8.290831E-02	-1.872445E-06
2	G	1.169337E-02	2.435198E-02	4.589307E-01	-2.176818E-01	-2.595287E-02	1.610669E-02
3	G	1.506099E-02	2.924569E-02	4.558258E-01	-1.643505E-01	3.448630E-02	2.278172E-03
4	G	1.742926E-02	2.716378E-02	4.003354E-01	-1.256098E-01	1.349082E-01	-9.295225E-03
5	G	1.564730E-02	2.047811E-02	3.019596E-01	-7.513366E-02	1.229699E-01	-7.603799E-03
6	G	9.895806E-03	1.121272E-02	1.691793E-01	-1.133889E-01	3.040682E-01	-2.209977E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.020698E-02	2.157471E-02	4.355848E-01	-1.621734E-01	-5.032849E-02	2.044918E-02
9	G	1.311058E-02	2.611857E-02	4.202676E-01	-1.241314E-01	4.827828E-02	1.171218E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST

4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 261

SEVEN TENTHS, 350 DEG
LOAD STEP = 8.00000E+00

SUBCASE 70

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	8.399854E-03	1.040245E-06	4.108500E-01	1.526046E-04	9.786027E-02	-1.192336E-06
2	G	1.292057E-02	2.699176E-02	4.827991E-01	-2.300845E-01	-2.718023E-02	1.781230E-02
3	G	1.666059E-02	3.242211E-02	4.795426E-01	-1.735389E-01	3.603790E-02	2.567872E-03
4	G	1.929003E-02	3.011985E-02	4.211745E-01	-1.325899E-01	1.422110E-01	-1.035035E-02
5	G	1.731882E-02	2.271203E-02	3.176647E-01	-7.842363E-02	1.290964E-01	-8.416805E-03
6	G	1.097675E-02	1.245438E-02	1.781121E-01	-1.204526E-01	3.195576E-01	-2.460743E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.128201E-02	2.389864E-02	4.581787E-01	-1.707841E-01	-5.290119E-02	2.266585E-02
9	G	1.449594E-02	2.894093E-02	4.420485E-01	-1.306107E-01	5.074237E-02	1.313120E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST

4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 262

EIGHT TENTHS, 350 DEG
LOAD STEP = 9.00000E+00

SUBCASE 80

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.149737E-03	1.248046E-06	4.294887E-01	1.886860E-04	1.121073E-01	-1.236320E-07
2	G	1.408604E-02	2.950457E-02	5.044689E-01	-2.412701E-01	-2.826409E-02	1.943508E-02
3	G	1.818186E-02	3.544793E-02	5.010725E-01	-1.818432E-01	3.743899E-02	2.848284E-03
4	G	2.106162E-02	3.293759E-02	4.400954E-01	-1.388958E-01	1.488231E-01	-1.135508E-02
5	G	1.891157E-02	2.484253E-02	3.319287E-01	-8.142164E-02	1.346735E-01	-9.192995E-03
6	G	1.200824E-02	1.363968E-02	1.862263E-01	-1.269012E-01	3.335645E-01	-2.700833E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.230252E-02	2.611138E-02	4.787022E-01	-1.785693E-01	-5.517653E-02	2.477075E-02
9	G	1.581343E-02	3.163031E-02	4.618331E-01	-1.364563E-01	5.295229E-02	1.454182E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST

4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 263

NINE TENTHS, 350 DEG
LOAD STEP = 1.00000E+01

SUBCASE 90

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.864134E-03	1.465681E-06	4.466515E-01	2.271329E-04	1.257172E-01	1.350265E-06
2	G	1.519975E-02	3.191101E-02	5.243810E-01	-2.514834E-01	-2.922722E-02	2.098723E-02
3	G	1.963751E-02	3.834770E-02	5.208541E-01	-1.894400E-01	3.871709E-02	3.121427E-03
4	G	2.275857E-02	3.563965E-02	4.574828E-01	-1.446638E-01	1.548845E-01	-1.231746E-02
5	G	2.043847E-02	2.688665E-02	3.450406E-01	-8.418700E-02	1.398095E-01	-9.938353E-03
6	G	1.299839E-02	1.477790E-02	1.936864E-01	-1.328605E-01	3.463882E-01	-2.932038E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.327723E-02	2.823112E-02	4.975703E-01	-1.856954E-01	-5.721118E-02	2.678104E-02
9	G	1.707410E-02	3.420852E-02	4.800217E-01	-1.417958E-01	5.495916E-02	1.594854E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST

4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 264

ONE, 350 DEG
LOAD STEP = 1.10000E+01

SUBCASE 101

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	1.054806E-02	1.692485E-06	4.626021E-01	2.677707E-04	1.387500E-01	3.242490E-06
2	G	1.626915E-02	3.422644E-02	5.428500E-01	-2.608993E-01	-3.008695E-02	2.247793E-02
3	G	2.103698E-02	4.113968E-02	5.392001E-01	-1.964553E-01	3.989239E-02	3.388768E-03
4	G	2.439168E-02	3.824294E-02	4.736111E-01	-1.499910E-01	1.604950E-01	-1.324351E-02
5	G	2.190916E-02	2.885706E-02	3.572066E-01	-8.676167E-02	1.445820E-01	-1.065734E-02
6	G	1.395323E-02	1.587594E-02	2.006095E-01	-1.384199E-01	3.582415E-01	-3.155690E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.421269E-02	3.027142E-02	5.150793E-01	-1.922809E-01	-5.904621E-02	2.870956E-02
9	G	1.828614E-02	3.669181E-02	4.968997E-01	-1.467205E-01	5.679954E-02	1.735423E-03

ONE TENTH, 400 DEG
LOAD STEP = 2.00000E+00

SUBCASE 10

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	2.375595E-03	7.316699E-08	2.175462E-01	4.605499E-06	-3.526167E-03	-5.823217E-07
2	G	3.676803E-03	7.267762E-03	2.555033E-01	-1.091997E-01	-1.576805E-02	5.143355E-03
3	G	4.688556E-03	8.735888E-03	2.535690E-01	-8.486806E-02	2.183642E-02	4.777535E-04
4	G	5.411728E-03	8.105053E-03	2.226620E-01	-6.474157E-02	7.153090E-02	-2.530499E-03
5	G	4.872420E-03	6.085756E-03	1.680888E-01	-4.672921E-02	7.208692E-02	-2.423175E-03
6	G	2.979317E-03	3.244825E-03	9.298830E-02	-5.324136E-02	1.691299E-01	-6.203623E-03
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	3.187724E-03	6.521059E-03	2.434190E-01	-8.696756E-02	-2.645250E-02	6.051285E-03
9	G	4.119399E-03	7.889617E-03	2.349769E-01	-6.711987E-02	2.611279E-02	3.898758E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST

4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 256

TWO TENTHS, 400 DEG
LOAD STEP = 3.00000E+00

SUBCASE 20

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	3.733935E-03	1.885501E-07	2.722536E-01	1.805493E-05	1.478611E-02	-1.279221E-06
2	G	5.748134E-03	1.162900E-02	3.202210E-01	-1.437745E-01	-1.879212E-02	7.940109E-03
3	G	7.353284E-03	1.396521E-02	3.179187E-01	-1.100140E-01	2.573429E-02	9.192888E-04
4	G	8.491748E-03	1.296247E-02	2.791967E-01	-8.418063E-02	9.181464E-02	-4.225964E-03
5	G	7.633354E-03	9.751987E-03	2.106973E-01	-5.600208E-02	8.808847E-02	-3.742016E-03
6	G	4.737653E-03	5.263553E-03	1.172291E-01	-7.226331E-02	2.125671E-01	-1.019221E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	4.998117E-03	1.037460E-02	3.045231E-01	-1.111432E-01	-3.428253E-02	9.724974E-03
9	G	6.433945E-03	1.254815E-02	2.939083E-01	-8.549895E-02	3.335973E-02	5.723552E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST

4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 257

THREE TENTHS, 400 DEG
LOAD STEP = 4.00000E+00

SUBCASE 30

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	4.861585E-03	3.278584E-07	3.108619E-01	3.726604E-05	3.306700E-02	-1.841065E-06
2	G	7.472223E-03	1.528826E-02	3.657176E-01	-1.681421E-01	-2.111217E-02	1.028525E-02
3	G	9.582272E-03	1.835506E-02	3.631519E-01	-1.278556E-01	2.860260E-02	1.296369E-03
4	G	1.107191E-02	1.703870E-02	3.189213E-01	-9.782568E-02	1.059956E-01	-5.672789E-03
5	G	9.944879E-03	1.282728E-02	2.406130E-01	-6.230319E-02	9.949146E-02	-4.852245E-03
6	G	6.218484E-03	6.962782E-03	1.342463E-01	-8.557986E-02	2.427735E-01	-1.357308E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	6.508590E-03	1.359880E-02	3.474863E-01	-1.279864E-01	-3.965485E-02	1.280859E-02
9	G	8.366616E-03	1.644967E-02	3.353307E-01	-9.827553E-02	3.833449E-02	7.333368E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST

4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 258

FOUR TENTHS, 400 DEG
LOAD STEP = 5.00000E+00

SUBCASE 40

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	5.859133E-03	4.848964E-07	3.416995E-01	6.095717E-05	5.054416E-02	-2.167042E-06
2	G	9.002356E-03	1.855123E-02	4.019397E-01	-1.874304E-01	-2.302005E-02	1.238324E-02
3	G	1.156625E-02	2.227236E-02	3.991598E-01	-1.420357E-01	3.093221E-02	1.637372E-03
4	G	1.337159E-02	2.067743E-02	3.505453E-01	-1.086259E-01	1.172219E-01	-6.970818E-03
5	G	1.200605E-02	1.557316E-02	2.644292E-01	-6.728283E-02	1.086453E-01	-5.846215E-03
6	G	7.543447E-03	8.483130E-03	1.477931E-01	-9.619916E-02	2.666505E-01	-1.661240E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	7.849985E-03	1.647112E-02	3.817101E-01	-1.412949E-01	-4.384582E-02	1.555870E-02
9	G	1.008567E-02	1.992885E-02	3.683245E-01	-1.083505E-01	4.222854E-02	8.848775E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST

4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 259

FIVE TENTHS, 400 DEG
LOAD STEP = 6.00000E+00

SUBCASE 50

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	6.768455E-03	6.572263E-07	3.678010E-01	8.836527E-05	6.712630E-02	-2.194291E-06
2	G	1.040198E-02	2.154575E-02	4.325095E-01	-2.035712E-01	-2.463720E-02	1.431434E-02
3	G	1.338463E-02	2.587019E-02	4.295443E-01	-1.539348E-01	3.291308E-02	1.955305E-03
4	G	1.548196E-02	2.402142E-02	3.772346E-01	-1.176785E-01	1.266510E-01	-8.165105E-03
5	G	1.389881E-02	1.809770E-02	2.845333E-01	-7.148017E-02	1.164171E-01	-6.762124E-03
6	G	8.763085E-03	9.883063E-03	1.592285E-01	-1.051883E-01	2.866855E-01	-1.942143E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	9.076860E-03	1.910670E-02	4.106124E-01	-1.524473E-01	-4.730994E-02	1.808158E-02
9	G	1.166084E-02	2.312433E-02	3.961880E-01	-1.167787E-01	4.547007E-02	1.031235E-03
1	LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE				AUGUST	4, 2000 MSC/NASTRAN 2/ 9/99	PAGE 260

SIX TENTHS, 400 DEG
LOAD STEP = 7.00000E+00

SUBCASE 60

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	7.612186E-03	8.426235E-07	3.906581E-01	1.189931E-04	8.285762E-02	-1.883469E-06
2	G	1.170497E-02	2.434145E-02	4.592100E-01	-2.175609E-01	-2.603541E-02	1.612013E-02
3	G	1.508040E-02	2.923174E-02	4.560797E-01	-1.642751E-01	3.464593E-02	2.256881E-03
4	G	1.745237E-02	2.714775E-02	4.005468E-01	-1.255375E-01	1.348544E-01	-9.281583E-03
5	G	1.566741E-02	2.045910E-02	3.020985E-01	-7.515299E-02	1.232357E-01	-7.620305E-03
6	G	9.904919E-03	1.119415E-02	1.692202E-01	-1.130732E-01	3.040983E-01	-2.206105E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.021872E-02	2.156743E-02	4.358717E-01	-1.621342E-01	-5.026603E-02	2.043379E-02
9	G	1.312958E-02	2.611042E-02	4.205391E-01	-1.240842E-01	4.826406E-02	1.174741E-03
1	LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE				AUGUST	4, 2000 MSC/NASTRAN 2/ 9/99	PAGE 261

SEVEN TENTHS, 400 DEG
LOAD STEP = 8.00000E+00

SUBCASE 70

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	8.404304E-03	1.039718E-06	4.111282E-01	1.524780E-04	9.781041E-02	-1.205694E-06
2	G	1.293220E-02	2.698131E-02	4.830652E-01	-2.299702E-01	-2.725959E-02	1.782601E-02
3	G	1.668005E-02	3.240825E-02	4.797845E-01	-1.734689E-01	3.619039E-02	2.546361E-03
4	G	1.931319E-02	3.010390E-02	4.213760E-01	-1.325206E-01	1.421595E-01	-1.033658E-02
5	G	1.733903E-02	2.269310E-02	3.177974E-01	-7.844444E-02	1.293490E-01	-8.433278E-03
6	G	1.098591E-02	1.243582E-02	1.781513E-01	-1.201524E-01	3.195872E-01	-2.456874E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.129379E-02	2.389141E-02	4.584518E-01	-1.707478E-01	-5.284194E-02	2.265045E-02
9	G	1.451497E-02	2.893284E-02	4.423069E-01	-1.305663E-01	5.072873E-02	1.316653E-03
1	LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE				AUGUST	4, 2000 MSC/NASTRAN 2/ 9/99	PAGE 262

EIGHT TENTHS, 400 DEG
LOAD STEP = 9.00000E+00

SUBCASE 80

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.154217E-03	1.247467E-06	4.297552E-01	1.885452E-04	1.120584E-01	-1.394339E-07
2	G	1.409769E-02	2.949419E-02	5.047241E-01	-2.411610E-01	-2.834068E-02	1.944901E-02
3	G	1.521143E-02	3.190069E-02	5.246270E-01	-2.513787E-01	-2.930137E-02	2.100135E-02
4	G	1.965705E-02	3.833400E-02	5.210778E-01	-1.893772E-01	3.758544E-02	2.826607E-03
5	G	2.108484E-02	3.292170E-02	4.402887E-01	-1.388290E-01	1.487734E-01	-1.134121E-02
6	G	1.893185E-02	2.482368E-02	3.320562E-01	-8.144341E-02	1.349152E-01	-9.209444E-03
7	G	1.201743E-02	1.362113E-02	1.862641E-01	-1.266137E-01	3.335938E-01	-2.696968E-02
8	G	0.0	0.0	0.0	0.0	0.0	0.0
9	G	1.231432E-02	2.610420E-02	4.789639E-01	-1.785352E-01	-5.512005E-02	2.475539E-02
1	LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE				AUGUST	4, 2000 MSC/NASTRAN 2/ 9/99	PAGE 263

NINE TENTHS, 400 DEG
LOAD STEP = 1.00000E+01

SUBCASE 90

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.868643E-03	1.465050E-06	4.469080E-01	2.269785E-04	1.256693E-01	1.331924E-06
2	G	1.521143E-02	3.190069E-02	5.246270E-01	-2.513787E-01	-2.930137E-02	2.100135E-02
3	G	1.965705E-02	3.833400E-02	5.210778E-01	-1.893772E-01	3.758544E-02	2.826607E-03
4	G	2.278183E-02	3.562384E-02	4.576691E-01	-1.445992E-01	1.548366E-01	-1.230351E-02
5	G	2.045882E-02	2.686787E-02	3.451637E-01	-8.420940E-02	1.400420E-01	-9.954786E-03
6	G	1.300761E-02	1.475936E-02	1.937229E-01	-1.325838E-01	3.464170E-01	-2.928176E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.328906E-02	2.822400E-02	4.978225E-01	-1.856630E-01	-5.715714E-02	2.676572E-02
9	G	1.709319E-02	3.420053E-02	4.802602E-01	-1.417556E-01	5.494669E-02	1.598363E-03
1	LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE				AUGUST	4, 2000 MSC/NASTRAN 2/ 9/99	PAGE 264

ONE, 400 DEG
LOAD STEP = 1.10000E+01

SUBCASE 101

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	1.055259E-02	1.691803E-06	4.628499E-01	2.676033E-04	1.387030E-01	3.221526E-06
2	G	1.628086E-02	3.421618E-02	5.430880E-01	-2.607983E-01	-3.015894E-02	2.249220E-02
3	G	2.105656E-02	4.112605E-02	5.394167E-01	-1.963952E-01	4.002913E-02	3.366856E-03
4	G	2.441499E-02	3.822718E-02	4.737915E-01	-1.499283E-01	1.604486E-01	-1.322949E-02
5	G	2.192957E-02	2.883835E-02	3.573260E-01	-8.678450E-02	1.448065E-01	-1.067376E-02
6	G	1.396248E-02	1.585742E-02	2.006450E-01	-1.381525E-01	3.582700E-01	-3.151833E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.422455E-02	3.026435E-02	5.153232E-01	-1.922499E-01	-5.899432E-02	2.869431E-02
9	G	1.830526E-02	3.668388E-02	4.971303E-01	-1.466819E-01	5.678761E-02	1.738909E-03
1	LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE				AUGUST	4, 2000 MSC/NASTRAN 2/ 9/99	PAGE 255

ONE TENTH, 450 DEG
LOAD STEP = 2.00000E+00

SUBCASE 10

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	2.379892E-03	7.301164E-08	2.180728E-01	4.583238E-06	-3.564603E-03	-5.839285E-07
2	G	3.688897E-03	7.255931E-03	2.559908E-01	-1.088630E-01	-1.585575E-02	5.151126E-03
3	G	4.707457E-03	8.720363E-03	2.540043E-01	-8.452626E-02	2.206690E-02	4.638024E-04
4	G	5.434502E-03	8.089309E-03	2.230393E-01	-6.462518E-02	7.143810E-02	-2.517711E-03
5	G	4.892296E-03	6.066959E-03	1.683361E-01	-4.672045E-02	7.255284E-02	-2.439747E-03
6	G	2.988612E-03	3.226925E-03	9.306674E-02	-5.271930E-02	1.691831E-01	-6.167647E-03
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	3.199272E-03	6.513967E-03	2.439357E-01	-8.681699E-02	-2.638813E-02	6.041190E-03
9	G	4.138685E-03	7.882405E-03	2.354764E-01	-6.701649E-02	2.612170E-02	3.912791E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE
AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 256

TWO TENTHS, 450 DEG
LOAD STEP = 3.00000E+00

SUBCASE 20

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	3.738055E-03	1.882692E-07	2.726732E-01	1.801215E-05	1.473438E-02	-1.282869E-06
2	G	5.760032E-03	1.161694E-02	3.206082E-01	-1.435075E-01	-1.888414E-02	7.951583E-03
3	G	7.372047E-03	1.394958E-02	3.182650E-01	-1.097892E-01	2.594177E-02	9.015515E-04
4	G	8.513919E-03	1.294565E-02	2.794884E-01	-8.405951E-02	9.173942E-02	-4.212505E-03
5	G	7.652112E-03	9.732138E-03	2.108834E-01	-5.598137E-02	8.846994E-02	-3.759125E-03
6	G	4.745886E-03	5.244903E-03	1.172817E-01	-7.179528E-02	2.125914E-01	-1.015221E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	5.009577E-03	1.036703E-02	3.049321E-01	-1.110283E-01	-3.420929E-02	9.711836E-03
9	G	6.452877E-03	1.254015E-02	2.943000E-01	-8.540792E-02	3.335472E-02	5.749034E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE
AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 257

THREE TENTHS, 450 DEG
LOAD STEP = 4.00000E+00

SUBCASE 30

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	4.865836E-03	3.277619E-07	3.112286E-01	3.724157E-05	3.301457E-02	-1.846221E-06
2	G	7.484106E-03	1.527649E-02	3.660582E-01	-1.679138E-01	-2.119611E-02	1.029740E-02
3	G	9.601242E-03	1.833982E-02	3.634581E-01	-1.276698E-01	2.878427E-02	1.277917E-03
4	G	1.109451E-02	1.702225E-02	3.191809E-01	-9.772547E-02	1.059258E-01	-5.659017E-03
5	G	9.964416E-03	1.280789E-02	2.407822E-01	-6.230897E-02	9.982358E-02	-4.868921E-03
6	G	6.227275E-03	6.944221E-03	1.342958E-01	-8.518291E-02	2.428046E-01	-1.353437E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	6.520138E-03	1.359133E-02	3.478452E-01	-1.278943E-01	-3.959193E-02	1.279484E-02
9	G	8.385642E-03	1.644170E-02	3.356743E-01	-9.820157E-02	3.832860E-02	7.360468E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE
AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 258

FOUR TENTHS, 450 DEG
LOAD STEP = 5.00000E+00

SUBCASE 40

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	5.863461E-03	4.845360E-07	3.420333E-01	6.087674E-05	5.049273E-02	-2.173812E-06
2	G	9.013922E-03	1.854048E-02	4.022568E-01	-1.872858E-01	-2.311064E-02	1.239595E-02
3	G	1.158552E-02	2.225816E-02	3.994472E-01	-1.419387E-01	3.111153E-02	1.616829E-03
4	G	1.339451E-02	2.066126E-02	3.507850E-01	-1.085443E-01	1.171616E-01	-6.957519E-03
5	G	1.202585E-02	1.555394E-02	2.645853E-01	-6.729543E-02	1.089492E-01	-5.862878E-03
6	G	7.552375E-03	8.464560E-03	1.478389E-01	-9.583732E-02	2.666810E-01	-1.657355E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	7.861647E-03	1.646375E-02	3.820367E-01	-1.412446E-01	-4.377534E-02	1.554354E-02
9	G	1.010461E-02	1.992066E-02	3.686340E-01	-1.082946E-01	4.221359E-02	8.882809E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE
AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 259

FIVE TENTHS, 450 DEG
LOAD STEP = 6.00000E+00

SUBCASE 50

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	6.772830E-03	6.568052E-07	3.681113E-01	8.826962E-05	6.707528E-02	-2.203164E-06
2	G	1.041356E-02	2.153515E-02	4.328052E-01	-2.034410E-01	-2.472361E-02	1.432748E-02
3	G	1.340398E-02	2.585615E-02	4.298128E-01	-1.538513E-01	3.308154E-02	1.934310E-03
4	G	1.550500E-02	2.400534E-02	3.774584E-01	-1.176024E-01	1.265942E-01	-8.151620E-03
5	G	1.391879E-02	1.807861E-02	2.846797E-01	-7.149711E-02	1.166995E-01	-6.778704E-03
6	G	8.772109E-03	9.864498E-03	1.592715E-01	-1.048526E-01	2.867158E-01	-1.938267E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	9.088566E-03	1.909938E-02	4.109164E-01	-1.524039E-01	-4.724374E-02	1.806626E-02
9	G	1.167981E-02	2.311617E-02	3.964759E-01	-1.167280E-01	4.545525E-02	1.034728E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE
AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 260

SIX TENTHS, 450 DEG
LOAD STEP = 7.00000E+00

SUBCASE 60

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	7.616600E-03	8.421514E-07	3.909505E-01	1.188821E-04	8.280727E-02	-1.894563E-06
2	G	1.171657E-02	2.433095E-02	4.594893E-01	-2.174399E-01	-2.611815E-02	1.613361E-02
3	G	1.509981E-02	2.921781E-02	4.563334E-01	-1.641997E-01	3.480573E-02	2.235579E-03
4	G	1.747548E-02	2.713175E-02	4.007583E-01	-1.254652E-01	1.348003E-01	-9.267941E-03
5	G	1.568751E-02	2.044010E-02	3.022372E-01	-7.517235E-02	1.235017E-01	-7.636834E-03
6	G	9.914004E-03	1.117559E-02	1.692611E-01	-1.127570E-01	3.041281E-01	-2.202233E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.023046E-02	2.156017E-02	4.361585E-01	-1.620950E-01	-5.020352E-02	2.041841E-02
9	G	1.314859E-02	2.610230E-02	4.208105E-01	-1.240371E-01	4.824972E-02	1.178274E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE
AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 261

SEVEN TENTHS, 450 DEG
LOAD STEP = 8.00000E+00

SUBCASE 70

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	8.408753E-03	1.039193E-06	4.114064E-01	1.523524E-04	9.776089E-02	-1.219147E-06
2	G	1.294383E-02	2.697088E-02	4.833313E-01	-2.298559E-01	-2.733912E-02	1.783976E-02
3	G	1.669950E-02	3.239441E-02	4.800264E-01	-1.733990E-01	3.634302E-02	2.524841E-03
4	G	1.933636E-02	3.008797E-02	4.215775E-01	-1.324513E-01	1.421077E-01	-1.032281E-02
5	G	1.735922E-02	2.267419E-02	3.179300E-01	-7.846528E-02	1.296018E-01	-8.449771E-03
6	G	1.099504E-02	1.241727E-02	1.781904E-01	-1.198517E-01	3.196166E-01	-2.453006E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.130556E-02	2.388420E-02	4.587249E-01	-1.707115E-01	-5.278263E-02	2.263507E-02
9	G	1.453401E-02	2.892477E-02	4.425653E-01	-1.305220E-01	5.071499E-02	1.320195E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 262

EIGHT TENTHS, 450 DEG
LOAD STEP = 9.00000E+00

SUBCASE 80

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.158698E-03	1.246889E-06	4.300215E-01	1.884056E-04	1.120098E-01	-1.553577E-07
2	G	1.410935E-02	2.948383E-02	5.049792E-01	-2.410519E-01	-2.841743E-02	1.946298E-02
3	G	1.822086E-02	3.542040E-02	5.015367E-01	-1.817114E-01	3.773203E-02	2.804921E-03
4	G	2.110805E-02	3.290584E-02	4.404820E-01	-1.387622E-01	1.487237E-01	-1.132734E-02
5	G	1.895213E-02	2.480485E-02	3.321836E-01	-8.146521E-02	1.351571E-01	-9.225911E-03
6	G	1.202660E-02	1.360259E-02	1.863017E-01	-1.263258E-01	3.336228E-01	-2.693102E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.232612E-02	2.609704E-02	4.792256E-01	-1.785010E-01	-5.506353E-02	2.474004E-02
9	G	1.585156E-02	3.161426E-02	4.623283E-01	-1.363721E-01	5.292611E-02	1.461242E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 263

NINE TENTHS, 450 DEG
LOAD STEP = 1.00000E+01

SUBCASE 90

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.873153E-03	1.464421E-06	4.471644E-01	2.268256E-04	1.256217E-01	1.313434E-06
2	G	1.522312E-02	3.189040E-02	5.248728E-01	-2.512740E-01	-2.937567E-02	2.101550E-02
3	G	1.967659E-02	3.832032E-02	5.213016E-01	-1.893146E-01	3.899975E-02	3.077804E-03
4	G	2.280509E-02	3.560804E-02	4.578555E-01	-1.445345E-01	1.547885E-01	-1.228956E-02
5	G	2.047917E-02	2.684911E-02	3.452868E-01	-8.423185E-02	1.402746E-01	-9.971236E-03
6	G	1.301681E-02	1.474083E-02	1.937594E-01	-1.323068E-01	3.464457E-01	-2.924314E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.330090E-02	2.821689E-02	4.980745E-01	-1.856306E-01	-5.710305E-02	2.675042E-02
9	G	1.711227E-02	3.419258E-02	4.804986E-01	-1.417155E-01	5.493414E-02	1.601880E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 264

ONE, 450 DEG
LOAD STEP = 1.10000E+01

SUBCASE 101

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	1.055713E-02	1.691123E-06	4.630978E-01	2.674374E-04	1.386564E-01	3.200387E-06
2	G	1.629258E-02	3.420595E-02	5.433258E-01	-2.606972E-01	-3.023108E-02	2.250651E-02
3	G	2.107613E-02	4.111245E-02	5.396332E-01	-1.963353E-01	4.016599E-02	3.344935E-03
4	G	2.443829E-02	3.821145E-02	4.739718E-01	-1.498655E-01	1.604020E-01	-1.321548E-02
5	G	2.194998E-02	2.881965E-02	3.574454E-01	-8.680738E-02	1.450311E-01	-1.069020E-02
6	G	1.397171E-02	1.583891E-02	2.006803E-01	-1.378848E-01	3.582984E-01	-3.147974E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.423641E-02	3.025729E-02	5.155671E-01	-1.922190E-01	-5.894239E-02	2.867907E-02
9	G	1.832437E-02	3.667597E-02	4.973609E-01	-1.466434E-01	5.677561E-02	1.742403E-03

LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 255

ONE TENTH, 500 DEG
LOAD STEP = 2.00000E+00

SUBCASE 10

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	2.384068E-03	7.291216E-08	2.185965E-01	4.563408E-06	-3.603701E-03	-5.854652E-07
2	G	3.700022E-03	7.246244E-03	2.564931E-01	-1.087304E-01	-1.598692E-02	5.159469E-03
3	G	4.726688E-03	8.707223E-03	2.544610E-01	-8.444023E-02	2.233709E-02	4.453065E-04
4	G	5.457414E-03	8.073675E-03	2.234183E-01	-6.454662E-02	7.136847E-02	-2.508022E-03
5	G	4.911560E-03	6.047737E-03	1.685756E-01	-4.668676E-02	7.302584E-02	-2.456606E-03
6	G	2.997373E-03	3.208845E-03	9.313981E-02	-5.217080E-02	1.692224E-01	-6.130717E-03
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	3.210887E-03	6.506738E-03	2.444452E-01	-8.676784E-02	-2.627027E-02	6.025924E-03
9	G	4.157424E-03	7.874170E-03	2.359560E-01	-6.694612E-02	2.609726E-02	3.943676E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 256

TWO TENTHS, 500 DEG
LOAD STEP = 3.00000E+00

SUBCASE 20

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	3.742372E-03	1.838797E-07	2.730900E-01	1.768127E-05	1.468790E-02	-1.282659E-06
2	G	5.771032E-03	1.160762E-02	3.210146E-01	-1.434421E-01	-1.900681E-02	7.961990E-03
3	G	7.391562E-03	1.393682E-02	3.186373E-01	-1.097774E-01	2.617310E-02	8.806915E-04
4	G	8.537259E-03	1.293012E-02	2.797957E-01	-8.400089E-02	9.167722E-02	-4.201985E-03
5	G	7.672146E-03	9.713178E-03	2.110816E-01	-5.599146E-02	8.884928E-02	-3.775878E-03
6	G	4.755110E-03	5.226652E-03	1.173425E-01	-7.136246E-02	2.126325E-01	-1.011580E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	5.021287E-03	1.035978E-02	3.053391E-01	-1.110195E-01	-3.410549E-02	9.695663E-03
9	G	6.471656E-03	1.253170E-02	2.946809E-01	-8.536322E-02	3.32527E-02	5.786013E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 257

nastran_final_results_positive_temp.txt

THREE TENTHS, 500 DEG
LOAD STEP = 4.00000E+00

SUBCASE 30

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	4.870356E-03	3.094987E-07	3.116078E-01	3.588219E-05	3.296534E-02	-1.873760E-06
2	G	7.495740E-03	1.526705E-02	3.664253E-01	-1.678081E-01	-2.130093E-02	1.030973E-02
3	G	9.621022E-03	1.832704E-02	3.637935E-01	-1.276123E-01	2.898657E-02	1.257069E-03
4	G	1.111803E-02	1.700704E-02	3.194594E-01	-9.765361E-02	1.058692E-01	-5.647257E-03
5	G	9.984640E-03	1.278928E-02	2.409637E-01	-6.232030E-02	1.001616E-01	-4.885959E-03
6	G	6.236496E-03	6.926060E-03	1.343523E-01	-8.479369E-02	2.428477E-01	-1.349712E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	6.532104E-03	1.358457E-02	3.482174E-01	-1.278649E-01	-3.950857E-02	1.277970E-02
9	G	8.404856E-03	1.643408E-02	3.360254E-01	-9.815235E-02	3.830853E-02	7.396855E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 258

FOUR TENTHS, 500 DEG
LOAD STEP = 5.00000E+00

SUBCASE 40

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	5.867814E-03	4.842311E-07	3.423668E-01	6.079773E-05	5.044195E-02	-2.180414E-06
2	G	9.025394E-03	1.853010E-02	4.025754E-01	-1.871589E-01	-2.320392E-02	1.240853E-02
3	G	1.160488E-02	2.224433E-02	3.997368E-01	-1.418603E-01	3.129270E-02	1.595970E-03
4	G	1.341758E-02	2.064528E-02	3.510262E-01	-1.084684E-01	1.171022E-01	-6.944564E-03
5	G	1.204582E-02	1.553487E-02	2.647425E-01	-6.731090E-02	1.092532E-01	-5.879495E-03
6	G	7.561414E-03	8.446063E-03	1.478853E-01	-9.547844E-02	2.667128E-01	-1.653509E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	7.873347E-03	1.645643E-02	3.823631E-01	-1.412032E-01	-4.370191E-02	1.552797E-02
9	G	1.012355E-02	1.991245E-02	3.689426E-01	-1.082423E-01	4.219606E-02	8.918732E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 259

FIVE TENTHS, 500 DEG
LOAD STEP = 6.00000E+00

SUBCASE 50

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	6.777220E-03	6.564130E-07	3.684214E-01	8.817429E-05	6.702453E-02	-2.211964E-06
2	G	1.042508E-02	2.152477E-02	4.331018E-01	-2.033206E-01	-2.481162E-02	1.434056E-02
3	G	1.342339E-02	2.584235E-02	4.300824E-01	-1.537782E-01	3.325116E-02	1.913114E-03
4	G	1.552811E-02	2.398939E-02	3.776829E-01	-1.175294E-01	1.265378E-01	-8.138334E-03
5	G	1.393886E-02	1.805961E-02	2.848266E-01	-7.151553E-02	1.169822E-01	-6.795271E-03
6	G	8.781188E-03	9.845980E-03	1.593149E-01	-1.045180E-01	2.867466E-01	-1.934411E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	9.100297E-03	1.909211E-02	4.112203E-01	-1.523654E-01	-4.717573E-02	1.805067E-02
9	G	1.169878E-02	2.310801E-02	3.967631E-01	-1.166792E-01	4.543886E-02	1.038353E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 260

SIX TENTHS, 500 DEG
LOAD STEP = 7.00000E+00

SUBCASE 60

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	7.621024E-03	8.416990E-07	3.912428E-01	1.187711E-04	8.275703E-02	-1.905620E-06
2	G	1.172813E-02	2.432060E-02	4.597690E-01	-2.173248E-01	-2.620193E-02	1.614707E-02
3	G	1.511926E-02	2.920405E-02	4.565878E-01	-1.641306E-01	3.496630E-02	2.214141E-03
4	G	1.749864E-02	2.711585E-02	4.009701E-01	-1.253948E-01	1.347464E-01	-9.254420E-03
5	G	1.570767E-02	2.042117E-02	3.023763E-01	-7.519259E-02	1.237680E-01	-7.653364E-03
6	G	9.923120E-03	1.115706E-02	1.693021E-01	-1.124411E-01	3.041582E-01	-2.198371E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.024222E-02	2.155294E-02	4.364451E-01	-1.620588E-01	-5.013982E-02	2.040285E-02
9	G	1.316759E-02	2.609419E-02	4.210815E-01	-1.239911E-01	4.823434E-02	1.181902E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 261

SEVEN TENTHS, 500 DEG
LOAD STEP = 8.00000E+00

SUBCASE 70

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	8.413209E-03	1.038684E-06	4.116844E-01	1.522265E-04	9.771143E-02	-1.232584E-06
2	G	1.295543E-02	2.696056E-02	4.835976E-01	-2.297454E-01	-2.741941E-02	1.785351E-02
3	G	1.671899E-02	3.238070E-02	4.802687E-01	-1.733332E-01	3.649625E-02	2.503217E-03
4	G	1.935956E-02	3.007211E-02	4.217792E-01	-1.323832E-01	1.420559E-01	-1.030911E-02
5	G	1.737946E-02	2.265533E-02	3.180627E-01	-7.848670E-02	1.298550E-01	-8.466274E-03
6	G	1.100419E-02	1.239874E-02	1.782296E-01	-1.195510E-01	3.196461E-01	-2.449141E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.131735E-02	2.387702E-02	4.589977E-01	-1.706772E-01	-5.272247E-02	2.261956E-02
9	G	1.455304E-02	2.891672E-02	4.428233E-01	-1.304783E-01	5.070049E-02	1.323813E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 262

EIGHT TENTHS, 500 DEG
LOAD STEP = 9.00000E+00

SUBCASE 80

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.163183E-03	1.246324E-06	4.302878E-01	1.882657E-04	1.119613E-01	-1.712811E-07
2	G	1.412099E-02	2.947355E-02	5.052345E-01	-2.409455E-01	-2.849477E-02	1.947697E-02
3	G	1.824039E-02	3.540674E-02	5.017689E-01	-1.816484E-01	3.787911E-02	2.783149E-03
4	G	2.113130E-02	3.289003E-02	4.406754E-01	-1.386962E-01	1.486738E-01	-1.131351E-02
5	G	1.897243E-02	2.478605E-02	3.323112E-01	-8.148740E-02	1.353994E-01	-9.242395E-03
6	G	1.203578E-02	1.358407E-02	1.863394E-01	-1.260377E-01	3.336518E-01	-2.689236E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.233794E-02	2.608991E-02	4.794872E-01	-1.784683E-01	-5.500634E-02	2.472459E-02
9	G	1.587062E-02	3.160625E-02	4.625756E-01	-1.363304E-01	5.291238E-02	1.464842E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 263

NINE TENTHS, 500 DEG
LOAD STEP = 1.00000E+01

SUBCASE 90

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.877667E-03	1.463802E-06	4.474207E-01	2.266722E-04	1.255741E-01	1.294933E-06
2	G	1.523480E-02	3.188017E-02	5.251188E-01	-2.511711E-01	-2.945046E-02	2.102969E-02
3	G	1.969615E-02	3.830672E-02	5.215254E-01	-1.892541E-01	3.914158E-02	3.055913E-03
4	G	2.282838E-02	3.559228E-02	4.580419E-01	-1.444704E-01	1.547403E-01	-1.227564E-02
5	G	2.049954E-02	2.683038E-02	3.454100E-01	-8.425456E-02	1.405076E-01	-9.987705E-03
6	G	1.302602E-02	1.472232E-02	1.937958E-01	-1.320293E-01	3.464743E-01	-2.920448E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.331274E-02	2.820981E-02	4.983265E-01	-1.855993E-01	-5.704841E-02	2.673504E-02
9	G	1.713137E-02	3.418463E-02	4.807369E-01	-1.416756E-01	5.492110E-02	1.605456E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE
AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 264

ONE, 500 DEG
LOAD STEP = 1.10000E+01

SUBCASE 101

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	1.056167E-02	1.690452E-06	4.633456E-01	2.672712E-04	1.386098E-01	3.179228E-06
2	G	1.630429E-02	3.419576E-02	5.435638E-01	-2.605976E-01	-3.030363E-02	2.252086E-02
3	G	2.109572E-02	4.109890E-02	5.398498E-01	-1.962769E-01	4.030324E-02	3.322945E-03
4	G	2.446162E-02	3.819575E-02	4.741523E-01	-1.498032E-01	1.603553E-01	-1.320148E-02
5	G	2.197041E-02	2.880098E-02	3.575647E-01	-8.683044E-02	1.452561E-02	-1.070666E-02
6	G	1.398094E-02	1.582041E-02	2.007157E-01	-1.376165E-01	3.583266E-01	-3.144109E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.424828E-02	3.025026E-02	5.158108E-01	-1.921888E-01	-5.888999E-02	2.866376E-02
9	G	1.834349E-02	3.666808E-02	4.975914E-01	-1.466051E-01	5.676319E-02	1.745951E-03

LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 255

ONE TENTH, 550 DEG
LOAD STEP = 2.00000E+00

SUBCASE 10

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	2.388267E-03	7.280973E-08	2.191201E-01	4.543870E-06	-3.641889E-03	-5.870224E-07
2	G	3.711288E-03	7.236405E-03	2.569935E-01	-1.085724E-01	-1.611334E-02	5.167950E-03
3	G	4.745899E-03	8.693922E-03	2.549151E-01	-8.432275E-02	2.260252E-02	4.273271E-04
4	G	5.480345E-03	8.058178E-03	2.237973E-01	-6.446496E-02	7.129483E-02	-2.498030E-03
5	G	4.930925E-03	6.028696E-03	1.688163E-01	-4.665829E-02	7.349914E-02	-2.473447E-03
6	G	3.006154E-03	3.190859E-03	9.321354E-02	-5.162504E-02	1.692632E-01	-6.094227E-03
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	3.222505E-03	6.499638E-03	2.449554E-01	-8.670709E-02	-2.615907E-02	6.011321E-03
9	G	4.176255E-03	7.866195E-03	2.364381E-01	-6.687260E-02	2.607632E-02	3.972538E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE
AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 256

TWO TENTHS, 550 DEG
LOAD STEP = 3.00000E+00

SUBCASE 20

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	3.746633E-03	1.836360E-07	2.735078E-01	1.763768E-05	1.464136E-02	-1.285664E-06
2	G	5.782385E-03	1.159740E-02	3.214133E-01	-1.432966E-01	-1.911722E-02	7.972746E-03
3	G	7.410825E-03	1.392315E-02	3.189994E-01	-1.096807E-01	2.639398E-02	8.611031E-04
4	G	8.560224E-03	1.291427E-02	2.800975E-01	-8.391875E-02	9.160904E-02	-4.190340E-03
5	G	7.691786E-03	9.694032E-03	2.112758E-01	-5.599122E-02	8.922979E-02	-3.792578E-03
6	G	4.763988E-03	5.208339E-03	1.174005E-01	-7.091705E-02	2.126676E-01	-1.007800E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	5.032929E-03	1.035249E-02	3.057469E-01	-1.109683E-01	-3.401383E-02	9.680378E-03
9	G	6.490520E-03	1.252352E-02	2.950664E-01	-8.530007E-02	3.330480E-02	5.819614E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE
AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 257

THREE TENTHS, 550 DEG
LOAD STEP = 4.00000E+00

SUBCASE 30

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	4.874426E-03	3.275399E-07	3.119546E-01	3.713303E-05	3.291753E-02	-1.855806E-06
2	G	7.506062E-03	1.525750E-02	3.667648E-01	-1.677881E-01	-2.142275E-02	1.032064E-02
3	G	9.640172E-03	1.831387E-02	3.641045E-01	-1.276549E-01	2.920357E-02	1.234053E-03
4	G	1.114087E-02	1.699055E-02	3.197110E-01	-9.759658E-02	1.058083E-01	-5.635855E-03
5	G	1.000419E-02	1.276958E-02	2.411235E-01	-6.233303E-02	1.004918E-01	-4.902317E-03
6	G	6.245314E-03	6.907277E-03	1.343965E-01	-8.439973E-02	2.428685E-01	-1.345797E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	6.543506E-03	1.357652E-02	3.485531E-01	-1.278752E-01	-3.940127E-02	1.276121E-02
9	G	8.423051E-03	1.642442E-02	3.363362E-01	-9.811316E-02	3.827032E-02	7.442383E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE
AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 258

FOUR TENTHS, 550 DEG
LOAD STEP = 5.00000E+00

SUBCASE 40

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	5.872163E-03	4.838752E-07	3.427002E-01	6.071966E-05	5.039133E-02	-2.187198E-06
2	G	9.036882E-03	1.851971E-02	4.028937E-01	-1.870299E-01	-2.329717E-02	1.242118E-02
3	G	1.162423E-02	2.223050E-02	4.000260E-01	-1.417798E-01	3.147392E-02	1.575133E-03
4	G	1.344063E-02	2.062933E-02	3.512670E-01	-1.083917E-01	1.170423E-01	-6.931568E-03
5	G	1.206575E-02	1.551581E-02	2.648995E-01	-6.732607E-02	1.095575E-01	-5.896146E-03
6	G	7.570401E-03	8.427578E-03	1.479316E-01	-9.511843E-02	2.667442E-01	-1.649659E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	7.885045E-03	1.644914E-02	3.826893E-01	-1.411608E-01	-4.362869E-02	1.551246E-02
9	G	1.014249E-02	1.990429E-02	3.692511E-01	-1.081897E-01	4.217865E-02	8.954583E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE
AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 259

FIVE TENTHS, 550 DEG
LOAD STEP = 6.00000E+00

SUBCASE 50

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	6.781608E-03	6.560183E-07	3.687315E-01	8.807931E-05	6.697395E-02	-2.220764E-06
2	G	1.043661E-02	2.151440E-02	4.333981E-01	-2.031991E-01	-2.489968E-02	1.435370E-02
3	G	1.344279E-02	2.582856E-02	4.303518E-01	-1.537039E-01	3.342085E-02	1.891930E-03
4	G	1.555122E-02	2.397347E-02	3.779072E-01	-1.174560E-01	1.264810E-01	-8.125029E-03
5	G	1.395890E-02	1.804062E-02	2.849734E-01	-7.153383E-02	1.172651E-01	-6.811866E-03
6	G	8.790229E-03	9.827474E-03	1.593581E-01	-1.041827E-01	2.867770E-01	-1.930553E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	9.112027E-03	1.908486E-02	4.115240E-01	-1.523264E-01	-4.710782E-02	1.803513E-02
9	G	1.171776E-02	2.309988E-02	3.970504E-01	-1.166302E-01	4.542249E-02	1.041974E-03
1	LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE				AUGUST	4, 2000 MSC/NASTRAN 2/ 9/99	PAGE 260

SIX TENTHS, 550 DEG
LOAD STEP = 7.00000E+00

SUBCASE 60

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	7.625446E-03	8.412459E-07	3.915350E-01	1.186605E-04	8.270695E-02	-1.916667E-06
2	G	1.173971E-02	2.431026E-02	4.600486E-01	-2.172091E-01	-2.628579E-02	1.616058E-02
3	G	1.513871E-02	2.919030E-02	4.568420E-01	-1.640609E-01	3.512696E-02	2.192709E-03
4	G	1.752179E-02	2.709996E-02	4.011818E-01	-1.253241E-01	1.346922E-01	-9.240888E-03
5	G	1.572781E-02	2.040226E-02	3.025152E-01	-7.521278E-02	1.240344E-01	-7.669917E-03
6	G	9.932203E-03	1.113855E-02	1.693430E-01	-1.121248E-01	3.041880E-01	-2.194508E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.025398E-02	2.154573E-02	4.367316E-01	-1.620223E-01	-5.007617E-02	2.038733E-02
9	G	1.318660E-02	2.608611E-02	4.213524E-01	-1.239450E-01	4.821894E-02	1.185531E-03
1	LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE				AUGUST	4, 2000 MSC/NASTRAN 2/ 9/99	PAGE 261

SEVEN TENTHS, 550 DEG
LOAD STEP = 8.00000E+00

SUBCASE 70

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	8.417662E-03	1.038174E-06	4.119624E-01	1.521011E-04	9.766211E-02	-1.246004E-06
2	G	1.296705E-02	2.695026E-02	4.838638E-01	-2.296345E-01	-2.749979E-02	1.786730E-02
3	G	1.673847E-02	3.236700E-02	4.805109E-01	-1.732671E-01	3.664955E-02	2.481595E-03
4	G	1.938277E-02	3.005627E-02	4.219809E-01	-1.323149E-01	1.420040E-01	-1.029541E-02
5	G	1.739968E-02	2.263649E-02	3.181954E-01	-7.850809E-02	1.301083E-01	-8.482797E-03
6	G	1.101330E-02	1.238023E-02	1.782687E-01	-1.192498E-01	3.196753E-01	-2.445276E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.132914E-02	2.386986E-02	4.592706E-01	-1.706427E-01	-5.266232E-02	2.260408E-02
9	G	1.457208E-02	2.890869E-02	4.430813E-01	-1.304346E-01	5.068596E-02	1.327433E-03
1	LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE				AUGUST	4, 2000 MSC/NASTRAN 2/ 9/99	PAGE 262

EIGHT TENTHS, 550 DEG
LOAD STEP = 9.00000E+00

SUBCASE 80

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.167667E-03	1.245760E-06	4.305540E-01	1.881262E-04	1.119129E-01	-1.871817E-07
2	G	1.413264E-02	2.946329E-02	5.054896E-01	-2.408388E-01	-2.857219E-02	1.949099E-02
3	G	1.825991E-02	3.539310E-02	5.020012E-01	-1.815853E-01	3.802626E-02	2.761379E-03
4	G	2.115454E-02	3.287424E-02	4.408687E-01	-1.386301E-01	1.486237E-01	-1.129969E-02
5	G	1.899272E-02	2.476727E-02	3.324386E-01	-8.150960E-02	1.356417E-01	-9.258896E-03
6	G	1.204493E-02	1.356556E-02	1.863770E-01	-1.257491E-01	3.336806E-01	-2.685370E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.234975E-02	2.608280E-02	4.797486E-01	-1.784354E-01	-5.494915E-02	2.470917E-02
9	G	1.588969E-02	3.159827E-02	4.628229E-01	-1.362888E-01	5.289862E-02	1.468445E-03
1	LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE				AUGUST	4, 2000 MSC/NASTRAN 2/ 9/99	PAGE 263

NINE TENTHS, 550 DEG
LOAD STEP = 1.00000E+01

SUBCASE 90

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.882179E-03	1.463183E-06	4.476770E-01	2.265193E-04	1.255266E-01	1.276459E-06
2	G	1.524648E-02	3.186995E-02	5.253647E-01	-2.510681E-01	-2.952533E-02	2.104390E-02
3	G	1.971570E-02	3.829313E-02	5.217493E-01	-1.891935E-01	3.928346E-02	3.034023E-03
4	G	2.285166E-02	3.557655E-02	4.582283E-01	-1.444063E-01	1.546919E-01	-1.226171E-02
5	G	2.051990E-02	2.681166E-02	3.455330E-01	-8.427729E-02	1.407407E-01	-1.000419E-02
6	G	1.303520E-02	1.470383E-02	1.938321E-01	-1.317515E-01	3.465028E-01	-2.916583E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.332458E-02	2.820274E-02	4.985785E-01	-1.855678E-01	-5.699378E-02	2.671967E-02
9	G	1.715046E-02	3.417670E-02	4.809751E-01	-1.416357E-01	5.490802E-02	1.609035E-03
1	LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE				AUGUST	4, 2000 MSC/NASTRAN 2/ 9/99	PAGE 264

ONE, 550 DEG
LOAD STEP = 1.10000E+01

SUBCASE 101

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	1.056621E-02	1.689781E-06	4.635933E-01	2.671055E-04	1.385634E-01	3.158102E-06
2	G	1.631601E-02	3.418560E-02	5.438017E-01	-2.604979E-01	-3.037626E-02	2.253524E-02
3	G	2.111532E-02	4.108538E-02	5.400664E-01	-1.962185E-01	4.044054E-02	3.300956E-03
4	G	2.448494E-02	3.818007E-02	4.743326E-01	-1.497408E-01	1.603085E-01	-1.318749E-02
5	G	2.199082E-02	2.878233E-02	3.576840E-01	-8.685353E-02	1.454813E-01	-1.072313E-02
6	G	1.399016E-02	1.580193E-02	2.007510E-01	-1.373480E-01	3.583548E-01	-3.140245E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.426015E-02	3.024324E-02	5.160545E-01	-1.921587E-01	-5.883757E-02	2.864846E-02
9	G	1.836261E-02	3.666021E-02	4.978218E-01	-1.465668E-01	5.675072E-02	1.749502E-03
1	LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE				AUGUST	4, 2000 MSC/NASTRAN 2/ 9/99	PAGE 255

ONE TENTH, 600 DEG
LOAD STEP = 2.00000E+00

SUBCASE 10

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	2.392462E-03	7.270886E-08	2.196432E-01	4.524498E-06	-3.679619E-03	-5.885798E-07
2	G	3.722555E-03	7.226671E-03	2.574936E-01	-1.084163E-01	-1.624089E-02	5.176541E-03
3	G	4.765115E-03	8.680749E-03	2.553691E-01	-8.420790E-02	2.286878E-02	4.092935E-04
4	G	5.503282E-03	8.042788E-03	2.241762E-01	-6.438421E-02	7.122042E-02	-2.488084E-03
5	G	4.950272E-03	6.009742E-03	1.690569E-01	-4.663039E-02	7.397334E-02	-2.490305E-03
6	G	3.014871E-03	3.172926E-03	9.328699E-02	-5.107787E-02	1.693034E-01	-6.057856E-03
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	3.234125E-03	6.492615E-03	2.454651E-01	-8.664764E-02	-2.604723E-02	5.996721E-03
9	G	4.195088E-03	7.858305E-03	2.369195E-01	-6.679972E-02	2.605457E-02	4.001726E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE
AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 256

TWO TENTHS, 600 DEG
LOAD STEP = 3.00000E+00

SUBCASE 20

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	3.750894E-03	1.834546E-07	2.739254E-01	1.759831E-05	1.459519E-02	-1.288709E-06
2	G	5.793739E-03	1.158726E-02	3.218120E-01	-1.431524E-01	-1.922833E-02	7.983570E-03
3	G	7.430095E-03	1.390956E-02	3.193615E-01	-1.095857E-01	2.661547E-02	8.414756E-04
4	G	8.583194E-03	1.289849E-02	2.803992E-01	-8.383708E-02	9.154045E-02	-4.178716E-03
5	G	7.711416E-03	9.674943E-03	2.114699E-01	-5.599129E-02	8.961087E-02	-3.809504E-03
6	G	4.772824E-03	5.190060E-03	1.174583E-01	-7.047077E-02	2.127024E-01	-1.004026E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	5.044574E-03	1.034526E-02	3.061544E-01	-1.109180E-01	-3.392176E-02	9.665103E-03
9	G	6.509386E-03	1.251540E-02	2.954515E-01	-8.523735E-02	3.328384E-02	5.853473E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE
AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 257

THREE TENTHS, 600 DEG
LOAD STEP = 4.00000E+00

SUBCASE 30

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	4.878764E-03	3.256768E-07	3.123232E-01	3.691364E-05	3.286748E-02	-1.861148E-06
2	G	7.517801E-03	1.524669E-02	3.671125E-01	-1.676054E-01	-2.151464E-02	1.033274E-02
3	G	9.659419E-03	1.829967E-02	3.644191E-01	-1.275174E-01	2.939189E-02	1.214781E-03
4	G	1.116383E-02	1.697468E-02	3.199762E-01	-9.750944E-02	1.057416E-01	-5.622885E-03
5	G	1.002403E-02	1.275060E-02	2.412966E-01	-6.234387E-02	1.008259E-01	-4.919051E-03
6	G	6.254257E-03	6.888930E-03	1.344482E-01	-8.400685E-02	2.429032E-01	-1.342003E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	6.555189E-03	1.356934E-02	3.489141E-01	-1.278066E-01	-3.933070E-02	1.274671E-02
9	G	8.442115E-03	1.641659E-02	3.366800E-01	-9.804896E-02	3.825825E-02	7.473653E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE
AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 258

FOUR TENTHS, 600 DEG
LOAD STEP = 5.00000E+00

SUBCASE 40

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	5.876515E-03	4.835413E-07	3.430334E-01	6.064158E-05	5.034099E-02	-2.193907E-06
2	G	9.048359E-03	1.850940E-02	4.032121E-01	-1.869034E-01	-2.339103E-02	1.243385E-02
3	G	1.164360E-02	2.221677E-02	4.003155E-01	-1.417021E-01	3.165558E-02	1.554242E-03
4	G	1.346370E-02	2.061343E-02	3.515081E-01	-1.083160E-01	1.169823E-01	-6.918628E-03
5	G	1.208569E-02	1.549680E-02	2.650566E-01	-6.734176E-02	1.098621E-01	-5.912810E-03
6	G	7.579378E-03	8.409121E-03	1.479779E-01	-9.475838E-02	2.667755E-01	-1.645817E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	7.896750E-03	1.644189E-02	3.830154E-01	-1.411198E-01	-4.355496E-02	1.549690E-02
9	G	1.016143E-02	1.989615E-02	3.695593E-01	-1.081376E-01	4.216071E-02	8.990810E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE
AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 259

FIVE TENTHS, 600 DEG
LOAD STEP = 6.00000E+00

SUBCASE 50

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	6.785997E-03	6.556292E-07	3.690414E-01	8.798464E-05	6.692357E-02	-2.229545E-06
2	G	1.044814E-02	2.150409E-02	4.336945E-01	-2.030790E-01	-2.498815E-02	1.436687E-02
3	G	1.346220E-02	2.581484E-02	4.306213E-01	-1.536314E-01	3.359086E-02	1.870709E-03
4	G	1.557434E-02	2.395759E-02	3.781316E-01	-1.173831E-01	1.264242E-01	-8.111755E-03
5	G	1.397896E-02	1.802168E-02	2.851202E-01	-7.155243E-02	1.175483E-01	-6.828476E-03
6	G	8.799255E-03	9.808990E-03	1.594013E-01	-1.038471E-01	2.868074E-01	-1.926699E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	9.123760E-03	1.907763E-02	4.118276E-01	-1.522883E-01	-4.703957E-02	1.801957E-02
9	G	1.173673E-02	2.309178E-02	3.973374E-01	-1.165816E-01	4.540577E-02	1.045624E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE
AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 260

SIX TENTHS, 600 DEG
LOAD STEP = 7.00000E+00

SUBCASE 60

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	7.629870E-03	8.407970E-07	3.918271E-01	1.185501E-04	8.265704E-02	-1.927697E-06
2	G	1.175128E-02	2.429996E-02	4.603282E-01	-2.170943E-01	-2.636996E-02	1.617411E-02
3	G	1.515816E-02	2.917661E-02	4.570964E-01	-1.639923E-01	3.528786E-02	2.171247E-03
4	G	1.754496E-02	2.708412E-02	4.013935E-01	-1.252538E-01	1.346379E-01	-9.227378E-03
5	G	1.574795E-02	2.038338E-02	3.026541E-01	-7.523316E-02	1.243012E-01	-7.686487E-03
6	G	9.941270E-03	1.112005E-02	1.693839E-01	-1.118081E-01	3.042177E-01	-2.190648E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.026575E-02	2.153855E-02	4.370181E-01	-1.619864E-01	-5.001226E-02	2.037179E-02
9	G	1.320561E-02	2.607806E-02	4.216233E-01	-1.238992E-01	4.820328E-02	1.189183E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE
AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 261

SEVEN TENTHS, 600 DEG
LOAD STEP = 8.00000E+00

SUBCASE 70

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	8.422118E-03	1.037668E-06	4.122403E-01	1.519759E-04	9.761293E-02	-1.259408E-06
2	G	1.297866E-02	2.693999E-02	4.841300E-01	-2.295242E-01	-2.758041E-02	1.788112E-02
3	G	1.675797E-02	3.235335E-02	4.807531E-01	-1.732017E-01	3.680306E-02	2.459951E-03
4	G	1.940597E-02	3.004047E-02	4.221825E-01	-1.322469E-01	1.419519E-01	-1.028173E-02
5	G	1.741990E-02	2.261767E-02	3.183280E-01	-7.852962E-02	1.303618E-01	-8.499337E-03
6	G	1.102241E-02	1.236173E-02	1.783077E-01	-1.189483E-01	3.197044E-01	-2.441412E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.134093E-02	2.386272E-02	4.595433E-01	-1.706086E-01	-5.260197E-02	2.258859E-02
9	G	1.459112E-02	2.890068E-02	4.433392E-01	-1.303911E-01	5.067121E-02	1.331074E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE
AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 262

EIGHT TENTHS, 600 DEG
LOAD STEP = 9.00000E+00

SUBCASE 80

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.172152E-03	1.245198E-06	4.308202E-01	1.879870E-04	1.118645E-01	-2.030653E-07
2	G	1.414429E-02	2.945306E-02	5.057449E-01	-2.407325E-01	-2.864981E-02	1.950504E-02
3	G	1.827944E-02	3.537950E-02	5.022334E-01	-1.815227E-01	3.817359E-02	2.739589E-03
4	G	2.117779E-02	3.285848E-02	4.410621E-01	-1.385642E-01	1.485736E-01	-1.128587E-02
5	G	1.901301E-02	2.474851E-02	3.325661E-01	-8.153189E-02	1.358843E-01	-9.275415E-03
6	G	1.205407E-02	1.354707E-02	1.864146E-01	-1.254603E-01	3.337093E-01	-2.681505E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.236157E-02	2.607570E-02	4.800101E-01	-1.784029E-01	-5.489179E-02	2.469373E-02
9	G	1.590876E-02	3.159032E-02	4.630701E-01	-1.362472E-01	5.288468E-02	1.472065E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE
AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 263

NINE TENTHS, 600 DEG
LOAD STEP = 1.00000E+01

SUBCASE 90

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.886692E-03	1.462568E-06	4.479332E-01	2.263666E-04	1.254793E-01	1.258004E-06
2	G	1.525817E-02	3.185976E-02	5.256106E-01	-2.509654E-01	-2.960037E-02	2.105814E-02
3	G	1.973527E-02	3.827958E-02	5.219731E-01	-1.891333E-01	3.942550E-02	3.012115E-03
4	G	2.287495E-02	3.556084E-02	4.584146E-01	-1.443423E-01	1.546435E-01	-1.224780E-02
5	G	2.054025E-02	2.679296E-02	3.456561E-01	-8.430009E-02	1.409740E-01	-1.002069E-02
6	G	1.304437E-02	1.468534E-02	1.938684E-01	-1.314733E-01	3.465311E-01	-2.912717E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.333643E-02	2.819569E-02	4.988303E-01	-1.855366E-01	-5.693899E-02	2.670430E-02
9	G	1.716956E-02	3.416880E-02	4.812133E-01	-1.415959E-01	5.489479E-02	1.612629E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE
AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 264

ONE, 600 DEG
LOAD STEP = 1.10000E+01

SUBCASE 101

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	1.057075E-02	1.689114E-06	4.638410E-01	2.669399E-04	1.385170E-01	3.136995E-06
2	G	1.632773E-02	3.417546E-02	5.440395E-01	-2.603984E-01	-3.044904E-02	2.254963E-02
3	G	2.113491E-02	4.107188E-02	5.402830E-01	-1.961604E-01	4.057798E-02	3.278951E-03
4	G	2.450827E-02	3.816441E-02	4.745129E-01	-1.496785E-01	1.602615E-01	-1.317350E-02
5	G	2.201124E-02	2.876369E-02	3.578033E-01	-8.687668E-02	1.457065E-01	-1.073962E-02
6	G	1.399935E-02	1.578345E-02	2.007862E-01	-1.370792E-01	3.583828E-01	-3.136380E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.427202E-02	3.023623E-02	5.162981E-01	-1.921286E-01	-5.878504E-02	2.863316E-02
9	G	1.838174E-02	3.665235E-02	4.980522E-01	-1.465286E-01	5.673813E-02	1.753068E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE
AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 255

ONE TENTH, 650 DEG
LOAD STEP = 2.00000E+00

SUBCASE 10

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	2.396631E-03	7.263070E-08	2.201649E-01	4.494810E-06	-3.724009E-03	-5.894872E-07
2	G	3.733338E-03	7.218203E-03	2.580023E-01	-1.083646E-01	-1.638951E-02	5.185166E-03
3	G	4.784567E-03	8.669081E-03	2.558362E-01	-8.422542E-02	2.315117E-02	3.893589E-04
4	G	5.526516E-03	8.027871E-03	2.245599E-01	-6.433925E-02	7.115740E-02	-2.479697E-03
5	G	4.969585E-03	5.990875E-03	1.692969E-01	-4.660303E-02	7.445305E-02	-2.507282E-03
6	G	3.023440E-03	3.155019E-03	9.335927E-02	-5.052365E-02	1.693404E-01	-6.021464E-03
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	3.245792E-03	6.485679E-03	2.459721E-01	-8.664273E-02	-2.591172E-02	5.979973E-03
9	G	4.213694E-03	7.850059E-03	2.373919E-01	-6.675060E-02	2.601795E-02	4.038124E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE
AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 256

TWO TENTHS, 650 DEG
LOAD STEP = 3.00000E+00

SUBCASE 20

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	3.755158E-03	1.827819E-07	2.743428E-01	1.752449E-05	1.454940E-02	-1.291294E-06
2	G	5.805083E-03	1.157723E-02	3.222111E-01	-1.430128E-01	-1.934065E-02	7.994456E-03
3	G	7.449385E-03	1.389610E-02	3.197241E-01	-1.094957E-01	2.683798E-02	8.217559E-04
4	G	8.606188E-03	1.288280E-02	2.807012E-01	-8.375679E-02	9.147172E-02	-4.167160E-03
5	G	7.731054E-03	9.655923E-03	2.116642E-01	-5.599204E-02	8.999249E-02	-3.826357E-03
6	G	4.781630E-03	5.171821E-03	1.175161E-01	-7.002407E-02	2.127371E-01	-1.000262E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	5.056229E-03	1.033808E-02	3.065618E-01	-1.108703E-01	-3.382880E-02	9.649805E-03
9	G	6.528255E-03	1.250733E-02	2.958363E-01	-8.517576E-02	3.326204E-02	5.887747E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE
AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 257

THREE TENTHS, 650 DEG
LOAD STEP = 4.00000E+00

SUBCASE 30

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	4.883074E-03	3.267453E-07	3.126891E-01	3.700026E-05	3.281844E-02	-1.865612E-06
2	G	7.529245E-03	1.523643E-02	3.674615E-01	-1.674676E-01	-2.161526E-02	1.034477E-02
3	G	9.678734E-03	1.828597E-02	3.647362E-01	-1.274290E-01	2.958900E-02	1.194421E-03
4	G	1.118685E-02	1.695884E-02	3.202405E-01	-9.742996E-02	1.056772E-01	-5.610404E-03
5	G	1.004384E-02	1.273153E-02	2.414681E-01	-6.235462E-02	1.011606E-01	-4.935806E-03
6	G	6.263141E-03	6.870555E-03	1.344988E-01	-8.361237E-02	2.429356E-01	-1.338188E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	6.566865E-03	1.356211E-02	3.492717E-01	-1.277603E-01	-3.925017E-02	1.273128E-02
9	G	8.461031E-03	1.640853E-02	3.370182E-01	-9.799194E-02	3.823913E-02	7.509108E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE
AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 258

FOUR TENTHS, 650 DEG
LOAD STEP = 5.00000E+00

SUBCASE 40

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	5.880866E-03	4.832229E-07	3.433665E-01	6.056406E-05	5.029088E-02	-2.200558E-06
2	G	9.059840E-03	1.849913E-02	4.035305E-01	-1.867773E-01	-2.348521E-02	1.244656E-02
3	G	1.166297E-02	2.220309E-02	4.006049E-01	-1.416249E-01	3.183750E-02	1.533332E-03
4	G	1.348678E-02	2.059755E-02	3.517490E-01	-1.082404E-01	1.169221E-01	-6.905696E-03
5	G	1.210563E-02	1.547782E-02	2.652135E-01	-6.735756E-02	1.101670E-01	-5.929497E-03
6	G	7.588326E-03	8.390655E-03	1.480241E-01	-9.439775E-02	2.668065E-01	-1.641976E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	7.908457E-03	1.643467E-02	3.833414E-01	-1.410791E-01	-4.348105E-02	1.548135E-02
9	G	1.018037E-02	1.988805E-02	3.698675E-01	-1.080857E-01	4.214255E-02	9.027202E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE
AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 259

FIVE TENTHS, 650 DEG
LOAD STEP = 6.00000E+00

SUBCASE 50

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	6.790385E-03	6.552415E-07	3.693512E-01	8.789029E-05	6.687338E-02	-2.238316E-06
2	G	1.045967E-02	2.149381E-02	4.339908E-01	-2.029590E-01	-2.507686E-02	1.438007E-02
3	G	1.348162E-02	2.580116E-02	4.308907E-01	-1.535591E-01	3.376107E-02	1.849474E-03
4	G	1.559746E-02	2.394175E-02	3.783560E-01	-1.173103E-01	1.263671E-01	-8.098488E-03
5	G	1.399900E-02	1.800276E-02	2.852669E-01	-7.157112E-02	1.178317E-01	-6.845107E-03
6	G	8.808253E-03	9.790523E-03	1.594444E-01	-1.035110E-01	2.868376E-01	-1.922846E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	9.135497E-03	1.907044E-02	4.121312E-01	-1.522503E-01	-4.697121E-02	1.800401E-02
9	G	1.175571E-02	2.308371E-02	3.976243E-01	-1.165331E-01	4.538889E-02	1.049287E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE
AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 260

SIX TENTHS, 650 DEG
LOAD STEP = 7.00000E+00

SUBCASE 60

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	7.634292E-03	8.403493E-07	3.921192E-01	1.184401E-04	8.260728E-02	-1.938713E-06
2	G	1.176285E-02	2.428970E-02	4.606077E-01	-2.169795E-01	-2.645431E-02	1.618767E-02
3	G	1.517761E-02	2.916293E-02	4.573506E-01	-1.639239E-01	3.544893E-02	2.149775E-03
4	G	1.756812E-02	2.706837E-02	4.016052E-01	-1.251836E-01	1.345835E-01	-9.213874E-03
5	G	1.576809E-02	2.036452E-02	3.027930E-01	-7.525361E-02	1.245681E-01	-7.703077E-03
6	G	9.950313E-03	1.110157E-02	1.694247E-01	-1.114910E-01	3.042472E-01	-2.186788E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.027751E-02	2.153135E-02	4.373045E-01	-1.619506E-01	-4.994826E-02	2.035625E-02
9	G	1.322462E-02	2.607003E-02	4.218940E-01	-1.238534E-01	4.818748E-02	1.192846E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE
AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 261

SEVEN TENTHS, 650 DEG
LOAD STEP = 8.00000E+00

SUBCASE 70

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	8.426571E-03	1.037163E-06	4.125181E-01	1.518511E-04	9.756389E-02	-1.272794E-06
2	G	1.299027E-02	2.692975E-02	4.843962E-01	-2.294141E-01	-2.766119E-02	1.789497E-02
3	G	1.677746E-02	3.233973E-02	4.809952E-01	-1.731366E-01	3.695671E-02	2.438296E-03
4	G	1.942918E-02	3.002469E-02	4.223841E-01	-1.321790E-01	1.418997E-01	-1.026805E-02
5	G	1.744011E-02	2.259867E-02	3.184606E-01	-7.855121E-02	1.306155E-01	-8.515896E-03
6	G	1.103149E-02	1.234325E-02	1.783467E-01	-1.186465E-01	3.197334E-01	-2.437549E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.135272E-02	2.385560E-02	4.598160E-01	-1.705746E-01	-5.254154E-02	2.257310E-02
9	G	1.461016E-02	2.889270E-02	4.435970E-01	-1.303476E-01	5.065635E-02	1.334724E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE
AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 262

EIGHT TENTHS, 650 DEG
LOAD STEP = 9.00000E+00

SUBCASE 80

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.176636E-03	1.244638E-06	4.310863E-01	1.878480E-04	1.118164E-01	-2.189290E-07
2	G	1.415594E-02	2.944286E-02	5.060000E-01	-2.406263E-01	-2.872758E-02	1.951911E-02
3	G	1.829896E-02	3.536592E-02	5.024656E-01	-1.814603E-01	3.832103E-02	2.717790E-03
4	G	2.120104E-02	3.284275E-02	4.412554E-01	-1.384984E-01	1.485233E-01	-1.127207E-02
5	G	1.903330E-02	2.472978E-02	3.326935E-01	-8.155423E-02	1.361270E-01	-9.291951E-03
6	G	1.206319E-02	1.352859E-02	1.864521E-01	-1.251711E-01	3.337378E-01	-2.677640E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.237339E-02	2.606863E-02	4.802715E-01	-1.783704E-01	-5.483436E-02	2.467830E-02
9	G	1.592783E-02	3.158239E-02	4.633172E-01	-1.362057E-01	5.287063E-02	1.475695E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE
AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 263

NINE TENTHS, 650 DEG
LOAD STEP = 1.00000E+01

SUBCASE 90

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.891205E-03	1.461955E-06	4.481894E-01	2.262143E-04	1.254320E-01	1.239571E-06
2	G	1.526986E-02	3.184960E-02	5.258564E-01	-2.508627E-01	-2.967553E-02	2.107240E-02
3	G	1.975483E-02	3.826606E-02	5.221969E-01	-1.890732E-01	3.956765E-02	2.990199E-03
4	G	2.289824E-02	3.554516E-02	4.586009E-01	-1.442783E-01	1.545949E-01	-1.223389E-02
5	G	2.056060E-02	2.677428E-02	3.457791E-01	-8.432294E-02	1.412075E-01	-1.003721E-02
6	G	1.305352E-02	1.466686E-02	1.939047E-01	-1.311949E-01	3.465592E-01	-2.908852E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.334827E-02	2.818866E-02	4.990821E-01	-1.855055E-01	-5.688414E-02	2.668894E-02
9	G	1.718866E-02	3.416091E-02	4.814514E-01	-1.415562E-01	5.488146E-02	1.616233E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE
AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 264

ONE, 650 DEG
LOAD STEP = 1.10000E+01

SUBCASE 101

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	1.057529E-02	1.688448E-06	4.640886E-01	2.667747E-04	1.384707E-01	3.115913E-06
2	G	1.633945E-02	3.416533E-02	5.442774E-01	-2.602990E-01	-3.052193E-02	2.256406E-02
3	G	2.115451E-02	4.105841E-02	5.404996E-01	-1.961025E-01	4.071552E-02	3.256938E-03
4	G	2.453160E-02	3.814878E-02	4.746933E-01	-1.496163E-01	1.602145E-01	-1.315951E-02
5	G	2.203165E-02	2.974507E-02	3.579225E-01	-8.689866E-02	1.459319E-01	-1.075613E-02
6	G	1.400853E-02	1.576498E-02	2.008214E-01	-1.368101E-01	3.584107E-01	-3.132516E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.428389E-02	3.022925E-02	5.165417E-01	-1.920987E-01	-5.873244E-02	2.861787E-02
9	G	1.840086E-02	3.664452E-02	4.982825E-01	-1.464904E-01	5.672544E-02	1.756643E-03

LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 255

ONE TENTH, 700 DEG
LOAD STEP = 2.00000E+00

SUBCASE 10

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	2.400796E-03	7.251109E-08	2.206867E-01	4.494347E-06	-3.746119E-03	-5.919482E-07
2	G	3.744928E-03	7.207649E-03	2.584939E-01	-1.081356E-01	-1.650461E-02	5.193141E-03
3	G	4.803563E-03	8.654914E-03	2.562785E-01	-8.401910E-02	2.340826E-02	3.729377E-04
4	G	5.549120E-03	8.012180E-03	2.249325E-01	-6.422967E-02	7.107346E-02	-2.469299E-03
5	G	4.988766E-03	5.971931E-03	1.695355E-01	-4.656918E-02	7.492381E-02	-2.523085E-03
6	G	3.032032E-03	3.137155E-03	9.343208E-02	-4.997508E-02	1.693791E-01	-5.978626E-03
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	3.257347E-03	6.478677E-03	2.464812E-01	-8.654481E-02	-2.581581E-02	5.967109E-03
9	G	4.232634E-03	7.842526E-03	2.378772E-01	-6.665990E-02	2.600576E-02	4.060643E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE
AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 256

TWO TENTHS, 700 DEG
LOAD STEP = 3.00000E+00

SUBCASE 20

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	3.759353E-03	2.111261E-07	2.747613E-01	1.944848E-05	1.450293E-02	-1.318511E-06
2	G	5.816979E-03	1.156576E-02	3.225980E-01	-1.427488E-01	-1.943334E-02	8.005741E-03
3	G	7.468268E-03	1.388118E-02	3.200709E-01	-1.092736E-01	2.704347E-02	8.041790E-04
4	G	8.628608E-03	1.286661E-02	2.809948E-01	-8.364225E-02	9.139358E-02	-4.153945E-03
5	G	7.750126E-03	9.636614E-03	2.118528E-01	-5.597922E-02	9.037520E-02	-3.843276E-03
6	G	4.789955E-03	5.153475E-03	1.175702E-01	-6.956083E-02	2.127638E-01	-9.963267E-03
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	5.067773E-03	1.033084E-02	3.069702E-01	-1.107574E-01	-3.375575E-02	9.636107E-03
9	G	6.547260E-03	1.249966E-02	2.962277E-01	-8.508676E-02	3.325507E-02	5.915537E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE
AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 257

THREE TENTHS, 700 DEG
LOAD STEP = 4.00000E+00

SUBCASE 30

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	4.887389E-03	3.354119E-07	3.130583E-01	3.760235E-05	3.276815E-02	-1.859002E-06
2	G	7.541316E-03	1.522489E-02	3.678037E-01	-1.672227E-01	-2.169714E-02	1.035714E-02
3	G	9.697783E-03	1.827105E-02	3.650435E-01	-1.272249E-01	2.976806E-02	1.176383E-03
4	G	1.120956E-02	1.694284E-02	3.205025E-01	-9.732803E-02	1.056052E-01	-5.596571E-03
5	G	1.006348E-02	1.271258E-02	2.416396E-01	-6.236218E-02	1.014952E-01	-4.952566E-03
6	G	6.271870E-03	6.852221E-03	1.345493E-01	-8.321395E-02	2.429681E-01	-1.334345E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	6.578496E-03	1.355499E-02	3.496337E-01	-1.276608E-01	-3.919065E-02	1.271779E-02
9	G	8.480207E-03	1.640101E-02	3.373659E-01	-9.791594E-02	3.823468E-02	7.536215E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE
AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 258

FOUR TENTHS, 700 DEG
LOAD STEP = 5.00000E+00

SUBCASE 40

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	5.885221E-03	4.828740E-07	3.436994E-01	6.048769E-05	5.024106E-02	-2.207328E-06
2	G	9.071305E-03	1.848895E-02	4.038491E-01	-1.866545E-01	-2.358011E-02	1.245930E-02
3	G	1.168236E-02	2.218951E-02	4.008946E-01	-1.415514E-01	3.202000E-02	1.512347E-03
4	G	1.350987E-02	2.058179E-02	3.519902E-01	-1.081658E-01	1.168618E-01	-6.892829E-03
5	G	1.212559E-02	1.545890E-02	2.653707E-01	-6.737387E-02	1.104721E-01	-5.946197E-03
6	G	7.597264E-03	8.372276E-03	1.480703E-01	-9.403708E-02	2.668376E-01	-1.638143E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	7.920173E-03	1.642749E-02	3.836672E-01	-1.410402E-01	-4.340646E-02	1.546573E-02
9	G	1.019932E-02	1.987998E-02	3.701754E-01	-1.080345E-01	4.212375E-02	9.064068E-04

FIVE TENTHS, 700 DEG
LOAD STEP = 6.00000E+00

SUBCASE 50

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	6.794775E-03	6.548590E-07	3.696609E-01	8.779628E-05	6.682339E-02	-2.247071E-06
2	G	1.047119E-02	2.148359E-02	4.342872E-01	-2.028406E-01	-2.516597E-02	1.439329E-02
3	G	1.350104E-02	2.578754E-02	4.311603E-01	-1.534885E-01	3.393159E-02	1.828201E-03
4	G	1.562059E-02	2.392595E-02	3.785804E-01	-1.172380E-01	1.263099E-01	-8.085255E-03
5	G	1.401906E-02	1.798388E-02	2.854137E-01	-7.159010E-02	1.181153E-01	-6.861753E-03
6	G	8.817239E-03	9.772078E-03	1.594875E-01	-1.031748E-01	2.868677E-01	-1.918997E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	9.147238E-03	1.906328E-02	4.124345E-01	-1.522132E-01	-4.690250E-02	1.798842E-02
9	G	1.177469E-02	2.307567E-02	3.979111E-01	-1.164849E-01	4.537165E-02	1.052979E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST

4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 260

SIX TENTHS, 700 DEG
LOAD STEP = 7.00000E+00

SUBCASE 60

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	7.638715E-03	8.399069E-07	3.924111E-01	1.183303E-04	8.255768E-02	-1.949713E-06
2	G	1.177442E-02	2.427948E-02	4.608873E-01	-2.168658E-01	-2.653898E-02	1.620126E-02
3	G	1.519707E-02	2.914934E-02	4.576049E-01	-1.638566E-01	3.561024E-02	2.128274E-03
4	G	1.759129E-02	2.705253E-02	4.018169E-01	-1.251136E-01	1.345289E-01	-9.200392E-03
5	G	1.578823E-02	2.034569E-02	3.029319E-01	-7.527426E-02	1.248352E-01	-7.719683E-03
6	G	9.959340E-03	1.108311E-02	1.694655E-01	-1.111736E-01	3.042766E-01	-2.182931E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.028928E-02	2.152426E-02	4.375907E-01	-1.619153E-01	-4.988401E-02	2.034070E-02
9	G	1.324363E-02	2.606203E-02	4.221647E-01	-1.238078E-01	4.817142E-02	1.196533E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST

4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 261

SEVEN TENTHS, 700 DEG
LOAD STEP = 8.00000E+00

SUBCASE 70

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	8.431026E-03	1.036662E-06	4.127959E-01	1.517265E-04	9.751497E-02	-1.286165E-06
2	G	1.300189E-02	2.691955E-02	4.846623E-01	-2.293046E-01	-2.774222E-02	1.790884E-02
3	G	1.679695E-02	3.232615E-02	4.812374E-01	-1.730722E-01	3.711055E-02	2.416618E-03
4	G	1.945239E-02	3.000895E-02	4.225858E-01	-1.321113E-01	1.418473E-01	-1.025439E-02
5	G	1.746033E-02	2.258009E-02	3.185932E-01	-7.857293E-02	1.308694E-01	-8.532472E-03
6	G	1.104056E-02	1.232478E-02	1.783857E-01	-1.183443E-01	3.197623E-01	-2.433687E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.136452E-02	2.394851E-02	4.600886E-01	-1.705410E-01	-5.248091E-02	2.255760E-02
9	G	1.462920E-02	2.888474E-02	4.438547E-01	-1.303043E-01	5.064128E-02	1.338395E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST

4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 262

EIGHT TENTHS, 700 DEG
LOAD STEP = 9.00000E+00

SUBCASE 80

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.181120E-03	1.244082E-06	4.313523E-01	1.877094E-04	1.117683E-01	-2.347758E-07
2	G	1.416760E-02	2.943268E-02	5.062551E-01	-2.405206E-01	-2.880555E-02	1.953322E-02
3	G	1.831850E-02	3.535238E-02	5.026978E-01	-1.813984E-01	3.846865E-02	2.695971E-03
4	G	2.122429E-02	3.282705E-02	4.414487E-01	-1.384327E-01	1.484729E-01	-1.125827E-02
5	G	1.905358E-02	2.471106E-02	3.328209E-01	-8.157667E-02	1.363699E-01	-9.308504E-03
6	G	1.207229E-02	1.351012E-02	1.864895E-01	-1.248816E-01	3.337662E-01	-2.673776E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.238521E-02	2.606158E-02	4.805328E-01	-1.783383E-01	-5.477677E-02	2.466286E-02
9	G	1.594690E-02	3.157447E-02	4.635643E-01	-1.361644E-01	5.285641E-02	1.479342E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST

4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 263

NINE TENTHS, 700 DEG
LOAD STEP = 1.00000E+01

SUBCASE 90

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.895717E-03	1.461344E-06	4.484455E-01	2.260622E-04	1.253849E-01	1.221156E-06
2	G	1.528154E-02	3.183946E-02	5.261022E-01	-2.507605E-01	-2.975088E-02	2.108669E-02
3	G	1.977440E-02	3.825257E-02	5.224206E-01	-1.890136E-01	3.970994E-02	2.968265E-03
4	G	2.292153E-02	3.552950E-02	4.587873E-01	-1.442145E-01	1.545462E-01	-1.221999E-02
5	G	2.058095E-02	2.675563E-02	3.459021E-01	-8.434586E-02	1.414411E-01	-1.005375E-02
6	G	1.306265E-02	1.464840E-02	1.939409E-01	-1.309162E-01	3.465873E-01	-2.904987E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.336012E-02	2.818165E-02	4.993339E-01	-1.854746E-01	-5.682915E-02	2.667357E-02
9	G	1.720776E-02	3.415305E-02	4.816894E-01	-1.415165E-01	5.486799E-02	1.619853E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST

4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 264

ONE, 700 DEG
LOAD STEP = 1.10000E+01

SUBCASE 101

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	1.057990E-02	1.687764E-06	4.643387E-01	2.666049E-04	1.384259E-01	3.095127E-06
2	G	1.635127E-02	3.415544E-02	5.445182E-01	-2.602017E-01	-3.059519E-02	2.257865E-02
3	G	2.117423E-02	4.104521E-02	5.407192E-01	-1.960463E-01	4.085343E-02	3.234886E-03
4	G	2.455507E-02	3.813339E-02	4.748762E-01	-1.495552E-01	1.601683E-01	-1.314569E-02
5	G	2.205218E-02	2.872662E-02	3.580437E-01	-8.692354E-02	1.461583E-01	-1.077274E-02
6	G	1.401778E-02	1.574662E-02	2.008577E-01	-1.365416E-01	3.584404E-01	-3.128687E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.429585E-02	3.022246E-02	5.167881E-01	-1.920702E-01	-5.868009E-02	2.860277E-02
9	G	1.842009E-02	3.663691E-02	4.985155E-01	-1.464532E-01	5.671296E-02	1.760213E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST

4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 255

ONE TENTH, 750 DEG
LOAD STEP = 2.00000E+00

SUBCASE 10

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	2.405020E-03	7.243550E-08	2.212085E-01	4.454281E-06	-3.798146E-03	-5.925373E-07
2	G	3.755897E-03	7.199269E-03	2.590016E-01	-1.080606E-01	-1.665000E-02	5.202679E-03
3	G	4.823062E-03	8.643380E-03	2.567441E-01	-8.400698E-02	2.368721E-02	3.532889E-04
4	G	5.572481E-03	7.997682E-03	2.253179E-01	-6.418441E-02	7.100501E-02	-2.459743E-03
5	G	5.008277E-03	5.953457E-03	1.697781E-01	-4.655251E-02	7.540581E-02	-2.541144E-03
6	G	3.040609E-03	3.119446E-03	9.350540E-02	-4.942478E-02	1.694186E-01	-5.949086E-03
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	3.269059E-03	6.472060E-03	2.469896E-01	-8.653062E-02	-2.568689E-02	5.951175E-03
9	G	4.251397E-03	7.834758E-03	2.383526E-01	-6.660961E-02	2.597188E-02	4.097794E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST

4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 256

TWO TENTHS, 750 DEG
LOAD STEP = 3.00000E+00

SUBCASE 20

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	3.763608E-03	2.090071E-07	2.751781E-01	1.927368E-05	1.445781E-02	-1.320034E-06
2	G	5.828347E-03	1.155579E-02	3.229961E-01	-1.426058E-01	-1.954606E-02	8.016753E-03
3	G	7.487546E-03	1.386781E-02	3.204326E-01	-1.091806E-01	2.726624E-02	7.845075E-04
4	G	8.651583E-03	1.285102E-02	2.812962E-01	-8.356129E-02	9.132352E-02	-4.142356E-03
5	G	7.769720E-03	9.617686E-03	2.120466E-01	-5.598005E-02	9.075785E-02	-3.860175E-03
6	G	4.798657E-03	5.135298E-03	1.176275E-01	-6.911182E-02	2.127973E-01	-9.925666E-03
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	5.079425E-03	1.032375E-02	3.073770E-01	-1.107083E-01	-3.366301E-02	9.620905E-03
9	G	6.566137E-03	1.249172E-02	2.966121E-01	-8.502465E-02	3.323302E-02	5.949977E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST

4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 257

THREE TENTHS, 750 DEG
LOAD STEP = 4.00000E+00

SUBCASE 30

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	4.891691E-03	3.133195E-07	3.134237E-01	3.590163E-05	3.271918E-02	-1.889497E-06
2	G	7.552533E-03	1.521530E-02	3.681568E-01	-1.671305E-01	-2.180711E-02	1.036926E-02
3	G	9.717239E-03	1.825805E-02	3.653658E-01	-1.271872E-01	2.997446E-02	1.154967E-03
4	G	1.123270E-02	1.692721E-02	3.207683E-01	-9.725703E-02	1.055439E-01	-5.584661E-03
5	G	1.008327E-02	1.269364E-02	2.418109E-01	-6.237239E-02	1.018319E-01	-4.969445E-03
6	G	6.280672E-03	6.833890E-03	1.345996E-01	-8.281651E-02	2.429993E-01	-1.330514E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	6.590212E-03	1.354785E-02	3.499905E-01	-1.276373E-01	-3.910023E-02	1.270160E-02
9	G	8.499039E-03	1.639283E-02	3.377010E-01	-9.786676E-02	3.820858E-02	7.575958E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST

4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 258

FOUR TENTHS, 750 DEG
LOAD STEP = 5.00000E+00

SUBCASE 40

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	5.889570E-03	4.826184E-07	3.440323E-01	6.040931E-05	5.019139E-02	-2.213748E-06
2	G	9.082793E-03	1.847876E-02	4.041672E-01	-1.865286E-01	-2.367481E-02	1.247210E-02
3	G	1.170173E-02	2.217591E-02	4.011839E-01	-1.414748E-01	3.220236E-02	1.491414E-03
4	G	1.353295E-02	2.056602E-02	3.522310E-01	-1.080904E-01	1.168011E-01	-6.879908E-03
5	G	1.214551E-02	1.543999E-02	2.655276E-01	-6.738991E-02	1.107776E-01	-5.962927E-03
6	G	7.606151E-03	8.353881E-03	1.481163E-01	-9.367534E-02	2.668682E-01	-1.634306E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	7.931883E-03	1.642033E-02	3.839930E-01	-1.409999E-01	-4.333232E-02	1.545021E-02
9	G	1.021827E-02	1.987195E-02	3.704833E-01	-1.079828E-01	4.210523E-02	9.100715E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST

4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 259

FIVE TENTHS, 750 DEG
LOAD STEP = 6.00000E+00

SUBCASE 50

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	6.799162E-03	6.544758E-07	3.699705E-01	8.770252E-05	6.677356E-02	-2.255820E-06
2	G	1.048272E-02	2.147338E-02	4.345834E-01	-2.027209E-01	-2.525512E-02	1.440657E-02
3	G	1.352046E-02	2.577394E-02	4.314297E-01	-1.534168E-01	3.410217E-02	1.806941E-03
4	G	1.564371E-02	2.391018E-02	3.788046E-01	-1.171654E-01	1.262524E-01	-8.072000E-03
5	G	1.403909E-02	1.796501E-02	2.855604E-01	-7.160895E-02	1.183992E-01	-6.878426E-03
6	G	8.826184E-03	9.753646E-03	1.595305E-01	-1.028378E-01	2.668975E-01	-1.915147E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	9.158978E-03	1.905614E-02	4.127379E-01	-1.521756E-01	-4.683390E-02	1.797288E-02
9	G	1.179367E-02	2.306767E-02	3.981979E-01	-1.164365E-01	4.535444E-02	1.056667E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST

4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 260

SIX TENTHS, 750 DEG
LOAD STEP = 7.00000E+00

SUBCASE 60

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	7.643136E-03	8.394632E-07	3.927030E-01	1.182209E-04	8.250824E-02	-1.960703E-06
2	G	1.178600E-02	2.426927E-02	4.611667E-01	-2.167513E-01	-2.662371E-02	1.621490E-02
3	G	1.521653E-02	2.913576E-02	4.578591E-01	-1.637887E-01	3.577162E-02	2.106780E-03
4	G	1.761446E-02	2.703677E-02	4.020285E-01	-1.250436E-01	1.344741E-01	-9.186900E-03
5	G	1.580835E-02	2.032688E-02	3.030707E-01	-7.529485E-02	1.251025E-01	-7.736312E-03
6	G	9.968336E-03	1.106466E-02	1.695062E-01	-1.108557E-01	3.043057E-01	-2.179073E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.030105E-02	2.151715E-02	4.378770E-01	-1.618798E-01	-4.981981E-02	2.032519E-02
9	G	1.326264E-02	2.605406E-02	4.224353E-01	-1.237621E-01	4.815535E-02	1.200220E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST

4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 261

SEVEN TENTHS, 750 DEG
LOAD STEP = 8.00000E+00

SUBCASE 70

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	8.435479E-03	1.056161E-06	4.130735E-01	1.516023E-04	9.746622E-02	-1.299518E-06
2	G	1.301351E-02	2.690937E-02	4.849284E-01	-2.291946E-01	-2.782332E-02	1.792275E-02
3	G	1.681645E-02	3.231259E-02	4.814795E-01	-1.730074E-01	3.726447E-02	2.394944E-03
4	G	1.947560E-02	2.999322E-02	4.227873E-01	-1.320435E-01	1.417948E-01	-1.024072E-02
5	G	1.748053E-02	2.256134E-02	3.187257E-01	-7.859464E-02	1.311234E-01	-8.549068E-03
6	G	1.104959E-02	1.231632E-02	1.784245E-01	-1.180418E-01	3.197910E-01	-2.429825E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.137631E-02	2.384144E-02	4.603611E-01	-1.705072E-01	-5.242030E-02	2.254213E-02
9	G	1.464825E-02	2.887681E-02	4.441124E-01	-1.302609E-01	5.062617E-02	1.342067E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE
AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 262

EIGHT TENTHS, 750 DEG
LOAD STEP = 9.00000E+00

SUBCASE 80

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.185603E-03	1.243526E-06	4.316183E-01	1.875711E-04	1.117204E-01	-2.506002E-07
2	G	1.417925E-02	2.942253E-02	5.065101E-01	-2.404146E-01	-2.888359E-02	1.954734E-02
3	G	1.833803E-02	3.533886E-02	5.029299E-01	-1.813364E-01	3.861633E-02	2.674154E-03
4	G	2.124754E-02	3.281137E-02	4.416420E-01	-1.383669E-01	1.484223E-01	-1.124447E-02
5	G	1.907386E-02	2.469236E-02	3.329482E-01	-8.159911E-02	1.366130E-01	-9.325075E-03
6	G	1.208137E-02	1.349166E-02	1.865269E-01	-1.245918E-01	3.337945E-01	-2.669912E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.239704E-02	2.603454E-02	4.807940E-01	-1.783060E-01	-5.471918E-02	2.464744E-02
9	G	1.596597E-02	3.15659E-02	4.638112E-01	-1.361230E-01	5.284215E-02	1.482992E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE
AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 263

NINE TENTHS, 750 DEG
LOAD STEP = 1.00000E+01

SUBCASE 90

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.900228E-03	1.460734E-06	4.487016E-01	2.259106E-04	1.253379E-01	1.202769E-06
2	G	1.529323E-02	3.182934E-02	5.263479E-01	-2.506580E-01	-2.982629E-02	2.110100E-02
3	G	1.979396E-02	3.823910E-02	5.226444E-01	-1.889539E-01	3.985230E-02	2.946332E-03
4	G	2.294482E-02	3.551386E-02	4.589735E-01	-1.441506E-01	1.544974E-01	-1.220609E-02
5	G	2.060129E-02	2.673698E-02	3.460251E-01	-8.436879E-02	1.416748E-01	-1.007030E-02
6	G	1.307177E-02	1.462995E-02	1.939771E-01	-1.306372E-01	3.466152E-01	-2.901123E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.337197E-02	2.817466E-02	4.995856E-01	-1.854437E-01	-5.677415E-02	2.665821E-02
9	G	1.722686E-02	3.414521E-02	4.819274E-01	-1.414769E-01	5.485447E-02	1.623476E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE
AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 264

ONE, 750 DEG
LOAD STEP = 1.10000E+01

SUBCASE 101

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	1.058443E-02	1.687102E-06	4.645862E-01	2.664404E-04	1.383798E-01	3.074097E-06
2	G	1.636299E-02	3.414536E-02	5.447560E-01	-2.601024E-01	-3.066830E-02	2.259312E-02
3	G	2.119383E-02	4.103179E-02	5.409357E-01	-1.959887E-01	4.099115E-02	3.212870E-03
4	G	2.457840E-02	3.81780E-02	4.750564E-01	-1.494931E-01	1.601210E-01	-1.313171E-02
5	G	2.202758E-02	2.877804E-02	3.581629E-01	-8.694680E-02	1.463839E-01	-1.078928E-02
6	G	1.402692E-02	1.572117E-02	2.008928E-01	-1.362720E-01	3.584681E-01	-3.124823E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.430772E-02	3.02551E-02	5.170316E-01	-1.920404E-01	-5.862736E-02	2.858748E-02
9	G	1.843922E-02	3.662911E-02	4.987457E-01	-1.464151E-01	5.670011E-02	1.763805E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE
AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 255

ONE TENTH, 800 DEG
LOAD STEP = 2.00000E+00

SUBCASE 10

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	2.409217E-03	7.23349E-08	2.217295E-01	4.434285E-06	-3.834364E-03	-5.940812E-07
2	G	3.767214E-03	7.189396E-03	2.595004E-01	-1.079043E-01	-1.678030E-02	5.211547E-03
3	G	4.842312E-03	8.637650E-03	2.571973E-01	-8.389262E-02	2.395480E-02	3.353807E-04
4	G	5.595482E-03	7.982764E-03	2.256968E-01	-6.410769E-02	7.092697E-02	-2.449727E-03
5	G	5.027640E-03	5.934914E-03	1.700190E-01	-4.652965E-02	7.588313E-02	-2.558075E-03
6	G	3.049131E-03	3.101758E-03	9.357842E-02	-4.887508E-02	1.694576E-01	-5.913106E-03
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	3.280696E-03	6.465385E-03	2.474979E-01	-8.647330E-02	-2.557588E-02	5.937027E-03
9	G	4.270277E-03	7.827287E-03	2.388329E-01	-6.653942E-02	2.594907E-02	4.127356E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE
AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 256

TWO TENTHS, 800 DEG
LOAD STEP = 3.00000E+00

SUBCASE 20

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	3.767862E-03	2.069973E-07	2.755946E-01	1.910698E-05	1.441305E-02	-1.321631E-06
2	G	5.839716E-03	1.154590E-02	3.233941E-01	-1.424637E-01	-1.965939E-02	8.027831E-03
3	G	7.506829E-03	1.385451E-02	3.207943E-01	-1.090887E-01	2.748950E-02	7.648080E-04
4	G	8.674560E-03	1.283551E-02	2.815975E-01	-8.348065E-02	9.125303E-02	-4.130782E-03
5	G	7.789301E-03	9.598813E-03	2.122403E-01	-5.598110E-02	9.114101E-02	-3.877098E-03
6	G	4.807315E-03	5.117154E-03	1.176847E-01	-6.866191E-02	2.128305E-01	-9.888115E-03
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	5.091081E-03	1.031672E-02	3.077836E-01	-1.106599E-01	-3.356996E-02	9.605721E-03
9	G	6.585016E-03	1.248383E-02	2.969963E-01	-8.496284E-02	3.321057E-02	5.984635E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE
AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 257

THREE TENTHS, 800 DEG
LOAD STEP = 4.00000E+00

SUBCASE 30

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	4.895988E-03	3.025601E-07	3.137889E-01	3.504160E-05	3.267023E-02	-1.906364E-06
2	G	7.563999E-03	1.520512E-02	3.685051E-01	-1.669908E-01	-2.190826E-02	1.038142E-02
3	G	9.736546E-03	1.824448E-02	3.656821E-01	-1.270972E-01	3.017187E-02	1.134657E-03
4	G	1.125570E-02	1.691151E-02	3.210321E-01	-9.717766E-02	1.054782E-01	-5.572170E-03
5	G	1.010305E-02	1.267473E-02	2.419820E-01	-6.238367E-02	1.021677E-01	-4.986264E-03
6	G	6.289448E-03	6.815590E-03	1.346498E-01	-8.241998E-02	2.430308E-01	-1.326708E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	6.601885E-03	1.354073E-02	3.503475E-01	-1.275905E-01	-3.901977E-02	1.268629E-02
9	G	8.517966E-03	1.638487E-02	3.380387E-01	-9.780969E-02	3.818903E-02	7.611650E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST

4, 2000 MSC/NASTRAN 2/ 9/99

PAGE 258

FOUR TENTHS, 800 DEG
LOAD STEP = 5.00000E+00

SUBCASE 40

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	5.893919E-03	4.822714E-07	3.443650E-01	6.033322E-05	5.014195E-02	-2.220505E-06
2	G	9.094284E-03	1.846860E-02	4.044853E-01	-1.864029E-01	-2.376981E-02	1.248495E-02
3	G	1.172111E-02	2.216236E-02	4.014731E-01	-1.413986E-01	3.238497E-02	1.470464E-03
4	G	1.355602E-02	2.055029E-02	3.524718E-01	-1.080152E-01	1.167401E-01	-6.866996E-03
5	G	1.216542E-02	1.542111E-02	2.656844E-01	-6.740604E-02	1.110834E-01	-5.979680E-03
6	G	7.615007E-03	8.335505E-03	1.481622E-01	-9.331303E-02	2.668985E-01	-1.630472E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	7.943596E-03	1.641321E-02	3.843186E-01	-1.409598E-01	-4.325803E-02	1.543470E-02
9	G	1.023722E-02	1.986396E-02	3.707911E-01	-1.079311E-01	4.208649E-02	9.137515E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST

4, 2000 MSC/NASTRAN 2/ 9/99

PAGE 259

FIVE TENTHS, 800 DEG
LOAD STEP = 6.00000E+00

SUBCASE 50

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	6.803548E-03	6.540931E-07	3.702801E-01	8.760913E-05	6.672394E-02	-2.264563E-06
2	G	1.049426E-02	2.146320E-02	4.348795E-01	-2.026014E-01	-2.534450E-02	1.441989E-02
3	G	1.353988E-02	2.576037E-02	4.316990E-01	-1.533454E-01	3.427294E-02	1.785669E-03
4	G	1.566683E-02	2.389444E-02	3.790288E-01	-1.170929E-01	1.261947E-01	-8.058753E-03
5	G	1.405911E-02	1.794618E-02	2.857069E-01	-7.162790E-02	1.186834E-01	-6.895120E-03
6	G	8.835103E-03	9.735231E-03	1.595734E-01	-1.025003E-01	2.869271E-01	-1.911298E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	9.170719E-03	1.904903E-02	4.130411E-01	-1.521381E-01	-4.676519E-02	1.795735E-02
9	G	1.181266E-02	2.305970E-02	3.984845E-01	-1.163882E-01	4.533708E-02	1.060367E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST

4, 2000 MSC/NASTRAN 2/ 9/99

PAGE 260

SIX TENTHS, 800 DEG
LOAD STEP = 7.00000E+00

SUBCASE 60

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	7.647557E-03	8.390211E-07	3.929948E-01	1.181119E-04	8.245897E-02	-1.971680E-06
2	G	1.179758E-02	2.425909E-02	4.614461E-01	-2.166370E-01	-2.670863E-02	1.622856E-02
3	G	1.523599E-02	2.912220E-02	4.581133E-01	-1.637211E-01	3.593316E-02	2.085275E-03
4	G	1.763763E-02	2.702105E-02	4.022401E-01	-1.249736E-01	1.344191E-01	-9.173414E-03
5	G	1.582847E-02	2.030809E-02	3.032095E-01	-7.531551E-02	1.253701E-01	-7.752960E-03
6	G	9.977307E-03	1.104623E-02	1.695468E-01	-1.105374E-01	3.043347E-01	-2.175217E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.031282E-02	2.151007E-02	4.381631E-01	-1.618444E-01	-4.975551E-02	2.030968E-02
9	G	1.328166E-02	2.604611E-02	4.227058E-01	-1.237165E-01	4.813914E-02	1.203917E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST

4, 2000 MSC/NASTRAN 2/ 9/99

PAGE 261

SEVEN TENTHS, 800 DEG
LOAD STEP = 8.00000E+00

SUBCASE 70

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	8.439931E-03	1.035662E-06	4.133511E-01	1.514784E-04	9.741759E-02	-1.312855E-06
2	G	1.302513E-02	2.689921E-02	4.851944E-01	-2.290847E-01	-2.790459E-02	1.793668E-02
3	G	1.683594E-02	3.229906E-02	4.817216E-01	-1.729429E-01	3.741853E-02	2.373259E-03
4	G	1.949881E-02	2.997753E-02	4.229888E-01	-1.319758E-01	1.417421E-01	-1.022706E-02
5	G	1.750073E-02	2.254261E-02	3.188582E-01	-7.861640E-02	1.313777E-01	-8.565682E-03
6	G	1.105861E-02	1.228788E-02	1.784633E-01	-1.177388E-01	3.198195E-01	-2.425964E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.138811E-02	2.383438E-02	4.606336E-01	-1.704736E-01	-5.235960E-02	2.252666E-02
9	G	1.466729E-02	2.886891E-02	4.443699E-01	-1.302176E-01	5.061096E-02	1.345749E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST

4, 2000 MSC/NASTRAN 2/ 9/99

PAGE 262

EIGHT TENTHS, 800 DEG
LOAD STEP = 9.00000E+00

SUBCASE 80

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.190085E-03	1.242971E-06	4.318842E-01	1.874332E-04	1.116726E-01	-2.664049E-07
2	G	1.419091E-02	2.941239E-02	5.067651E-01	-2.403087E-01	-2.896178E-02	1.956150E-02
3	G	1.835756E-02	3.532537E-02	5.031620E-01	-1.812745E-01	3.876413E-02	2.652328E-03
4	G	2.127079E-02	3.279571E-02	4.418352E-01	-1.383013E-01	1.483717E-01	-1.123068E-02
5	G	1.909413E-02	2.467368E-02	3.330756E-01	-8.162159E-02	1.368562E-01	-9.341664E-03
6	G	1.209042E-02	1.347322E-02	1.865643E-01	-1.243016E-01	3.338226E-01	-2.666049E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.240886E-02	2.604753E-02	4.810552E-01	-1.782739E-01	-5.466152E-02	2.463203E-02
9	G	1.598505E-02	3.155873E-02	4.640582E-01	-1.360816E-01	5.282779E-02	1.486651E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST

4, 2000 MSC/NASTRAN 2/ 9/99

PAGE 263

NINE TENTHS, 800 DEG
LOAD STEP = 1.00000E+01

SUBCASE 90

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.904739E-03	1.460126E-06	4.489576E-01	2.257592E-04	1.252910E-01	1.184404E-06
2	G	1.530493E-02	3.181924E-02	5.265937E-01	-2.505556E-01	-2.990182E-02	2.111534E-02
3	G	1.981353E-02	3.822565E-02	5.228681E-01	-1.888944E-01	3.999476E-02	2.924391E-03
4	G	2.296811E-02	3.549825E-02	4.591597E-01	-1.440868E-01	1.544485E-01	-1.219219E-02
5	G	2.062162E-02	2.671836E-02	3.461480E-01	-8.439176E-02	1.419087E-01	-1.008687E-02
6	G	1.308086E-02	1.461151E-02	1.940132E-01	-1.303578E-01	3.466430E-01	-2.897259E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.338382E-02	2.816769E-02	4.998373E-01	-1.854129E-01	-5.671909E-02	2.664286E-02
9	G	1.724596E-02	3.413739E-02	4.821653E-01	-1.414373E-01	5.484086E-02	1.627107E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

ONE, 800 DEG
LOAD STEP = 1.10000E+01

SUBCASE 101

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	1.058897E-02	1.686442E-06	4.648337E-01	2.662762E-04	1.383338E-01	3.053091E-06
2	G	1.637471E-02	3.413530E-02	5.449938E-01	-2.600031E-01	-3.074152E-02	2.260761E-02
3	G	2.121343E-02	4.101840E-02	5.411522E-01	-1.959312E-01	4.112897E-02	3.190834E-03
4	G	2.460172E-02	3.810223E-02	4.752367E-01	-1.494310E-01	1.600737E-01	-1.311774E-02
5	G	2.209298E-02	2.868947E-02	3.582820E-01	-8.697009E-02	1.466097E-01	-1.080584E-02
6	G	1.403605E-02	1.570974E-02	2.009279E-01	-1.360021E-01	3.584956E-01	-3.120959E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.431960E-02	3.020857E-02	5.172750E-01	-1.920108E-01	-5.857456E-02	2.857220E-02
9	G	1.845835E-02	3.662134E-02	4.989759E-01	-1.463770E-01	5.668717E-02	1.767406E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 255

ONE TENTH, 850 DEG
LOAD STEP = 2.00000E+00

SUBCASE 10

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	2.413418E-03	7.224163E-08	2.222500E-01	4.413967E-06	-3.870352E-03	-5.956138E-07
2	G	3.778560E-03	7.180582E-03	2.599986E-01	-1.077444E-01	-1.691037E-02	5.220483E-03
3	G	4.861564E-03	8.617995E-03	2.576499E-01	-8.377372E-02	2.422177E-02	3.175886E-04
4	G	5.618501E-03	7.967975E-03	2.260758E-01	-6.403174E-02	7.084761E-02	-2.439675E-03
5	G	5.047027E-03	5.916492E-03	1.702601E-01	-4.650891E-02	7.636105E-02	-2.575012E-03
6	G	3.057620E-03	3.084141E-03	9.365150E-02	-4.832567E-02	1.694968E-01	-5.877363E-03
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	3.292335E-03	6.458806E-03	2.480060E-01	-8.641482E-02	-2.546616E-02	5.923080E-03
9	G	4.289178E-03	7.819947E-03	2.393133E-01	-6.646952E-02	2.592663E-02	4.156616E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 256

TWO TENTHS, 850 DEG
LOAD STEP = 3.00000E+00

SUBCASE 20

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	3.772129E-03	1.882832E-07	2.760105E-01	1.780172E-05	1.436925E-02	-1.309143E-06
2	G	5.850880E-03	1.153663E-02	3.237965E-01	-1.423677E-01	-1.978103E-02	8.038891E-03
3	G	7.526264E-03	1.384186E-02	3.211616E-01	-1.090465E-01	2.772048E-02	7.441988E-04
4	G	8.697723E-03	1.282023E-02	2.919012E-01	-8.341078E-02	9.118555E-02	-4.119762E-03
5	G	7.809015E-03	9.580082E-03	2.124352E-01	-5.598504E-02	9.152503E-02	-3.894025E-03
6	G	4.816039E-03	5.099081E-03	1.177426E-01	-6.821406E-02	2.128647E-01	-9.850820E-03
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	5.102781E-03	1.030977E-02	3.081896E-01	-1.106357E-01	-3.346835E-02	9.589828E-03
9	G	6.603840E-03	1.247585E-02	2.973777E-01	-8.491036E-02	3.318162E-02	6.022662E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 257

THREE TENTHS, 850 DEG
LOAD STEP = 4.00000E+00

SUBCASE 30

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	4.900307E-03	3.242815E-07	3.141540E-01	3.665649E-05	3.262341E-02	-1.885886E-06
2	G	7.575484E-03	1.519500E-02	3.688534E-01	-1.668504E-01	-2.200970E-02	1.039363E-02
3	G	9.755863E-03	1.823097E-02	3.659984E-01	-1.270069E-01	3.036955E-02	1.114339E-03
4	G	1.127871E-02	1.689588E-02	3.212960E-01	-9.709845E-02	1.054122E-01	-5.559691E-03
5	G	1.012281E-02	1.265587E-02	2.421531E-01	-6.239516E-02	1.025038E-01	-5.003108E-03
6	G	6.298190E-03	6.797316E-03	1.346999E-01	-8.202291E-02	2.430620E-01	-1.322906E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	6.613571E-03	1.353366E-02	3.507046E-01	-1.275435E-01	-3.893945E-02	1.267102E-02
9	G	8.536905E-03	1.637698E-02	3.383765E-01	-9.775277E-02	3.816962E-02	7.647147E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 258

FOUR TENTHS, 850 DEG
LOAD STEP = 5.00000E+00

SUBCASE 40

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	5.898267E-03	4.819513E-07	3.446976E-01	6.025681E-05	5.009273E-02	-2.227163E-06
2	G	9.105776E-03	1.845849E-02	4.048034E-01	-1.862778E-01	-2.386514E-02	1.249783E-02
3	G	1.174049E-02	2.214886E-02	4.017623E-01	-1.413231E-01	3.256787E-02	1.449489E-03
4	G	1.357910E-02	2.053461E-02	3.527125E-01	-1.079401E-01	1.166789E-01	-6.854097E-03
5	G	1.218533E-02	1.540226E-02	2.658411E-01	-6.742228E-02	1.113895E-01	-5.996456E-03
6	G	7.623834E-03	8.317149E-03	1.482080E-01	-9.295017E-02	2.669286E-01	-1.626639E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	7.955311E-03	1.640611E-02	3.846441E-01	-1.409201E-01	-4.318351E-02	1.541919E-02
9	G	1.025617E-02	1.985601E-02	3.710987E-01	-1.078797E-01	4.206750E-02	9.174506E-04

FIVE TENTHS, 850 DEG
LOAD STEP = 6.00000E+00

SUBCASE 50

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	6.807934E-03	6.537123E-07	3.705895E-01	8.751604E-05	6.667449E-02	-2.273295E-06
2	G	1.050580E-02	2.145305E-02	4.351756E-01	-2.024821E-01	-2.543410E-02	1.443324E-02
3	G	1.355930E-02	2.574685E-02	4.319682E-01	-1.532743E-01	3.444390E-02	1.764385E-03
4	G	1.568995E-02	2.387874E-02	3.792529E-01	-1.170205E-01	1.261368E-01	-8.045512E-03
5	G	1.407912E-02	1.792737E-02	2.858534E-01	-7.164693E-02	1.189678E-01	-6.911833E-03
6	G	8.843997E-03	9.716834E-03	1.596162E-01	-1.021624E-01	2.869564E-01	-1.907451E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	9.182462E-03	1.904195E-02	4.133443E-01	-1.521008E-01	-4.669637E-02	1.794184E-02
9	G	1.183164E-02	2.305176E-02	3.987711E-01	-1.163399E-01	4.531955E-02	1.064080E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 260

SIX TENTHS, 850 DEG
LOAD STEP = 7.00000E+00

SUBCASE 60

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	7.651977E-03	8.385808E-07	3.932865E-01	1.180031E-04	8.240986E-02	-1.982643E-06
2	G	1.180917E-02	2.424895E-02	4.617254E-01	-2.165228E-01	-2.679374E-02	1.624226E-02
3	G	1.525545E-02	2.910868E-02	4.583673E-01	-1.636536E-01	3.609486E-02	2.063758E-03
4	G	1.766079E-02	2.700536E-02	4.024516E-01	-1.249036E-01	1.343639E-01	-9.159934E-03
5	G	1.584858E-02	2.028933E-02	3.033482E-01	-7.533624E-02	1.256379E-01	-7.769627E-03
6	G	9.986255E-03	1.102781E-02	1.695873E-01	-1.102186E-01	3.043635E-01	-2.171361E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.032459E-02	2.150301E-02	4.384492E-01	-1.618092E-01	-4.969111E-02	2.029418E-02
9	G	1.330068E-02	2.603820E-02	4.229762E-01	-1.236710E-01	4.812279E-02	1.207627E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 261

SEVEN TENTHS, 850 DEG
LOAD STEP = 8.00000E+00

SUBCASE 70

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	8.444383E-03	1.035165E-06	4.136287E-01	1.513549E-04	9.736912E-02	-1.326176E-06
2	G	1.303675E-02	2.688907E-02	4.854603E-01	-2.289750E-01	-2.798601E-02	1.795065E-02
3	G	1.685544E-02	3.228557E-02	4.819636E-01	-1.728785E-01	3.757272E-02	2.351565E-03
4	G	1.952202E-02	2.996187E-02	4.231902E-01	-1.319081E-01	1.416893E-01	-1.021340E-02
5	G	1.752092E-02	2.252390E-02	3.189906E-01	-7.863822E-02	1.316321E-01	-8.582314E-03
6	G	1.106761E-02	1.226945E-02	1.785021E-01	-1.174355E-01	3.198478E-01	-2.422103E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.139991E-02	2.382736E-02	4.609060E-01	-1.704401E-01	-5.229882E-02	2.251120E-02
9	G	1.468634E-02	2.886103E-02	4.446275E-01	-1.301744E-01	5.059562E-02	1.349442E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 262

EIGHT TENTHS, 850 DEG
LOAD STEP = 9.00000E+00

SUBCASE 80

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.194567E-03	1.242418E-06	4.321500E-01	1.872956E-04	1.116249E-01	-2.821901E-07
2	G	1.420257E-02	2.940229E-02	5.070201E-01	-2.402029E-01	-2.904010E-02	1.957568E-02
3	G	1.837709E-02	3.531191E-02	5.033941E-01	-1.812128E-01	3.891205E-02	2.630493E-03
4	G	2.129404E-02	3.278008E-02	4.420284E-01	-1.382357E-01	1.483209E-01	-1.121689E-02
5	G	1.911439E-02	2.465502E-02	3.332028E-01	-8.164413E-02	1.370996E-01	-9.358269E-03
6	G	1.209946E-02	1.345478E-02	1.866016E-01	-1.240111E-01	3.338506E-01	-2.662186E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.242068E-02	2.604054E-02	4.813163E-01	-1.782419E-01	-5.460377E-02	2.461663E-02
9	G	1.600412E-02	3.155088E-02	4.643051E-01	-1.360403E-01	5.281332E-02	1.490320E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 263

NINE TENTHS, 850 DEG
LOAD STEP = 1.00000E+01

SUBCASE 90

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.909249E-03	1.459520E-06	4.492135E-01	2.256083E-04	1.252442E-01	1.166062E-06
2	G	1.531662E-02	3.180917E-02	5.268393E-01	-2.504533E-01	-2.997748E-02	2.112970E-02
3	G	1.983310E-02	3.821223E-02	5.230917E-01	-1.888350E-01	4.013733E-02	2.902442E-03
4	G	2.299140E-02	3.548266E-02	4.593459E-01	-1.440231E-01	1.543995E-01	-1.217831E-02
5	G	2.064195E-02	2.669975E-02	3.462709E-01	-8.441477E-02	1.421427E-01	-1.010346E-02
6	G	1.308994E-02	1.459308E-02	1.940493E-01	-1.300782E-01	3.466707E-01	-2.893395E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.339567E-02	2.816073E-02	5.000889E-01	-1.853822E-01	-5.666395E-02	2.662752E-02
9	G	1.726506E-02	3.412959E-02	4.824032E-01	-1.413977E-01	5.482716E-02	1.630748E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE

AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 264

ONE, 850 DEG
LOAD STEP = 1.10000E+01

SUBCASE 101

DISPLACEMENT VECTOR

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	1.059351E-02	1.685783E-06	4.650811E-01	2.661124E-04	1.382880E-01	3.032111E-06
2	G	1.638644E-02	3.412526E-02	5.452314E-01	-2.599040E-01	-3.081485E-02	2.262212E-02
3	G	2.123303E-02	4.100503E-02	5.413686E-01	-1.958738E-01	4.126689E-02	3.168791E-03
4	G	2.462505E-02	3.808668E-02	4.754169E-01	-1.493690E-01	1.600262E-01	-1.310377E-02
5	G	2.211337E-02	2.867091E-02	3.584011E-01	-8.699342E-02	1.468356E-01	-1.082241E-02
6	G	1.404516E-02	1.569131E-02	2.009629E-01	-1.357319E-01	3.585230E-01	-3.117096E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.433147E-02	3.020165E-02	5.175185E-01	-1.919812E-01	-5.852170E-02	2.855693E-02
9	G	1.847748E-02	3.661359E-02	4.992060E-01	-1.463390E-01	5.667415E-02	1.771015E-03

THIS PAGE INTENTIONALLY LEFT BLANK

LIST OF REFERENCES

- Acree, Robert L. "Large Array Antenna Structure (SBR)." CD-ROM. Air Force Research Laboratory.
- Acree, Bob. "Inflatable Spacecraft Technology." CD-ROM. Air Force Research Laboratory.
- Agrawal, Brij. AA4816 Class Notes. Naval Postgraduate School. 2000. Monterey, CA.
- Baldwin, Craig. "SATCOM 101." Naval Space Command and Naval Postgraduate School. 1999. Monterey, CA.
- Bradford, Rodney. "Thin Film Inflatable Structures for Space Applications." Chantilly, VA. 27 Apr 1999.
- Cassapakis, Costas. "Status of Space Inflatable Structures Technology Elements at L'Garde, Inc." Chantilly, VA. 27 Apr 1999.
- Cassapakis, Constantine G., Allan W. Love, and Arthur L. Palisoc. Inflatable Space Antennas: A Brief Overview. IEEE Aerospace Applications Conference Proceedings of the 1998 IEEE Aerospace Conference. 1998.
- Cassapakis, Costa, and Mitch Thomas. "Inflatable Structures Technology Development Overview." Diss. L'Garde, Inc. Newport Beach, CA.
- Chmielewski, Artur B. "NASA Space Inflatables Program." Chantilly, VA. 27 Apr 1999.
- Chmielewski, Artur B. "ARISE Antenna." Diss. Jet Propulsion Laboratory. Pasadena, CA.
- Chmielewski, Art B., and Jim Ulvestad. "ARISE." Online. L'Garde. Internet. 8 Dec. 1999. Available : www.lgarde.com/people/papers/arise/arise1/arise1a
- Criswell, Marvin E. et al. "Design and Performance Criteria for Inflatable Structures in Space." Diss. Space Engineering/Construction/Operations.
- Clayton, Chris. "Large Space Optics." Diss. Air Force Research Laboratory.
- Douglas, Robert L. Satellite Communications Technology. New Jersey: Prentice Hall, 1988.
- Freeland, R. E. et al. "Large Inflatable Deployable Antenna Flight Experiment Results." Diss. Jet Propulsion Laboratory/California Institute of Technology, L'Garde, Incorporated, and National Aeronautics and Space Administration.

- Freeland, R. E., and G. Bilyeu. "In-Step Inflatable Antenna Experiment." Diss. Jet Propulsion Laboratory/California Institute of Technology, L'Garde, Incorporated.
- Freeland, R. E., G. D. Bilyeu, and M. M. Mikulas. "Inflatable Deployable Space Structures Technology Summary." Diss. Jet Propulsion Laboratory/California Institute of Technology, L'Garde, Incorporated, and University of Colorado.
- Freeland, Robert E., and Richard G. Helms. "History of Inflatable Structures." Chantilly, VA. 27 Apr 1999.
- Gipson, Lillian. "Commercial Development of Space." Innovation v4 n2 (May/June 1996).
- Grahne, Mark. "STA Workshop on Inflatable Structures." Chantilly, VA., 27 Apr 1999.
- Hoferer, Robert A., and Yahya Rahmat-Samii. "RF Characterization of an Inflatable Parabolic Torus Reflector Antenna for Space-Borne Applications." IEEE Transactions on Antennas and Propagation v46 n10 (1998): 1449-1457.
- Katuin, Kevan D. "An Analysis of Space Inflatable Applications and Technology." Diss. Naval Postgraduate School, 1999.
- Kimura, Shinichi, Toshiyuki Okuyama, Yuji Yamaha, Yasushi Nagai, and Hajime Morikawa. Teleoperation System for Antenna Assembly by Space Robots. Proceedings of SPIE – The International Society for Optical Engineering - Proceedings of the 1998 Conference on Telemanipulator and Telepresence Technologies, v 3524. Boston, MA. 1998.
- Kunath R. and R. Sharp. "Design of an Inflatable, Optically Controlled and Fed, Phased Array Antenna." Proceeding of AIAA/NASA/OAI Conference on Advanced SEI Technologies. Cleveland, OH, 1991.
- Larson, Wiley J., and James R. Wertz, eds. Space Mission Analysis and Design. Torrance, CA: Microcosm, Inc., 1992, and Boston: Kluwer Academic Publishers, 1992.
- L'Garde. "Space Technology Alliance: Meeting on Inflatable Space Structures." CD-ROM. Chantilly, VA. 27 Apr. 1999.
- Loomis, H. H. Jr. "Communications Link Equations." Diss. Naval Postgraduate School. Monterey, CA.
- Miller, Mark P. Getting Started with MSC/NASTRAN. USA: The MacNeal-Schwendler Corporation, 1996.
- Measurement Specialties, Inc. "Definition of Piezo Film Polarity." Application Note 65773, 1 Aug. 1998 REV D.

Neurgaonkar, R. R., and J. G. Nelson. "High Performance Piezoelectric Thin Films for Shape Control in Large Inflatable Structures: Summary of Research Final Report." Diss. National Aeronautics and Space Administration. 1999.

Palisoc, A. et al. Geometry Attained by Pressurized Membranes. Proceedings of SPIE – The International Society for Optical Engineering – Proceeding of the 1998 Conference on Space Telescopes and Instruments V. Kona, HI, 1998. SPIE Bellingham, WA.

Robbins, Gary. "Space Target – Air Force to Bounce Lasers off Tustin-Made Balloon." The Orange County Resister. 29 Oct 1999.

Salama, M., J. Kuo, J. Garba, B. Wada, and M. Thomas. On-Orbit Shape Correction of Inflatable Structures. Diss. Jet Propulsion Laboratory, California Institute of Technology. Pasadena, CA, and L'Garde Inc. Tustin, CA.

Satter, Celeste M., and Robert L. Freeland. "Inflatable Structures Technology Applications and Requirements." Diss. Jet Propulsion Laboratory, California Institute of Technology. Pasadena, CA.

Shields, John Potter. Basic Piezoelectricity. New York: Howard W. Sams & Co., Inc. and the Bobbs-Merrill Company, Inc.

ILC Dover. "STA Workshop on Inflatable Structures." 1999.

Thomas, Mitchell, and Gilbert J. Friese. "Pressurized Antennas for Space Radars." Diss. L'Garde, Inc. Newport Beach, CA.

Tomasi, Wayne. Electronic Communications Systems. New Jersey: Prentice Hall, 1998.

Ulvestad, James S., Roger P. Linfield, and Joel G. Smith. "ARISE: A Space VLBI Mission Using an Inflatable Antenna Structure." Diss. Jet Propulsion Laboratory, California Institute of Technology. Pasadena, CA.

United States. National Aeronautics and Space Administration. "Space Technology Development." Online. Internet. 13 Jul. 2000. Available:
www.sti.nasa.gov/tto/spinoff1996/13

THIS PAGE INTENTIONALLY LEFT BLANK

INITIAL DISTRIBUTION LIST

Defense Technical Information Center	2
8725 John J. Kingman Road, Suite 0944	
Ft. Belvoir, VA 22060-6218	
Dudley Knox Library	2
Naval Postgraduate School	
411 Dyer Road	
Monterey, CA 93943-5101	
Craig Whittinghill	1
P.O. Box 472	
Athens, WV 24712	
Brij Agrawal	1
Department of Aeronautics and Astronautics	
Code AA/Ag	
Naval Postgraduate School	
699 Dyer Road, Bldg 234, Room 137	
Monterey, CA 93943-5107	
Donald Wadsworth	1
Department of Electrical and Computer Engineering	
Code EC/Wd	
833 Dyer Room 437	
Naval Postgraduate School	
Monterey, CA 93943	
Ramesh Kolar	1
Department of Aeronautics and Astronautics	
Code AA/Kj	
Naval Postgraduate School	
699 Dyer Road, Bldg 234, Room 137	
Monterey, CA 93943-5107	
Department of Aeronautics and Astronautics	1
Code AA	
Naval Postgraduate School	
699 Dyer Road, Bldg 234, Room 137	
Monterey, CA 93943-5107	