

REPORT DOCUMENTATION PAGE

Form Approved
OMB NO. 0704-0188

Public Reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comment regarding this burden estimates or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188,) Washington, DC 20503.

1. AGENCY USE ONLY (Leave Blank)	2. REPORT DATE -	3. REPORT TYPE AND DATES COVERED FINAL 01 Apr 95 - 30 Jun 99	
4. TITLE AND SUBTITLE Mechanics of Long Rod Penetration Into Ceramic Targets		5. FUNDING NUMBERS DAAH04-95-1-0134	
6. AUTHOR(S) Dusan Krajcinovic		8. PERFORMING ORGANIZATION REPORT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Arizona State University			
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) U. S. Army Research Office P.O. Box 12211 Research Triangle Park, NC 27709-2211		10. SPONSORING / MONITORING AGENCY REPORT NUMBER ARO 32660.1-EG	
11. SUPPLEMENTARY NOTES The views, opinions and/or findings contained in this report are those of the author(s) and should not be construed as an official Department of the Army position, policy or decision, unless so designated by other documentation.			
12 a. DISTRIBUTION / AVAILABILITY STATEMENT Approved for public release; distribution unlimited.		12 b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) The objective of this program is to formulate an approximate analytical method for the estimate of penetration depth of a projectile into a target and provide a rational basis to deduce the constitutive equations of the target material at large damage. An array of benchmark cases was simulated, and new statistical methods are developed and discussed. <div style="text-align: right; margin-top: 20px;"> DTIC QUALITY INSPECTED 20010117 064 </div>			
14. SUBJECT TERMS		15. NUMBER OF PAGES 4	
17. SECURITY CLASSIFICATION OR REPORT UNCLASSIFIED		16. PRICE CODE	
		19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	
18. SECURITY CLASSIFICATION ON THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT UL	

ARMY RESEARCH OFFICE

PROJECT: DAAH04-95-1-0134

MECHANICS OF LONG ROD PENETRATION INTO CERAMIC TARGETS

Dusan Krajcinovic, PI

Final Report

The thermodynamics of the penetration of a projectile through a target is non-linear, irreversible, non-stationary and far from the equilibrium. This is especially true when the inelastic deformation of the target is traced to the extensive microcracking that eventually leads to crushing and/or localization into microcracks. The available test data are almost as a rule limited to the observations of the crater and measures of penetration length are crater geometry.

The objective of this program was to formulate an approximate analytical method for the estimate of the penetration depth of a projectile into a target and provide a rational basis needed to deduce the constitutive equations of the target material at large damage. Traditional local continuum models and strain rate dependent constitutive relations are not applicable since the deformation is far from the equilibrium and damage large. Moreover, the test data at given strain rates are not available. Furthermore, deterministic measures of deformation and damage patterns in materials with microstructural disorder may not always be useful.

The only realistic strategy is to approximate the material by a lattice made of continuum particles interconnected by links. The size of continuum particles; which consist of many molecules, is determined by micromechanical considerations. For example, a particle can be as large as the smallest volume that cannot be fractured by compressive stresses. The statistics of the lattice morphology and link properties are determined from the microstructural properties of material.

An array of benchmark cases is simulated to check the model and simulations at large strain rates to gain confidence in selection of parameters and microstructural statistics. The Taylor or rigid-anvil test is used to check for the distribution of fragment sizes, relative shortening of the projectile, stress wave features, disturbance propagation velocity and temperature field. Simulations of the planar impact are used to model spalling, shock wave attenuation and to formulate the proper initial strain-rate that keeps the strain rates homogeneous afterwards. Further biaxial compressive and tensile tests are performed to observe damage patterns and optimize the time-step.

The final set of simulations is focused on determination of radial forces needed to drive the expansion of a circular void within a brittle material at a given rate. The effective material parameters, stress, strain and damage fields, kinetic, potential energy and energy consumed by the formation of new internal surfaces are used to deduce the constitutive relations. These constitutive equations are then used to formulate a

DISTRIBUTION STATEMENT A

Approved for Public Release

Distribution Unlimited

surprisingly simple analytical model. The fit between the simulation data and analytical solution of the model is exemplary.

The simulation strategy, involving mapping the lattice on the material, bench-mark problems, identified universal trends, interpretation of simulation data, and statistical methods used in the model, are carefully discussed in the papers published by D. Krajinovic and S. Mastilovic (whose complete his theses on this work).

PUBLISHED PAPERS

PAPERS SUPPORTED BY THE ARMY OFFICE OF RESEARCH

Project: DAAH04-95-1-0134

1. D. Krajcinovic, "Essential Structure of the Damage Mechanics Theories", in: Theoretical and Applied Mechanics 1996, Ed.: T. Tatsumi, E. Watanabe and T. Kambe, Proc. XIXth Int. Congress of Theoretical and Applied Mechanics, Kyoto, Japan, pp. 411-426, North-Holland, Elsevier, Amsterdam, The Netherlands, 1997.
2. D. Krajcinovic, "Effective Material Properties in the Limit of Large Defect Concentrations", Engng Fracture Mechanics, Vol. 57, No. 2/3, pp. 227-240, 1997.
3. S. Mastilovic and D. Krajcinovic, "Application of Particle Dynamics to the Mechanics of Penetration Through Brittle Solids", in: Proc. 14th US Army Symposium on Solid Mechanics, Ed.: K.R. Iyer and S.-c. Chow, Battelle Memorial Institute Publ., pp. 206-214, 1997.
4. D. Krajcinovic, "Selection of Damage Parameter - Art or Science?", Mechanics of Materials, Vol. 28, No. 1-4, 1998, pp. 165-179.
5. D. Krajcinovic, S. Mastilovic and M. Vujosevic, "Brittle to Quasi-Brittle Transition", Meccanica, Vol. 33, 1998, pp. 363-379.
6. S. Mastilovic and D. Krajcinovic, "High Velocity Expansion of a Cavity Within a Brittle Material, Journal of Mechanics and Physics of Solids, 1999, Vol. 47, No. 3, pp. 577-610.
7. D. Krajcinovic and S. Mastilovic, "Statistical Models of Brittle Deformation: Part I - Introduction, Int. J. of Plasticity, 1999, Vol. 15, pp. 401-426.
8. S. Mastilovic and D. Krajcinovic, "Statistical Models of Brittle Deformation: Part II - Simulations, Int. J. of Plasticity, 1999, Vol. 15, pp. 427-456.
9. D. Krajcinovic, "Damage Mechanics: Accomplishments, Trends and Needs", a invited paper for a special issue of "Research Trends in Solid Mechanics" coordinate by invitations from U.S. National Com. on Theoretical and Applied Mechanics, Int. J. Solids and Structures, 1999, Vol. 37, pp. 267-277.
10. S. Mastilovic and D. Krajcinovic, "Penetration of Rigid Projectiles Through Quasi-Brittle Materials, J. Appl. Mechanics, 1999, Vol. 66, Number 3, pp. 585-592.
11. D. Krajcinovic, "Brittle and Quasi-ductile Deformations at Large Strain Rates", Journal of Theoretical & Applied Fracture Mechanics, (in print).
12. D. Krajcinovic, "Introduction to Damage Mechanics", Chapter 1 of "Deformation and Fracture of Materials with Disordered Microstructure", pp. 1-16, D. Krajcinovic and J. van Mier, Eds., Springer Verlag, 2000.

- 13 D. Krajcinovic, "Molecular and Particle Simulations", Chapter 3 of "Deformation and Fracture of Materials with Disordered Microstructure", pp. 103-134, D. Krajcinovic and J. van Mier, Eds., Springer Verlag, 2000.
 - 14 D. Krajcinovic and S. Mastilovic, "Thermodynamics and Micromechanics of Damage" in: Continuous Damage and Fracture, A. Benallal Ed., pp. 19-28, Elsevier Publ., 2000.
 - 15 D. Krajcinovic, "Damage Mechanics – Bridging the Scales", Lecture Series on "Damage Mechanics of Materials and Structures", pp. 4-1 to 4-29, Centre National de la Recherche Scientifique, LMT-Cachan, France.2000.
 - 16 D. Krajcinovic and S. Mastilovic, "Models of Quasi-ductile Deformation that Bridges the Scales", Journal of Theoretical & Applied Fracture Mechanics, (in print).
 - 17 D. Krajcinovic and S. Mastilovic, "Model of Quasi-Ductile Deformations that Bridges the Scale, Journal of Theoretical & Applied Fracture Mechanics, (in print).
- Book:** D. Krajcinovic, Damage Mechanics, North-Holland Series in Applied Mathematics and Mechanics, Elsevier, Amsterdam, 1997.