

REPORT DOCUMENTATION PAGE

AFRL-SR-BL-TR-01-

0150

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing this collection of information. Send comments regarding this burden estimate or this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to provide information if it does not display a current valid OMB control number. PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.

maintaining t
or reduci
A 22202-

1. REPORT DATE (DD-MM-YYYY) 20/2/2001		2. REPORT TYPE Final Report		3. DATES COVERED (From - To) 1/4/99-30/9/00	
4. TITLE AND SUBTITLE Micromechanical Measurements of Foams, Adhesives And Composites (DURIP 99)				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER F49620-99-1-0228	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S) Stelios Kyriakides and Kenneth M. Liechti				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) The University of Texas at Austin Austin, TX 78712				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) AFOSR/NA 801 N. Randolph St. Room 732 Arlington, VA 22203-1977				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION / AVAILABILITY STATEMENT DISTRIBUTION STATEMENT A Approved for Public Release Distribution Unlimited				AIR FORCE OFFICE OF SCIENTIFIC RESEARCH (AFOSR) NOTICE OF TRANSMITTAL DTIC. THIS TECHNICAL REPORT HAS BEEN REVIEWED AND IS APPROVED FOR PUBLIC RELEASE LAW AFR 190-12. DISTRIBUTION IS UNLIMITED.	
13. SUPPLEMENTARY NOTES					
14. ABSTRACT This was an AFOSR DURIP 99 Instrumentation Grant. The grant was used to purchase two major pieces of equipment and to design and fabricate two others. The equipment are being used to perform micromechanical testing and image processing in fiber polymeric foams and honeycomb adhesives and composites. The first piece of equipment purchased is an M-5 Atomic Force Microscope from ThermoMicroscopes. The facility is being used for general surface scanning and for custom material testing. An Optronics digital camera and a digital video disk recorder were purchased for general monitoring of material testing. A 15 ft drop weight testing facility along with related accessories was designed, fabricated and tested during the period of the grant. The facility is being used to establish the dynamic energy absorption capacity of honeycombs and other light weight materials. A Mixed-Mode Delamination Tester was designed and fabricated for examining interfacial and near interfacial crack growth in composites. The facilities have become part of the laboratory of the Center for Mechanics of Solids Structures & Materials of the University of Texas.					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT None	18. NUMBER OF PAGES 4	19a. NAME OF RESPONSIBLE PERSON S. Kyriakides
a. REPORT None	b. ABSTRACT None	c. THIS PAGE None			19b. TELEPHONE NUMBER (include area code) (512) .471-5963

MICROMECHANICAL MEASUREMENTS IN FOAMS, ADHESIVES AND COMPOSITES

Final Report for DURIP 99
Grant No. F49620-99-1-0228

by

Stelios Kyriakides and Kenneth M. Liechti

Center for Mechanics of Solids, Structures & Materials
WRW 110
The University of Texas at Austin
Austin, TX 78712

February 2001

20010320 067

FORWARD

This DURIP 99 grant from the AFOSR was aimed to develop some new capabilities in the laboratories of the Center for Mechanics of Solids, Structures and Materials of the University of Texas at Austin. The grant was used to purchase two state of the art pieces of equipment and to design and fabricate two others. The new facilities which are briefly described below will enable the co-investigators to perform micromechanical testing and image processing in fiber polymeric foams, adhesives and composites. These are subjects of ongoing research at their Center funded by AFOSR and other DOD agencies.

EQUIPMENT PURCHASED/DEVELOPED

1. Atomic Force Microscope

An M-5 AFM was purchased from ThermoMicroscopes. The instrument has been housed in a specially modified clean room dedicated to microscopy. It is currently being used for high resolution surface roughness analysis and three-dimensional surface relief mapping with nanometer resolution. A second major use under development involves use of the AFM with a suitably designed probe to conduct tensile tests on miniature specimens of lengths of the order of 50 μm . Such size tests are necessary for the analysis of carbon and glass fibers as well as for establishing the in situ properties of ligaments from polymeric foams. This is a novel application of this versatile device which could open up a whole new avenue in materials testing. Extending the use of AFMs to such applications is expected to be a significant breakthrough in mechanical

characterization at the microscale. ThermoMicroscopes has agreed to assist the two PIs in designing new probes suitable for this new application of the instrument.

2. Video Camera and Recorder

An Optronics digital camera was purchased. The camera provides 768 x 494 pixel resolution. Shutter speeds range from 1/10000 to 4 seconds. The recorder is a digital video disk recorder. It can record at 780 x 480 pixels every 0.07 seconds. It accepts a variety of video input signals and can do time lapse recording.

3. Mixed-Mode Delamination Tester

A mixed-mode delamination tester was fabricated for examining interfacial or near interfacial crack growth in composites. The device makes use of piezo-electric actuators to provide displacements in the micrometer range. The displacements are provided normal and tangential to the interface of bimaterial specimens. The loads that can be accommodated in each direction are 1000 lbs. Special flexures are used to provide flexibility in one direction and rigidity in an orthogonal direction. The device was fabricated in the College of Engineering machine shop. The piezo actuators are controlled via a PC using measured displacements across and tangential to the interface.

4. Drop-Weight Testing Facility

One of the PIs (Kyriakides) is working on understanding the energy absorption capacities of foams and honeycombs. Until recently this has involved quasi-static experiments carried out in standard testing machines coupled with complex numerical simulations using implicit and explicit numerical algorithm. In many application of impact mitigation, the dynamical behavior of such materials must also be understood. The original intention was to purchase new drop-weight testing facility capable of performing moderate velocity impact tests. The cost of commercially available facilities of this type was prohibitive while their capabilities was not optimal or flexible enough for the applications. For this reason a custom drop-weight facility was designed and fabricated by the PI and a graduate student. It consists of a three-rail system which guides a yoke on which the weights are attached. Weights of 70 to 500 lb. can be dropped from as high as has a 12 ft. Targets of

10 inches in diameter can be impacted. The impact force is derived from an accelerometer and the velocity from a non-contact fiber-optic displacement transducer. A high speed data acquisition system (National Instruments) is used to monitor the experiments. Special extension of the laboratory including safety precautions was made in order to accommodate installation and operation the new facility.