

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188		
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing this collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.					
1. REPORT DATE		2. REPORT TYPE Professional Paper		3. DATES COVERED	
4. TITLE AND SUBTITLE MIDS Simulation at ACETEF			5a. CONTRACT NUMBER		
			5b. GRANT NUMBER		
			5c. PROGRAM ELEMENT NUMBER		
6. AUTHOR(S) Jon Anderson; John McMaster; Robert Ruddy			5d. PROJECT NUMBER		
			5e. TASK NUMBER		
			5f. WORK UNIT NUMBER		
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Naval Air Warfare Center Aircraft Division 22347 Cedar Point Road, Unit #6 Patuxent River, Maryland 20670-1161			8. PERFORMING ORGANIZATION REPORT NUMBER		
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)			10. SPONSOR/MONITOR'S ACRONYM(S)		
			11. SPONSOR/MONITOR'S REPORT NUMBER(S)		
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution is unlimited.					
13. SUPPLEMENTARY NOTES					
14. ABSTRACT A software package for passing Simulated Warfare Environment Generator (SWEG) and Joint Interim Mission Model (JIMM) shared memory data in Link-16 format has been developed. The Air Combat Environment Test and Evaluation Facility (ACETEF) has special consoles (Mini-Crew Stations) which are interfaced to the warfare model with this software. Each station plays the role of an aircraft in the simulation and displays its information to the pilot in Multifunctional Information Distribution System (MIDS) format. The software functionality, initial demonstration results and plans for further upgrades will be discussed in this paper.					
15. SUBJECT TERMS Simulated Warfare Environment Generator (SWEG); Joint Interim Mission Model (JIMM); Multifunctional Information Distribution System (MIDS); Air Combat Environment Test and Evaluation Facility (ACETEF)					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT	18. NUMBER OF PAGES 4	19a. NAME OF RESPONSIBLE PERSON Jon Anderson / John McMaster / Rob Ruddy
a. REPORT	b. ABSTRACT	c. THIS PAGE			19b. TELEPHONE NUMBER (include area code) (301) 342-6370 / 342-6357 / 342-6371

Standard Form 298 (Rev. 8-98)
Prescribed by ANSI Std. Z39-18

20010426 095

MIDS Simulation at ACETEF

Jon G. Anderson

John W. McMaster

Robert J. Ruddy

Department of the Navy

Commander

ACETEF 516200A BLDG 2019

48150 Shaw Road Unit 5

Patuxent River, MD 20670-1907

301-342-6370,301-342-6357,301-342-6371

andersonjg@navair.navy.mil,mcmasterjw@navair.navy.mil,ruddyjrj@navair.navy.mil

Mark R. Freed

Eagan McAllister Associates, Inc.

P.O. Box 986

Lexington Park, MD 20653

301-342-6351

freedmr@navair.navy.mil

Stephen C. O'Day, Ph.D.

J.F. Taylor, Inc.

21610 South Essex Drive

Lexington Park, MD 20653

301-342-6101

odaysc@navair.navy.mil

Michael R. Willmore

American Electronic Warfare Associates, Inc.

21783 N. Coral Drive

Lexington Park, MD 20653

301-342-6387

willmoremr@navair.navy.mil

Keywords:

MIDS,JIMM,SWEG,ACETEF,manned,JTIDS,Link-16

ABSTRACT: *A software package for passing Simulated Warfare Environment Generator(SWEG) and Joint Interim Mission Model(JIMM) shared memory data in Link-16 format has been developed. The Air Combat Environment Test and Evaluation Facility(ACETEF) has special consoles(Mini-Crew stations) which are interfaced to the warfare model with this software. Each station plays the role of an aircraft in the simulation and displays its information to the pilot in Multifunctional Information Distribution System (MIDS) format. The software functionality, initial demonstration results and plans for further upgrades will be discussed in this paper.*

1. Overview

A MIDS simulation capability is being developed at ACETEF which links to the simulated warfare environment generated by the SWEG/JIMM[1] models. The MIDS graphical user interface display software runs on mini-crew stations. Multiple aircraft may be simulated simultaneously within a gaming environment using these manned stations.

The proposed system consists of the following parts:

- 1) A mini-crew station with a touch panel display, a hand controller, a throttle and graphics support software to emulate the principal functions of a MIDS display.
- 2) An interface between the MIDS display program and the SWEG/JIMM model. This model serves as the MIDS mission control computer(MC).
- 3) A JIMM/SWEG process run using reflected shared memory[2].
- 4) A Multi-Link System Test/Training Tool(MLST3)[3] JIMM interface asset which will stimulate a Combat Direction System interface to produce Link-16 messages for use with aircraft and stimulator hardware.

Table 1 lists a subset of the Link-16 messages that are considered relevant to an F/A-18[4]. These may be modeled in JIMM and processed to the interface or result from interface mission control processing of JIMM shared memory data.

Table 1: F/A-18 Link-16 Messages

Link-16 Message	Label
Air PPLI	J2.2
Surface (Maritime) PPLI	J2.3
Land (Ground) Point PPLI	J2.5
Land(Ground) Track PPLI	J2.6
Reference	J3.0
Air Track	J3.2
Surface (Maritime) Track	J3.3
Land (Ground) Point/Track	J3.5
Electronic Warfare Product Data	J3.7
Track Management	J7.0
Engagement Status	J10.2
Mission Assignment	J12.0
Vector	J12.1
Controlling Unit Change	J12.4
Target/Track Correlation	J12.5
Target Sorting	J12.6

Some applicable messages have been omitted from this table since they pertain to the details of Link-16

electronic signal transmission and networking and are inappropriate for a virtual wargaming environment. Non F/A-18 aircraft will utilize a message set similar to table 1 as well.

2. MIDS Simulation Software

The MIDS simulation software is described in the next two sections. The MIDS multi-tiered menuing system, situational awareness displays and an interface to the SWEG/JIMM engine are all part of this package.

2.1 Graphical User Interface

The baseline MIDS display is shown in figure 1 and consists of a Multipurpose Display Indicator(MDI), a Multipurpose Color Display Indicator(MPCD) and an Up-Front Control (UFC). Gauges are displayed for throttle/fuel, heading, attitude, altitude, speed and climb/dive rate as well.




Figure 1: MIDS Simulation Display

The MDI and MPCD screens are surrounded by twenty push buttons. These buttons allow the pilot to navigate up and down through the menu levels. The top-level MIDS Support display has a menu push button which leads to the MIDS Terminal Control Format menu which shows network status information. The top-level Tactical menu has both a Situational Awareness(SA) menu and an Attack menu beneath it.

The SA menu contains precise participant location and identification (PPLI) and surveillance tracks displayed in appropriate MIDS symbology in a compass display format. The Attack menu contains Link-16 along with sensor information in a radar display format. The SWEG/JIMM model performs the Multi-Source Integration(MSI) function and creates a "perception list" from which the Attack display is filled.

2.2 SWEG/JIMM Model and Interface

The JIMM and SWEG models have a common origin and are both language-based. These models permit the developer to create objects that have capabilities, susceptibilities, resources, tactics and systems(i.e. sensors, weapons, communicators, jammers, thinkers and movers). Player, platform and system object information is stored in persistent shared memory. Interactions between objects and events involving objects appear in the form of "asset action messages". Each hardware and software asset to the SWEG/JIMM model has a block of shared memory(i.e. a "mailbox") allocated for such messages. The MLST3 interface and each MIDS simulation will be an asset. It should be possible to run more than ten MIDS simulation assets simultaneously in real-time. Each MIDS simulation asset will assume the role, mission and function of one aircraft in the environment. This feature will allow SWEG/JIMM players, MIDS simulation players and real aircraft connected via MLST3 to all interact in the same environment.

The MIDS display interface receives PPLI information from designated platforms via persistent shared memory. Link-16 explicit communication messages are read from the asset's shared memory mailbox. The perception list comes into the interface through the mailbox as well. The Link-16 messages are generated dynamically by the model and sent to the appropriate C4ISR assets.

The SWEG/JIMM model handles the content of the J7.0(Track Management) and J12.5(Target/Track Correlation) messages internally. Since the model is performing this part of the mission computer function for all assets, these messages need not be broadcast.

3. Operational Testing

The prototype MIDS display, graphical user interface and MIDS SWEG/JIMM scenario databases have been run successfully. Virtual tracks in the scenario appear on the display in the appropriate locations and the response of the virtual MIDS aircraft to pilot actions is good. The data reflected on the gauges match well with the content of persistent shared memory. As more capability is added to the scenario and simulation, matching requirements will be written and results will be documented.

3.1 SWEG/JIMM Scenario

The prototype MIDS scenario passes PPLI and surveillance information via explicit communications messages. Explicit communications messages may be sent to or received from an asset's interface. Each Network Participation Group(NPG) in the game is represented as a separate communications network. Donors and member are thus, organized at the scenario database level- not in the interface.

An E-2C and an F/A-18 aircraft constitute the MIDS C2 participants in the scenario. There are generic targets for air, ground, surface and ELINT in the scenario as well. These players are sufficient to test existing capabilities.

4. Future Plans

The important features which need to be built into the ACETEF MIDS simulation pertain to command and control. There are some less-critical features like cursor slewing and on-screen data availability which will be added nonetheless. The level of detail will be driven by customer demand.

The J10.2(Engagement Status), the J12.0(Mission Assignment) and J12.1(Vector) messages will be added. Changes to the SWEG/JIMM model are required to execute these messages properly. At the moment, the recipient will calculate a flight path given a target rather than following the command heading, speed and altitude in J12 series messages.

5. Summary

A software package has been written which emulates a MIDS display on a Mini-Crew station and interfaces to the SWEG/JIMM model . The prototype version has considerable tested capability and greater functionality is to be added in the coming year.

6. References

- [1] TRW, Incorporated: "JIMM1.2 USERS GUIDE" September 1999.
- [2] Systran Corporation: "SCRAMNet®-LX Network EISA Hardware Interface Reference" Document No. C-T-MR-EISALX##-A-0-A1 February 1995.
- [3] Logicon, Incorporated: "System Specification for the MULTOTS/ISA Multi-Link System(MLS) for Naval Air Test Center CNIL" LGN 109-1100130-04 June 1991.
- [4] Boeing Corporation: "MIDS Student Guide" F1839OSE00-00121-0 Revised 25 April 2000.

Author Biographies

JON ANDERSON is the Lead Integrator for the Aircraft Stimulation Division at the Air Combat Environment Test & Evaluation Facility (ACETEF). Jon has developed interfaces to hardware-in-the-loop stimulators and man-in-the-loop simulators at ACETEF. He has worked on interfaces for distributed exercises such as Joint Theater Missile Defense. Jon received his BSEE from the University of Nebraska-Lincoln in 1985 and is a member of IEEE.

JOHN MCMASTER is the leader of the Interface Development Team at ACETEF. John has developed software for the ACETEF HLA interface and the DISI interface. John has participated in Atlantic Ranges and Facilities projects such as JSF VSWE events, ACETEF-REDCAP integration, JADS-EW, HLA Engineering Profederation (1996), STOWE-1994 and KERNEL BLITZ. John received his BSEE from Drexel University in 1982 and is a member of IEEE and NMIA.

ROBERT RUDDY is the Deputy Head of the Aircraft Stimulation Division and has over six years of experience in distributed simulation project management. He was the JTIDS engineer for the F-14D Technical Evaluation. Bob received his BSEE from Villanova University in 1985.

MARK FREED is a Senior Engineer at Eagan McAllister Associates, Incorporated. He works in the Interface Development Team at ACETEF on real time software design and hardware/software integration. Mark has twenty-one years of DOD weapon systems experience with a strong background in acoustic sensor systems, as well as ocean and target modeling. He has served many projects such as Joint Advanced Distributed Simulation, Joint Theater Missile Defense, Transportable Advanced Display and Debriefing Subsystem and Joint Strike Fighter. Mark received his BSEE in 1978 from the Pennsylvania State University.

STEPHEN O'DAY is a Senior Scientist at J.F. Taylor, Incorporated. He works in the Interface Development Team at ACETEF on JIMM HLA interface development and kinematic transformations. Various present/past efforts include Joint Strike Fighter, Joint Test Training Capability Assessment, Distributed Engineering Plant and Network Centric Warfare. Dr. O'Day received his Ph.D. in physics from the University of Maryland in 1990 for work done at Fermi National Accelerator Laboratory in Chicago, IL

MICHAEL WILLMORE is the Corporate Chief Scientist at American Electronic Warfare Associates, Incorporated. He is also the lead scenario developer in the ACETEF Modeling and Simulation group. During his twenty-one years of service in the United States Navy, he received numerous awards and citations for his achievements as a naval aviator and for research projects done as a staff officer at the Naval War College's Center for Advanced Research. Lieutenant Commander Willmore authored a book entitled "Principles of Engagement Analysis" and contributed to "The Art of Wargaming" authored by Dr. Peter Perla. Michael has held many high level positions within the defense industry and was nominated for staff positions in the Bush Administration and the Senate Armed Services Committee.