

ARMY RESEARCH LABORATORY



ARL Experimental Facility 108 A/B Blast Tests - Summary Report

by Neil M. Gniazdowski

ARL-MR-511

April 2001

Approved for public release; distribution is unlimited.

20010420 014

The findings in this report are not to be construed as an official Department of the Army position unless so designated by other authorized documents.

Citation of manufacturer's or trade names does not constitute an official endorsement or approval of the use thereof.

Destroy this report when it is no longer needed. Do not return it to the originator.

Army Research Laboratory

Aberdeen Proving Ground, MD 21005-5066

ARL-MR-511

April 2001

ARL Experimental Facility 108 A/B Blast Tests – Summary Report

Neil M. Gniazdowski

Weapons and Materials Research Directorate, ARL

Approved for public release; distribution is unlimited.

Abstract

The Impact Physics Branch of the Terminal Effects Division of the Weapons and Materials Research Directorate (WMRD), U.S. Army Research Laboratory (ARL), was tasked by the Armor Mechanics Branch, WMRD, ARL, to perform blast measurements in ARL Experimental Facility 108 A/B. This memorandum report briefly summarizes the results of four blast tests that were conducted on 8 November 1999. The purpose of this test program was to measure the blast pressure exhibited on various walls of the experimental facility's chamber (108A) as a result of the detonation of various size spheres of Detasheet and to determine the maximum explosive weight that could be used in this facility without extensive modifications.

Acknowledgments

The author would like to thank Carl Paxton, Sterling "Doc" Shelley, Donald Little, and Vaughn Torbert for their expert assistance during these tests.

INTENTIONALLY LEFT BLANK.

Contents

Acknowledgments	iii
List of Figures	vii
List of Tables	ix
1. Introduction	1
2. Test Setup	1
3. Results	6
4. Conclusions	11
Appendix: Transducer and Mount Specifications	31
Distribution List	39
Report Documentation Page	43

INTENTIONALLY LEFT BLANK.

List of Figures

Figure 1. Photograph of entrance to chamber showing locking mechanism and target stand.....	2
Figure 2. Photograph of chamber showing locking mechanism and baffle opening.....	3
Figure 3. Photograph of pressure gauge and mount clamped to entrance door.....	3
Figure 4. Photograph of pressure gauge and mount at entrance to vent.....	4
Figure 5. Schematic of Experimental Facility 108 A/B chamber.....	5
Figure 6. Photograph of steel baffle door.....	5
Figure 7. Photograph of data acquisition equipment.....	6
Figure 8. Test 1 long duration time history of pressure gauge mounted on door.....	7
Figure 9. Test 1 short duration time history of pressure gauge mounted on door.....	8
Figure 10. Test 1 long duration time history of pressure gauge mounted in vent.....	9
Figure 11. Test 1 short duration time history of pressure gauge mounted in vent.....	10
Figure 12. Test 1 impulse measured at the door.....	12
Figure 13. Test 2 long duration time history of pressure gauge mounted on door.....	13
Figure 14. Test 2 short duration time history of pressure gauge mounted on door.....	14
Figure 15. Test 2 long duration time history of pressure gauge mounted in vent.....	15
Figure 16. Test 2 short duration time history of pressure gauge mounted in vent.....	16
Figure 17. Test 2 impulse measured at the door.....	17
Figure 18. Test 3 long duration time history of pressure gauge mounted on door.....	18
Figure 19. Test 3 short duration time history of pressure gauge mounted on door.....	19

Figure 20. Test 3 long duration time history of pressure gauge mounted in vent.	20
Figure 21. Test 3 short duration time history of pressure gauge mounted in vent.	21
Figure 22. Test 3 impulse measured at the door.	22
Figure 23. Photograph of door with damaged locking mechanism.	23
Figure 24. Close-up photograph of damaged locking mechanism.	24
Figure 25. Test 4 long duration time history of pressure gauge mounted on door.	25
Figure 26. Test 4 short duration time history of pressure gauge mounted on door.	26
Figure 27. Test 4 long duration time history of pressure gauge mounted in vent.	27
Figure 28. Test 4 short duration time history of pressure gauge mounted in vent.	28
Figure 29. Test 4 impulse measured at the door.	29
Figure A-1. Engineering drawing of PCB 102M230 pressure gauge.	33
Figure A-2. Manufacturer's specification sheet for 102M230 pressure gauge.	34
Figure A-3. Engineering drawing of lead "pig" pressure transducer mount.	35
Figure A-4. Calibration sheet for pressure transducer mounted on door.	36
Figure A-5. Calibration sheet for pressure transducer mounted in vent.	37

List of Tables

Table 1. Experimental Facility 108 A/B blast study.	11
--	----

INTENTIONALLY LEFT BLANK.

1. Introduction

The Impact Physics Branch of the Terminal Effects Division of the Weapons and Materials Research Directorate (WMRD), U.S. Army Research Laboratory (ARL) was tasked by the Armor Mechanics Branch, WMRD, ARL, to perform blast measurements in ARL Experimental Facility 108 A/B. This memorandum report briefly summarizes the results of four blast tests that were conducted on 8 November 1999. The purpose of this test program was to measure the blast pressure exhibited on various walls of the experimental facility's chamber as a result of the detonation of various size spheres of Detasheet and to determine the maximum explosive weight that could be used in this facility without extensive modifications.

2. Test Setup

Hand-formed Detasheet spheres were detonated on top of a target table 57 in away from the entrance door of the chamber. Again, it should be noted that the Detasheet spheres used were handpacked and not cast, but they were considered adequate for the purpose of this study. An RP 87 detonator was used to detonate the explosive. The detonator was placed in the center of the explosive and was positioned facing toward the door of the chamber. This was done to ensure that the maximum pressure obtained by the detonation was aimed at the door and that the majority of the fragments from the detonator were propelled away from the pressure gauge mounted on the door. The door to the chamber is made of 1/2-in steel and has a 1/2-in bar stock locking pin, which is shown in Figures 1 and 2. Figure 3 shows a PCB 102M230 pressure gauge mounted into a lead "pig" pressure mount, which is attached to the chamber door facing the inside of the chamber. This pressure gauge was mounted so that it was in the direct line of sight of the explosive. The distance between the center of initiation and the pressure gauge was 72 in. (Figure A-1 in the Appendix shows a schematic of this pressure transducer. Figure A-2 lists the operating specifications of this transducer model. Figure A-3 is an engineering drawing of the lead pig pressure transducer mount.) A second PCB 102M230 pressure gauge in a lead pig mount was placed at the opening of a vent located on the sidewall of the chamber. This location was selected because the walls of the vent are constructed out of sheet metal. It was feared that this duct would be ruptured or severely damaged from the blast waves. The vent has a 1-ft² opening. Figure 4 shows the pressure gauge and lead pig mount at the entrance of the vent. (Calibration curves for both




Figure 1. Photograph of entrance to chamber showing locking mechanism and target stand.




Figure 2. Photograph of chamber showing locking mechanism and baffle opening.




Figure 3. Photograph of pressure gauge and mount clamped to entrance door.




Figure 4. Photograph of pressure gauge and mount at entrance to vent.

pressure transducers can be found in Figures A-4 and A-5.) Figure 5 shows the approximate layout of the chamber with dimensions. The approximate volume of the chamber is 669 ft³. The chamber has an additional baffle that can be opened. This baffle has a 107-ft² opening and is shown in Figures 2 and 6.

Two Lecroy LT344 500-MHz oscilloscopes were used to capture the data obtained in these tests (Figure 7). Data were sampled at 1 μ s per point for a duration of 190 ms. The 190-ms duration was used to enable the signal to return to baseline as much as possible, which gives us an idea of the venting rate for the chamber. Two plots for each signal are given in section 3. The first time history is a full-duration plot to show how the pressure levels change with time. The second time history plot is a short-duration plot of the initial pressure wave measured and the initial reflected waves that were seen shortly after. It should be noted that all of the measurements shown herein are reflected pressure. The impulse of the pressure measurements obtained on the door were calculated for the first blast wave that struck the door. Impulses from secondary reflections were not considered. In all, four blast tests were conducted.

Simplified Schematic of
Experimental Facility 108 A/B
Chamber




Figure 5. Schematic of Experimental Facility 108 A/B chamber.




Figure 6. Photograph of steel baffle door.




Figure 7. Photograph of data acquisition equipment.

3. Results

In test no. 1, a 10-g sphere of Detasheet was detonated. The 107-ft² steel baffle door was closed, which is shown in Figure 6. Time histories from the gauges are shown in Figures 8–11. Table 1 summarizes the peak pressures obtained in all of the tests. A maximum pressure of 10.1 psi was measured on the door with an impulse of 2.2E-3 psi · s. Figure 12 shows the impulse of the initial pressure wave striking the door of the chamber. A maximum pressure of 2.1 psi was measured at the entrance to the vent. No damage was done to the chamber.

In test no. 2, a 20-g sphere of Detasheet was detonated. Again, the baffle door was closed for this test. Time histories from the gauges are shown in Figures 13–16.

A maximum pressure of 14.1 psi was measured on the door with an impulse of 3.4E-3 psi · s. Figure 17 shows the impulse of the initial pressure wave striking the door of the chamber. A maximum pressure of 3.5 psi was measured at the entrance to the vent. No damage was done to the chamber.

In test no. 3, a 50-g sphere of Detasheet was detonated. The baffle door was open for this test. Time histories from the gauges are shown in Figures 18–21.

Experimental Facility 108 A/B Blast Tests, 11/8/99
Test # 1, Gauge # 12636, Mounted on Door




Figure 8. Test 1 long duration time history of pressure gauge mounted on door.

Experimental Facility 108 A/B Blast Tests, 11/8/99
Test # 1, Gauge # 12636, Mounted on Door




Figure 9. Test 1 short duration time history of pressure gauge mounted on door.

Experimental Facility 108 A/B Blast Tests, 11/8/99
Test 1, Gauge # 12638, Mounted in Vent




Figure 10. Test 1 long duration time history of pressure gauge mounted in vent.

Experimental Facility 108 A/B Blast Tests, 11/8/99
Test 1, Gauge # 12638, Mounted in Vent




Figure 11. Test 1 short duration time history of pressure gauge mounted in vent.

Table 1. Experimental Facility 108 A/B blast study.

Test No.	Explosive Weight (g)	Pressure on Door (psi)	Impulse on Door (psi · s)	Pressure in Vent (psi)
1	10	10.1	2.2E-3	2.1
2	20	14.1	3.4E-3	3.5
3	50	30.5	6.4E-3	5.4
4	35	24.2	4.8E-3	5.1

A maximum pressure of 30.5 psi was measured on the door with an impulse of 6.4E-3 psi · s. Figure 22 shows the impulse of the initial pressure wave striking the door of the chamber. A maximum pressure of 5.4 psi was measured at the entrance to the vent. In this test, the pin locking mechanism for the chamber door was severely bent as shown in Figures 23 and 24.

In test no. 4, a 35-g sphere of Detasheet was detonated. Again, the baffle door was open for this test. Time histories from the gauges are shown in Figures 25–28.

A maximum pressure of 14.1 psi was measured on the door with an impulse of 3.4E-3 psi · s. Figure 29 shows the impulse of the initial pressure wave striking the door of the chamber. A maximum pressure of 3.5 psi was measured at the entrance to the vent. In this test, a c-clamp was used to temporarily secure the chamber door. The c-clamp was knocked loose during the detonation, but no other damage was found in the chamber.

4. Conclusions

A maximum allowable explosive weight for this chamber should be less than 50 g of explosive unless modifications are made to the chamber door locking mechanism and other critical areas. No damage was seen at 35 g of explosive with the baffle open. The door should be secured with the locking mechanism instead of a c-clamp. Peak pressures at the vent were relatively low—especially the initial blast wave that was seen at the entrance to the vent. Over time, the peak pressure ramped up due to multiple reflections and the establishment of a quasi-static over pressure. The maximum pressure at the vent was 5.4 psi, but it should be noted that the vent is partially blocked by a steel interior door.

Experimental Facility 108 A/B Blast Tests, 11/8/99
Test # 1, Gauge # 12636, Mounted on Door




Figure 12. Test 1 impulse measured at the door.

Experimental Facility 108 A/B Blast Tests, 11/8/99
Test 2, Gauge # 12636, Mounted on Door




Figure 13. Test 2 long duration time history of pressure gauge mounted on door.

Experimental Facility 108 A/B Blast Tests, 11/8/99
Test # 2, Gauge # 12636, Mounted on Door




Figure 14. Test 2 short duration time history of pressure gauge mounted on door.

Experimental Facility 108 A/B Blast Tests, 11/8/99
Test # 2, Gauge # 12638, Mounted in Vent




Figure 15. Test 2 long duration time history of pressure gauge mounted in vent.

Experimental Facility 108 A/B Blast Tests, 11/8/99
Test # 2, Gauge # 12638, Mounted in Vent




Figure 16. Test 2 short duration time history of pressure gauge mounted in vent.

Experimental Facility 108 A/B Blast Tests, 11/8/99
Test # 2, Gauge # 12636, Mounted on Door




Figure 17. Test 2 impulse measured at the door.

Experimental Facility 108 A/B Blast Tests, 11/8/99
Test # 3, Gauge # 12636, Mounted on Door




Figure 18. Test 3 long duration time history of pressure gauge mounted on door.

Experimental Facility 108 A/B Blast Tests, 11/8/99
Test # 3, Gauge 12636, Mounted on Door




Figure 19. Test 3 short duration time history of pressure gauge mounted on door.

**Experimental Facility 108 A/B Blast Tests, 11/8/99
Test # 3, Gauge # 12638, Mounted in Vent**




Figure 20. Test 3 long duration time history of pressure gauge mounted in vent.

**Experimental Facility 108 A/B Blast Tests, 11/8/99
Test # 3, Gauge # 12638, Mounted in Vent**




Figure 21. Test 3 short duration time history of pressure gauge mounted in vent.

Experimental Facility 108 A/B Blast Tests, 11/8/99
Test # 3, Gauge 12636, Mounted on Door




Figure 22. Test 3 impulse measured at the door.




Figure 23. Photograph of door with damaged locking mechanism.




Figure 24. Close-up photograph of damaged locking mechanism.

Figure 5 shows the position of this door relative to the vent and explosive. No damage was seen in the vent during any of the tests but the vent was protected somewhat by the lead pig pressure mount and the interior door. Assuming this door is kept in the position shown in Figure 5, during most tests, the vent should be safe. However, it would be advisable to examine this vent to ensure that repeated use does not have a cumulative damage effect on its structural integrity. Once again, Table 1 summarizes all of the peak pressures and impulses measured in these tests.

**Experimental Facility 108 A/B Blast Tests, 11/8/99
Test # 4, Gauge 12636, Mounted on Door**




Figure 25. Test 4 long duration time history of pressure gauge mounted on door.

**Experimental Facility 108 A/B Blast Tests, 11/8/99
Test # 4, Gauge # 12636, Mounted on Door**




Figure 26. Test 4 short duration time history of pressure gauge mounted on door.

**Experimental Facility 108 A/B Blast Tests, 11/8/99
Test # 4, Gauge # 12638, Mounted in Vent**




Figure 27. Test 4 long duration time history of pressure gauge mounted in vent.

Experimental Facility 108 A/B Blast Tests, 11/8/99
Test # 4, Gauge # 12638, Mounted in Vent




Figure 28. Test 4 short duration time history of pressure gauge mounted in vent.

Experimental Facility 108 A/B Blast Tests, 11/8/99
Test # 4, Gauge # 12636, Mounted on Door




Figure 29. Test 4 impulse measured at the door.

INTENTIONALLY LEFT BLANK.

Appendix:
Transducer and Mount Specifications

INTENTIONALLY LEFT BLANK.




Figure A-1. Engineering drawing of PCB 102M230 pressure gauge.




Figure A-3. Engineering drawing of lead "pig" pressure transducer mount.



CALIBRATION CERTIFICATE

Model: 102M230
 Serial #: 12636
 Description: Pressure Sensor
 Type: ICP

Nat'l Freq: 500 kHz

Date: 5/4/99
 By: Tom Johnston, Cal. Tech. 70
 Station: Dead Weight #1

Sensitivity*: 5.133 mV/PSI
 Linearity*: 0.46% FS


Cert #: 32929

Bias: 9.9 VDC

* Zero based, least-squares straight line.

Notes:

- 1 Calibration is traceable to NIST and complies with ISO 10012-1 and former MIL-STD-45662A.
- 2 NIST traceability through project # 822/255136-95
- 3 This certificate may not be reproduced, except in full, without written approval.



TEST DATA

INPUT (PSI)	OUTPUT (mV)
20	103
40	203
60	310
80	413
100	511

PCB PIEZOTRONICS, INC.
 3425 Walden Avenue, Depew NY 14043
 Tel: 716-684-0001 Fax: 716-684-0987
 Email: sales@pcb.com Web: www.pcb.com

ISO 9001 CERTIFIED

Figure A-4. Calibration sheet for pressure transducer mounted on door.



CALIBRATION CERTIFICATE

Model: 102M230
Serial #: 12638 Nat'l Freq: 550 kHz Date: 5/4/99
Description: Pressure Sensor By: Tom Johnston, Cal. Tech.
Type: ICP Station: Dead Weight #1

Sensitivity*: 5.158 mV/PSI
Linearity*: 0.45% FS


Bias: 9.9 VDC

Cert #: 32937

* Zero based, least-squares straight line.

Notes:

- 1 Calibration is traceable to NIST and complies with ISO 10012-1 and former MIL-STD-45662A.
- 2 NIST traceability through project # 822/255136-95
- 3 This certificate may not be reproduced, except in full, without written approval.



TEST DATA

INPUT (PSI)	OUTPUT (mV)
20	101
40	204
60	310
80	415
100	515

PCB PIEZOTRONICS, INC.
3425 Walden Avenue, Depew NY 14043
Tel: 716-684-0001 Fax: 716-684-0987
Email: sales@pcb.com Web: www.pcb.com

ISO 9001 CERTIFIED

Figure A-5. Calibration sheet for pressure transducer mounted in vent.

INTENTIONALLY LEFT BLANK.

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>	<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
2	DEFENSE TECHNICAL INFORMATION CENTER DTIC DDA 8725 JOHN J KINGMAN RD STE 0944 FT BELVOIR VA 22060-6218	1	DIRECTOR US ARMY RESEARCH LAB AMSRL D D R SMITH 2800 POWDER MILL RD ADELPHI MD 20783-1197
1	HQDA DAMO FDT 400 ARMY PENTAGON WASHINGTON DC 20310-0460	1	DIRECTOR US ARMY RESEARCH LAB AMSRL DD 2800 POWDER MILL RD ADELPHI MD 20783-1197
1	OSD OUSD(A&T)/ODDDR&E(R) R J TREW THE PENTAGON WASHINGTON DC 20301-7100	1	DIRECTOR US ARMY RESEARCH LAB AMSRL CI AI R (RECORDS MGMT) 2800 POWDER MILL RD ADELPHI MD 20783-1145
1	DPTY CG FOR RDA US ARMY MATERIEL CMD AMCRDA 5001 EISENHOWER AVE ALEXANDRIA VA 22333-0001	3	DIRECTOR US ARMY RESEARCH LAB AMSRL CI LL 2800 POWDER MILL RD ADELPHI MD 20783-1145
1	INST FOR ADVNCD TCHNLGY THE UNIV OF TEXAS AT AUSTIN PO BOX 202797 AUSTIN TX 78720-2797	1	DIRECTOR US ARMY RESEARCH LAB AMSRL CI AP 2800 POWDER MILL RD ADELPHI MD 20783-1197
1	DARPA B KASPAR 3701 N FAIRFAX DR ARLINGTON VA 22203-1714		<u>ABERDEEN PROVING GROUND</u>
1	US MILITARY ACADEMY MATH SCI CTR OF EXCELLENCE MADN MATH MAJ HUBER THAYER HALL WEST POINT NY 10996-1786	4	DIR USARL AMSRL CI LP (BLDG 305)

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>	<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
1	HQDA DAMO FDQ DENNIS SCHMIDT 400 ARMY PENTAGON WASHINGTON DC 20310-0460	1	US MILITARY ACADEMY MATH SCI CTR OF EXCELLENCE DEPT OF MATH SCI MDN A MAJ D ENGEN THAYER HALL WEST POINT NY 10996-1786
1	DPTY ASSIST SCY FOR R&T SARD TT F MILTON RM 3EA79 THE PENTAGON WASHINGTON DC 20310-0103	1	DIRECTOR US ARMY RESEARCH LAB AMSRL CS AL TP 2800 POWDER MILL RD ADELPHI MD 20783-1145
1	OSD OUSD(A&T)/ODDDR&E(R) J LUPO THE PENTAGON WASHINGTON DC 20310-7100	1	DIRECTOR US ARMY RESEARCH LAB AMSRL CS AL TA 2800 POWDER MILL RD ADELPHI MD 20783-1145
1	CECOM SP & TRRSTRL COMMCTN DIV AMSEL RD ST MC M H SOICHER FT MONMOUTH NJ 07703-5203		
1	PRIN DPTY FOR TCHNLGY HQ US ARMY MATCOM AMCDCG T M FIFETTE 5001 EISENHOWER AVE ALEXANDRIA VA 22333-0001		<u>ABERDEEN PROVING GROUND</u>
1	DPTY CG FOR RDE HQ US ARMY MATCOM AMCRD BG BEAUCHAMP 5001 EISENHOWER AVE ALEXANDRIA VA 22333-0001	25	DIR USARL AMSRL WM CS IS PW MRS ABBOTT AMSRL WM CS IS RK MR SERRANO AMSRL SL BS MR BELY MR PETTY MR KUSS MR GROTE AMSRL WM T DR BURNS AMSRL WM TA MR GOOCH MR BURKINS (2 CPS) MR HAVEL
1	GPS JOINT PROG OFC DIR COL J CLAY 2435 VELA WAY STE 1613 LOS ANGELES AFB CA 90245-5500		
3	DARPA L STOTTS J PENNELA B KASPAR 3701 N FAIRFAX DR ALEXANDRIA VA 22203-1714		

NO. OF
COPIES ORGANIZATION

ABERDEEN PROVING GROUND

AMSRL WM TA
MR BRUCHEY
MR ZOLTOSKI
MR RUNYEON
MR PAXTON
MR LITTLE
AMSRL WM TB
DR FREY
MR WATSON
AMSRL WM TC
MR COATES
MR COPELAND
AMSRL WM TD
MR GREGORY (2 CPS)
MR GNIAZDOWSKI (2 CPS)
DR DIETRICH

INTENTIONALLY LEFT BLANK.

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project(0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)	2. REPORT DATE April 2001	3. REPORT TYPE AND DATES COVERED Final, 5-10 November 1999	
4. TITLE AND SUBTITLE ARL Experimental Facility 108 A/B Blast Tests – Summary Report		5. FUNDING NUMBERS IL162618AH80	
6. AUTHOR(S) Neil M. Gniazdowski			
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army Research Laboratory ATTN: AMSRL-WM-TD Aberdeen Proving Ground, MD 21005-5066		8. PERFORMING ORGANIZATION REPORT NUMBER ARL-MR-511	
9. SPONSORING/MONITORING AGENCY NAMES(S) AND ADDRESS(ES)		10. SPONSORING/MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES			
12a. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution is unlimited.		12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) The Impact Physics Branch of the Terminal Effects Division of the Weapons and Materials Research Directorate (WMRD), U.S. Army Research Laboratory (ARL), was tasked by the Armor Mechanics Branch, WMRD, ARL, to perform blast measurements in ARL Experimental Facility 108 A/B. This memorandum report briefly summarizes the results of four blast tests that were conducted on 8 November 1999. The purpose of this test program was to measure the blast pressure exhibited on various walls of the experimental facility's chamber (108A) as a result of the detonation of various size spheres of Detasheet and to determine the maximum explosive weight that could be used in this facility without extensive modifications.			
14. SUBJECT TERMS blast, pressure measurements, Experimental Facility 108 A/B		15. NUMBER OF PAGES 46	
		16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT UL

INTENTIONALLY LEFT BLANK.

USER EVALUATION SHEET/CHANGE OF ADDRESS

This Laboratory undertakes a continuing effort to improve the quality of the reports it publishes. Your comments/answers to the items/questions below will aid us in our efforts.

1. ARL Report Number/Author ARL-MR-511 (Gniazdowski) Date of Report April 2001

2. Date Report Received _____

3. Does this report satisfy a need? (Comment on purpose, related project, or other area of interest for which the report will be used.) _____

4. Specifically, how is the report being used? (Information source, design data, procedure, source of ideas, etc.) _____

5. Has the information in this report led to any quantitative savings as far as man-hours or dollars saved, operating costs avoided, or efficiencies achieved, etc? If so, please elaborate. _____

6. General Comments. What do you think should be changed to improve future reports? (Indicate changes to organization, technical content, format, etc.) _____

CURRENT
ADDRESS

Organization

Name

E-mail Name

Street or P.O. Box No.

City, State, Zip Code

7. If indicating a Change of Address or Address Correction, please provide the Current or Correct address above and the Old or Incorrect address below.

OLD
ADDRESS

Organization

Name

Street or P.O. Box No.

City, State, Zip Code

(Remove this sheet, fold as indicated, tape closed, and mail.)
(DO NOT STAPLE)


DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO 0001, APG, MD

POSTAGE WILL BE PAID BY ADDRESSEE

DIRECTOR
US ARMY RESEARCH LABORATORY
ATTN AMSRL WM TD
ABERDEEN PROVING GROUND MD 21005-5066



NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

