

REPORT DOCUMENTATION PAGE

AFRL-SR-BL-TR-01-

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing the data needed, and completing and reviewing this collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden to Washington Headquarters Services, Directorate for Information Operations and Reports (4302), and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

ling

0597

1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE 10/02/01	3. REPORT TYPE AND DATES COVERED Final Technical Report 9/1/99-2/28/01	
4. TITLE AND SUBTITLE (U) Computations of Droplet/Flow Interactions in Sprays			5. FUNDING NUMBERS PE-61103D PR-3484 SA-WS F49620-00-1-0124- F49620-99-1-0525	
6. AUTHOR(S) Gretar Tryggvason				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) University of Michigan Dept. of Mechanical Engineering 2031 Lay Automotive Lab. Ann Arbor, MI 48109-2121			8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) AFOSR/NA 801 North Randolph Street Room 732 Arlington, VA 22203-1977			10. SPONSORING / MONITORING AGENCY REPORT NUMBER 20011203 181	
11. SUPPLEMENTARY NOTES				
12a. DISTRIBUTION / AVAILABILITY STATEMENT Approved for public release; distribution is unlimited			DEPARTMENT OF SCIENTIFIC RESEARCH (AFOSR) DISTRIBUTION CODE UNCLASSIFIED AND IS APPROVED FOR PUBLIC RELEASE DISTRIBUTION IS UNLIMITED.	
13. ABSTRACT (Maximum 200 Words) The behavior of liquid fuel sprays was studied by direct numerical simulations. Two- and three-dimensional simulations were used to determine both the formation of drops and their interaction with the ambient flow. The Navier-Stokes equations were solved by a finite difference/front tracking technique that allowed resolution of inertial and viscous forces as well as the inclusion of surface tension at the deformable boundary between the fuel and the air. To examine the primary atomization and the formation of drops, several simulations of the breakup of sheared immiscible interfaces have been done. Two-dimensional simulations were used to examine the initial breakup and to establish the necessary numerical resolution. A three-dimensional code using cylindrical coordinates and local grid refinement has been used to examine how the initial two-dimensional instability becomes a fully three-dimensional "fiber" that eventually breaks up into drops.				
14. SUBJECT TERMS Atomization, Spray, Generation of drops			15. NUMBER OF PAGES 3	
			16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT Unclassified	18. SECURITY CLASSIFICATION OF THIS PAGE Unclassified	19. SECURITY CLASSIFICATION OF ABSTRACT Unclassified	20. LIMITATION OF ABSTRACT UL	

Final Report

~~F49620-00-1-0124~~

F49620-97-1-0525

The AASERT grant has supported the Ph.D. studies of Mr. Warren Tauber. Mr. Tauber is an excellent student and has done very well in his classes. He has given talks about his research at several meetings and co-authored one paper describing his results. Other papers are in preparation. However, Mr. Tauber has, suffered from health problems that have slowed down his progress. He seems to be over that now and did defended his thesis on September 7th 2001. The dissertation committee was unanimously in their opinion that Mr. Tauber had completed enough work to satisfy the degree requirement and he is currently writing his dissertation (funded as a teaching assistant).

Mr. Warren Tauber studies have focused on the atomization of a jet using direct numerical simulations using a front-tracking technique. Both two-dimensional and three-dimensional simulations of the Kelvin-Helmholtz instability of a small pie-shaped section of the jet are discussed. Unlike the Kelvin-Helmholtz instability for miscible fluids, where the sheared interface evolves into well-defined concentrate vortices if the Reynolds number is high enough, the presence of surface tension leads to the generation of folds that run parallel to the jet. While the initial growth rate is well predicted by inviscid theory, once the Reynolds numbers are sufficiently high, the large amplitude behavior is strongly affected by viscosity. Two-dimensional simulations were used to examine the initial breakup and to establish the necessary numerical resolution. A three-dimensional code using cylindrical coordinates and local grid refinement has been used to examine how the initial two-dimensional instability becomes a fully three-dimensional. These simulations have shown that initially axisymmetric waves on a jet will develop into narrow fingers that run parallel to the jet and eventually break into drops by a capillary instability. The axisymmetric waves are driven by the high shear between the jet and the ambient fluid. Eventually, viscous dissipation and separation of vorticity increases the thickness of the shear layer. The local shear becomes weaker and surface tension stops the waves from growing further. Three-dimensionality sets in as the axisymmetric waves start to retreat. Even though "fiber" breakup of jets takes place at relatively high Reynolds number, viscous effects appear to be critical for the generation of three-dimensional fibers.

Approved for public release;
distribution unlimited.

The work has been described in the following journal papers:

- W. Tauber; G. Tryggvason. Direct Numerical Simulations of Primary Breakup. *Computational Fluid Dynamics Journal*. vol.9 no.1, April 2000.
- W. Tauber, S.O. Unverdi, and G. Tryggvason. The nonlinear behavior of a sheared immiscible fluid interface. Submitted to *Phys. Fluids*
- W. Tauber and G. Tryggvason. Numerical Studies of Primary Atomization. Submitter to the International Journal of Multiphase Flow.