


NASA TECHNICAL
MEMORANDUM



NASA TM X-969

NASA TM X-969

B056182

AMPTIAC

DISTRIBUTION STATEMENT A
Approved for Public Release
Distribution Unlimited

NATIONAL ALTITUDE
ROCKET TEST FACILITIES

by Jack A. Suddreth
NASA Headquarters
Washington, D. C.

Reproduced From
Best Available Copy

20011210 061

56182

NATIONAL ALTITUDE ROCKET TEST FACILITIES

By Jack A. Suddreth

Office of Advanced Research and Technology
Washington, D. C.

NATIONAL AERONAUTICS AND SPACE ADMINISTRATION

For sale by the Office of Technical Services, Department of Commerce,
Washington, D.C. 20230 -- Price \$0.50

NATIONAL ALTITUDE ROCKET TEST FACILITIES

by Jack A. Suddreth

Office of Advanced Research and Technology

SUMMARY

The necessity for experimental verification of rocket-engine performance at altitude or near-space conditions has long been recognized in the aerospace industry. Recent spacecraft rocket-engine research and development trends toward higher area ratios, advanced nozzle concepts, and nonequilibrium flow considerations have made altitude simulation a requirement of development programs. Because the need for information regarding the capabilities and characteristics of altitude test facilities that are suitable for liquid-rocket-engine operation was recognized, this survey was compiled with the help of representatives of industry and government agencies. *end*

INTRODUCTION

The advent of upper-stage and spacecraft engine-vehicle development programs along with the need for more rigorous performance and reliability data justified the construction of a number of altitude test facilities. The test capabilities of these facilities range from small attitude-control engines to large upper-stage engines. The altitude-simulating systems include simple diffusers coupled to the engine nozzle exit (fig. 1), steam ejector coupled to the engine-driven diffuser (fig. 2), and pumped environmental chambers coupled to a diffuser or ejector system for use during engine firing (fig. 3). Several techniques for vacuum generation exist. In addition to the conventional systems of mechanical pumps and steam boilers for steam ejectors, there are semi-portable liquid-propellant-driven steam generators.

GENERAL COMMENTS

Certain facts must be kept in mind when using the information in this report:

(a) Tabular listing, which is convenient to use, cannot provide sufficient detail to describe a facility completely. Only the most basic characteristics of the facility are included in the tabulation.

(b) Modification and expansion of facilities is a continuous effort.

(c) Many existing facilities can be varied to provide a wide range of environment, propellant combination, exhaust pressure level, starting and shut-down transients, types of data, recording capability, and accuracy.

The various columns of table I are described more fully as follows:

Operator; Owner: The operator is the division and/or corporation having jurisdiction of the facility. The owner is the corporation and/or government agency owning the facility.

Stand: The code or popular name by which the stand is known.

Location: The community or geographical area where the stand is located.

Type: The type of propulsion system, liquid and/or solid, that can be tested in the cell. (Several factors including exhaust-gas composition, scrubber capability, and available propellant plumbing and storage can affect the type of system tested.) Any predominant capability for a liquid-propellant combination that exists in the facility has been noted.

Rated thrust; Simulated altitude: The thrusts and altitudes shown are typical of a particular installation and are provided for geometrical considerations as well as facility capability. In some cases, mass-flow limitations as well as altitude at no engine flow (start conditions) are provided. Thrust and altitude were chosen as the major parameters of interest instead of mass flow, vacuum, and other factors such as maximum area ratio and blockage; cooling of combustion products; exhaust-product flow limitations (free hydrogen, solids, water vapor, etc.). Lastly, comments regarding safety considerations for facility, personnel, or the surrounding community are not included.

Environment: The manner in which the engine is coupled to the facility, either by encapsulation or by direct connection at the nozzle exit.

Attitude: The direction of firing or installation within the facility.

Vacuum generation: The equipment available to generate and/or maintain a vacuum condition.

Status: The operational or planning status as of the summer of 1963.

SUMMARY OF RESULTS

The modern high-performance upper stage and spacecraft rocket-engine systems require extensive testing. The proof of reliability in addition to an accurate determination of space performance of propulsion systems has placed a severe demand on test facilities capable of simulating altitude conditions. Therefore, a survey was made in order to provide a tabulation of altitude facilities available for rocket engine testing.

COMMENT

Because it is recognized that this tabulation may be incomplete, comments, corrections, and additions are solicited so that it may be revised.

Office of Advanced Research and Technology
National Aeronautics and Space Administration
Washington, D. C., March 12, 1964

TABLE I. - NATIONAL ALTITUDE ROCKET TEST FACILITIES, SUMMER 1963

Owner	Stand	Location	Type	Rated thrust, lb	Simulated altitude, ft	Engine environment	Attitude	Vacuum generation	Status
Operator, Arnold Engineering Development Center (AEDC)a									
Air Force	RAC T-1	Tullahoma, Tenn.	Liquid or solid	20,000 (Max., 490 lb _m /sec)	120,000 - Run	Capsuled	Horizontal	Pump	Operational
	RAC T-3			20,000	140,000 - Run				
	RAC T-4			20,000 (Max., 490 lb _m /sec)	120,000 - Run				
	RAC T-5B			3,000 (Max., 490 lb _m /sec)	150,000 - Run				
	RAC J-2			60,000	120,000 - Run				
	RAC J-2A			20,000	140,000 - Run				
	SRC J-3		Liquid	100,000	350,000 - Start		Vertical		Operational 6/64
	VRC J-4			500,000	100,000 - Run		Vertical		Operational 6/64
	SRC J-5		Solid	100,000	120,000 - Run		Vertical		
Operator, Aerojet-General									
Air Force	C-2	Sacramento, Calif.	Liquid	100,000	70,000 - Run	Ambient	Horizontal	Diffuser	Operational
Air Force	C-3			100,000	160,000 - Start		Vertical	Pump and diffuser	
NASA	C-6			60,000	60,000 - Run		Vertical	Diffuser	
Air Force	E-5			200,000	160,000 - Start		Horizontal	Pump	
	G-6			100,000	70,000 - Run			Diffuser	
	G-7			5,000	60,000 - Run			Diffuser	
	H-3			100,000	60,000 - Run			Diffuser	
NASA	H-3 (Apollo)			21,000	60,000 - Run			Diffuser and plug	Operational 4/64
	H-4			60,000	60,000 - Run			Diffuser	Operational 5/64
	H-5			Unknown	60,000 - Run			Ejector	Operational 1/65
	J-2			1,500,000	90,000 - Start		Vertical	Pump and steam ejector	Proposal for 1/65
	J-2			1,500,000	70,000 - Start		Horizontal	Diffuser and steam ejector	Proposal for 1/65
Aerojet-General		Azusa, Calif.		1.0 nominal lb _m /sec (800 max.)	60,000	Capsuled		Steam ejector	Operational
Air Force	P-1	Sacramento, Calif.	Solid	80,000 max.	220,000 - Start	Ambient		Pump and diffuser	
Navy	W-7			80,000 max.	40,000 to 80,000 - Run			Pump and diffuser	
AGC	W-10			8,000	40,000 to 80,000 - Run			Pump and diffuser	
Air Force	T-2			Variable	40,000 to 80,000 - Run (Ignition conditions only)			Mechanical pump only	

Operator, Douglas Aircraft									
NASA	Stand A (6 engine) Stand 2B Beta Complex (A) Beta Complex (B)	Sacramento, Calif.	Liquid hydrogen and oxygen	15,000/engine 15,000/engine 20,000 20,000	53,000 - Start 46,000 - Run 53,000 - Start 46,000 - Run 53,000 - Start 46,000 - Run 53,000 - Start 46,000 - Run	Ambient	Vertical	Steam ejector and diffuser	Operational Operational fall-winter 1963 Operational early 1964
Operator, Edwards Air Force Base									
Air Force	Test Area 1-14 (Cell A) Modification of Cell A	Edwards AFB Edwards AFB	Liquid and solid Liquid and solid	500 (2.5 lb _m /sec) 4,000	100,000 100,000	Capsuled Capsuled	Horizontal Horizontal	Steam ejector and diffuser Steam ejector and diffuser	Operational (31 by 43 in. access door) Operational
Operator, General/Dynamics									
Air Force - General Dynamics/ Aeronautics	Centaur	Sycamore Canyon, Calif.	Liquid hydrogen and oxygen	15,000/engine	53,000 - Start 46,000 - Run	Ambient	Vertical	Ejector and diffuser	Operational
Operator, Pomona Division Ordnance Aerophysics Laboratory ^b									
Navy	4 ft diam. 10 ft diam. 15 ft diam.	Dairingerfield, Texas	Liquid and solid	20,000	120,000	Capsuled	Horizontal	Pump and steam ejector	Operational Operational Operational ^c
Operator, Jet Propulsion Laboratory									
NASA	"D" Stand	Edwards AFB	Liquid and solid	800 50	85,000 122,000	Capsuled	Horizontal	Hyprox ejector and diffuser (For Hyprox ejector alone at 225,000 lb _m /hr of steam)	Operational (5 by 5 ft access door)
Operator, Lockheed Aircraft Corporation, California Div.									
Lockheed	C-1 Propulsion Tunnel	Rye Canyon (near Burbank, Calif.) Rye Canyon	Solid	5,000 10,000	150,000 - Start	Capsuled	Horizontal or vertical	Pump Pump	Operational Operational

^aFor additional information, see Test Facilities Handbook, Arnold Engineering Development Center.

^bFor additional information, see Ordnance Aerophysics Laboratory Facility Handbook, General Dynamics - Pomona, Dairingerfield Division.

^cHigh-temperature inlet air at 1600° F and 300 lb/sq in. added in summer of 1963; inlet air at 1900° F and 1000 lb/sq in. available early 1965.

TABLE I. - Concluded. NATIONAL ALTITUDE ROCKET TEST FACILITY INVENTORY, APRIL 1963

Owner	Stand	Location	Type	Rated thrust, lb	Simulated altitude, ft	Engine environment	Attitude	Vacuum generation	Status
Operator, Marquardt Corporation ^d									
Air Force	AF-MJL-VN Cell 8	Van Nuys, Calif.	Liquid and solid	20,000	90,000	Ambient	Vertical	Pump, steam ejector, and diffuser	Operational
Air Force - NASA	Cell 6		Liquid	100	100,000	Ambient	Vertical	Steam ejector and diffuser	
Marquardt - Air Force - NASA	Aerothermo Lab (ATL-4 Cells) Rocket System Test Stand (20-in. diam. sphere)		Liquid and solid	230	160,000	Capsuled	Any direction		
Marquardt - NASA	North Test Area (Short Pulse)			25	400,000	Ambient	Horizontal	Diffusion and mechanical pump	
Marquardt - Air Force	Cell 2 (Minor Mod)			20,000	90,000	Ambient		Pump and steam ejector or diffuser	
Marquardt - Air Force	Research Field Lab (RFL) 1 and 2	Saugus, Calif.		500	140,000			Steam ejector and diffuser	
Air Force	AF-MJL-O	Ogden, Utah		20,000	90,000			Pump, steam ejector, and diffuser	Idle
Operator, NASA Lewis Research Center									
NASA	PSL 1	Cleveland, Ohio	Liquid hydrogen and oxygen	15,000	100,000 - Start 75,000 - Run	Capsuled	Horizontal	Pump	Operational
	PSL 2		Liquid and solid	15,000	100,000 - Start 75,000 - Run		Horizontal and vertical		
	8 by 6 Foot Supersonic Wind Tunnel			2,000	35,000 - Run		Horizontal		Proposed
	10 by 10 Foot Supersonic Wind Tunnel B-1	Plum Brook (near Sandusky, Ohio)		4,000	50,000 - Run				Operational 1/65
	B-2		Liquid hydrogen and oxygen	45,000	150,000 - Run 10 ⁻⁵ (in. Hg) - Start			Diffusion pump, steam ejector, and diffuser	Proposed
	B-3								Proposed
Operator, NASA Marshall Space Flight Center									
NASA	LHTS	Huntsville, Ala.	Liquid hydrogen and oxygen	15,000	46,000 - Run	Capsuled	Horizontal	Steam ejector and diffuser	Operational
	Vacuum chamber	Huntsville, Ala.	Liquid and solid	To 5,000	120,000 - Start	Capsuled	Horizontal or vertical	Mechanical pump	Operational

Operator, NASA Manned Spacecraft Center						
NASA	Undesignated	Clear Lake, Tex.	Liquid	2,000 to 5,000	46,000 - Run	Operational complete fall 1964
Operator, Pratt & Whitney Aircraft Company, Florida Research & Development Div.						
NASA	E-1 E-2 E-3 E-4 E-5 Dual Engine Stand E-6 E-7 E-8	West Palm Beach, Fla.	Liquid hydrogen and oxygen	15,000	53,000 - Start 46,000 - Run 53,000 - Start 46,000 - Run 53,000 - Start 46,000 - Run 53,000 - Start 46,000 - Run 15,000/engine	Operational
Pratt & Whitney	Undesignated Area 10K Bay		Liquid hydrogen and fluorine		Ambient Capsuled Capsuled Ambient Ambient	Operational
Operator, Rocketdyne Division of North American Aviation, Inc.						
NASA	VTS-3A	Santa Susanna, Calif.	Liquid hydrogen and oxygen	200,000	60,000 - Start 90,000 - Run	Operational
NASA	Delta-2A			200,000	60,000 - Start 90,000 - Run 110,000 - Start 130,000 - Run	Operational
Air Force	CTL-3 28B CTL-3 28C			100 25		Ejector and diffuser Ejector Diffuser and ejector
	CTL-39 CTL-4 35A			300 50	100,000 - Run 150,000 - Start 110,000 - Run 130,000 - Start	All Ejector Horizontal Pump, diffuser, and ejector Horizontal Ejector Horizontal ejector
	CTL-4 35B			100	150,000 - Run	Pump, diffuser, and ejector
	CTL-4 37			300	80,000 - Start 120,000 - Run	All Ejector
	CTL-4 38			100	100,000 - Start 100,000 - Run	All Ejector
Rocketdyne	Undesignated	Reno, Nev.		Similar to CTL-3 stands	100,000 - Run (nominal)	Ejector and diffuser Ejector and diffuser Ejector Ejector
Operator, Thiokol Chemical Corporation						
Navy	Undesignated	Elkton, Md.	Solid	20,000	100,000 - Start 70,000 - Run	Operational
	Stand 10B	Lake Denmark, Denville, N.J.	Liquid and solid	20,000	250,000 - Start 120,000 - Run	Hyprox ejector and diffuser 250,000 lb/hr Hyprox ejector and diffuser 140,000 lb/hr
	Stand 10B-1	Lake Denmark, Denville, N.J.	Liquid and solid	1,000 Max.	100,000	Ejector and diffuser

Several other cells have altitude capability with minor modification.




Figure 1. - Simple diffuser providing only altitude simulation at nozzle exit during firing.




Figure 2 - Steam ejector and diffuser with an encapsulated engine providing altitude ignition with altitude environment before and during engine operation.




Figure 3. - Environmental chambers for long term space simulation with high altitude simulation at ignition and altitude simulation during engine runs. (AEDC-Cell J-2A)

NASA TM X-969
National Aeronautics and Space Administration.
NATIONAL ALTITUDE ROCKET TEST FACILITIES.
Jack A. Suddreth. June 1964. 10p. OTS price,
\$0.50. (NASA TECHNICAL MEMORANDUM X-969)

A tabular inventory of altitude test facilities available for testing rocket engines is provided. Included in the listing are ownership, contractual operator if applicable, code name of stand, geographic location, propulsion system type, nominal thrust level and operating altitude, engine operating environment, firing attitude, vacuum generation system, and status in summer of 1963.

I. Suddreth, Jack A.
II. NASA TM X-969

NASA

NASA TM X-969
National Aeronautics and Space Administration.
NATIONAL ALTITUDE ROCKET TEST FACILITIES.
Jack A. Suddreth. June 1964. 10p. OTS price,
\$0.50. (NASA TECHNICAL MEMORANDUM X-969)

A tabular inventory of altitude test facilities available for testing rocket engines is provided. Included in the listing are ownership, contractual operator if applicable, code name of stand, geographic location, propulsion system type, nominal thrust level and operating altitude, engine operating environment, firing attitude, vacuum generation system, and status in summer of 1963.

I. Suddreth, Jack A.
II. NASA TM X-969

NASA

NASA TM X-969
National Aeronautics and Space Administration.
NATIONAL ALTITUDE ROCKET TEST FACILITIES.
Jack A. Suddreth. June 1964. 10p. OTS price,
\$0.50. (NASA TECHNICAL MEMORANDUM X-969)

A tabular inventory of altitude test facilities available for testing rocket engines is provided. Included in the listing are ownership, contractual operator if applicable, code name of stand, geographic location, propulsion system type, nominal thrust level and operating altitude, engine operating environment, firing attitude, vacuum generation system, and status in summer of 1963.

I. Suddreth, Jack A.
II. NASA TM X-969

NASA

NASA TM X-969
National Aeronautics and Space Administration.
NATIONAL ALTITUDE ROCKET TEST FACILITIES.
Jack A. Suddreth. June 1964. 10p. OTS price,
\$0.50. (NASA TECHNICAL MEMORANDUM X-969)

A tabular inventory of altitude test facilities available for testing rocket engines is provided. Included in the listing are ownership, contractual operator if applicable, code name of stand, geographic location, propulsion system type, nominal thrust level and operating altitude, engine operating environment, firing attitude, vacuum generation system, and status in summer of 1963.

I. Suddreth, Jack A.
II. NASA TM X-969

NASA

"The aeronautical and space activities of the United States shall be conducted so as to contribute . . . to the expansion of human knowledge of phenomena in the atmosphere and space. The Administration shall provide for the widest practicable and appropriate dissemination of information concerning its activities and the results thereof."

—NATIONAL AERONAUTICS AND SPACE ACT OF 1958

NASA SCIENTIFIC AND TECHNICAL PUBLICATIONS

TECHNICAL REPORTS: Scientific and technical information considered important, complete, and a lasting contribution to existing knowledge.

TECHNICAL NOTES: Information less broad in scope but nevertheless of importance as a contribution to existing knowledge.

TECHNICAL MEMORANDUMS: Information receiving limited distribution because of preliminary data, security classification, or other reasons.

CONTRACTOR REPORTS: Technical information generated in connection with a NASA contract or grant and released under NASA auspices.

TECHNICAL TRANSLATIONS: Information published in a foreign language considered to merit NASA distribution in English.

TECHNICAL REPRINTS: Information derived from NASA activities and initially published in the form of journal articles.

SPECIAL PUBLICATIONS: Information derived from or of value to NASA activities but not necessarily reporting the results of individual NASA-programmed scientific efforts. Publications include conference proceedings, monographs, data compilations, handbooks, sourcebooks, and special bibliographies.

Details on the availability of these publications may be obtained from:

SCIENTIFIC AND TECHNICAL INFORMATION DIVISION
NATIONAL AERONAUTICS AND SPACE ADMINISTRATION
Washington, D.C. 20546