

REPORT DOCUMENTATION PAGE

Form Approved
OMB NO. 0704-0188

Public Reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comment regarding this burden estimates or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave Blank)		2. REPORT DATE 05/12/01	3. REPORT TYPE AND DATES COVERED <i>74998 to 7101 Final 10 Jul 98 - 09 Jul 01</i>	
4. TITLE AND SUBTITLE An Acoustic Parametric Effect MEMS Amplifier/Transducer for Sonar Applications			5. FUNDING NUMBERS 38962EL DAAG55-98-1-0432	
6. AUTHOR(S) Gabriel M. Rebeiz				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) University of Michigan 1301 Beal Ave, EECS Department, Ann Arbor, MI 48109-2122			8. PERFORMING ORGANIZATION REPORT NUMBER RadLab 03729Dec01	
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) U. S. Army Research Office P.O. Box 12211 Research Triangle Park, NC 27709-2211			10. SPONSORING / MONITORING AGENCY REPORT NUMBER <i>38962.2-EL</i>	
11. SUPPLEMENTARY NOTES The views, opinions and/or findings contained in this report are those of the author(s) and should not be construed as an official Department of the Army position, policy or decision, unless so designated by other documentation.				
12 a. DISTRIBUTION / AVAILABILITY STATEMENT Approved for public release; distribution unlimited.			12 b. DISTRIBUTION CODE Unlimited	
13. ABSTRACT (Maximum 200 words) We have developed the first MEMS parametric amplifier for Sonar applications. The device used is a MEMS time-varying capacitor which is composed of an array of low-stress metallized silicon-nitride diaphragms, and is pumped by a large signal voltage at 1.64 MHz. This induces a large change in the capacitance, and results in parametric amplification of an input signal at 200 kHz. To our knowledge, this device is the first-ever MEMS mechanical up-converter parametric-effect amplifier developed with an up-conversion ratio of 9:1. The measurements agree very well with theory, including the effect the series resistance and the Q of the MEMS time-varying capacitor. The application areas are in amplifiers which operate at very high temperatures (200-600C), under high particle bombardment (nuclear applications), in non semiconductor-based amplification, and in low-noise systems since parametric amplifiers do not suffer from thermal, shot or $1/f$ noise problems.				
14. SUBJECT TERMS MEMS, Parametric Amplifiers, Transducers, Sonar, Low Noise			15. NUMBER OF PAGES 1	
			16. PRICE CODE	
17. SECURITY CLASSIFICATION OR REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION ON THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT UL	

NSN 7540-01-280-5500

Standard Form 298 (Rev.2-89)
Prescribed by ANSI Std. Z39-18
298-102

20020201 144

MASTER COPY: PLEASE KEEP THIS "MEMORANDUM OF TRANSMITTAL" BLANK FOR REPRODUCTION PURPOSES. WHEN REPORTS ARE GENERATED UNDER THE ARO SPONSORSHIP, FORWARD A COMPLETED COPY OF THIS FORM WITH EACH REPORT SHIPMENT TO THE ARO. THIS WILL ASSURE PROPER IDENTIFICATION. NOT TO BE USED FOR INTERIM PROGRESS REPORTS; SEE PAGE 2 FOR INTERIM PROGRESS REPORT INSTRUCTIONS.

MEMORANDUM OF TRANSMITTAL

U.S. Army Research Office
ATTN: AMSRL-RO-BI (TR)
P.O. Box 12211
Research Triangle Park, NC 27709-2211

- | | |
|---|---|
| <input checked="" type="checkbox"/> Reprint (Orig + 2 copies) | <input type="checkbox"/> Technical Report (Orig + 2 copies) |
| <input type="checkbox"/> Manuscript (1 copy) | <input checked="" type="checkbox"/> Final Progress Report (Orig + 2 copies) |
| | <input type="checkbox"/> Related Materials, Abstracts, Theses (1 copy) |

CONTRACT/GRANT NUMBER: DAAG55-98-1-0432

REPORT TITLE: An Acoustic Parametric Effect MEMS Amplifier/Transducer for Sonar Applications

is forwarded for your information.

SUBMITTED FOR PUBLICATION TO (applicable only if report is manuscript):

Sincerely,

Gabriel M. Rebeiz
Professor, EECS Department
Univ. of Michigan, Ann Arbor
rebeiz@umich.edu

REPORT DOCUMENTATION PAGE (SF298)
(Continuation Sheet)

Accomplishments:

We have developed the first MEMS parametric amplifier for Sonar applications. The device used is a MEMS time-varying capacitor which is composed of an array of low-stress metalized silicon-nitride diaphragms, and is pumped by a large signal voltage at 1.64 MHz. This induces a large change in the capacitance, and results in parametric amplification of an input signal at 200 kHz. To our knowledge, this device is the first-ever MEMS mechanical up-converter parametric-effect amplifier developed with an up-conversion ratio of 9:1. The measurements agree very well with theory, including the effect the series resistance and the Q of the MEMS time-varying capacitor. The application areas are in amplifiers which operate at very high temperatures (200-600C), under high particle bombardment (nuclear applications), in non semiconductor-based amplification, and in low-noise systems since parametric amplifiers do not suffer from thermal, shot or $1/f$ noise problems.

Publications:

J.P. Raskin, A.R. Brown, B.T. Yakub and G.M. Rebeiz, "A novel parametric-effect MEMS amplifier," *IEEE Trans. Micro. Electro. Mechanical Systems*, Vol. 9, pp. 528-537, Dec. 2000.

J.P. Raskin, A.R. Brown, B.T. Khuri-Yakub and G.M. Rebeiz, "Novel parametric-effect MEMS amplifiers/transducers," *Transducers 2000*, Hilton Head, June 2000.

Post-Doctoral Personnel Supported:

Jean-Pierre Raskin
Andrew Brown