

DATA ANALYSIS OF IBSS AND CIRRIIS-1A DATA COLLECTED DURING STS-39

Cynthia Beeler

Visidyne
10 Corporate Place
South Bedford Street
Burlington, MA 01803

7 October 1997

Final Report

APPROVED FOR PUBLIC RELEASE; DISTRIBUTION IS UNLIMITED.

20020524 109



AIR FORCE RESEARCH LABORATORY
Space Vehicles Directorate
29 Randolph Road
AIR FORCE MATERIEL COMMAND
HANSCOM AFB MA 01731-3010

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188	
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.				
1. AGENCY USE ONLY (Leave blank)	2. REPORT DATE 7 October 1997	3. REPORT TYPE AND DATES COVERED FINAL REPORT (SUMMARY)		
4. TITLE AND SUBTITLE Data Analysis of IBSS and CIRRIS-1A Data Collected During STS-39			5. FUNDING NUMBERS PE: 63215C PR: S321 TA: GG WU: AG Contract No: F19628-93-C-0055	
6. AUTHOR(S) Cynthia Beeler				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Visidyne 10 Corporate Place South Bedford Street Burlington, MA 01803			8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) Air Force Research Laboratory 29 Randolph Road Hanscom AFB MA 01731-3010 Contract Manager: John Wise/VSBC			10. SPONSORING/MONITORING AGENCY REPORT NUMBER AFRL-VS-TR-2002-1551	
11. SUPPLEMENTARY NOTES				
12a. DISTRIBUTION AVAILABILITY STATEMENT Approved for Public Release; Distribution Unlimited			12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) Performed data analysis on the IBSS (Infrared Background Signature Survey) and CIRRIS-1A (Cryogenic Infrared Radiance Instrumentation for Shuttle) data collected during the space shuttle mission STS-39 in the spring of 1991. Analysis of these data included filter waveband studies, construction of two-dimensional imagery from pushbroom scans, Fourier Transform analysis Wavelet Transform analysis, and other statistical estimations to examine the spatial structure content of the radiometric data.				
14. SUBJECT TERMS IBSS Fourier transform analysis CIRRIS-1A MODTRAN STS-39			15. NUMBER OF PAGES	
			16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT SAR	



10 Corporate Place • South Bedford Street • Burlington, MA 01803 • (617) 273-2820 • Fax: (617) 272-1068

VI-3216

9 October 1997

Letter Final Report

Dr. John O. Wise
Phillips Laboratory
29 Randolph Road
Hanscom AFB, MA 01731-3010

Dear Dr. Wise:

This letter final report is respectfully submitted to satisfy the requirements of contract F19628-93-C-0055. The contract was active during the period May 1993 to March 1997 and was funded for a total of \$1,550,566. As a result of funding limitations, the government descope the contract by \$1.3 million in March 1997, revised the contract completion date, and authorized a final letter report.

Early in this contract we performed data analysis on the IBSS (Infrared Background Signature Survey) and CIRRI-1A (Cryogenic Infrared Radiance Instrumentation for Shuttle) data collected during the space shuttle mission STS-39 in the spring of 1991. Analysis of these data included filter waveband studies, construction of two-dimensional imagery from pushbroom scans, Fourier Transform analysis, Wavelet Transform analysis, and other statistical estimations to examine the spatial structure content of the radiometric data.

Conclusions drawn from the IBSS 4.3 μ m background structure data required taking into consideration the filter spectral response in order to ensure the proper application to the development of structure models or future sensors. Estimates of the MODTRAN radiance integrated over the remeasured 4.3 μ m IBSS filter transmission curves indicated that the narrow filter (5E) had radiance contributions from the blue side (below 4.2 μ m) of 10-17% and contributions from the red side (above 4.35 μ m) of 3-5%. Also, the wider filter (2D) had substantial integrated radiance from both the blue and red edges near 4.3 μ m. A comparison of the Earthscan radiance measurements with MODTRAN estimates showed agreement for the wider (2D) filter and a discrepancy of approximately 50% for the more narrow (5E) filter.

We constructed representative samples of MWIR strip images of BTH and Earth limb scenes. By analyzing the BTH scenes with a conventional PSD and Morlet Wavelet transform, we established the existence of significant non-stationary spatial structure on all scales down to ~1 km; the overall rms variations about the mean were approximately 5×10^{-7} Watts/cm²-str (or ~15% of the mean).

Statistically significant spatial structure was also detected with both the wide and narrow IBSS 4.3 μ m filters in the Earth's limb with rms variations of approximately 3×10^{-8} Watts/cm²-str (~2% rms variations about the mean). This structure had a quasi-monochromatic appearance which was further

quantified in the two-dimensional PSD analysis of these scenes. The characteristic angles ($\sim 20^\circ$) and vertical wavelengths (~ 16 km) of these features were highly suggestive of gravity waves.

Other activities during the earlier period of this contract included experiment and spectral filter design for the SPAS III Program (Shuttle Palette Satellite). Our experience drawn from the spectral analyses performed in the IBSS and CIRRIS 1A data analysis activities was very valuable for this task. We performed simulations using output from the atmospheric codes (MODTRAN and SHARC) with models of the proposed spectral filters. From the results of these simulations, we could evaluate the performance of the candidate filters and modify the passbands as required. The objective of the set of filters was to experimentally determine the structure dependence on wavelength by varying the red side of the 2.7 and 4.3 micron regions while holding the blue side close to constant.

The major focus of the work effort on this contract was the SPAS III data analysis, for which Visidyne designed and built a software package we called SPASware. This software was an interactive data analysis tool which incorporated many of the analysis algorithms that were written as part of the IBSS/CIRRIS-1A activities as well as some new algorithms designed specifically for SPAS III. Some of the algorithms used for previous data analysis programs had to be modified for specific use on SPAS-like data. The SPAS sensor was very different from those of either IBSS or CIRRIS in that it was a staring focal plane array (256×256) as opposed to the detector-array sensors on IBSS and CIRRIS that had to be used in a pushbroom scanning fashion in order to build up a data "image".

SPASware was constructed with a very user-friendly GUI and its focus was geared toward in-depth analysis of a very manageable, limited dataset. We quickly saw the need for a different type of analysis tool; one that could handle large volumes of data and operate in a semi, if not, fully automated manner. We started with the algorithms in SPASware, improved on and added to them based on the changing needs of the backgrounds community and the SBIRS office, and developed the Automated Software Analyzer and Processor (ASAP).

The ASAP software, as its name suggests, was designed to operate in an automated manner, and it has proven to be extremely robust, efficient, and reliable in its performance. It was engineered to be highly modularized for maximum flexibility and to minimize maintenance requirements. ASAP is extremely fault-tolerant in that it includes a very effective error handling and logging mechanism which allows automatic processing to continue even upon failure of an individual image or analysis routine. This feature is essential to the success of a high-volume data processing assignment, as one could not permit prolonged interruption of program execution, nor would one be able to debug problems without an error logging system.

Most of the ASAP algorithms were programmed in IDL (Interactive Data Language) which is a commercially available programming language for use on VMS, UNIX, or PC systems. The Visidyne software was developed on a UNIX system. ASAP's output data products are written as a variable length byte stream. There is a short header (variable length) at the beginning of each data product file which describes the contents and structure of that file. The data output format is fully documented, and is accompanied by readers written in both IDL and C languages.

Examples of the ASAP data products are: minimum, maximum, mean, and median radiances, standard deviation, skewness, and kurtosis of original, gradient, and sigma images; N^{th} percentile radiance values of gradient images; spectral correlation coefficients and slopes; power spectral density (PSD) slopes, and correlation lengths. ASAP also performs a significant amount of geometric computation to aid in the statistical analysis. For example, ASAP computes the angle with which the


camera axes are oriented with respect to the Earth's horizon so that the individual images can be rotated to be aligned with that horizon prior to analysis. In addition, many of the analyses require two images to be co-registered on a pixel by pixel basis; ASAP performs the two necessary forms of co-registration, i.e., below-the-horizon (BTH), requiring reprojection of both images onto a common latitude/longitude grid, and above-the-horizon (ATH) requiring rotation and translation of one image (in camera space) with respect to the other.

The ASAP software also includes a module that constructs mosaic scenes by "stitching" together continuous, overlapping sub-images. This is accomplished using the pointing information available in the data headers. The projection that we have implemented in our LMS ASAP software puts the mosaic into the tangent plane of a sensor located at an arbitrary location in space, viewing the scene (in a single exposure) with a camera of arbitrary angular resolution and field of regard. We chose this type of projection for several reasons, the most important of which is that out of all possible projections, it most accurately mimics a scene which could have been collected by a sensor with a very large field of regard. In our processing of the large mosaic scenes, the algorithm places the "LMS sensor" at approximately 435 km altitude and at the location of the collecting sensor at approximately the center of the satellite track during the LMS data collection event. We set the angular resolution of the LMS to be approximately 200 μ rad.

The LMS ASAP process consists of four steps: defining the axes of the tangent plane coordinate system, transforming the "tie points" of each of the sub-images from the original coordinate system to the new coordinate system, reprojecting the sub-images, and approximately averaging the regions of overlap between adjacent sub-images in the mosaic. The software has proven to work extremely well.

Other activities during this contract have included documentation of both SPASware and ASAP, their algorithms, outputs, and formats. We wrote and presented several papers to the IRIS TBD meetings, and IEEE Aerospace meetings. We also participated in many Background Working Group, Data Review, and Calibration Meetings, and provided support to the SBIRS PEP and other higher level meetings in the form of briefing materials.

Sincerely,



Cynthia Beeler

cc: Alfred Parino
fax: (617) 753-4169