

A progress report on the estimation of geoacoustic parameters from measured time series taken during the East China Sea component of ASIAEX

D. P. Knobles and T. W. Yudichak

Applied Research Laboratories, The University of Texas at Austin

P. G. Cable and Y. Dorfman

BBN Technologies

ASIAEX Collaborators:

R. Zhang, Z. Peng, F. Li, Z. Li (IOA, Chinese Academy of Sciences)

Ji-Xun Zhou (GT)

P.H. Dahl (APL-UW)

J.H. Miller, G.R. Potty (URI)

Prepared for ASIAEX Analysis International Symposium October 14-18 Chengdu, China

Report Documentation Page				Form Approved OMB No. 0704-0188	
Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.					
1. REPORT DATE 01 DEC 2002		2. REPORT TYPE N/A		3. DATES COVERED -	
4. TITLE AND SUBTITLE A Progress Report on the Estimation of Geoacoustic Parameters from Measured Time Series Taken During the East China Sea Component of ASIAEX				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S)				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Applied Research Lab., The University of Texas at Austin, BBN Technologies, and ASIAEX Collaborators				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release, distribution unlimited					
13. SUPPLEMENTARY NOTES Also See: M001452, The original document contains color images.					
14. ABSTRACT					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT UU	18. NUMBER OF PAGES 20	19a. NAME OF RESPONSIBLE PERSON
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified			

OUTLINE

- I. Modeling of forward transmission data
- II. Comparisons to analyses of previous experiments
- III. Summary and future work

Issues and Objectives


Extract information on physics of low-frequency scattering from seabed


Use acoustic forward transmission data to establish average geoacoustic structure

Employ this information in the scattering equations to invert for the scattering potential of the seabed using reverberation data.


What features in the forward data allow for extraction of sound speed and attenuation structure?

ARL Analysis and Inversion Methodology






Comparison of measured and modeled time series data on the
APL/URI VLA. Range = 16.94 km, source depth = 55 m



Comparison of measured and modeled magnitude of spectra for a single phone on VLA in East China Sea measurements. Source-receiver range = 16.94 km. Source depth 55 m. Source spectra from Chapman-Wakely model convolved with modeled frequency response in 50-350 Hz band. Modeled frequency response made with ORCA normal mode model.

Depth - m	Compressional Speed - m/s	Density - g/cc	Attenuation db/m-kHz	Frequency Exponent	
0.0	1640.0	1.76	0.45	1.8	Sand
7.6	1664.9	1.76	0.45	1.8	
7.6	1839.8	1.9	0.27	1.0	Sand-Gravel
95.5	1918.1	1.9	0.27	1.0	
95.5	3000.0	2.5	0.02	1.0	Basement

Current Estimated Geoacoustic Profile
 in ECS basin from data analysis



Comparison of modeled TL using the ECS geoacoustic profile to m
TL taken at 29 05 N 126 43 E.

Estimated sound speed structure of upper 10 m of sediment describes relative arrival times of main multipath arrivals and general time spread characteristics as a function of range. Arrivals demonstrate critical angle effect at the water sediment interface.

A top sediment sound speed of 1640 m/s with a high sound speed depth gradient appears to be the key structure of the geoacoustic profile. Analysis, however, may have slightly overestimated sound speed because of incorrect water depth.

Very difficult to establish precise sediment thickness from time series data.

Comparisons of geoacoustic profiles in ECS region

East China Sea basin Yellow Sea basin Southern Strait of Korea*

Depth - m	Compressional Speed - m/s	Density - g/cc	Attenuation db/m-kHz	Frequency Exponent
0.0 0.0 0.0	1640.0 1644.7 1629.0	1.76 1.72 1.88	0.45 0.89 0.28	1.8 2.0 1.8
7.62 5.96 10.0	1664.9 1650.4 1644.0	1.76 1.72 1.88	0.45 0.94 0.30	1.8 2.0 1.8
7.62 5.96 10.0	1839.8 1725.3 1760.0	1.9 1.8 1.95	0.27 0.47 0.15	1.0 1.3 1.8
95.48 131.9 132.0	1918.1 1848.9 1761.0	1.9 1.8 1.95	0.27 1.0 0.15	1.0 1.3 1.8
95.48 131.1 132.0	3000.0 3000.0 2200.0	2.5 2.5 2.2	0.02 0.02 0.02	1.0 1.0 1.0

Geoacoustic Models for ECS and YS basins and SOK
Obtained From Analysis and Inversion of TL and
Time Series Data.

* Rozenfeld et al IEEE JOE
* * Knobles et al

Summary

An approximate geoacoustic description has been established for ECS
Consistent with previous geophysical measurements.

Key characteristics of both forward time series and
transmission loss measurements are reproduced by range-independent

Geoacoustic model used in analysis of scattering data.

Uniqueness of attenuation and layering structure in seabed difficult to es

Elastic description may be required for consistent picture
of seabed acoustics.

Modeling of ASIAEX Reverberation

Research in progress

Sources of Reverberation


Surface Scattering

$$z_{\text{int}} = H + z(r, q)$$

Volume Scattering

$$c_{\text{sed}} = c_s(z)[1 + m(r, q, z)]$$

$$r_{\text{sed}} = r_s(z)[1 + h(r, q, z)]$$



Model Assumptions

- Density fluctuations proportional to sound speed fluctuations: $h(\mathbf{r}) = 2gm(\mathbf{r})$
 - Sound speed fluctuations small: $|m(\mathbf{r})| \ll 1$
- Water sediment interface nearly flat, slightly rough:
 $|k_0 z(\mathbf{r})| \ll 1 \quad |\nabla_{\parallel} z(\mathbf{r})| \ll 1$
- Perturbation approximation: keep only first order terms in above small quantities

Equation for Scattered Field

$$p_{scat}(\mathbf{r}) = -\frac{1}{4p} \left\{ \begin{aligned} & \int_V (2g + 2)m(\mathbf{r}')k_0^2(z')[G_0(\mathbf{r};\mathbf{r}')G(\mathbf{r}';\mathbf{r}_0)]dV' \\ & - \int_V (2g)m(\mathbf{r}')[\nabla' G_0(\mathbf{r};\mathbf{r}') \cdot \nabla' G(\mathbf{r}';\mathbf{r}_0)]dV' \\ & + \int_S (2g)m(\mathbf{r}'_-) \left[G_0(\mathbf{r};\mathbf{r}'_+) \frac{\partial G}{\partial z'}(\mathbf{r}'_+;\mathbf{r}_0) \right] dA' \\ & + \int_S z(\mathbf{r}') \left(1 - \frac{r_w}{r_s} \right) [\nabla'_{\parallel} G_0(\mathbf{r};\mathbf{r}'_+) \cdot \nabla'_{\parallel} G(\mathbf{r}'_+;\mathbf{r}_0)] dA' \\ & - \int_S z(\mathbf{r}') w^2 \left(\frac{1}{c_w^2} - \frac{r_w}{r_s c_s^2} \right) [G_0(\mathbf{r};\mathbf{r}'_+)G(\mathbf{r}'_+;\mathbf{r}_0)] dA' \end{aligned} \right\}$$

Fluctuation Fields

Described by radially isotropic, power-law, power spectra:

-Interface deviations:

$$W(k_r) = \frac{4pn s^2 l_r^2}{(1 + l_r^2 k_r^2)^{n+1}}$$

-Sound Speed Fluctuations:

$$W(k_r) = \frac{8p^{3/2} s^2 l_r^2 l_z \Gamma(n + 3/2)}{\Gamma(n) (1 + l_r^2 k_r^2 + l_z^2 k_z^2)^{n+1}}$$

- Single-scattering: Use Born Approximation (i.e. $G(\mathbf{r}_1; \mathbf{r}_2) = G_0(\mathbf{r}_1; \mathbf{r}_2)$)
- Monostatic scattering geometry
- Compute unperturbed Green's function by normal mode decomposition
- Narrow (30 Hz) band processing
- Fit ensemble-averaged simulated time series to band-filtered time series via power spectrum parameters

References

- Bass, F.G. and Fuks, I.M., *Wave Scattering from Statistically Rough Surfaces*, Pergamon, Oxford, 1979
- Yamamoto, T., “Acoustic scattering in the ocean from velocity and density fluctuations in the sediments,” JASA **99**, 866-879 (1996)
- Li, D. et al., “Modeling of bottom backscattering from three-dimensional volume inhomogeneities and comparisons with experimental data,” JASA **109**, 1384-1397 (2001)