



# **A Novel Wave Front Method used for Tracking Terrestrial Concentrator Focal Spot Location**

**Joseph N. Beasley**

**USAF/AFRL/PRSO**

**Cal State University, Long Beach**

**Claremont Graduate University**

**52<sup>nd</sup> JANNAF JPM**

**13 May 2004**

Approved for public release; distribution unlimited.

# Report Documentation Page

Form Approved  
OMB No. 0704-0188

Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.

1. REPORT DATE <b>22 APR 2004</b>		2. REPORT TYPE		3. DATES COVERED -	
4. TITLE AND SUBTITLE <b>A Novel Wave Fron Method Used for Tracking Terrestrial Concentrator Focal Spot Location</b>				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S) <b>Joseph Beasley</b>				5d. PROJECT NUMBER <b>1011</b>	
				5e. TASK NUMBER <b>0062</b>	
				5f. WORK UNIT NUMBER <b>10110062</b>	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) <b>Air Force Research Laboratory ,AFRL/PRSS,5 Pollux Drive,Edwards AFB,CA,93524-7048</b>				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT <b>Approved for public release; distribution unlimited</b>					
13. SUPPLEMENTARY NOTES <b>The original document contains color images.</b>					
14. ABSTRACT <b>A major requirement for using a solar propulsion system is the proper placement of the focal spot on the thruster absorber plane. Without proper placement of the focal spot, solar energy is not transferred to the propellant gas or at worst case, a significantly smaller proportion of the incident energy is transferred to the gas.</b>					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT <b>1</b>	18. NUMBER OF PAGES <b>31</b>	19a. NAME OF RESPONSIBLE PERSON
a. REPORT <b>unclassified</b>	b. ABSTRACT <b>unclassified</b>	c. THIS PAGE <b>unclassified</b>			



# Agenda



- **Introduction**
- **Problem Statement**
- **Wave Front Sensor**
- **Proposed Solution**
- **Experiment Description**
- **Results**
- **Conclusions and Future Work**




# Introduction



- **A major requirement for using a solar propulsion system is the proper placement of the focal spot on the thruster absorber plane. Without proper placement of the focal spot, solar energy is not transferred to the propellant gas or at worst case, a significantly smaller proportion of the incident energy is transferred to the gas.**



# Solar Thermal Spacecraft Configuration





Approved for public release; distribution unlimited.



# Problem



**Determine location of solar focal spot on a visually complex thruster absorber and secondary concentrator. Visual complexity is compounded by specular reflection from the secondary concentrator and by the fact that the camera is moving with the concentrator.**



Approved for public release; distribution unlimited.



## Basic Problem Solution Concept



- **Use Charge Coupled Device (CCD) Camera as the primary fine focus sensor. Images of the thruster absorber are taken by the camera to be analyzed.**
- **Develop algorithm(s) for determining focal spot position from image of thruster absorber and secondary concentrator to produce control commands for the main concentrator. Optimize control with respect to power or energy (temperature) transferred to the propellant gas.**



# Focus Parameters



- **The focal beam of a real concentrator is a distorted and spread Gaussian; since a non-imaging concentrator can have large aberrations and non-zero slope errors, the focal beam would not perform ideally.**
- **Maximum intensity is related to maximum temperature. However, this parameter is not enough to indicate when the focal maximum is above or below the absorber instead of having its focal maximum exactly on the absorber plane.**
- **The intensity on the absorber should be symmetric for an on focus condition and may be utilized for coarse positioning as the focal beam is coming onto the absorber.**
- **Output temperature of the propellant could also be used as a determinant for on focus condition.**
- **Control to 0.1 inch and 0.1 degree are the required control tolerances.**





# Wave Front Sensing



- **Hartmann Sensor**
  - Utilized an array of holes or apertures to measure differences in tilt angle of waves by measuring the differences in position of the images of the apertures with a tilted waveform versus the images of the apertures with a non-tilted waveform. A lens behind the aperture plate collects the information and directs that information to a collector array.
- **Shack-Hartmann Sensor**
  - Replaced the array of apertures with small lenses or lenslets.






# Comparison of Wave Front Sensors





# Wave Front Sensing(Cont.)



Approved for public release; distribution unlimited.



# Reflection and Mirror Equations



- **Cylindrical mirrors are similar to convex spherical mirrors in one dimension.**
- **Cylindrical mirrors tend to elongate images along the axis of the cylinder surface, and reduce or squash the images along the radial surface.**
- **The mirror equations for convex mirrors are the same as for concave mirrors:**

$$H_i = f \cdot H_0 / D_0$$

**Where  $H_i$  is the image height,  $f$  is focal length,  $H_0$  is the height of the object and  $D_0$  is the distance from the object to the focus.**

**The equation for reflection is used to ray trace the images in the cylindrical mirror, since the cylindrical mirror is a more complex shape than a convex mirror. (Actually, a cylindrical mirror performs like a flat mirror in one direction and a spherical convex mirror in the perpendicular direction)**




# Absorber/Sensor Model



Approved for public release; distribution unlimited.



# Cylindrical Mirror and Conical Absorber



“Cylindrical  
Mirror”

Approved for public release; distribution unlimited.




## Focus Problem Solutions



- **Measure images of the concentrator in each tubular mirror. (Images would be much like those found in a cylindrical mirror, at least for a single tube. Most like a wave front sensor, with torroidal mirrors in multiple tube version)**
- **Calculate gradients (differences between areas) across and up and down images of tubes and compare to on focus levels. Assumed symmetry that occurs across the face of the absorber could be used as a rough estimate of on focus condition.**
- **Determine inter-tube reflection positions as a determination of focus level. (Least likely to have relevance, as preliminary analysis of images have determined.)**
- **Perturbation of focus, derive gradient.**



# Schematic of Proposed Solution



### FOV Calculate

Lens:  $f = 100 \text{ mm}$

Pixel in camera :  $7.4 \mu\text{m}$

Distance from lens to absorber:  $1 \text{ m}$

One pixel then covers:

$$(1000/100) \cdot 7.4 \mu\text{m} = 0.074 \text{ mm}$$

So that the FOV is equal to:

$$H: 657 \cdot 0.074 = 48.62 \text{ mm (2 inch)}$$

$$V: 495 \cdot 0.074 = 36.63 \text{ (1.4 inch)}$$

THETAc is the angle we are trying to find.

$$X \cdot r / |X| = t \cdot r / |t|$$

Approved for public release; distribution unlimited.



# Algorithms



- **Each image taken would be processed by utilizing profile information along diagonal lines representing the four quadrants of the circle (along the 45 degree angles, say).**
- **The areas of maximum intensity would be determined along each profile line. The maximums should occur roughly where the tubes appear in the image as they act like cylindrical mirrors. The difference or gradient between these areas should give an indication of the direction to the focal spot. (Almost a centroiding operation on the maximum areas in the image)**
- **By knowing where the center of the absorber is located with respect to the camera (a non-trivial assumption as the camera would probably be mounted on one of the concentrator's movable struts) , the computer should be able to generate x, y, z, roll, pitch, and yaw commands for the hexapod controller to move the concentrator to a new position to provide better focus and thus better heating.**




## Experiment Setup



- **Utilize Stainless Steel Tubes to determine feasibility of method. Use first one tube then two tubes**
- **CCD Camera used to take images**
- **Overhead projector used to back light concentrator models**
- **Matlab used to analyze images**
- **Different concentrator models were designed in PowerPoint to represent the half angle of the concentrator and to represent different “power” levels**
- **Mylar Wrapped can used because it provided a larger reflected image**




## Schematic of Test Setup



Approved for public release; distribution unlimited.



# Concentrator Models




Full Concentrator

Pattern 1



Pattern 2



Approved for public release; distribution unlimited.




# Results

## Two Tubes Full Concentrator



Approved for public release; distribution unlimited.




Approved for public release; distribution unlimited.



# Pattern 1 Two Tube



Approved for public release; distribution unlimited.




Approved for public release; distribution unlimited.



## Pattern 2, Two Tube



Approved for public release; distribution unlimited.



Approved for public release; distribution unlimited.



## Conclusion and Future Work



- **Showed that the concept works with limited models for the concentrator.**
- **Results showed that a camera with better resolution will be needed to improve recognition of the concentrator image in the tubes of the absorber.**
- **Will need to work with full size concentrator to develop better concentrator models.**
- **Will also need to expand the experiment to use the copper coiled absorber model.**
- **Will have to analyze the optical system to determine how the correct positioning information is presented in the images.**




# BACKUP SLIDES



Approved for public release; distribution unlimited.




# Geometry For Spacecraft






# Wave Fronts and Concentrator



Approved for public release; distribution unlimited.




# Control System Block Diagram (Power Calculation)



Approved for public release; distribution unlimited.



# Intensity Schematic (Off Axis Paraboloid)



Ideal Concentration:  $A_c / A_a$   $A_a$  is assumed to be at the focal spot of the concentrator.

Ideal ratio is 46000:1

Approved for public release; distribution unlimited.