



ORCA User's Manual Glossary

by Owen P. Litt

ARL-SR-124

September 2004

NOTICES

Disclaimers

The findings in this report are not to be construed as an official Department of the Army position unless so designated by other authorized documents.

Citation of manufacturer's or trade names does not constitute an official endorsement or approval of the use thereof.

Destroy this report when it is no longer needed. Do not return it to the originator.

Army Research Laboratory

Aberdeen Proving Ground, MD 21005-5068

ARL-SR-124

September 2004

ORCA User's Manual Glossary

Owen P. Litt

Survivability/Lethality Analysis Directorate, ARL

Report Documentation Page			Form Approved OMB No. 0704-0188		
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing the burden, to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.					
1. REPORT DATE (DD-MM-YYYY) September 2004		2. REPORT TYPE Final		3. DATES COVERED (From - To) 1 October 2002–1 August 2003	
4. TITLE AND SUBTITLE ORCA User's Manual Glossary			5a. CONTRACT NUMBER		
			5b. GRANT NUMBER		
			5c. PROGRAM ELEMENT NUMBER		
6. AUTHOR(S) Owen P. Litt			5d. PROJECT NUMBER D6-75		
			5e. TASK NUMBER		
			5f. WORK UNIT NUMBER		
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army Research Laboratory ATTN: AMSRD-ARL-SL-BE Aberdeen Proving Ground, MD 21005-5068			8. PERFORMING ORGANIZATION REPORT NUMBER ARL-SR-124		
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)			10. SPONSOR/MONITOR'S ACRONYM(S)		
			11. SPONSOR/MONITOR'S REPORT NUMBER(S)		
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution is unlimited.					
13. SUPPLEMENTARY NOTES					
14. ABSTRACT The Operational Requirements-based Casualty Assessment (ORCA) User's Manual consists of technical, chemical, anatomical, physiological, and medical terms. It also consists of abbreviations, acronyms, and symbols. This glossary in intended to be used as an aid in providing a convenient source of definitions or brief explanations of the contents.					
15. SUBJECT TERMS ORCA model, casualty assessment, insult, blast insult, penetration insult, acceleration insult, toxic substance insult, directed energy insult, thermal exposure, lethality, injury severity, injury vector, elemental capabilities, incapacitation, modeling and simulation					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT UL	18. NUMBER OF PAGES 32	19a. NAME OF RESPONSIBLE PERSON Owen P. Litt
a. REPORT UNCLASSIFIED	b. ABSTRACT UNCLASSIFIED	c. THIS PAGE UNCLASSIFIED			19b. TELEPHONE NUMBER (Include area code) 410-278-6281

Contents

1. Chapter 1: Section Ordered Glossary	1
1.1 Introduction	1
1.2 Methodology	1
1.3 Running ORCA	3
1.4 Insults	3
1.4.1 Blast Insults	3
1.4.2 Penetration.....	4
1.4.3 Acceleration Insult	5
1.4.4 Toxic Substance Insult	7
1.4.5 Thermal Exposure	8
1.4.6 Directed Energy.....	9
1.4.7 Directed Energy Input Menu.....	9
1.5 Injury Results	9
1.5.1 Blast Injury	10
1.5.2 Penetration Injury	10
1.5.3 Toxic Substance Injury.....	10
1.5.4 Thermal Exposure Injury.....	11
1.5.5 Directed Energy Injury	11
1.6 ORCA's Databases.....	11
1.6.1 Individual Characteristics.....	11
1.6.2 Operational Requirements Database	12
1.7 Assessment	12
1.8 External Files.....	12
2. Chapter 2: Alphabetically Ordered Glossary	12
Distribution List	23

INTENTIONALLY LEFT BLANK.

1. Chapter 1: Section Ordered Glossary

This chapter consists of words, symbols, acronyms, and phrases from the Operational Requirements-based Casualty Assessment (ORCA) User's Manual. They are arranged by the section in which they are found and usually in the order in which they appear.

1.1 Introduction

ORCA	Operational Requirements-based Casualty Assessment.
Insult	External event which causes injury.
GUI	Graphical user interface.

Insults addressed by ORCA:

- blast,
- penetration,
- thermal exposure,
- toxic gases,
- directed energy (electromagnetic waves: laser, microwaves, x-rays, etc.),
- blunt trauma, and
- abrupt acceleration.

1.2 Methodology

Systemic	Affecting the entire body.
Respiratory	Affecting breathing.
Toxic	Poison.
Deleterious	Injurious.
Injury vector	The 473 body elements which have been specifically defined and geometrically modeled.
ECV	Elemental capability vector.
Operational casualty	An individual who does not have the elemental capabilities to fully perform the job.

Partial casualty	An individual's capabilities fall between the full requirements and the minimal requirements to perform an assigned task.
Visual acuity and color discrimination	Compared to normal vision standards.
Night vision	Compared to standard night vision scale.
Visual field of view	Peripheral vision.
Binocularism and motility	Coordinated vision through both eyes and ability to move at will.
Hearing-threshold: low frequency	Compared to standard of normal threshold.
Hearing-threshold: high frequency	Compared to standard of normal threshold.
Binauralism	Coordinated hearing through both ears.
Somatic senses	Whole-body senses: touch, hot and cold, etc.
Balance	Standing stability while performing required tasks.
Cognitive mental processing	Rational interpretation of situation and application to required tasks.
Visual mental processing	Correctly understanding what is seen.
Auditory mental processing	Correctly understanding what is heard.
Psychomotor mental processing	Correctly able to respond physically to situation.
Speech articulation/intelligibility	Correctly and clearly describe the situation.
Vocal power/background noise	Decibel (dB) of useful vocal information at 1 m/dB of noise.

dB

Decibel: The dB value is calculated by taking the log of the ratio of the measured or calculated power (P_2) with respect to a reference power (P_1). This result is then multiplied by 10 to obtain the value in dB. The formula for calculating the dB value of two ratios is shown in the following equation:

$$dB = 10 \log_{10} \frac{P_2}{P_1}.$$

1.3 Running ORCA

Operational requirements

Random distribution.

1.4 Insults

1.4.1 Blast Insults

Landmine

Explosive device placed beneath the ground.

Blast overpressure

Blast wave-front pressure minus ambient air pressure.

Blast loading

Blast wave-front impact characteristics and distribution on a target.

Fragment loading

Fragment wave-front impact characteristics and distribution on a target.

Time history data

Blast overpressure as a function of time.

Friedlander equation

Simulated blast wave front. Assumes instant increase of pressure from ambient to peak, then an exponential decay back to ambient pressure. User inputs include peak (pressure pounds per square inch [psi]), duration (milliseconds [ms]), and time constant (the number of time constants within the duration of the blast overpressure wave front).

Triangular blast wave

Simulated blast wave front. Assumes instant increase of pressure from ambient to peak, then a constant decay back to ambient pressure. User inputs include peak pressure (psi), duration (ms), and time constant (the number of time constants within the duration of the blast overpressure wave front).

Blast orientation

Orientation of an individual with respect to the blast wave front. User inputs only apply to Friedlander and triangular blast wave options.

1.4.2 Penetration

Flechette	A long slender pointed rod with fins.
ComputerMan	Computer model of a man for the purpose of injury studies.
Degradation	Incapacitation.
Density	Mass per volume.
Shape factor	A shape-related coefficient of momentum (mass $\times$ velocity) and density for predicting penetration. A shape-related coefficient of mass and density for predicting penetration hole size.
Metric units	SI (International System of Units) units: meters, kilograms, newtons, and seconds. Non-SI units: centimeters, grams, and dyne.
English units	Feet, pound-mass or slugs, pounds, grains (0.000142857 lb, or 7000 gr = 1 lb), and seconds.
Casing fragment	Warhead cover.
Grid of shots	Projectiles from different origins.
Point-burst shots	Projectiles from one origin.
Yaw angle	An angle, with respect to the shotline and in a plane perpendicular to the vertical plane and intersecting the central axis of the projectile.
Pitch angle (elevation angle)	An angle, with respect to the shotline and in the vertical plane through the central axis of the projectile.
1.4.2.1 The Anatomical Model	
Shotline	Path along which the penetrator travels.
Hit location	Location where the projectile shotline intersects ComputerMan.

1.4.2.2 Processing a Single Shot

Azimuth angle (= yaw angle)

An angle, with respect to the shotline and in a plane perpendicular to the vertical plane and intersecting the central axis of the projectile.

Elevation angle (= pitch angle)

An angle, with respect to the shotline and in the vertical plane through the central axis of the projectile.

1.4.2.3 Processing Grid Run

Attack direction

Azimuth angle.

1.4.2.4 Processing Point-Burst Shot

Cone half-angle

The angle from the origin, of a directed explosion of fragments, between the shotline and the greatest angle containing the fragment distribution.

1.4.3 Acceleration Insult

SAE

Society of Automotive Engineers.

SAEJ211

Document which specifies manikin transducer frequency responses.

CFC

Channel frequency classes.

Manikin

Crash test dummy with accelerometer transducers, which was used in acceleration injury studies.

Landmine blast tests

Landmine explosion beneath a vehicle with one or more instrumented manikins.

USAARL

U.S. Army Aeromedical Research Laboratory.

AMANDA

Analysis of MANikin Data.

Acceleration time history

Graph of acceleration vs. time.

Triaxial plots

Acceleration time histories along three mutually orthogonal directions.

1.4.3.1 AMANDA Assessment

Head accelerations	Triaxial time history.
Neck forces	Determined from $\text{force} = \text{mass} \times \text{acceleration}$.
Neck moments	Twisting force.
Chest accelerations	Triaxial time history.
Pelvis accelerations	Triaxial time history.
Lumbar spine forces	Determined from $\text{force} = \text{mass} \times \text{acceleration}$.
Lumbar spine moments	Twisting force.
Femur and tibia loads	Determined from $\text{force} = \text{mass} \times \text{acceleration}$.
Seat (pelvis) accelerations	Triaxial time history.
Transducer	Instrument which measures physical phenomenon.
Dataset	Set of computer files of data for a particular event.
Polarity of the signal	+ polarity: positive accelerations displayed above the horizontal axis. – polarity: positive accelerations displayed below the horizontal axis.
Hz	Frequency in cycles (of pulses) per second.
dB/octave	Octave refers to two times a given frequency.
Frequency response	Domain of frequencies within which there is physical response to the signal.
Hybrid III manikin	A manikin used in crash tests.
Pelvis	Skeletal structure at the base of the spinal column.
Lumbar spine	The five lowest vertebrae of the spine.
Femur	Thighbone.
Tibia	The leg bone directly beneath the base of the femur and directly above the connective tissue of the foot.

1.4.3.2 Zero Shift (Bias Removal)

Direct current (DC) (constant current amplitude)	The vertical level of zero.
---	-----------------------------

1.4.3.3 AMANDA's Analysis Selection Window

Triaxial signal	Measured signal at a point along three mutually perpendicular directions.
-----------------	---

1.4.3.4 The Interactive Injury Assessment Window

Time history plot	Graph of amplitude vs. time.
-------------------	------------------------------

1.4.4 Toxic Substance Insult

Combustion	Burning.
Combustion products	Chemical compounds produced by combustion.
Industrial agents	Industrial chemical toxins.
Military agents	Military chemical toxins.
Injury vector	Anatomical elements subject to injury.
ECV	Elemental capabilities vector.
Toxin	Poisonous substance.
ProbInc	Probability of incapacitation.
External partial pressures	Anatomical impact points from external sources.
ExtCon	External concentrations.
O ₂	Molecular oxygen.
CO ₂	Carbon dioxide.
Ac	Actinium.
HCN	Hydrogen cyanide.
CO	Carbon monoxide.
NO ₂	Nitrous oxide.
HCL	Hydrogen chloride (hydrochloric acid).
RMV	Root mean velocity (milliliter per minute).

1.4.4.1 Toxic Agent Lookup (Analysis 3)

ppm	Parts per million.
mg/m ³	Milligrams per cubic meter.

1.4.4.2 Military Agents

GA	Tabun: nerve agent.
GB	Sarin: nerve agent.
GD	Soman: nerve agent.
GF	Cyclosarin: nerve agent.
VX	Tabun: nerve agent.

1.4.5 Thermal Exposure

Exposure time	Time that the skin is exposed to the heat source.
Maximum calculation time	Maximum interval of time allowed by the software.
Calculation interval	Time step interval.
Water boiling temperature	Temperature at which water boils.
Density	Mass per unit volume of the skin.
Thickness	Thickness between the surface and base of the skin.
Absorptivity	Absorption rate of the skin.
Convective blood cooling factor	Rate at which blood absorbs heat as it goes through muscle tissue.
Number of nodes	Number of units of depth increments from the skin surface.
Number of extra nodes	Smaller skin depth increments.
Heat flux	Calories per square centimeter per second.
Core temperature	Temperature at the base of the skin.
Absorptivity	Fraction of incident heat which is absorbed by the skin.
Diffusion	Rate at which heat spreads.
Micron	1/1,000,000 m.

1.4.6 Directed Energy

Directed energy	Distance traveled by one cycle of a signal: wavelength = signal speed per signal frequency.
Laser intensity	Power per unit area or energy per area*time.
Continuous wave laser	Uninterrupted sine wave signal.
Pulsed laser	Short duration sequence of sine wave signals.
PRF	Pulse repetition frequency.
Pulse width	Duration of a laser output pulse of light.
Flash blindness	Temporary blindness from exposure to intense light.
Cornea	Transparent membrane at the front of the eye.
Retina	Light-sensitive membrane in the eye.

1.4.7 Directed Energy Input Menu

Exponential notation	$1\text{E} - 07 = 0.0000001$.
μm	1/1,000,000 m.
Joule	Unit of energy.
Joules/cm ²	Intensity per unit time.

1.5 Injury Results

Deleterious	Harmful.
Lung(superior lobe)L	Upper left lobe.
Lung(inferior lobe)L	Lower left lobe.
Lung(middle lobe)R	Middle right lobe.
Lung(superior lobe)R	Upper left lobe.
Lung(inferior lobe)R	Upper left lobe.
Sepsis	Presence of pathogenic substances in blood or tissues.
Pathogenic	Disease-causing substances.

1.5.1 Blast Injury

Blast overpressure

Pressure shock wave resulting from an explosion.

Deleterious process

A process resulting in injury.

Respiration

Breathing.

1.5.2 Penetration Injury

Core vein

Internal organic veins.

Core artery

Internal organic arteries.

Muscle (pectoralis major, R)

Chest muscle.

Muscle (thorax, NFS)

Intercostal muscles: muscles connected to the rib cage.

Subcutaneous tissue

Tissue beneath the skin.

Heart (epicardium and myocardium)

Outer wall and muscle tissue.

Heart (right atrium)

Right chamber.

Kidney

Anatomical structures in rear of the abdominal cavity.

Adrenals

Glands located near the kidneys.

Liver

Large gland just beneath the diaphragm.

Thorax

Anatomical region between the neck and the diaphragm.

Abdomen

Anatomical region between the diaphragm and the pelvis.

Pelvis

Skeletal structure at the base of the spinal column.

1.5.3 Toxic Substance Injury

Vapor

Gas.

Systemic

Throughout the body.

Visceral

Pertaining to the internal organs of the body.

Cardio

Pertaining to the heart.

Meiosis

Cell division.

Photophobia

Abnormal intolerance of light.

Rhinorrhea

A mucous discharge from the nose.

1.5.4 Thermal Exposure Injury

Antecubital area

Biceps based at the upper and forearm connection.

1.5.5 Directed Energy Injury

LASER

Light amplification by stimulated emission of radiation. The emitted light is coherent: in phase.

Laser power

Energy per time. The units in figure 6.16 of the ORCA User's Manual are surface energy density.

Flash blindness

Temporary blindness from exposure to intense light.

Retina

Light-sensitive membrane in the eye.

Cornea

Transparent membrane at the front of the eye.

Photokeratitis

Inflammation of the cornea.

Ultraviolet

Wavelengths of light shorter than violet and longer than x-ray wavelengths.

1.6 ORCA's Databases

1.6.1 Individual Characteristics

Visual acuity

Visual resolution.

Visual field of view

Relative range of focus.

Visual binocularism

Distance resolution.

Visual motility

Visual image of moving object.

Somatic senses

Sense of touch.

Cognitive mental processing

Understanding observed events.

Psychomotor

Mental control of physical actions.

Torso

Trunk of the human body.

Aerobic

Cardiopulmonary effects.

1.6.2 Operational Requirements Database

Task element	Single action.
Task	Sequence of actions to complete a single task.
Mission	Sequence of tasks to complete a mission (objective).
Job	Collection of tasks required to meet job objectives.
Operational requirements	What is necessary for task elements/tasks or missions/jobs?
Weight factor	Coefficient representing relative importance.

1.7 Assessment

Single analysis	Injury assessment from single insult or from single analysis of multiple insults.
Multiple analysis	Injury assessment from multiple injuries: grid shot and point burst.
Degradation	Diminished capability to perform a task.
Standard deviation	Deviation from average value, which includes about 63% of statistical samples for one standard deviation. Each succeeding deviation includes 63% of the remainder; i.e., $.63 * .37 + .63 = .86$, or 86% for the second standard deviation. The third standard deviation is $.63 * .14 + .86 = .95$, or 95%.

1.8 External Files

OBC vector	ORCA body component vector.
------------	-----------------------------

2. Chapter 2: Alphabetically Ordered Glossary

This chapter consists of words, symbols, acronyms, and phrases from the ORCA User's Manual. They are arranged in alphabetical order.

Abdomen	Anatomical region between the diaphragm and the pelvis.
Absorptivity	Absorption rate of the skin.

Absorptivity	Fraction of incident heat, which is absorbed by the skin.
Ac	Actinium.
Acceleration time history	Graph of acceleration vs. time.
Adrenals	Glands located near the kidneys.
Aerobic	Cardiopulmonary effects.
AMANDA	Analysis of MANikin Data.
Antecubital area	Biceps based at the upper and forearm connection.
Attack direction	Azimuth angle.
Auditory mental processing	Correctly understanding what is heard.
Azimuth angle (= yaw angle)	An angle, with respect to the shotline and in a plane perpendicular to the vertical plane and intersecting the central axis of the projectile.
Balance	Standing stability while performing required tasks.
Binauralism	Coordinated hearing through both ears.
Binocularism and motility	Coordinated vision through both eyes and ability to move at will.
Blast loading	Blast wave-front impact characteristics and distribution on a target.
Blast orientation	Orientation of an individual with respect to the blast wave front. User inputs only apply to Friedlander and triangular blast wave options.
Blast overpressure	Pressure shock wave resulting from an explosion.
Blast overpressure	Blast wave-front pressure minus ambient air pressure.
Calculation interval	Time step interval.
Cardio	Pertaining to the heart.
Casing fragment	Warhead cover.
CFC	Channel frequency classes.
Chest accelerations	Triaxial time history.

CO	Carbon monoxide.
CO ₂	Carbon dioxide.
Cognitive mental processing	Understanding observed events.
Cognitive mental processing	Rational interpretation of situation and application to required tasks.
Combustion products	Chemical compounds produced by combustion.
Combustion	Burning.
ComputerMan	Computer model of a man for the purpose of injury studies.
Cone half-angle	The angle from the origin, of a directed explosion of fragments, between the shotline and the greatest angle containing the fragment distribution.
Continuous wave laser	Uninterrupted sine wave signal.
Convective blood cooling factor	Rate at which blood absorbs heat as it goes through muscle tissue.
Core artery	Internal organic arteries.
Core temperature	Temperature at the base of the skin.
Core vein	Internal organic veins.
Cornea	Transparent membrane at the front of the eye.
Dataset	Set of computer files of data for a particular event.
dB	Decibel: The dB value is calculated by taking the log of the ratio of the measured or calculated power (P ₂) with respect to a reference power (P ₁). This result is then multiplied by 10 to obtain the value in dB. The formula for calculating the dB value of two ratios is shown in the following equation:
	$dB = \log_{10} \frac{P_2}{P_1}.$
dB/octave	Octave refers to two times a given frequency.
DC bias	The vertical level of zero.

Degradation	Incapacitation.
Degradation	Diminished capability to perform a task.
Deleterious process	A process resulting in injury.
Deleterious	Injurious.
Deleterious	Harmful.
Density	Mass per unit volume of the skin.
Density	Mass per volume.
Diffusion	Rate at which heat spreads.
Directed energy	Distance traveled by one cycle of a signal.
ECV	Elemental capability vector.
Elevation angle (= pitch angle)	An angle, with respect to the shotline and in the vertical plane through the central axis of the projectile.
English units	Feet, pound-mass or slugs, pounds, grains (0.000142857 lb, or 7000 gr = 1 lb), and seconds.
Exponential notation	1E-07 = 0.0000001.
Exposure time	Time that the skin is exposed to the heat source.
ExtCon	External concentrations.
External partial pressures	Anatomical impact points from external sources.
Femur and tibia loads	Determined from force = mass $\times$ acceleration.
Femur	Thighbone.
Flash blindness	Temporary blindness from exposure to intense light.
Flechette	A long slender pointed rod with fins.
Fragment loading	Fragment wave-front impact characteristics and distribution on a target.
Frequency response	Domain of frequencies within which there is physical response to the signal.

Friedlander equation	Simulated blast wave front. Assumes instant increase of pressure from ambient to peak, then an exponential decay back to ambient pressure. User inputs include peak pressure (psi), duration (ms), and time constant (the number of time constants within the duration of the blast overpressure wave front from ambient to peak, then a constant decay back to ambient pressure).
GA	Tabun: nerve agent.
GB	Sarin: nerve agent.
GD	Soman: nerve agent.
GF	Cyclosarin: nerve agent.
Grid of shots	Projectiles from different origins.
GUI	Graphical user interface.
HCL	Hydrogen chloride (hydrochloric acid).
HCN	Hydrogen cyanide.
Head accelerations	Triaxial time history.
Hearing-threshold: high frequency	Compared to standard of normal threshold.
Hearing-threshold: low frequency	Compared to standard of normal threshold.
Heart (epicardium and myocardium)	Outer wall and muscle tissue.
Heart (right atrium)	Right chamber.
Heat flux	Calories per square centimeter per second.
Hit location	Location where the projectile shotline intersects ComputerMan.
Hybrid III manikin	A manikin used in crash tests.
Hz	Frequency in cycles (of pulses) per second.
Industrial agents	Industrial chemical toxins.
Injury vector	Anatomical elements subject to injury.
Injury vector	The 473 body elements which have been specifically defined and geometrically modeled.

Insult	External event which causes injury.
Job	Collection of tasks required to meet job objectives.
Joule	Unit of energy.
Joules/cm ²	Intensity per unit time.
Kidney	Anatomical structures in rear of the abdominal cavity.
Landmine blast tests	Landmine explosion beneath a vehicle with one or more instrumented manikins.
Landmine	Explosive device placed beneath the ground.
Laser intensity	Power per unit area or energy per area*time.
Laser power	Energy per time. The units in figure 6.16 of the ORCA User's Manual are surface energy density.
LASER	Light amplification by stimulated emission of radiation. The emitted light is coherent: in phase.
Liver	Large gland just beneath the diaphragm.
Lumbar spine forces	Determined from force = mass × acceleration.
Lumbar spine moments	Twisting force.
Lumbar spine	The five lowest vertebrae of the spine.
Lung(inferior lobe)L	Lower left lobe.
Lung(inferior lobe)R	Upper left lobe.
Lung(middle lobe)R	Middle right lobe.
Lung(superior lobe)L	Upper left lobe.
Lung(superior lobe)R	Upper left lobe.
Manikin	Crash test dummy with accelerometer transducers, which was used in acceleration injury studies.
Maximum calculation time	Maximum interval of time allowed by the software.
Meiosis	Cell division.
Metric units	SI (International System Units) units: meters, kilograms, newtons, and seconds.

mg/m ³	Milligrams per cubic meter.
Micron	1/1,000,000 m.
Military agents	Military chemical toxins.
Mission	Sequence of tasks to complete a mission (objective).
Multiple analysis	Injury assessment from multiple injuries: grid shot and point burst.
Muscle (pectoralis major, R)	Chest muscle.
Muscle (thorax, NFS)	Intercostal muscles: muscles connected to the rib cage.
Neck forces	Determined from force = mass × acceleration.
Neck moments	Twisting force.
Night vision	Compared to standard night vision scale.
NO ₂	Nitrous oxide.
Non-SI units	Centimeters, grams, and dyne.
Number of extra nodes	Smaller skin depth increments.
Number of nodes	Number of units of depth increments from the skin surface.
O ₂	Molecular oxygen.
OBC vector	ORCA body component vector.
Operational casualty	An individual who does not have the elemental capabilities to fully perform the job.
Operational requirements	Mental and physical requirements associated with assigned tasks.
Operational requirements	What is necessary for task elements/tasks or missions/jobs?
ORCA	Operational Requirements-based Casualty Assessment.
Partial casualty	An individual's capabilities fall between the full requirements and the minimal requirements to perform an assigned task.

Pathogenic	Disease-causing substances.
Pelvis accelerations	Triaxial time history.
Pelvis	Skeletal structure at the base of the spinal column.
Photokeratitis	Inflammation of the cornea.
Photophobia	Abnormal intolerance of light.
Pitch angle (elevation angle)	An angle, with respect to the shotline and in the vertical plane through the central axis of the projectile.
Point-burst shots	Projectiles from one origin.
Polarity of the signal	+ polarity: positive accelerations displayed above the horizontal axis. – polarity: positive accelerations displayed below the horizontal axis.
ppm	Parts per million.
PRF	Pulse repetition frequency.
ProbInc	Probability of incapacitation.
Psychomotor mental processing	Correctly able to respond physically to situation.
Psychomotor	Mental control of physical actions.
Pulse width	Duration of a laser output pulse of light.
Pulsed laser	Short duration sequence of sine wave signals.
Respiration	Breathing.
Respiratory	Affecting breathing.
Retina	Light-sensitive membrane in the eye.
Rhinorrhea	A mucous discharge from the nose.
RMV	Root mean velocity (millimeter per minute).
SAE	Society of Automotive Engineers.
SAEJ211	Document which specifies manikin transducer frequency responses.
Seat (pelvis) accelerations	Triaxial time history.

Sepsis	Presence of pathogenic substances in blood or tissues.
Shape factor	A shape-related coefficient of momentum (mass $\times$ velocity) and density for predicting penetration. A shape-related coefficient of mass and density for predicting penetration hole size.
Shotline	Path along which the penetrator travels.
Single analysis	Injury assessment from single insult or from single analysis of multiple insults.
Somatic senses	Whole-body senses: touch, hot and cold, etc.
Somatic senses	Sense of touch.
Speech articulation/intelligibility	Correctly and clearly describe the situation.
Standard deviation	Deviation from average value, which includes about 63% of statistical samples for one standard deviation. Each succeeding deviation includes 63% of the remainder; i.e., $.63 * .37 + .63 = .86$, or 86% for the second standard deviation. The third standard deviation is $.63 * .14 + .86 = .95$, or 95%.
Stochastic	Random distribution.
Subcutaneous tissue	Tissue beneath the skin.
Systemic	Affecting the entire body.
Systemic	Throughout the body.
Task element	Single action.
Task	Sequence of actions to complete a single task.
Thickness	Thickness between the surface and base of the skin.
Thorax	Anatomical region between the neck and the diaphragm.
Tibia	The leg bone directly beneath the base of the femur and directly above the connective tissue of the foot.
Time history plot	Graph of amplitude vs. time.
Time history data	Blast overpressure as a function of time.

Torso	Trunk of the human body.
Toxic	Poison.
Toxin	Poisonous substance.
Transducer	Instrument which measures physical phenomenon.
Triangular blast wave	Simulated blast wave front. Assumes instant increase of pressure
Triaxial plots	Acceleration time histories along three mutually orthogonal directions.
Triaxial signal	Measured signal at a point along three mutually perpendicular directions.
Ultraviolet	Wavelengths of light shorter than violet and longer than x-ray wavelengths.
USAARL	U.S. Army Aeromedical Research Laboratory.
Vapor	Gas.
Visceral	Pertaining to the internal organs of the body.
Visual acuity and color discrimination	Compared to normal vision standards.
Visual acuity	Visual resolution.
Visual binocularism	Distance resolution.
Visual field of view	Peripheral vision.
Visual field of view	Relative range of focus.
Visual mental processing	Correctly understanding what is seen.
Visual motility	Visual image of moving object.
Vocal power/background noise	Decibel of useful vocal information at 1m/dB of noise.
VX	Tabun: nerve agent.
Water boiling temperature	Temperature at which water boils: wavelength = signal speed per signal frequency.
Weight factor	Coefficient representing relative importance.

Weighted Task Average (WTA)	A numerical measure of effect (between 0 and 1) represented by the weighted average of all computed task degradations observed in the set of tasks that comprise a job. It is equal to the sum of the performance value, multiplied by the tasks weight factor, and divided by the sum of the weight factors for the entire job.
Weighted Task Average Impairment (WTAI)	A numerical measure of effect (between 0 and 1) represented by the weighted average of all computed task degradations observed in the set of tasks that comprise a job. It is equal to one minus the sum of the performance value, multiplied by the tasks weight factor, and divided by the sum of the weight factors for the entire job. WTAI is an expected level of incapacitation.
Yaw angle	An angle, with respect to the shotline and in a plane perpendicular to the vertical plane and intersecting the central axis of the projectile.
μm	1/1,000,000 m.

NO. OF
COPIES ORGANIZATION

1 DEFENSE TECHNICAL
(PDF INFORMATION CTR
ONLY) DTIC OCA
8725 JOHN J KINGMAN RD
STE 0944
FT BELVOIR VA 22060-6218

1 COMMANDING GENERAL
US ARMY MATERIEL CMD
AMCRDA TF
5001 EISENHOWER AVE
ALEXANDRIA VA 22333-0001

1 INST FOR ADVNCD TCHNLGY
THE UNIV OF TEXAS
AT AUSTIN
3925 W BRAKER LN STE 400
AUSTIN TX 78759-5316

1 US MILITARY ACADEMY
MATH SCI CTR EXCELLENCE
MADN MATH
THAYER HALL
WEST POINT NY 10996-1786

1 DIRECTOR
US ARMY RESEARCH LAB
IMNE AD IM DR
2800 POWDER MILL RD
ADELPHI MD 20783-1197

3 DIRECTOR
US ARMY RESEARCH LAB
AMSRD ARL CI OK TL
2800 POWDER MILL RD
ADELPHI MD 20783-1197

3 DIRECTOR
US ARMY RESEARCH LAB
AMSRD ARL CS IS T
2800 POWDER MILL RD
ADELPHI MD 20783-1197

NO. OF
COPIES ORGANIZATION

ABERDEEN PROVING GROUND
1 DIR USARL
AMSRD ARL CI OK TP (BLDG 4600)

NO. OF
COPIES ORGANIZATION

1 OASD C3I
J BUCHHEISTER
RM 3D174
6000 DEFENSE PENTAGON
WASHINGTON DC 20301-6000

1 OUSD(AT)/S&T AIR WARFARE
R MUTZELBURG
RM 3E139
3090 DEFENSE PENTAGON
WASHINGTON DC 20301-3090

1 OUSD(AT)/S&T LAND WARFARE
A VIILU
RM 3B1060
3090 DEFENSE PENTAGON
WASHINGTON DC 20310-3090

1 UNDER SECY OF THE ARMY
DUSA OR
ROOM 2E660
102 ARMY PENTAGON
WASHINGTON DC 20310-0102

1 ASST SECY ARMY
ACQSTN LOGISTICS & TECH
SAAL ZP ROOM 2E661
103 ARMY PENTAGON
WASHINGTON DC 20310-0103

1 ASST SECY ARMY
ACQSTN LOGISTICS & TECH
SAAL ZS ROOM 3E448
103 ARMY PENTAGON
WASHINGTON DC 20310-0103

1 DIRECTOR FORCE DEV
DAPR FDZ
ROOM 3A522
460 ARMY PENTAGON
WASHINGTON DC 20310-0460

1 US ARMY TRADOC ANL CTR
ATRC W
A KEINTZ
WSMR NM 88002-5502

1 USARL
AMSRD ARL SL EA
R FLORES
WSMR NM 88002-5513

NO. OF
COPIES ORGANIZATION

1 USARL
AMSRD ARL SL EI
J NOWAK
FT MONMOUTH NJ 07703-5601

ABERDEEN PROVING GROUND

1 US ARMY DEV TEST COM
CSTE DTC TT T
APG MD 21005-5055

1 US ARMY EVALUATION CTR
CSTE AEC SVE
R BOWEN
4120 SUSQUEHANNA AVE
APG MD 21005-3013

1 US ARMY EVALUATION CTR
CSTE AEC SVE S
R POLIMADEI
4120 SUSQUEHANNA AVE
APG MD 21005-3013

1 US ARMY EVALUATION CTR
CSTE AEC SV L
R LAUGHMAN
4120 SUSQUEHANNA AVE
APG MD 21005-3013

13 DIR USARL
AMSRD ARL SL
DR WADE
J BEILFUSS
AMSRD ARL SL B
P TANENBAUM
J FRANZ
J MORRISSEY
AMSRD ARL SL BB
M RITONDO
S JUARASCIO
D FARENWALD
AMSRD ARL SL BD
R GROTE
AMSRD ARL SL BE
L ROACH
AMSRD ARL SL E
M STARKS
AMSRD ARL SL EC
J FEENEY
E PANUSKA