

NOISE INDUCED HEARING LOSS AND AUDITORY LOCALIZATION

M. A. Ericson¹ and A. B. Staley²

¹Air Force Research Laboratory, U.S.A., ²The Ohio State University, U.S.A.

Introduction Many studies have been conducted on the ability of normal hearing listeners to judge the locations of various sounds. A few researchers have explored the effects of noise-induced hearing loss on auditory localization acuity (Noble, Byrne and Lepage, 1994; Smith-Olinde, Koehnke and Besing, 1998; and Lorenzi, Gatehouse and Lever, 1999). These researchers have shown that the use of higher frequency energy in the signal is reduced by high-frequency hearing loss. Elevation acuity is more affected by high-frequency hearing loss than azimuth acuity, which is dominated by interaural time difference cues. Many factors, including the temporal and spectral characteristics of the sound source, the listening environment, the types of interfering sound sources, and the listener’s auditory system, affect localization acuity. Two of those factors, the effects of noise-induced hearing loss and head motion cues, are reported in the current study.

Methods The experiments were conducted in the auditory localization facility at Wright-Patterson Air Force Base. The facility includes a 2.13-meter-diameter geodesic sphere with 272 loudspeakers housed inside an anechoic chamber. Sounds were generated with Tucker Davis Technology equipment and controlled by a Pentium® based personal computer.

Subjects: Six subjects ranging from 18 to 50 years of age were recruited from the general population for these experiments. The listeners’ hearing profiles are shown in the table below.

	Test Frequency (Hz)													
	500		1000		2000		3150		4000		6300		8000	
Subject #	R	L	R	L	R	L	R	L	R	L	R	L	R	L
1	-5	-5	-5	0	0	5	5	5	5	10	5	5	0	10
2	0	10	-10	0	15	15	25	15	15	10	-10	35	0	65
3	-5	0	0	0	-5	-10	10	-10	40	-10	15	0	0	-10
4	25	25	30	25	15	20	25	35	25	45	25	40	35	20
5	10	10	15	20	30	30	50	45	55	40	20	10	15	60
6	10	60	15	65	10	40	10	65	10	70	10	70	0	75

Stimuli: Pink noise with a bandwidth of 200 to 13 kHz was used as the target stimulus. The noise stimulus was presented at 75 dB SPL and at three durations of 250 ms, one second, and as a continuous sound until localized. The spectrum was corrected for the frequency response of the loudspeakers. One hundred seventy-two locations were selected for the noise stimuli.

Procedure: Localization acuity was measured using a pointing response method called the God’s-Eye Localization Procedure (GELP) (Gilkey, Good, Ericson, Brinkman, and Stewart, 1995). In this technique, the subject responded after each stimulus presentation by positioning the tip of an electro-magnetic stylus at a point on the surface of a 20-cm plastic spherical model of auditory space to indicate the perceived direction of the auditory image. Localization acuity was measured with restricted head motion by a chin rest and with unrestricted motion.

Results The main effect of hearing loss had a large effect on localization acuity and front-to-back reversal rates. Mild levels of noise-induced hearing loss mostly affected elevation acuity, especially at very high and low angles. The moderately hearing impaired subjects showed degraded acuity in azimuth as well as in elevation.

Report Documentation Page				Form Approved OMB No. 0704-0188	
Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.					
1. REPORT DATE 2003		2. REPORT TYPE N/A		3. DATES COVERED -	
4. TITLE AND SUBTITLE Noise Induced Hearing Loss and Auditory Localization				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S)				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Air Force Research Laboratory Wright Patterson AFB, OH 45433-7022				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release, distribution unlimited					
13. SUPPLEMENTARY NOTES					
14. ABSTRACT					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT UU	18. NUMBER OF PAGES 2	19a. NAME OF RESPONSIBLE PERSON
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified			

Head motion improved localization acuity and greatly reduced front-to-back reversal rates for the normal and mildly impaired subjects (1-4). However, the moderately hearing impaired subjects (5 and 6) had lower acuity and higher front-to-back reversal rates for the free head motion condition than for the restricted head motion condition. These data are shown below in Figure 1 (a) and (b).




Figure 1: Angle of error (a) and percent of front-to-back reversals versus subject (b), chin rest (solid) and unrestricted (dashed) for 0.25S (dark), 1S (gray) and continuous (light) durations.

Discussion Lower acuity and higher reversal rates typically occur when the sound source is under-specified in spectral complexity and temporal envelope patterns. The presence of interfering sounds tends to confuse the identities of the target and maskers. These problems are expected to be further complicated due to reduced frequency and spatial acuity of hearing impaired listeners. Further research is needed to address these issues and to determine the expected utility of spatial auditory displays by hearing impaired listeners.

Acknowledgments The authors would like to thank the US Army Aeromedical Research Laboratory for sponsoring this research and William Ahroon for his guidance and insight.

Keywords Auditory localization, noise induced hearing loss, head motion.

References

- Gilkey, R. H., Goode, M. D., Ericson, M. A., Brinkman, J., and Stewart, J. M. (1995). A pointing technique for rapidly collecting localization responses in auditory research, *Behavioral Research Methods, Instruments, and Computers* **27**, 1-11.
- Koehnke, J. and Besing, J. (1997). Binaural performance in listeners with impaired hearing: Aided and unaided results. In R. H. Gilkey and T. R. Anderson (Eds.), *Binaural and Spatial Hearing in Real and Virtual Environments*. (pp. 99-115). NJ: Lawrence Erlbaum Assoc.
- Lorenzi, C., Gatehouse, S. and Lever, C. (1999). Sound localization in noise in hearing-impaired listeners. *J. Acoust. Soc. Am.* **105**(6), 3454-3463.
- Noble, W., Byrne, D. and Lepage, B. (1994). Effects on Sound localization of configuration and type of hearing impairment. *J. Acoust. Soc. Am.* **95**(2), 992-1005.
- Smith-Olinde, L., Koehnke, J. and Besing, J. (1998). Effects of sensorineural hearing loss on interaural discrimination and virtual localization. *J. Acoust. Soc. Am.* **103**(4), 2084-2099.