

Enhancement of Efficiency of Operation of High-Speed Aircraft Engine Elements by Means of Separation Flow Controlling

N.V. Guryleva, M.A. Ivankin, O.M. Kolesnikov, G.N. Lavrukhin, D.V. Merekin

Central Aerohydrodynamic Institute (TsAGI) named after Prof. N.E. Zhukovsky
Zhukovsky, Moscow Region, Russia

Results of investigations of the mechanism of appearance and destruction of separation zones in supersonic gas flows are presented. Methods for controlling separation phenomena were developed to increase the operation efficiency of ducts, combustors, inlets and outlets of high-speed aircrafts.

The main trends of investigations were:

- 1) Study of deceleration flows in ducts of various shapes with pseudoshock;
- 2) Development of non-traditional manners of spatial implementation of combustion in supersonic flows;
- 3) Computational analysis of optimum methods of energy supply in internal flows with separation zones;
- 4) Control of separation phenomena for increasing efficiency of power plant outlets.

The following major results were obtained:

For 1st trend:

Features of the structure of the non-steady separation in the ducts with deceleration of the supersonic flow in the pseudoshock were determined.

Methods for controlling the pseudoshock were developed.

Conditions for forming separation zones under interference of various shear layers (vortex, jet) generated ahead of the entrance and in ducts with the pseudoshock were studied.

For 2nd trend:

For the first time in the world practice the gasdynamic stabilizers of combustion were developed. Their principle of operation was based on artificial generation of free-hanging separation zones in the supersonic flow. Successful experimental try-out of some schemes of gasdynamic stabilizers was carried out at the TsAGI's hypersonic test rig T-131 at $M=2.5 - 2.6$. They permitted to obtain self-ignition and stable combustion of hydrogen:

Report Documentation Page

Form Approved
OMB No. 0704-0188

Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.

| | | | | | |
|---|------------------------------------|--|----------------------------|---------------------|---------------------------------|
| 1. REPORT DATE 20 OCT 2003 | 2. REPORT TYPE N/A | 3. DATES COVERED - | | | |
| 4. TITLE AND SUBTITLE Enhancement of Efficiency of Operation of High-Speed Aircraft Engine Elements by Means of Separation Flow Controlling | | 5a. CONTRACT NUMBER | | | |
| | | 5b. GRANT NUMBER | | | |
| | | 5c. PROGRAM ELEMENT NUMBER | | | |
| 6. AUTHOR(S) | | 5d. PROJECT NUMBER | | | |
| | | 5e. TASK NUMBER | | | |
| | | 5f. WORK UNIT NUMBER | | | |
| 7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Central Aerohydrodynamic Institute (TsAGI) named after Prof. N.E. Zhukovsky Zhukovsky, Moscow Region, Russia | | 8. PERFORMING ORGANIZATION REPORT NUMBER | | | |
| 9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) | | 10. SPONSOR/MONITOR'S ACRONYM(S) | | | |
| | | 11. SPONSOR/MONITOR'S REPORT NUMBER(S) | | | |
| 12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release, distribution unlimited | | | | | |
| 13. SUPPLEMENTARY NOTES See also ADM001739, Thermochemical processes in plasma aerodynamics (Conference Proceedings, 28-31 July 2003 (CSP 03-5031)). | | | | | |
| 14. ABSTRACT | | | | | |
| 15. SUBJECT TERMS | | | | | |
| 16. SECURITY CLASSIFICATION OF: | | | 17. LIMITATION OF ABSTRACT | 18. NUMBER OF PAGES | 19a. NAME OF RESPONSIBLE PERSON |
| a. REPORT unclassified | b. ABSTRACT unclassified | c. THIS PAGE unclassified | UU | 2 | |

3 Workshop “Thermochemical processes in plasma aerodynamics”

- in the local bow subsonic zone which was produced as a result of interference of the sonic gas jet with the strong shock wave;
- in the bow subsonic zone arising under flowing around the axisymmetric shaped non-started ducted body with the central hollow needle through which the gas jet was ejected upstream. The needle protruded before the diffuser edge at the length of $L=0.28\dots1.28D$ (where D was the diameter of the diffuser entrance);
- in the free-hanging subsonic zone arising as a result of interference of coaxial jets of fuel and air behind the first barrel of the off-design air jet flowing out from the body with the passage.

For the aerated hydrocarbon fuel the scheme of the gasdynamic stabilizer was experimentally verified. The stabilizer ensured the self-ignition and combustion of the fuel in the pilot torch arising behind the first barrel of the off-design jet of the fuel-air mixture flowing out from the body with the passage.

For 3rd trend:

The semi-empirical procedure for calculation of hydrocarbon fuels combustion was developed. The efficiency of various manners of the fuel supply to the duct with generation of both global and local separation zones in the wall region was analyzed. Influence of the type of separation zones on efficiency of the working process in the supersonic combustors was estimated.

The mathematical model of processes of the ignition and combustion in three-dimensional statement was proposed taking into account zones of combustion stabilization. The mathematical model was based on the averaged Navier-Stokes equations supplemented with the model of turbulent viscosity and the detailed scheme of the chemical kinetics.

For 4th trend:

The concept of the artificial generation of separation zones was developed to increase the efficiency of high-speed aircraft outlets. The features of change of characteristics of supersonic and hypersonic nozzles were considered taking into account the influence on losses of friction thrust, chemical non-uniformity and conicity of the flow.

The practical application of the obtained fundamental results is aimed at:

- 1) Improvement of inlets and isolators of advanced supersonic air-breathing engines;
- 2) Creation of high-effective combustors of advanced supersonic air-breathing engines operating over the wide range of speeds and flight altitudes;
- 3) Choice of optimum manners of fuel supply to the combustor of high-speed ramjets and increase of their thrust-economic characteristics;
- 4) Increase of efficiency of supersonic and hypersonic nozzles.