

ADAPTIVE REVERBERATION NULLING USING A TIME REVERSAL MIRROR

H.C. Song, S. Kim, W.S. Hodgkiss, and W.A. Kuperman, *Marine Physical Lab./Scripps Institution of Oceanography, La Jolla, CA*
T. Akal, *NATO SACLANT Undersea Research Centre, La Spezia, Italy*



Sponsored by ONR Contract No. N00014-01-D-0043-D06/D07

Abstract


The major problem for active sonar systems operating in shallow water is the detection of target in the presence of severe bottom reverberation. The focusing capability of a time reversal mirror (TRM) suggest two different approaches to this problem. First, a TRM focuses acoustic energy on a target enhancing the target echo while shadowing the boundaries below and above the focus in an acoustic waveguide, thereby reducing reverberation. The resulting echo-to-reverberation enhancement has been demonstrated experimentally in the 3-4 kHz band in shallow water. The second approach is reverberation nulling to enhance target detectability since focusing and nulling are complementary. The idea is to minimize the acoustic excitation incident on the corresponding scattering interface by applying an excitation weight vector which is orthogonal to the time-gated reverberation focusing vector. Both numerical simulations and experimental results illustrate the potential of reverberation nulling using a time reversal mirror.

Problem


Active sonar systems operating in shallow water is to detect targets in the presence of severe bottom reverberation. The focusing capability of time reversal suggests two different approaches to this problem: echo-to-reverberation enhancement and reverberation nulling.

Goal

Demonstrate the concept of the two proposed approaches both numerically and experimentally in a shallow water.




Reverberation: Numerical Simulation




FAF-00 Reverberation Reduction Experiment

(a) Experimental configuration and (b) enhancement in the ensonification level at the probe source location of 5 dB using time reversal (TR) over BS transmission filling the water column in (c).



Reverberation Nulling: Numerical Simulation



Singular Value Decomposition (SVD)

$$\mathbf{R} = \frac{1}{K} \sum_{i=1}^K \mathbf{H}_i \mathbf{H}_i^H = \sum_{j=1}^N \lambda_j \mathbf{U}_j \mathbf{U}_j^H = \sum_{j=1}^d \lambda_j \mathbf{U}_j \mathbf{U}_j^H + \sum_{j=d+1}^N \lambda_j \mathbf{U}_j \mathbf{U}_j^H$$

$\mathbf{W}_{\text{focus}} = \text{conj}(\mathbf{U}_1)$


$\mathbf{W}_{\text{null}} = \text{conj}\left(\sum_{j=10}^N \mathbf{U}_j \mathbf{U}_j^H\right)$

Distribution of eigenvalues

$\text{TRO} = \text{Conj}(\mathbf{R})$


Numerical demonstration of reverberation focusing and nulling

Simultaneous, two points reverberation nulling



FAF-00: Echo enhancement experiment (bi-static)

Experimental results including an artificial target show improved target detectability with the time reversal method. An air-filled tube was used as an artificial target. The broad area around 4.2 sec is the direct arrival from the SRA to VRA. An echo is visible around 4.52 sec using time reversal in (b).




Air-filled tube



FAF-03 Reverberation Nulling Experiment

The SRA was moored in water depth of 105 m close to the Elba Island. A seamount at 2.5 km range is visible in the bottom topography (small black circle) which provides a good candidate for reverberation nulling.



The upper plots are BS reverberation return (before). The resulting reverberation nulling (after) is superimposed in (d), indicating the reduction of reverberation level at 2.5 km range to the background level by 2 dB. On the other hand, the reverberation return from the interaction with the island has increased at 5.8 km range.

References

- Kim et al., "Echo-to-reverberation enhancement using a time reversal mirror," *JASA* (in press).
- Song et al., "Environmentally adaptive reverberation nulling using a time reversal mirror," submitted to *JASA*.
- Song et al., "Experimental demonstration of adaptive reverberation nulling using a time reversal mirror," submitted to *JASA*.

Report Documentation Page				Form Approved OMB No. 0704-0188	
Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.					
1. REPORT DATE 20 DEC 2004		2. REPORT TYPE N/A		3. DATES COVERED -	
4. TITLE AND SUBTITLE Adaptive Reverberation Nulling Using a Time Reversal Mirror				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S)				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) MPL/SIO, UCSD				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release, distribution unlimited					
13. SUPPLEMENTARY NOTES See also, ADM001741 Proceedings of the Twelfth Annual Adaptive Sensor Array Processing Workshop, 16-18 March 2004 (ASAP-12, Volume 1)., The original document contains color images.					
14. ABSTRACT					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT UU	18. NUMBER OF PAGES 2	19a. NAME OF RESPONSIBLE PERSON
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified			

Adaptive Reverberation Nulling Using a Time Reversal Mirror

Hee-Chun Song, William S. Hodgkiss, and William A. Kuperman

MPL/SIO, UCSD

phone: 858-534-0954

email: hcsong@ucsd.edu

email: wsh@mpl.ucsd.edu

email: wak@mpl.ucsd.edu

S. Kim

ADD

email: sikim@add.re.kr

Abstract Typically, active sonar systems operate in reverberation-limited ocean environments. The focusing capability of a time reversal mirror (TRM) suggests two different approaches. First, a TRM focuses acoustic energy on a target enhancing the target echo while shadowing the boundaries below and above the focus in a waveguide, thereby reducing reverberation. The resulting echo-to-reverberation enhancement has been demonstrated experimentally using a time reversal mirror in the 3–4-kHz band in shallow water. The second approach is reverberation nulling to enhance target detectability. The idea is to minimize the acoustic energy incident on the corresponding scattering interface by applying an excitation weight vector, which is in the complementary subspace orthogonal to the time-gated reverberation focusing vector. Both numerical simulations and experimental results illustrate the potential of reverberation nulling using a time reversal mirror.