

Body Dynamics Computer Modeling:

Prototyping of Safety Systems and Laboratory Tests

Ed Sieveka, Ph.D.
NAVAIR Human Systems Department
Crashworthy Systems Branch
4.6.7.2

Report Documentation Page				Form Approved OMB No. 0704-0188	
Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.					
1. REPORT DATE SEP 2004		2. REPORT TYPE N/A		3. DATES COVERED -	
4. TITLE AND SUBTITLE Body Dynamics Computer Modeling: Prototyping of Safety Systems and Laboratory Tests				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S)				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) NAVAIR Human Systems Department Crashworthy Systems Branch 4.6.7.2 47123 Buse RD Patuxent River, Md.				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release, distribution unlimited					
13. SUPPLEMENTARY NOTES Published in the Proceedings of the Forty Second Annual SAFE Association Symposium, Held in the Salt Lake City, Utah, September 27-28, 2004. SAFE Association, Post Office Box 130, Creswell, OR 97426-0130. http://www.safeassociation.org. , The original document contains color images.					
14. ABSTRACT					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT SAR	18. NUMBER OF PAGES 24	19a. NAME OF RESPONSIBLE PERSON
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified			

Modeling and Simulation: A Crashworthy Systems Perspective

1. How does the human body move during highly dynamic events?
2. What loads does the body experience?
3. How can motion be controlled and loads reduced to enhance safety and survivability?

Modeling and Simulation: Specifics for System or Experiment Prototyping

1. What limits on body motion are acceptable for a safety system?
2. What range-of-motion must be accommodated by a proposed test fixture?
3. What are the approximate peak loads on the body and the equipment?
4. For systems, how well do various approaches control motion and reduce loads?
5. For experiments, what safety precautions are needed to protect test dummies and equipment?



Understanding Motion: Kinematics Visualization is a Powerful Prototyping Tool

- Highly dynamic events are hard to visualize and comprehend because they are so beyond our everyday experience
- Modeling lets us “experience” these events so that our search for safety improvements, or our experiment design, is bounded by actual kinematics

Simulation Examples: MADYMO™ Models

(Pictures and Videos Produced with the HyperView™ Postprocessor)

H-60 Cockpit & Pilot: *Crash Protection System*




Ejection Seat Parachute Opening Snatch Loads: *Horizontal Accelerator (HA) Test*




H-60 Cabin & Mobile Crewman: *Safety Tether System*

H-60 Cockpit & Pilot: Crash Protection System




H-60 Cockpit & Pilot: Model Components




H-60 Cockpit & Pilot: Crash Protection System Performance in a 36G, 30° Pitch-down Crash


Standard Harness and Energy-absorbing Seat



Inflating Harness and Energy-absorbing Seat



H-60 Cockpit & Pilot: Maximum Head Flail in a 36G, 30° Pitch-down Crash



Standard Harness and
Energy-absorbing Seat


Inflating Harness and
Energy-absorbing Seat



H-60 Seahawk Cabin & Mobile Crewman: Mission Environment



H-60 Cabin & Mobile Crewman: Model Components




Current System with Full-Length Tether: Medium Severity Crash (10G Vertical, 10G Horizontal at 45°)




Current System with Short Tether: Medium Severity Crash (10G Vertical, 10G Horizontal at 45°)

Time = 0.000000




New System with Retractor and Better Anchor Point:


Medium Severity Crash (10G Vertical, 10G Horizontal at 45°)



Future Safety Tether Improvements: Connect Tether to Lifting Harness




Chest Strap Tether vs. Harness Tether: Torso Excursion and Chest Compression




Harness Interface

Chest Strap Interface




Ejection Seat Parachute Opening Snatch Loads: Horizontal Accelerator (HA) Test

Time = 0.000000




Ejection Seat Parachute Opening Snatch Load Test: Model Components




Parachute Opening Snatch Load Test: Phases


Initial



Snatch



Catch



Snatch Load Test: 30° Pitch Simulation (Sled Reference Frame)

Time = 0.000000




Snatch Load Test: 90° Pitch Simulation **without Safety Tethers** (Sled Reference Frame)

Time = 0.000000



Snatch Load Test: 90° Pitch Simulation **with Safety Tethers** (Sled Reference Frame)

Time = 0.000000



Conclusions:

Benefits of Modeling and Simulation for Safety System Prototyping

- Understand the safety issues
- Evaluate current system performance
- Establish realistic performance bounds
- Explore potential improvements

Conclusions:

Benefits of Modeling and Simulation for Lab Experiment Prototyping

- Conceptualize proposed experiment
- Evaluate probable dynamics and loads
- Guide fixture fabrication
- Establish realistic test parameters
- Provide a reality check for test results