

Mixed analytical/numerical method applied to the low Reynolds number k -epsilon turbulence model

T. Du¹, Z. N. Wu²

1. Department of Engineering Mechanics, Tsinghua University, Beijing 100084, P.R. China
Dutao00@mails.tsinghua.edu.cn
2. Department of Engineering Mechanics, Tsinghua University, Beijing 100084, P.R. China
ziniuwu@mails.tsinghua.edu.cn

Abstract

A mixed analytical/numerical method is developed here to solve the low Reynolds number k -epsilon turbulence model. In this method the advection-diffusion part is solved numerically, while the source terms are split into two parts: one part is solved analytically and the next is solved numerically.

Keyword: Mixed analytical/numerical method, k -epsilon turbulence model, low Reynolds number, source term

1. Introduction

Because of the recent enormously progress in the capability of computers, low Reynolds two-equation turbulent models become more and more welcome in engineering fluid computation. In the past, various forms of low-Reynolds-number k - ϵ turbulent models have been proposed. The detail of two-equation models and low Reynolds corrections are presented in Chapter 14 (Turbulence Modeling and Simulation) of handbook [1].

Though mathematically the k - ϵ model is well-posed[2], the strong nonlinearities may interact with numerical errors in such a way that computation may break down easily. A typical behavior of unstable computations involves the loss of positivity of k or ϵ , though the original differential equations have positive solution [3]. The appearance of negative values changes the sign of several terms in the models, so that turbulent quantities may increase unboundedly [4]. Even though the two turbulence equations can be solved exactly in the same manner as the mean flow equations, it has been found that such a method often leads to an unstable solution, or even incorrect solutions [5]. The damping functions in the low Reynolds turbulent models improve the model prediction capability for near wall flow, but also introduce more severe numerical stiffness for the source terms.

There are a huge amount of numerical methods for compressible Navier-Stokes equations coupled with two equation models [6-9]. The two-equation turbulent model is a typical example of partial differential equations with source terms. Great progress has been made in efficient treatment of the source terms [10-12]. Helzel, LeVeque, and Warnecke [12] treated chemical reacting flow with an Arrhenius law for the source term by mixed method in detonation waves computation. In [13], a mixed analytical/numerical method for oscillating source terms has studied. In this method the advection-diffusion part and the source terms are treated separately through operator splitting. The advection-diffusion part (PDE) is integrated numerically while the source term part (ODE) is integrated analytically. Hence this method is called mixed analytical/numerical method. The mixed method performs well for partial differential equations with source terms, in which the time scale of source term (S-scale, denoted T_S) is much smaller than the mean flow scale (M-Scale, denoted T_M) inherent to the advection-diffusion part. Furthermore, the mixed method has been extended to the implicit solution of high Reynolds number and compressible turbulent flows[14]. Numerical results show the mixed method can give robust, steady and fast convergent solution.

In this paper, we extend the mixed method to low Reynold number turbulent models. The essential new feature of the mixed method for low Reynolds number turbulent models lies in the treatment of the source terms which contain new damping functions. With respect to the high Reynolds number counterpart, the low Reynolds number turbulent models retain the

Report Documentation Page				Form Approved OMB No. 0704-0188	
Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.					
1. REPORT DATE 15 APR 2005		2. REPORT TYPE N/A		3. DATES COVERED -	
4. TITLE AND SUBTITLE Mixed analytical/numerical method applied to the low Reynolds number k-epsilon turbulence model				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S)				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Department of Engineering Mechanics, Tsinghua University, Beijing 100084, P.R. China				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release, distribution unlimited					
13. SUPPLEMENTARY NOTES See also ADM001800, Asian Computational Fluid Dynamics Conference (5th) Held in Busan, Korea on October 27-30, 2003., The original document contains color images.					
14. ABSTRACT					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT UU	18. NUMBER OF PAGES 7	19a. NAME OF RESPONSIBLE PERSON
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified			

original source terms modified with damping factors and sometimes contain additional damping terms. In the mixed method proposed in this paper, the damping factors are treated as constant at each time step, so that the main part of the source terms are still analytically integrable at each time step. The additional damping terms are treated numerically.

2. Governing Equations

The governing equations are obtained by Favre Averaging the Navier-Stokes equations and modeling the Reynolds stress. In conservative form these equations are written as

$$\frac{\partial U}{\partial t} + \frac{\partial F_c}{\partial x} + \frac{\partial G_c}{\partial y} = \frac{\partial F_v}{\partial x} + \frac{\partial G_v}{\partial y} \quad (1)$$

In this paper, we use the Hwang-Lin low-Reynolds number k - $\mathcal{E}$ turbulence model^[14] as example.

$$\frac{\partial U^T}{\partial t} + \frac{\partial F_c^T}{\partial x} + \frac{\partial G_c^T}{\partial y} = \frac{\partial F_v^T}{\partial x} + \frac{\partial G_v^T}{\partial y} + S \quad (2)$$

where

$$U^T = \begin{bmatrix} \rho k \\ \rho \mathcal{E} \end{bmatrix} \quad F_c^T = \begin{bmatrix} \rho u k \\ \rho u \mathcal{E} \end{bmatrix} \quad G_c^T = \begin{bmatrix} \rho v k \\ \rho v \mathcal{E} \end{bmatrix}, \quad (3)$$

$$F_v^T = \begin{bmatrix} \left(\mu + \frac{\mu_t}{\sigma_k} \right) \frac{\partial k}{\partial x} \\ \left(\mu + \frac{\mu_t}{\sigma_\varepsilon} \right) \frac{\partial \mathcal{E}}{\partial x} \end{bmatrix} \quad G_v^T = \begin{bmatrix} \left(\mu + \frac{\mu_t}{\sigma_k} \right) \frac{\partial k}{\partial y} \\ \left(\mu + \frac{\mu_t}{\sigma_\varepsilon} \right) \frac{\partial \mathcal{E}}{\partial y} \end{bmatrix} \quad (4)$$

and

$$S = \begin{bmatrix} P_k - \rho \mathcal{E} + \Pi \\ f_1 C_{\varepsilon 1} \frac{\mathcal{E}}{k} P_k - f_2 C_{\varepsilon 2} \frac{\rho \mathcal{E}^2}{k} + \xi \end{bmatrix} \quad (5)$$

The production term P_k is given by

$$P_k = \mu_t \left(\frac{\partial U_i}{\partial x_k} + \frac{\partial U_k}{\partial x_i} \right) \frac{\partial U_i}{\partial x_k} \quad (6)$$

The eddy viscosity is calculated as

$$\mu_t = f_\mu C_\mu \rho k^2 / \mathcal{E} \quad (12)$$

The functions Π and ξ are defined as

$$\Pi = -\frac{1}{2} \frac{\partial}{\partial x_j} \left(\nu \frac{k}{\varepsilon} \frac{\partial D}{\partial x_j} \right), \quad \xi = -\frac{1}{2} \frac{\partial}{\partial x_j} \left(\nu \frac{\mathcal{E}}{k} \frac{\partial k}{\partial x_j} \right) \quad (13)$$

The coefficients and damping functions are

$$C_\mu = 0.09, \quad C_{\varepsilon 1} = 1.44, \quad C_{\varepsilon 2} = 1.92$$

$$f_\mu = 1 - \exp[-0.01 y_\lambda - 0.008 y_\lambda^3]$$

$$\sigma_k = 1 - \exp[-0.01 y_\lambda - 0.008 y_\lambda^3], \quad \sigma_\varepsilon = 1.3 - 1.0 \exp[-y_\lambda / 10]$$

$$f_1 = 1.0, \quad f_2 = 1.0$$

$$\varepsilon = \mathcal{E} \left(1 + 2 \nu \left(\frac{\partial \sqrt{k}}{\partial y} \right)^2 \right)$$

where $y_\lambda = \frac{y}{\sqrt{\nu k} / \mathcal{E}}$

3. Numerical Method

The two set equations (1) and (2) are solved separately. The convective numerical flux at the cell interface is evaluated using Roe's approximated Riemann solver with MUSCL treatment

to achieve second order accuracy. The simplified multistage scheme with four stages is applied to advance in time.

The advection-diffusion part of the two-equation model is discretized in the same way as for the Navier-Stokes equations. Only the source term needs special treatment. The numerical treatment of source terms of the turbulence model equations is of mayor importance for the stability of this scheme[16]. The fundamental means is to treat the negative source terms implicitly and the positive terms explicitly[7]. However, the time step still has to be small enough in order to obtain realistic values of k , ε and μ_t . According to the different treatment for Jacobian matrix for implicit part, there are three method: point implicit method[6], approximate Jacobian method[5,17] and exact Jacobian method[18]. In this paper, we adopt the second method.

4. Mixed Analytical/numerical Method for low Reynolds number turbulent models

The turbulence model equations contain advection-diffusion operators and source terms. In the mixed method the advection diffusion part (PDE) is integrated numerically, while the source term (ODE) is integrated analytically.

4.1 Treatment of the source terms

For the case of low Reynolds number models it is not always possible to integrate the source terms analytically. With respect to the high Reynolds number counterpart, the low Reynolds number turbulent models retain the original source terms modified with damping factors and sometimes contain additional damping terms. In the mixed method proposed in this paper, the damping factors are treated as constant at each time step, so that the main part of the source terms are still analytically integrable at each time step. The additional damping terms are treated numerically.

Following the original construction of the mixed method, we first consider the ODE due to the source terms

$$\frac{dU^T}{dt} = S_s(U) + S_D(U) \quad (7)$$

Here $S_s(U)$ is the standard part which is similar to the source term of the high Reynolds number model, modified only by adding damping factors, and $S_D(U)$ stands for the additional damping terms. Precisely, $S_s(U)$ is defined by

$$S_s(U) = \begin{pmatrix} P_k - \rho \mathcal{E} \\ f_1 C_{\varepsilon 1} \frac{\rho \mathcal{E}}{k} P_k - f_2 C_{\varepsilon 2} \frac{\rho \mathcal{E}^2}{k} \end{pmatrix} \quad (8)$$

The additional damping terms $S_D(U)$ are treated numerically, while the standard part $S_s(U)$ is solved analytically by considering the following ODE

$$\begin{cases} \frac{d \rho k}{dt} = P_k - \rho \mathcal{E} \\ \frac{d \rho \mathcal{E}}{dt} = C'_{\varepsilon 1} P_k \frac{\rho \mathcal{E}}{k} - C'_{\varepsilon 2} \frac{\rho \mathcal{E}^2}{k} \end{cases} \quad (9)$$

with the parameters

$$C'_{\varepsilon 1} = f_1 C_{\varepsilon 1} \quad C'_{\varepsilon 2} = f_2 C_{\varepsilon 2} \quad C'_\mu = f_\mu C_\mu$$

treated as constant at each time step. Hence the standard part should have the same form of analytical solution as the high Reynolds number model[13], and this analytical solution for (16) can be written as

$$\rho k = K \left((\rho k)_0, (\rho \mathcal{E})_0, t \right) = (\rho k)_0 2^\alpha F^\gamma \left(\frac{G}{\frac{1}{\zeta} \Psi_0} \right)^{-\beta} \exp(-\delta \sqrt{\Phi} t) \quad (10)$$

$$\rho \mathcal{E} = E \left((\rho k)_0, (\rho \mathcal{E})_0, t \right) = (\rho \mathcal{E})_0 2^\alpha F^\nu \left(\frac{G}{\frac{1}{\zeta} \Psi_0} \right)^{-\tau} \exp(-\delta \sqrt{\Phi} t) \quad (11)$$

where

$$\begin{aligned}
 F &= 1 - \frac{1}{\zeta} \Psi_0 + \left(1 + \frac{1}{\zeta} \Psi_0\right) \exp\left(2\mu\sqrt{\Phi}t\right) \\
 G &= \frac{1}{\zeta} \Psi_0 - 1 + \left(1 + \frac{1}{\zeta} \Psi_0\right) \exp\left(2\mu\sqrt{\Phi}t\right) \\
 \Psi_0 &= \frac{k_0}{\varepsilon_0} \Phi^{\frac{1}{2}} \\
 \aleph &= \sqrt{(C'_{\varepsilon 2} - 1)C'_\mu(C'_{\varepsilon 1} - 1)}, \quad \zeta = \sqrt{\frac{C'_{\varepsilon 2} - 1}{C'_\mu(C'_{\varepsilon 2} - 1)}}, \quad \beta = \frac{1}{C'_{\varepsilon 2} - 1} \\
 \alpha &= \frac{C'_{\varepsilon 1} - C'_{\varepsilon 2}}{(C'_{\varepsilon 2} - 1)(C'_{\varepsilon 1} - 1)}, \quad \zeta = \frac{1}{C'_{\varepsilon 1} - 1}, \quad \sigma = \frac{C'_\mu(C'_{\varepsilon 2} - C'_{\varepsilon 1})}{\sqrt{(C'_{\varepsilon 2} - 1)C'_\mu(C'_{\varepsilon 1} - 1)}} \\
 \delta &= \frac{C'_\mu(C'_{\varepsilon 2} - C'_{\varepsilon 1})}{\sqrt{(C'_{\varepsilon 2} - 1)C'_\mu(C'_{\varepsilon 1} - 1)}}, \quad \varpi = \frac{C'_{\varepsilon 2}}{C'_{\varepsilon 2} - 1} \\
 \varsigma &= \frac{C'_{\varepsilon 1} - C'_{\varepsilon 2}}{(C'_{\varepsilon 2} - 1)(C'_{\varepsilon 1} - 1)}, \quad \upsilon = \frac{C'_{\varepsilon 1}}{C'_{\varepsilon 1} - 1}
 \end{aligned}$$

Here k_0 and ε_0 stand for initial value of turbulent kinetic energy k and dissipation rate ε .

4.2 Mixed method

Now the mixed method for low Reynolds number models can be written as

$$\left(I - \Delta t \cdot [A]^n\right) \Delta(U^T)^n = \Delta t \cdot R_j^n + \bar{S}_s\left((U^T)^n\right) + S_d\left((U^T)^n\right) \quad (12)$$

where $S_d((U^T)^n)$ is due to the additional damping terms, and $\bar{S}_s((U^T)^n)$ is the analytical solution of the ODE due to the standard source terms. This analytical solution, when limited, can be written as

$$\bar{S}_s\left((U^T)^n\right) = \begin{bmatrix} \min\left(K\left((\rho k)_j^n, (\rho \varepsilon)_j^n, \Delta t\right) - (\rho k)_j^n, \delta\right) \\ \min\left(E\left((\rho k)_j^n, (\rho \varepsilon)_j^n, \Delta t\right) - (\rho \varepsilon)_j^n, \delta\right) \end{bmatrix} \quad (13)$$

The parameter δ limits the maximum of the source term integral. The choice of $\delta=0.1$ works well in our numerical experiments.

5. Numerical Results

5.1 Flat plate

We first calculate a turbulent flow past a flat plane. The grid is 80×41 . The distance of the first grid next to the wall is no more than $y^+ = 0.45$. The Reynolds number is $Re = 1.0 \times 10^7$, the inflow Mach number is $Ma = 0.2$. The convergence history of mixed method is compared with that of traditional method in Fig.1. The latter can't converge with the same condition. The inner layer velocity profile of flat plane flow is shown in Fig.2, comparing the van Driest's and Spalding's theory. The figure gives the velocity profile of 7 sites in x direction. The agreement is also good.

5.2 Transonic Diffuser

Consider transonic flow with a weak shock through a converging diverging diffuser^[19]. This configuration has an entrance to throat area ratio of 1.4, an exit to throat area ratio of 1.5. The corresponding Reynolds number is 9.370×10^5 and the Mach number is $M_{in} = 0.9$. The total pressure at inflow is 1.349×10^5 Pa, the static pressure at the outflow is 1.11×10^5 Pa. These flows were characterized by the ratio, R , of exit static to inflow total pressure. For the weak-shock case the value of R was 0.82.

Mixed analytical/numerical method applied to the low Reynolds number k-epsilon turbulence model explicit computation

The convergence history is shown in Fig.3, comparing that with traditional method. We see the computation with traditional method fails to converge, while the mixed method not only converge steadily, but also converge faster than the traditional method.




Fig.1

Fig.1. Comparative convergence history for flat plane




Fig.2

Fig.2. Velocity profile of flat plate flow




Fig.3

Fig.3. Comparative convergence history for transonic diffuser




Fig.4

Fig.4 Velocity profiles at four axial locations for transonic diffuser

5.3 RAE2822 Airfoil

The RAE2822 airfoil has been extensively used for the validation of Navier-Stokes codes applied to transonic flow. The key flow condition for this test case is: Free stream Mach Number $Ma_\infty=0.73$, Reynolds number $Re=6.5 \times 10^6$, and angle of attack in degree $\alpha=3.19$. The convergence histories with mixed method and with conventional numerical method are compared in Fig.5. The first one converges faster. The pressure coefficient and skin friction coefficient with experimental results are shown in Fig.6 and Fig.7 respectively, comparing the conventional method results. The numerical results with mixed method agree with experiment data.




Fig. 5

Fig. 5. Comparative convergence history for RAE2822 airfoil




Fig.6

Fig. 6. The pressure coefficient profiles of RAE2822 airfoil




Fig. 7. The skin friction coefficient profiles of RAE2822 airfoil

5.4 NLR7301 Wing-flap Airfoil

The flow around the two-element NLR7301 airflow with 2.6% gap has been computed for the flow condition: $Re=2.51 \times 10^6$ and angle of attack $\alpha=13.1$. Fig.8 gives the pressure distribution on wing and flap.




Fig. 8. The pressure coefficient profiles of NLR7301 airfoil

6. Concluding Remarks

The mixed analytical/numerical method has been extended to the numerical solutions of low Reynolds number $k-\epsilon$ turbulence models. The mixed method is applied to Hwang-Lin low Reynolds turbulent model and several test problems. The numerical results show that the mixed method is numerically more robust than the traditional pure numerical method.

References:

- [1] Johnson R.W., "The handbook of fluid dynamics", CRC Press (1998).
- [2] Mohammadi B. and Pironneau O., "Analysis of the K-epsilon turbulence model", Wiley Masson, (1994).
- [3] Wu Z.N. and Fu S., "Positivity of k-epsilon turbulence models for incompressible flow", *Mathematical Model & Methods in Applied Science*, Vol..12, No.3, (2002), pp.393-406.
- [4] Lew A.J., Buscaglia G.C. and Carrica PMA, "Note on the numerical treatment of the k-epsilon turbulence model", *International Journal of Computational Fluid Dynamics*, Vol..14, (2001), pp.201-209.
- [5] Zhao Y., "Stable computation of turbulent flow with a low-Reynolds-number K- ϵ turbulence model and explicit solver", *Advances in Engineering Software*, Vol..28, (1997), pp.487-499.
- [6] Vandromme D. and Ha Minh H., "About the coupling of turbulence closure models with averaged Navier-Stokes equations", *Journal of Computational Physics*, Vol..65, No.2, (1986), pp.384-409.
- [7] Huang P.G. and Coakley T.J. AIAA paper92-0547, *AIAA 30th Aerospace Sciences Meeting*, Reno, NV, 1992.
- [8] Merci B., Steelant J. etl, "Computational treatment of source terms in two-equation turbulence models", *AIAA Journal*, Vol..38, No.11, (2000), pp.2085-2093.
- [9] Kunz R.F. and Lakshminarayana B., "Stability of explicit Navier-Stokes procedures using $k-\epsilon$ and $k-\epsilon$ algebraic Reynolds stress turbulence models", *Journal of Computational Physics*, Vol.103, (1992), pp.141-159.
- [10] Bermudez L. and Vazquez M.E., "Upwind methods for hyperbolic conservation laws with source terms", *Computers and Fluids*, Vol 23, (1994), pp.1049-1071.

Mixed analytical/numerical method applied to the low Reynolds number k-epsilon turbulence model explicit computation

- [11] Greenberg J.M. and Le Roux A.-Y., "A well-balanced scheme for the numerical processing of source terms in hyperbolic equations", *SIAM Journal on Numerical Analysis*, Vol..33, (1996), pp.1-16.
- [12] Helzel C., LeVeque R.J., and Warnecke G., "A modified fractional step method for the accurate approximation of detonation waves", *SIAM Journal on Scientific Computing*, Vol..22, (2000), pp.1489-1510.
- [13] Du T., Shi J. and Wu Z.N., "Mixed analytical/numerical method for flow equations with a source term", *Computers & Fluids*, Vol..32, (2003), pp.659-690, June.
- [14] Du T. and Wu Z.N., "Mixed analytical/numerical method applied to the high Reynolds number $k-\epsilon$ turbulence model", 2002,(submitted)
- [15] Hwang C.B. and Lin C.A., Improved low-Reynolds-number model based on Direct Numerical Simulation data, *AIAA Journal*, Vol.36, No.1 pp.38-43, 1998.
- [16] Bardina J.B., Huang P.G. and Coakley T.J., Turbulence modeling validation, testing, and development. NASA TM-110446, April 1997
- [17] Steelant J. and Dick E., A multigrid method for the compressible Navier-Stokes equations coupled to the $k - \epsilon$ turbulence equations. *International Journal of Numerical Methods in Heat and Fluid Flow* 4:99-113,1994
- [18] Merke,C.L. Deshpande,M. and Venkateswaran,S. Efficient implementation of turbulence modeling in computational schemes. *Proceedings of the Second U.S. National Congress on Computational Mechanics*, Pergamon Oxford, 1993
- [19] Sajben M. and Kroutil J.C., Effects of initial boundary-layer thickness on transonic diffuser flows. *AIAA Journal*, 1981:19:1386-1393