



Enhancement of Visual Target Detection With Night Vision Goggles

by William A. Monaco, Rachel A. Weatherless, and Joel T. Kalb

ARL-TR-3809

June 2006

NOTICES

Disclaimers

The findings in this report are not to be construed as an official Department of the Army position unless so designated by other authorized documents.

Citation of manufacturer's or trade names does not constitute an official endorsement or approval of the use thereof.

DESTRUCTION NOTICE—Destroy this report when it is no longer needed. Do not return it to the originator.

Army Research Laboratory

Aberdeen Proving Ground, MD 21005-5425

ARL-TR-3809**June 2006**

Enhancement of Visual Target Detection With Night Vision Goggles

William A. Monaco, Rachel A. Weatherless, and Joel T. Kalb
Human Research and Engineering Directorate, ARL

REPORT DOCUMENTATION PAGE				Form Approved OMB No. 0704-0188	
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing the burden, to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.					
1. REPORT DATE (DD-MM-YYYY) June 2006		2. REPORT TYPE Final		3. DATES COVERED (From - To) March 2004 through September 2005	
4. TITLE AND SUBTITLE Enhancement of Visual Target Detection With Night Vision Goggles				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S) William A. Monaco, Rachel A. Weatherless, and Joel T. Kalb (all of ARL)				5d. PROJECT NUMBER 622716H70	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army Research Laboratory Human Research and Engineering Directorate Aberdeen Proving Ground, MD 21005-5425				8. PERFORMING ORGANIZATION REPORT NUMBER ARL-TR-3809	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution is unlimited.					
13. SUPPLEMENTARY NOTES					
14. ABSTRACT IMPRINT (Improved Performance Research Integration Tool) was developed by the Army as a model to predict human performance in specific operational settings. This report describes an initial effort to quantify visual acuity improvement with the use of night vision goggles (NVGs) in a manner that could be incorporated into the IMPRINT model. Visual acuity was compared with NVGs and without NVGs under five specific luminance levels that the Soldier may encounter in actual battle environments. These data were then translated for use in a predictive equation for target detection. The quantified differences in Soldier target detection performance may then be applied to the IMPRINT model.					
15. SUBJECT TERMS LogMar acuity; modeling; night vision goggles; vision performance					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT SAR	18. NUMBER OF PAGES 20	19a. NAME OF RESPONSIBLE PERSON William A. Monaco
a. REPORT Unclassified	b. ABSTRACT Unclassified	c. THIS PAGE Unclassified			19b. TELEPHONE NUMBER (Include area code) 410-278-5984

Contents

List of Figures	iv
List of Tables	iv
1. Introduction	1
2. Methods	2
2.1 Task	2
2.2 Experimental Design	2
2.3 Participants	3
2.4 Apparatus.....	3
2.4.1 Visual Screening.....	3
2.4.2 NVG	3
2.4.3 Chart Illumination	3
2.4.4 Photometric Equipment.....	3
2.5 Procedure.....	3
3. Results	5
4. Discussion	10
5. Conclusions	11
6. References	12
Glossary of Terms	13
Distribution List	15

List of Figures

Figure 1. The USAF 1951 tri-bar resolution chart used in this study.....	2
Figure 2. Plots are shown for 95% confidence intervals on predictions made by a linear regression model based on subject logMAR acuity for the four highest luminance levels.....	7
Figure 3. Plots are shown for 95% confidence intervals on predictions made by a linear regression model based on subject logMAR acuity for five luminance levels.....	8
Figure 4. Example depicting the differences between binocular visual acuity with and without NVGs at the five selected luminance levels.	11

List of Tables

Table 1. The 30 steps needed to obtain unaided acuity measures.	5
Table 2. Detection range for targets viewed with and without NVGs during quarter moon luminance conditions.	10

1. Introduction

IMPRINT (Improved Performance Research Integration Tool) (1,2) is a modeling and analysis tool that was developed by the U.S. Army Research Laboratory's (ARL's) Human Research and Engineering Directorate. IMPRINT is a dynamic modeling tool that uses data from a specific operational mission that has been divided into a flow of task events to accomplish the mission. A number of human performance factors may be incorporated into specific task sequences. Visual performance is one parameter that may require quantification in an IMPRINT model. Vision data, with and without night vision goggles (NVGs) in a selected range of nighttime conditions, could be incorporated into a model as one task event in a specific task sequence. Task sequences are used to effectively represent and analyze Soldier performance of a given operational scenario during a wide variety of environmental stressors.

The focus of this experiment is to quantify the degree of improvement of visual performance with NVGs, relative to unaided vision and to generate predictive data for use in the IMPRINT model. Currently, there is a need to generate data for incorporation into models of human performance that reflect the manner and extent of improvement derived with NVGs. For example, the accuracy and speed of target acquisition may be improved with NVGs. Our data demonstrate that a visual performance advantage is derived from NVGs over unaided vision in very dark settings. The data generated from this research effort may be incorporated into a predictive model such as IMPRINT. The modeler may use the quantified degree of visual acuity improvement when using NVGs instead of unaided vision in specific light levels. These visual acuity data may then be translated into a target detection scenario in a manner that predicts human detection performance for specific targets.

This experiment specifically quantifies the potential enhancement of visual performance gained with NVGs over five luminance levels ranging from 4.6E-05 footlamberts (fL) (approximately starlight) to 1.00E-03 fL (approximately a quarter moon). These light levels were selected because they represent the levels where parallel data could be obtained for aided and unaided visual performance while Soldiers are working at the limit of the unaided dark adapted eye. These data may have future applications for creating predictive visual models for determining the ranges at which targets may be detected, recognized, or identified with the NVGs. Further, our data provide a means of comparing target ranges of an observer with NVGs to those of an observer without NVGs. Differences between aided and unaided night vision may allow us to assess the ability of an observer to detect and recognize the location and direction of objects relative to himself or the objects to each other. Early target detection and localization are important to the process of perception of visual space and may facilitate safer navigation in complex operational settings. We have measured distinctions in visual capability with and without NVGs and we will demonstrate how our derived visual model may be incorporated into IMPRINT.

2. Methods

2.1 Task

To measure visual acuity in low light levels, this experiment used the high contrast form of the U.S. Air Force (USAF) 1951 tri-bar resolution chart shown in figure 1. The tri-bar chart consists of six groups of six “elements”; the elements contain three vertical and three horizontal bars. The six elements in each successive group are half the size of the elements in the preceding group. To complete the tri-bar task in this experiment, the observer reported the smallest group and element number where s/he could see the element’s horizontal or vertical bars distinctly. The size of the tri-bar chart was 1 square meter.




Figure 1. The USAF 1951 tri-bar resolution chart used in this study.

2.2 Experimental Design

A within-subjects design was used for this study. Three independent variables were manipulated: *view type*, *ocular type*, and *light level*. The *view-type* variable consisted of two levels; for the “aided” level, the observers wore an NVG to view the tri-bar chart. For the “unaided” level, the observers viewed the tri-bar chart directly. The *ocular-type* variable consisted of the three levels. The participant viewed the tri-bar chart with his left eye only, right eye only, or with both eyes. The *light-level* variable consisted of five levels: 4.60E-05, 1.00E-

04, 2.20E-04, 4.60E-04, and 1.00E-03 fL. These values represented a light level as dark as starlight to a light level as bright as a quarter moon.

2.3 Participants

Eight female and six male college students participated in this study. All observers were between 19 and 28 years of age. Each observer had 20/30 or better visual acuity (with or without correction) in each eye and normal stereopsis and color vision. Ten of the observers were from Morgan State University in Baltimore, Maryland; the other four observers were from colleges outside Baltimore.

2.4 Apparatus

2.4.1 Visual Screening

All vision screening tests were performed with the Titmus¹ vision tester.

2.4.2 NVG

The NVG used for this experiment was the AN/AVS-9², model F4949G, a binocular NVG. The goggle's resolution was 1.2 cycles/milliradian (approximately 20/30 acuity), with a circular 40-degree field of view and 1X magnification.

2.4.3 Chart Illumination

The tri-bar chart was back-lit with incandescent tungsten lamps of various wattages. All bulbs approximated a 2856 Kelvin black-body spectral composition. The experimenter precisely controlled the light levels by turning on or off combinations of switches to obtain the five light levels. The output produced by the chart illuminator was measured with a precisely calibrated radiometer.

2.4.4 Photometric Equipment

A model IL-1700 research radiometer was used to ensure that the light levels produced by the light level board were accurate. The actual footlambert readings were recorded for each data point taken.

2.5 Procedure

When the observer arrived for testing, s/he read and signed a certificate of informed consent. Next, his or her vision was screened to determine if the vision requirements were met. When the

¹Titmus is a registered trademark of Titmus Optical.

²AN/AVS stands for Army Navy/airborne visual search equipment.

observer began the tri-bar portion of the study, the experimenter started the process with training that included procedures for focusing the goggles. The observer was then told how to view the chart through the left or through the right ocular of the NVG to obtain a monocular view.

Each observer then received training in how to read the tri-bar chart. The experimenter evaluated the observer's understanding of this training by pointing to a group and element combination on the tri-bar chart and requiring the observer to state the appropriate group and element number. This training continued until the observer reported six consecutive correct answers. The duration of this training was usually about 10 minutes.

Next, the observer was seated facing the tri-bar chart so that the tri-bar chart was positioned perpendicular to the observer's line of sight. The observer sat 3.86 meters from the chart. (This viewing distance was selected so that the smallest element on the tri-bar chart corresponded to 20/10 Snellen acuity and the largest element corresponded to 20/570 Snellen acuity.) Next, the observer adapted to the dark for 30 minutes.

In this experiment, we progressively enhanced the thresholds for acuity by increasing levels of both independent variables, that is, by wearing the NVG and also by increasing the light levels. Because of this inherent enhancement feature of the independent variables, a counterbalancing scheme for exposing levels of the independent variables to the observers would have been prohibitive³. In other words, lower levels of illumination could not follow higher levels without some time needed for the observers to adapt to the dark. Likewise, allowing the observers to view the chart with the NVG might affect an honest assessment of what s/he could actually see when asked to view the chart without the goggle. The experimenter therefore presented the experimental conditions in the order given in table 1 for the unaided condition. These same 30 steps were repeated for these same observers for the aided condition. Specifically, the experimenter illuminated the chart at the lowest light level. While viewing the chart with the left eye only, the observer reported the smallest discernible group and element number. The observer then stated the smallest discernible group and element number by viewing the chart with the right eye only, and finally the observer stated the smallest discernible group and element number by viewing the chart with both eyes. These three steps were then repeated. The experimenter recorded the responses along with the actual light levels produced by the chart illuminator for that trial. Next, the experimenter illuminated the chart corresponding to the next higher light level. Again, the observer gave the left-eye, right-eye, and binocular acuity responses. The experimenter continued this process until the observer had given his or her binocular acuity response at the highest light level condition.

³Linear regression techniques were used to control for any potential but unavoidable order or practice effects that may have resulted from this method of controlling for potential enhancement impacts of the independent variables. This technique is described in the results section.

Table 1. The 30 steps needed to obtain unaided acuity measures.

Step	Condition	Luminance (fL)	Configuration
1	Unaided	4.60E-05	Left monocular
2	Unaided	4.60E-05	Right monocular
3	Unaided	4.60E-05	Binocular
4	Unaided	4.60E-05	Left monocular
5	Unaided	4.60E-05	Right monocular
6	Unaided	4.60E-05	Binocular
7	Unaided	1.00E-04	Left monocular
8	Unaided	1.00E-04	Right monocular
9	Unaided	1.00E-04	Binocular
10	Unaided	1.00E-04	Left monocular
11	Unaided	1.00E-04	Right monocular
12	Unaided	1.00E-04	Binocular
13	Unaided	2.20E-04	Left monocular
14	Unaided	2.20E-04	Right monocular
15	Unaided	2.20E-04	Binocular
16	Unaided	2.20E-04	Left monocular
17	Unaided	2.20E-04	Right monocular
18	Unaided	2.20E-04	Binocular
19	Unaided	4.60E-04	Left monocular
20	Unaided	4.60E-04	Right monocular
21	Unaided	4.60E-04	Binocular
22	Unaided	4.60E-04	Left monocular
23	Unaided	4.60E-04	Right monocular
24	Unaided	4.60E-04	Binocular
25	Unaided	1.00E-03	Left monocular
26	Unaided	1.00E-03	Right monocular
27	Unaided	1.00E-03	Binocular
28	Unaided	1.00E-03	Left monocular
29	Unaided	1.00E-03	Right monocular
30	Unaided	1.00E-03	Binocular

The experimenter then asked the observer to use the NVG to view the tri-bar chart. The same 30 steps were repeated with the experimenter starting the trials at the lowest light level and ending at the highest light level. When the observer completed the last light-level condition, any questions that s/he may have had were answered by the experimenter, and the observer was thanked and paid for participating in the study.

3. Results

Visual acuity scores were converted by means of a logarithmic transformation to logMAR⁴ units for all 14 participants. These logMAR scores were then averaged for each participant across the five light levels for each *view type* (aided or unaided) and for each *ocular-type* condition (left eye, right eye, binocular). The averages were then used in a 2 x 3 repeated measures analysis of variance.

⁴Logarithm of the minimum angle of resolution (see “Glossary of Terms” for definition).

As expected, the results indicated a highly significant effect for *view type* $F(1,13) = 2154.87$, $p < .000$. Participants' acuity was significantly better with the NVGs than without the NVGs. The main effect of *ocular type* was also significant, $F(2,26) = 39.98$, $p < .000$. A "Difference" Planned Comparison revealed that binocular acuity was significantly different from the average of the left-eye and right-eye acuity, $t(13) = 76.44$, $p = .004$. As expected, results indicated no significant difference in acuity between the left and the right eye. The interaction of *view type* and *ocular type* was insignificant.

The data were then compiled into a matrix comprised of 14 individual acuity scores for each of the five selected luminance levels under aided and unaided conditions, and these data were incorporated into a regression model. The model yielded the "average person's" visual acuity obtainable within the range of light levels selected in the experiment. These data were also shown to follow a psycho-physical power law of the luminance consistent with the following equations:

$$Y_{(\text{individual})} = Y_{(\text{mean})} + \beta_{(\text{mean})} (X_{(\text{individual})} - X_{(\text{mean})})$$

in which $y_{(\text{individual})} = \log\text{MAR} = \log_{10} (1.719 \text{ cycles per milliradian}/VA^5 \text{ in cycles per milliradian})$
 $X_{(\text{individual})} = \log_{10} (L_{\text{individual}}/L_{\text{mean}})$
 β = the slope
 L = luminance in footlamberts

In combining these equations, we derived a general equation for the power law of the luminance for unaided and aided visual acuity:

$$VA_{(\text{individual})} = VA_{(\text{mean})} (L_{(\text{individual})}/L_{(\text{mean})})^{-\beta}$$

Specifically, the power law of the luminance for binocular unaided vision is

$$\textbf{VA (Binocular Unaided) = 1.88L}^{0.347} \textbf{ cycles per milliradian}$$

and for binocular aided vision is

$$\textbf{VA (Binocular Aided) = 3.42L}^{0.130} \textbf{ cycles per milliradian}$$

and for monocular aided vision is

$$\textbf{VA (Right, Monocular Aided) = 3.38L}^{0.141} \textbf{ cycles per milliradian}$$

$$\textbf{VA (Right, Monocular Unaided) = 1.05L}^{0.294} \textbf{ cycles per milliradian}$$

$$\textbf{VA (Left, Monocular Aided) = 3.38L}^{0.138} \textbf{ cycles per milliradian}$$

$$\textbf{VA (Left, Monocular Unaided) = 1.04}^{0.293} \textbf{ cycles per milliradian}$$

A complete summary of all the power law equations and their corresponding data plots is depicted next.

⁵VA = a measure of visual capability of the subject.

At the lowest luminance level, half of the subjects did not respond, while the acuity of the responders fell within the predicted confidence interval with one exception. Since no tri-bars were presented with a logMAR higher than 1.45, the distribution of responses is seen to be truncated at that level.

This psycho-physical model was then incorporated into a model for prediction of detection range that was proposed by Johnson (3) to provide insight into the detection range differences with and without goggles in monocular and binocular viewing conditions.




Figure 2. Plots are shown for 95% confidence intervals on predictions made by a linear regression model based on subject logMAR acuity for the four highest luminance levels.




Figure 3. Plots are shown for 95% confidence intervals on predictions made by a linear regression model based on subject logMAR acuity for five luminance levels. (The measured acuity fell within the predicted confidence intervals.)

Johnson Model: Range of Detection (meters) = 1000 (D) (VA) / C

Where:

D = Critical Target Dimension (given as 0.4 meter for a human target)

C = Johnson criteria (1.5 cycles across the critical dimension of the target, i.e., standing Soldier)

The Johnson model provides a prediction of performance of a given task based on ensemble or group performance data, thereby allowing performance predictions based on the average observer.

Example depicting the detection range of monocular and binocular NVGs over unaided vision in a given light condition:

“What is the approximate range advantage for detection of a Soldier target by the average observer or group of observers with and without NVGs under quarter moon conditions? “What detection range difference is there between monocular and binocular NVG?”

Range of Detection (Soldier) with **Binocular** NVGs = 1000 (D) (VA) / C
= 1000 mrad (0.4 meters) [3.42 (1/4 moon luminance)^{0.130} cycles/mrad] / 1.5 cycles
= 400 mrad-meters [3.42 (0.001)^{0.130} cycles/mrad] / 1.5 cycles
= 400 mrad-meters [3.42 (0.407) cycles/mrad] / 1.5 cycles
= 400 mrad-meters [1.39 cycles/mrad] / 1.5 cycles
= **372 meters**

Range of Detection (Soldier) without NVGs (**Binocular**) = 1000 (D) (VA) / C
= 1000 mrad (0.4 meters) [1.88 (1/4 moon luminance)^{0.347} cycles/mrad] / 1.5 cycles
= 400 mrad-meters [1.88 (0.091) cycles/mrad] / 1.5 cycles
= **46 meters**

Range of Detection (Soldier) with **Monocular** NVG = 1000 (D) (VA) / C
= 1000 mrad (0.4 meters) [3.38 (0.001)^{0.141} cycles/mrad] / 1.5 cycles
= 400 mrad-meters [3.38 (.378) cycles/mrad] / 1.5 cycles
= **340 meters**

Our derived model of visual detection predicts a range advantage with binocular NVGs of approximately 326 meters or an eight-fold improvement over unaided binocular vision under quarter moon luminance conditions. The detection range advantage is less (approximately 294 meters) with monocular NVG viewing, and there is a seven-fold improvement over unaided binocular vision. These data may be generalized to other targets (e.g., Abrams tank, Bradley armored personnel carrier and high mobility multipurpose wheeled vehicle [HMMWV]), provided the optical image transformations (lines across the target) are calculated.

Table 2. Detection range for targets viewed with and without NVGs during quarter moon luminance conditions.

Goggle Wear	Light level	Soldier	HMMWV	M-1 Abrams	M-3 Bradley
With NVG	¼ Moon	340 m	1950 m	4040 m	5050 m
Without NVG	¼ Moon	36.7 m	210 m	437 m	546 m
Johnson Criteria (cycles on target)		1.5 cycles	1.2 cycles	0.75 cycles	0.75 cycles
Target Minimum Dimension		0.4 meter	1.83 meters	2.38 meters	2.97 meters

4. Discussion

Our data clearly demonstrate a significant improvement in visual acuity with AN/AVS-9 Model 4949G NVGs over unaided vision at all of the luminance levels selected. Further, in accordance with existing well-established clinical data, binocular vision is better than monocular vision aided or unaided. Also, as luminance increases, the unaided visual acuity was demonstrated to improve more rapidly than aided acuity. This may be explained by a greater number of photoreceptor cells remaining adapted to the dark in the unaided condition and then being stimulated at an exponential rate as light levels were increased. This finding may be confirmed by visual inspection of the plotted data where it is noted that the slope (β) for unaided acuity is consistently greater than for the aided acuity (see figures 2 and 3).

Our original goal was to quantify visual acuity improvement derived from the use of NVGs in specific luminance conditions and then translate those data into predictive equations for incorporation into the IMPRINT model. We have derived and tested the effectiveness of our predictive model across median acuity values (in VA), at given luminance levels, for this population of participants. We have provided an example of improved target detection performance with NVGs by applying our power law to Johnson's predictive model for target detection performance.

Finally, it is possible to observe the impact on an individual's visual performance by selecting and analyzing data from a single subject. The following example demonstrates the value of NVGs in improving an individual's night vision performance:

Using Subject 9 (see figure 4) as an example, we can compare binocular acuity with and without NVGs at the lowest light level (4.60E-05fL). Binocular unaided visual acuity translates to 20/570, whereas visual acuity with NVGs improves to 20/36 for this individual. The visual acuity difference represents a 16-fold increase in visual function. At the highest light level selected (1.00E-03fL), the unaided binocular visual acuity is 20/160 and the acuity improves to 20/25 with NVGs. The visual acuity difference represents a 6.4-fold increase in visual function. These data quantify the quality of visual acuity improvement for this individual and demonstrate that NVGs provide the most dramatic improvement in visual function at levels where unaided

vision is significantly degraded. Visual acuity improvement trends were exhibited in similar degrees for all 14 of the study participants.




Figure 4. Example depicting the differences between binocular visual acuity with and without NVGs at the five selected luminance levels.

5. Conclusions

This report describes an initial effort to translate specific visual performance data in a manner that may be used in the IMPRINT model. Our data clearly demonstrate that there is significant visual improvement when NVGs are used at the selected light levels. These data were incorporated into the Johnson target detection model, and actual target detection ranges were calculated. The improved target detection range with NVGs allows us to suggest that these data increase the time available for decision making and target recognition in specified light levels. These data may be used by IMPRINT modelers for a given operational task analysis. As demonstrated in table 2, the IMPRINT user would select one of the five lighting conditions (with or without NVGs) calculate the desired target's minimum dimension, and derive its detection range. The impact that darkness (defined as a "stressor" in the IMPRINT model) has on target detection range could be quantified with and without NVGs. Reaction time could be calculated from the detection range and incorporated into IMPRINT. Then, the IMPRINT modeler could compare the differences in length of reaction time and more precisely predict Soldier performance in given environmental conditions.

6. References

1. Allender, L.; Salvi, L.; Promisel, D. Evaluation of Human Performance Under Diverse Conditions via Modeling Technology. *Proceedings of Workshop on Emerging Technologies in Human Engineering Testing and Evaluation*, NATO Research Study Group 24, Brussels, Belgium, June 1997.
2. Mitchell, D. K. *Mental Workload and ARL Workload Modeling Tools*; ARL-TN-161; U.S. Army Research Laboratory: Aberdeen Proving Ground, MD, 2000.
3. Johnson, J. Analysis of Image Forming Systems. *In Proceedings of the Image Intensifier Symposium*, 1957.

Glossary of Terms

Log of the minimum angle of resolution (logMAR): Most modern visual acuity charts are designed so that the letters on each line follow a geometric progression, i.e., each line represents a uniform step on a logarithmic scale. The geometric progression most accurately represents the manner in which the human visual system functions. The typical step progression is 0.1 log unit, which corresponds to the letter changing in size by a factor of 1.2589. The simplest and most widely accepted means of performing statistical analyses on visual acuity data is to convert the visual acuity of each participant to logMAR. The conversion equations are

$$\log\text{Mar} = -\log(\text{visual acuity in decimal connotation})$$

$$\text{decimal acuity} = \text{antilog}(-\log\text{MAR}) = 10^{-\log\text{MAR}}$$

Cycles per milliradian (VA): A measure of resolution. A milliradian is the angle subtended by an object whose height is one yard viewed at a distance of 1,000 yards. One cycle/milliradian resolution is required to detect a separation of 0.5 yard between two objects that are 0.5 yard in size.

Luminance: The amount of light per unit area reflected from or emitted by a surface. Luminance can be expressed in a variety of units. For this experiment, we selected footlamberts.

Acuity Conversion Table

SNELLEN	logMAR	CPMRAD	SNELLEN	logMAR	CPMRAD	SNELLEN	logMAR	CPMRAD
20/400	1.30	0.086	20/270	1.13	0.127	20/140	0.85	0.246
20/390	1.29	0.088	20/260	1.11	0.132	20/130	0.81	0.264
20/380	1.28	0.090	20/250	1.10	0.138	20/120	0.78	0.286
20/370	1.27	0.093	20/240	1.08	0.143	20/110	0.74	0.313
20/360	1.26	0.095	20/230	1.06	0.149	20/100	0.70	0.344
20/350	1.24	0.098	20/220	1.04	0.156	20/90	0.65	0.382
20/340	1.23	0.101	20/210	1.02	0.164	20/80	0.60	0.430
20/330	1.22	0.104	20/200	1.00	0.172	20/70	0.54	0.491
20/320	1.20	0.107	20/190	0.98	0.181	20/60	0.48	0.573
20/310	1.19	0.111	20/180	0.95	0.191	20/50	0.40	0.688
20/300	1.18	0.115	20/170	0.93	0.202	20/40	0.30	0.859
20/290	1.16	0.119	20/160	0.90	0.215	20/30	0.18	1.146
20/280	1.15	0.123	20/150	0.88	0.229	20/20	0.00	1.719

*CPMRAD = cycles per milliradian

NO. OF
COPIES ORGANIZATION

1 DEFENSE TECHNICAL
(PDF INFORMATION CTR
ONLY) DTIC OCA
 8725 JOHN J KINGMAN RD
 STE 0944
 FORT BELVOIR VA 22060-6218

1 US ARMY RSRCH DEV & ENGRG CMD
 SYSTEMS OF SYSTEMS
 INTEGRATION
 AMSRD SS T
 6000 6TH ST STE 100
 FORT BELVOIR VA 22060-5608

1 INST FOR ADVNCD TCHNLGY
 THE UNIV OF TEXAS AT AUSTIN
 3925 W BRAKER LN STE 400
 AUSTIN TX 78759-5316

1 DIRECTOR
 US ARMY RESEARCH LAB
 IMNE ALC IMS
 2800 POWDER MILL RD
 ADELPHI MD 20783-1197

1 DIRECTOR
 US ARMY RESEARCH LAB
 AMSRD ARL CI OK TL
 2800 POWDER MILL RD
 ADELPHI MD 20783-1197

2 DIRECTOR
 US ARMY RESEARCH LAB
 AMSRD ARL CS OK T
 2800 POWDER MILL RD
 ADELPHI MD 20783-1197

1 RDECOM-NATICK SOLDIER CTR
 HUMAN PERF/MANPRINT/SSI LEAD
 FUTURE FORCE WARRIOR TECH PRO OFC
 ATTN C L BLACKWELL
 100 KANSAS ST
 NATICK MA 01760-5020

1 ARMY RSCH LABORATORY - HRED
 ATTN AMSRD ARL HR M DR M STRUB
 6359 WALKER LANE SUITE 100
 ALEXANDRIA VA 22310

1 ARMY RSCH LABORATORY - HRED
 ATTN AMSRD ARL HR MA J MARTIN
 MYER CENTER RM 2D311
 FT MONMOUTH NJ 07703-5630

NO. OF
COPIES ORGANIZATION

1 ARMY RSCH LABORATORY - HRED
 ATTN AMSRD ARL HR MC A DAVISON
 320 MANSCEN LOOP STE 166
 FT LEONARD WOOD MO 65473-8929

1 ARMY RSCH LABORATORY - HRED
 ATTN AMSRD ARL HR MD T COOK
 BLDG 5400 RM C242
 REDSTONE ARSENAL AL 35898-7290

1 COMMANDANT USAADASCH
 ATTN ATSA CD
 ATTN AMSRD ARL HR ME MS A MARES
 5800 CARTER RD
 FT BLISS TX 79916-3802

1 ARMY RSCH LABORATORY - HRED
 ATTN AMSRD ARL HR MI J MINNINGER
 BLDG 5400 RM C242
 REDSTONE ARSENAL AL 35898-7290

1 ARMY RSCH LABORATORY - HRED
 ATTN AMSRD ARL HR MM DR V RICE
 BLDG 4011 RM 217
 1750 GREELEY RD
 FT SAM HOUSTON TX 78234-5094

1 ARMY RSCH LABORATORY - HRED
 ATTN AMSRD ARL HR MG R SPINE
 BUILDING 333
 PICATINNY ARSENAL NJ 07806-5000

1 ARMY RSCH LABORATORY - HRED
 ATTN AMSRD ARL HR MH C BURNS
 BLDG 1002 ROOM 117
 1ST CAVALRY REGIMENT RD
 FT KNOX KY 40121

1 ARMY RSCH LABORATORY - HRED
 AVNC FIELD ELEMENT
 ATTN AMSRD ARL HR MJ D DURBIN
 BLDG 4506 (DCD) RM 107
 FT RUCKER AL 36362-5000

1 ARMY RSCH LABORATORY - HRED
 ATTN AMSRD ARL HR MK MR J REINHART
 10125 KINGMAN RD
 FT BELVOIR VA 22060-5828

1 ARMY RSCH LABORATORY - HRED
 ATTN AMSRD ARL HR MV HQ USAOTC
 S MIDDLEBROOKS
 91012 STATION AVE ROOM 111
 FT HOOD TX 76544-5073

NO. OF
COPIES ORGANIZATION

- 1 ARMY RSCH LABORATORY - HRED
ATTN AMSRD ARL HR MY M BARNES
2520 HEALY AVE STE 1172 BLDG 51005
FT HUACHUCA AZ 85613-7069
- 1 ARMY RSCH LABORATORY - HRED
ATTN AMSRD ARL HR MP D UNGVARSKY
BATTLE CMD BATTLE LAB
415 SHERMAN AVE UNIT 3
FT LEAVENWORTH KS 66027-2326
- 1 ARMY RSCH LABORATORY - HRED
ATTN AMSRD ARL HR M DR B KNAPP
ARMY G1 MANPRINT DAPE MR
300 ARMY PENTAGON ROOM 2C489
WASHINGTON DC 20310-0300
- 1 ARMY RSCH LABORATORY - HRED
ATTN AMSRD ARL HR MJK MS D BARNETTE
JFCOM JOINT EXPERIMENTATION J9
JOINT FUTURES LAB
115 LAKEVIEW PARKWAY SUITE B
SUFFOLK VA 23435
- 1 ARMY RSCH LABORATORY - HRED
ATTN AMSRD ARL HR MQ M R FLETCHER
US ARMY SBCCOM NATICK SOLDIER CTR
AMSRD NSC SS E BLDG 3 RM 341
NATICK MA 01760-5020
- 1 ARMY RSCH LABORATORY - HRED
ATTN AMSRD ARL HR MT DR J CHEN
12350 RESEARCH PARKWAY
ORLANDO FL 32826-3276
- 1 ARMY RSCH LABORATORY - HRED
ATTN AMSRD ARL HR MS MR C MANASCO
SIGNAL TOWERS RM 303A
FORT GORDON GA 30905-5233
- 1 ARMY RSCH LABORATORY - HRED
ATTN AMSRD ARL HR MU M SINGAPORE
6501 E 11 MILE RD MAIL STOP 284
BLDG 200A 2ND FL RM 2104
WARREN MI 48397-5000
- 1 ARMY RSCH LABORATORY - HRED
ATTN AMSRD ARL HR MF MR C HERNANDEZ
BLDG 3040 RM 220
FORT SILL OK 73503-5600
- 1 ARMY RSCH LABORATORY - HRED
ATTN AMSRD ARL HR MW E REDDEN
BLDG 4 ROOM 332
FT BENNING GA 31905-5400

NO. OF
COPIES ORGANIZATION

- 1 ARMY RSCH LABORATORY - HRED
ATTN AMSRD ARL HR MN R SPENCER
DCSFDI HF
HQ USASOC BLDG E2929
FORT BRAGG NC 28310-5000
- ABERDEEN PROVING GROUND
- 1 DIRECTOR
US ARMY RSCH LABORATORY
ATTN AMSRD ARL CI OK TECH LIB
BLDG 4600
- 1 DIRECTOR
US ARMY RSCH LABORATORY
ATTN AMSRD ARL CI OK S FOPPIANO
BLDG 459
- 1 DIRECTOR
US ARMY RSCH LABORATORY
ATTN AMSRD ARL HR MR F PARAGALLO
BLDG 459
- 30 DIRECTOR
US ARMY RSCH LABORATORY
ATTN AMSRD ARL HR SD W MONACO
R WEATHERLESS J KALB
BLDG 459