



An Internal Variable Theory of Deformation, Damage, and Fragmentation of Solids

by John D. Clayton

ARL-RP-149

September 2006

*A reprint from Plasticity 2006 Conference Proceedings, Halifax, Nova Scotia,
Canada, pp. 601–603, 17 July 2006.*

NOTICES

Disclaimers

The findings in this report are not to be construed as an official Department of the Army position unless so designated by other authorized documents.

Citation of manufacturer's or trade names does not constitute an official endorsement or approval of the use thereof.

Destroy this report when it is no longer needed. Do not return it to the originator.

Army Research Laboratory

Aberdeen Proving Ground, MD 21005-5066

ARL-RP-149**September 2006**

An Internal Variable Theory of Deformation, Damage, and Fragmentation of Solids

John D. Clayton

Weapons and Material Research Directorate, ARL

*A reprint from **Plasticity 2006 Conference Proceedings**, Halifax, Nova Scotia,
Canada, pp. 601–603, 17 July 2006.*

REPORT DOCUMENTATION PAGE				Form Approved OMB No. 0704-0188	
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing the burden, to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.					
1. REPORT DATE (DD-MM-YYYY) September 2006		2. REPORT TYPE Reprint		3. DATES COVERED (From - To) October 2002–October 2003	
4. TITLE AND SUBTITLE An Internal Variable Theory of Deformation, Damage, and Fragmentation of Solids				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S) John D. Clayton				5d. PROJECT NUMBER WHPR01E	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army Research Laboratory ATTN: AMSRD-ARL-WM-TD Aberdeen Proving Ground, MD 21005-5069				8. PERFORMING ORGANIZATION REPORT NUMBER ARL-RP-149	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution is unlimited.					
13. SUPPLEMENTARY NOTES A reprint from <i>Plasticity 2006 Conference Proceedings</i> , Halifax, Nova Scotia, Canada, pp. 601–603, 17 July 2006.					
14. ABSTRACT A unified framework of continuum elasticity, inelasticity, damage mechanics, and fragmentation in solid materials is presented. A free energy functional accounts for thermodynamics of elastic deformation and damage, with kinetic relations for inelastic rates adapted from prior literature. Average fragment velocities follow from momentum conservation, average fragment sizes are deduced from an energy balance, and size and velocity distributions are constructed following entropy maximization. The model is further developed to study concrete subjected to ballistic loading scenarios.					
15. SUBJECT TERMS concrete, damage mechanics, damage fracture, fragmentation, spall					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT UL	18. NUMBER OF PAGES 10	19a. NAME OF RESPONSIBLE PERSON John D. Clayton
a. REPORT UNCLASSIFIED	b. ABSTRACT UNCLASSIFIED	c. THIS PAGE UNCLASSIFIED			19b. TELEPHONE NUMBER (Include area code) 410-306-0975

AN INTERNAL VARIABLE THEORY OF DEFORMATION, DAMAGE, AND FRAGMENTATION OF SOLIDS

John D. Clayton

Impact Physics Branch, U.S. Army Research Laboratory,
AMSRD-ARL-WM-TD, Aberdeen Proving Ground, MD 21005-5069
jclayton@arl.army.mil

ABSTRACT: A unified framework of continuum elasticity, inelasticity, damage mechanics, and fragmentation in solid materials is presented. A free energy functional accounts for thermodynamics of elastic deformation and damage, with kinetic relations for inelastic rates adapted from prior literature. Average fragment velocities follow from momentum conservation, average fragment sizes are deduced from an energy balance, and size and velocity distributions are constructed following entropy maximization. The model is further developed to study concrete subjected to ballistic loading scenarios.

INTRODUCTION: Constitutive models of dynamic deformation, damage evolution, and fragmentation of solid materials are needed in order to describe complex physical phenomena occurring, for example, in solid body collisions and ballistic impacts. Previous research efforts have often relied on a patchwork of separate models consisting of an equation-of-state for pressure, plasticity model for deviatoric strength, damage model for stress reduction/elimination, and fragmentation model for average fragment size [Johnson *et al.*, 1997; Raftenberg, 1998; Silling, 2001]. Such patchwork implementations may lack consistency from a kinematic and thermodynamic point-of-view. The aim of the present study is development of a self-consistent theory accounting for the above mechanisms, specifically amenable to brittle, crushable solids such as concrete, mortar, and cinder block. Static and dynamic properties of concrete follow from previous investigations [Holmquist *et al.*, 1993], while fragment sizes and distributions are predicted via an approach accounting for momentum and energy conservation [Grady, 1982], history-dependence of damage accumulation [Miller *et al.*, 1999], and maximum disorder principles [Englman *et al.*, 1987; Grady & Winfree, 2001].

PROCEDURES, RESULTS AND DISCUSSION: Fundamental aspects of the model framework for a deforming and fragmenting solid are presented here. The kinematic description begins with a multiplicative decomposition of the deformation gradient:

$$F_{.A}^a = \partial x^a / \partial X^A = F_{.a}^{Ea} F_{.A}^{D\alpha}, \quad (1)$$

where x^a and X^A denote spatial and reference coordinates, $F_{.a}^{Ea}$ is the recoverable elastic deformation, and $F_{.A}^{D\alpha}$ is the irreversible deformation associated with defects such as micro-cracks, voids, dislocations, or shear discontinuities evolving within the material. The spatial velocity gradient then follows directly from (1) as

$$L_{.b}^a = \partial \dot{\chi}^a / \partial \chi^b = \dot{F}_{.a}^{Ea} F^{E-1a}_{.b} + F_{.a}^{Ea} \dot{F}_{.B}^{D\alpha} F^{D-1B}_{.b} F^{E-1\beta}_{.b}, \quad (2)$$

with the superposed "□" a material time derivative. Standard balances of linear and angular momentum apply. The Helmholtz free energy, on a per unit intermediate configuration volume basis, is assumed to exhibit the following general dependencies:

$$\tilde{\psi} = \tilde{\psi}(E_{\alpha\beta}^E, \theta, \xi^{(k)}), \quad (3)$$

where the elastic strain $2E_{\alpha\beta}^E = F_{.a}^{Ea} g_{ab} F_{.b}^{Eb} - \delta_{\alpha\beta}$, with g_{ab} the spatial metric, θ the absolute temperature, and $\xi^{(k)}$ a dimensionless set of internal variables. Stress-strain, temperature-entropy, and internal dissipation relations are then deduced as

$$\sigma^{ab} = J^{E-1} F_{.a}^{Ea} \frac{\partial \tilde{\psi}}{\partial E_{\alpha\beta}^E} F_{.b}^{Eb}, \quad \tilde{\eta} = -\partial_{\theta} \tilde{\psi}, \quad P_{.b}^{\alpha} L_{.a}^{D\beta} - \partial_{\xi^{(k)}} \tilde{\psi} \dot{\xi}^{(k)} \geq 0, \quad (4)$$

with $P_{.b}^{\alpha} = J^E F_{.a}^{E-1\alpha} (\sigma_{.b}^a - \psi \delta_{.b}^a) F_{.b}^{Eb}$. Here, σ^{ab} is the symmetric Cauchy stress, J^E is the elastic Jacobian, ψ is the free energy per unit current volume, $\tilde{\eta}$ is the entropy per unit intermediate volume, and $L_{.a}^{D\beta} = \dot{F}_{.B}^{D\beta} F^{D-1B}_{.a}$ is the purely inelastic velocity gradient.

The framework is hereafter specialized to brittle crushable solids, with $F_{.A}^{D\alpha}$ now associated with crack opening and sliding, as well as pore collapse during compression. Let $\tilde{A}$ represent the cumulative local micro-cracked area per unit intermediate volume $\tilde{V}$, such that $D = \xi^{(1)} \propto \tilde{A} \tilde{V}^{1/3}$, and restrict $0 \leq D \leq 1$. Furthermore, let $\varphi = \xi^{(2)} = J^{D-1} - 1$ represent volume reduction upon crushing. The specific free energy density then is postulated as

$$\tilde{\psi} = \frac{1}{2} K_1 (E_{.a}^{Ea})^2 + \frac{1}{3} K_2 (E_{.b}^{Eb})^3 + \frac{1}{4} K_3 (E_{.c}^{Ec})^4 + G(1-D) \hat{E}_{\delta\epsilon}^E \hat{E}^{E\delta\epsilon} + \Gamma(D) + Y(\theta), \quad (5)$$

where K_1 , K_2 , and K_3 depend on φ and D , G is the shear modulus, $\hat{E}_{\alpha\beta}^E$ is the elastic strain deviator, Γ accounts for surface and concentrated energy of micro-cracks, and Y describes the specific heat content. Deviatoric plasticity follows from the potential Φ :

$$\dot{\hat{\epsilon}}_{ab}^D = \lambda \frac{\partial \Phi}{\partial \hat{\sigma}^{ab}}, \quad \Phi = \left[A(1-D) + B(p/p_0)^N \right] \left[1 + C \ln(\lambda/\dot{\epsilon}_0) \right] \sigma_0, \quad (6)$$

where $\dot{\hat{\epsilon}}_{ab}^D$ is the spatial deviatoric inelastic strain rate, $3\lambda^2 = 2\dot{\hat{\epsilon}}_{ab}^D \dot{\hat{\epsilon}}^{Dba}$ for stresses exceeding the elastic limit, $\hat{\sigma}^{ab}$ is the deviatoric stress, $-3p = \sigma_{.a}^a$, and A , B , C , p_0 , N , $\dot{\epsilon}_0$, and σ_0 are material parameters [Holmquist *et al.*, 1993]. In the present

implementation, we assume small elastic shape changes and material isotropy such that the inelastic spin may be neglected. Porosity and damage evolution are controlled via

$$\varphi = \begin{cases} 0 & (p \leq p_c); (p \geq p_l), \\ \alpha p & (p_c < p < p_l), \end{cases} \quad \dot{D} = \hat{\kappa} \lambda \langle 1 - \pi_D (p/p_0) \rangle, \quad (7)$$

where α , $\hat{\kappa}$, and π_D are positive constants, and the bracket notation $\langle x \rangle = x \forall x > 0$ and $\langle x \rangle = 0 \forall x \leq 0$. Fragmentation of the local volume element is assumed to occur when the damage reaches a critical magnitude, $D = D_F$. At this instant, a spatial energy balance relating intact and fragmented configurations is written, in rate form, as

$$d(U + E_c)/dt = d\left(\sum(u + e_l + e_s) + E_c\right)/dt, \quad (8)$$

where $U = J^{E-1}(\tilde{\psi} + \tilde{\eta}\theta)$, u is the internal energy per fragment, e_l and e_s are energy due to the relative linear and spin momentum per fragment, and E_c is the equivalent kinetic energy of both the continuum element and the center-of-mass of the fragment cloud. Summation is implied over all fragments in (8), which yields the average fragment dimension b . Subscale distributions of cumulative fragment number per unit volume (N) and velocity relative to the center-of-mass follow from statistical mechanics principles [Grady & Winfree, 2001], i.e. $N = N_0 \exp(-N_0 b^3)$ where $N_0 = N_f/V$ is the mean number of fragments per unit volume, while spatial-nonlocal averaging methods describe fragments larger than grid sizes in numerical implementations.

REFERENCES:

- Englman, R., Rivier, N., and Jaeger, Z., 1987. "Fragment-size Distribution in Disintegration by Maximum-entropy Formalism", *Phil. Mag. B* **56**, 751-769.
- Grady, D.E., 1982. "Local Inertial Effects in Dynamic Fragmentation", *J. Appl. Phys.* **53**, 322-325.
- Grady, D.E. and Winfree, N.A., 2001. "Impact Fragmentation of High-velocity Compact Projectiles on Thin Plates: A Physical and Statistical Characterization of Fragment Debris", *Int. J. Impact Engng.* **26**, 249-262.
- Holmquist, T.J., Johnson, G.R., and Cook, W.H., 1993. "A Computational Constitutive Model for Concrete Subjected to Large Strains, High Strain Rates, and High Pressures", *Proc. 14th Int. Symp. Ballistics*, Quebec City, Canada.
- Johnson, G.R., Stryk, R.A., Holmquist, T.J., and Beissel, S.R., 1997. "Numerical Algorithms in a Lagrangian Hydrocode", Alliant Techsystems, Inc., Hopkins, MN.
- Miller, O., Freund, L.B., and Needleman, A., 1999. "Modeling and Simulation of Dynamic Fragmentation in Brittle Materials", *Int. J. Fracture* **96**, 101-125, 1999.
- Raftenberg, M., 1998. "Behind Armor Debris Calculations with the EPIC Wavecode", ARL-TR-1748, Aberdeen Proving Ground, MD.
- Silling, S.A., 2001. "CTH Reference Manual: BFK Model for Concrete", SNL-NM, draft.

NO. OF
COPIES ORGANIZATION

1 DEFENSE TECHNICAL
(PDF INFORMATION CTR
ONLY) DTIC OCA
8725 JOHN J KINGMAN RD
STE 0944
FORT BELVOIR VA 22060-6218

1 US ARMY RSRCH DEV &
ENGRG CMD
SYSTEMS OF SYSTEMS
INTEGRATION
AMSRD SS T
6000 6TH ST STE 100
FORT BELVOIR VA 22060-5608

1 DIRECTOR
US ARMY RESEARCH LAB
IMNE ALC IMS
2800 POWDER MILL RD
ADELPHI MD 20783-1197

3 DIRECTOR
US ARMY RESEARCH LAB
AMSRD ARL CI OK TL
2800 POWDER MILL RD
ADELPHI MD 20783-1197

ABERDEEN PROVING GROUND

1 DIR USARL
AMSRD ARL CI OK TP (BLDG 4600)

NO. OF
COPIES ORGANIZATION

ABERDEEN PROVING GROUND

32 DIR USARL
AMSRD ARL CI HC
P CHUNG
AMSRD ARL WM
J MCCAULEY
T WRIGHT
AMSRD ARL WM MA
W NOTHWANG
AMSRD ARL WM TA
S SCHOENFELD
AMSRD ARL WM TC
M FERMEN COKER
R COATES
AMSRD ARL WM TD
S BILYK
T BJERKE
D CASEM
J CLAYTON (5 CPS)
T CLINE
D DANDEKAR
W EDMANSON
M GREENFIELD
C GUNNARSSON
Y HUANG
K IYER
R KRAFT
B LOVE
S MCNEILL
H MEYER
R MUDD
M RAFTENBERG
E RAPACKI
M SCHEIDLER
S SEGLETES
T WEERASOORIYA

INTENTIONALLY LEFT BLANK.