

The Microchip Optera Project



Photo: Dr. Elisabeth Kalko

As they seek to capture aerial targets, bats can sort echoes from their own vocalizations from the signals and echoes produced by other bats. This project aims to produce a neuromorphic VLSI-based system with similar abilities.

The potential

Bats use sonar to fly through their environment and catch insects in complete darkness. Studying their behavior and neurophysiology may help in building miniature autonomous air vehicles with sonar sensors.

The long-term goal of this project is to build a tiny, low-power, neuromorphic VLSI-based model of an FM bat echolocation system that can be demonstrated in an aerial target capture task using a flying vehicle. This system will work in real time and at low power.

Echolocating bats

Bats use ultrasonic vocalization signals as their sonar pulse and construct some type of 3-D representation of the environment with the returning echoes. A bat's sophisticated sonar processing system can clearly support a sufficiently detailed spatial percept which they use to guide complex maneuvers, such as insect capture on the wing. Exactly to what degree they perceive a spatial "image" is unknown.

Bats use binaural differences in echo arrival time, intensity and spectrum for horizontal localization. The big brown bat, *Eptesicus fuscus*, has been shown to have a horizontal localization accuracy of about 1 degree. On the other hand, they use only spectral cues for vertical localization. The pinnae, the tragus, and the head collectively form a complex direction-dependent acoustic filter that influences the spectral profile of

the returning echo and plays a critical role in the bat's ability to localize targets in the vertical plane. A bat's vertical discrimination threshold is about three degrees.

With sound traveling at speed of about 34cm (out and back means 17cm target range) for every millisecond of delay time, bats show astonishing accuracy along the range (near/far) axis. Given that their internal neural representation of sensory signals are voltage spikes of about millisecond duration, bats are able to aggregate signals from many neurons to easily distinguish targets that differ by ranges of 1 cm. Many experiments, while controversial, show significantly better resolution.

Echolocating bats can organize acoustic information from multiple targets, arriving from different directions and at different delays. The spatial information comes when the sound, reaching the ears, undergoes transformation in the bat's brain. A class of neurons in the brain show echo-delay tuning, a response property believed to play a role in target ranging. These neurons respond selectively to pulse-echo pairs, separated by particular delays. Other cells are sensitive to the relative intensity of sounds in the two ears and are selective for targets from certain ranges of angles.

What is neuromorphic VLSI?

Neuromorphic VLSI merges current knowledge about the morphology of neurons and neural circuits with parallel

continued...

Report Documentation Page				Form Approved OMB No. 0704-0188	
Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.					
1. REPORT DATE 2006		2. REPORT TYPE		3. DATES COVERED 00-00-2006 to 00-00-2006	
4. TITLE AND SUBTITLE The Microchip Optera Project				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S)				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) University of California at Santa Cruz, Department of Computer Engineering, Santa Cruz, CA, 95064				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution unlimited					
13. SUPPLEMENTARY NOTES The original document contains color images.					
14. ABSTRACT					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT	18. NUMBER OF PAGES 2	19a. NAME OF RESPONSIBLE PERSON
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified			

VLSI computational architectures. Brains primarily use a combination of massively-parallel, nonlinear, analog computations and asynchronous digital communication. For example, a silicon retina is a camera-like chip with photoreceptor pixels that perform image processing in the space surrounding each pixel. This is analogous to what occurs in mammalian retinas.

Developing sonar capabilities (bearing and range)

ISR researchers are studying how the physical shape of a bat's head, its flight behavior, its choice of sonar pulse and its repetition rate contribute to the incredible sensory performance it achieves. Engineering efforts to replicate some of these tasks do not come anywhere near the performance in weight, speed and power consumption of a common bat.

The separate extraction of sensory attributes is a common theme in neural computation and the neuromorphic bat system is a good example of this processing approach.

To mimic the neurons that detect target range, the researchers use analog circuit models of the bat's delay-tuned cells to design a neuromorphic chip that implements range detection based on echo delay. This model uses a cellular rebound mechanism to correlate the time of flight to an internal time constant. Place coding is achieved with arrays of units tuned to different delay times.

To mimic the neurons that detect target bearing (azimuth), the researchers use an array of cells active for targets beyond a certain threshold angle. As with the delay-tuned cells, angle is extracted from the population response of cells with different threshold angles.

Consistent with the low-power nature of these computations, the circuits operate with a power consumption on the order of milliwatts.

Status

The researchers currently are developing low-power ultrasonic cochleae for use in broadband echo analysis, to extract target elevation, and to pursue more complex integration of sensory cues for guiding the flight of their test vehicle.

Research team

Cynthia Moss and Timothy Horiuchi

Contacts

Cynthia Moss
Professor, Psychology and ISR
2123M Biology/Psychology Building
University of Maryland
College Park, MD 20742
Phone: 301-405-0353
Fax: 301-314-9920
Email: cmoss@psyc.umd.edu
Web: www.bsos.umd.edu/psyc/faculty/newcmoss/

Timothy K. Horiuchi
Assistant Professor, Electrical and
Computer Engineering and ISR
2215 A.V. Williams Building
University of Maryland
College Park, MD 20742

Phone: 301-405-7412
Fax: 301-314-9920
Email: timmer@isr.umd.edu
Web: www.isr.umd.edu/Labs/CSSL/csslhome/

Additional information

Auditory Neuroethology Lab
www.bsos.umd.edu/psyc/batlab/

Computational Sensorimotor Systems Lab
www.isr.umd.edu/Labs/CSSL/csslhome/

Support

Dr. Horiuchi's work is supported by the Minta Martin Fund for Aeronautical Research at the University of Maryland and by the Air Force Office of Strategic Research (AFOSR-F496200110415).

Dr. Moss's work is supported by NIMH Grant R01-MH56366, NSF Grant IBN-9258255 and Whitehall Foundation Grant S97-20.



Narrowband test system (40 kHz)



Wideband system (10 kHz to 100 kHz)