



Australian Government
Department of Defence
Defence Science and
Technology Organisation

A Preliminary Comparison Between TNT and PE4 Landmines

Samuel Weckert and Christopher Anderson

Weapons Systems Division
Defence Science and Technology Organisation

DSTO-TN-0723

ABSTRACT

This report details preliminary findings on the difference in explosive output between a PE4 and TNT surrogate landmine. Previous DSTO landmine vulnerability research was undertaken using PE4 surrogate landmines, however the NATO STANAG 4569 states that all testing should be undertaken using TNT filled surrogate landmines. An explosive field trial was conducted to look at the explosive performance of buried PE4 against an equivalent amount of buried TNT. The test was also modelled using the Finite Element Analysis software, LS-DYNA.

RELEASE LIMITATION

Approved for public release

Published by

*Weapons Systems Division
DSTO Defence Science and Technology Organisation
PO Box 1500
Edinburgh South Australia 5111 Australia*

*Telephone: (08) 8259 5555
Fax: (08) 8259 6567*

*© Commonwealth of Australia 2006
AR-013-769
September 2006*

APPROVED FOR PUBLIC RELEASE

A Preliminary Comparison Between TNT and PE4 Landmines

Executive Summary

In February 2005, two plate tests were conducted at the Proof and Experimental Establishment (P&EE), Graytown, to investigate the difference in explosive output between buried PE4 and buried TNT. The motivation for this was to assess the accuracy of an air burst derived, peak pressure based equivalency ratio of 1.37 previously used in DSTO landmine vehicle vulnerability research.

A 4.38 kg PE4 and a 6 kg TNT surrogate landmine were each placed under a $1219 \times 1219 \times 50.8$ mm mild steel plate, weighing approximately 590 kg, and standing on 400 mm wooden legs. The mines were buried such that the top surface was 50 mm below the soil surface and that the centre of the mine was directly beneath the centre of the plate.

The 4.38 kg PE4 charge was shown to be almost equivalent to the 6 kg TNT charge in its ability to deform a metal plate, but it was much less effective in forming a crater and accelerating the plate. Thus, the equivalency ratio required was shown to depend on the measure of interest. The peak pressure based equivalency ratio of 1.37 appeared reasonable for studying deformation effects, however an equivalency ratio of 1.09 - 1.21 was suggested for plate acceleration effects and an equivalency ratio of unity was required to match the crater size.

The test was also modelled using the Finite Element Analysis (FEA) software, LS-DYNA. The steel plate was modelled using a Lagrangian mesh and the landmine blast was simulated using a LS-DYNA specific pressure based loading condition.

Contents

1. INTRODUCTION	1
2. EXPERIMENTAL SETUP	1
2.1 Instrumentation	2
3. EXPERIMENTAL RESULTS	3
3.1 Post Event Craters	3
3.2 Crater Moisture Content	5
3.3 Plate Deformation	5
3.4 Height Reached	7
3.5 Shock Data Logger	7
3.6 Results Summary	7
4. CONCLUSION	8
5. REFERENCES	9
6. ACKNOWLEDGEMENTS	9
APPENDIX A: MODELLING	11
A.1. Material Model	11
A.2. Blast Offset Comparison	13
A.3. Comparison with Experimental Results	13

Glossary

DSTO	Defence Science and Technology Organisation
FEA	Finite Element Analysis
NATO	North Atlantic Treaty Organisation
P&EE	Proof and Experimental Establishment
PE4	Plastic Explosive 4
STANAG	Standardisation Agreement
TNT	Trinitrotoluene

List of Figures

Figure 1. Pre-event plate test set-up. Note that the mine has not yet been buried	2
Figure 2. Post event crater.....	3
Figure 3. PE4 crater showing a 1000 mm tape measure for scale. The plate is shown in its post event resting position	4
Figure 4. TNT crater showing a 1000 mm tape measure for scale. The plate is shown in its post event resting position	4
Figure 5. Deformed TNT plate	6
Figure 6. Plate permanent deformation	6
Figure 7. Finite element mesh.....	11
Figure 8. Bilinear stress strain curve.....	12

List of Tables

Table 1. Crater dimensions.....	3
Table 2. Post event plate deformation	5
Table 3. Equivalency ratio dependence on chosen measure	7
Table 4. Material properties used to model the steel plate and wooden legs.....	12
Table 5. Explosive weight correction factors	13

1. Introduction

For landmine vulnerability testing the NATO STANAG 4569 states that all testing should be undertaken using Trinitrotoluene (TNT) filled surrogate landmines. However, previous DSTO work in this field used Plastic Explosive 4 (PE4) instead of TNT because of the inability to cast TNT on-site at the time. The PE4 was used such that 4.38 kg of PE4 was considered equivalent to 6kg of TNT. This equivalency of 1.37 was based on air burst test data [1], as no buried explosive equivalency test data was available. Additionally the air burst equivalency ratio of 1.37 is based on peak pressure, but there is also an air burst equivalency ratio of 1.19 based on impulse [1].

A test was conducted to look at the explosive performance of PE4 against TNT surrogate landmines to investigate the buried explosive equivalency of these two explosives. To achieve this, 590 kg steel plates were placed over a 4.38 kg PE4 and a 6 kg TNT surrogate landmine and the maximum plate height reached, the post event permanent deformation, and the crater size were recorded as measures of explosive effects.

The plate test was also modelled using the Finite Element Analysis software, LS-DYNA [2].

2. Experimental Setup

The two tests were conducted at the Proof and Experimental Establishment (P&EE), Graytown, Victoria, in February 2005. DSTO constructed a hand pressed 4.38 kg PE4 surrogate mine and a 6 kg cast TNT surrogate mine. Each mine was placed under a 1219 x 1219 x 50.8 mm steel plate, standing on 400 mm wooden legs. The mines were buried such that the top surface was 50 mm below the soil surface and the centre of the mine was directly beneath the centre of the plate. The experimental setup is shown in Figure 1.




Figure 1. Pre-event plate test set-up. Note that the mine has not yet been buried

2.1 Instrumentation

High-speed video and real-time video were used to record the explosive events. Additionally a small self-contained shock data logger unit was strapped to the centre of the plate, as shown in Figure 1. This was intended to record the acceleration of the centre of the plate at a sampling rate of 100 Hz.

3. Experimental Results

3.1 Post Event Craters

Both the 6 kg TNT and 4.38 kg PE4 explosives created craters consisting of two sections resembling bowls as shown in the schematic in Figure 2. This is consistent with work reported by Conniff and Skaggs [3], where a double-dished crater was formed from a landmine detonation inside a container of compacted soil.

The dimensions for the craters are presented in Table 1 and photographs of the PE4 and TNT craters are shown in Figure 3 and Figure 4 respectively. The crater diameter, $D1$, for the TNT charge is approximately 10% larger than that from the PE4 charge. For a buried charge at constant depth of burial, the crater radius scales with the explosive weight to the power of $1/3.4$ [4]. Thus using the primary crater diameter, $D1$, results this suggests a TNT-to-PE4-equivalency ratio of 1.




Figure 2. Post event crater

Table 1. Crater dimensions

	Large Bowl		Small Bowl	
Explosive type	D1 (mm)	H1 (mm)	D2 (mm)	H2 (mm)
PE4	2000	230	800	650
TNT	2200	300	900	730
% Increase for TNT over PE4	10.0	30.4	12.5	12.3




Figure 3. PE4 crater showing a 1000 mm tape measure for scale. The plate is shown in its post event resting position




Figure 4. TNT crater showing a 1000 mm tape measure for scale. The plate is shown in its post event resting position

3.2 Crater Moisture Content

Soil samples were taken from the post event craters and were analysed for moisture content. This revealed 6.9 % moisture content for the 4.38 kg PE4 crater and 9.3 % for the 6 kg TNT crater. Many references in the literature report an increase in energy/impulse with increasing moisture content [3, 5, 6, 7, 8], and experimental data from Hlady [5] also shows that this effect is dependent on the moisture content range. For prairie soil with moisture content varying from 10 – 20%, there was a strong increase in energy transfer to the target with increasing moisture content, however for both sand and prairie soil with a moisture content range of 0 – 10% the energy transfer was independent of the moisture content value. As a result, the difference in moisture contents between the PE4 and TNT craters is not expected to have any influence on the results.

3.3 Plate Deformation

The TNT deformed plate is shown in Figure 5. The post event deformation of the plate was measured at 100 mm increments along the plate. These values are presented in Table 2 and Figure 6. The deformation at the centre of the plate is larger for the 6 kg TNT explosive, however modelling studies (Appendix A) indicated that the observed deformations would have required only a slightly larger PE4 charge (1.34 equivalency ratio) for the PE4 results to match the TNT results. Thus, the plate deformation outcomes indicate that the two charges were close to identical for this aspect of the test.

Table 2. Post event plate deformation

Distance from edge of plate (mm) along centreline	Depth of Dishing (mm)	
	PE4	TNT
0	0	0
100	10	9.22
200	19	19.91
300	29	32.05
400	42	45.37
500	53	58.92
600	58	65.03
700	53	54.89
800	42	41.46
900	29	28.22
1000	19	16.96
1100	10	7.92
1200	0	0



Figure 5. Deformed TNT plate




Figure 6. Plate permanent deformation

3.4 Height Reached

The 4.38 kg PE4 surrogate landmine caused the plate to reach a maximum height of 31 m, and the 6 kg TNT surrogate landmine caused the plate to obtain a maximum height of 39 m. This result indicates that the 6 kg TNT charge was more effective than the 4.38 kg charge in throwing the plate into the air. Using a linear relationship between the explosive weight and the energy imparted to the target, this gives a TNT-to-PE4-equivalency ratio of 1.09 in the ability of the explosive to accelerate a plate.

The modelling studies (Appendix A) indicated that the observed plate heights would have required a TNT-to-PE4-equivalency ratio of 1.21 for the PE4 results to match the TNT results.

The ratios of 1.09 and 1.21 are reasonably similar to the impulse based air burst equivalency ratio of 1.19 reported in [1].

3.5 Shock Data Logger

The loads experienced during the event exceeded the capacity of the mounting mechanism holding the shock data logger to the plate. The shock data logger was found on the ground after the event, with considerable damage representative of excessive shock loading. Many components inside the device were damaged and it was not possible to recover any data from the device.

3.6 Results Summary

A summary of the results presented in Table 3 indicates that the TNT to PE4 equivalency ratio varies with the chosen measure.

Table 3. *Equivalency ratio dependence on chosen measure*

Measure	TNT to PE4 Equivalency Ratio
Crater Diameter	1.00
Plate Deformation	1.34
Plate Height	1.09/1.21

4. Conclusion

The 4.38 kg PE4 charge was shown to be almost equivalent to the 6 kg TNT charge in its ability to deform a metal plate, but it was much less effective in forming a crater and accelerating the plate. Thus, the equivalency ratio required is very much dependent on the measure of interest. It appears reasonable to use the peak pressure based equivalency ratio of 1.37 when deformation effects are being studied, however an equivalency ratio of 1.09 - 1.21 maybe more appropriate for plate acceleration effects and an equivalency ratio of unity is suggested for crater size.

Since the effects of a landmine on a vehicle may include both acceleration of the vehicle and deformations, it is suggested that an equivalency ratio of 1.3 may be appropriate, since this will be reasonably close to both the acceleration and deformation results. Work conducted by Wharton, Formby and Merrifield [9] also indicated an overall TNT to PE4 equivalency of approximately 1.3.

5. References

1. US Army, "TM 5-855-1 Fundamentals of Protective Design for Conventional Weapons", US Army Waterways Experimental Station, 1986.
2. LS-DYNA Version 970, Finite element modelling program for the non-linear dynamic analysis of inelastic structures, Livermore Software Technology Corporation.
3. D. E. Conniff and R. R. Skaggs, "Soil Properties Influence on Land-Mine Blast Effects", The 12th Annual Army Research Laboratory/ United States Military Academy Technical Symposium, US, CD Edition, 2004.
4. P. W. Cooper, "Explosives Engineering", Wiley-VCH, New York, 1996.
5. S. L. Hlady, "Effect of Soil Parameters on Land Mine Blast", Proceedings of the 18th International Symposium on the Military Aspects of Blast and Shock, Bad Reichenhall (Germany), CD Edition, 2004.
6. L. Donahue, R. Link and S. L. Hlady, "Numerical Modelling of Soils Subjected to Explosive Loading", Proceedings of the 18th International Symposium on the Military Aspects of Blast and Shock, Bad Reichenhall (Germany), CD Edition, 2004.
7. A. Gupta, "Modelling and Analysis of a 3D Asymmetric Mine-Soil-Structure Interaction Problem with Mine Buried in Dry and Wet Sand", Proceedings of the 71st Shock and Vibration Symposium, Arlington, USA, CD edition, 2000.
8. L. Donahue, R. Link, T. Josey, S. Hlady, D. Bergeron, R. Durocher, K. Williams, "Structural Response to Land Mines", Proceedings of the 74th Shock and Vibration Symposium, San Diego, California, CD Edition, 2003.
9. R. K. Wharton, S. A. Formby, R. Merrifield, "Airblast TNT equivalence for a range of commercial blasting explosives", Journal of Hazardous Materials, 79 (1-2), p 31-39.
10. G. Randers-Pehrson and K. A. Bannister, "Airblast Loading Model for DYNA2D and DYNA3D", Army Research Laboratory, ARL-TR-1310, 1997.
11. D. W. Hyde, "User's Guide for Microcomputer Program CONWEP, Applications of TM 5-855-1, 'Fundamentals of Protective Design for Conventional Weapons'.", SL-88-1, US Army Corps of Engineers Waterways Experiment Station Instruction, Vicksburg, 1988, revised 1993.
12. <http://www.bluescopesteel.com.au/go/product/350-xlerplate>, cited 5th May 2006.

6. Acknowledgements

The authors wish to acknowledge the assistance of:

- Other members of the trials team – Dr Christopher Anderson and Roy Bird from WSD and Frank Marion and Andrew McLean from MPD;
- The P&EE Graytown staff for their excellent support;
- General Dynamics Land Systems Australia for financing the cost of the steel plates;
- Dr Ray Johnson for his thorough reading of this report and his valuable comments.

Appendix A: Modelling

The plate test was modelled using the Finite Element Analysis (FEA) software package, LS-DYNA [2]. The steel plate and wooden legs were modelled using a Lagrangian mesh, and the landmine blast was simulated using the LS-DYNA LOAD_BLAST function. The LOAD_BLAST function [10] utilises a pressure loading condition based on the Conwep program [11] to simulate a blast loading condition. The inputs for this function are restricted to the initial position of the blast, an equivalent weight of TNT, and a toggle to change between a spherical blast and a hemispherical blast. As the landmine was buried in soil, 50 mm under the surface, the hemispherical blast was used and additionally, the equivalent weight of TNT was multiplied by a correction factor (discussed further in Section A.3) to take into account the focusing effects of the soil.

The plate legs were meshed with a coarse mesh as they were unimportant, whereas the steel plate was meshed with a much finer mesh, as shown in Figure 7, to enable calculation of the plate deformation. The plate was meshed uniformly with a 72×72 element mesh that was 3 elements deep giving a total of 15 552 elements for the plate. The legs contained 4 elements each, resulting in a total of 15 568 elements for the complete model.




Figure 7. Finite element mesh

A.1. Material Model

Both the legs and the steel plate were modelled using solid elements with a simple ISOTROPIC_ELASTIC_PLASTIC material model. The material properties are summarised in Table 4. The material properties used for the wooden legs were very approximate as the legs do not represent a critical part of the model and could have alternatively been

modelled as rigid elements. The ISOTROPIC_ELASTIC_PLASTIC material model approximates the stress-strain curve as two linear segments as shown in Figure 8. The slope of the first line is the Young's modulus (derivable from the shear modulus and bulk modulus) and represents the elastic region. The second line segment begins at the yield stress, has a slope designated by the plastic hardening modulus, and represents the plastic region.

Table 4. Material properties used to model the steel plate and wooden legs

	Density kg/m ³	Shear Modulus Gpa	Yield Stress Mpa	Plastic Hardening Modulus Mpa	Bulk Modulus Gpa
Steel Plate	7850	80	350	450	160
Wooden Legs	500	10	50	100	50




Figure 8. Bilinear stress strain curve

The yield stress and plastic hardening modulus values for the steel plate were based on data from Blue Scope Steel AS/NZS 3678 - 350 Xlerplate [12]. The plastic hardening modulus was approximated by assuming the ultimate tensile strength occurred at the failure strain. Although this is a simplification of the actual stress-strain curve, the model seemed relatively insensitive to the plastic hardening modulus over the possible error range expected.

A.2. Blast Offset Comparison

It was desired to estimate the effects of having the surrogate landmine offset from the centre of the plate. In practice it would be impossible to position the centre of the surrogate landmine exactly beneath the centre of the steel plate and consequently the model was used to simulate different degrees of offset. 10 mm, 20 mm, 50 mm and 100 mm offsets were investigated.

The comparison of the different offsets revealed that the maximum height decreased slightly and the amount of rotation increased as the offset was increased. This was due to an increased amount of the blast energy contributing to plate rotation instead of vertical translation. However as the offset was increased the X-Y translation of the plate was not significantly altered. This was very good from a safety point of view as it meant that if the landmine were not accurately positioned directly beneath the centre of the plate, the plate would still land close to its starting position.

A.3. Comparison with Experimental Results

A correction factor multiplied by the explosive weight was applied to the model to take into account the focussing effect of the soil. For the 6 kg TNT test, a correction factor of 2.80 was required to match the experimental height result, and a factor of 3.17 was required to match the experimental deformation result. For the 4.38 kg PE4 test, correction factors of 3.40 and 4.25 were required to match the experimental height and deformation results respectively. The ratio of the correction factors used to match the experimental heights gives a TNT-to-PE4-equivalency ratio of 1.21. Similarly, an equivalency ratio of 1.34 is derived from the correction factors for matching the experimental deformations. A summary of these correction factors is presented in Table 5.

Table 5. Explosive weight correction factors

	Experimental height matched		Experimental deformation matched	
	Weight	Correction Factor	Weight	Correction Factor
6 kg TNT	16.8	2.80	19.0	3.17
4.38 kg PE4	14.9	3.40	18.6	4.25
Equivalency ratio		1.21		1.34

DISTRIBUTION LIST

"As per the Research Library's *Policy on electronic distribution of official series reports* (<http://web-vic.dsto.defence.gov.au/workareas/library/aboutrl/roles&policies/mission.htm>) Unclassified (both Public Release and Limited), xxx-in-confidence and Restricted reports and their document data sheets will be sent by email through DRN to all recipients with Australian defence email accounts who are on the distribution list apart from the author(s) and the task sponsor(s). Other addressees and Libraries and Archives will also receive hardcopies."

A Preliminary Comparison Between TNT and PE4 Landmines

Samuel Weckert and Christopher Anderson

AUSTRALIA

DEFENCE ORGANISATION	No. of copies
Task Sponsor	
Chief, Weapons Systems Division	1 Printed
S&T Program	
Chief Defence Scientist	1
Deputy Chief Defence Scientist Policy	1
AS Science Corporate Management	1
Director General Science Policy Development	1
Counsellor Defence Science, London	Doc Data Sheet
Counsellor Defence Science, Washington	Doc Data Sheet
Scientific Adviser to MRDC, Thailand	Doc Data Sheet
Scientific Adviser Joint	1
Navy Scientific Adviser	Doc Data Sheet & Distribution List
Scientific Adviser – Army	1
Air Force Scientific Adviser	Doc Data Sheet & Distribution List
Scientific Adviser to the DMO	Doc Data Sheet & Distribution List
Deputy Chief Defence Scientist Platform and Human Systems	Doc Data Sht & Exec Summary
Research Leader, Land Weapons Systems	Doc Data Sht & Dist List
Head, Threat Mitigation Group	1
Task Managers: John Leach	1
Roy Bird	1

Author(s):	Samuel Weckert	1 Printed
	Christopher Anderson	1 Printed
DSTO Library and Archives		
Library Fishermans Bend		Doc Data Sheet
Library Edinburgh		1 printed
Defence Archives		1 printed
Capability Development Executive		
Director General Maritime Development		Doc Data Sheet
Director General Land Development		1
Director General Capability and Plans		Doc Data Sheet
Assistant Secretary Investment Analysis		Doc Data Sheet
Director Capability Plans and Programming		Doc Data Sheet
Chief Information Officer Group		
Head Information Capability Management Division		Doc Data Sheet
Director General Australian Defence Simulation Office		Doc Data Sheet
AS Information Strategy and Futures		Doc Data Sheet
Director General Information Services		Doc Data Sheet
Strategy Executive		
Assistant Secretary Strategic Planning		Doc Data Sheet
Assistant Secretary International and Domestic Security Policy		Doc Data Sheet
Navy		
Maritime Operational Analysis Centre, Building 89/90 Garden Island Sydney NSW		Doc Data Sht & Dist List
Deputy Director (Operations)		
Deputy Director (Analysis)		
Director General Navy Capability, Performance and Plans, Navy Headquarters		Doc Data Sheet
Director General Navy Strategic Policy and Futures, Navy Headquarters		Doc Data Sheet
Air Force		
SO (Science) - Headquarters Air Combat Group, RAAF Base, Williamstown NSW 2314		Doc Data Sht & Exec Summary
Staff Officer Science Surveillance and Response Group		Doc Data Sht & Exec Summary
Army		
Australian National Coordination Officer ABCA (AS NCE ABCA), Land Warfare Development Sector, Puckapunyal		Doc Data Sheet
J86 (TCS GROUP), DJFHQ		Doc Data Sheet
SO (Science) - Land Headquarters (LHQ), Victoria Barracks NSW		Doc Data Sht & Exec Summary

SO (Science) - Special Operations Command (SOCOMD), R5-SB-15, Russell Offices Canberra	Doc Data Sht & Exec Summary
SO (Science), Deployable Joint Force Headquarters (DJFHQ) (L), Enoggera QLD	Doc Data Sheet

Joint Operations Command

Director General Joint Operations	Doc Data Sheet
Chief of Staff Headquarters Joint Operations Command	Doc Data Sheet
Commandant ADF Warfare Centre	Doc Data Sheet
Director General Strategic Logistics	Doc Data Sheet

Intelligence and Security Group

AS Concepts, Capability and Resources	1
DGSTA , Defence Intelligence Organisation	1
Manager, Information Centre, Defence Intelligence Organisation	1
Director Advanced Capabilities	Doc Data Sheet

Defence Materiel Organisation

Deputy CEO	Doc Data Sheet
Head Aerospace Systems Division	Doc Data Sheet
Head Maritime Systems Division	Doc Data Sheet
Program Manager Air Warfare Destroyer	Doc Data Sheet
Guided Weapon & Explosive Ordnance Branch (GWEO)	Doc Data Sheet
CDR Joint Logistics Command	Doc Data Sheet

OTHER ORGANISATIONS

National Library of Australia	1
NASA (Canberra)	1

UNIVERSITIES AND COLLEGES

Australian Defence Force Academy

Library	1
Head of Aerospace and Mechanical Engineering	1
Hargrave Library, Monash University	Doc Data Sheet

OUTSIDE AUSTRALIA

INTERNATIONAL DEFENCE INFORMATION CENTRES

US Defense Technical Information Center	1
UK Dstl Knowledge Services	1
Canada Defence Research Directorate R&D Knowledge & Information Management (DRDKIM)	1
NZ Defence Information Centre	1

ABSTRACTING AND INFORMATION ORGANISATIONS

Library, Chemical Abstracts Reference Service	1
Engineering Societies Library, US	1
Materials Information, Cambridge Scientific Abstracts, US	1
Documents Librarian, The Center for Research Libraries, US	1
 SPARES	 5 Printed

Total number of copies: 35 Printed: 10 PDF: 25

DEFENCE SCIENCE AND TECHNOLOGY ORGANISATION DOCUMENT CONTROL DATA					
				1. PRIVACY MARKING/CAVEAT (OF DOCUMENT)	
2. TITLE A Preliminary Comparison Between TNT and PE4 Landmines			3. SECURITY CLASSIFICATION (FOR UNCLASSIFIED REPORTS THAT ARE LIMITED RELEASE USE (L) NEXT TO DOCUMENT CLASSIFICATION) Document (U) Title (U) Abstract (U)		
4. AUTHOR(S) Samuel Weckert and Christopher Anderson			5. CORPORATE AUTHOR DSTO Defence Science and Technology Organisation PO Box 1500 Edinburgh South Australia 5111 Australia		
6a. DSTO NUMBER DSTO-TN-0723		6b. AR NUMBER AR-013-769		6c. TYPE OF REPORT Technical Note	
				7. DOCUMENT DATE September 2006	
8. FILE NUMBER 2005/1013375/1		9. TASK NUMBER Task # 06/020		10. TASK SPONSOR CWSD	
				11. NO. OF PAGES 14	
				12. NO. OF REFERENCES 12	
13. URL on the World Wide Web http://www.dsto.defence.gov.au/corporate/reports/DSTO-TN-0723.pdf				14. RELEASE AUTHORITY Chief, Weapons Systems Division	
15. SECONDARY RELEASE STATEMENT OF THIS DOCUMENT <i>Approved for public release</i>					
OVERSEAS ENQUIRIES OUTSIDE STATED LIMITATIONS SHOULD BE REFERRED THROUGH DOCUMENT EXCHANGE, PO BOX 1500, EDINBURGH, SA 5111					
16. DELIBERATE ANNOUNCEMENT No Limitations					
17. CITATION IN OTHER DOCUMENTS Yes					
18. DSTO RESEARCH LIBRARY THESAURUS http://web-vic.dsto.defence.gov.au/workareas/library/resources/dsto_thesaurus.htm TNT, PE4, landmines, Equivalence, Equivalency, buried charge, comparison, flying plate					
19. ABSTRACT This report details preliminary findings on the difference in explosive output between a PE4 and TNT surrogate landmine. Previous DSTO landmine vulnerability research was undertaken using PE4 surrogate landmines, however the NATO STANAG 4569 states that all testing should be undertaken using TNT filled surrogate landmines. An explosive field trial was conducted to look at the explosive performance of buried PE4 against an equivalent amount of buried TNT. The test was also modelled using the Finite Element Analysis software, LS-DYNA.					