

A Distributed Parallel Embedded System for Autonomous Sonar Arrays

W.A. Rosen
ECE Department
Drexel University

A.D. George
ECE Department
University of Florida

Report Documentation Page				Form Approved OMB No. 0704-0188	
Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.					
1. REPORT DATE 1997		2. REPORT TYPE		3. DATES COVERED 00-00-1997 to 00-00-1997	
4. TITLE AND SUBTITLE A Distributed Parallel Embedded System for Autonomous Sonar Arrays				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S)				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) University of Florida, Department of Electrical and Computer Engineering, High-performance Computing and Simulation (HCS) Research Laboratory, Gainesville, FL, 32611				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution unlimited					
13. SUPPLEMENTARY NOTES The original document contains color images.					
14. ABSTRACT					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT	18. NUMBER OF PAGES 21	19a. NAME OF RESPONSIBLE PERSON
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified			

Acknowledgments




This work was supported by grants N00014-96-1-0569, N00014-97-1-0117, and N00014-97-1-0229 from the Office of Naval Research. The authors wish to express their thanks to Drs. John Tague and Don Davison, and CDR Mitch Shipley of the Office of Naval Research for their continued support and Jeff Markwell and Ryan Fogarty, research assistants at the University of Florida, for their assistance in this effort.

Outline



-
1. Background
 2. Candidate network topologies
 3. Node architecture
 4. Distributed parallel algorithms and programs
 5. Experimental results
 6. Integrated simulation environment
 7. Conclusions and future research

Background



The U.S. Navy is developing a series of disposable air-deployed sonar arrays for undersea surveillance. The arrays must be


- high-gain (high-element-count)
- low-cost
- reliable
- autonomous (in-array processing)
- battery-powered (30-day mission time)

Background (cont.)




First Generation Concept:

"freight train" architecture in which data taken at each node is loaded onto a train which passes down a "track" to a centralized data processor. The data processor in this architecture represents a single-point-of-failure, a potential performance bottleneck, and a major cost driver



Next Generation Architecture:

each node of the network represents a processing element of a parallel processor, essentially turning the array itself into a distributed parallel processing machine.




Background (cont.)




Advantages:

- This approach offers the potential for greatly reduced cost with increased system performance, dependability, and versatility.
- Using the spare processing capacity in the network protocol processors together with the high data rate offered by fiber optics, these improvements can be achieved at essentially no increase to the per-node cost of the array.


Candidate Network Topologies



(a) uni-directional linear array




(b) uni-directional ring array



(c) bi-directional linear array

Node Architecture




Modeling & Simulation

- simulates COTS devices (μP , RAM, ADC, etc.) as well as key ASIC characteristics
- determines device characteristics for optimal
 - performance (MHz, MFLOPS)
 - power consumption
 - standby-mode usage
 - size and weight
 - cost
- development for hardware prototype

Distributed Parallel Algorithms and Programs




- decomposition, partitioning, mapping, tuning, and T&E for conventional (both time- and frequency-domain) parallel beamforming algorithms
- testbed performance studies provide insight into advantages and disadvantages of each new variant
- interrelationships between each promising variant and the candidate node and network architectures are explored



Distributed Parallel Algorithms and Programs (cont.)




*Parallel
beamformer for
uni-directional
linear arrays*



Distributed Parallel Algorithms and Programs (cont.)




*Coarse-grain
parallel
beamformer for
bi-directional
and ring arrays*




Distributed Parallel Algorithms and Programs (cont.)



*Medium-grain
parallel
beamformer for
bi-directional and
ring arrays*




Experimental Results



Performance of coarse- and medium-grain parallel beamformers on a cluster of eight SPARCstation-20/85 workstations connected by OC-3c ATM (155-Mbps), for steering directions from -90 to 90 degrees in increments of 0.5, 1, or 2 degrees

Experimental Results (cont.)




Performance of unidirectional array, ring, and bidirectional array parallel beamformers with network-dependent link-by-link communication on the ATM cluster, for steering directions from -90 to 90 degrees in increments of 0.5 degrees

Integrated Simulation Environment (ISE)




- Unified design tool for modeling and simulating next-generation sonar arrays and beamforming algorithms
 - Rapid virtual prototyping
 - Fine-grain system simulation
 - Integrates and augments
 - Algorithm research
 - Network research
 - Node architecture research
 - Can model current technology and predict performance of future technology



ISE Timing




- **Parallel programs written in unmodified C-MPI code**
- **User process (via BONEs/MPI calls) informs BONEs how long code block computation takes**
- **BONEs will simulate the communication, informing the process when complete**
- **Thus, both HWIL computation and simulated communication are taken into consideration for prototype development**




ISE MPI/BONeS


Parameter Vectoring



ISE Runtime Environment



Preliminary ISE Results



Performance of medium-grain parallel beamformer both on a cluster of eight UltraSPARC-2/200 workstations connected by OC-3c ATM (155-Mbps) and on UltraSPARC-HWIL ISE, for increments of 2 degrees

ISE Advantages



-
- Existing and new beamforming programs can be simulated on nonexistent platforms; thus dozens of systems may be simulated which would be too costly to build
 - Interface provides a universal glue to which any MPI programs can attach to a simulated network
 - Real application data flows, so programs are validated as well. Conversely, working applications may effectively be used to debug and improve network protocols
 - Although BONeS/MPI is run on Sun workstations, the ISE may simulate many architectures and processors by scaling the performance of the SPARC code block measurements

Conclusions and Future Research



- ◆ The use of distributed and parallel processing techniques will reduce the size and cost and improve the performance and reliability of autonomous disposable sonar arrays.
- ◆ The performance of architectures based on uni-directional rings and bi-directional linear networks are comparable.
- ◆ Both coarse- and medium-grain parallel algorithms provide near-linear speedup for high-spatial-resolution beamforming, with coarse-grain beamformers performing marginally better at all spatial resolutions.
- ◆ An integrated simulation approach can provide a rapid virtual prototyping capability that will further reduce system costs.
- ◆ Future plans include extending this work to split-array with cross spectral correlation and adaptive beamforming. A laboratory network prototype is also planned.