
**Noise Reduction in support-constrained multi-frame
blind-deconvolution restorations as a function of the
number of data frames and the support constraint sizes
(Preprint)**

Charles Matson and Alim Haji

6 December 2006

Journal Article

APPROVED FOR PUBLIC RELEASE; DISTRIBUTION IS UNLIMITED.



**AIR FORCE RESEARCH LABORATORY
Directed Energy Directorate
3550 Aberdeen Ave SE
AIR FORCE MATERIEL COMMAND
KIRTLAND AIR FORCE BASE, NM 87117-5776**

REPORT DOCUMENTATION PAGE				Form Approved OMB No. 0704-0188	
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing this collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.					
1. REPORT DATE (DD-MM-YYYY) 6-12-2006		2. REPORT TYPE Journal Article		3. DATES COVERED (From - To) October 2004-December 2006	
4. TITLE AND SUBTITLE Noise reduction in support-constrained multi-frame blind-deconvolution restorations as a function of the number of data Frames and the support constraint sizes (Preprint)				5a. CONTRACT NUMBER F29601-01-D-0083 TO 6	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER 061102F	
6. AUTHOR(S) Charles L. Matson, Alim Haji				5d. PROJECT NUMBER D0D0	
				5e. TASK NUMBER B3	
				5f. WORK UNIT NUMBER AD	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) AFRL/DESA 3550 Aberdeen Avenue SE Kirtland AFB, NM 87117-5776				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) Air Force Research Laboratory 3550 Aberdeen Ave. SE Kirtland AFB, NM 87117-5776				10. SPONSOR/MONITOR'S ACRONYM(S) AFRL/DESA	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S) AFRL-DE-PA-JA-2007-1004	
12. DISTRIBUTION / AVAILABILITY STATEMENT Approved for Public Release; DISTRIBUTION IS UNLIMITED. Cleared for Public Release, AFRL/DEO-PA, 6 Dec 06, control number AFRL/DE 06-790.					
13. SUPPLEMENTARY NOTES Submitted for publication in Optical Society of America (OSA), 2007. "GOVERNMENT PURPOSE RIGHTS"					
14. ABSTRACT We show that the amount of relative noise reduction in multi-frame blind deconvolution image restorations is greatest for just a few data frames and is a more complicated function of the support constraint sizes.					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT SAR	18. NUMBER OF PAGES 6	19a. NAME OF RESPONSIBLE PERSON Charles Matson
a. REPORT Unclassified	b. ABSTRACT Unclassified	c. THIS PAGE Unclassified			19b. TELEPHONE NUMBER (include area code)

Noise reduction in support-constrained multi-frame blind-deconvolution restorations as a function of the number of data frames and the support constraint sizes

Charles L. Matson and Alim Haji

Air Force Research Laboratory, 3550 Aberdeen Ave SE, Kirtland AFB, New Mexico, USA 87117-5776

Abstract: We show that the amount of relative noise reduction in multi-frame blind deconvolution image restorations is greatest for just a few data frames and is a more complicated function of the support constraint sizes.

©2007 Optical Society of America

OCIS codes: (100.3020) Image reconstruction-restoration; (100.2980) Image enhancement

1. Introduction

Multi-frame blind deconvolution (MFB) algorithms seek to estimate jointly an object being imaged along with all the system point spread functions (PSFs) present in the measured data frames. It is well known that the quality of an object restoration improves as the number of data frames included in the restoration process is increased and as the sizes of the support constraints used in the algorithm decrease in size (while still including the true support). This improvement is due to both a greater likelihood of finding the global minimum of the MFB cost function (when a cost-function based approach is used, of course) and the decreased noise levels in the restored image. In this paper we report on results we have obtained while investigating the latter source of improvement. Our interest in exploring the amount of noise reduction as a function of the number of data frames and the support constraint sizes is due to a desire to better understand the tradeoff between improved image quality and increased algorithm execution time. We show that the amount of total noise reduction in the restored images is an increasing function of the number of data frames, and that the amount of relative noise reduction is greatest when adding including just a few data frames and is greater than might be expected. We define the term “relative noise reduction” in Section 3. We also discuss how the amount of relative noise reduction depends on the object and PSF support constraint sizes. Because we desire to obtain answers that are algorithm independent, we employ a Cramér-Rao lower bound (CRB) approach in the analysis. The outline of this paper is as follows: Section 2 contains a description of the imaging model and CRB theory, results are given in Section 3, and conclusions are presented in Section 4.

2. Imaging model and Cramér-Rao lower bound theory

The equation describing image formation is

$$i_m(\mathbf{x}) = h_m(\mathbf{x}) * o(\mathbf{x}) + n_m(\mathbf{x}) \quad ; \quad m = 1, \dots, M \quad (1)$$

where $*$ denotes convolution, $\mathbf{x}$ is a two-dimensional spatial variable, $i_m(\mathbf{x})$ is the m^{th} data frame, $h_m(\mathbf{x})$ is the m^{th} PSF, $o(\mathbf{x})$ is the object being imaged, $n_m(\mathbf{x})$ is the m^{th} noise realization, and bold-faced type denotes vectors and matrices. Because CRB theory requires a set of random variables, not stochastic processes, Eq.(1) must be rewritten in a vector form rather than as a continuous function. To this end, let $\boldsymbol{\alpha}$ be a square grid of spatial locations of the intensity values of $i_m(\mathbf{x})$ and let $\mathbf{y}_m$, $\boldsymbol{\psi}$, $\boldsymbol{\phi}_m$ and $\boldsymbol{\eta}_m$ be one-dimensional vectors that contain the values of $i_m(\boldsymbol{\alpha})$, $o(\boldsymbol{\alpha})$, $h_m(\boldsymbol{\alpha})$, and $n_m(\boldsymbol{\alpha})$, respectively, on the grid defined by $\boldsymbol{\alpha}$. The vectors $\mathbf{y}_m$, $\boldsymbol{\psi}$, $\boldsymbol{\phi}_m$ and $\boldsymbol{\eta}_m$ can be generated from $i_m(\boldsymbol{\alpha})$, $o(\boldsymbol{\alpha})$, $h_m(\boldsymbol{\alpha})$ and $n_m(\boldsymbol{\alpha})$ by stacking their columns. In addition, let $\mathbf{H}_m$ be the block-circulant matrix associated with $\boldsymbol{\phi}_m$ [1]. Then Eq.(1) can be rewritten as

$$\mathbf{y}_m = \mathbf{H}_m \boldsymbol{\psi} + \boldsymbol{\eta}_m \quad ; \quad m = 1, \dots, M \quad (2)$$

Multi-frame blind deconvolution algorithms seek to estimate jointly the parameters contained in the vectors $\boldsymbol{\psi}$ and $\{\boldsymbol{\phi}_m\}$ given the data vectors $\{\mathbf{y}_m\}$, where the quantities in braces are the collection of vectors for all m . Although we could have carried out this analysis using sample statistics generated from restorations produced by a specific MFB algorithm, we desired to generate algorithm-independent results. Therefore, we chose to use CRB theory [2] for the analysis since it produces lower bounds to the variances of any unbiased estimates of a set of parameters. The CRBs for any unbiased estimates of the elements of the concatenated vector $\boldsymbol{\theta} = [\boldsymbol{\psi}^T, \boldsymbol{\phi}_1^T, \dots, \boldsymbol{\phi}_M^T]^T$ are the diagonal elements of the inverse of $\mathbf{F}$, the FIM associated with $\mathbf{y}_m$ and $\boldsymbol{\theta}$. The element of $\mathbf{F}$ in the p^{th} row and the q^{th} column is given by

$$\mathbf{F}_{pq}(\boldsymbol{\theta}) = E \left[\frac{\partial \ln f(\mathbf{y}; \boldsymbol{\theta})}{\partial \boldsymbol{\theta}_p} \frac{\partial \ln f(\mathbf{y}; \boldsymbol{\theta})}{\partial \boldsymbol{\theta}_q} \right] \quad (3)$$

where $f(\mathbf{y};\boldsymbol{\theta})$ is the probability density function of $\{\mathbf{y}_m\}$ parameterized by the vector $\boldsymbol{\theta}$ and $\ln$ denotes the natural logarithm. Equation (3) gives the elements of $\mathbf{F}$ for the imaging model of Eq.(2) without the application of any constraints. Support constraints are implemented by including in the vectors $\boldsymbol{\psi}$ and $\{\boldsymbol{\phi}_m\}$ only those elements that are inside their support constraint regions [3]. The unbiased CRBs of the parameters $\boldsymbol{\theta}$, $\text{CRB}(\boldsymbol{\theta})$, are given by

$$\text{CRB}(\boldsymbol{\theta}) = \text{diag}(\mathbf{F}^{-1}) \quad (4)$$

where $\text{diag}()$ denotes a vector containing the diagonal elements of the bracketed matrix. Because of the scaling redundancy of blind deconvolution, this expression for $\mathbf{F}$ is non-invertible. We make $\mathbf{F}$ invertible by estimating only $N-1$ elements of $\boldsymbol{\psi}$ and N_m-1 elements of $\{\boldsymbol{\phi}_m\}$, where N and N_m are the numbers of pixels in the support constraints applied to these vectors, and by requiring that all the $\mathbf{H}_m$ have full rank, which occurs when the Fourier transforms of $\{h_m(\mathbf{x})\}$ are non-zero.

3. Results

We calculated CRBs using the object in Fig.1 for $o(\mathbf{x})$ and zero mean white noise with variance σ^2 for $n_m(\mathbf{x})$. The PSFs $\{h_m(\mathbf{x})\}$ are related to atmospheric PSFs for $D/r_o = 8$, where D is the telescope diameter and r_o is the atmospheric correlation length [4]. We created $\{h_m(\mathbf{x})\}$ by creating $D/r_o = 8$ PSFs, Fourier transforming them, cutting out a square portion of this Fourier transform centered at zero frequency and contained within the telescope OTF support, and then inverse Fourier transforming the results. The resulting $\{h_m(\mathbf{x})\}$ are invertible, making $\mathbf{F}$ invertible. We chose to do this to avoid the complications of calculating and interpreting biased CRBs.

A plot of the unbiased CRBs for $\boldsymbol{\psi}$, $\text{CRB}_M(\boldsymbol{\psi})$, normalized to one for $M=1$, is given in Fig. 2 as a function of the number of data frames M included in the MFBD process. For this plot, the true object support was used for $\boldsymbol{\psi}$ and a circular support that contained more than 99% of the energy of the $\{h_m(\mathbf{x})\}$ was used. For each M , the corresponding point in the plot is the sum of $\text{CRB}_M(\boldsymbol{\psi})$, denoted $\text{sum}(\text{CRB}_M(\boldsymbol{\psi}))$. Notice that $\text{sum}(\text{CRB}_M(\boldsymbol{\psi}))$ is a decreasing function of M , as expected. Simplistically, one might expect $\text{sum}(\text{CRB}_M(\boldsymbol{\psi}))$ to decrease as $1/M$ since the noises are statistically independent from frame to frame. This $1/M$ behavior is present, for example, when using speckle imaging techniques to estimate the energy spectrum of an object [4]. To investigate this expectation, we plotted the function $1/M$ in Fig. 2 as well. Notice that the $\text{sum}(\text{CRB}_M(\boldsymbol{\psi}))$ plot decreases more rapidly than $1/M$ for small values of M . We refer to the slope of $\text{sum}(\text{CRB}_M(\boldsymbol{\psi}))$ as the amount of relative noise reduction. This implies that MFBD image restorations benefit more than might be expected from adding just a few frames to the estimation process as compared to carrying out blind deconvolution using only one data frame. We have seen this behavior in restorations obtained using field data as well. Notice also that the slopes of the $\text{sum}(\text{CRB}_M(\boldsymbol{\psi}))$ plot and the $1/M$ plot appear to be equal for larger values of M . This means that the expected $1/M$ relative noise reduction in the restored images occurs for larger values of M .




Fig. 1. Computer-simulated satellite model (a), and support constraints used for CRB calculations: (b) true, (c) blur2, (d) blur 5, and (e) blur 7.




Fig. 2. Plots of the normalized $\text{sum}(\text{CRB}_M(\boldsymbol{\psi}))$ values (solid line) and $1/M$ (dashed line) as a function of M




Fig. 3. Decrease in the normalized sum(CRB₂(ψ)) values as a function of object and PSF support sizes.

We then investigated how the amount of relative noise reduction that occurs in $\text{sum}(\text{CRB}_M(\psi))$ as a result of using two ($M=2$) instead of one ($M=1$) frames of data depends on the object and PSF support constraint sizes. To do this, we calculated $\text{sum}(\text{CRB}_2(\psi))$ for several object and PSF support constraints. We used four different object support constraint sizes: the true support region and three larger support regions created by blurring the true support region with 2×2 , 5×5 , and 7×7 blurring kernels (see Fig. 1). The PSF supports were all circular with increasing radii. The amounts of relative noise reduction are displayed in Fig. 3. Several properties of $\text{sum}(\text{CRB}_M(\psi))$ can be observed. The first property is that $\text{sum}(\text{CRB}_2(\psi))$ is an increasing function of the PSF support constraint size for all object support constraint sizes, and the rate of increase grows as the size of the object support constraint increases. The second property is that the benefit of adding a second frame to the MFBD process usually increases as the object support constraint size increases for a fixed PSF support constraint size. This second property is especially useful since highly-accurate object supports are difficult to generate, in general.

We emphasize that the results in Fig. 3 are based on the normalized $\text{sum}(\text{CRB}_M(\psi))$ values, not the absolute values. Without this awareness, the results in Fig. 3 could be interpreted to mean that a less-accurate object support constraint produces lower CRB values than does a more-accurate object support constraint, which is not true. The proper conclusion to draw from Fig. 3 is that noise reduction occurs more swiftly as M increases for less-accurate support sizes.

4. Conclusions

Using an algorithm-independent CRB approach, we have analyzed the amount of noise reduction possible when using MFBD algorithms. We investigated the amount of absolute and relative noise reduction as a function of the number of data frames included in the restoration process and the sizes of the object and PSF support constraints. We showed that the relative noise reduction is greater than $1/M$ for values of M on the order of one, where M is the number of data frames, and is approximately equal to $1/M$ for larger values of M . We also showed that the amount of relative noise reduction achieved for $M = 2$ is generally an increasing function of object support constraint size. For many object support constraint sizes, the amount of relative noise reduction is a decreasing function of the PSF support size.

The authors wish to thank the Air Force Office of Scientific Research for their financial support of this research.

5. References

- ¹ R. C. Gonzalez and R. E. Woods, *Digital Image Processing* (Addison-Wesley, Reading, MA, 1992), Chap. 5.
- ² B. Porat, *Digital Processing of Random Signals, Theory and Methods* (Prentice-Hall, Englewood Cliffs, NJ, 1994), Chap. 3.
- ³ J. D. Gorman and A. O. Hero, "Lower bounds for parametric estimation with constraints," *IEEE Trans. Inf. Theory* **26**, 1285-1301 (1990).
- ⁴ M.C. Roggemann and B. Welsh, *Imaging Through Turbulence* (CRC Press, Boca Raton, FL, 1996).