

~~CONFIDENTIAL~~
UNCLASSIFIED



DISTRIBUTION STATEMENT A
Approved for Public Release
Distribution Unlimited

MINISTRY OF SUPPLY

676094

EXPLOSIVES RESEARCH & DEVELOPMENT
ESTABLISHMENT

REPORT No. 21/R/49

REVIEW ON Nov 79

PORTSMOUTH ARSENAL L
DOVER, N. J.

The Preparation and Properties of Diethylene Glycol Dinitrate

PART VI

Conclusions and Recommendation

S. E. Smith

INCLOSURE 4 TO REPORT No. R-1814-50
ARMY ATTACHE, LONDON,

ENV 90

THIS DOCUMENT IS THE PROPERTY OF H.B.M. GOVERNMENT
AND ATTENTION IS CALLED TO THE PENALTIES ATTACHING
TO ANY INFRINGEMENT OF THE OFFICIAL SECRETS ACTS

It is intended for the use of the recipient only, and for communication to such officers under him as may require to be acquainted with its contents in the course of their duties. The officers exercising this power of communication are responsible that such information is imparted with due caution and reserve. Any person other than the authorised holder, upon obtaining possession of this document, by finding or otherwise, should forward it together with his name and address in a closed envelope to:-
THE SECRETARY, MINISTRY OF SUPPLY, ADELPHI, LONDON, W.C. 2.

Letter postage need not be prepaid, other postage will be refunded. All persons are hereby warned that the unauthorised retention or destruction of this document is an offence against the Official Secrets Acts.

Best Available Copy

Waltham Abbey,
Essex.

UNCLASSIFIED

November,
1949

20071109071

038051
PTC

A.R.E.
Publishing Section

UNCLASSIFIED

MINISTRY OF SUPPLY

EXPLOSIVES RESEARCH AND DEVELOPMENT ESTABLISHMENT

THE PREPARATION AND PROPERTIES OF DIETHYLENE
GLYCOL DINITRATE

Parts I and II. E.R.D.E. Report No. 18/R/48 - Ref. C.R.Temp. 7/11/2/1

By

S. Masterman
S.E.Smith
W.E.Turner

Parts III.	E.R.D.E. Report	2/R/49	-	Ref. X.R.	510/1.
" IV.	"	3/R/49	-	" X.R.	510/2
" V.	"	4/R/49	-	" X.R.	510/3
" VI.	"	21/R/49	-	" X.R.	510/5

by

S.E.Smith

WALTHAM ABBEY
ESSEX

Best Available Copy

UNCLASSIFIED

~~CONFIDENTIAL~~

UNCLASSIFIED

SUMMARY

I. Objects of the investigation

To examine the properties of diethylene glycol dinitrate, and to develop a method for its manufacture from diethylene glycol.

II. Scope of the investigation

The requirements of commercial diethylene glycol for nitration to the dinitrate for Service use have been investigated. The optimum conditions for the nitration, and for the stabilisation of diethylene glycol dinitrate, have been determined by laboratory and semi-technical scale investigations, and batch and continuous pilot plants for these operations have been developed.

The manufacture of D.E.G.N. and recovery of the spent acid have been established on the semi-manufacturing scale and quantities of the product supplied for experimental propellant manufacture.

The chemistry of D.E.G.N., the mechanism of its nitration and the reactions of the spent acid have been given some fundamental study.

No difficulty has been met in obtaining D.E.G.N. of acceptable purity and chemical stability by these processes.

The maximum overall manufacturing yield of D.E.G.N. so far obtained is 90 per cent theory as against 94 per cent for nitroglycerine. This is a disadvantage of D.E.G.N.

The spent acid from D.E.G.N. nitration retains some D.E.G.N. in solution and fumes off at ordinary temperatures after a 'life' depending on the composition of the acid. An acid composition for continuous nitration has been devised to give a spent acid with a safe life around 12 hours at 20°C. A procedure has been developed in which the spent acid from the continuous process is run directly down a dinitration tower in which the dissolved organic matter is destroyed. This involves the recovery of NO₂ as 60 per cent nitric acid and some additional nitric acid concentration.

The physical, chemical, explosive and physiological properties of diethylene glycol dinitrate so obtained have been determined.

Conclusions

1. D.E.G.N. can be safely manufactured in the same types of plant, batch or continuous, as are used for nitroglycerine. The continuous process is more suitable for operation with a continuous waste acid denitration. In both batch and continuous nitration the safety of D.E.G.N. enables simplifications to be made. The yield of D.E.G.N. is less and the consumption of nitric acid is somewhat higher than for nitroglycerine.
2. The spent acid from D.E.G.N. nitration is unstable and needs to be decomposed directly and continuously. Denitration tower practice has been found suitable for this purpose and can be safely linked up with continuous nitration.
3. D.E.G.N. is superior to nitroglycerine in safety in handling.
4. D.E.G.N. appears to have no disadvantageous physiological effects during the short manufacture to date; the long term effect on health of the workers is yet to be determined.

UNCLASSIFIED

~~CONFIDENTIAL~~

MINISTRY OF SUPPLY.

EXPLOSIVES RESEARCH AND DEVELOPMENT ESTABLISHMENT.

E.R.D.E. REPORT NO. 21/R/49.

The Preparation and Properties of Diethylene
Glycol Dinitrate.

Part VI. Conclusions and Recommendation.

by

S.E. Smith.

This report does not contain information of overseas
origin.

Submitted by

A. Foster
S.E.I.

Approved by

C.H. Johnson
A/C.S., E.R.D.E.

Waltham Abbey,
Essex.

UNCLASSIFIED

~~CONFIDENTIAL~~

DISTRIBUTION.

EXTERNAL.

T.P.A.3./T.I.B. (41)

Ministry of Supply.

Chief Scientist

C.S.(M)

C.I.

I.A. (Air), R.A.E., Farnborough

C.S.A.R. (2)

A.D. Amm. P.(X)

D.M.X.R.D.(3)

D.O.F.(X)

P.D.S.R.D.

Sec.O.B.(2)

S.A.C. (47)

War Office.

M.C. of S. Shrivenham (2)

Air Ministry.

D.D.O.R.(2)

Admiralty.

C.I.N.O.

Supt., R.N.P.F.

Consultant.

Dr. G. Rotter, C.B., C.B.E.

INTERNAL.

C.S.,E.R.D.E.

S.P.R.I.

S.P.R.II.

S.E.I.

S.C.E.

Mr. S.E. Smith

Technical Registry (2)

Library (2)

Information Bureau (2 + stock)

CONFIDENTIAL

Reference X.R.510/5.

CONCLUSIONS.

1. Diethylene Glycol.

DEG used for the manufacture of DEGN must be of high purity, otherwise the stability of the waste acid and the colour and stability of the ester itself, will be adversely affected.

The DEG used in the semi-technical and pilot plant scale manufacture was of adequate purity for large scale manufacture.

It is recommended that DEG supplied for nitration should conform to the specification attached to Part II of this report.

2. Nitration of DEG.

The nitration of DEG is very similar to that of glycerine; the mechanism of the reaction is the same, and the heat evolved is almost the same.

The chief differences between the two nitrations are :-

- (1) The best yield of DEGN obtainable is less than that of N.G., owing to the greater solubility of DEGN in its waste acid and in the wash liquors.
- (2) The waste acids produced in nitrations which give good yields of DEGN are unstable and decompose violently within a few hours of separation. On no account may water be added to the waste acid, since this accelerated the decomposition.
- (3) The separated DEGN contains considerably more dissolved acid than does N.G. (22-23% compared with 5-7%), and this acid must be recovered, otherwise the consumption of nitric acid would make the process uneconomic.

3. Properties of DEGN.

The most important differences between the properties of DEGN and N.G. are :-

- (1) DEGN is more volatile than N.G.
- (2) It is less sensitive than N.G.
- (3) It is more soluble in water and acid solutions than N.G.; and acids are more soluble in DEGN than in N.G. These enhanced solubilities in the case of DEGN are no doubt due to the ether link in its chemical structure.
- (4) DEGN freezes at a lower temperature than N.G.

/4.Plant Design.

CONFIDENTIAL

4. Plant Design.

DEGN can be made in the same types of plant as are used for N.G.

The lower sensitivity of DEGN permits simplifications in the design, compared with N.G. practise. For example, in the batch pilot plant, gravity separation with a sight glass and plug cock was used instead of a cockless system with displacement separation.

The lower freezing point of DEGN also largely eliminates the need for precautions against the freezing of the ester during manufacture and storage.

Batch manufacture of DEGN suffers from the following disadvantages :-

- (1) The spent acid cannot be stored for longer than a few hours, owing to its instability, except by fortifying it with additional strong acid.
- (2) Batch washing is less suitable for recovering acid from the separated DEGN than continuous countercurrent washing. A solution of 43% HNO_3 can be recovered by continuous countercurrent washing, whereas by batch washing, 30% HNO_3 is the maximum that can be obtained without undue loss of DEGN. In addition the need for sharp separation of the acid wash liquor requires a more complicated arrangement of plant, since the skimming method usually used in N.G. batch washing tanks is unsatisfactory in this case.

Hence, although a relatively simple batch nitrator can be used for DEGN, the batch process as a whole is unsuitable, and is not recommended.

On the other hand, a continuous process of nitration, separation, and washing, in which the waste acid and acid wash liquors are also continuously removed and denitrated, is especially suitable for DEGN manufacture, and this arrangement is recommended. The Schmid plant is suitable for this purpose, if means are provided for removing and denitrating the acids produced, without delay.

5. Yield and Nitrating Conditions.

As with N.G., the yield depends largely on fixing the nitrating conditions so as to produce a waste acid in which the loss of DEGN is as small as possible. Owing to the instability of acids having a minimum solvent power for DEGN, it is necessary to compromise between adequate stability and minimum solubility (i.e. maximum yield).

In the continuous pilot plant, the throughput time for the waste acid, from the time of nitration to the time of denitration, was 3 hours; allowing for a factor of safety, it is considered that the safe life of the waste acid, for this throughput time, should be 12 hours. The optimum nitration conditions arrived at in Part II of this report on the basis of laboratory investigations, produced a spent acid having a life of only four hours, and this is not thought good enough for safe working.

/A

UNCLASSIFIED

A waste acid with a safe life of approximately 12 hours, has a water content of 24% and this may be produced by nitrating with 2.76 parts of a mixed acid containing 69% nitric acid, 31% sulphuric acid.

A flow sheet for this recommended procedure is attached, from which it may be seen that the overall yield of DEGN is 90%.

This composition of mixed acid assumes that an anhydrous acid can be obtained from the nitric and sulphuric acids available. It is also necessary that the initial nitrous acid content of the mixed acid should not exceed 0.05%, otherwise the stability of the waste acid will be lessened.

RECOMMENDATION.

That for DEGN manufacture, DEG be nitrated in a continuous Schmidt or similar nitrator with 2.76 parts of a mixed acid containing 69% nitric acid and 31% sulphuric acid and not more than 0.05% nitrous acid, to give a spent acid with a safe life of approximately 12 hours, and an overall yield of DEGN of 90% theory.

The nitration procedure, spent acid treatment and recovery and the washing of the DEGN should be as described in parts IV and V of this Report.

/Flow Sheet

UNCLASSIFIED

FLOW SHEET FOR THE MANUFACTURE OF D

2.76 PARTS OF 69/

(BASIS: 100 PARTS O

D.E.G. used		M.A. used		W.A. Produced		Acid ester produced		Prewas liquor produced	
60.0 parts		165.6 parts		85.3 parts		140.3 parts		74.9 parts	
	%		% pts.		% pts.		% pts.		% pt
Recovered as DEGN	90.0	H ₂ SO ₄	31 51.4	H ₂ SO ₄	58.0 49.5	1.3 1.9		2.4 1.	
Lost in W.A.	4.2	HNO ₃	69 114.2	HNO ₃	12.6 10.7	22.9 32.1		43.0 32.	
Lost in Prewash	4.0			DEGN	5.5 4.7	75.8 106.3		6.0 4.	
Lost in later washing	0.9			H ₂ O	23.9 20.4	- -		48.6 36.	
Mechanical, etc. losses	0.9			H					
								Wash water used 36.4	

ATURE OF DEGN BY THE CONTINUOUS PROCESS
RTS OF 69/31 MIXED ACID
OO PARTS OF DEGN PRODUCED)

UNCLASSIFIED

Prewash liquors produced	Ester after prewash	Denitration acid produced	Nitric acid consumed (as 100%)	Sulphuric acid consumed (as 100%)
74.9 parts	101.8 pts.	306.0 parts	66.7 parts	2.9 parts
% pts.	% pts.	% pts.	pts.	Pts.
2.4 1.9	- -	63.0 192.8	Total usage 114.2	M.A. usage 51.4
			Recoverable	Fertification 141.4
43.0 32.1	- -	14.0 42.8	From W.A. 10.7	Total usage 192.8
			" DEGN in WA 3.0	
6.0 4.5	100 101.8	3.0 9.2	" Prewash 32.1	Recovery losses 2.9
			" DEGN in P.W. 2.9	(1 1/2%)
48.6 36.4	- -	20.0 61.2	Total recoverable 48.7	
			Consumed in nitration 65.5	
Wash water used 36.4pts		97% COV used 145.8 pts.	Recovery losses 1.2	
			(2 1/2%)	
			Total consumed 66.7	

S.No. 111
M.No. 485/49

August 14, 87

~~CONFIDENTIAL~~

UNCLASSIFIED



UNCLASSIFIED

~~CONFIDENTIAL~~