



AFRL-ML-WP-TP-2007-519

**DESCRIPTION OF SPHERICAL ABERRATION AND
COMA OF A MICROLENS USING VECTOR
DIFFRACTION THEORY (POSTPRINT)**

Glen D. Gillen and Shekhar Guha

Hardened Materials Branch

Survivability and Sensor Materials Division

SEPTEMBER 2006

Approved for public release; distribution unlimited.

See additional restrictions described on inside pages

STINFO COPY

© 2006 SPIE-OSA

**AIR FORCE RESEARCH LABORATORY
MATERIALS AND MANUFACTURING DIRECTORATE
WRIGHT-PATTERSON AIR FORCE BASE, OH 45433-7750
AIR FORCE MATERIEL COMMAND
UNITED STATES AIR FORCE**

NOTICE AND SIGNATURE PAGE

Using Government drawings, specifications, or other data included in this document for any purpose other than Government procurement does not in any way obligate the U.S. Government. The fact that the Government formulated or supplied the drawings, specifications, or other data does not license the holder or any other person or corporation; or convey any rights or permission to manufacture, use, or sell any patented invention that may relate to them.

This report was cleared for public release by the Air Force Research Laboratory Wright Site (AFRL/WS) Public Affairs Office and is available to the general public, including foreign nationals. Copies may be obtained from the Defense Technical Information Center (DTIC) (<http://www.dtic.mil>).

AFRL-ML-WP-TP-2007-519 HAS BEEN REVIEWED AND IS APPROVED FOR PUBLICATION IN ACCORDANCE WITH ASSIGNED DISTRIBUTION STATEMENT.

*//Signature//

SHEKHAR GUHA, Ph.D.
Agile IR Limiters
Exploratory Development
Hardened Materials Branch

//Signature//

MARK S. FORTE, Acting Chief
Hardened Materials Branch
Survivability and Sensor Materials Division

//Signature//

TIM J. SCHUMACHER, Chief
Survivability and Sensor Materials Division

This report is published in the interest of scientific and technical information exchange, and its publication does not constitute the Government's approval or disapproval of its ideas or findings.

*Disseminated copies will show “//Signature//” stamped or typed above the signature blocks.

REPORT DOCUMENTATION PAGE				<i>Form Approved</i> OMB No. 0704-0188	
The public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.					
1. REPORT DATE (DD-MM-YY) September 2006		2. REPORT TYPE Conference Paper Postprint		3. DATES COVERED (From - To)	
4. TITLE AND SUBTITLE DESCRIPTION OF SPHERICAL ABERRATION AND COMA OF A MICROLENS USING VECTOR DIFFRACTION THEORY (POSTPRINT)				5a. CONTRACT NUMBER In-house	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER 62102F	
6. AUTHOR(S) Glen D. Gillen (General Dynamics Information Technology, Inc.) Shekhar Guha (AFRL/MLPJ)				5d. PROJECT NUMBER 4348	
				5e. TASK NUMBER RG	
				5f. WORK UNIT NUMBER M08R1000	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) General Dynamics Information Technology, Inc. 5100 Springfield Pike, Suite 509 Dayton, OH 45431-1264				8. PERFORMING ORGANIZATION REPORT NUMBER AFRL-ML-WP-TP-2007-519	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) Air Force Research Laboratory Materials and Manufacturing Directorate Wright-Patterson Air Force Base, OH 45433-7750 Air Force Materiel Command United States Air Force				10. SPONSORING/MONITORING AGENCY ACRONYM(S) AFRL/MLPJ	
				11. SPONSORING/MONITORING AGENCY REPORT NUMBER(S) AFRL-ML-WP-TP-2007-519	
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution unlimited.					
13. SUPPLEMENTARY NOTES Conference paper published in the Proceedings of the International Optical Design Conference 2006, Vol. 6342. © 2006 SPIE-OSA. The U.S. Government is joint author of this work and has the right to use, modify, reproduce, release, perform, display, or disclose the work. PAO Case Number: AFRL/WS 06-1610, 30 Jun 2006. Paper contains color.					
14. ABSTRACT Light distributions of a plane wave refracted by a microlens are calculated using Kirchhoff vector diffraction theory. Numerical results for one and two-dimensional beam profiles and the onset and effects of spherical aberration and coma are investigated for different lens parameters.					
15. SUBJECT TERMS vector diffraction theory, microlenses, aberration					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT: SAR	18. NUMBER OF PAGES 18	19a. NAME OF RESPONSIBLE PERSON (Monitor) Shekhar Guha 19b. TELEPHONE NUMBER (Include Area Code) N/A
a. REPORT Unclassified	b. ABSTRACT Unclassified	c. THIS PAGE Unclassified			

Description of Spherical Aberration and Coma of a Microlens Using Vector Diffraction Theory

Glen D. Gillen^a and Shekhar Guha^b

^aAir Force Research Laboratory, Materials and Manufacturing Directorate, Anteon Corporation, Dayton, Ohio, 45431, USA;

^bAir Force Research Laboratory, Materials and Manufacturing Directorate, Wright-Patterson AFB, Ohio, 45433, USA

ABSTRACT

Light distributions of a plane wave refracted by a microlens are calculated using Kirchhoff vector diffraction theory. Numerical results for one and two-dimensional beam profiles and the onset and effects of spherical aberration and coma are investigated for different lens parameters.

Keywords: vector diffraction theory, microlenses, aberration

1. INTRODUCTION

Ray-tracing and geometrical optics are traditionally used to locate the focal regions of lenses. Although these techniques are useful for quick calculations of focal distances and the magnitudes and regions of spherical aberration and coma, they are limited if the vector components of the light fields and/or detailed beam distributions are desired. For example, in the field of optical trapping and manipulation of cold atoms, it is desirable to have precise knowledge of the field components of tightly focused laser beams. The trapping of cold atoms using the dipole radiation force was first observed in 1978, by Bjorkholm, *et al.*¹ Recent work by Dumke *et al.*² used a microlens array to focus laser light for the trapping of cold, neutral ⁸⁵Rb atoms. In this work we apply vector diffraction theory to the special case of a microlens in order to calculate light distributions and beam profiles in the focal region. Using the radiation and vector diffraction theory of Stratton,³ the diffraction integrals are numerically evaluated using average desktop computers. The onset and effects of spherical aberration and coma on one and two-dimensional beam profiles is investigated for various microlens and light parameters.

2. THEORY

The vector electromagnetic fields within a given source-free volume of space can be determined from the vector analog of Green's second identity using Stratton and Chu's method.⁴ The fields at point $\vec{r}$ can be expressed in terms of the field values on a surface, S , surrounding the point $\vec{r}$ using the formulae of Rothwell and Cloud⁵ as

$$\vec{E}(\vec{r}) = - \int_S da' \left[-i\omega\mu \left(\hat{n}' \times \vec{H}(\vec{r}') \right) G + \left(\hat{n}' \times \vec{E}(\vec{r}') \right) \times \vec{\nabla}' G + \left(\hat{n}' \cdot \vec{E}(\vec{r}') \right) \nabla' G \right], \quad (1)$$

$$\vec{H}(\vec{r}) = - \int_S da' \left[i\omega\epsilon \left(\hat{n}' \times \vec{E}(\vec{r}') \right) G + \left(\hat{n}' \times \vec{H}(\vec{r}') \right) \times \vec{\nabla}' G + \left(\hat{n}' \cdot \vec{H}(\vec{r}') \right) \nabla' G \right], \quad (2)$$

where $\hat{n}'$ is the normal to the input surface pointing into the volume, $\vec{r}'$ denotes a point on the surface S and da' is the surface area element pointing in the direction of $\hat{n}'$. The integrations extend over the input surface S and the values of $\vec{E}(\vec{r}')$ and $\vec{H}(\vec{r}')$ in the integrands are those evaluated 'just inside' the volume of space after the input surface. The Green's function, G , used in Eqs. 1 and 2 is given by

$$G = \frac{e^{-ik_1\rho}}{4\pi\rho}, \quad (3)$$

Further author information: (Send correspondence to G. D. Gillen)
G. D. Gillen: E-mail: ggillen@anteton.com, Telephone: 1 937 252 3132

where $k_1 = 2\pi n_1/\lambda$, n_1 being the refractive index of the medium between $\vec{r}$ and $\vec{r}'$, and

$$\rho^2 = |\vec{r}(x, y, z) - \vec{r}'(x', y', z')|^2. \quad (4)$$

When the surface separating the two media is spherical in shape, it is convenient to use a spherical coordinate system to evaluate the field integrals. For an incident plane wave traveling parallel to the z -axis, the values of the electromagnetic field components $\vec{E}(\vec{r}')$ and $\vec{H}(\vec{r}')$ ‘just outside’ of the spherical surface can be obtained from the surface curvature, refraction effects, and the appropriate Fresnel transmission coefficients. If E_o denotes the amplitude of the electric field of the incident plane wave, assumed to be polarized along the x -direction,

$$\vec{E}(\vec{r}') = E_o e^{-ip_2 \cos \theta'} \left(T_p \sin \theta'_t \cos \phi' \hat{r} + T_p \cos \theta'_t \cos \phi' \hat{\theta} - T_s \sin \phi' \hat{\phi} \right), \quad (5)$$

and

$$\vec{H}(\vec{r}') = \frac{n_1}{Z_o} E_o e^{-ip_2 \cos \theta'} \left(T_s \sin \theta'_t \sin \phi' \hat{r} + T_s \cos \theta'_t \sin \phi' \hat{\theta} + T_p \cos \phi' \hat{\phi} \right), \quad (6)$$

where $Z_o = \sqrt{\frac{\mu_o}{\epsilon_o}}$, $p_2 = 2\pi n_2 R/\lambda$, and R is the radius of curvature. θ' and ϕ' denote the angular coordinates of the point $\vec{r}'$. T_p is the Fresnel transmission function for p -polarized light,

$$T_p = \frac{2n_1 \cos \theta'}{n_1 \cos \theta' + n_2 \cos \theta'_t}, \quad (7)$$

and T_s is the Fresnel transmission function for s -polarized light,

$$T_s = \frac{2n_1 \cos \theta'}{n_2 \cos \theta' + n_1 \cos \theta'_t}. \quad (8)$$

The angle of transmission, θ'_t , is given through Snell’s Law, or

$$\theta'_t = \sin^{-1} \left(\frac{n_2}{n_1} \sin \theta' \right). \quad (9)$$

2.1. Normally incident light

The theoretical setup for this investigation is illustrated in Fig. 1. A plane wave is traveling within the microlens medium having a refractive index of n_2 and incident upon the spherical exit surface of the microlens. The curvature of the spherical exit surface is assumed to have a maximum half-angle of θ_{max} . Beyond the exit surface, the refractive index is assumed to be n_1 , where $n_2 > n_1$.

For incident plane waves traveling parallel to the z -axis, the electric and magnetic fields can be expressed as

$$E(\vec{r}) \equiv A \vec{U}(\vec{r}), \quad (10)$$

and

$$H(\vec{r}) \equiv A \frac{n_1}{Z_o} \vec{V}(\vec{r}), \quad (11)$$

where

$$\vec{U}(\vec{r}) = \int_0^{2\pi} \int_0^{\theta_m} \sin \theta' d\theta' d\phi' [\vec{u}_1 + \vec{u}_2 + \vec{u}_3] \quad (12)$$

and

$$\vec{V}(\vec{r}) = \int_0^{2\pi} \int_0^{\theta_m} \sin \theta' d\theta' d\phi' [\vec{v}_1 + \vec{v}_2 + \vec{v}_3] \quad (13)$$

with

$$A = \frac{-ip_1 T_p}{4\pi} E_o, \quad (14)$$

where $p_1 = 2\pi n_1 R/\lambda$.

The angle θ_m is the maximum half-angle of the aperture, and $\vec{u}_1, \vec{u}_2, \vec{u}_3, \vec{v}_1, \vec{v}_2$ and $\vec{v}_3$ represent the three vectors of the three individual terms of $\vec{E}$ and $\vec{H}$ in Eqs. 1 and 2, respectively. Each of these vectors have the following components:

$$\begin{aligned} u_{1x} &= f_2 G_1 (\cos \theta' \cos^2 \phi' + t_1 \cos \theta'_t \sin^2 \phi') \\ u_{1y} &= f_2 G_1 \sin \phi' \cos \phi' (\cos \theta' - t_1 \cos \theta'_t) \\ u_{1z} &= -f_2 G_1 \sin^2 \theta' \cos \phi', \end{aligned} \quad (15)$$

$$\begin{aligned} u_{2x} &= f_2 G_2 [(z_1 - z'_1) \alpha_{1y} - (y_1 - y'_1) \alpha_{1z}] \\ u_{2y} &= f_2 G_2 [(x_1 - x'_1) \alpha_{1z} - (z_1 - z'_1) \alpha_{1x}] \\ u_{2z} &= f_2 G_2 [(y_1 - y'_1) \alpha_{1x} - (x_1 - x'_1) \alpha_{1y}], \end{aligned} \quad (16)$$

$$\begin{aligned} u_{3x} &= f_2 G_2 \sin \theta'_t \cos \phi' (x_1 - x'_1) \\ u_{3y} &= f_2 G_2 \sin \theta'_t \cos \phi' (y_1 - y'_1) \\ u_{3z} &= f_2 G_2 \sin \theta'_t \cos \phi' (z_1 - z'_1), \end{aligned} \quad (17)$$

$$\begin{aligned} v_{1x} &= f_2 G_1 \sin \phi' \cos \phi' (t_1 \cos \theta' - \cos \theta'_t) \\ v_{1y} &= f_2 G_1 (t_1 \cos \theta' \sin^2 \phi' + \cos \theta'_t \cos^2 \phi') \\ v_{1z} &= f_2 G_1 (t_1 \sin \theta' \sin \phi'), \end{aligned} \quad (18)$$

$$\begin{aligned} v_{2x} &= f_2 G_2 [(z_1 - z'_1) \beta_{1y} - (y_1 - y'_1) \beta_{1z}] \\ v_{2y} &= f_2 G_2 [(x_1 - x'_1) \beta_{1z} - (z_1 - z'_1) \beta_{1x}] \\ v_{2z} &= f_2 G_2 [(y_1 - y'_1) \beta_{1x} - (x_1 - x'_1) \beta_{1y}], \end{aligned} \quad (19)$$

and

$$\begin{aligned} v_{3x} &= f_2 G_2 t_1 \sin \theta'_t \sin \phi' (x_1 - x'_1) \\ v_{3y} &= f_2 G_2 t_1 \sin \theta'_t \sin \phi' (y_1 - y'_1) \\ v_{3z} &= f_2 G_2 t_1 \sin \theta'_t \sin \phi' (z_1 - z'_1). \end{aligned} \quad (20)$$

The function f_2 is the phase of the electromagnetic field at the point $\vec{r}'$, or

$$f_2 = e^{-ip_2 \cos \theta'}, \quad (21)$$

and G_1 and G_2 are the functions:

$$G_1 \equiv 4\pi R G = \frac{e^{-ip_2 \rho_1}}{\rho_1}, \text{ and} \quad (22)$$

$$G_2 \equiv -\frac{1}{ip_2 \rho_1} \frac{\partial G_1}{\partial \rho_1} = \frac{G_1}{\rho_1} \left(1 + \frac{1}{ip_2 \rho_1}\right). \quad (23)$$

The parameter t_1 is the ratio of the Fresnel transmission function for s -polarized light to the transmission function for p -polarized light, or

$$t_1 \equiv \frac{T_s}{T_p} = \frac{n_1 \cos \theta' + n_2 \cos \theta'_t}{n_1 \cos \theta'_t + n_2 \cos \theta'}. \quad (24)$$

The components of $\vec{\alpha}_1$ and $\vec{\beta}_1$ introduced in Eqs. 17 and 20 are given by:

$$\begin{aligned} \alpha_{1x} &= \sin \phi' \cos \phi' (t_1 \cos \theta' - \cos \theta'_t) \\ \alpha_{1y} &= \cos \theta'_t \cos^2 \phi' + \cos \theta' \sin^2 \phi' \\ \alpha_{1z} &= -t_1 \sin \theta' \sin \phi', \end{aligned} \quad (25)$$

and

$$\begin{aligned}\beta_{1x} &= -\cos \theta' \cos^2 \phi' - t_1 \cos \theta'_t \sin^2 \phi' \\ \beta_{1y} &= \sin \phi' \cos \phi' (t_1 \cos \theta'_t - \cos \theta') \\ \beta_{1z} &= \sin \theta' \cos \phi'.\end{aligned}\quad (26)$$

The coordinates $x_1, y_1, z_1, x'_1, y'_1$, and z'_1 can be expressed in terms of the spherical coordinates as

$$\begin{aligned}x_1 &= r_1 \sin \theta \cos \phi \\ y_1 &= r_1 \sin \theta \sin \phi \\ z_1 &= r_1 \cos \theta,\end{aligned}\quad (27)$$

and

$$\begin{aligned}x'_1 &= \sin \theta' \cos \phi' \\ y'_1 &= \sin \theta' \sin \phi' \\ z'_1 &= \cos \theta',\end{aligned}\quad (28)$$

where $r_1 \equiv r/R$.




Figure 1. Theoretical setup for calculating light fields beyond the exit surface of a microlens. The plane wave is incident in the $+\hat{z}$ direction and refracted at the spherical exit surface with maximum half angle θ_{max} , and radius of curvature R .

2.2. Light incident at an angle

Figure 2 illustrates the theoretical setup for light incident upon the spherical surface at an angle of γ with respect to the z -axis. For ease of calculation, a second (double-primed) coordinate system is introduced such that $\hat{x}''$ and $\hat{z}''$ are rotated about $\hat{y}'$ by the angle of incidence, γ , with respect to $\hat{x}'$ and $\hat{z}'$, and $\hat{y}'' = \hat{y}'$.

All of the equations described previously for normally incident plane waves are valid for light incident at an angle, except for the fact that they apply to the double-primed coordinate system; i.e., all of the “primes” in Eqs. 1–29 are replaced with “double-primes.” The difficulty in using the double-primed coordinate system arises in the limits of the integrations. The limits of the integrations are determined by the shape of the exit surface in that coordinate system. In the primed coordinate system of Fig. 2, the limits of integration are $\theta' = 0$ to θ_m , and $\phi' = 0$ to 2π . In the double-primed coordinate system, the limits of integration are a complicated function of θ'' and ϕ'' due to the fact that z'' does not pass through the center of the exit surface and the exit surface is not angularly symmetric about r'' for all values of θ'' . Mathematically and computationally it would be desirable to perform the integrations over the primed coordinates. If an expression is found that transforms the double-primed coordinates to the primed coordinates, then the integration can be performed in the primed coordinate system where all of the variables and functions of $\vec{U}$ and $\vec{V}$ (Eqs. 12 and 13) are expressed in the primed coordinate system.




Figure 2. Theoretical setup for calculating light fields beyond the exit surface of a microlens. The plane wave is incident at an angle of γ with respect to the $+\hat{z}$ direction.

The relationships between the primed and double-primed spherical coordinates can be found by first expressing the spherical primed coordinates in terms of the cartesian primed coordinates, or

$$\begin{aligned} x' &= \sin \theta' \cos \phi' \\ y' &= \sin \theta' \sin \phi' \\ z' &= \cos \theta'. \end{aligned} \quad (29)$$

Then the double-primed coordinate system is rotated about $\hat{y}''$ by an angle $-\gamma$ to become the primed cartesian coordinates:

$$\begin{aligned} x'' &= x' \cos \gamma - z' \sin \gamma \\ y'' &= y' \\ z'' &= x' \sin \gamma + z' \cos \gamma. \end{aligned} \quad (30)$$

Substituting Eq. 29 into 30, we get

$$\begin{aligned} x'' &= (\sin \theta' \cos \phi') \cos \gamma - (\cos \theta') \sin \gamma \\ y'' &= \sin \theta' \sin \phi' \\ z'' &= (\sin \theta' \cos \phi') \sin \gamma + (\cos \theta') \cos \gamma. \end{aligned} \quad (31)$$

Expressing the double-primed spherical coordinates in terms of the double-primed cartesian coordinates results in

$$\theta'' = \cos^{-1} (\cos \theta' \cos \gamma + \sin \theta' \cos \phi' \sin \gamma) \quad (32)$$

and

$$\phi'' = \tan^{-1} \left(\frac{\sin \theta' \sin \phi'}{\sin \theta' \cos \phi' \cos \gamma - \cos \theta' \sin \gamma} \right). \quad (33)$$

Equations 1–29 can now be used for light incident upon a microlens at an angle of γ if the right hand side of Eqs. 32 and 33 are substituted for all of the “ θ'' ” and “ ϕ'' ” variables, respectively, in Eqs. 1–29.

3. NORMAL INCIDENCE CALCULATIONS

Figure 3 is a calculation of the modulus square of the electric field versus the on-axis distance from the center of curvature. The parameters chosen for this calculation are the same as those for the microlenses by Dumke *et al.*² to optically trap cold ^{85}Rb atoms. The microlens array is an array of spherically curved surfaces on one side of a fused silica substrate ($n = 1.454$ at $\lambda = 780$ nm). The light enters the other (flat) side of the substrate and

exits each spherical surface. The spherical surface has a radius of curvature of $R = 312.5 \mu\text{m}$ and a maximum half-angle of $\theta_m = 11.5^\circ$. Using geometrical optics, the focal spot should be observed at an axial distance of $3.2 R$ from the center of curvature. The peak intensity calculated in Fig. 3 is found at an axial distance of $3.11 R$. Figure 4 is a plot of the modulus square of the x -component of the electric field versus the radial position, at the focal plane ($z = 3.11 R$). One interesting feature of the on-axis intensity is the asymmetry before and after the focal region. The on-axis intensity modulations before the primary focal plane resemble the on-axis intensity characteristics for the diffraction of light by a circular aperture without a focusing medium.^{6,7} The on-axis intensity features before the focal spot indicate that light distributions in this region are influenced by the diffractive nature of the circular edge of the exit surface as well as the focal nature of the spherical shape of the exit surface. To further investigate the features before the focal plane, Figs. 5 and 6 are plots of the radial intensity at the locations of the on-axis minimum and maximum occurring just before the focal plane, respectively. The beam profiles calculated in Figs. 5 and 6 very closely resemble those of beam profiles calculated for diffraction of light by a simple circular aperture using scalar diffraction theory,⁶ and vector diffraction theory.^{7,8}




Figure 3. Modulus square of the x -component of the electric field versus axial position for a microlens with $2\pi nR/\lambda = 3660$ and a maximum half-angle of 11.5° .




Figure 4. Modulus square of the x -component of the electric field versus radial position for a microlens with $2\pi nR/\lambda = 3660$ and a maximum half-angle of 11.5° .

4. SPHERICAL ABERRATION

Figure 7 is a plot of the on-axis intensity for a lens with a focal parameter of $p_2 = 2\pi n_2 R/\lambda = 5 \times 10^5$ for a variety maximum half-angles. A lens parameter of $p_2 = 5 \times 10^5$ would correspond to a radius of curvature of 2.8 cm for 532-nm light. For $p_2 = 5 \times 10^5$ the onset of the effects of spherical aberration are evident for even a maximum half-angle of $\theta_m = 7.5^\circ$. As θ_m is increased from 5 to 7.5° the maximum value of the on-axis intensity increases. Beyond a half-angle of 7.5° , the maximum on-axis intensity no longer increases in magnitude with increasing θ_m . For $\theta_m = 10^\circ$, significant deviations exist in the on-axis intensity profile from that of an aberration-free lens such




Figure 5. Modulus square of the x -component of the electric field versus radial position for a microlens with $2\pi nR/\lambda = 3660$, a maximum half-angle of 11.5° , and an axial position of the on-axis minimum closest to the focal plane, or $z = 2.69R$.




Figure 6. Modulus square of the x -component of the electric field versus radial position for a microlens with $2\pi nR/\lambda = 3660$, a maximum half-angle of 11.5° , and an axial position of the first localized on-axis maximum closest to the focal plane, or $z = 2.54R$.

as that of the $\theta_m = 5^\circ$ on-axis intensity plot. Note that this was not the case for a microlens with $p_2 = 3660$ and $\theta_m = 11.5^\circ$, discussed in the previous section, illustrating that the onset of spherical aberration is dependent upon the ratio of the curvature of radius to the wavelength of light. The higher the ratio, the earlier the onset of spherical aberration for increasing maximum half-angles. In Fig. 7(b) the maximum half-angle is increased even further to investigate the effects of severe spherical aberration. Once the maximum on-axis intensity has saturated (around 7.5° for $p_2 = 5 \times 10^5$), the region of higher intensities elongates along the axis of propagation towards the exit surface of the lens. The growth of the “focal spot” towards the exit surface of the lens can be explained using geometrical optics. According to geometrical optics, if a series of parallel rays are refracted by a spherical surface then the paraxial rays focus at the expected focal spot. Non-paraxial rays will be refracted by the spherical surface such that they will cross the optical axis at a point closer to the exit surface. The farther the initial ray is located from the optical axis, the closer to the surface of the lens the ray will cross the optical axis.

Figures 8(a) and (b) are plots of the radial intensity profile at the focal plane of a plane wave refracted by a spherical exit surface as a function of the maximum half-angle on a linear and a logarithmic scale, respectively. The intensity axis of Fig. 8 is normalized to the incident intensity before the spherical surface. Once the on-axis maximum intensity saturation point is reached for increasing θ_m , no significant changes in the radial beam profile is observed on a linear scale for increasing θ_m . Figure 8(b) is the same plot as Fig. 8(a), except that the intensity scale is logarithmic. On a logarithmic scale it is apparent that the light collected by the outer rings of the spherical surface crosses the “focal” plane at off-axis locations; i.e., the energy collected by the outer regions of the spherical surface is propagated to off-axis locations in the focal plane. Away from the central focal region, the intensity of a spherically aberrated beam can be orders of magnitude higher than that of a non-aberrated beam.




Figure 7. Calculated values of the intensity (normalized to the incident intensity) along the axis of the lens (normalized to the radius of curvature of the lens) for various values of the maximum half-angle θ_m (5° , 7.5° , 10° , 15° , 20° , and 25°) of the lens surface for a normally incident plane wave with $2\pi nR/\lambda = 5 \times 10^5$.




Figure 8. Calculated values of the focal plane intensity distributions (normalized to the incident intensity) along the x -axis (normalized to the radius of curvature of the lens) on a linear and long scale, respectively, for various values of the maximum half-angle θ_m (5° , 8° , 10° , 15° , and 25°) of the lens surface. The light is a normally incident plane wave with $2\pi nR/\lambda = 5 \times 10^5$, and the ‘focal plane’ occurs for $z/R = 2.984$.

5. OFF-AXIS FOCUSING AND COMA

Figure 9 is a calculation of the intensity of the light field versus x and y in the focal plane ($z/R = 3.15$ for $2\pi n_2 R/\lambda = 10^4$) and incident angles, γ , of 0° , 7° and 15° . With an incident angle of 7° the effects of coma are observed as subtle partial rings on the far side of the focal spot, and a slight elongation of the focal spot in the direction of the incident angle. For an incident angle of 15° , severe coma is observed as a broadening of the focal spot in both the x and y -directions in addition to conical beam fanning as expected according to geometrical optics. However, contrary to geometrical optics (which would predict a smooth intensity decay throughout the beam fanning) intensity calculations presented here predict the interference patterns arising from the wave nature of light. The degree of coma observed is also a function of the radius of curvature to wavelength ratio. Similar to Fig. 9, Fig. 10 is a series of intensity versus x and y images, where the only difference is that the value of p_2 has been decreased from 10^4 to 3660. For smaller p_2 , the effects of coma for $\gamma = 7^\circ$ have essentially been eliminated, and the coma effects for $\gamma = 15^\circ$ have been significantly reduced, as compared to Fig. 9.

Figure 11 is a calculation of the beam intensity profile (along the x -axis) for the same parameters as that of Fig. 9, but a series of angles of incident leading up to 7° . The relative ranges for each graph are kept constant to aid in the visual comparison of the absolute intensities and radial beam fanning. Even for an angle of incidence of 3° asymmetries in the beam profile are observed for $2\pi nR/\lambda = 10^4$. As the angle of incidence is increased, the overall maximum intensity decreases and the width of the focal spot increases as well as the amount of energy observed outside of the primary focal spot.




Figure 9. Calculated intensity distributions in the focal plane for $2\pi nR/\lambda = 10^4$ with $\theta_m = 11.54^\circ$, $n = 1.454$, and incident angles of $\gamma = 0^\circ$, 7° and 15° , respectively.




Figure 10. Calculated intensity distributions in the focal plane for $2\pi nR/\lambda = 3660$ with $\theta_m = 11.54^\circ$, $n = 1.454$, and incident angles of $\gamma = 0^\circ$, 7° and 15° , respectively.




Figure 11. Effects of coma on the radial beam profile of a plane wave incident on a microlens spherical exit surface with $2\pi nR/\lambda = 10^4$ and $z/R = 3.15$ at an angle of (a) 3° , (b) 5° , and (c) 7° . All horizontal and vertical scales are over the same ranges.

6. CONCLUSIONS

A computational method has been employed to determine all of the vector electromagnetic field components for a region of space beyond a spherical microlens using vector diffraction theory. Using this method the field and intensity distributions are obtained and the onset and effects of spherical aberration and coma can be studied. The onset and severity of spherical aberration depend on both the maximum collection angle of the lens and the ratio of the radius of curvature to the wavelength of light. The onset and severity of coma depend on both the angle of incidence and the ratio of the radius of curvature of the lens to the wavelength of the incident light.

REFERENCES

1. J. E. Bjorkholm, R. R. Freeman, A. Ashkin, and D. B. Pearson, "Observation of focusing of neutral atoms by the dipole forces of resonance-radiation pressure," *Phys. Rev. Lett.* **41**, 1361–1364 (1978).
2. R. Dumke, M. Volk, T. Mütther, F. B. J. Buchkremer, G. Birkel, and W. Ertmer, "Micro-optical realization of arrays of selectively addressable dipole traps: a scalable configuration for quantum computation with atomic qubits," *Phys. Rev. Lett.* **89**, 097903 (2002).
3. J. A. Stratton *Electromagnetic Theory* (McGraw-Hill Book Company, Inc., New York, NY 1941.)
4. J. A. Stratton and L. J. Chu, "Diffraction theory of electromagnetic waves," *Phys. Rev.* **56**, 99 (1939).
5. E. J. Rothwell and E. J. Cloud, *Electromagnetics* (CRC Press, Boca Raton, FL 2001.)
6. G. D. Gillen and S. Guha, "Modeling and propagation of near-field diffraction patterns: a more complete approach," *Am. J. Phys.* **72**, 1195 (2004).
7. S. Guha and G. D. Gillen, "Description of light propagation through a circular aperture using nonparaxial vector diffraction theory," *Opt. Express* **13**, 1424 (2005).
8. G. D. Gillen, S. Guha, and K. Christandl, "Optical dipole traps for cold atoms using diffracted laser light," *Phys. Rev. A* **73**, 013409 (2006).