

UM-Translog-2: A Planning Domain Designed for AIPS-2002

Dan Wu

Department of Computer Science
University of Maryland
College Park, MD 20742
E-mail: dandan@cs.umd.edu

Dana Nau

Department of Computer Science,
and Institute for Systems Research
University of Maryland
College Park, MD 20742
E-mail: nau@cs.umd.edu

First version: Jan. 8 2002

Revision: Sept. 18, 2002

This work was supported in part by the following grants, contracts, and awards: Air Force Research Laboratory F30602-00-2-0505, Army Research Laboratory DAAL0197K0135, Naval Research Laboratory N00173021G005, and the University of Maryland General Research Board. Opinions expressed in this paper are those of authors and do not necessarily reflect opinion of the funders.

Report Documentation Page				Form Approved OMB No. 0704-0188	
Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.					
1. REPORT DATE 18 SEP 2002		2. REPORT TYPE		3. DATES COVERED 00-00-2002 to 00-00-2002	
4. TITLE AND SUBTITLE UM-Translog-2: A Planning Domain Designed for AIPS-2002				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S)				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) University of Maryland, Department of Computer Science, College Park, MD, 20742				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution unlimited					
13. SUPPLEMENTARY NOTES					
14. ABSTRACT This document describes UM-Translog-2, which is an extended version of the UM Translog planning domain. The extensions include some numerical-computation features to make the domain a more realistic model of transportation-logistics problems. We are proposing UMTranslog-2 as a candidate domain for AIPS-2002 planning competition.					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT Same as Report (SAR)	18. NUMBER OF PAGES 18	19a. NAME OF RESPONSIBLE PERSON
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified			

Abstract

This document describes UM-Translog-2, which is an extended version of the UM Translog planning domain. The extensions include some numerical-computation features to make the domain a more realistic model of transportation-logistics problems. We are proposing UM-Translog-2 as a candidate domain for AIPS-2002 planning competition.

1 Background and Motivation

As planning systems grow in sophistication and capabilities, planning domains with matching complexity need to be devised to assist in the analysis and evaluation of planning systems and techniques. UM Translog [1] is a planning domain designed specially for this purpose. UM-Translog provides a rich set of entities, attributes, operators and conditions, which can be used to specify rather complex planning problems with a variety of plan interactions.

This document describes UM-Translog-2, which is an extended version of the UM Translog planning domain. The extensions include some numerical-computation features to make the domain a more realistic model of transportation-logistics problems.

We have written descriptions of UM-Translog-2 both as an HTN planning problem, using the SHOP2 [5] domain-definition syntax, and as a PDDL2.1 planning problem. PDDL2.1 [3] is the language developed for the AIPS-2002 planning competition: it is a significant extension of PDDL that is intended to support representation of real time problem domains involving numeric-valued resources.

Section 2 describes domain testing, and Section 3 describes some current issues about the domain. Section 4 describes the domain, in PDDL format.

2. Domain Testing

Writing the HTN definition of UM-Translog-2 was relatively straightforward, since UM Translog was also an HTN planning domain. However, writing a PDDL2.1 version of the same definition was more difficult.

In general, rewriting an HTN planning problem as a PDDL planning problem is not always possible. Some HTN planning problems that have no equivalent in PDDL, because HTN planning is strictly more expressive than classical planning. UM-Translog-2 is not one of those problems: such problems have an unbounded amount of recursion in their HTN methods, whereas the HTN methods for UM-Translog-2 have no recursion at all. However, even when an HTN planning problem is translatable into a PDDL planning problem, the translation task can still be quite complicated (see [4] for a description of some of the difficulties that can occur). As a result, it took us several months to complete the translation and test it for correctness.

Here was how we tested the translation for correctness:

- a. We wrote a random problem generator for UM-Translog-2.
- b. We implemented the domain for an action-based planner, namely TLPlan [2]. It would have been better to use a fully automated planner that could take the PDDL2.1 description as its only input—but such a planner was not available that could also solve the problems efficiently. We also added some control formulas into the TLPlan version of the domain, being careful only to specify control formulas that would not affect the correctness of the translation.
- c. We implemented UM-Translog-2 domain for our HTN planner, SHOP2.
- d. We ran ten problem-sets (10 problems in each set) generated by random problem generator on both TLPlan and SHOP2. For all problems, we checked whether both planners reached the same conclusion, i.e. that there existed a solution or that there did not exist a solution.

For those problems in which both planners found plans, we translated the problem and the plans into PDDL format, and used the PDDL plan validator (which was provided to us by the chairs of the AIPS-2002 planning competition) to check if these plans were valid.

3. Current Issues

Here are some issues that still need to be addressed, especially with regards to testing the validity of the domain:

- a. Because the domain is very complicated, it is hard for the random problem generator to generate problems that are solvable with a good probability.
- b. It would be better if we there were an action-based planner that could take PDDL2.1 directly as input and was efficient enough to handle the domain.
- c. Although we added some control formulas to TLPlan, we did not succeed in making it efficient enough to handle big problems in the domain—so we were unable to test those problems using TLPlan. We could only use small problems, and try to manipulate the parameters in the random problem generator so that we could get cases that are as comprehensive as possible.

4 Domain Description

4.1 Overview

As in UM Translog, in UM-Translog-2, the planner is given one or more goals, where a goal is typically the delivery of a particular package from an origin to a destination.

In UM-Translog-2, we added some numerical computation features to make it more realistic and suitable for AIPS2002 competition.

In order to do this, we modeled additional aspects of transport logistics not present in the UM Translog. These include the following restrictions:

- A vehicle can be moved only with enough gas, given the newly-introduced numerical distances between locations and gpm, gasoline consumed by a vehicle per mile.
- There is no refueling for vehicles
- A vehicle cannot load packages beyond its weight and volume capacity
- A vehicle has weight, height, length and width
- A package has weight and volume.
- An equipment like crane cannot pick up a package beyond its weight and volume capacity
- A route cannot accommodate a vehicle beyond its height and weight capacity
- A location cannot accommodate packages beyond its volume capacity
- A location cannot accommodate vehicle beyond its length, height and width capacity

The domain is described in more detail in the following sections. Section 4.2 introduces entities. Predicates and functions are described in section 4.3 and operators are described in section 4.4.

4.2 Entities

Entities include regions, cities within each region, locations within each city and individual objects (routes, vehicles, equipment, and packages). Each entity is described by a constant symbol (e.g., “Truck-1”, “Package-2”) and one or more functions and predicates that are asserted by a user (in the initial state given to the planner) or by the effects of instantiated plan operators. Predicates and functions are summarized in section 4.3. Each entity has a type. Primary entity types include region, city, location, route, vehicle, equipment and package, described in the following subsections.

4.2.1 Region

Each region contains one or more cities (specified via predicate **in-region**).

4.2.2 City

Each city can have one or more locations (specified via predicate **in-city**).

4.2.3 Location

Each location is located in a specific city (specified via predicate **in-city**).

Location subtypes include transportation centers (specified via predicate **tcenter**) and non-transportation centers. Transportation center subtypes (specified via predicate **typel**) include **airport** and **train-station**. Non-transportation centers denote customer locations, such as businesses, homes, etc.

A transport center can be used for air/rail direct and indirect transportation (see section 4.4). Transportation centers can be available (specified via predicate **availablel**) or unavailable. For example, a particular airport may be temporarily unavailable due to bad weather.

A transportation center can optionally be specified as a transportation hub (via **hub** predicate). Hub transportation centers can be used for indirect transportation (see section 4.4). A transportation center serves its own city. Thus, air or rail travel from a specific city must use a transportation center in that city. Hub transport centers serve specific regions (specified via predicate **serves**), rather than cities. A hub serves a region if it has rail/air route connection to a transport center in that region.

Locations can serve as the origin or destination of a package. Locations have their volume capacity (specified via function **volume-cap-l**). The total volume of all packages (see section 4.2.7) in a location (specified via function **volume-load-l**) at any given time cannot exceed its volume capacity.

Also, a location cannot accommodate a vehicle (see Section 4.2.5) whose length exceeds location’s length capacity (specified via function **length-cap-l**) or whose width exceeds location’s width capacity (specified via function **width-cap-l**) or whose height exceeds location’s height capacity (specified via function **height-cap-l**). The distance between any two locations is specified via function **distance**.

4.2.4 Routes

Route includes types **road-route**, **rail-route**, and **air-route**.

Road routes connect two cities (specified via predicate **connect-city**). All locations within a city are assumed to be connected by roads, and thus road routes between individual city locations are not specified. Rail and air routes connect airports and train stations, respectively (specified via predicate **connect loc**).

Routes have an origin, a destination, and a route type (specified via predicate **connect-city** or **connect loc**). Note that routes are directional: traffic flows from the origin to the destination. Route has an availability status (specified via predicate **availabler**). For example, a particular road route may be temporarily unavailable due to construction. Routes types are compatible with particular types of vehicles (see Section 4.2.5), as follows:

Route Type	Vehicle Type
road-route	truck
rail-route	train
air-route	airplane

Route-vehicle type compatibilities are specified via predicate **rv-compatible**.

A route cannot be used by a vehicle whose height exceeds route's height capacity (specified via function **height-cap-r**) or whose total weight (including vehicle weight and load) exceeds route's weight capacity (specified via function **weight-cap-r**). The height and weight capacity of local roads within a city are specified via functions **local-height** and **local-weight**.

4.2.5 Vehicle Types

Primary vehicle types include **truck**, **airplane** and **train** (specified via predicate **typevp**). Each vehicle also has a physical subtype (specified via predicate **typev**). The physical subtype for airplane is **air**, and the physical subtype for trucks and trains are as following:

Physical Subtype	Examples
regularv	tractor-trailer truck, delivery van, boxcar, etc.
flatbed	flatbed truck, flatcar, etc.
tanker	tanker truck, tanker car, etc.
hopper	dump truck, hopper car, etc.
auto	car carrier truck/train

A vehicle's primary type determines its compatibility with a particular route (see Section 4.2.4), while its physical subtype determines its compatibility with a package (see Section 4.2.7).

A vehicle is at a location and has availability status (specified via predicates **at-vehicle** and **availablev**, respectively). A vehicle may have other properties, depending on its subtype, as shown in the following table:

Physical Subtype	Predicates
air	door-open, ramp connected

auto hopper regular tanker	ramp-down chute-connected door-open hose-connected, valve-open
---	---

A vehicle has weight (specified via function **weight-v**), length (specified via function **length-v**), width (specified via function **width-v**) and height (specified via function **height-v**).

A vehicle consumes gas when moving. The gas-consumption rate of a vehicle is specified via function **gpm** (gallon per mile). A vehicle can be moved between two locations only if we have:

Gas left in the vehicle (specified via function **gas-left**) $\geq$ vehicle's **gpm** * distance between two locations.

The total volume of all packages in a vehicle (specified via function **volume-load-v**) cannot exceed its volume capacity (specified via function **volume-cap-v**) and the total weight of all packages in a vehicle (specified via function **weight-load-v**) cannot exceed its weight capacity (specified via function **weight-cap-v**).

4.2.6 Equipment Types

Equipment types are **plane-ramp** and **crane**. Equipments of these types are used to load airplanes and flatbed trucks/trains, respectively.

An equipment is at a location (specified via predicate **at-equipment**). And there is no action that changes the location of an equipment.

The status of a plane ramp is described using predicate **ramp-connected**.

The status of a crane is described using predicate **empty**. Also a crane cannot pick up a package beyond its weight capacity (specified via function **weight-cap-c**) or volume capacity (specified via function **volume-cap-c**).

4.2.7 Package Types

Each packages has a physical subtype from the following list (specified via predicate **typep**)

Physical Subtype	Examples
regular	parcels, furniture, etc.
bulky	steel, lumber, etc.
liquid	water, petroleum, chemicals, etc.
granular	sand, ore, etc.
cars	automobiles
mail	mail

The physical subtype of a package must be compatible with the vehicle's physical subtype (see Section 4.2.5). The following table lists compatible package and vehicle physical subtypes (specified via predicate **pv-compatible**):

Package Subtype	Vehicle Subtype
regularp	regularv
bulky	flatbed
liquid	tanker
granular	hopper
cars	auto
regularp	air
mail	air, regularv

Each package has a location (specified via predicate **at-package**), weight (specified via function **weight-p**) and volume (specified via function **volume-p**). Fees need to be collected before a package can be transported (specified via predicate **fees-collected**)

When package is at its destination, it will be delivered (specified via predicate **delivered**).

4.3 Predicates and Functions

This section presents a summary of domain predicates and functions present in the PDDL version.

The following are the domain predicates:

Predicates	Descriptions
(at-equipment ?e - equipment ?l - location)	equipment ?e is at location ?l
(at-packagec ?p - package ?c - crane)	package ?p is at crane ?c
(at-packagel ?p - package ?l - location)	package ?p is at location ?l
(at-packagev ?p - package ?v - vehicle)	package ?p is at vehicle ?v
(at-vehicle ?v - vehicle ?l - location)	vehicle ?v is at location ?l
(availablel ?l - location)	location ?l (a transport center) is available
(availablel ?r - route)	route ?r is available
(availablev ?v - vehicle)	vehicle ?v is available
(chute connected ?v - vehicle)	chute of vehicle ?v (hopper) is connected to (un)load cargo
(clear)	bookkeeping predicate in the domain (see section 4.4)
(connect-city ?r - route ?rtype - rtype ?c1 ?c2 - city)	route ?r of type ?rtype connects city ?c1 to city ?c2
(connect-loc ?r - route ?rtype - rtype ?l1 ?l2 - location)	route ?r of type ?rtype connects location ?l1 to location ?l2
(delivered ?p - package ?d - location)	package ?p is delivered at location ?d
(door-open ?v - vehicle)	door of vehicle ?v is open
(empty ?c - crane)	crane ?c is empty
(fees-collected ?p - package)	fees have been collected for package ?p
(hose-connected ?v - vehicle)	hose connected for ?v (tanker) to (un)load cargo
(h-start ?p - package)	bookkeeping predicate in the domain (see section 4.4)
(hub ?l - location)	location ?l is a hub
(in-city ?l - location ?c - city)	location ?l is located in city ?c
(in-region ?c - city ?r - region)	city ?c is inside region ?r
(move ?p - package) / (move-emp ?v - vehicle) / (over ?p - package)	bookkeeping predicate in the domain (see section 4.4)
(pv-compatible ?ptype - ptype ?vtype - vtype)	package physical subtype ?ptype is compatible with vehicle physical subtype ?vtype
(ramp-connected ?v - vehicle ?r - plane-ramp)	plane ramp ?r is connected to vehicle ?v (airplane)
(ramp-down ?v - vehicle)	ramp of vehicle ?v (auto) is down to (un)load cargo
(rv-compatible ?rtype - rtype ?vptype - vptype)	route type ?rtype is compatible with primary vehicle type ?vptype
(serves ?h- location ?r - region)	location ?l (hub) serves region ?r

(tcenter ?l - location) (t-end ?p - package) / (t-start ?p - package) (typel ?l - location ?type - ltype) (typep ?p - package ?type - ptype) (typev ?v - vehicle ?type - vtype) (typevp ?v - vehicle ?type - vptype) (unload ?v - vehicle) (valve-open ?v - vehicle)	location ?l is tcenter bookkeeping predicate in the domain (see section 4.4) location ?l (tcenter) is of type ?type (train station or airport) package ?p has physical subtype ?type vehicle ?v has physical subtype ?type vehicle ?v has primary type ?type (truck, train, airplane) bookkeeping predicate in the domain (see section 4.4) valve open for vehicle ?v (tanker) to (un)load cargo
---	---

The following are the domain functions:

Functions	Descriptions
(distance ?l1 ?l2 - location) (gas-left ?v - vehicle) (gpm ?v - vehicle) (height-v ?v - vehicle) (height-cap-l ?l - location) (height-cap-r ?r - route) (length-v ?v - vehicle) (length-cap-l ?l - location) (local-height ?c - city) (local-weight ?c - city) (volume-cap-c ?c - crane) (volume-cap-l ?l - location) (volume-cap-v ?v - vehicle) (volume-load-l ?l - location) (volume-load-v ?v - vehicle) (volume-p ?p - package) (weight-cap-c ?c - crane) (weight-cap-r ?r - route) (weight-cap-v ?v - vehicle) (weight-p ?p - package) (weight-load-v ?v - vehicle) (weight-v ?v - vehicle) (width-v ?v - vehicle) (width-cap-l ?l - location)	distance between two locations ?l1 and ?l2 gallons of gas left in vehicle ?v gallons of gas ?v consumes per mile height of vehicle ?v in feet height capacity of location ?l in feet height capacity of route ?r in feet length of vehicle ?v in feet length capacity of location ?l in feet height capacity of local road route in city ?c in feet weight capacity of local road route in city ?c in pounds volume capacity of crane ?c in liters volume capacity of location ?l in liters volume capacity of vehicle ?v in liters total volume of packages at location ?l in liters total volume of packages in vehicle ?v in liters volume of package ?p in liters weight capacity of crane ?c in pounds weight capacity of route ?r in pounds weight capacity of vehicle ?v in pounds weight of package ?p in pounds total weight of packages in vehicle ?v in pounds weight of vehicle ?v in pounds width of vehicle ?v in feet width capacity of location ?l in feet

4.4 Operators

This section describes the symbols that denote operators in UM-Translog-2. Although UM-Translog-2 is based on UM Translog, the operators in these two domains are quite different. UM translog is developed for HTN planning systems while UM-Translog-2 is written in action-based format for competition purpose. Some bookkeeping predicates are needed during the translation process as described below.

4.4.1 Administrative Operators

Prior to carrying a package to its destination, fees should be collected. Each package must be delivered to its destination. These activities are denoted by the operator symbols **collect-fees(?p)** and **deliver(?p, ?l)**, where ?p is a variable symbol denoting a package and ?l is a variable symbol denoting a location. Fees for a package need to be collected only once, and a package can be delivered only once.

4.4.2 Operators for Loading/Unloading

There are a number of operators for loading and unloading packages into/from vehicles, depending on the type of the vehicle and the package. In some cases, special equipment such as crane needs to be used for that purpose.

Before loading a regular vehicle, the door of the vehicle must be open and after loading all packages, the door of the vehicle must be closed. These steps are denoted by actions **open-door-regular(?v)**, **load-regular(?p ?v ?l)**, **close-door-regular(?v)**. Unloading a regular vehicle involves the same steps, just replacing **load-regular(?p, ?v, ,?l)** with **unload-regular(?p ?v ?l)**. ?p is a variable of type package, v? is a variable of type vehicle, and ?l is a variable of type location. ?l is used to make sure the vehicle and the package are at the same location.

Loading a flatbed requires sequence of actions **pick-up-package-ground(?p ?c ?l)** and **put-down-package-vehicle(?p ?c ?v ?l)**. Unloading a flatbed requires sequence of actions **pick-up-package-vehicle(?p ?c ?v ?l)** and **put-down-package-ground(?p ?c ?l)**. ?c denotes crane needed for loading and unloading the flatbed.

Before loading a truck or train of type hopper, the chute of the vehicle must be connected and after loading all packages, the chute must be disconnected. These steps are denoted by actions **connect-chute(?v)**, **fill-hopper(?p ?v ?l)**, and **disconnect-chute(?v)**. Unload is similar, except that **empty-hopper(?p ?v ?l)** should be replaced with **fill-hopper(?p ?v ?l)**.

Before loading a vehicle of type tanker, the hose of the vehicle must be connected first and then the valve of the vehicle needs to be open. After loading all packages, the valve must be closed first and then the host must be disconnected. These steps are denoted by actions **connect hose(?v)**, **open-valve(?v)**, **fill-tank(?v ?p ?l)**, **close valve(?v)**, **disconnect-hose(?v ?p)**. Unload is similar, except that **fill-tank(?v ?p ?l)** should be replaced with **empty-tank(?v ?p ?l)**.

Before loading a vehicle of type auto, the ramp of the vehicle must be lowered and after loading all packages, the ramp must be raised. These steps are denoted by actions **lower-ramp(?v)**, **load-**

cars(?p ?v ?l) and **raise ramp(?v)**. Unloading is similar, except that **load-cars(?p ?v ?l)** should be replaced with **unload-cars(?p ?v ?l)**.

Before loading a vehicle of type air, a conveyor ramp must be attached to the vehicle first and then the door of the vehicle must be open. After loading vehicles, the door must be closed first and then the ramp needs to be detached. These steps are denoted by actions **attach-conveyor ramp(?v, ?r, ?l)**, **open-door-airplane(?v)**, **load-airplane(?p, ?v, ?l)**, **detach-conveyor-ramp(?v, ?r, ?l)** and **close door-airplane(?v)**. Unloading is similar, except that **load-airplane(?p, ?v, ?l)** should be replaced with **unload-airplane(?p, ?v, ?l)**.

In the effect list of operators for unloading a vehicle, there are some special predicates used for bookkeeping purpose as explained below:

a. **(not (move ?p))**

As a rule in UM Translog domain (see section 4.4.3 for more explanation), each movement of a package ?p from a location ?l1 to a location ?l2 by using a vehicle ?v involves three steps: loading ?p into ?v at ?l1, moving ?v from ?l1 to ?l2 and unloading ?p from ?v at ?l2. This means that ?p must be unloaded at ?l2 before it can be moved further more. So after each movement of ?v from ?l1 to ?l2, predicate **(move ?p)** will be added to the current state, and after ?p is unloaded at ?l2, this predicate will be removed from current state which means ?p can be moved again.

b. **(unload ?v)** and **(not (clear))**

After our task is finished, we need to make sure that all things are cleaned up after us. For example, we should close the door of all regular vehicles we have used, raise the ramps of all auto vehicles we have used, etc. **(clear)** is a predicate used to indicate that all things have been cleaned up after us. **(unload ?v)** means that we have used vehicle ?v and need to do some clean up stuff for ?v. So in the effect of unloading operators, **(unload ?v)** is added to the current state and **(clear)** is deleted from the current state. **(clear)** can be added to the current state by **clean-domain** operator(see section 4.4.4) when there is nothing which needs to be cleaned up. **(clear)** is the goal of each problem of the domain.

4.4.3 Operators for Moving


In UM Translog domain, there are some rules about how to move a package from its origin to its destination. This involves choosing a suitable path (a sequence of routes from the origin to the destination), and moving the package along that path via a series of carry-direct tasks.

A (carry-direct ?package ?location1 ?location2) task involves picking a route directly connecting ?location1 and ?location2, and choosing a vehicle that is compatible both with the package and the route. Only those vehicles that are at ?location1 or one step away from ?location1 (which means that this vehicle can be moved from its location to location1 directly without passing by any other locations) can be used. The task is accomplished by moving that vehicle to ?location1, loading the package into the vehicle, moving the vehicle to ?location2, and finally unloading the package. When a vehicle moves, so do the packages it contains.

The diagram in Figure 1 shows the legal paths to transport a package. The origin of the package can be either clocation1 (a customer location, not a transportation center) or tcenter1 (a transportation center), and similarly the destination of a package can be either clocation2 (a

customer location, not transportation center) or tcenter2 (a transportation center). There are some additional rules about this path:

1. clocation1 can only use a transportation center (tcenter1) in the same city, so does clocation2
2. tcenter1 and tcenter2 can not be hubs if hub1 is used.
3. The route that connects tcenter1 and hub1 is a rail/air route.
4. The route that connects hub1 and tcenter2 is a rail/air route.
5. If a package is transported from clocation1 or transported to clocation2 using a route between tcenter1 and tcenter2, then this route must be a rail/air route.



All possible legal paths for transporting a package are defined more precisely as follows.

A package p must be transported from origin $?ori$ to destination $?des$ through one of following paths:

- a. If $?ori$ and $?des$ are in the same city c , use local road route in city c .
- b. If $?ori$ and $?des$ are in two different cities $c1$, $c2$, use a road route r that connects $c1$ and $c2$.
- c. If $?ori$ and $?des$ are both train stations, use a rail route r that connects $?ori$ and $?des$.
- d. If $?ori$ and $?des$ are both airports, use an air route r that connects $?ori$ and $?des$.
- e. If $?ori$ and $?des$ are both tcenters (train station or airport), but are both not hub and hub $hub1$ is of same type as $?ori$ and $?des$ (train station or airport), then
 - transport p from $?ori$ to $hub1$ use method c or d
 - transport p from $hub1$ to $?des$ use method c or d
- f. If $?ori$ is not tcenter, $?des$ is tcenter, and
 - $?ori$ is in city $c1$ and
 - $tcenter1$ is a transportation center in $c1$ and $tcenter1$ is of same type as $?des$, then
 - transport p from $?ori$ to $tcenter1$ use method a
 - transport p from $tcenter1$ to $?des$ use method c, d or e
- g. If $?ori$ is tcenter, $?des$ is not tcenter, and
 - $?des$ is city $c2$, and
 - $tcenter2$ is a transportation center in $c2$ and $tcenter1$ is of same type as $?ori$, then
 - transport p from $?ori$ to $tcenter2$ use method c, d or e
 - transport p from $tcenter2$ to $?des$ use method a
- h. If $?ori$ is not tcenter, $?des$ is not tcenter, and
 - $?ori$ is in city $c1$ and $?des$ is in city $c2$ ($c1$ and $c2$ can be the same city), and
 - $tcenter1$ is a transportation center in $c1$, $tcenter2$ is a transportation center in $c2$ and
 - $tcenter1$, $tcenter2$ are of same type, then
 - transport p from $?ori$ to $tcenter1$ use method a

transport p from tcenter1 to tcenter2 use method c, d or e
transport p from tcenter2 to ?des use method a

In UM-Translog-2 domain, we still follow the rules as described above. In order to make sure that a package is transported along a legal path, we have to keep track of the movement of a package in an action-based planner. Following predicates are used for this bookkeeping purpose. Variable ?p is of type package.

Predicates	Meaning
(over ?p)	?p cannot be moved anymore according to Figure 1
(t-start ?p)	?p is at tcenter1 according to Figure1
(t-end ?p)	?p is at tcenter2 according to Figure1
(h-start ?p)	?p has visited one hub and is at hub1 or tcenter2 (when tcenter2 is hub and hub1 is not used in the path) as shown in Figure1.

In order to keep track of the movement of a package, we also divided the movement of a vehicle into different cases and have following vehicle moving operators (variable ?v denotes vehicle, variable ?ori denotes the origin, variable ?des denotes the destination):

1. When moving ?v using local-road-route within a city ?ocity, we have following operators:
 - a. **move-vehicle-local-road-route1 (?v, ?ori, ?des, ?ocity)** for the case that either ?ori and ?des are both transportation centers or are both non-transportation centers
Before using this operator, none of the packages inside the vehicle have been moved ever and after using this operator, none of the packages inside the vehicle can be moved anymore (i.e. predicate (over ?p) is added in the current state for all packages inside the vehicle).
 - b. **move-vehicle-local-road-route2 (?v, ?ori, ?des, ?ocity)** for the case that ?ori is not a transportation center and ?des is one
Before using this operator, none of the packages inside the vehicle have been moved ever, and after using this operator, all packages inside the vehicle are at point tcenter1 in Figure1 (i.e. predicate (t-start ?p) is added in the current state for all packages inside the vehicle).
 - c. **move-vehicle-local-road-route3 (?v, ?ori, ?des, ?ocity)** for the case that ?ori is a transportation center and ?des is not one
According to Figure1, before using this operator, either none of the packages inside the vehicle have been moved ever, or all of them must be at tcenter2 (with predicate (h-start ?p) or (t-end ?p)) and after using this operator, none of packages inside the vehicle can be moved anymore.
2. When moving ?v using road-route ?r which connects two different cities ?ocity and ?dcity, we have operator
move-vehicle-road-route-crossCity(?v, ?ori, ?des, ?ocity, ?dcity, ?r)
Before using this operator, none of the packages inside the vehicle have been moved ever and after using this operator, none of the packages inside the vehicle can be moved anymore.
3. When moving ?v using a rail or air route ?r, we have following operators

- a. **move-vehicle-nonroad-route1(?v, ?ori, ?des, ?r)** for the case that either ?ori and ?des are both hubs or are both not hubs
Before using this operator, either none of the packages inside the vehicle have been moved ever or all of them must be at tcenter1 in Figure 1 and after using this operator, all packages inside the vehicle are at tcenter2 in Figure1.
- b. **move-vehicle-nonroad-route2(?v, ?ori, ?des, ?r)** for the case that ?ori is not a hub and ?des is a hub
According to Figure1, before using this operator, either none of the packages inside the vehicle have been moved ever or all of them must be at tcenter1 (with predicate (t-start ?p)) and after using this operator, all packages inside the vehicle are at either hub1 or tcenter2 (with predicate (h-start ?p)).
- c. **move-vehicle-nonroad-route3(?v, ?ori, ?des, ?ocity)** for the case that ?ori is a hub and ?des is not a hub
According to Figure1, before using this operator, either none of the packages inside the vehicle have been moved ever or all of them must be at tcenter1 or hub1 (with predicate (t-start ?p) or (h-start ?p)) and after using this operator, all packages inside the vehicle are at tcenter2 (with predicate (t-end ?p)).

In both preconditions and effects of all moving operators, we have a predicate (move-emp ?v) where ?v is a variable symbol denoting a vehicle. The reason for using this predicate is that in UM Translog, there is a rule saying that if a package needs to be moved from a location and there is no vehicle at this location, then only those vehicles that are one step away from the current location can be used to move this package. What this rule means is that if an empty vehicle is moved to a location, it cannot be moved anymore before it picks up something from this location. This is guaranteed through:

- a. If we use moving operators to move an empty vehicle ?v, (move-emp ?v) predicate will be added to the current state.
- b. In moving operators, (not (move-emp ?v)) is used as a precondition for empty vehicle.
- c. (move-emp ?v) will be deleted from the current state after ?v is moved as a non-empty vehicle.

4.4.4 Clean Domain

We also have an operator **clean-domain()** This operator is used to check if we have cleaned up after us, that is, if we have closed doors of all regular vehicles we have used, disconnected chutes of all tankers we have used, etc. This operator is applicable if everything is cleaned up and predicate (clear) will be added to the current state. (clear) is also the goal of every problem in the domain.

Reference

- [1] S. Andrews, B. Kettler, K. Erol and J. Hendler. "UM Translog: A Planning Domain for the Development and Benchmarking of Planning Systems." Tech. Report CS-TR-3487, Dept. of Computer Science, University of Maryland, College Park, MD, 1995.
- [2] F. Bacchus and F. Kabanza. "Using Temporal Logics to Express Search Control Knowledge for Planning,." *Artificial Intelligence*, 116(1-2):123-191, January, 2000.
- [3] Maria Fox and Derek Long. "PDDL2.1: An Extension to PDDL for Expressing Temporal Planning Domains." Tech. Report, University of Durham, UK, 2001.
- [4] A. Lotem, D. Nau and J. Hendler. Using Planning Graphs for Solving HTN Problems. In *AAAI-99*, 1999, pages 534-540.
- [5] D. Nau, H. Muñoz-Avila, Y. Cao, A. Lotem, and S. Mitchell. "Total-Order Planning with Partially Ordered Subtasks." In *IJCAI-2001*. Seattle, August, 2001.