

Report Documentation Page				Form Approved OMB No. 0704-0188	
Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.					
1. REPORT DATE 28 JAN 2004		2. REPORT TYPE Technical, Success Story		3. DATES COVERED 07-01-2004 to 28-01-2004	
4. TITLE AND SUBTITLE NAVSEA Aircraft Carrier Filter Housing				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S)				5d. PROJECT NUMBER 04-0030-01	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) National Center for Defense Manufacturing & Machining,1600 Technology Way,Latrobe,PA,15650				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution unlimited					
13. SUPPLEMENTARY NOTES					
14. ABSTRACT During the production of a filter housing for the Naval Sea Systems Command (NAVSEA), Hamill Manufacturing Company, Trafford, Pa., was required to drill a 5.5"-dia., 21.5"-deep hole in a block of 1020 steel. The operation consumed excessive time and tooling. It took 63 minutes and four drills -- in spot, 3.0", 5.0", and 5.5" diameters -- to complete the hole. Chip control was an additional problem, frequently making it necessary to retract the drills in mid-cut to clear out the unwieldy mild steel chips. NAVSEA asked if the National Center for Defense Manufacturing & Machining (NCDMM) could provide a solution to reduce machining time and improve chip control.					
15. SUBJECT TERMS National Center for Defense Manufacturing & Machining; NCDMM; Success Stories; Hamill Manufacturing Company; Naval Sea Systems Command					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT 1	18. NUMBER OF PAGES 1	19a. NAME OF RESPONSIBLE PERSON
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified			

PROBLEM / OBJECTIVE

During the production of a filter housing for the Naval Sea Systems Command (NAVSEA), Hamill Manufacturing Company, Trafford, Pa., was required to drill a 5.5"-dia., 21.5"-deep hole in a block of 1020 steel. The operation consumed excessive time and tooling. It took 63 minutes and four drills -- in spot, 3.0", 5.0", and 5.5" diameters -- to complete the hole. Chip control was an additional problem, frequently making it necessary to retract the drills in mid-cut to clear out the unwieldy mild steel chips. NAVSEA asked if the National Center for Defense Manufacturing & Machining (NCDMM) could provide a solution to reduce machining time and improve chip control.



Deep-hole drill with similar component

ACCOMPLISHMENTS / PAYOFF

Process Improvement

NCDMM suggested application of a 5.5"-dia. deep-hole drilling system that featured a coated carbide pilot drill flanked by two flutes tooled with a total of four indexable carbide cutting inserts. The inserts had titanium-nitride coating for wear resistance, and an advanced chip control geometry. Internal passages in the drill body delivered coolant directly to the cutting edge/workpiece interface.

Implementation and Technology Transfer

The drilling system was implemented on a horizontal machining center with coolant supplied at 100-200 pounds per square inch (psi), in volume adequate to

facilitate chip removal. Effective chip control made it unnecessary to withdraw the drill to clear chips, and the new tooling completed the hole in a single pass.

Through the elimination of multiple drills and repeated retractions, drilling time dropped 65 percent, to 22 minutes. Smoother cutting action and reliable chip removal improved hole roundness, tolerances, and surface finish.

The Hamill shop manager said, "The drilling system and parameters allowed me to machine this part with much better accuracy and finish. The parameters were within the horsepower and torque limits of my machining center. The successful implementation of this drill on the first try went a long way in building confidence with my operators."

Expected Benefits

Implementation resulted in:

- Reduced machining time from 63 min. to 22 min.
- Reduction of tooling required 75%
- Improved chip control 100%
- Capable of producing required hole finish and maintaining hole quality with one tool

Yearly savings for a 240-unit annual production run exceed \$10,920 from machine time savings alone. Further savings accrue from reduced tool (insert) replacement costs, lower setup times, and reduced scrap rate. Savings resulting from the implementation of this technology will ultimately rise to \$75,000 annually and total \$375,000 over a five-year period.

TIME LINE / MILESTONE

Start Date Jan 04
Implemented End Jan 04

PROJECT FUNDING

NCDMM funding <\$1K

PARTICIPANTS

NCDMM
Naval Sea Systems Command (NAVSEA)
Hamill Manufacturing Company