



AFRL-RB-WP-TP-2007-3100

**QUANTIFYING THE EFFECT OF FUSELAGE CROSS-SECTIONAL SHAPE ON STRUCTURAL WEIGHT
(PREPRINT)**

Michael A. Falugi

**Advanced Structural Concepts Branch
Structures Division**

MARCH 2007

Approved for public release; distribution unlimited.

See additional restrictions described on inside pages

STINFO COPY

**AIR FORCE RESEARCH LABORATORY
AIR VEHICLES DIRECTORATE
WRIGHT-PATTERSON AIR FORCE BASE, OH 45433-7542
AIR FORCE MATERIEL COMMAND
UNITED STATES AIR FORCE**

NOTICE AND SIGNATURE PAGE

Using Government drawings, specifications, or other data included in this document for any purpose other than Government procurement does not in any way obligate the U.S. Government. The fact that the Government formulated or supplied the drawings, specifications, or other data does not license the holder or any other person or corporation; or convey any rights or permission to manufacture, use, or sell any patented invention that may relate to them.

This report was cleared for public release by the Air Force Research Laboratory Wright Site (AFRL/WS) Public Affairs Office and is available to the general public, including foreign nationals. Copies may be obtained from the Defense Technical Information Center (DTIC) (<http://www.dtic.mil>).

AFRL-RB-WP-TP-2007-3100 HAS BEEN REVIEWED AND IS APPROVED FOR PUBLICATION IN ACCORDANCE WITH ASSIGNED DISTRIBUTION STATEMENT.

//Signature//

MICHAEL A. FALUGI
Program Manager
Advanced Structural Concepts Branch

//Signature//

JOSEPH P. NALEPKA
Chief
Advanced Structural Concepts Branch

//Signature//

DAVID M. PRATT, Ph.D.
Acting Technical Advisor
Structures Division

This report is published in the interest of scientific and technical information exchange, and its publication does not constitute the Government's approval or disapproval of its ideas or findings.

Disseminated copies will show "//signature//*" stamped or typed above the signature blocks.

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

The public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. **PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.**

1. REPORT DATE (DD-MM-YY) March 2007	2. REPORT TYPE Interim	3. DATES COVERED (From - To) 01 March 2005 – 01 March 2007
--	----------------------------------	--

4. TITLE AND SUBTITLE QUANTIFYING THE EFFECT OF FUSELAGE CROSS-SECTIONAL SHAPE ON STRUCTURAL WEIGHT (PREPRINT)	5a. CONTRACT NUMBER In-house
	5b. GRANT NUMBER
	5c. PROGRAM ELEMENT NUMBER 63211F

6. AUTHOR(S) Michael A. Falugi	5d. PROJECT NUMBER A0AE
	5e. TASK NUMBER
	5f. WORK UNIT NUMBER 0A

7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Advanced Structural Concepts Branch (AFRL/RBSA) Structures Division Air Force Research Laboratory, Air Vehicles Directorate Wright-Patterson Air Force Base, OH 45433-7542 Air Force Materiel Command, United States Air Force	8. PERFORMING ORGANIZATION REPORT NUMBER AFRL-RB-WP-TP-2007-3100
---	--

9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) Air Force Research Laboratory Air Vehicles Directorate Wright-Patterson Air Force Base, OH 45433-7542 Air Force Materiel Command United States Air Force	10. SPONSORING/MONITORING AGENCY ACRONYM(S) AFRL/RBSA
	11. SPONSORING/MONITORING AGENCY REPORT NUMBER(S) AFRL-RB-WP-TP-2007-3100

12. DISTRIBUTION/AVAILABILITY STATEMENT
Approved for public release; distribution unlimited.

13. SUPPLEMENTARY NOTES
PAO Case Number: AFRL/WS 07-0118, 01 Mar 2007. Report contains color.
Slideshow presented at the 32st AIAA Dayton-Cincinnati Aerospace Sciences Symposium.

14. ABSTRACT
Analytical trade studies were set up and are being performed to quantify the effect of fuselage cross-sectional shape on structural weight for a cargo transport aircraft. The target vehicle design reflects various geometry, aerodynamic and inertia loads, internal pressurization, and other requirements associated with a medium-sized military transport configuration. Several elliptical cross-sections and at least one cross section containing one or more flat (LO-friendly) outer mold line segments are being evaluated. Aerodynamic loading on the fuselage is being accounted for in the trades. FEM generation and analysis includes automated structural sizing for the cargo compartment portion of the fuselage using HyperSizer. The results of this study will be used to influence decisions regarding the shape preferences for potential fuselage design candidates. The models that are created can also be used to support additional in-house trade studies to look at new structural materials and design concept candidates for transport fuselage primary structure.

15. SUBJECT TERMS

16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT: SAR	18. NUMBER OF PAGES 26	19a. NAME OF RESPONSIBLE PERSON (Monitor) Michael A. Falugi
a. REPORT Unclassified	b. ABSTRACT Unclassified	c. THIS PAGE Unclassified			



Quantifying the Effect of Fuselage Cross- Sectional Shape on Structural Weight (Work in progress)


AIAA

The 32nd AIAA Dayton-Cincinnati Aerospace
Sciences Symposium

Michael Falugi

Air Vehicle Directorate

Air Force Research Laboratory



A preliminary in-house analysis was recently initiated to assess the effect of fuselage cross-sectional shape on structural weight.



Outline



- Objective & approach
- Assumptions
- Structural description
- Fuselage structural trades
- Weight optimization
- Summary



Objective & Approach



Objective: Perform assessment and determine impact of various fuselage aspect ratios on structural weight

Approach:

- FEM and optimization code
- 3 configurations
- Representative flight loads

Coordination: Steve Clay AFRL/VASA
Barth Shenk AFRL/VAOT
David Brown AFRL/VASA
Daniel Tejtel AFRL/VAAA

Tools used: Nastran & HyperSizer

3

Analytical trade studies were set up and are being performed to quantify the effect of fuselage cross-sectional shape on structural weight for a cargo transport aircraft.

FEM generation and analysis includes automated structural sizing for the cargo compartment portion of the fuselage using NASTRAN and HyperSizer.

An elliptical or other non-circular fuselage provides a potentially more efficient interior shape to maximize cargo.



Introduction



Three different configurations explored:


- Circular Fuselage
- Elliptical Fuselage 3/4 Aspect Ratio
- Elliptical Fuselage 4/3 Aspect Ratio

NASTRAN to calculate stresses

NASTRAN model imported into Hypersizer for structural weight optimization

4

Preliminary design trade studies of 3 different fuselage configurations have been accomplished. MSC/NASTRAN was used to calculate stresses and Hypersizer is planned to be used for structural optimization.



As a background, an initial trade study was done on six generic fuselage configurations. This was followed by a more realistic study on three representative fuselage structures.



Fuselage Structural Trades



Elliptical Fuselage Configurations (Equal Volume)


a (ft)	b (ft)	b/a
6.665	6.665	1 (circular)
5.77	7.70	4/3
7.70	5.77	3/4
9.42	4.71	1/2
10.88	4.08	3/8
13.47	3.297	1/4

Applied Loads:


- 3G Inertia
- Fuselage Aerodynamic Pressure Loads for 3G Pull-up Condition
- 7 psi Pressure

6


Shown are the initial six generic fuselage configurations that were studied. The baseline configuration was circular and the remaining were elliptical with different ratios of height to width. The applied loads are shown.




The finite element models generated for this study is shown. The panels are designed to be hat stiffened for the fuselage , and the ring frames are I-beam shaped.



Initial stress results were collected for the six generic fuselage configurations.



Shown are the analysis results for the peak stresses for each configuration. As the ratio of fuselage height over length gets smaller the peak stress rises. The curve can be represented by the shown exponential equation.



Different stress curves are shown for each fuselage configuration as compared to the baseline circular configuration.




Fuselage Structural Trades



Assumptions











- 3 different fuselage designs: Circular, Elliptical 3/4 & Elliptical 4/3
- All have same volume
- All subjected to same loads:
 - 7 psi Pressure
 - Aerodynamic loads
 - $M=0.8$ at 36,000 ft
 - Angle of attack = 10 deg.
 - 3 g Inertia
- Loads introduced from tail
- Loads reacted at approximate center of lift for each wing



12


Here are the assumptions that were made for the three different fuselage configurations. Representative flight loadings, internal pressure, aerodynamic loading and gravity were used to calculate stresses.

 **3 Different Design Transport Configurations** 


Circular Configuration		
Elliptical Configuration 3/4		
Elliptical Configuration 4/3		

13


The initial analysis was done on generic configurations. Getting into the more realistic model loading and geometry, a more representative of actual aircraft structure including the cargo floor are shown.



Shown are the aerodynamic loads that were applied to the circular fuselage with a minimum pressure of 1.75 psi and a maximum pressure of 5 psi.



Shown are the aerodynamic loads that were applied to the elliptical fuselage with a minimum pressure of 1.63 psi and a maximum pressure of 5 psi.



Also shown are the aerodynamic loads that were applied to the third elliptical fuselage.



Weight Optimization Nastran into HyperSizer



Weight Optimization



- **Import Nastran results into HyperSizer**
- **Perform optimized structural sizing on 3 different configurations**
 - **Initial trades all Aluminum**
 - **Next trade using composite material**
- **Compare results to provide recommendations for future transport aircraft design**

18

MSC/NASTRAN was used as the loads model, and the entire model will be optimized using HyperSizer. HyperSizer, developed by Collier Research Corporation, is able to optimize in a manner which guarantees structural integrity of the entire model using methods to accurately compute margins of safety (MoS) for all potential failures.



Summary



- **Representative fuselage dimensions, takeoff gross weight, various distributed masses, and limit aerodynamic and inertia loading conditions used to reflect realistic design for a large military transport aircraft**
- **FEMs created to simulate realistic internal loads for primary structure**
- **HyperSizer will be used to determine optimized structural weight for fuselage**
- **Work continuing to obtain detailed results**

19

A summary of the effort is shown. The results of this study will be used to influence decisions regarding the shape preferences for potential fuselage design candidates.