

PRIMARY REFERENCE CLOCKS USING INDOOR ANTENNAS

**Don Mitchell
Truetime, Inc.
3750 Westwind Blvd., Santa Rosa, CA 95403, USA**

Abstract

This paper discusses a new technology of synchronizing clocks and disciplining oscillators using CDMA cellular transmissions. Like cellular telephones, these receivers will operate in most buildings without rooftop antennas. They are reported accurate to within microseconds of UTC with stable frequencies available.

INTRODUCTION

UTC Time and Frequency Dissemination via the IS-95 CDMA Mobile Telecommunications Infrastructure

Base Station Transmissions in IS-95 CDMA Systems

- All use the same pilot pseudonoise (PN) spreading code
- All use the same carrier frequency (within an individual provider's system)

Base Station Transmissions in IS-95 CDMA Systems Must be Synchronized

- To control interface between cells:
 - ⇒ Cell-to-cell interference is controlled by having each base station transmit the pilot PN code with its own unique time offset relative to GPS time
 - ⇒ The pilot PN offsets must be maintained accurately or adjacent cells would interfere with each other

Base Station Transmissions in IS-95 CDMA Systems Must be Synchronized

- To allow a "soft hand-off" as the mobile user travels between cells.
 - ⇒ The mobile unit must be able to calculate the approximate time offset of the new base station's pilot PN code in order to rapidly acquire and lock to it before losing the current base station
 - ⇒ If the base stations are synchronized, and the mobile user decodes the neighboring cell PN offset data that it receives from the currently tracked base station, this can be achieved

Report Documentation Page				Form Approved OMB No. 0704-0188	
Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.					
1. REPORT DATE NOV 2000		2. REPORT TYPE		3. DATES COVERED 00-00-2000 to 00-00-2000	
4. TITLE AND SUBTITLE Primary Reference Clocks Using Indoor Antennas				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S)				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Truetime Inc,3750 Westwind Blvd,Santa Rosa,CA,95403				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution unlimited					
13. SUPPLEMENTARY NOTES See also ADM001509. 32nd Annual Precise Time and Time Interval (PTTI) Meeting, 28-30 Nov 2000, Reston, VA					
14. ABSTRACT see report					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT Same as Report (SAR)	18. NUMBER OF PAGES 4	19a. NAME OF RESPONSIBLE PERSON
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified			

The IS-95 CDMA System Time Base is the GPS Time Scale Because...

- GPS is globally available
- GPS can maintain the required level of synchronization between base stations
 - ⇒ Less than 1 us while tracking a satellite
 - ⇒ Less than 10 us for up to 24 hours while in holdover (IS-95 spec) using either
 - A rubidium vapor local oscillator
 - An ultra-stable, ovenized quartz local oscillator with software temperature compensation

The IS-95 CDMA Signal Structure Supports Precision Recovery of GPS Time & Frequency

- Spread spectrum modulation at GPS-like chipping rate of 1.2288 Megachips/second
- Pilot PN code can be acquired using long integration time—no data modulation
 - ⇒ 32768 chip code repeats every 26.666...ms
 - ⇒ Base station pilot PN codes are offset from each other in 64 chip increments (52.08333....us)

The IS-95 CDMA Signal Structure Supports Precision Recovery of GPS Time & Frequency

- Cellular (881 MHz)/PCS (1960 MHz) carriers support GPS-like low-noise frequency recovery and aiding/smoothing of the code tracking loop
- Sync channel message: base station PN offset, UTC leap seconds and local time offset
 - ⇒ 1200 bits/second data is convolutionally encoded ($k=2$, $m=9$) to 2400 symbols/second
 - ⇒ Block interleaved with 2:1 redundancy to 4800 symbols/second
 - ⇒ CRC-30 performed on complete message
 - ⇒ Message repeated every 240 milliseconds

Received IS-95 Signal Level is Much Higher than GPS

- IS-95 coverage spec minimum is -100 dbm – at least 30 dB greater than GPS
- Cellular band carrier penetrates buildings to much greater degree than GPS
- Provides an excellent alternative in situations that are difficult for “direct” GPS

SUMMARY

CDMA “Indirect” GPS Performance Relative to “Direct” GPS

- Uncertainty in the propagation delay from base station to user limits absolute accuracy of the recovered UTC time to tens of microseconds.
- With stationary users, the time offset due to propagation delay is fixed and the repeatability and stability of the recovered UTC time is at the 100 ns level.
- With stationary users, the quality of the base station GPS receiver/oscillator system provides excellent transmitted frequency accuracy and stability which is virtually reproduced with a well-designed receiver.

Questions and Answers

JEREMY ELSON (UCLA): I am wondering if anybody has talked about trying to recover position by locking to, let's say, four CMA space stations the same as you would lock on to four GPS satellites.

DONALD MITCHELL: That's a good thought. You could certainly do that. Because if you're looking at the offsets that are received, then most certainly you could be able to determine your location by looking at the offsets that you receive from three carriers. You have four carriers, and it makes it even better. So yes, that's a possibility. Although, like I say, I am not aware of anybody doing that. That could be something that is going on.

I really wasn't aware of this until I heard about it, but I think the first real notice I had that somebody was actually doing something in this area was Ed Butterline at the ION in '99 bringing the subject up.