

Report Documentation Page				Form Approved OMB No. 0704-0188	
Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.					
1. REPORT DATE 2008		2. REPORT TYPE		3. DATES COVERED 00-00-2008 to 00-00-2008	
4. TITLE AND SUBTITLE Energy Losses in Simulated Relativistic Michigan A6 Magnetron With Shaped Cathode				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S)				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Air Force Research Laboratory, Directed Energy Directorate, High Power Microwave Division, Kirtland AFB, NM, 87117				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution unlimited					
13. SUPPLEMENTARY NOTES See also ADM002087. Proceedings of the 2008 IEEE International Vacuum Electronic Conference (9th) (IVEC 2008) Held in Monterey, CA on April 22-24, 2008. U.S. Government or Federal Rights License					
14. ABSTRACT					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT Same as Report (SAR)	18. NUMBER OF PAGES 1	19a. NAME OF RESPONSIBLE PERSON
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified			

P2.31: Energy losses in simulated relativistic Michigan A6 magnetron with shaped cathode

Peter Mardahl

Air Force Research Laboratory, Directed Energy Directorate

High Power Microwave Division

Kirtland AFB, NM 87117

Phone: 505-846-8571, Fax: 505-853-3081

Email: icepic@kirtland.af.mil

Recently there has been much research interest in improving magnetron performance by employing various priming techniques, such as shaped cathodes and nonuniform magnetic fields. These priming techniques have been successfully applied to reduce magnetron noise and also improve mode-locking and efficiency [1][2].

Inserting a shaped cathode into the simulated Michigan magnetron yields a maximum efficiency (the RF output power for a cycle divided by the current times voltage input for that cycle) of 33% as opposed to 15% for the standard cathode. 33% is a very good efficiency figure for a relativistic high power magnetron—however conventional magnetrons often achieve efficiencies greater than 85%.

The current effort is to characterize the various energy losses with the eventual goal of improving efficiency beyond 33%. We have found that for an RF cycle, 41% of the input energy is deposited by the electrons into the anode, 3% of the energy is deposited by electrons in the cathode, 23% is deposited by electrons downstream of the cathode, and 33% is emitted as RF, as is shown in Fig. 1. We will show in detail the spatial profile of the energy deposition by the electrons.

The hope is that with a detailed understanding of the energy losses, we can invent means of improving the efficiency without making key tradeoffs, such as going to higher magnetic fields, achieving higher peak efficiency at the expense of longer rise times (which would lead to reduced energy efficiency), increasing device size, reduced maximum power output, etc.




Fig. 1. Shown is the distribution of energy output for a single RF cycle of the A6 Michigan Magnetron. Most of the energy is lost as electron kinetic energy deposited in the anode, with lesser amounts deposited downstream and in the cathode. 33% of the energy input is converted to RF.

[1] “Magnetic priming effects on noise, startup, and mode competition in magnetrons”, Neculaes et. al., *IEEE Transactions on Plasma Science*, Feb. 2005.

[2] “Virtual Prototyping of Novel Cathode Designs for the Relativistic Magnetron”, Timothy P. Fleming et al., *Computing in Science & Engineering*, Nov/Dec 2007.