

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

The public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing the burden, to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.

PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.

1. REPORT DATE (DD-MM-YYYY) 30-09-2008			2. REPORT TYPE final		3. DATES COVERED (From - To) 1. Jun. 2007 - 30. Sep. 2008	
4. TITLE AND SUBTITLE Modeling of Electroresistive and Magnetoelectric Oxide Heterostructures					5a. CONTRACT NUMBER N00014-07-1-1028	
					5b. GRANT NUMBER N00014-07-1-1028	
					5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S) Tsymbal, Evgeny					5d. PROJECT NUMBER 07PR08028-00	
					5e. TASK NUMBER	
					5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Department of Physics and Astronomy University of Nebraska-Lincoln Lincoln, NE 68588-0111					8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) Office of Naval Research 875 North Randolph Street Arlington, VA 22203-1995					10. SPONSOR/MONITOR'S ACRONYM(S)	
					11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT no limitations						
13. SUPPLEMENTARY NOTES						
14. ABSTRACT Using first-principles calculations we have predicted new functional properties of oxide ferroic heterostructures. One class of heterostructures utilizes an ultrathin ferroelectric film serving as a barrier between two metal electrodes which makes a ferroelectric tunnel junction (FTJ). The electric-field-induced polarization reversal of the ferroelectric is predicted to have a profound effect on the conductance of the junction leading to a new kind of electroresistive switches. Another class of devices extends functional properties of the FTJs by replacing normal metal electrodes by ferromagnetic which makes the junctions multiferroic. The interplay between ferroelectric and ferromagnetic properties of the two ferroic constituents affects the spin polarization of the tunneling current. Thus, multiferroic tunnel junctions (MFTJ) may provide a new degree of freedom in functionality of magnetoresistive devices. Also we have explored new possibilities to control the interface magnetization of a magnetic film by an adjacent ferroelectric layer.						
15. SUBJECT TERMS We have predicted new functional properties of oxide ferroic heterostructures and have explored new possibilities to control the interface magnetization of a magnetic film.						
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT UU	18. NUMBER OF PAGES 1	19a. NAME OF RESPONSIBLE PERSON Evgeny Tsymbal	
a. REPORT U	b. ABSTRACT U	c. THIS PAGE U			19b. TELEPHONE NUMBER (Include area code) 402-472-2586	



DEFENSE TECHNICAL INFORMATION CENTER

Information for the Defense Community

DTIC® has determined on 02/19/2009 that this Technical Document has the Distribution Statement checked below. The current distribution for this document can be found in the DTIC® Technical Report Database.

- ☒ **DISTRIBUTION STATEMENT A.** Approved for public release; distribution is unlimited.
- ☐ **© COPYRIGHTED;** U.S. Government or Federal Rights License. All other rights and uses except those permitted by copyright law are reserved by the copyright owner.
- ☐ **DISTRIBUTION STATEMENT B.** Distribution authorized to U.S. Government agencies only (fill in reason) (date of determination). Other requests for this document shall be referred to (insert controlling DoD office)
- ☐ **DISTRIBUTION STATEMENT C.** Distribution authorized to U.S. Government Agencies and their contractors (fill in reason) (date of determination). Other requests for this document shall be referred to (insert controlling DoD office)
- ☐ **DISTRIBUTION STATEMENT D.** Distribution authorized to the Department of Defense and U.S. DoD contractors only (fill in reason) (date of determination). Other requests shall be referred to (insert controlling DoD office).
- ☐ **DISTRIBUTION STATEMENT E.** Distribution authorized to DoD Components only (fill in reason) (date of determination). Other requests shall be referred to (insert controlling DoD office).
- ☐ **DISTRIBUTION STATEMENT F.** Further dissemination only as directed by (inserting controlling DoD office) (date of determination) or higher DoD authority.
- Distribution Statement F is also used when a document does not contain a distribution statement and no distribution statement can be determined.*
- ☐ **DISTRIBUTION STATEMENT X.** Distribution authorized to U.S. Government Agencies and private individuals or enterprises eligible to obtain export-controlled technical data in accordance with DoDD 5230.25; (date of determination). DoD Controlling Office is (insert controlling DoD office).

Modeling of Electroresistive and Magnetoelectric Oxide Heterostructures: Final Report

Using first-principles calculations we have predicted new functional properties of oxide ferroic heterostructures. One class of heterostructures utilizes an ultrathin ferroelectric film serving as a barrier between two metal electrodes which makes a ferroelectric tunnel junction (FTJ). The electric-field-induced polarization reversal of the ferroelectric is predicted to have a profound effect on the conductance of the junction leading to a new kind of electroresistive switches. Another class of devices extends functional properties of the FTJs by replacing normal metal electrodes by ferromagnetic which makes the junctions multiferroic. The interplay between ferroelectric and ferromagnetic properties of the two ferroic constituents affects the spin polarization of the tunneling current. Thus, multiferroic tunnel junctions (MFTJ) may provide a new degree of freedom in functionality of magnetoresistive devices.

We have performed first-principles calculation of $\text{SrRuO}_3/\text{BaTiO}_3/\text{SrRuO}_3$ MFTJs which exhibit an tunneling electroresistance (TER) effect associated with the change in the electric polarization of BaTiO_3 . We demonstrated that the reversal of the electric polarization in BaTiO_3 produces a notable change in the conductance, provided that the two interfaces have different terminations. Since SrRuO_3 is ferromagnetic, we demonstrated that the $\text{SrRuO}_3/\text{BaTiO}_3/\text{SrRuO}_3$ FTJs exhibit a sizable tunneling magnetoresistance (TMR) effect which is sensitive to the polarization orientation of the ferroelectric spacer layer. Thus, we have proven that these MFTJs may serve as four-state resistance devices. These results reveal the exciting prospects of MFTJs for application as multifunctional spintronic devices.

Also we have explored new possibilities to control the interface magnetization of a magnetic film by an adjacent ferroelectric layer. We have performed first-principles calculations of the magnetoelectric effect at $\text{Fe}_3\text{O}_4/\text{BaTiO}_3$ interfaces. We found that the magnetoelectric coupling in this system originates from the interface bonding sensitive to atomic displacements at the interface. This leads to the change in the interface magnetization when the polarization of the ferroelectric layer reverses. We considered two types of interface terminations of Fe_3O_4 which have different iron cation valence and oxygen atom environment. We found that the magnitude of the magnetoelectric coupling is stronger for the oxygen-deficient $\text{Fe}_3\text{O}_4/\text{BaTiO}_3$ interface. The sensitivity to the interface oxygen content suggests that oxidation or oxygen vacancies at the interface may play an important role in determining the strength of the interface magnetoelectric coupling.

As a result of this work one paper was published and another one was submitted for publication:

1. M. K. Niranjan, J. P. Velev, C.-G. Duan, S. S. Jaswal and E. Y. Tsymbal, "Magnetoelectric effect at the $\text{Fe}_3\text{O}_4/\text{BaTiO}_3$ (001) interface: A first-principles study", *Physical Review B* 78, 104405 (2008).
2. J. P. Velev, C.-G. Duan, J. D. Burton, A. Smogunov, M.K. Niranjan, E. Tosatti, S. S. Jaswal, and E. Y. Tsymbal, "Magnetic tunnel junctions with ferroelectric barriers: Prediction of four resistance states from first-principles", submitted for publication.