

Report Documentation Page

Form Approved
OMB No. 0704-0188

Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.

1. REPORT DATE 2005		2. REPORT TYPE		3. DATES COVERED 00-00-2005 to 00-00-2005	
4. TITLE AND SUBTITLE Interactive Operations for Understanding Embedded Sensor Domains				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S)				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Virtual Reality Laboratory, Naval Research Laboratory, Washington, DC, 20375				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution unlimited					
13. SUPPLEMENTARY NOTES 2005 ACM Symposium on Interactive 3D Graphics and Games, Washington, D.C., April 3-6, 2005					
14. ABSTRACT					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT Same as Report (SAR)	18. NUMBER OF PAGES 1	19a. NAME OF RESPONSIBLE PERSON
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified			

Interactive Operations for Understanding Embedded Sensor Domains

Mark A. Livingston*

Evan V. Herbst

Virtual Reality Laboratory, Naval Research Laboratory, Washington D.C.

CR Categories: H.5.2 [Information Interfaces and Presentation]: User Interfaces—Graphical user interfaces, User-centered design; H.2.8 [Database Management]: Database Applications—Data mining

Keywords: pervasive computing, visualization, interaction, sensor networks

1 Introduction

Embedded sensors have the potential to provide users vast amounts of information about the environment [Estrin et al. 2001]. However, in many situations, the sensors and associated databases are only capable of delivering low-level, unstructured data such as raw measurements. If users are to be able to extract meaning from the stream of data, interfaces must be provided to allow users to form and execute queries.


We implemented visualizations of the sensor domain and enabled a user to interactively plan and understand the sensor domain. We consider a military use of sensors: providing early warning of movement toward friendly positions [USMC Combat Development Command 1997]. The user views each sensor output on a dial-shaped or numerical display and integrates these values into a coherent picture to determine what action to take.

We consulted with domain experts to determine the operations and limitations with current interfaces to remote sensors. They noted the following driving issues. Current sensor suites require that line-of-sight contact be maintained (possibly through relays) to each sensor. It is hard to know what area is covered by the existing sensors. It is hard to predict how best to extend the current domain over which the sensors are effective.

2 Implemented Visualization Methods

We visualize the domain of sensors and line-of-sight relationships between sensors (top left). We add the sensor coverage in the domain (top right). The color indicates how many sensors extract the data for their reading from that region. (Key: red=1, yellow=2, green=3, blue=4.) The coverage computations account for the terrain shape, whereas the simple domains do not. Finally, we enable the user to plan sensor locations to most effectively monitor a space. Compare the bottom pair of images in the figure with the top pair. The bottom images show the result of the user interactively specifying a new string of sensors. Note how the sensor at the far left can be seen to have line-of-sight contact in only one direction with this interactive visualization.

*e-mail: mark.livingston@nrl.navy.mil



3 Discussion

Our initial efforts have focused on design of the sensor environment. The geometric operations may be grouped into area-based operations (extension of a domain and coverage within that domain) and point-based operations (line-of-sight queries). We would like to extend our efforts to include interactive detection of objects in the environment. This requires integration of our interface with a tracking algorithm [Schmidt et al. 2004].

We would like to be able to add different types of sensors. Thus far, we have largely been considering point-sampling sensors, such as magnetic or vibration detectors; however, imaging sensors are in use. The domain and coverage queries become more complex geometric problems, requiring the integration of qualitatively different shapes into a single geometric description.

This simple interface improves the understand of the sensor domain. The interactive 3D display for an application that had not previously seen such a display gives the user a tool for planning how to best use the resources available to get information. The interactions themselves require nothing more than simple desktop or mobile systems, but the 3D display converts important operations from challenging to interactive.

References

- DEBORAH L. ESTRIN ET AL., Ed. 2001. *Embedded, Everywhere*. National Academy Press.
- SCHMIDT, G. S., CHEN, S.-L., BRYDEN, A. N., LIVINGSTON, M. A., ROSENBLUM, L. J., AND OSBORN, B. R. 2004. Multi-dimensional visual representations for underwater environmental uncertainty. *IEEE Computer Graphics and Applications* 24, 5 (September/October), 56–65.
- U.S. MARINE CORPS COMBAT DEVELOPMENT COMMAND, 1997. Remote sensor operations.