



AFRL-RZ-WP-TR-2010-2078

NATIONAL AEROSPACE FUELS RESEARCH COMPLEX

Tim Edwards

Fuels and Energy Branch

Energy/Power/Thermal Division

MARCH 2010

Final Report

Approved for public release; distribution unlimited.

See additional restrictions described on inside pages

STINFO COPY

**AIR FORCE RESEARCH LABORATORY
PROPULSION DIRECTORATE
WRIGHT-PATTERSON AIR FORCE BASE, OH 45433-7251
AIR FORCE MATERIEL COMMAND
UNITED STATES AIR FORCE**

NOTICE AND SIGNATURE PAGE

Using Government drawings, specifications, or other data included in this document for any purpose other than Government procurement does not in any way obligate the U.S. Government. The fact that the Government formulated or supplied the drawings, specifications, or other data does not license the holder or any other person or corporation; or convey any rights or permission to manufacture, use, or sell any patented invention that may relate to them.

This report was cleared for public release by the USAF 88th Air Base Wing (88 ABW) Public Affairs (AFRL/PA) Office and is available to the general public, including foreign nationals. Copies may be obtained from the Defense Technical Information Center (DTIC) (<http://www.dtic.mil>).

AFRL-RZ-WP-TR-2010-2078 HAS BEEN REVIEWED AND IS APPROVED FOR PUBLICATION IN ACCORDANCE WITH THE ASSIGNED DISTRIBUTION STATEMENT.

*//Signature//

TIM EDWARDS
Senior Chemical Engineer
Fuels and Energy Branch
Energy/Power/Thermal Division

//Signature//

JERMONT CHEN, Lt Col, USAF
Chief, Fuels and Energy Branch
Energy/Power/Thermal Division
Propulsion Directorate

This report is published in the interest of scientific and technical information exchange, and its publication does not constitute the Government's approval or disapproval of its ideas or findings.

*Disseminated copies will show “//Signature//” stamped or typed above the signature blocks.

REPORT DOCUMENTATION PAGE				Form Approved OMB No. 0704-0188	
The public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.					
1. REPORT DATE (DD-MM-YY) March 2010		2. REPORT TYPE Final		3. DATES COVERED (From - To) 01 October 1999 – 30 September 2009	
4. TITLE AND SUBTITLE NATIONAL AEROSPACE FUELS RESEARCH COMPLEX				5a. CONTRACT NUMBER In-house	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER 62203F	
6. AUTHOR(S) Tim Edwards				5d. PROJECT NUMBER 3048	
				5e. TASK NUMBER 05	
				5f. WORK UNIT NUMBER 304805F1	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Fuels and Energy Branch (AFRL/RZPF) Energy/Power/Thermal Division Air Force Research Laboratory, Propulsion Directorate Wright-Patterson Air Force Base, OH 45433-7251 Air Force Materiel Command, United States Air Force				8. PERFORMING ORGANIZATION REPORT NUMBER AFRL-RZ-WP-TR-2010-2078	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) Air Force Research Laboratory Propulsion Directorate Wright-Patterson Air Force Base, OH 45433-7251 Air Force Materiel Command United States Air Force				10. SPONSORING/MONITORING AGENCY ACRONYM(S) AFRL/RZPF	
				11. SPONSORING/MONITORING AGENCY REPORT NUMBER(S) AFRL-RZ-WP-TR-2010-2078	
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution unlimited.					
13. SUPPLEMENTARY NOTES Paper contains color. PA Case Number: 88ABW-2010-1824; Clearance Date: 05 Apr 2010.					
14. ABSTRACT This report summarizes extensive in-house research performed by the Air Force Research Laboratory/ Propulsion Directorate Fuels Branch for the 2000-2009 time period under in-house work unit 304805F1. This work was organized under the organizational umbrella of the National Aerospace Fuels Research Complex (NAFRC). This in-house work unit is a successor/consolidation to a number of in-house work units, such as 30480537, 30480587, 2308P700, and is the predecessor to 5330SBF1. This work unit covered the time period from 2000-2009, and includes all the in-house efforts supporting the Fuels Branch of the AFRL Propulsion Directorate. The major on-site contract support was provided by the University of Dayton Research Institute through contracts F33615-97-C-2719 and F33615-03-2-2347. Approximately 60 on-site contractors work on this in-house program as of March 2010. This summary includes a general description of the in-house work areas – a more complete description will be found in the final report for F33615-03-2-2347, forthcoming in early 2011. Areas discussed in some detail include endothermic fuels, fuel hydrocarbon class analysis, and jet fuel naphthalene analysis.					
15. SUBJECT TERMS Jet fuel, thermal stability, endothermic fuels, FSII, low temperature fuel, nanoenergetics, biological growth/mitigation, emissions					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT: SAR	18. NUMBER OF PAGES 30	19a. NAME OF RESPONSIBLE PERSON (Monitor) Tim Edwards 19b. TELEPHONE NUMBER (Include Area Code) N/A
a. REPORT Unclassified	b. ABSTRACT Unclassified	c. THIS PAGE Unclassified			

TABLE OF CONTENTS

<u>Section</u>	<u>Page</u>
LIST OF FIGURES	iv
LIST OF TABLES	iv
ACKNOWLEDGEMENTS	v
1.0 SUMMARY	1
2.0 INTRODUCTION	2
3.0 METHODS	3
4.0 DISCUSSION	4
5.0 CONCLUSIONS	17
6.0 REFERENCES	18
LIST OF ACRONYMS, ABBREVIATIONS AND SYMBOLS	20

LIST OF FIGURES

<u>Figure</u>	<u>Page</u>
1. Comparison of the volumetric liquid-to-gas conversion as a function of the bulk outlet fuel temperature.	6
2. Comparison of the total surface carbon deposition for Jet A-1 and F-T fuels as a function of bulk outlet temperature.	6
3. Comparison of the surface deposition profile for Jet A-1 and F-T fuels with ~18% gaseous product conversion.	7
4. Comparison of aromatic content in stressed liquid and total surface deposition as a function of gas conversion for pyrolytic testing with Jet A-1.	7
5. Representative chromatogram of stressed Jet A-1 liquid product from supercritical pyrolysis.	7
6. Representative chromatogram of low conversion stressed S-8 liquid product from supercritical pyrolysis on ECAT.	7
7. Representative chromatogram of very high conversion stressed S-8 liquid product from supercritical pyrolysis at UTRC.	9
8. Representative chromatogram of stressed S-8 liquid product from supercritical pyrolysis at Louisiana State University.	9
9. GC-MS scanning total ion chromatograms of fuels.	10
10. Distribution of naphthalene content in jet fuels from this study.	11
11. Correlation between total naphthalenes by ASTM D1840 and D6379.	12
12. Relationship between total naphthalene content and individual naphthalene components for jet fuel samples.	13
13. Naphthalene content as a function of jet fuel type.	13
14. 1-methyl naphthalene content as a function of jet fuel type.	14
15. Naphthalene content for the four classes of ground fuels.	14
16. 1-methyl naphthalene content for the four classes of ground fuels.	15
17. 2-methyl naphthalene content for the four classes of ground fuels.	15
18. Aerial view of January 2009 aircraft emissions testing.	17

LIST OF TABLES

<u>Table</u>	<u>Page</u>
1. Classification of compounds using MDGC-TOFMS analysis compared to total HPLC polars analysis.	5
2. Library matches to various compound classes in jet fuels.	6
3. Hydrocarbon-type composition for representative and test fuels by ASTM D2425.	7
4. Mean naphthalene content and standard deviation for fuel classes.	11

ACKNOWLEDGEMENTS

This in-house research was partially funded by the Air Force Office of Scientific Research, with Julian Tishkoff as the program manager. A portion of the in-house work on aviation biofuels was supported by DARPA. Initial low temperature fuels work was supported by the U-2 program office. A significant portion of the FSII work was supported by the Defense Supply Center Richmond and the Air Force Petroleum Agency.

1.0 SUMMARY

This report summarizes extensive in-house research performed by the Air Force Research Laboratory/Propulsion Directorate Fuels Branch for the 2000-2009 time period under in-house work unit 304805F1. This work was organized under the organizational umbrella of the National Aerospace Fuels Research Complex (NAFRC).

2.0 INTRODUCTION

This in-house work unit is a successor/consolidation to a number of in-house work units, such as 30480537, 30480587, 2308P700, and is the predecessor to 5330SBF1. This work unit covered the time period from 2000-2009, and includes all the in-house efforts supporting the Fuels Branch of the AFRL Propulsion Directorate. The major on-site contract support was provided by the University of Dayton Research Institute through contracts F33615-97-C-2719 and F33615-03-2-2347. The publications for this in-house program are mostly included with the reports for the two UDRI contracts – there are hundreds! Approximately 60 on-site contractors work on this in-house program as of March 2010. This summary includes a general description of the in-house work areas – a more complete description will be found in the final report for F33615-03-2-2347, forthcoming in early 2011.

3.0 METHODS, ASSUMPTIONS, AND PROCEDURES

The Fuels Branch treats in-house research as an integrated part of the overall AFRL fuel research effort. Fuel Branch funding goes to various research areas which may include both in-house and contracted efforts. External funding is actively sought in most areas. The Fuels Branch also acts as a clearinghouse for research samples of aerospace fuels.

4.0 DISCUSSION

Fuels in-house efforts were managed as portfolios, and results will be summarized for each effort.

1) Thermal stability/thermal management

In the 1990s, the major development in this area was the first JP-8+100 additive. In the next decade (for this current report), DESC co-funded an effort develop further +100 additives for cost reduction. Four additives were developed for further testing. RZPF's in-house efforts included thermal stability testing. Testing of the second wave of JP-8+100 additives is still underway (March 2010). Results will be reported under F33615-03-D-2354-0015. An up-to-the-date summary of the JP-8+100 program can be found in AFRL-RZ-WP-TR-2008-2126 [1]. This portfolio also included extensive modeling and trace species assessment in jet fuels, e.g. [2]. These measurements are necessary for accurate thermal stability modeling, which is often controlled by trace species concentration in jet fuel. The following discussion is from Reference 2.

Aviation fuel is so complex that it is virtually impossible to separate all of the major components of the mixture, much less the minor components. The minor components are typically separated from the major components using preparative techniques (such as solid phase extraction, SPE) and then re-examined by gas chromatography-mass spectrometry (GC-MS). Without SPE, GC-MS is not capable of a comprehensive determination of the trace polar components in jet fuel due to fuel complexity. In the UDRI work for AFRL, jet fuel mixtures are pre-separated by normal-phase SPE, followed by a single analysis using multidimensional gas chromatography-time of flight mass spectrometry (MDGC-TOFMS), which is similar to the recently popularized technique of GC X GC. This two-column sequential analysis followed by TOFMS identifications is able to accurately identify more of the polar components of jet fuel. Automated data analysis routines, based on improved mass spectral library identifications (due to the better chromatographic separations), are able to determine individual components in the polar fractions that are of interest. Spreadsheet-based sorting of the highest quality identifications was also performed and used to quantify important polar fuel classes such as amines, indoles, pyridines, anilines, sulfur compounds, oxygenates, aromatics, and others. These compound classes can have very different effects on thermal stability. The relative amounts of each group were determined and related to similar measurements found in the literature (see Table 1 and 2). The ability to identify and quantify polar components in fuel may be useful in developing relationships between fuel composition and properties such as thermal stability.

MDGC-TOFMS is an elegant way to identify and measure both individual compounds and compound classes in the polar fraction of jet fuel. These complex fractions are extremely difficult to measure by conventional GC-MS, except for the most abundant components. The measurements obtained did not agree quantitatively to existing HPLC compound class measurements. However, the two techniques did generally agree in a qualitative sense. The MDGC-TOFMS technique was shown to be a superior qualitative analysis technique compared to traditional GC-MS and HPLC. MDGC-TOFMS is also superior in trace analysis of complex mixtures because peak identifications can be made in an automated way with more confidence. Work is continuing to examine the complex results obtained; chemometrics and other statistical methods may be appropriate to apply to these measurements. In addition, improvement of the separations by changing columns, column lengths, phases, and other chromatographic

parameters is also possible. Distinguishing improvements achieved because of multidimensional separations versus improvements made due to TOFMS deconvolution needs to be performed to direct further experiments in this area.

Table 1. Classification of compounds using MDGC-TOFMS analysis compared to total HPLC polars analysis [2].

fuel	phenols (mg/L)	pyridine (mg/L)	carbazole (mg/L)	indole (mg/L)	amine (mg/L)	quinolines (mg/L)	sum of groups (mg/L)	HPLC polars (mg/L)
3084	92.8	4.4	0.1	2.7	6.7	0.8	106.6	
2985	736.4	540.4	0.2	57.1	65.4	87.6	1399.4	2400
3166	119.9	13.0	0.2	2.2	1.9	1.1	137.3	514
3603	< 1.0	0.7	0.1	0.5	0.5	0.7	2.5	110
3633	361.8	3.2	0.1	1.5	3.8	4.2	370.4	470
3658	200.5	507.3	3.0	63.3	133.6	60.4	907.8	2200
3684	21.2	0.5	0.1	0.8	0.6	0.8	23.2	240
3686	432.8	16.8	0.2	10.4	8.4	4.9	468.6	710
3688	199.9	37.3	0.3	6.6	15.8	6.1	260.1	510
3773	73.8	1.4	0.1	0.9	19.4	0.7	95.6	190
3804	37.0	0.0	0.1	0.7	0.6	1.5	38.5	190
4108	122.4	10.3	0.1	1.7	4.0	1.0	138.5	
4110	69.1	0.3	0.1	0.4	0.6	0.1	70.5	
4195	111.3	42.5	0.1	2.6	2.3	1.2	158.7	

Table 2. Library matches to various compound classes in jet fuels [2].

R.T. (s)	name	match quality of a possible 1	R.T. (s)	name	match quality (out of a possible 1000)
Phenols			Fuel Example 3166		
1688.08	phenol, 2,6-dimethyl-	940	1613.32	benzenamine, 2,5-dimethyl-	740
1790.14	phenol, 3-ethyl-	704	1840.68	benzenamine, 2-ethyl-	933
1836.36	phenol, 2,3-dimethyl-	932	1862.82	benzenamine, N,N,3,5-tetramethyl-	774
1897.2	phenol, 3,5-dimethyl-	933	1900.18	benzenamine, 3,5-dimethyl-	931
1941.38	phenol, 2-ethyl-6-methyl-	916	1938.02	benzenamine, 2,3,4,5,6-pentamethyl-	725
1972.9	phenol, 3,4-dimethyl-	907	1991.56	benzenamine, 2,3-dimethyl-	939
1984.6	phenol, 2-(1-methylethyl)-	881	2112.08	benzenamine, 2-(1-methylethenyl)-	769
2001.78	phenol, 2,4,6-trimethyl-	909	2124.2	benzenamine, 4-propyl-	884
2016.2	phenol, 3,4,5-trimethyl-	920	2168.26	benzenamine, 2-ethyl-6-methyl-	889
2045.12	phenol, 2-propyl-	709	2347.56	benzenamine, 2,6-diethyl-	729
2075.94	phenol, 4-(1-methylethyl)-	856	2450.84	naphthalenamine, tetrahydro-N,N-dimethyl-	732
2092.18	phenol, 2,3,6-trimethyl-	927	2514.56	1-naphthalenamine, 5,6,7,8-tetrahydro-	735
2180.98	phenol, 4-propyl-	818	Indoles		
2195.62	phenol, 2-methyl-6-propyl	851	Fuel Example 3658		
2211.3	phenol, 2-ethyl-5-methyl-	748	2065.26	2-methylindoline	919
2223.94	phenol, 2-(1-methylpropyl)-	918	2259.2	1H-indole, 2,3-dihydro-1-methyl-	849
2225.28	phenol, 2,3,5,6-tetramethyl-	886	2308.34	indole	926
2239.26	phenol, 2-methyl-5-(1-methylethyl)-	732	2505.1	1H-indole, 5-methyl-	922
2255.64	phenol, 2-ethyl-4,5-dimethyl-	860	2561.94	1H-indole, 3-methyl-	846
2314.78	phenol, 3-methyl-6-propyl-	839	2565.48	1H-indole, 1-methyl-	871
2329.9	phenol, 4-(1-methylpropyl)-	793	2580.18	1H-indole, 2-methyl-	864
2435.62	phenol, 3,5-diethyl-	779	2747.42	2H-isindole, 4,7-dimethyl-	831
2463.74	phenol, 2-(1,1-dimethylethyl)-5-methyl-	772	2830.7	1H-indole, 1,3-dimethyl-	863
2481.82	2-allyl-4-methylphenol	796	2833.78	1H-indole, 2,3-dimethyl-	912
2555.56	2-ethyl-5-n-propylphenol	808	2910.42	1H-indole, 5,6,7-trimethyl-	869
2748.22	phenol, 2,5-bis(1-methylethyl)-	732	2984.28	1H-indole, 1,2,3-trimethyl-	871
2928.2	6- <i>tert</i> -butyl-2,4-dimethylphenol	719	2986.82	2,3,7-trimethylindole	702
2974.02	3,4-diethylphenol	703	2998.42	1H-indole, 2,3,5-trimethyl-	758
3079.92	phenol, 2-cyclohexyl-	756	3030.14	1H-indole, dihydro-trimethyl-2-methylene-	803
3156.8	4-methyl-2-phenylphenol	777	3162.48	2H-isindole, 4,5,6,7-tetramethyl-	803
Quinolines			3294.4	ethanone, 1-(1,3-dimethyl-1H-indol-2-yl)-	718
Fuel Example 2985			3311.16	1H-indole, 3-methyl-2-propanoyl-	716
2014.14	6-methyl-1,2,3,4-tetrahydroquinoline	734	3340.64	1,2,3,4,7-pentamethylindole	735
2171.76	quinoline	966	3388.5	1H-indole, 1-butyl-3-methyl-	807
2185.2	quinoline, 5,6,7,8-tetrahydro-	759	Carbazoles		
2269.8	quinoline, 5,6,7,8-tetrahydro-3-methyl-	749	Fuel Example 2985		
2303.38	quinoline, 1,2,3,4-tetrahydro-2-methyl-	799	3674.3	carbazole	924
2327.92	3-ethyl-5,6,7,8-tetrahydroquinoline	726	3686.9	carbazole, 1,2,3,4-tetrahydro-3-methyl-	741
2349.7	quinoline, 2-methyl-	895	3811.16	3-methylcarbazole	927
2363.28	quinoline, 8-methyl-	798	3917.12	carbazole, 1,6-dimethyl-	913
2487.54	quinoline, 5-methyl-	899	3945.12	3-ethylcarbazole	740
2503.32	quinoline, 3-methyl-	878	4035.64	carbazole, 3,6-dimethyl-	913
2529.76	isoquinoline, tetrahydro-3-methyl-	826	4064.36	carbazole, 2,5-dimethyl-	888
2559.96	dimethyl-1,2,3,4-tetrahydroisoquinoline	729	4123.34	carbazole, 1,3-dimethyl-	705
2664.24	2,8-dimethylquinoline	805	4125.88	carbazole, 2,4,6-trimethyl-	853
2803.32	quinoline, 5,8-dimethyl-	704	4154.66	carbazole, 2,3,5-trimethyl-	868
2856.98	dihydro-dimetquinolinylidene methane	733	Sulfur		
Pyridines			Fuel Example 2985		
Fuel Example 3658			1631.96	cyclothiazide	596
1252.16	pyridine, 2,4,6-trimethyl-	918	1968.46	1,2-dithiane	924
1311.72	pyridine, 2,3,6-trimethyl-	836	2376.54	benzothiazole	957
1358.48	pyridine, 2-ethyl-6-methyl-	718	3635.16	2-benzothiophene, dihydro-5,6-dimethyl-	743
1522.1	2-ethyl-3,5-dimethylpyridine	798	Amines		
1535.68	pyridine, 2-ethyl-4,6-dimethyl-	740	Fuel Example 2985		
1667.5	pyridine, 2-ethyl-6-isopropyl	812	1070.9	2-benzoyloxyethylamine	715
1935.08	pyridine, 3-ethyl-5-methyl-	726	1587.64	benzenamine, 3-methyl-	944
2134.16	pyridine, 2-methyl-4,6-dipropyl-	761			
2227.72	pyridine, 4-methyl-2-(2-methyl-1-C3-tetrahydropyridine, 4-[4-hydroxyphenyl]-	775			
2658.18	2,4-dimethyl-6-phenylpyridine	717			
3159.34		769			

^aGroups of compounds were taken from a particular fuel, as noted.

2) Endo fuels and propellants

This portfolio includes efforts supporting endothermic fuels for hypersonics and hydrocarbon rocket propellants. In general, all of these studies involve the mitigation of coking under various

flow and temperature regimes [3,4]. One of the key aspects of this work is linking the chemical compound classes in jet fuels (Table 3) with coking behavior. This class analysis is discussed further below in section 3).

Table 3. Hydrocarbon-type composition for representative and test fuels by ASTM D2425 [11]

	World survey average, vol %	Composite Jet A blend (POSF4658)	Jet A-1 (POSF 4877)	JP-7 (POSF 3327)	F-T Jet A-1 (POSF 4820)
Paraffins (normal + iso)	58.8	55.2	64.2	67.9	> 99%
monocycloparaffins	10.9	17.2	13.5	21.2	< 1
dicycloparaffins	9.3	7.8	3.8	9.4	< 1
tricycloparaffins	1.1	< 1	< 1	< 1	< 1
alkyl benzenes	13.4	12.7	12.6	0.7	<0.2
indans+tetralins	4.9	4.9	3.8	<0.2	<0.2
naphthalene	< 0.2	<0.2	0.3	<0.2	<0.2
substituted naphthalenes	1.6	1.3	< 0.2	<0.2	<0.2

* The technique also measures acenaphthenes, acenaphthylenes, tricyclic aromatics, and indenenes, but these were below detection limits in all cases.

As can be seen in Figures 1 and 2, Fischer-Tropsch fuels and conventional fuels can have very different reactivity (Figure 1) and deposition (Figure 2) behavior [4]. It was somewhat surprising that the deposition from the F-T was so much larger under pyrolysis conditions. Even when tests with equivalent conversions are compared (Figure 3), the F-T fuel is still a much higher depositor. The working hypothesis was that aromatic components in fuels were serving as growth sites for polycyclic aromatic hydrocarbons (PAH), the presumed precursors to deposit formation. Figure 4 shows that aromatic formation is indeed seen in typical jet fuels with a correlation to deposit formation, with PAH formation seen in Figure 5 in measurements by LSU (none of these PAH are detectable in the original fuel). However, the aromatic-free F-T fuels still form copious amounts of deposits (and PAH – Figure 6), so the initial steps of aromatic formation are obviously important and poorly understood. All of these coking tests were performed in-house – similar PAH formation is seen in tests performed with F-T at UTRC (Figure 7) and LSU (Figure 8) – so the data is not an artifact.




Figure 1. Comparison of the volumetric liquid-to-gas conversion as a function of the bulk outlet fuel temperature.




Figure 2. Comparison of the total surface carbon deposition for Jet A-1 and F-T fuels as a function of bulk outlet temperature.




Figure 3. Comparison of the surface deposition profile for Jet A-1 and F-T fuels with ~18% gaseous product conversion.




Figure 4. Comparison of aromatic content in stressed liquid and total surface deposition as a function of gas conversion for pyrolytic testing with Jet A-1.




Figure 5. Representative chromatogram of stressed Jet A-1 liquid product from supercritical pyrolysis.




Figure 6. Representative chromatogram of low conversion stressed S-8 liquid product from supercritical pyrolysis on ECAT.




Figure 7. Representative chromatogram of very high conversion stressed S-8 liquid product from supercritical pyrolysis at UTRC.




Figure 8. Representative chromatogram of stressed S-8 liquid product from supercritical pyrolysis at Louisiana State University.

3) Alternative fuels, fuel characterization

This portfolio supported studies of conventional jet fuel composition, as well as alternative fuels composition and properties, e.g. [11]. The in-house compositional analyses supported updates

of the JP-8 (MIL-DTL-83133F) and Jet A (ASTM D7566) specifications. The in-house effort also supported the development of MIL-HDBK-510, Alternative Fuel Certification. In support of the DARPA Biojet program, extensive compositional and property analyses were performed on biofuels, which led to the decision to certify hydrotreated renewable jet (HRJ). This AF effort will lead to flight demonstrations/tests in 2010, initially with the A-10 on March 25, 2010.

Typically the analysis focused on separating the thousands of hydrocarbons in typical jet fuels into classes. Occasionally, specific molecules are targeted. One interesting example was a request to quantify naphthalene ($C_{10}H_8$) levels in fuels due to potential toxicity issues. Linda Shafer of UDRI performed an extensive analysis of naphthalene levels in transportation fuels, to be described in detail in a forthcoming refereed paper. However, it is worth showing a few of the highlights. As shown in Figure 9, naphthalene and its derivatives fall within the typical molecular weight range of jet and diesel fuels. The total of naphthalene derivatives are typically characterized by ASTM D1840, and limited to 3 vol% in jet fuels. Often, this is mis-interpreted as 3% naphthalene ($C_{10}H_8$), which is incorrect. This research verified the levels of naphthalene and two derivatives in gasoline, diesel, and jet fuels samples world-wide (166 total samples). The results are shown in Table 4. For jet fuel, the 1+ vol% total naphthalenes (~10,000 mg/L) far exceeds the levels of the specific identified naphthalene isomers (~2000 mg/L typically). Also of interest was the distribution of naphthalene and its isomers (Figure 10) to verify if there were a few high-naphthalene fuels or if the distribution was more “normal”.




Figure 9. GC-MS scanning total ion chromatograms of fuels.

Table 4. Mean naphthalene content and standard deviation for fuel classes. It has been previously noted that the D6379 technique yields somewhat different values than D1840 [2].

Fuel	Naphthalene, $\mu\text{g/mL}$	1-methyl naphthalene, $\mu\text{g/mL}$	2-methyl naphthalene, $\mu\text{g/mL}$	D1840total naphthalenes, vol %	D6379 total naphthalenes, vol %
Jet	1526 $\pm$ 772	1525 $\pm$ 495	2365 $\pm$ 869	1.15 $\pm$ 0.38	1.33 $\pm$ 1.49
F-76	1587 $\pm$ 599	1688 $\pm$ 701	3008 $\pm$ 1505	4.05 $\pm$ 0.84	5.74 $\pm$ 1.21
auto diesel	357 $\pm$ 241	563 $\pm$ 467	1047 $\pm$ 875	2.61 $\pm$ 1.01	3.19 $\pm$ 1.48
gasoline	1484 $\pm$ 797	467 $\pm$ 319	1077 $\pm$ 733	0.42 $\pm$ 0.21	0.42 $\pm$ 0.23
Jet [2,3]	1583 $\pm$ 1037			1.23 $\pm$ 0.72	1.80 $\pm$ 1.00




Figure 10. Distribution of naphthalene content in jet fuels from this study.

Also of interest was the relationship between the typical “total naphthalenes” test (ASTM D1840) and other tests that can report similar data, such as ASTM D6379. As shown in Figure 11, there is a good correlation at lower “naphthalenes” content, which breaks down somewhat at the upper end of the range. There was also interest in determining if concentrations of specific naphthalene isomers could be inferred from the total “naphthalenes” data. As shown in Figure 12, there is a correlation – but it does have a lot of scatter. The scatter is reduced somewhat when the jet fuels are divided up by type (Figures 13 and 14), but the correlation is still not

predictive (note the scatter in the JP-8 points). So, for example, it is not possible to infer 1-methyl naphthalene content in JP-8 from the typical ASTM D1840 “naphthalenes” measurements – at least not to less than a factor of ~2 accuracy. It is interesting to note the correlation is much stronger for gasoline apparently, as shown in Figure 15 for naphthalene, Figure 16 for 1-methyl naphthalene, and Figure 17 for 2-methyl naphthalene.




Figure11. Correlation between total naphthalenes by ASTM D1840 and D6379.




Figure 12. Relationship between total naphthalene content and individual naphthalene components for jet fuel samples.




Figure 13. Naphthalene content as a function of jet fuel type.




Figure 16. 1-methyl naphthalene content for the four classes of ground fuels.




Figure 17. 2-methyl naphthalene content for the four classes of ground fuels.

4) Low temperature fuels

The in-house effort supported an ATD “JP-8+100LT Upgrade for the U-2 and Global Hawk”. This ATD successfully developed an JP-8 additive package that enabled JPTS behavior in JP-8 [5,6]. This work was partially funded by the U-2 program office.

5) Fuel system icing inhibitor (FSII) studies

The current FSII in JP-8 (diethylene glycol monomethyl ether) is causing operational problems at its current usage level (0.1-0.15 vol % in MIL-DTL-83133F). RZPF evaluated both alternative FSII's (such as triethylene glycol monomethyl ether) and lower levels of the current FSII to ensure that the effectiveness of the additive is maintained [7,8]. Flight tests involving both options are planned in 2010. Both biological growth mitigation testing (see 6) below) and component icing tests indicate that levels of the current FSII as low as 0.04 vol% are effective at mitigating biological growth and preventing icing – as well as preventing the material compatibility problems caused by FSII.

6) Biological growth in aviation fuels

This portfolio examined the current microbial growth issues in aircraft (largely mitigated by FSII) and studied alternative FSII's and alternative fuels [9,10]. An ongoing AF effort to assess the use of commercial Jet A fuel instead of JP-8 is driving further research on biological growth mitigation.

7) Emissions Reduction via Fuel Technologies

This portfolio focused on state-of-the-art emissions measurements, focusing on particulates [12]. An extensive amount of effort was spent improving particulate measurement technology as part of a multi-agency group. For example, note the multiple agencies present at an aerial view of a January 2009 test in California sponsored by NASA and AFRL (Figure 18).

8) Nanofuels, nanoenergetics

This portfolio developed nano-particle solutions for fuel additives and energetic materials. A key aspect of the work was ensuring controlled reactivity as a function of temperature and air exposure [13-15]. This research enables new avenues for field hydrogen generation [16].

5.0 CONCLUSIONS

This large in-house effort has been a very productive part of the Propulsion Directorate in-house research effort.




Figure 18. Aerial view of January 2009 aircraft emissions testing.

6.0 REFERENCES

1. Morris, R. W., et al, "JP-8+100 – Current Knowledge and Best Practices," AFRL-RZ-WP-TR-2008-2126, April 2008.
2. Striebich, R. C., et al, "Identification of Polar Species in Aviation Fuels using Multidimensional Gas Chromatography-Time of Flight Mass Spectrometry," *Energy Fuels* 2009, 23, 5474–5482.
3. Edwards, T., "Cracking and Deposition Behavior of Supercritical Hydrocarbon Aviation Fuels," *Combustion Science and Technology*, Vol. 178, pp. 307-334, 2006
4. Edwards, T., DeWitt, M, Shafer, L., Brooks, D., Huang, H., Bagley, S, Oña, J., and Wornat, M. J., "Fuel Composition Influence on Deposition in Endothermic Fuels, AIAA Paper 2006-7973, November 2006.
5. R. Assudani, J.S. Ervin and S. Zabarnick, "Computational Fluid Dynamic Simulations of Jet Fuel Flow Near the Freeze Point Temperature," *Prepr.-Am. Chem. Soc., Div Pet. Chem.*, Vol. 49, pp. 502-505, 2004.
6. L.M. Shafer, J.S. Ervin and S. Zabarnick, "Effects of Low-temperature Additives on Phase Compositions of Jet Fuel," *Prepr.-Am. Chem. Soc., Div Pet. Chem.*, Vol. 49, pp. 506-509, 2004.
7. M.J. DeWitt, S. Zabarnick, T. Williams, Z. West, L. Shafer, R. Striebich, S. Breitfield, C. Delaney, and D. Phelps, "Determination of Minimum Required FSII Dosage for Use on USAF Aircraft," Proceedings of the 10th International Conference on Stability, Handling and Use of Liquid Fuels, 2007.
8. S. Zabarnick, Z. West, M.J. DeWitt, L. Shafer, R. Striebich, C. Delaney, and D. Phelps, "Development of Alternative Fuel System Icing Inhibitor Additives that are Compatible with Aircraft Tank Topcoat Material," Proceedings of the 10th International Conference on Stability, Handling and Use of Liquid Fuels, 2007.
9. Vangness, M., et al, "Biocontamination Diversity in JP-8 and Jet-A," Proceedings of the 11th International Conference on Stability, Handling and Use of Liquid Fuels, 2009.
10. Balster, L. M., et al, "Effect of FSII on Microbial Contamination in Jet Fuel; DiEGME and TriEGME," Proceedings of the 11th International Conference on Stability, Handling and Use of Liquid Fuels, 2009.
11. Shafer, L, Striebich, R., Gomach, J., Edwards, T., "Chemical Class Composition of Commercial Jet Fuels and Other Specialty Kerosene Fuels," AIAA Paper 2006-7972, November 2006.
12. Corporan, E. et al, "Emissions Characteristics of Legacy Military Aircraft," ASME-GT-2009-59255, MISSIONS CHARACTERISTICS OF A LEGACY MILITARY AIRCRAFT, Proceedings of ASME Turbo Expo, June 2009.

13. Fernando, K. A. S.; Smith, M. J.; Harruff, B. A.; Lewis, W. K.; Guliants, E. A.; Bunker, C. E. "Sonochemical Assisted Thermal Decomposition of Alane N,N-Dimethylethylamine with Titanium (IV) Isopropoxide in the Presence of Oleic Acid to Yield Air-Stable and Size-Selective Aluminum Core-Shell Nanoparticles" *J. Phys. Chem. C* 2009, 113, 500-503.
14. Chung, S. W.; Guliants, E. A.; Bunker, C. E.; Hammerstroem, D. W.; Deng, Y.; Burgers, M. A.; Jelliss, P. A.; Buckner, S. W. "Capping and Passivation of Aluminum Nanoparticles Using Alkyl-Substituted Epoxides" *Langmuir* 2009, 25, 8883–8887.
15. Li, H.; Meziani, M. J.; Lu, F.; Bunker, C. E.; Guliants, E. A.; Sun, Y.-P. "Templated Synthesis of Aluminum Nanoparticles – A New Route to Stable Energetic Materials" *J. Phys. Chem. C* 2009, 113, 20539-20542.
16. Bunker, C. E.; Smith, M. J.; Fernando, K. A. S.; Harruff, B. A.; Lewis, W. K.; Gord, J. R.; Guliants, E. A.; Phelps, D. K. "Spontaneous Hydrogen Generation from Organic-Capped Al Nanoparticles and Water" *ACS Applied Materials & Interfaces* 2010, 2, 11-14.

LIST OF ACRONYMS, ABBREVIATIONS AND SYMBOLS

<u>Acronym</u>	<u>Description</u>
AF	Air Force
AFB	Air Force Base
AFRL	Air Force Research Laboratory
ASTM	American Society for Testing of Materials
ATD	Advanced Technology Demonstrator/Demonstration
DARPA	Defense Advanced Research Projects Agency
DESC	Defense Energy Support Center (part of Defense Logistics Agency)
ECAT	Estudios Combustibles y Altas Temperaturas (rig)
F-T	Fischer-Tropsch
FSII	Fuel System Icing Inhibitor
GC	Gas Chromatograph
GC-MS	Gas Chromatograph – Mass Spectrometer
HPLC	High Performance Liquid Chromatography
HRJ	Hydroprocessed Renewable Jet
JP-8	Jet Propellant 8
JPTS	Jet Propellant Thermally Stable
LSU	Louisianan State University
MDGC	Multi-Dimensional Gas Chromatograph
MIL-HDBK-510	Military Handbook 510
NAFRC	National Aerospace Fuels Research Complex
NASA	National Aerospace Research Complex
PAH	Polycyclic Aromatic Hydrocarbons
RZPF	AFRL Fuels Branch (organizational symbol, not an acronym)
SPE	Solid Phase Extraction
TOFMS	Time-Of-Flight Mass Spectrometer
UDRI	University of Dayton Research Institute
UTRC	United Technologies Research Center