

Report Documentation Page				Form Approved OMB No. 0704-0188	
Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.					
1. REPORT DATE 2006		2. REPORT TYPE		3. DATES COVERED 00-00-2006 to 00-00-2006	
4. TITLE AND SUBTITLE Seismo-Acoustics in Laterally Varying Media				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S)				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Naval Research Laboratory, 4555 Overlook Avenue SW, Washington, DC, 20375				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution unlimited					
13. SUPPLEMENTARY NOTES					
14. ABSTRACT					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT Same as Report (SAR)	18. NUMBER OF PAGES 3	19a. NAME OF RESPONSIBLE PERSON
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified			

Seismo-Acoustics in Laterally Varying Media

M.D. Collins,¹ D.C. Calvo,¹ H.J. Simpson,¹ R.J. Soukup,¹
J.M. Collis,² E.T. Küsel,² D.A. Outing,² and W.L.
Siegmann²

¹Acoustics Division

²Rensselaer Polytechnic Institute/Dept. of Mathematical
Sciences

Introduction: Many wave propagation problems in the geosciences involve a nearly stratified waveguide. When lateral variations in the medium (ocean, solid Earth, or atmosphere) are sufficiently gradual, outgoing energy dominates backscattered energy, and solutions can be obtained using an approximate wave equation that only accounts for outgoing waves.¹ This approach, which is known as the parabolic equation method, often improves efficiency by several orders of magnitude with no significant loss in accuracy. For example, outgoing solutions can be obtained in minutes for global-scale ocean acoustics problems² that would be out of the question to solve in terms of the full-wave equation.

Improved Techniques: The extension of the parabolic equation method to problems involving solid layers has been an area of great interest for nearly 30 years. Solid layers are governed by the elastic-wave equation and support two types of body waves and interface waves. This vector equation is more complicated than the scalar equation that governs acoustic waves, and the solutions are more prone to instabilities. Due to these difficulties, it was nearly 20 years

between the introduction of the parabolic equation method into ocean acoustics and its first successful application to problems involving elastic layers.³

For the past decade, there has been a focus on improving the accuracy of parabolic equation solutions when there are lateral variations in solid layers. One of the key developments in this area was to rederive the elastic parabolic equation in terms of a new set of dependent variables.⁴ In order to facilitate the derivation of the parabolic-wave equation from the full-wave equation, it is necessary to choose the dependent variables so that they have certain symmetry properties. Otherwise, it is impossible to derive a parabolic-wave equation. The first derivations were based on an unconventional choice of variables. The fact that one of the variables is not continuous makes it difficult to handle interfaces between solid layers. The new formulation is also based on an unconventional choice of variables, but both of the variables are continuous, and this has made it possible not only to handle arbitrary layering, but also to handle lateral variations more accurately.

We have considered two approaches for handling lateral variations, and both of them have produced promising results. One of the approaches is based on rotating coordinates so that one of the coordinates is aligned with the interface. This approach has proven to be effective for handling a sloping ocean bottom, which is an important and difficult case. Appearing in Fig. 6 is a problem involving two types of interface waves that was solved with this approach. In this example, a Scholte wave propagates along the ocean bottom and onto the beach, where it becomes a Rayleigh wave. We are also developing approaches based




FIGURE 6
Propagation of a Scholte wave along
the ocean bottom. This interface wave
becomes a Rayleigh wave beyond the
beach.

on the original coordinate system that can handle a larger class of lateral variations. These approaches are based on making corrections to the field as the properties of the waveguide vary with range. Appearing in Fig. 7 is a seismic problem involving complex layering that was solved with this approach.

Comparison with Data: When possible, we compare parabolic equation solutions with solutions obtained by other means. Since such solutions are very limited, we have also made comparisons with data from tank experiments. Appearing in Fig. 8 is a comparison of the parabolic equation solution with data

taken in a carefully controlled experiment involving a slab of poly vinyl chloride (PVC) that was suspended in a tank of water to model a sloping, elastic ocean bottom (Fig. 9).

[Sponsored by ONR]

References

- ¹ F.B. Jensen, W.A. Kuperman, M.B. Porter, and H. Schmidt, *Computational Ocean Acoustics* (American Institute of Physics, New York, 1994), pp. 343-412.
- ² B.E. McDonald, M.D. Collins, W.A. Kuperman, and K.D. Heaney, "Comparison of Data and Model Predictions for Heard Island Acoustic Transmissions," *J. Acoust. Soc. Am.* **96**, 2357-2370 (1994).




FIGURE 7
Elastic wave propagation in a medium with complex layering. This plot only shows the compressional wave energy.




FIGURE 8
Comparison between model results (dashed curve) and tank data (solid curve) along a line at constant depth. The frequency is 225 kHz.




FIGURE 9
Geometry of the tank experiment.

³ M. D. Collins, "Higher-order parabolic approximations for accurate and stable elastic parabolic equations with application to interface wave propagation," *J. Acoust. Soc. Am.* **89**, 1050-1057 (1991).

⁴ W. Jerzak, W.L. Siegmann, and M.D. Collins, "Modeling Rayleigh and Stoneley Waves and Other Interface and Boundary Effects with the Parabolic Equation," *J. Acoust. Soc. Am.* **117**, 3497-3503 (2005). ★