

REPORT DOCUMENTATION PAGE				Form Approved OMB No. 0704-0188	
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing this collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.					
1. REPORT DATE (DD-MM-YYYY) 25-06-2010		2. REPORT TYPE Journal Article		3. DATES COVERED (From - To)	
4. TITLE AND SUBTITLE One-Dimensional Compressible Flow in Variable Area Duct with Heat Addition (Preprint)				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S) Leonid Pekker (ERC, Inc.)				5d. PROJECT NUMBER	
				5f. WORK UNIT NUMBER 50260542	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Air Force Research Laboratory (AFMC) AFRL/RZSA 10 E. Saturn Blvd. Edwards AFB CA 93524-7680				8. PERFORMING ORGANIZATION REPORT NUMBER AFRL-RZ-ED-JA-2010-303	
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) Air Force Research Laboratory (AFMC) AFRL/RZS 5 Pollux Drive Edwards AFB CA 93524-7048				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S NUMBER(S) AFRL-RZ-ED-JA-2010-303	
12. DISTRIBUTION / AVAILABILITY STATEMENT Approved for public release; distribution unlimited (PA #10318).					
13. SUPPLEMENTARY NOTES For publication in the Journal of Thermophysics and Heat Transfer.					
14. ABSTRACT One-dimensional compressible flows of calorically perfect gases in which only a single driving potential is present are called simple flows ^{1, 2, 3} . Because Mach number and property relations for simple flows can be expressed in closed form, such flows are usually treated individually. Most introductory compressible flow courses and most compressible flow textbooks discuss three types of simple flows: isentropic flow in a variable area duct, the heat addition (or rejection) flow in constant area duct (Rayleigh flow), and adiabatic flow in a constant area duct with gas-wall-surface friction (Fanno flow). A more complicated case of a simple mass addition flow is described in literature ⁴ . In the present paper we consider a case of two driving potentials: heat addition and variable area duct. Therefore, the obtained governing ordinary differential equations cannot be solved analytically, as in the case of simple flows, but they can be easily solved numerically. This research has been inspired by recent papers ^{5, 6} , where the authors discussed the thermal augmentation of solid rocket motors by heating the alumina particles in the exhaust of the motor by a microwave beam generated by a ground-based microwave generation facility. Thus, the equations obtained in the paper can be used, for example, as benchmarks for numerical investigation of gas flows in a nozzle heated by an external heating source, such as in ^{5, 6} .					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT SAR	18. NUMBER OF PAGES 5	19a. NAME OF RESPONSIBLE PERSON Mr. Marcus Young
a. REPORT Unclassified	b. ABSTRACT Unclassified	c. THIS PAGE Unclassified			19b. TELEPHONE NUMBER (include area code) N/A

One-Dimensional Compressible Flow in Variable Area Duct with Heat Addition (Preprint)

L. Pekker¹

ERC Inc., 10 East Saturn Blvd., Edwards AFB, CA 93524

Nomenclature

A	= area of the duct
c_p	= specific heat of perfect gas per unit of mass at constant pressure
k	= Boltzmann constant
M	= Mach number
m	= mass of gas molecule
$\dot{m}$	= mass flux through the duct
n	= number density
P	= pressure
T	= temperature
u	= fluid velocity
x	= axis along the duct
Γ	= enthalpy per unit of mass at the duct inlet
γ	= gaseous constant
ε	= heat input per unit of mass
ρ	= mass density

I. Introduction

One-dimensional compressible flows of calorically perfect gases in which only a single driving potential is present are called simple flows^{1, 2, 3}. Because Mach number and property relations for simple flows can be expressed in closed form, such flows are usually treated individually. Most introductory compressible flow courses and most compressible flow textbooks discuss three types of simple flows: isentropic flow in a variable area duct, the heat addition (or rejection) flow in constant area duct (Rayleigh flow), and adiabatic flow in a constant area duct with gas-wall-surface friction (Fanno flow). A more complicated case of a simple mass addition flow is described in literature⁴. In the present paper we consider a case of two driving potentials: heat addition and variable area duct. Therefore, the obtained governing ordinary differential equations cannot be solved analytically, as in the case of simple flows, but they can be easily solved numerically. This research has been inspired by recent papers^{5, 6}, where the authors discussed the thrust augmentation of solid rocket motors by heating the alumina particles in the exhaust of the motor by a microwave beam generated by a ground-based microwave generation facility. Thus, the equations

¹ Research Scientist, leonid.pekker.ctr@edwards.af.mil

obtained in the paper can be used, for example, as benchmarks for numerical investigation of gas flows in a nozzle heated by an external heating source, such as in^{5,6}.

II. Theory

A set of equations describing a one-dimensional gas flow in a nozzle heated by an external heating source, Fig. 1, can be written as

$$\dot{m} = \rho \cdot u \cdot A \quad (1)$$

$$\rho \cdot u \cdot \frac{du}{dx} = -\frac{dP}{dx} \quad (2)$$

$$\frac{d\varepsilon}{dx} = \frac{d}{dx} \left(c_P \cdot T + \frac{u^2}{2} \right) \quad (3)$$

where the first, second, and the equations correspond to the laws of conservation of mass, momentum, and energy.




Fig. 1. Schematic of gas flow through the nozzle

Introducing the gas enthalpy per unit mass at the inlet of the duct, Fig. 1, we obtain from Eq. (3) that

$$\Gamma = c_P \cdot T + \frac{u^2}{2} - \varepsilon \quad (4)$$

Substituting

$$n = \frac{\dot{m}}{m \cdot u \cdot A} \quad \text{and} \quad T = \frac{1}{c_P} \cdot \left(\Gamma - \frac{u^2}{2} + \varepsilon \right) \quad (5)$$

where T is obtained from Eq. (4), into the equation for pressure $P = n \cdot k \cdot T$, we obtain

$$P = \frac{\dot{m} \cdot k}{m \cdot c_P \cdot u \cdot A} \cdot \left(\Gamma - \frac{u^2}{2} + \varepsilon \right) = \frac{\dot{m} \cdot (\gamma - 1)}{\gamma \cdot u \cdot A} \cdot \left(\Gamma - \frac{u^2}{2} + \varepsilon \right) \quad (6)$$

Here we have used γ for a perfect gas, i.e., $(\gamma - 1)/\gamma = k/m \cdot c_P$. Substituting Eq. (6) for P and $\rho \cdot u = \dot{m}/A$, Eq.

(1), into Eq. (2) after simple algebra we obtain a governing equation for flow velocity u vs. x

$$\frac{d}{dx} \left[\left(\frac{\Gamma}{u} + u \cdot \frac{(\gamma + 1)}{2 \cdot (\gamma - 1)} + \frac{\varepsilon}{u} \right) \right] = \left(\frac{\Gamma}{u} - \frac{u}{2} + \frac{\varepsilon}{u} \right) \cdot \frac{d(\ln A)}{dx} \quad (7)$$

where $\gamma = 5/3$, Γ is an input constant and ε and A are input functions on x .

Let us obtain a governing equation for Mach number. Substituting T from Eq. (5) into the expression for Mach number

$$M = \frac{u}{\sqrt{(\gamma - 1) \cdot T \cdot c_P}} \quad (8)$$

we obtain

$$u = M \cdot \left(\frac{(\Gamma + \varepsilon) \cdot (\gamma - 1)}{1 + 0.5 \cdot \frac{\gamma - 1}{2} \cdot M^2} \right)^{1/2} \quad (9)$$

Substituting Eq. (9) into Eq. (7) after some algebra we obtain a governing equation for Mach number:

$$\left[\frac{1 - M^2}{M \cdot \left(1 + \frac{\gamma - 1}{2} \cdot M^2 \right)} \right] \cdot \frac{dM}{dx} = \frac{(1 + \gamma \cdot M^2)}{2} \cdot \frac{d(\ln[\varepsilon + \Gamma])}{dx} - \frac{d(\ln A)}{dx} \quad (10)$$

Unlike in the case of a simple flow, Eq. (10) generally cannot be solved in radicals; however, it can be solved numerically via standard methods. It can be shown that the governing equations for isentropic and Rayleigh flows (the cases of $\varepsilon = 0$ and $A = \text{const}$, respectively) can be derived from Eq. (10).

Acknowledgments

The author would like to express his appreciation to Dr. A. Ketsdever for initiation this research and helpful discussions.

References

- ¹Shapiro, A. H., *The Dynamics and Thermodynamics of Compressible Fluid Flow*, Ronald Press, New York, 1953.
- ²Zucrow, M. J., and Hoffman, J. D., *Gas Dynamics*, Willey, New York, 1976.
- ³Saad, M. A., *Compressible Fluid Flow*, Prentice-Hall, Englewood Cliffs, New Jersey, 1987.
- ⁴Hodge, B. K. and Young, F., “Mass Addition Process in One-Dimensional Compressible Flow,” *31st Aerospace Sciences Meeting & Exhibit*, Reno, NV, 11-14 January, 1993, AIAA 93-0487.
- ⁵Cornella, B., Hammerland, S., Ketsdever, A. D., and Song, H., “Power Generation for a Beamed Microwave Propulsion Concept,” *45st Joint Propulsion Conference & Exhibit*, Denver, CO, 2-5 August, 2009, AIAA 2009-4872.
- ⁶Gimelshein, N. E., Gimelshein, S. F., P. and Ketsdever, A., “Thrust Augmentation in Solid Rocket Motor Using Beamed Microwave Energy,” *45st Joint Propulsion Conference & Exhibit*, Denver, CO, 2-5 August, 2009, AIAA 2009-4962.