

Power-Aware Cognitive Packet Networks

Erol Gelenbe
Dennis Gabor Chair

Ricardo Lent
Research Fellow

Department of Electrical and Electronic Engineering
Imperial College London, UK

IST 054 - Rome -April 2005

Report Documentation Page				Form Approved OMB No. 0704-0188	
Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.					
1. REPORT DATE DEC 2006		2. REPORT TYPE N/A		3. DATES COVERED -	
4. TITLE AND SUBTITLE Power-Aware Cognitive Packet Networks				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S)				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Department of Electrical and Electronic Engineering Imperial College London Exhibition Road London SW7 2AZ UK				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release, distribution unlimited					
13. SUPPLEMENTARY NOTES See also ADM202750. RTO-MP-IST-054, Military Communications (Les communications militaires), The original document contains color images.					
14. ABSTRACT					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT UU	18. NUMBER OF PAGES 32	19a. NAME OF RESPONSIBLE PERSON
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified			



Motivation

- ❑ Mobile nodes have limited energy
- ❑ In ad hoc routing, nodes rely on other nodes to deliver their messages
- ❑ Routing algorithms unaware of energy in nodes may shorten network lifetime
- ❑ Objective: Identify paths which intelligently distribute energy consumption



Cognitive Packet Networks

- ❑ Distributed algorithms that implements self-adaptation that searches QoS on demand
- ❑ Data flows are characterized by a QoS goal (one or more metrics)
- ❑ Packets can acquire network status (experience) as they move and this information can be exploited in future decision makings
- ❑ Different data flows can collaborate by sharing information



Information Collection and Storage

- ❑ Smart packets search for routes, dumb packets transport payload, both of which accumulate experience
- ❑ Acknowledgements distribute experience
- ❑ Information is stored in nodes along paths (mailboxes and RNNs)

Header	Cognitive Map	Payload
--------	---------------	---------



Routing Decisions


- At each hop, smart packets use a random neural network (RNN) with as many neurons as possible decisions (neighbors)
- The most excited neuron in steady-state gives the best decision for the packet



CPN in Ad Hoc Networks

- ❑ Neighboring information is acquired by listening to channel transmissions
- ❑ Each packet reception updates a time-to-live value for the sending neighbor
- ❑ Expired entries are removed
- ❑ Smart packets may use broadcasts instead of unicast decisions (RNN/RL):
 - When not sufficient information is available at a node to construct a valid RNN (for example, when the node just entered the network)
 - With a small probability to avoid trapping the algorithm in local minima

Random Neural Networks (RNN)



$$\lambda^+(i) = \sum_j q_j w_{ji}^+ + \Lambda_i$$

$$\lambda^-(i) = \sum_j q_j w_{ji}^- + \lambda_i$$

$$q_i = \frac{\lambda^+(i)}{r(i) + \lambda^-(i)} \quad ; 1 \leq i \leq N$$



Reinforcement Learning in RNN

- Measured performance (with respect to a particular routing goal) is used to adjust the weights of the RNN
- Example of routing goal:
 - $G = 1/D$; $D = \text{delay}$

Power-Aware Routing Goal

$$G_{id} = P_p(n_i, n_d)D(n_i, n_d) + [1 - P_p(n_i, n_d)](T_o + G_i)$$

$$P_p(n_i, n_d) = \prod_{j=i}^{d-1} P_n(n_{i+1})P_l(n_i, n_{i+1})$$

$$P_n(n_i) = \frac{B_i}{B_m}$$

G_{id} = goal at node i to destination d

P_p = path availability, T_o = time penalty, B_i = battery level

P_n, P_l = Probability of being available of nodes and links



Simulation

- ❑ NS-2
- ❑ 50 nodes divided into 2 populations:
 - 10 nodes (full battery charge = 2 hours operation)
 - 40 nodes (1/8 of full battery charge = 15 min)
- ❑ Area: 1500 x 500 m
- ❑ Assume random starting locations and random waypoint mobility at 2 m/s with no pause
- ❑ Traffic: 5 concurrent connections between nodes of the first population
- ❑ Smart packets sent at a ratio of 0.01



Number of nodes with no residual energy over time

QuickTime™ and a
TIFF (LZW) decompressor
are needed to see this picture.



Packets Delivered to Destination

QuickTime™ and a
TIFF (LZW) decompressor
are needed to see this picture.



Total DP and SP Transmitted

QuickTime™ and a
TIFF (LZW) decompressor
are needed to see this picture.



Total DP and SP Received

QuickTime™ and a
TIFF (LZW) decompressor
are needed to see this picture.



Summary

- ❑ CPN offers “best effort” QoS routing with smart packets both for wireline and wireless networks
- ❑ A focused information collection mechanism allows smart packets make decisions towards the desired QoS target
- ❑ Decisions can be tailored to enable energy-awareness, which in combination with delay gives balance between fast routes and an intelligent distribution of energy consumption in the network

Power-Aware Cognitive Packet Networks

Erol Gelenbe
Dennis Gabor Chair

Ricardo Lent
Research Fellow

Department of Electrical and Electronic Engineering
Imperial College London, UK

IST 054 - Rome -April 2005



Motivation

- ❑ Mobile nodes have limited energy
- ❑ In ad hoc routing, nodes rely on other nodes to deliver their messages
- ❑ Routing algorithms unaware of energy in nodes may shorten network lifetime
- ❑ Objective: Identify paths which intelligently distribute energy consumption



Cognitive Packet Networks

- ❑ Distributed algorithms that implements self-adaptation that searches QoS on demand
- ❑ Data flows are characterized by a QoS goal (one or more metrics)
- ❑ Packets can acquire network status (experience) as they move and this information can be exploited in future decision makings
- ❑ Different data flows can collaborate by sharing information



Information Collection and Storage

- ❑ Smart packets search for routes, dumb packets transport payload, both of which accumulate experience
- ❑ Acknowledgements distribute experience
- ❑ Information is stored in nodes along paths (mailboxes and RNNs)

Header	Cognitive Map	Payload
--------	------------------	---------



Routing Decisions


- At each hop, smart packets use a random neural network (RNN) with as many neurons as possible decisions (neighbors)
- The most excited neuron in steady-state gives the best decision for the packet



CPN in Ad Hoc Networks

- ❑ Neighboring information is acquired by listening to channel transmissions
- ❑ Each packet reception updates a time-to-live value for the sending neighbor
- ❑ Expired entries are removed
- ❑ Smart packets may use broadcasts instead of unicast decisions (RNN/RL):
 - When not sufficient information is available at a node to construct a valid RNN (for example, when the node just entered the network)
 - With a small probability to avoid trapping the algorithm in local minima

Random Neural Networks (RNN)



$$\lambda^+(i) = \sum_j q_j w_{ji}^+ + \Lambda_i$$

$$\lambda^-(i) = \sum_j q_j w_{ji}^- + \lambda_i$$

$$q_i = \frac{\lambda^+(i)}{r(i) + \lambda^-(i)} \quad ; 1 \leq i \leq N$$



Reinforcement Learning in RNN

- Measured performance (with respect to a particular routing goal) is used to adjust the weights of the RNN
- Example of routing goal:
 - $G = 1/D$; $D = \text{delay}$

Power-Aware Routing Goal

$$G_{id} = P_p(n_i, n_d)D(n_i, n_d) + [1 - P_p(n_i, n_d)](T_o + G_i)$$

$$P_p(n_i, n_d) = \prod_{j=i}^{d-1} P_n(n_{i+1})P_l(n_i, n_{i+1})$$

$$P_n(n_i) = \frac{B_i}{B_m}$$

G_{id} = goal at node i to destination d

P_p = path availability, T_o = time penalty, B_i = battery level

P_n, P_l = Probability of being available of nodes and links



Simulation

- ❑ NS-2
- ❑ 50 nodes divided into 2 populations:
 - 10 nodes (full battery charge = 2 hours operation)
 - 40 nodes (1/8 of full battery charge = 15 min)
- ❑ Area: 1500 x 500 m
- ❑ Assume random starting locations and random waypoint mobility at 2 m/s with no pause
- ❑ Traffic: 5 concurrent connections between nodes of the first population
- ❑ Smart packets sent at a ratio of 0.01



Number of nodes with no residual energy over time

QuickTime™ and a
TIFF (LZW) decompressor
are needed to see this picture.



Packets Delivered to Destination

QuickTime™ and a
TIFF (LZW) decompressor
are needed to see this picture.



Total DP and SP Transmitted

QuickTime™ and a
TIFF (LZW) decompressor
are needed to see this picture.



Total DP and SP Received

QuickTime™ and a
TIFF (LZW) decompressor
are needed to see this picture.



Summary

- ❑ CPN offers “best effort” QoS routing with smart packets both for wireline and wireless networks
- ❑ A focused information collection mechanism allows smart packets make decisions towards the desired QoS target
- ❑ Decisions can be tailored to enable energy-awareness, which in combination with delay gives balance between fast routes and an intelligent distribution of energy consumption in the network

Power-Aware Cognitive Packet Networks

Erol Gelenbe and Ricardo Lent

Department of Electrical and Electronic Engineering
Imperial College London
Exhibition Road
London SW7 2AZ
UK

This paper was received as a PowerPoint presentation without supporting text.

[Click here to view PowerPoint presentation; Press Esc to exit](#)

Power-Aware Cognitive Packet Networks

